# 8-1/2” CR616M-XR(BR)

### *Drill Bit Specifications:*

| | |
|---|---|
| Cutter Size (Primary, Sec) | 5/8”, 1/2” |
| Cutter Count (Total, Gage, Back Ream) | 63, 12, 6 |
| Blade Count | 6 |
| Gage Length (Inches) | 4.00 |
| Nozzle Count (Primary, Sec.) | 6 |
| Nozzle Series (Primary, Sec.) | 60 |
| JSA (Sq. Inches) | 13.08 |
| Max. TFA (Sq. Inches) | 2.23 |

### *Operating Parameters:*

| | |
|---|---|
| Max. Weight on Bit (1,000 Lbs.) | 60 |
| Make-up Torque (ft/lbs) | 16,488 |

### *Nominal Dimensions:*

| | |
|---|---|
| Overall Length (Inches) | 16.27 |
| Make Up Length (Inches) | 12.15 |
| Bit Breaker | SKB-21010 |
| Connection | Ø4-1/2" API Reg. |
| Approx. Weight (Lbs.) | 160 |

### *Tailor-Made Features:*

- Premium grade cutters maximize ROP and Life
- Nozzle configuration and large open face volume optimize blade cleaning and cuttings removal

### *616M-XR(BR) Nomenclature Explained:*

- 6 = Number of Blades
- 16 = Primary Cutter Size (16mm)
- M = Matrix Bit Body
- XR = Double Row of Cutters
- BR = Back Reaming Cutters

3446 S. Main
Pearland, TX 77581
1-866-470-4202