# 12-1/4” CR616-XB12(K)(BR)

### *Drill Bit Specifications:*

| | |
|---|---|
| Cutter Size (Primary, Sec) | 5/8”,1/2” |
| Cutter Count (Total, Gage, Back Ream) | 104, 9, 9 |
| Blade Count | 6 |
| Gage Length (Inches) | 5.00 |
| Nozzle Count (Primary, Sec.) | 9, 3 |
| Nozzle Series (Primary, Sec.) | 60, 45 |
| JSA (Sq. Inches) | 25.08 |
| Max. TFA (Sq. Inches) | 3.93 |

### *Operating Parameters:*

| | |
|---|---|
| Max. Weight on Bit (1,000 Lbs.) | 60 |
| Make-up Torque (ft/lbs) | 40,563 |

### *Nominal Dimensions:*

| | |
|---|---|
| Overall Length (Inches) | *21.48 |
| Make Up Length (Inches) | *16.61 |
| Bit Breaker | SKB-21011 |
| Connection | Ø6-5/8" API Reg. |
| Approx. Weight (Lbs.) | *315 |

*Long tool joint available upon request (adds 6” to fishing neck, makeup and overall length, and 64 lbs. to approximate weight).

### *Taylor-Made Features:*

- Premium grade cutters maximize ROP and Life
- Selectively positioned bullets for smooth drilling
- Nozzle configuration and large open face volume optimize blade cleaning and cuttings removal
- Double blade design extends bit life for increased footage

### *616-XB12(K)(BR) Nomenclature Explained:*

- 6 = Number of Blades
- 16 = Primary Cutter Size (16mm)
- XB = Backup Cutters & Double Blade
- 12 = Number of Nozzles
- K = Bullets
- BR = Back Reaming Cutters

3446 S. Main
Pearland, TX 77581
1-866-470-4202