9-7/8” CR616-XB9(K)(BR)

Drill Bit Specifications:

Cutter Size (Primary, Sec)	5/8”,1/2”
Cutter Count (Total, Gage, Back Ream)	87, 9, 9
Blade Count	6
Gage Length (Inches)	4.00
Nozzle Count (Primary, Sec.)	6, 3
Nozzle Series (Primary, Sec.)	60, 45
JSA (Sq. Inches)	15.437
Max. TFA (Sq. Inches)	2.82

Operating Parameters:

Max. Weight on Bit (1,000 Lbs.)	60
Make-up Torque (ft/lbs)	40,563

Nominal Dimensions:

Overall Length (Inches)	*18.36
Make Up Length (Inches)	*13.48
Bit Breaker	SKB-21011
Connection	Ø6-5/8" API Reg.
Approx. Weight (Lbs.)	*190

*Long tool joint available upon request (adds 6” to fishing neck, makeup and overall length, and 64 lbs. to approximate weight).

Taylor-Made Features:

- Premium grade cutters maximize ROP and Life
- Selectively positioned bullets for smooth drilling
- Nozzle configuration and large open face volume optimize blade cleaning and cuttings removal
- Double blade design extends bit life for increased footage

616-XB9(K)(BR) Nomenclature Explained:

- 6 = Number of Blades
- 16 = Primary Cutter Size (16mm)
- XB = Backup Cutters & Double Blade
- 9 = Number of Nozzles
- K = Bullets
- BR = Back Reaming Cutters

3446 S. Main
Pearland, TX 77581
1-866-470-4202