7-7/8” CR416-XB8

Drill Bit Specifications:

Cutter Size (Primary, Sec)	5/8”
Cutter Count (Total, Gage)	43, 8
Blade Count	4
Gage Length (Inches)	4.00
Nozzle Count (Primary, Sec.)	4, 4
Nozzle Series (Primary, Sec.)	60, 45
JSA (Sq. Inches)	9.29
Max. TFA (Sq. Inches)	2.27

Operating Parameters:

Max. Weight on Bit (1,000 Lbs.)	60
Make-up Torque (ft/lbs)	17,399

Nominal Dimensions:

Overall Length (Inches)	14.85
Make Up Length (Inches)	10.72
Bit Breaker	SKB-21010
Connection	Ø4-1/2" API Reg.
Approx. Weight (Lbs.)	100

Standard Features:

- Premium grade cutters maximize ROP and Life
- Nozzle configuration and large open face volume optimize blade cleaning and cuttings removal
- Double blade design extends bit life for increased footage

416-XB8 Nomenclature Explained:

- 4 = Number of blades
- 16 = Primary Cutter Size (16mm)
- XB = Backup Cutters & Double Blade
- 8 = Number of Nozzles

3446 S. Main
Pearland, TX 77581
1-866-470-4202