12-1/4” CR519-SR7

Drill Bit Specifications:

Cutter Size (Primary, Sec)	3/4”
Cutter Count (Total, Gage, Back Ream)	37, 6
Blade Count	5
Gage Length (Inches)	3.00
Nozzle Count (Primary, Sec.)	7
Nozzle Series (Primary, Sec.)	60
JSA (Sq. Inches)	36.84
Max. TFA (Sq. Inches)	2.60

Operating Parameters:

Max. Hydraulic Flow Rate (GPM)	810
Make-up Torque (ft/lbs)	40,563

Nominal Dimensions:

Overall Length (Inches)	*17.90
Make Up Length (Inches)	*13.03
Bit Breaker	SKB-21011
Connection	Ø6-5/8" API Reg.
Approx. Weight (Lbs.)	*215

*Long tool joint available upon request (adds 6” to fishing neck, makeup and overall length, and 64 lbs. to approximate weight).

Taylor-Made Features:

- Premium grade cutters maximize ROP and Life
- Nozzle configuration and large open face volume optimize blade cleaning and cuttings removal

519-SR7 Nomenclature Explained:

- 5 = Number of Blades
- 19 = Primary Cutter Size (19mm)
- SR = Single Row Cutters
- 7 = Number of Nozzles

3446 S. Main
Pearland, TX 77581
1-866-470-4202