10-5/8” CR616-SR(K)

Drill Bit Specifications:

Cutter Size (Primary, Sec)	5/8”
Cutter Count (Total, Gage, Back Ream)	49, 6
Blade Count	6
Gage Length (Inches)	5.00
Nozzle Count (Primary, Sec.)	6
Nozzle Series (Primary, Sec.)	60
JSA (Sq. Inches)	27.57
Max. TFA (Sq. Inches)	2.23

Operating Parameters:

Max. Weight on Bit (1,000 Lbs.)	60
Make-up Torque (ft/lbs)	40,563

Nominal Dimensions:

Overall Length (Inches)	*19.23
Make Up Length (Inches)	*14.36
Bit Breaker	SKB-21011
Connection	Ø6-5/8" API Reg.
Approx. Weight (Lbs.)	*200

*Long tool joint available upon request (adds 6” to fishing neck, makeup and overall length, and 64 lbs. to approximate weight).

Taylor-Made Features:

- Premium grade cutters maximize ROP and Life
- Nozzle configuration and large open face volume optimize blade cleaning and cuttings removal

616-SR(K) Nomenclature Explained:

- 6 = Number of Blades
- 16 = Primary Cutter Size (16mm)
- SR = Single Row of Cutters
- K = Bullets

3446 S. Main
Pearland, TX 77581
1-866-470-4202