RUN WITH THE BULL™

TAUREX DRILL BITS
POWERED BY: BITVISION™

10 5/8 in. TSt616 D9 EU

270 mm
PN: T11543

Design Specifications

IADC	S423							
Blades	6							
Cutters	80							
Cutter Size	C	16	F	16	G	13	mm	
Nozzles	S44	0	S65	0	S55	9	Port	0
Junk Slot Area	26.9 (in²)				173.55 sq cm			
Face Volume	136.4 (in³)				2235.2 cu cm			

Operating Guidelines*

Makeup Torque	37,500 - 42,000 ft-lbs
	50,843 - 56,944 Nm

*Guidelines only. See a Taurex rep for application specifics.

Nominal Dimensions

Makeup Length	17.1 in	434.3 mm
Overall Length	22.1 in	561.3 mm
Gage Length	6 in	152.4 mm
Fishing Neck OD	8 in	203.2 mm
API Pin Size	6-5/8 REG	

Features

- E Feature - Extended Gage
- U Feature - Updrill Cutters

TOUGHSET SERIES

DESIGNED TO IMPROVE ROP AND FOOTAGE

The layout, features and cutters are customized to provide drill bit solutions tailored to maximize performance for specific applications.

TOUGHSET

Provides a stable environment for individual cutting elements resulting in a tough cutting structure.

DEEP LEACH CUTTERS

Premium application specific deep leached cutters are utilized to customize our bits to meet the needs of the formations drilled.

405.321.8850 SERVICE@TAUREXBITS.COM WWW.TAUREXBITS.COM

Copyright © 2021 Taurex Drill Bits, LLC. This document is copyrighted and, whether patentable or non-patentable matter, embodies the proprietary and confidential information and property of Taurex. Recipients agree it is loaned in confidence with the understanding the document nor the information in it will be reproduced, used or disclosed to others in whole or in part without the written authorization of Taurex.