RUN WITH THE BULL™

TAUREX DRILL BITS
POWERED BY: BITVISION™

7 7/8 in. TSd516 S5 EU

200 mm
PN: T11566

Design Specifications

IADC	S123							
Blades	5							
Cutters	38							
Cutter Size	C	16	F	16	G	16	mm	
Nozzles	S44	0	S65	0	S55	5	Port	0
Junk Slot Area	16.28 (in²)				105.03 sq cm			
Face Volume	73.6 (in³)				1206.09 cu cm			

Operating Guidelines*

Makeup Torque	12,600 - 13,700 ft-lbs
	17,083 - 18,575 Nm

*Guidelines only. See a Taurex rep for application specifics.

Nominal Dimensions

Makeup Length	10.8 in	274.3 mm
Overall Length	15 in	381 mm
Gage Length	4 in	101.6 mm
Fishing Neck OD	6 in	152.4 mm
API Pin Size	4-1/2 REG	

Features

E Feature - Extended Gage

U Feature - Updrill Cutters

DIRECTRAC SERIES

DESIGNED TO IMPROVE ROP AND FOOTAGE

The layout, features and cutters are customized to provide drill bit solutions tailored to maximize performance for specific applications.

DIRECTRAC

Yields a smooth distribution of torque and work load from cone to shoulder.

DEEP LEACH CUTTERS

Premium application specific deep leached cutters are utilized to customize our bits to meet the needs of the formations drilled.

TFC INSERTS

TFC inserts are tungsten carbide inserts strategically placed to reduce volatility in the torque generated making the bit easier to steer.

405.321.8850 SERVICE@TAUREXBITS.COM WWW.TAUREXBITS.COM

Copyright © 2021 Taurex Drill Bits, LLC. This document is copyrighted and, whether patentable or non-patentable matter, embodies the proprietary and confidential information and property of Taurex. Recipients agree it is loaned in confidence with the understanding the document nor the information in it will be reproduced, used or disclosed to others in whole or in part without the written authorization of Taurex.