SPLIT BLADE™

SPL616 12.250 IN 311 MM

DETAIL PN: U05026	IADC S323
TOTAL CUTTERS	80
CUTTER SIZE	5/8 IN | 16 MM
BLADE COUNT	6
FACE CUTTERS	62 (44 PRIMARY, 18 DOUBLE)
GAUGE CUTTERS	18 (6 IN GAUGE, 6 UP DRILL)
NOZZLES	9 (55 SERIES)
GAUGE LENGTH	6.0 IN | 152 MM
GAUGE TYPE	TSD & PDC & Hard Facing
BIT MATERIAL	STEEL BODY
MAKE UP LENGTH	15.98 IN | 406 MM
JUNK SLOT AREA	32.47 SQ IN | 209.5 SQ CM
FACE VOLUME	199.75 CU IN | 3273.3 CU CM
BIT CONNECTION	6-5/8 API REGULAR
BIT BREAKER(S)	6-5/8" REGULAR (960004) 12.250 CAGE BREAKER (960005)
ROTARY SPEED	SUITABLE FOR ROTARY AND PDM
WEIGHT ON BIT (TYPICAL MAX)	49,000 lbs | 21,800 daN
FLOW RATE	550-1,200 GPM 2,000-4,400 LPM
MAKE UP TORQUE	37,900 - 42,000 FT LB 51,400 - 56,900 N M
FEATURE(S)	LOAD LIMITERS CASING DRILL OUT DOUBLE ROW PDC EXTENDED GAUGE IN-GAUGE PDC UP-DRILL PDC

Powered by: UniSpec V2.10.D91

BIT Lab

These parameters are general guidelines. Make-Up Torque parameters are based on a mid-range Bit Sub OD. Please contact your local Ulterra representative for application specific recommendations.

©2025 Ulterra Drilling Technologies L.P., all rights reserved. The trademarks and logos (collectively, the "Marks") set forth in this document are registered and unregistered Marks owned by Ulterra Drilling Technologies L.P.

ULTERRA®

THINKING FORWARD. CHALLENGING LIMITS.™