## Model

# 12-1/4” DR16(K)(BR)

## Standard Features

Premium-grade cutters to maximize ROP and extend bit life.

Nozzle placement is optimized for maximum cuttings removal.

Large open face volume to enhance cuttings removal.

## Specifications

| | |
|---|---|
| Blade Count | 6 |
| Gauge Length | 6.00" |
| Cutter Size (Primary, Secondary) | 5/8”, 1/2” |
| Cutter Count (Primary, Secondary) | 81, 23 |
| Nozzle Series (Primary, Secondary) | 60, 45 |
| Nozzle Count (Primary, Secondary) | 9, 3 |
| Max. Nozzle Size (Primary, Secondary) | 22, 16 |
| Junk Slot Area (JSA) | 25.08 in² |
| Max. Total Flow Area (TFA) | 3.93 in² |

## Operating Parameters

| | |
|---|---|
| Max. Hydraulic Flow Rate | 1,860 gal/min |
| Max. Weight On Bit (WOB) | 60,000 lbs |
| Make Up Torque | 40,563 ft/lbs |

## Dimensions

| | |
|---|---|
| Overall Length | 22.92" |
| Make Up Length | 18.05" |
| Weight | 345 lbs |
| Bit Breaker | SKB-21011 |
| Connection | 6-5/8" API Reg. |

Caprock DRILL BITS

3446 South Main Street | Pearland, Texas 77581 | www.caprockdrillbits.com