

RWorksheet_Malayas#4c

Andrew Miguel M. Malayas BSIT2A

2024-11-01

1. Use the dataset mpg

a. Show your solutions on how to import a csv file into the environment.

```
library(readr)
mpg <- read_csv("mpg.csv")
```

```
## New names:
## Rows: 234 Columns: 12
## -- Column specification
## ----- Delimiter: "," chr
## (6): manufacturer, model, trans, drv, fl, class dbl (6): ...1, displ, year,
## cyl, cty, hwy
## i Use 'spec()' to retrieve the full column specification for this data. i
## Specify the column types or set 'show_col_types = FALSE' to quiet this message.
## * ' -> '...1'
```

mpg

```
## # A tibble: 234 x 12
##   ...1 manufacturer model      displ  year  cyl trans drv    cty   hwy fl
##   <dbl> <chr>      <chr>    <dbl> <dbl> <dbl> <chr> <chr> <dbl> <dbl> <chr>
## 1     1 audi      a4        1.8  1999    4 auto~ f     18   29 p
## 2     2 audi      a4        1.8  1999    4 manu~ f     21   29 p
## 3     3 audi      a4         2   2008    4 manu~ f     20   31 p
## 4     4 audi      a4         2   2008    4 auto~ f     21   30 p
## 5     5 audi      a4        2.8  1999    6 auto~ f     16   26 p
## 6     6 audi      a4        2.8  1999    6 manu~ f     18   26 p
## 7     7 audi      a4        3.1  2008    6 auto~ f     18   27 p
## 8     8 audi      a4 quattro 1.8  1999    4 manu~ 4     18   26 p
## 9     9 audi      a4 quattro 1.8  1999    4 auto~ 4     16   25 p
## 10    10 audi      a4 quattro 2    2008    4 manu~ 4     20   28 p
## # i 224 more rows
## # i 1 more variable: class <chr>
```

b. Which variables from mpg dataset are categorical?

manufacturer - The car manufacturer (e.g., Audi, Chevrolet). - model - trans - drv - cyl - fl - class - manufacturer

c. Which are continuous variables?

- displ
- year
- cyl
- hwy

2. Which manufacturer has the most models in this data set? Which model has the most variations?
Show your answer.

```
library(dplyr)

##
## Attaching package: 'dplyr'

## The following objects are masked from 'package:stats':
##
##   filter, lag

## The following objects are masked from 'package:base':
##
##   intersect, setdiff, setequal, union

manufacturer_model_count <- mpg %>%
  group_by(manufacturer) %>%
  summarise(model_count = n_distinct(model)) %>%
  arrange(desc(model_count))

most_models_manufacturer <- manufacturer_model_count[1, ]

model_variation_count <- mpg %>%
  group_by(model) %>%
  summarise(variation_count = n()) %>%
  arrange(desc(variation_count))

most_variations_model <- model_variation_count[1, ]

most_models_manufacturer

## # A tibble: 1 x 2
##   manufacturer model_count
##   <chr>             <int>
## 1 toyota             6

most_variations_model

## # A tibble: 1 x 2
##   model          variation_count
##   <chr>             <int>
## 1 caravan 2wd         11
```

a. Group the manufacturers and find the unique models. Show your codes and result.

```
unique_models <- mpg %>%
  group_by(manufacturer) %>%
  summarise(unique_models = list(unique(model))) %>%
  arrange(manufacturer)

print(unique_models)
```


```
## # A tibble: 15 x 2
##   manufacturer unique_models
##   <chr>         <list>
## 1 audi         <chr [3]>
## 2 chevrolet    <chr [4]>
## 3 dodge        <chr [4]>
## 4 ford         <chr [4]>
## 5 honda        <chr [1]>
## 6 hyundai      <chr [2]>
## 7 jeep         <chr [1]>
## 8 land rover   <chr [1]>
## 9 lincoln      <chr [1]>
## 10 mercury     <chr [1]>
## 11 nissan       <chr [3]>
## 12 pontiac     <chr [1]>
## 13 subaru       <chr [2]>
## 14 toyota       <chr [6]>
## 15 volkswagen  <chr [4]>
```

b. Graph the result by using plot() and ggplot(). Write the codes and its result.

```
model <- mpg %>%
  group_by(manufacturer) %>%
  summarise(unique_count = n_distinct(model)) %>%
  arrange(desc(unique_count))

barplot(model$unique_count,
        names.arg = model$manufacturer,
        las = 2,
        col = "lightgrey",
        main = "Number of Unique Models by Manufacturer",
        xlab = "Manufacturer",
        ylab = "Number of Unique Models")
```

Number of Unique Models by Manufacturer



```
library(ggplot2)
```

```
##
```


```
## Attaching package: 'ggplot2'
```

```
## The following object is masked _by_ '.GlobalEnv':
```

```
##
```

```
## mpg
```

```
ggplot(model, aes(x = reorder(manufacturer, unique_count), y = unique_count)) +  
  geom_bar(stat = "identity", fill = "lightgrey") +  
  coord_flip() +  
  labs(title = "Number of Unique Models by Manufacturer",  
        x = "Manufacturer",  
        y = "Number of Unique Models") +  
  theme_minimal()
```



2. Same dataset will be used. You are going to show the relationship of the model and the manufacturer.


a. What does `ggplot(mpg, aes(model, manufacturer)) + geom_point()` show? x-axis: represents the model. y-axis: represents the manufacturer. This code generates a scatter plot where each point represents a unique pairing of model and manufacturer. It illustrates which models are produced by each manufacturer, showing the distribution of models across different manufacturers.

b. For you, is it useful? If not, how could you modify the data to make it more informative? Usefulness:

As it stands, the plot isn't particularly helpful for analyzing the relationship between model and manufacturer because of the overplotting of points and the absence of numerical or continuous variables that could offer deeper insights.

3. Plot the model and the year using `ggplot()`. Use only the top 20 observations. Write the codes and its results.

```
Top_20 <- mpg %>%
  arrange(desc(cty)) %>%
  head(20)
ggplot(Top_20, aes(x = model, y = year)) +
  geom_point() +
  labs(title = "Top 20 Models by Year", x = "Model", y = "Year") +
  theme(axis.text.x = element_text(angle = 90, hjust = 0.5))
```



4. Using the pipe (`%>%`), group the model and get the number of cars per model. Show codes and its result

```
model_counts <- mpg %>%
  group_by(model) %>%
  summarise(num_of_cars = n()) %>%
  arrange(desc(num_of_cars))


print(model_counts)
```

```
## # A tibble: 38 x 2
##   model                num_of_cars
##   <chr>                <int>
## 1 caravan 2wd           11
## 2 ram 1500 pickup 4wd    10
## 3 civic                 9
## 4 dakota pickup 4wd      9
## 5 jetta                 9
## 6 mustang                9
## 7 a4 quattro             8
## 8 grand cherokee 4wd     8
## 9 impreza awd            8
## 10 a4                    7
## # i 28 more rows
```

- a. Plot using `geom_bar()` using the top 20 observations only. The graphs should have a title, labels and colors. Show code and results.

```
top_20_models <- mpg %>%
  group_by(model) %>%
  summarise(num_of_cars = n()) %>%
  arrange(desc(num_of_cars)) %>%
  slice_head(n = 20)


ggplot(top_20_models, aes(x = reorder(model, num_of_cars), y = num_of_cars, fill = model)) +
  geom_bar(stat = "identity") +
  coord_flip() +
  labs(title = "Top 20 Car Models by Number of Cars",
       x = "Car Model",
       y = "Number of Cars",
       fill = "Model") +
  theme_minimal() +
  scale_fill_viridis_d()
```



- b. Plot using the `geom_bar()` + `coord_flip()` just like what is shown below. Show codes and its result.


```
top_20_models <- mpg %>%
  group_by(model) %>%
  summarise(num_of_cars = n()) %>%
  arrange(desc(num_of_cars)) %>%
  slice_head(n = 20)
```

```
ggplot(top_20_models, aes(x = reorder(model, num_of_cars), y = num_of_cars, fill = model)) +
  geom_bar(stat = "identity") +
  coord_flip() +
  labs(title = "Top 20 Car Models by Number of Cars",
       x = "Car Model",
       y = "Number of Cars") +
  theme_minimal() +
  scale_fill_viridis_d()
```



- Plot the relationship between cyl - number of cylinders and displ - engine displacement using `geom_point` with aesthetic color = engine displacement. Title should be "Relationship between No. of Cylinders and Engine Displacement".

```
ggplot(mpg, aes(x = cyl, y = displ, color = displ)) +
  geom_point(size = 2, alpha = 0.8) +
  labs(title = "Relationship between No. of Cylinders and Engine Displacement",
       x = "Number of Cylinders",
       y = "Engine Displacement") +
  theme_minimal() +
  scale_color_viridis_c()
```

a. How would you describe its relationship? Show the codes and its result.


The plot indicates that as the number of cylinders rises, engine displacement generally follows an upward trend. This suggests a positive correlation, where vehicles with a higher cylinder count tend to have greater engine displacement.

The color gradient adds another layer of information, with darker colors representing lower engine displacement values and lighter colors representing higher values. This helps illustrate how engine displacement varies across different cylinder counts.

6. Plot the relationship between `displ` (engine displacement) and `hwy` (highway miles per gallon). Mapped it with a continuous variable you have identified in #1-c. What is its result? Why it produced such output?

```
ggplot(mpg, aes(x = displ, y = hwy, color = cty)) +
  geom_point(size = 3, alpha = 0.7) +
  labs(title = "Relationship between Engine Displacement and Highway MPG",
       x = "Engine Displacement (L)",
       y = "Highway MPG",
       color = "City MPG") +
  theme_minimal() +
  scale_color_viridis_c()
```

Relationship between Engine Displacement and Highway MPG



6. Import the traffic.csv onto your R environment.

```
library(readr)
traffic_info <- read_csv("traffic.csv")
```

```
## Rows: 48120 Columns: 4
## -- Column specification -----
## Delimiter: ","
## dbl (3): Junction, Vehicles, ID
## dtm (1): DateTime
##
## i Use 'spec()' to retrieve the full column specification for this data.
## i Specify the column types or set 'show_col_types = FALSE' to quiet this message.
```

```
head(traffic_info)
```

```
## # A tibble: 6 x 4
##   DateTime      Junction Vehicles      ID
##   <dtm>         <dbl>    <dbl>    <dbl>
## 1 2015-11-01 00:00:00      1      15 20151101001
## 2 2015-11-01 01:00:00      1      13 20151101011
## 3 2015-11-01 02:00:00      1      10 20151101021
## 4 2015-11-01 03:00:00      1       7 20151101031
## 5 2015-11-01 04:00:00      1       9 20151101041
## 6 2015-11-01 05:00:00      1       6 20151101051
```

- a. How many numbers of observation does it have? What are the variables of the traffic dataset the Show your answer.

```
num_of_observations <- nrow(traffic_info)
variables <- colnames(traffic_info)
num_of_observations
```

```
## [1] 48120
```

```
variables
```

```
## [1] "DateTime" "Junction" "Vehicles" "ID"
```

- b. subset the traffic dataset into junctions. What is the R codes and its output?

```
data_to_junctions <- subset(traffic_info, Junction == TRUE)
head(data_to_junctions)
```

```
## # A tibble: 6 x 4
##   DateTime          Junction Vehicles      ID
##   <dtm>            <dbl>    <dbl>    <dbl>
## 1 2015-11-01 00:00:00         1      15 20151101001
## 2 2015-11-01 01:00:00         1      13 20151101011
## 3 2015-11-01 02:00:00         1      10 20151101021
## 4 2015-11-01 03:00:00         1       7 20151101031
## 5 2015-11-01 04:00:00         1       9 20151101041
## 6 2015-11-01 05:00:00         1       6 20151101051
```

- c. Plot each junction in a using geom_line(). Show your solution and output.

```
library(ggplot2)
ggplot(traffic_info, aes(x = DateTime, y = Vehicles, color = factor(Junction))) +
  geom_line() +
  labs(title = "Vehicle Counts at Junctions Over Time",
       x = "Date and Time",
       y = "Number of Vehicles",
       color = "Junction") +
  theme_minimal() +
  theme(axis.text.x = element_text(angle = 45, hjust = 1))
```

