## **Data Structures and Algorithms**

Pierre Collet/ Manal ElZant-Karray

## Practical work n°7: Binary Tree

Exercise 1: Write a function to print all Root-to-Leaf paths in a binary tree.

Algorithm: Steps for print all paths from root to leaf are:

- If node is null then return 0
- Put node->data in array and increment length by 1.
- If encountered leaf node (node->left is null and node->right is null) then print array.
- Recursively visit left subtree and right subtree


Exercise 2: Write a program to print all ancestors of a given node N in a binary tree. Use a recursive approach to print ancestors of a node.

Let **root** be the pointer to the root node of given binary tree.

- if root is equal to NULL, return false (node not found).
- If root is equal to N, return true (node found).
- ullet Recursively search N in left and right sub tree. If N is present in any of the sub tree, then root must be an ancestor of N.
- $\bullet\,$  If neither left sub tree nor right sub tree contains N, then N is not ancestor of N.

Exercise 3: Write a program to checks if a binary tree is max heap or not! Don't forget to check if the binary tree is complete.

Exercise 4: Complete the C program for recursive **level order traversal** in *spiral form*.



```
#include <stdbool.h>
#include <stdio.h>
#include <stdlib.h>
struct node {
      int data;
      struct node* left;
      struct node* right;
};
// Function to print spiral traversal of a tree
void printSpiral(struct node* root) {
... .
}
// Print nodes at a given level
void printGivenLevel(struct node* root, int level, int lt) {
int height(struct node* node) {
}
struct node* newNode(int data) {
      struct node* node = (struct node*)
      malloc(sizeof(struct node));
      node->data = data;
      node->left = NULL;
      node->right = NULL;
      return (node);
int main() {
      struct node* root = newNode(1);
      root->left = newNode(2);
     root->right = newNode(3);
     root->left->left = newNode(4);
     root->left->right = newNode(5);
     root->right->left = newNode(6);
      root->right->right = newNode(7);
      root->right->right = newNode(9);
      root->left->right->left = newNode(8);
      printf("The Spiral Order traversal of binary tree is \n");
      printSpiral(root);
      return 0;
```

Exercise 4: Write a function to mirror binary tree.

