Practice · Terminal

Each question lists its options; the right one is marked **Right answer**. *Feedback* is what students see after they answer. In a typed question the blank is in square brackets, with the accepted answers separated by `|`.

(mc) L1 · Which command shows the folder you are in

You are in the terminal and you do not know which folder you are in. Which command tells you?

- **Right answer:** `pwd`
- `ls`
- `cd`
- `mkdir`

Feedback: `pwd` prints the folder you are standing in. `ls` shows what is inside it, `cd` moves you, `mkdir` makes a new folder.

(mc) L1 · Which command lists the files in the folder

Which command shows the files in the folder you are in?

- `pwd`
- `cd`
- **Right answer:** `ls` (on Windows also `dir`)
- `gcc`

Feedback: `ls` lists what is in the folder. On Windows PowerShell `dir` does the same. `pwd` only prints the folder's name, not its contents.

(mc) L1 · Which command makes a new folder

Which command creates a new folder?

- `cd`
- `ls`
- `new`
- **Right answer:** `mkdir`

Feedback: `mkdir` means "make directory". A directory is a folder. `new` is not a command.

(mc) L2 · Going into a folder

You are in your home folder and it contains a folder called `c_week1`. Which command takes you into `c_week1`?

- `cd`
- **Right answer:** `cd c_week1`
- `mkdir c_week1`
- `ls c_week1`

Feedback: `cd` followed by the folder's name goes into that folder. `cd` alone goes home. `mkdir c_week1` would try to make it again. `ls c_week1` only shows what is inside it without moving you.

(mc) L2 · Going back up

You are inside `c_week1` and want to go back to the folder that contains it. Which command does that?

- `cd back`
- `cd /`
- **Right answer:** `cd ..`
- `pwd ..`

Feedback: `cd ..` means "go up one level". The two dots stand for "the folder above this one". `cd /` goes to the very top of the disk, which is not where you want to be.

(mc) L2 · gcc cannot find the file

You type `gcc hello.c -o hello` and see `gcc: error: hello.c: No such file or directory`. What is the most likely reason?

- The program has a missing semicolon.
- gcc is not installed.
- **Right answer:** You are in the wrong folder, so gcc cannot see `hello.c`.
- The file must be called `hello.exe`.

Feedback: "No such file" means gcc looked in the folder you are in and did not find `hello.c`. Run `pwd` and `ls` to see where you are and what is there, then `cd` into the right folder. A missing semicolon gives a different message, with a line number.

(fib) L3 · Make a folder called practice

Write the command that creates a folder named `practice`. Type it exactly, with one space: [mkdir practice]

Feedback: `mkdir practice`. The command first, then a space, then the name of the new folder.

(fib) L3 · Go into that folder

You just created the folder `practice`. Write the command that goes into it: [cd practice]

Feedback: `cd practice`. `cd` means "change directory", and the name after it is where you go.

(fib) L3 · Compile and run

Complete the two commands. To compile `hello.c` into a program called `hello`, with all warnings on: `gcc -Wall hello.c` [-o hello]. Then, to run it on Linux or macOS: [./hello]

Feedback: The compile command is `gcc -Wall hello.c -o hello`. `-o hello` means "put the output in a file called hello". To run it you type `./hello` (on Windows PowerShell `.\hello`). The `./` means "the one in this folder".