



北京航空航天大学
BEIHANG UNIVERSITY

信息系统分析与设计 PART II 关联分析 Association Analysis

Dr. Guannan Liu



>>> Outline



- Basic concepts
- Frequent Itemset
- Frequent Itemset Generation: Apriori
- Rule generation

>> Association Rule Mining



- Given a set of transactions, find rules that will predict the occurrence of an item based on the occurrences of other items in the transaction

Market-Basket transactions

<i>TID</i>	<i>Items</i>
1	Bread, Milk
2	Bread, Diaper, Beer, Eggs
3	Milk, Diaper, Beer, Coke
4	Bread, Milk, Diaper, Beer
5	Bread, Milk, Diaper, Coke

Example of Association Rules

$\{\text{Diaper}\} \rightarrow \{\text{Beer}\},$
 $\{\text{Milk, Bread}\} \rightarrow \{\text{Eggs, Coke}\},$
 $\{\text{Beer, Bread}\} \rightarrow \{\text{Milk}\},$

Implication means co-occurrence,
not causality!

>>> Definition: Frequent Itemset



- Itemset
 - A collection of one or more items
 - Example: {Milk, Bread, Diaper}
 - k-itemset
 - An itemset that contains k items
- Support count (σ)
 - Frequency of occurrence of an itemset
 - E.g. $\sigma(\{\text{Milk, Bread, Diaper}\}) = 2$
- Support
 - Fraction of transactions that contain an itemset
 - E.g. $s(\{\text{Milk, Bread, Diaper}\}) = 2/5$
- Frequent Itemset
 - An itemset whose support is greater than or equal to a minsup threshold

<i>TID</i>	<i>Items</i>
1	Bread, Milk
2	Bread, Diaper, Beer, Eggs
3	Milk, Diaper, Beer, Coke
4	Bread, Milk, Diaper, Beer
5	Bread, Milk, Diaper, Coke

>>> Definition: Association Rule



■ Association Rule

- An implication expression of the form $X \rightarrow Y$, where X and Y are itemsets
- Example:
 $\{\text{Milk, Diaper}\} \rightarrow \{\text{Beer}\}$

<i>TID</i>	<i>Items</i>
1	Bread, Milk
2	Bread, Diaper, Beer, Eggs
3	Milk, Diaper, Beer, Coke
4	Bread, Milk, Diaper, Beer
5	Bread, Milk, Diaper, Coke

■ Rule Evaluation Metrics

- Support (s)
 - Fraction of transactions that contain both X and Y
- Confidence (c)
 - Measures how often items in Y appear in transactions that contain X

Example:

$$\{\text{Milk, Diaper}\} \Rightarrow \{\text{Beer}\}$$

$$s = \frac{\sigma(\text{Milk, Diaper, Beer})}{|T|} = \frac{2}{5} = 0.4$$

$$c = \frac{\sigma(\text{Milk, Diaper, Beer})}{\sigma(\text{Milk, Diaper})} = \frac{2}{3} = 0.67$$

>>> Association Rule Mining Task

- Given a set of transactions T , the goal of association rule mining is to find all rules having
 - support \geq *minsup* threshold
 - confidence \geq *minconf* threshold


- Brute-force approach:
 - List all possible association rules
 - Compute the support and confidence for each rule
 - Prune rules that fail the *minsup* and *minconf* thresholds

⇒ **Computationally prohibitive!**

>>> An exercise



- Total number of itemsets in a transactional data set with d items.
- The total number of possible rules extracted from a transactional data set with d items.
 - Tips



>>> Mining Association Rules



<i>TID</i>	<i>Items</i>
1	Bread, Milk
2	Bread, Diaper, Beer, Eggs
3	Milk, Diaper, Beer, Coke
4	Bread, Milk, Diaper, Beer
5	Bread, Milk, Diaper, Coke

Example of Rules:

$\{\text{Milk, Diaper}\} \rightarrow \{\text{Beer}\}$ ($s=0.4$, $c=0.67$)

$\{\text{Milk, Beer}\} \rightarrow \{\text{Diaper}\}$ ($s=0.4$, $c=1.0$)

$\{\text{Diaper, Beer}\} \rightarrow \{\text{Milk}\}$ ($s=0.4$, $c=0.67$)

$\{\text{Beer}\} \rightarrow \{\text{Milk, Diaper}\}$ ($s=0.4$, $c=0.67$)

$\{\text{Diaper}\} \rightarrow \{\text{Milk, Beer}\}$ ($s=0.4$, $c=0.5$)

$\{\text{Milk}\} \rightarrow \{\text{Diaper, Beer}\}$ ($s=0.4$, $c=0.5$)

Observations:


- All the above rules are binary partitions of the same itemset:
 $\{\text{Milk, Diaper, Beer}\}$
- Rules originating from the same itemset have identical support but can have different confidence
- Thus, we may decouple the support and confidence requirements

>>> Mining Association Rules



- Two-step approach:
 1. Frequent Itemset Generation
 - Generate all itemsets whose support \geq minsup
 2. Rule Generation
 - Generate high confidence rules from each frequent itemset, where each rule is a binary partitioning of a frequent itemset
- Frequent itemset generation is still computationally expensive

>>> Frequent Itemset Generation




Given d items, there are 2^d possible candidate itemsets

>>> Frequent Itemset Generation

■ Brute-force approach:

- Each itemset in the lattice is a **candidate** frequent itemset
- Count the support of each candidate by scanning the database



- Match each transaction against every candidate
- Complexity $\sim O(NMw) \Rightarrow$ **Expensive since $M = 2^d$!!!**

>>> Frequent Itemset Generation Strategies

- Reduce the **number of candidates** (M)
 - Complete search: $M=2^d$
 - Use pruning techniques to reduce M
- Reduce the **number of transactions** (N)
 - Reduce size of N as the size of itemset increases
 - Used by DHP and vertical-based mining algorithms
- Reduce the **number of comparisons** (NM)
 - Use efficient data structures to store the candidates or transactions
 - No need to match every candidate against every transaction


>>> Reducing Number of Candidates

- **Apriori principle:**
 - If an itemset is frequent, then all of its subsets must also be frequent
- Apriori principle holds due to the following property of the support measure:

$$\forall X, Y : (X \subseteq Y) \Rightarrow s(X) \geq s(Y)$$

- Support of an itemset never exceeds the support of its subsets
- This is known as the **anti-monotone** property of support

>>> Illustrating Apriori Principle



>>> Illustrating Apriori Principle



Item	Count
Bread	4
Coke	2
Milk	4
Beer	3
Diaper	4
Eggs	1

Items (1-itemsets)



Itemset	Count
{Bread,Milk}	3
{Bread,Beer}	2
{Bread,Diaper}	3
{Milk,Beer}	2
{Milk,Diaper}	3
{Beer,Diaper}	3

Pairs (2-itemsets)

(No need to generate candidates involving Coke or Eggs)

Minimum Support = 3

If every subset is considered,

$$C_6^1 + C_6^2 + C_6^3 = 41$$

With support-based pruning,

$$C_6^1 + C_6^2 + 1 = 13$$



Triplets (3-itemsets)

Itemset	Count
{Bread,Milk,Diaper}	3



>> Apriori Algorithm




- Method:
 - Let $k=1$
 - Generate frequent itemsets of length 1
 - Repeat until no new frequent itemsets are identified
 - Generate length $(k+1)$ candidate itemsets from length k frequent itemsets
 - Prune candidate itemsets containing subsets of length k that are infrequent
 - Count the support of each candidate by scanning the dataset
 - Eliminate candidates that are infrequent, leaving only those that are frequent

>>> Candidate Generation



- $F_{k-1} \times F_1$
 - Complete because each k-itemset is composed of a frequent (k-1)-itemset and a frequent 1-itemset
 - $\{\text{beer, diaper}\} * \{\text{milk}\}$
 - Not necessary, because $\{\text{milk, beer}\}$ is already infrequent!
- $F_{k-1} \times F_{k-1}$




>>> Reducing Number of Comparisons



■ Candidate counting:

- Scan the database of transactions to determine the support of each candidate itemset
- To reduce the number of comparisons, store the candidates in a hash structure
 - Instead of matching each transaction against every candidate, match it against candidates contained in the hashed buckets



- How to efficiently generate rules from frequent itemsets?

- In general, confidence does not have an anti-monotone property

$c(ABC \rightarrow D)$ can be larger or smaller than $c(AB \rightarrow D)$

- But confidence of rules generated from the same itemset has an anti-monotone property

- e.g., $L = \{A, B, C, D\}$:


$$c(ABC \rightarrow D) \geq c(AB \rightarrow CD) \geq c(A \rightarrow BCD)$$

- Confidence is anti-monotone w.r.t. number of items on the RHS of the rule

>>> Rule Generation for Apriori Algorithm




Lattice of rules



>> Rule Generation for Apriori Algorithm



- Candidate rule is generated by merging two rules that share the same prefix in the rule consequent
- $\text{join}(\text{CD} \Rightarrow \text{AB}, \text{BD} \Rightarrow \text{AC})$ would produce the candidate rule $\text{D} \Rightarrow \text{ABC}$
- Prune rule $\text{D} \Rightarrow \text{ABC}$ if its subset $\text{AD} \Rightarrow \text{BC}$ does not have high confidence



>>> Factors Affecting Complexity

- Choice of minimum support threshold
 - lowering support threshold results in more frequent itemsets
 - this may increase number of candidates and max length of frequent itemsets
- Dimensionality (number of items) of the data set
 - more space is needed to store support count of each item
 - if number of frequent items also increases, both computation and I/O costs may also increase
- Size of database
 - since Apriori makes multiple passes, run time of algorithm may increase with number of transactions
- Average transaction width
 - transaction width increases with denser data sets
 - This may increase max length of frequent itemsets and traversals of hash tree (number of subsets in a transaction increases with its width)

>>> Compact Representation of Frequent Itemsets



- Some itemsets are redundant because they have identical support as their supersets

TID	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	C1	C2	C3	C4	C5	C6	C7	C8	C9	C10
1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
3	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
4	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
5	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
6	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0
7	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0
8	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0
9	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0
10	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0
11	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1
12	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1
13	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1
14	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1
15	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1


- Number of frequent itemsets

$$= 3 \times \sum_{k=1}^{10} \binom{10}{k}$$

- Need a compact representation

>>> Maximal Frequent Itemset

An itemset is maximal frequent if none of its **immediate supersets** is frequent



>>> Closed Itemset



- An itemset is closed if none of its immediate supersets has the same support as the itemset


TID	Items
1	{A,B}
2	{B,C,D}
3	{A,B,C,D}
4	{A,B,D}
5	{A,B,C,D}

Itemset	Support
{A}	4
{B}	5
{C}	3
{D}	4
{A,B}	4
{A,C}	2
{A,D}	3
{B,C}	3
{B,D}	4
{C,D}	3


Itemset	Support
{A,B,C}	2
{A,B,D}	3
{A,C,D}	2
{B,C,D}	3
{A,B,C,D}	2

>>> Maximal vs Closed Itemsets


TID	Items
1	ABC
2	ABCD
3	BCE
4	ACDE
5	DE



>>> Maximal vs Closed Frequent Itemsets



>>> Maximal vs Closed Itemsets





- Thanks!

Let's enjoy playing with data!

