

JQUERY SELECTORS

Selector	Example	Selects
<code>*</code>	<code>\$("*")</code>	All elements
<code>#id</code>	<code>\$("#lastname")</code>	The element with id="lastname"
<code>.class</code>	<code>\$(".intro")</code>	All elements with class="intro"
<code>.class.class</code>	<code>\$(".intro,.demo")</code>	All elements with the class "intro" or "demo"
<code>element</code>	<code>\$("p")</code>	All <p> elements
<code>el1,el2,el3</code>	<code>\$("h1,div,p")</code>	All <h1>, <div> and <p> elements
<code>:first</code>	<code>\$("p:first")</code>	The first <p> element
<code>:last</code>	<code>\$("p:last")</code>	The last <p> element
<code>:even</code>	<code>\$("tr:even")</code>	All even <tr> elements
<code>:odd</code>	<code>\$("tr:odd")</code>	All odd <tr> elements
<code>:first-child</code>	<code>\$("p:first-child")</code>	All <p> elements that are the first child of their parent
<code>:first-of-type</code>	<code>\$("p:first-of-type")</code>	All <p> elements that are the first <p> element of their parent
<code>:last-child</code>	<code>\$("p:last-child")</code>	All <p> elements that are the last child of their parent
<code>:last-of-type</code>	<code>\$("p:last-of-type")</code>	All <p> elements that are the last <p> element of their parent
<code>:nth-child(n)</code>	<code>\$("p:nth-child(2)")</code>	All <p> elements that are the 2nd child of their parent
<code>:nth-last-child(n)</code>	<code>\$("p:nth-last-child(2)")</code>	All <p> elements that are the 2nd child of their parent, counting from the last child
<code>:nth-of-type(n)</code>	<code>\$("p:nth-of-type(2)")</code>	All <p> elements that are the 2nd <p> element of their parent
<code>:nth-last-of-type(n)</code>	<code>\$("p:nth-last-of-type(2)")</code>	All <p> elements that are the 2nd <p> element of their parent, counting from the last child
<code>:only-child</code>	<code>\$("p:only-child")</code>	All <p> elements that are the only child of their parent
<code>:only-of-type</code>	<code>\$("p:only-of-type")</code>	All <p> elements that are the only child, of its type, of their parent
<code>parent > child</code>	<code>\$("div > p")</code>	All <p> elements that are a direct child of a <div> element
<code>parent descendant</code>	<code>\$("div p")</code>	All <p> elements that are descendants of a <div> element
<code>element + next</code>	<code>\$("div + p")</code>	The <p> element that are next to each <div> elements

<code>element ~ siblings</code>	<code>\$("div ~ p")</code>	All <code><p></code> elements that appear after the <code><div></code> element
<code>:eq(<i>index</i>)</code>	<code>\$("ul li:eq(3)")</code>	The fourth element in a list (index starts at 0)
<code>:gt(<i>no</i>)</code>	<code>\$("ul li:gt(3)")</code>	List elements with an index greater than 3
<code>:lt(<i>no</i>)</code>	<code>\$("ul li:lt(3)")</code>	List elements with an index less than 3
<code>:not(<i>selector</i>)</code>	<code>\$("input:not(:empty)")</code>	All input elements that are not empty
<code>:header</code>	<code>\$(":header")</code>	All header elements <code><h1></code> , <code><h2></code> ...
<code>:animated</code>	<code>\$(":animated")</code>	All animated elements
<code>:focus</code>	<code>\$(":focus")</code>	The element that currently has focus
<code>:contains(<i>text</i>)</code>	<code>\$(":contains('Hello'))"</code>	All elements which contains the text "Hello"
<code>:has(<i>selector</i>)</code>	<code>\$("div:has(p)")</code>	All <code><div></code> elements that have a <code><p></code> element
<code>:empty</code>	<code>\$(":empty")</code>	All elements that are empty
<code>:parent</code>	<code>\$(":parent")</code>	All elements that are a parent of another element
<code>:hidden</code>	<code>\$("p:hidden")</code>	All hidden <code><p></code> elements
<code>:visible</code>	<code>\$("table:visible")</code>	All visible tables
<code>:root</code>	<code>\$(":root")</code>	The document's root element
<code>:lang(<i>language</i>)</code>	<code>\$("p:lang(de)")</code>	All <code><p></code> elements with a lang attribute value starting with "de"
<code>[<i>attribute</i>]</code>	<code>\$("[href]")</code>	All elements with a href attribute
<code>[<i>attribute</i>=<i>value</i>]</code>	<code>\$("[href='default.htm']")</code>	All elements with a href attribute value equal to "default.htm"
<code>[<i>attribute</i>!=<i>value</i>]</code>	<code>\$("[href!='default.htm']")</code>	All elements with a href attribute value not equal to "default.htm"
<code>[<i>attribute</i>\$=<i>value</i>]</code>	<code>\$("[href\$='.jpg']")</code>	All elements with a href attribute value ending with ".jpg"
<code>[<i>attribute</i> =<i>value</i>]</code>	<code>\$("[title ='Tomorrow']")</code>	All elements with a title attribute value equal to 'Tomorrow', or starting with 'Tomorrow' followed by a hyphen
<code>[<i>attribute</i>^=<i>value</i>]</code>	<code>\$("[title^='Tom']")</code>	All elements with a title attribute value starting with "Tom"
<code>[<i>attribute</i>~=<i>value</i>]</code>	<code>\$("[title~='hello']")</code>	All elements with a title attribute value containing the specific word "hello"
<code>[<i>attribute</i>*=<i>value</i>]</code>	<code>\$</code>	All elements with a title attribute value

lue] `("[title*='hello']` containing the word "hello"
`")`

<code>:input</code>	<code>\$(":input")</code>	All input elements
<code>:text</code>	<code>\$(":text")</code>	All input elements with type="text"
<code>:password</code>	<code>\$(":password")</code>	All input elements with type="password"
<code>:radio</code>	<code>\$(":radio")</code>	All input elements with type="radio"
<code>:checkbox</code>	<code>\$(":checkbox")</code>	All input elements with type="checkbox"
<code>:submit</code>	<code>\$(":submit")</code>	All input elements with type="submit"
<code>:reset</code>	<code>\$(":reset")</code>	All input elements with type="reset"
<code>:button</code>	<code>\$(":button")</code>	All input elements with type="button"
<code>:image</code>	<code>\$(":image")</code>	All input elements with type="image"
<code>:file</code>	<code>\$(":file")</code>	All input elements with type="file"
<code>:enabled</code>	<code>\$(":enabled")</code>	All enabled input elements
<code>:disabled</code>	<code>\$(":disabled")</code>	All disabled input elements
<code>:selected</code>	<code>\$(":selected")</code>	All selected input elements
<code>:checked</code>	<code>\$(":checked")</code>	All checked input elements