

Multi-Partner Webhook Strategy

Carland Service - Architecture and product advisory

Short answer: the foundation for multi-partner support partially exists, but the webhook and visit layers are effectively locked to Hyper today. Adding Toyota Absheron (or similar partners) tomorrow would work in a pinch, but clean and secure separation requires a few strategic changes.

1. What is already in place?

partners table:	Ready - id, name, source, logo, dealer
EnumPartnerId:	Ready - HYPER(1), AVTOVAZ(2)
Partner on visit:	Ready - serviceCenterId + serviceCenterName
Car profile:	Ready - servicedPartnerIds[]
Mobile API v2:	Ready - partner, serviceCenterId on each visit
Webhook ingest:	Hyper-specific - DTOs, mapper, default partner = Hyper
Auth:	Single WEBHOOK_SECRET - signature does not identify partner
Visit unique key:	(car_id, hyper_record_id) - no partner scope

In short: the data model's partner identity layer was designed with multi-partner in mind; the integration layer still behaves like a single partner.

2. Critical risk: recordId collision

Today the idempotency key is: car + recordId. If Toyota sends recordId=19387 and Hyper also has recordId=19387 for the same car, the second record would either overwrite the first or hit a unique constraint failure. For multi-partner, this is the most urgent issue.

What it should be: composite unique key (car_id, partner_id, record_id).

The column is named hyperRecordId - semantically it should be generalized (e.g. partnerRecordId / externalRecordId).

3. How do we separate partners?

3.1 URL path (recommended - clearest)

```
POST /webhook/partner/hyper/new-service-visit
POST /webhook/partner/toyota-absheron/new-service-visit
```

- Partner identity comes from the URL; do not rely on the body alone
- Easy per-partner rate limits and IP allowlists in nginx
- Extends the existing /webhook/partner/... path pattern

3.2 Per-partner secret (recommended - security)

```
Hyper -> WEBHOOK_SECRET_HYPER
Toyota -> WEBHOOK_SECRET_TOYOTA
```

- Signature provides both authentication and partner identity
- If one partner's secret leaks, others are unaffected
- Webhook gateway partner registry: { slug, secret, carlandPartnerId }

3.3 source / partnerId in body (not sufficient alone)

- Can be used together with auth, but not trusted by itself
- Real identity should come from URL or secret

Practical combination: path slug + per-partner secret + same JSON body format

4. JSON format: exact copy vs adapter?

Scenario A - All partners accept the same spec (ideal)

The format standardized for Hyper becomes the Carland Partner Webhook Spec:

```
{ "plate": "...", "vin": "...", "serviceHistory": [{ "recordId": ..., "services": [...] }] }
```

- Toyota sends the same shape -> one mapper, one validator
- Lowest maintenance cost
- Partner onboarding = secret + DB row + path

Scenario B - Partners send different JSON (realistic)

```
Toyota JSON -> ToyotaWebhookAdapter -> Canonical PartnerVisitPayload -> DB
Hyper JSON  -> HyperWebhookAdapter  -> Canonical PartnerVisitPayload -> DB
```

- Internal model is partner-agnostic; adapters sit at the edge
- Hyper adapter effectively exists today; naming should become generic

Recommendation: Publish the spec and ask new partners to implement it; add adapters only for partners that cannot comply. Use the Hyper format as the reference implementation.

5. Percentage / universalServiceId

HyperServiceMapping today maps Hyper's universalServiceId to our name_en. If Toyota uses a different catalog:

- Partner-scoped mapping table: (partner_id, external_service_id) -> service_name_en
- Or migrate all partners to a shared catalog (cleanest long term)
 - Percentage.partnerRecordId exists but which partner applied it is not stored - with multiple partners, partnerId should be stored too

The percentage sync rule (only refresh from the newest visit) should be partner-aware. Service mapping must be partner-scoped.

6. Mobile / history API

GET .../service-history/v2 today:

- If cache exists -> reads from DB (all partners' visits)
- If no cache -> pulls only from Hyper API

Even if Toyota sends visits via webhook, when a customer adds a car the live pull still goes to Hyper. With multiple partners:

- Remove live pull (webhook + cache only), or
- Add a per-partner pull adapter, or
- Treat webhook as primary source; pull only for backfill/onboarding

7. Recommended roadmap

- Phase 1:** (car_id, partner_id, record_id) unique constraint + migration [Small, critical]
- Phase 2:** Partner slug in path + per-partner webhook secret [Medium]
- Phase 3:** Rename Hyper* -> Partner*; partner from request context [Medium]
- Phase 4:** Partner-aware percentage / service mapping [Medium]
- Phase 5:** Toyota adapter (if JSON differs) [Per partner]
- Phase 6:** Clarify live history pull strategy [Product decision]

8. Minimum to add Toyota tomorrow

- Row in partners + EnumPartnerId.TOYOTA_ABSHERON(3) (or DB-only id)
- Separate webhook secret + path slug
- Fix DB unique constraint (partner-scoped recordId)
- In ingest: replace DEFAULT_PARTNER = HYPER with partner id from request context

9. Conclusion

Infrastructure ~40% ready:

- Partner table, visit serviceCenterId, mobile partner display

~60% gap:

- Webhook auth/partner separation, recordId scope, Hyper-centric code, percentage mapping, live fetch strategy

Infrastructure is partially ready; integration is Hyper-centric today.

10. Open product question

Before implementation, clarify: Will new partners adopt the same JSON spec as Hyper, or will each send its own format? That answer determines whether adapters are required; the rest of the architecture stays the same.

Generated for the Carland Service project - multi-partner webhook advisory.