

# Experimental unicode mathematical typesetting: The unicode-math package

Will Robertson

2009/09/29 v0.4

## Abstract

**Warning! This package is experimental and subject to change without regard for backwards compatibility. Performance issues may be encountered until algorithms are refined.**

## Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>	4.3	Other things	19
<b>2</b>	<b>Unicode maths font setup</b>	<b>1</b>	<b>5</b>	<b>Fundamentals</b>	<b>20</b>
2.1	Using multiple fonts	2	5.1	Enlarging the number of maths families	20
2.2	Script and scriptscript fonts/features	2	5.2	\DeclareMathSymbol for unicode ranges	20
<b>3</b>	<b>Maths input</b>	<b>3</b>	5.3	The main \setmathfont macro	22
3.1	Math ‘style’	3	5.4	(Big) operators	29
3.2	Bold style	3	5.5	Radicals	32
3.3	Sans serif style	5	5.6	Delimiters	33
3.4	All (the rest) of the mathematical alphabets	5	5.7	Maths accents	35
3.5	Miscellanea	6	<b>6</b>	<b>Font features</b>	<b>36</b>
<b>I</b>	<b>The unicode-math package</b>	<b>11</b>	6.1	OpenType maths font features	37
<b>4</b>	<b>Things we need</b>	<b>11</b>	6.2	Script and scriptscript font options	37
4.1	Package options	14	6.3	Range processing	37
4.2	Overcoming \onlypreamble	18	6.4	Resolving Greek symbol name control sequences	41

6.5	Setting up the mappings	43	<b>II</b>	<b>stix table data extraction</b>	<b>65</b>
<b>7</b>	<b>Maths alphabets mapping definitions</b>	<b>45</b>	<b>A</b>	<b>Documenting maths support in the NFSS</b>	<b>67</b>
7.1	Non-bold math alphabets	47	A.1	Overview	67
7.2	Bold math alphabets	51			
7.3	Definitions of the math symbols	56	<b>III</b>	<b>X<sub>Y</sub>TeX math font dimensions</b>	<b>68</b>
<b>8</b>	<b>Epilogue</b>	<b>58</b>			

## 1 Introduction

This document describes the unicode-math package, which is an *experimental* implementation of a macro to unicode glyph encoding for mathematical characters. Its intended use is for X<sub>Y</sub>TeX, although it is conjectured that some effect could be spent to create a cross-format package that would also work with LuaTeX.

Users who desire to specify maths alphabets only from various fonts may wish to use Andrew Moschou’s mathspec package instead.

## 2 Unicode maths font setup

In the ideal case, a single unicode font will contain all maths glyphs we need. The file unicode-math-table.tex (based on Barbara Beeton’s stix table) provides the mapping between unicode maths glyphs and macro names (all 3298 — or however many — of them!). A single command

```
\setmathfont[⟨font features⟩]{⟨font name⟩}
```

implements this for every every symbol and alphabetic variant. That means  $x$  to  $\mathcal{x}$ ,  $\xi$  to  $\mathcal{X}$ ,  $\leq$  to  $\mathcal{L}$ , etc.,  $\mathcal{H}$  to  $\mathcal{H}$  and so on, all for unicode glyphs within a single font.

This package deals well with unicode characters for maths input. This includes using literal Greek letters in formulae, resolving to upright or italic depending on preference.

Finally, maths versions must also be provided for. While I guess version selection in L<sup>A</sup>TeX will remain the same, the specification for choosing the version fonts will probably be an optional argument:

```
\setmathfont[Version=Bold,⟨font features⟩]{⟨font name⟩}
```

This has not been implemented yet.

Instances above of

```
[⟨font features⟩]{⟨font name⟩}
```

follow from my fontspec package, and therefore any additional  $\langle font features \rangle$  specific to maths fonts will hook into fontspec’s methods.

## 2.1 Using multiple fonts

There will probably be few cases where a single unicode maths font suffices (simply due to glyph coverage). The upcoming `stix` font comes to mind as a possible exception. It will therefore be necessary to delegate specific unicode ranges of glyphs to separate fonts:

```
\setmathfont[Range=<unicode range>,<font features>]{<font name>}
```

where *<unicode range>* is a comma-separated list of unicode slots and ranges such as `{27D0-27EB,27FF,295B-297F}`. You may also use the macro for accessing the glyph, such as `\`, or whole collection of symbols with the same math type, such as `\mathopen`. (Only numerical slots, however, can be used in proper ranges.) This interface still requires some thought.

Not yet implemented: preset names ranges could be used in the range spec., such as `MiscMathSymbolsA`, with such ranges based on unicode chunks. The amount of optimisation required here to achieve acceptable performance has yet to be determined. Techniques such as saving out unicode subsets based on *<unicode range>* data to be `\input` in the next  $\text{\LaTeX}$  run are a possibility, but at this stage, performance without such measures seems acceptable.

## 2.2 Script and scriptscript fonts/features

Cambria Math uses OpenType font features to activate smaller optical sizes for `scriptsize` and `scriptscriptsize` symbols (the *B* and *C*, respectively, in  $A_{B_C}$ ). Other fonts will possibly use entirely separate fonts.

Not yet implemented: Both of these options must be taken into account. I hope this will be mostly automatic from the users' points of view. The `+ssty` feature can be detected and applied automatically, and appropriate optical size information embedded in the fonts will ensure this latter case. Fine tuning should be possible automatically with `fontspec` options. We might have to wait until `MnMath`, for example, before we really know.

## 3 Maths input

$\text{\XeTeX}$ 's unicode support allows maths input through two methods. Like classical  $\text{\TeX}$ , macros such as `\alpha`, `\sum`, `\pm`, `\leq`, and so on, provide verbose access to the entire repertoire of characters defined by unicode. The literal characters themselves may be used instead, for more readable input files.

### 3.1 Math 'style'

Classically,  $\text{\TeX}$  uses italic lowercase Greek letters and *upright* uppercase Greek letters for variables in mathematics. This is contrary to the ISO standards of using italic forms for both upper- and lowercase. Furthermore, the French (contrary

Table 1: Effects of the `math-style` package option.

Package option	Example	
	Latin	Greek
<code>math-style=ISO</code>	$(a, z, B, X)$	$(\alpha, \beta, \Gamma, \Xi)$
<code>math-style=TeX</code>	$(a, z, B, X)$	$(\alpha, \beta, \Gamma, \Xi)$
<code>math-style=French</code>	$(a, z, B, X)$	$(\alpha, \beta, \Gamma, \Xi)$

again, *quelle surprise*) have been known to use upright uppercase *Latin* letters as well as upright upper- and lowercase Greek.

The `unicode-math` package accommodates these possibilities with an interface heavily inspired by Walter Schmidt’s `lucimatx` package: a package option `math-style` that takes one of three arguments: `TeX`, `ISO`, or `French` (case *in*-sensitive).

The philosophy behind the interface to the mathematical alphabet symbols lies in L<sup>A</sup>T<sub>E</sub>X’s attempt of separating content and formatting. Because input source text may come from a variety of places, the upright and ‘mathematical’ italic Latin and Greek alphabets are *unified* from the point of view of having a specified meaning in the source text. That is, to get a mathematical ‘*x*’, either the `ascii` (‘keyboard’) letter `x` may be typed, or the actual unicode character may be used. Similarly for Greek letters. The upright or italic forms are then chosen based on the `math-style` package option.

If glyphs are desired that do not map as per the package option (for example, an upright ‘*g*’ is desired but typing `$g$` yields ‘*g*’), *markup* is required to specify this; to follow from the example: `\mathup{g}`. Maths alphabets commands such as `\mathup` are detailed later.

**Alternative interface** However, some users may not like this convention. For them, an upright `x` is an upright ‘*x*’ and that’s that. (This will be the case when obtaining source text from copy/pasting PDF or Microsoft Word documents, for example.) For these users, the `literal` option to `math-style` will effect this behaviour.

The `math-style` options’ effects are shown in brief in table 1.

### 3.2 Bold style

Similar as in the previous section, ISO standards differ somewhat to T<sub>E</sub>X’s conventions (and classical typesetting) for ‘boldness’ in mathematics. In the past, it has been customary to use bold *upright* letters to denote things like vectors and matrices. For example,  $\mathbf{M} = (M_x, M_y, M_z)$ . Presumably, this was due to the relatively

Table 2: Effects of the bold-style package option.

Package option	Example	
	Latin	Greek
<code>bold-style=ISO</code>	$(\mathbf{a}, \mathbf{z}, \mathbf{B}, \mathbf{X})$	$(\boldsymbol{\alpha}, \boldsymbol{\beta}, \boldsymbol{\Gamma}, \boldsymbol{\Xi})$
<code>bold-style=TeX</code>	$(\mathbf{a}, \mathbf{z}, \mathbf{B}, \mathbf{X})$	$(\boldsymbol{\alpha}, \boldsymbol{\beta}, \boldsymbol{\Gamma}, \boldsymbol{\Xi})$
<code>bold-style=French</code>	$(\mathbf{a}, \mathbf{z}, \mathbf{B}, \mathbf{X})$	$(\boldsymbol{\alpha}, \boldsymbol{\beta}, \boldsymbol{\Gamma}, \boldsymbol{\Xi})$

scarcity of bold italic fonts in the pre-digital typesetting era. It has been suggested that *italic* bold symbols are used nowadays instead.

Bold Greek letters have simply been bold variant glyphs of their regular weight, as in  $\boldsymbol{\xi} = (\xi_r, \xi_\varphi, \xi_\theta)$ . Confusingly, the syntax in  $\text{\LaTeX}$  has been different for these two examples: `\mathbf{bf}` in the former (`'M'`), and `\bm` (or `\boldsymbol`, deprecated) in the latter (`'ξ'`).

In unicode-math, the `\mathbf{bf}` command works directly with both Greek and Latin maths alphabet characters and depending on package option either switches to upright for Latin letters (`bold-style=TeX`) as well or keeps them italic (`bold-style=ISO`).

To match the package options for non-bold characters, for `bold-style=French` all bold characters are upright, and `bold-style=literal` does not change the upright/italic shape of the letter.

Upright and italic bold mathematical letters input as direct unicode characters are normalised with the same rules. For example, with `bold-style=TeX`, a literal bold italic latin character will be typeset upright.

Note that `bold-style` is independent of `math-style`, although if the former is not specified then sensible defaults are chosen based on the latter.

The `bold-style` options' effects are shown in brief in table 2.

### 3.3 Sans serif style

Unicode contains upright and italic, medium and bold mathematical alphabet characters. These may be explicitly selected with the `\mathsfup`, `\mathsfit`, `\mathbf{sfup}`, and `\mathbf{sfit}` commands discussed in section §3.4.

How should the generic `\mathsf` behave? Unlike bold, sans serif is used much more sparingly in mathematics. I've seen recommendations to typeset tensors in sans serif italic or sans serif italic bold (e.g., examples in the `isomath` and `mattens` packages). But  $\text{\LaTeX}$ 's `\mathsf` is *upright* sans serif.

Therefore I reluctantly add the package options `[sans-style=TeX]` and `[sans-style=ISO]` to control the behaviour of `\mathsf`. The `TeX` style sets up the command to use the seemingly-useless upright sans serif, including Greek; the `ISO` style switches to using italic in both Latin and Greek alphabets. In other words,

this option simply changes the meaning of `\mathsf` to either `\mathsfup` or `\mathsf{fit}`, respectively. Please let me know if more granular control is necessary here.

There is also a `[sans-style=literal]` setting, set automatically with `[math-style=literal]`, which retains the uprightness of the input characters used when selecting the sans serif output.

### 3.3.1 What about bold sans serif?

While you might want your bold upright and your sans serif italic, I don't believe you'd also want your bold sans serif upright (or all vice versa, if that's even conceivable). Therefore, bold sans serif follows from the setting for sans serif; it is completely independent of the setting for bold.

In other words, `\mathbfsf` is `\mathbfsfup` or `\mathbfsfit` based on `[sans-style=TeX]` or `[sans-style=ISO]`, respectively. And `[sans-style=literal]` causes `\mathbfsf` to retain the same italic or upright shape as the input, and turns it bold sans serif.

Note well! There is no medium-weight sans serif Greek alphabet in unicode; therefore, `\mathsf{\alpha}` does not make sense (simply produces 'α') while `\mathbfsf{\alpha}` gives 'α'.

## 3.4 All (the rest) of the mathematical alphabets

Unicode contains separate codepoints for most if not all variations of alphabet shape one may wish to use in mathematical notation. The complete list is shown in table 3. Some of these have been covered in the previous sections.

At present, the math font switching commands do not nest; therefore if you want sans serif bold, you must write `\mathsfbf{...}` rather than `\mathbf{\mathsf{...}}`. This may change in the future.

## 3.5 Miscellanea

### 3.5.1 Nabla

The symbol  $\nabla$  comes in the six forms shown in table 4. We want an individual option to specify whether we want upright or italic nabla by default (when either upright or italic nabla is used in the source).  $\text{\TeX}$  classically uses an upright nabla, but ISO standards differ (I think). The package options `nabla=upright` and `nabla=italic` switch between the two choices. This is then inherited through `\mathbf`; `\mathit` and `\mathup` can be used to force one way or the other.

`nabla=italic` is implicit when using `math-style=ISO` and `nabla=upright` follows both `math-style=TeX` and `math-style=French`.

Table 3: Mathematical alphabets defined in unicode. Black dots indicate an alphabet exists in the font specified; grey dots indicate shapes that should always be taken from the upright font even in the italic style.

Font				Alphabet		
Style	Shape	Series	Switch	Latin	Greek	Numerals
Serif	Upright	Normal	<code>\mathup</code>	•	•	•
		Bold	<code>\mathbfup</code>	•	•	•
	Italic	Normal	<code>\mathit</code>	•	•	•
		Bold	<code>\mathbfit</code>	•	•	•
Sans serif	Upright	Normal	<code>\mathsfup</code>	•		•
	Italic	Normal	<code>\mathsfit</code>	•		•
	Upright	Bold	<code>\mathsfbfup</code>	•	•	•
	Italic	Bold	<code>\mathsfbfit</code>	•	•	•
Typewriter	Upright	Normal	<code>\mathtt</code>	•		•
Double-struck	Upright	Normal	<code>\mathbb</code>	•		•
Script	Upright	Normal	<code>\mathscr</code>	•		
		Bold	<code>\matbfscr</code>	•		
Fraktur	Upright	Normal	<code>\mathfrak</code>	•		
		Bold	<code>\mathbffrac</code>	•		

Table 4: The various forms of nabla.

Description		Glyph
Upright	Serif	$\nabla$
	Bold serif	<b><math>\nabla</math></b>
	Bold sans	<b><math>\nabla</math></b>
Italic	Serif	$\nabla$
	Bold serif	<b><math>\nabla</math></b>
	Bold sans	<b><math>\nabla</math></b>

Table 5: The various forms of the partial differential. Note that in the fonts used to display these glyphs, the first upright partial is incorrectly shown in an italic style.

Description		Glyph
Regular	Upright	$\partial$
	Italic	$\partial$
Bold	Upright	<b><math>\partial</math></b>
	Italic	<b><math>\partial</math></b>
Sans bold	Upright	$\partial$
	Italic	$\partial$

### 3.5.2 Partial

The same applies to the symbols U+2202: PARTIAL DIFFERENTIAL and U+1D715: MATH ITALIC PARTIAL DIFFERENTIAL.

At time of writing, both the Cambria Math and STIX fonts display these two glyphs in the same italic style, but this is hopefully a bug that will be corrected in the future — the ‘plain’ partial differential should really have an upright shape.

Use the `partial=upright` or `partial=italic` package options to specify which one you would like. The default is (always, unless someone requests and argues otherwise) `partial=italic`.<sup>1</sup>

See table 5 for the variations on the partial differential symbol.

### 3.5.3 Epsilon and phi: $\epsilon$ vs. $\varepsilon$ and $\phi$ vs. $\varphi$

TeX defines `\epsilon` to look like  $\varepsilon$  and `\varepsilon` to look like  $\epsilon$ . The Unicode glyph directly after delta and before zeta is ‘epsilon’ and looks like  $\epsilon$ ; there is a subsequent variant of epsilon that looks like  $\varepsilon$ . This creates a problem. People who use unicode input won’t want their glyphs transforming; TeX users will be confused that what they think as ‘normal epsilon’ is actual the ‘variant epsilon’. And the same problem exists for ‘phi’.

We have a package option to control this behaviour. With `vargreek-shape=TeX`, `\phi` and `\epsilon` produce  $\phi$  and  $\epsilon$  and `\varphi` and `\varepsilon` produce  $\varphi$  and  $\varepsilon$ . With `vargreek-shape=unicode`, these symbols are swapped. Note, however, that unicode characters are not affected by this option. That is, no remapping occurs of the characters/glyphs, only the control sequences.

Unless `math-style=literal` is in effect, the default is to use `vargreek-shape=TeX`.

<sup>1</sup>A good argument would revolve around some international standards body recommending upright over italic. I just don’t have the time right now to look it up.



A	0	1	2	3	4	5	6	7	8	9	+	-	=	(	)	i	n	Z
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

Figure 1: The unicode superscripts supported as input characters. These are the literal glyphs from Charis SIL, not the output seen when used for maths input. The ‘A’ and ‘Z’ are to provide context for the size and location of the superscript glyphs.

U+3B5: GREEK SMALL LETTER EPSILON  
U+3F5: GREEK LUNATE EPSILON SYMBOL  
U+3C6: GREEK SMALL LETTER PHI  
U+3D5: GREEK SMALL LETTER SCRIPT PHI

### 3.5.4 Primes

Primes ( $x'$ ) may be input in several ways. You may use any combination of ascii straight quote ('), unicode prime (′), and `\prime`; when multiple primes occur next to each other, they chain together to form double, triple, or quadruple primes if the font contains pre-drawn glyphs. These may also be accessed with `\primedouble`, `\primetripel`, and `\primequadruple`.

If the font does not contain the pre-drawn glyphs or more than four primes are used, the single prime glyph is used multiple times with a negative kern to get the spacing right. There is no user interface to adjust this negative kern yet (because I haven’t decided what it should look like); if you need to, write something like this:

```
\ExplSyntaxOn
\muskip_gset:Nn \g_um_primekern_muskip { -\thinmuskip/2 }
\ExplSyntaxOff
```

### 3.5.5 Unicode subscripts and superscripts

You may, if you wish, use unicode subscripts and superscripts in your source document. For basic expressions, the use of these characters can make the input more readable. Adjacent sub- or super-scripts will be concatenated into a single expression.

The range of subscripts and superscripts supported by this package are shown in figures 1 and 2. Please request more if you think it is appropriate.

### 3.5.6 Colon ‘:’

The colon is one of the few confusing characters of unicode maths. In  $\TeX$ , `:` is defined as a colon with relation spacing: ‘ $a : b$ ’. While `\colon` is defined as a colon with punctuation spacing: ‘ $a:b$ ’.

A 0 1 2 3 4 5 6 7 8 9 + - = ( ) a e i o r u v x β γ ρ ϕ χ Z

Figure 2: The unicode subscripts supported as input characters. See note from figure 1.

Table 6: Slashes and backslashes.

Slot	Name	Glyph	Command
U+002F	SOLIDUS	/	\solidus
U+2044	FRACTION SLASH	/	\fracslash
U+2215	DIVISION SLASH	/	\slash
U+29F8	BIG SOLIDUS	/	\xsol
U+005C	REVERSE SOLIDUS	\	\backslash
U+2216	SET MINUS	\	\smallsetminus
U+29F5	REVERSE SOLIDUS OPERATOR	\	\setminus
U+29F9	BIG REVERSE SOLIDUS	\	\xbsol

In unicode, U+003A: COLON is defined as a punctuation symbol, while U+2236: RATIO is the colon-like symbol used in mathematics to denote ratios and other things.

This breaks the usual straightforward mapping from control sequence to unicode input character to (the same) unicode glyph.

To preserve input compatibility, we remap the ASCII input character ‘:’ to U+2236: RATIO. Typing a literal U+2236: RATIO char will result in the same output. If amsmath is loaded, then the definition of \colon is inherited from there (it looks like a punctuation colon with additional space around it). Otherwise, \colon is made to output a colon with \mathpunct spacing.

The package option [colon=literal] forces ASCII input ‘:’ to be printed as \mathcolon instead.

### 3.5.7 Slashes and backslashes

There are several slash-like symbols defined in unicode. These are shown in table 6. The ASCII slashes / and \ are useful as input characters but should not be used in the rendering of mathematics. (I think.)

In regular L<sup>A</sup>T<sub>E</sub>X we can write \left\slash...\right\backslash and so on and obtain extensible delimiter-like symbols. Not all of the unicode slashes are suitable for this (and do not have the font support to do it).

**Slash** Of U+2044: FRACTION SLASH, TR25 says that it is:

...used to build up simple fractions in running text...however parsers of mathematical texts should be prepared to handle fraction slash when it is received from other sources.

If encountered in the input stream, therefore, I believe it should be mapped to the meaning of U+2215: DIVISION SLASH. (Alas, see the note below.)

U+2215: DIVISION SLASH should be used when division is represented without a built-up fraction;  $\pi \approx 22/7$ , for example.

I do not know what U+29F8: BIG SOLIDUS is intended to be used for. It's a 'math operator' (like  $\Sigma$ ) so it falls outside the topic of discussion here.

**Backslash** MathML uses U+2216: SET MINUS like this:  $A \setminus B$ .<sup>2</sup> I think the STIX name for this glyph slot should just be `\setminus`.

Presumably, U+29F5: REVERSE SOLIDUS OPERATOR is intended to be used in a similar way, but it could also (perhaps?) be used to represent 'inverse division':  $\pi \approx 7 \backslash 22$ .<sup>3</sup>

Again, I don't know what U+29F9: BIG REVERSE SOLIDUS is for. But it's not too important at this stage.

**How to use all of these things** Unfortunately, font support for the above characters/glyphs is rather spotty. In Cambria Math, the only slash that grows (say when writing

$$\left[ \begin{array}{cc} a & b \\ c & d \end{array} \right] \bigg/ \left[ \begin{array}{cc} 1 & 1 \\ 1 & 0 \end{array} \right] )$$

is the FRACTION SLASH, which we just established above is sort of only supposed to be used in text.

And none of the backslashes stretch. Which leaves me in a bit of a pickle.  $\TeX$  has a stretchy backslash. Cambria Math does not. What will? And in which glyph slot? I give up, for now. This is an impossible problem.

All of the above characters are allowed to be used after `\left`, `\middle`, and `\right`. Only the font will know whether or not it will actually stretch, however. If you like you may redefine `\slash` and `\backslash` to fit your needs. Perhaps this will be a package option some day.

### 3.5.8 Normalising some input characters

I believe all variant forms should be used as legal input that is normalised to a consistent output glyph, because we want to be fault-tolerant in the input. Here are the duplicates:

---

<sup>2</sup>§4.4.5.11 :// . 3. / / 3/

<sup>3</sup>This is valid syntax in the Octave and Matlab programming languages, in which it means matrix inverse pre-multiplication. I.e.,  $A \backslash B = A^{-1}B$ .

U+251: LATIN SMALL LETTER ALPHA  
 U+25B: LATIN SMALL LETTER EPSILON  
 U+263: LATIN SMALL LETTER GAMMA  
 U+269: LATIN SMALL LETTER IOTA  
 U+278: LATIN SMALL LETTER PHI  
 U+28A: LATIN SMALL LETTER UPSILON  
 U+190: LATIN CAPITAL LETTER EPSILON  
 U+194: LATIN CAPITAL LETTER GAMMA  
 U+196: LATIN CAPITAL LETTER IOTA  
 U+1B1: LATIN CAPITAL LETTER UPSILON

(Not yet implemented.)

## File I

# The unicode-math package

This is the package.

```

1 \ProvidesPackage{unicode-math}
2 [2009/09/29 v0.4 Unicode maths in XeLaTeX]

```

## 4 Things we need

### Packages

```

3 \RequirePackage{expl3}[2009/08/12]
4 \RequirePackage{xparse}[2009/08/31]
5 \RequirePackage{fontspec}
    Start using LATEX3 — finally!
6 \ExplSyntaxOn

```

### Counters and conditionals

```

7 \newcounter{um@fam}
8 \newif\if@um@fontspec@feature
9 \newif\if@um@ot@math@

```

For math-style:

```

10 \newif\if@um@literal
11 \newif\if@um@upGreek
12 \newif\if@um@upgreek

```

```

13 \newif\if@um@upLatin
14 \newif\if@um@uplatin

```

For bold-style:

```

15 \newif\if@um@bfliteral
16 \newif\if@um@bfupGreek
17 \newif\if@um@bfupgreek
18 \newif\if@um@bfupLatin
19 \newif\if@um@bfuplatin

```

For nabla:

```

20 \newif\if@um@upNabla
21 \newif\if@um@uppartial
22 \bool_new:N \g_um_texgreek_bool

```

#### 4.0.9 Alphabet unicode positions

Before we begin, let's define the positions of the various unicode alphabets so that our code is a little more readable.<sup>4</sup>

```

23 \def\um@usv@num{\0}
24 \def\um@usv@upLatin{\A}
25 \def\um@usv@uplatin{\a}
26 \def\um@usv@upGreek{"391}
27 \def\um@usv@upgreek{"3B1}
28 \def\um@usv@itLatin{"1D434}
29 \def\um@usv@itlatin{"1D44E}
30 \def\um@usv@itGreek{"1D6E2}
31 \def\um@usv@itgreek{"1D6FC}
32 \def\um@usv@bbnum{"1D7D8}
33 \def\um@usv@bbLatin{"1D538}
34 \def\um@usv@bblatin{"1D552}
35 \def\um@usv@scrLatin{"1D49C}
36 \def\um@usv@scrlatin{"1D4B6}
37 \def\um@usv@frakLatin{"1D504}
38 \def\um@usv@fraklatin{"1D51E}
39 \def\um@usv@sfnum{"1D7E2}
40 \def\um@usv@sfupLatin{"1D5A0}
41 \def\um@usv@sfLatin {"1D5A0}
42 \def\um@usv@sfuplatin{"1D5BA}
43 \def\um@usv@sfitLatin{"1D608}
44 \def\um@usv@sfitlatin{"1D622}
45 \def\um@usv@ttnum{"1D7F6}
46 \def\um@usv@ttLatin{"1D670}
47 \def\um@usv@ttlLatin{"1D68A}

```

**Bold:**

---

<sup>4</sup>'u.s.v.' stands for 'unicode scalar value'.

```

48 \def\um@usv@bfnum{"1D7CE}
49 \def\um@usv@bfupLatin{"1D400}
50 \def\um@usv@bfLatin {"1D400}
51 \def\um@usv@bfuplatin{"1D41A}
52 \def\um@usv@bfupGreek{"1D6A8}
53 \def\um@usv@bfupgreek{"1D6C2}
54 \def\um@usv@bfitLatin{"1D468}
55 \def\um@usv@bfitlatin{"1D482}
56 \def\um@usv@bfitGreek{"1D71C}
57 \def\um@usv@bfitgreek{"1D736}
58 \def\um@usv@bffrakLatin{"1D56C}
59 \def\um@usv@bffraklatin{"1D586}
60 \def\um@usv@bfscrLatin{"1D4D0}
61 \def\um@usv@bfscrlatin{"1D4EA}
62 \def\um@usv@bfsfnum{"1D7EC}
63 \def\um@usv@bfsfupLatin{"1D5D4}
64 \def\um@usv@bfsfLatin {"1D5D4}
65 \def\um@usv@bfsfuplatin{"1D5EE}
66 \def\um@usv@bfsfupGreek{"1D756}
67 \def\um@usv@bfsfupgreek{"1D770}
68 \def\um@usv@bfsfitLatin{"1D63C}
69 \def\um@usv@bfsfitlatin{"1D656}
70 \def\um@usv@bfsfitGreek{"1D790}
71 \def\um@usv@bfsfitgreek{"1D7AA}

```

Greek variants:

```

72 \def\um@usv@varTheta{"3F4}
73 \def\um@usv@Digamma{"3DC}
74 \def\um@usv@varepsilon{"3F5}
75 \def\um@usv@vartheta{"3D1}
76 \def\um@usv@varkappa{"3F0}
77 \def\um@usv@varphi{"3D5}
78 \def\um@usv@varrho{"3F1}
79 \def\um@usv@varpi{"3D6}
80 \def\um@usv@digamma{"3DD}

```

**Bold:**

```

81 \def\um@usv@bfvarTheta{"1D6B9}
82 \def\um@usv@bfDigamma{"1D7CA}
83 \def\um@usv@bfvarepsilon{"1D6DC}
84 \def\um@usv@bfvartheta{"1D6DD}
85 \def\um@usv@bfvarkappa{"1D6DE}
86 \def\um@usv@bfvarphi{"1D6DF}
87 \def\um@usv@bfvarrho{"1D6E0}
88 \def\um@usv@bfvarpi{"1D6E1}
89 \def\um@usv@bfdigamma{"1D7CB}

```

*Italic Greek variants:*

```

90 \def\um@usv@ith{"210E}
91 \def\um@usv@itvarTheta{"1D6F3}
92 \def\um@usv@itvarepsilon{"1D716}
93 \def\um@usv@itvartheta{"1D717}
94 \def\um@usv@itvarkappa{"1D718}
95 \def\um@usv@itvarphi{"1D719}
96 \def\um@usv@itvarrho{"1D71A}
97 \def\um@usv@itvarpi{"1D71B}

```

**Bold:**

```

98 \def\um@usv@bfuph{"1D421}
99 \def\um@usv@bfith{"1D489}
100 \def\um@usv@bfitvarTheta{"1D72D}
101 \def\um@usv@bfitvarepsilon{"1D750}
102 \def\um@usv@bfitvartheta{"1D751}
103 \def\um@usv@bfitvarkappa{"1D752}
104 \def\um@usv@bfitvarphi{"1D753}
105 \def\um@usv@bfitvarrho{"1D754}
106 \def\um@usv@bfitvarpi{"1D755}

```

**Nabla:**

```

107 \def\um@usv@Nabla{"2207}
108 \def\um@usv@itNabla{"1D6FB}
109 \def\um@usv@bfNabla{"1D6C1}
110 \def\um@usv@bfitNabla{"1D735}
111 \def\um@usv@bfsfNabla{"1D76F}
112 \def\um@usv@bfsfitNabla{"1D7A9}

```

**Partial:**

```

113 \def\um@usv@partial{"2202}
114 \def\um@usv@itpartial{"1D715}
115 \def\um@usv@bfpartial{"1D6DB}
116 \def\um@usv@bfitpartial{"1D74F}
117 \def\um@usv@bfsfpartial{"1D789}
118 \def\um@usv@bfsfitpartial{"1D7C3}

```

## 4.1 Package options

xkeyval's package support is used here.

### **math-style**

```

119 \define@choicekey*{unicode-math.sty}
120   {math-style}[\@tempa\@tempb]{iso,tex,french,literal}{
121   \ifcase\@tempb\relax
122     \um@upGreekfalse
123     \um@upgreekfalse
124     \um@upLatinfalse

```

```

125 \um@uplatinfalse
126 \um@bfupGreekfalse
127 \um@bfupgreekfalse
128 \um@uppartialfalse
129 \um@bfupLatinfalse
130 \um@bfuplatinfalse
131 \um@upNablafalse
132 \bool_set_false:N \g_um_upsans_bool
133 \bool_set_false:N \g_um_texgreek_bool
134 \or
135 \um@upGreektrue
136 \um@upgreekfalse
137 \um@upLatinfalse
138 \um@uplatinfalse
139 \um@bfupGreektrue
140 \um@bfupgreekfalse
141 \um@uppartialfalse
142 \um@bfupLatintrue
143 \um@bfuplatintrue
144 \um@upNablatrue
145 \bool_set_true:N \g_um_upsans_bool
146 \bool_set_true:N \g_um_texgreek_bool
147 \or
148 \um@upGreektrue
149 \um@upgreektrue
150 \um@upLatintrue
151 \um@uplatinfalse
152 \um@bfupGreektrue
153 \um@bfupgreektrue
154 \um@uppartialtrue
155 \um@bfupLatintrue
156 \um@bfuplatintrue
157 \um@upNablatrue
158 \bool_set_true:N \g_um_upsans_bool
159 \bool_set_false:N \g_um_texgreek_bool
160 \or
161 \um@literaltrue
162 \um@bfliteraltrue
163 \bool_set_true:N \g_um_sfliteral_bool
164 \bool_set_false:N \g_um_texgreek_bool
165 \fi
166 }

```

### **bold-style**

```

167 \define@choicekey*{unicode-math.sty}{bold-style}[\@tempa\@tempb]{iso,tex,french,literal}{
168 \ifcase\@tempb\relax

```



```

169 \um@bfupGreekfalse
170 \um@bfupgreekfalse
171 \um@uppartialfalse
172 \um@bfupLatinfalse
173 \um@bfuplatinfalse
174 \or
175 \um@bfupGreektrue
176 \um@bfupgreekfalse
177 \um@uppartialfalse
178 \um@bfupLatintrue
179 \um@bfuplatintrue
180 \or
181 \um@bfupGreektrue
182 \um@bfupgreektrue
183 \um@uppartialtrue
184 \um@bfupLatintrue
185 \um@bfuplatintrue
186 \or
187 \um@bfliteraltrue
188 \fi
189 }

```

### **sans-style**

```

190 \bool_new:N \g_um_upsans_bool
191 \bool_new:N \g_um_sf literal_bool
192 \define@choicekey*{unicode-math.sty}
193 {sans-style}[\@tempa\@tempb]{iso,tex,literal}{
194 \ifcase\@tempb\relax
195 \bool_set_false:N \g_um_upsans_bool
196 \or
197 \bool_set_true:N \g_um_upsans_bool
198 \or
199 \bool_set_true:N \g_um_sf literal_bool
200 \fi
201 }

```

### **Symbol obliqueness**

```

202 \define@choicekey*{unicode-math.sty}{nabla}[\@tempa\@tempb]{upright,italic}{
203 \ifcase\@tempb\relax
204 \um@upNablatrue
205 \or
206 \um@upNablafalse
207 \fi
208 }
209 \cs_set:Nn \um_setup_nabla: {

```

```

210 \if@um@upNabla
211   \tl_set:Nn \um_Nabla_up_or_it_usv { \um@usv@Nabla }
212   \tl_set:Nn \um_bfNabla_up_or_it_usv { \um@usv@bfNabla }
213   \tl_set:Nn \um_bfsfNabla_up_or_it_usv { \um@usv@bfsfNabla }
214 \else
215   \tl_set:Nn \um_Nabla_up_or_it_usv { \um@usv@itNabla }
216   \tl_set:Nn \um_bfNabla_up_or_it_usv { \um@usv@bfitNabla }
217   \tl_set:Nn \um_bfsfNabla_up_or_it_usv { \um@usv@bfsfitNabla }
218 \fi
219 }

220 \define@choicekey*{unicode-math.sty}{partial}[\@tempa\@tempb]{upright,italic}{
221   \ifcase\@tempb\relax
222     \um@uppartialtrue
223   \or
224     \um@uppartialfalse
225   \fi
226 }
227 \cs_set:Nn \um_setup_partial: {
228   \if@um@uppartial
229     \tl_set:Nn \um_partial_up_or_it_usv { \um@usv@partial }
230     \tl_set:Nn \um_bfpartial_up_or_it_usv { \um@usv@bfpartial }
231     \tl_set:Nn \um_bfsfpartial_up_or_it_usv { \um@usv@bfsfpartial }
232   \else
233     \tl_set:Nn \um_partial_up_or_it_usv { \um@usv@itpartial }
234     \tl_set:Nn \um_bfpartial_up_or_it_usv { \um@usv@bfitpartial }
235     \tl_set:Nn \um_bfsfpartial_up_or_it_usv { \um@usv@bfsfitpartial }
236   \fi
237 }

```

### Epsilon and phi shapes

```

238 \define@choicekey*{unicode-math.sty}{vargreek-shape}[\@tempa\@tempb]{unicode,TeX}{
239   \ifcase\@tempb\relax
240     \bool_set_false:N \g_um_texgreek_bool
241   \or
242     \bool_set_true:N \g_um_texgreek_bool
243   \fi
244 }

```

### Colon style

```

245 \bool_new:N \g_um_literal_colon_bool
246 \define@choicekey*{unicode-math.sty}{colon}[\@tempa\@tempb]{literal,TeX}{
247   \ifcase\@tempb\relax
248     \bool_set_true:N \g_um_literal_colon_bool
249   \or
250     \bool_set_false:N \g_um_literal_colon_bool

```

```

251 \fi
252 }
253 \ExecuteOptionsX{math-style=TeX}
254 \ProcessOptionsX

```

## 4.2 Overcoming \@onlypreamble

The requirement of only setting up the maths fonts in the preamble is now removed. The following list might be overly ambitious.

```

255 \tl_map_inline:nn {
256 \new@mathgroup
257 \cdp@list
258 \cdp@elt
259 \DeclareMathSizes
260 \@DeclareMathSizes
261 \newmathalphabet
262 \newmathalphabet@@
263 \newmathalphabet@@@
264 \DeclareMathVersion
265 \define@mathalphabet
266 \define@mathgroup
267 \addtoversion
268 \version@list
269 \version@elt
270 \alpha@list
271 \alpha@elt
272 \restore@mathversion
273 \init@restore@version
274 \dorestore@version
275 \process@table
276 \new@mathversion
277 \DeclareSymbolFont
278 \group@list
279 \group@elt
280 \new@symbolfont
281 \SetSymbolFont
282 \SetSymbolFont@
283 \get@cdp
284 \DeclareMathAlphabet
285 \new@mathalphabet
286 \SetMathAlphabet
287 \SetMathAlphabet@
288 \DeclareMathAccent
289 \set@mathaccent
290 \DeclareMathSymbol
291 \set@mathchar

```

```

292 \set@mathsymbol
293 \DeclareMathDelimiter
294 \@xxDeclareMathDelimiter
295 \@DeclareMathDelimiter
296 \@xDeclareMathDelimiter
297 \set@mathdelimiter
298 \set@@mathdelimiter
299 \DeclareMathRadical
300 \mathchar@type
301 \DeclareSymbolFontAlphabet
302 \DeclareSymbolFontAlphabet@
303 }{
304 \tl_remove_in:Nn \@preamblecmds {\do#1}
305 }

```

### 4.3 Other things

`\um@fontdimen@percent` #1 : Font dimen number

`\fontdimens` 10, 11, and 65 aren't actually dimensions, they're percentage values given in units of sp. This macro takes a font dimension number and outputs the decimal value of the associated parameter.

---

0.73  
0.60  
0.65

---

```

\font\tmpfont="Cambria Math"
\um@fontdimen@percent{10}{\tmpfont}\
\um@fontdimen@percent{11}{\tmpfont}\
\um@fontdimen@percent{65}{\tmpfont}

```

---

```

306 \def\um@fontdimen@percent#1#2{
307   0.\strip@pt\dimexpr\fontdimen#1#2 *65536\relax
308 }

```

`\um@scaled@apply` #1 : A math style

#2 : Macro that takes a non-delimited length argument (like `\kern`)

#3 : Length control sequence to be scaled according to the math style

This macro is used to scale the lengths reported by `\fontdimen` according to the scale factor for script- and scriptscript-size objects.

```

309 \def\um@scaled@apply#1#2#3{
310   \ifx#1\scriptstyle
311     #2\um@fontdimen@percent{10}\um@font#3
312   \else
313     \ifx#1\scriptscriptstyle
314       #2\um@fontdimen@percent{11}\um@font#3
315     \else
316       #2#3%
317     \fi
318   \fi

```

319 }

## 5 Fundamentals

### 5.1 Enlarging the number of maths families

To start with, we've got a power of two as many `\fams` as before. So (from `ltxssbas.dtx`) we want to redefine

```
320 \def\new@mathgroup{\alloc@8\mathgroup\chardef\@cc1vi}  
321 \let\newfam\new@mathgroup
```

This is sufficient for L<sup>A</sup>T<sub>E</sub>X's `\DeclareSymbolFont`-type commands to be able to define 256 named maths fonts. Now we need a new `\DeclareMathSymbol`.

### 5.2 `\DeclareMathSymbol` for unicode ranges

This command is a bit funny at the moment; it doesn't define the actual macro for almost all of the symbols passed to it, but it does assign the `\XeTeXmathchar`.

```
\um@mathsymbol #1 : Symbol, e.g., \alpha  
                #2 : Type, e.g., \mathalpha  
                #3 : Math font name, e.g., operators  
                #4 : Slot, e.g., "221E  
322 \def \um@mathsymbol#1#2#3#4{  
323   \expandafter\um@set@mathsymbol\csname sym#3\endcsname#1#2{#4}}
```

The final macros that actually define the maths symbol with X<sub>Ǝ</sub>T<sub>E</sub>X primitives.

```
\um@set@mathsymbol #1 : Symbol font number  
                   #2 : Symbol macro, e.g., \alpha  
                   #3 : Type, e.g., \mathalpha  
                   #4 : Slot, e.g., "221E
```

If the symbol definition is for a macro. There are a bunch of tests to perform to process the various characters.

```
324 \def\um@set@mathsymbol#1#2#3#4{
```

**Operators** In the examples following, say we're defining for the symbol `\sum`( $\Sigma$ ).

```
325 \ifx\mathop#3\relax
```

In order for literal unicode characters to be used in the source and still have the correct limits behaviour, big operators are made math-active.

The active math char is defined to expand to the macro `\sumop`.

```
326   \begingroup  
327   \char_make_active:n {#4}
```

```

328     \global\mathcode#4="8000\relax
329     \um@scanactivedef #4 \@nil { \csname\cs_to_str:N #2 op\endcsname }
330 \endgroup

```

Some of these require a `\nolimits` suffix. This is controlled by the `\um@nolimits` macro, which contains a list of such characters. This list is checked dynamically because we're not interested in efficiency. Or something. This allows the list to be updated in the middle of a document.

Declare the plain old `\mathchardef` for the control sequence `\sum@sym`.

```

331 \expandafter\global\expandafter\XeTeXmathchardef
332 \csname\string#2@sym\endcsname
333 =" \mathchar@type#3 #1 #4\relax

```

Now define `\sumop` as `\sum@sym`, followed by `\nolimits` if necessary.

```

334 \cs_gset:cpn { \cs_to_str:N #2 op } {
335   \csname\string#2@sym\endcsname
336   \expandafter\in@\expandafter#2\expandafter{\um@nolimits}
337   \ifin@
338     \expandafter\nolimits
339   \fi
340 }

```

Don't forget that the actual `\sum` macro is simply defined in terms of the literal unicode symbol!

```

341 \else

```

**Radicals** Needs to be before the delimiters because the radical is, for some reason, `\mathopen`.

```

342 \expandafter\in@\expandafter#2\expandafter{\um@radicals,}
343 \ifin@
344 \cs_gset:cpn {\cs_to_str:N #2 sign} { \XeTeXradical #1 #4 \relax }
345 \else

```

**Delimiters** TODO: sort out which of these three declarations are necessary! (Definitely the first, to work with `\left/\right`.)

```

346 \ifx\mathopen#3\relax
347   \cs_gset:Npn #2 {\XeTeXdelimiter "\mathchar@type#3 #1 #4\relax}
348   \global\XeTeXdelcode#4=#1 #4\relax
349   \global\XeTeXmathcode#4="\mathchar@type#3 #1 #4\relax
350 \else
351   \ifx\mathclose#3\relax
352     \cs_gset:Npn #2 {\XeTeXdelimiter "\mathchar@type#3 #1 #4\relax}
353     \global\XeTeXdelcode#4=#1 #4\relax
354     \global\XeTeXmathcode#4="\mathchar@type#3 #1 #4\relax
355   \else

```

## Accents

```

356         \ifx\mathaccent#3\relax
357         \cs_gset:Npx #2 {\XeTeXmathaccent "\mathchar@type#3 #1 #4\relax}
358         \else

```

And finally, the general case. We define the unicode mathcode for the character. The macro is defined generically in terms of the unicode character.

```

359         \global\XeTeXmathcode#4="\mathchar@type#3 #1 #4\relax
360     \fi
361 \fi
362 \fi
363 \fi
364 \fi
365 }

```

`\um_set_mathcode:nnnn` [For later] or if it's for a character code (just a wrapper around the primitive). Note that this declaration *isn't* global so that it can be constrained by grouping inside math alphabet switches.

```

366 \cs_set:Nn \um_set_mathcode:nnnn {
367   \XeTeXmathcode#1="\mathchar@type#2 \csname sym#3\endcsname #4\relax
368 }

```

## 5.3 The main `\setmathfont` macro

Using a Range including large character sets such as `\mathrel`, `\mathalpha`, *etc.*, is *very slow*! I hope to improve the performance somehow.

`\setmathfont` [#1]: font features  
#2 : font name

```

369 \DeclareDocumentCommand \setmathfont { O{} m } {

```

- Erase any conception  $\text{\LaTeX}$  has of previously defined math symbol fonts; this allows `\DeclareSymbolFont` at any point in the document.

```

370     \let\glb@currsize\relax

```

- To start with, assume we're defining the font for every math symbol character.

```

371     \let\um@char@range\@empty
372     \let\um@char@num@range\@empty

```

- Tell fontspec that maths font features are actually allowed.

```

373     \@um@fontspec@featuretrue

```

- Grab the current size information (is this robust enough? Maybe it should be preceded by `\normalsize`).

```
374 \csname S@\f@size\endcsname
```

- Set the name of the math version being defined. (obviously more needs to be done here!)

```
375 \def\um@mversion{normal}
376 \DeclareMathVersion{\um@mversion}
```

Define default font features for the script and scriptscript font. (This needs to be generalised so users can override it.)

```
377 \tl_set:Nn \l_um_script_features_tl {ScriptStyle}
378 \tl_set:Nn \l_um_sscript_features_tl {ScriptScriptStyle}
379 \tl_set:Nn \l_um_script_font_tl      {#2}
380 \tl_set:Nn \l_um_sscript_font_tl    {#2}
```

Use `fontspec` to select a font to use. The macro `\S@{size}` contains the definitions of the sizes used for maths letters, subscripts and subsubscripts in `\tf@size`, `\sf@size`, and `\ssf@size`, respectively.

```
381 \setkeys*[um]{options}{#1}
382 \edef\@tempa{\noexpand\zf@fontspec{
383     Script = Math,
384     SizeFeatures = {
385         {Size = \tf@size-} ,
386         {Size = \sf@size-\tf@size ,
387         Font = \l_um_script_font_tl ,
388         \l_um_script_features_tl
389         } ,
390         {Size = -\sf@size ,
391         Font = \l_um_sscript_font_tl ,
392         \l_um_sscript_features_tl
393         }
394     },
395     \XKV@rm
396 }{#2}
397 }
398 \@tempa
```

Probably want to check there that we're not creating multiple symbol fonts with the same NFSS declaration.

Check for the correct number of `\fontdimens`:

```
399 \font\um@font="#2"\relax
400 %% \ifdim \dimexpr\fontdimen9\um@font*65536\relax =65pt\relax
401 %% \um@ot@math@true
402 %% \else
```



```

403 %% \PackageWarningNoLine{unicode-math}{
404 %%     The~ font~ '#2' ~is~ not~ a~ valid~ OpenType~ maths~ font.~
405 %%     Some~ maths~ features~ will~ not~ be~ available~ or~ behave~
406 %%     in~ a~ substandard~ manner
407 %% }
408 %% \fi

```

If we're defining the full unicode math repertoire, then we skip all the parsing processing needed if we're only defining a subset.

- Math symbols are defined with `\UnicodeMathSymbol`; see section §5.3.1 for the individual definitions

```

409 \ifx\um@char@range\@empty
410   \tl_set:Nn \um_symfont_tl {um@allsym}
411   \PackageInfo{unicode-math}{Defining~ the~ default~ maths~ font~ as~ '#2'}
412   \cs_set_eq:NN \UnicodeMathSymbol \um_process_symbol_noparse:nnnn
413   \cs_set_eq:NN \um_mathmap:Nnn \um_mathmap_noparse:Nnn
414   \cs_set_eq:NN \um_remap_symbol:nnn \um_remap_symbol_noparse:nnn
415   \cs_set_eq:NN \um_maybe_init_alphabet:n \um_init_alphabet:n
416 \else
417   \stepcounter{um@fam}
418   \tl_set:Nx \um_symfont_tl {um@fam\theum@fam}
419   \cs_set_eq:NN \UnicodeMathSymbol \um_process_symbol_parse:nnnn
420   \cs_set_eq:NN \um_mathmap:Nnn \um_mathmap_parse:Nnn
421   \cs_set_eq:NN \um_remap_symbol:nnn \um_remap_symbol_parse:nnn
422   \cs_set_eq:NN \um_maybe_init_alphabet:n \use_none:n
423 \fi

```

Now defined `\um_symfont_tl` as the L<sup>A</sup>T<sub>E</sub>X math font to access everything:

```

424 \DeclareSymbolFont{\um_symfont_tl}
425   {\encodingdefault}{\zf@family}{\mddefault}{\updefault}

```

And now we input every single maths char. See File II for the source to `unicode-math.tex` which is used to create `unicode-math-table.tex`.

```

426 \@input{unicode-math-table.tex}

```

Finally,

- Set up shapes for italic/upright or ordinary/var symbols as per package options.
- Remap symbols that don't take their natural mathcode
- Activate any symbols that need to be math-active
- Setup all symbols not covered by the table (mostly alphanumerics)
- Setup the maths alphabets (`\mathbf` etc.)

```

427 \um_setup_shapes:
428 \um_remap_symbols:
429 \um_setup_mathactives:
430 \um_setup_alphanum:
431 \um_setup_alphabets:

End of the \setmathfont macro.
432 }

```

```

433 \cs_new:Nn \um_setup_shapes: {
434   \um_setup_nabla:
435   \um_setup_partial:
436 }

```

### 5.3.1 Functions for setting up symbols with mathcodes

`\um_process_symbol_noparse:nnnn` If the Range font feature has been used, then only a subset of the unicode glyphs are to be defined. See section §6.3 for the code that enables this.

```

437 \cs_set:Nn \um_process_symbol_noparse:nnnn {
438   \um@mathsymbol{#2}{#3}{\um_symfont_tl}{#1}
439 }

440 \cs_set:Nn \um_process_symbol_parse:nnnn {
441   \um@parse@term{#1}{#2}{#3}{
442     \um_process_symbol_noparse:nnnn{#1}{#2}{#3}{#4}
443   }
444 }

```

`\um_remap_symbols:` This function is used to define the mathcodes for those chars which should be mapped to a different glyph than themselves.

```

\um_remap_symbol_noparse:nnn
\um_remap_symbol_parse:nnn
445 \cs_new:Nn \um_remap_symbols: {
446   \um_remap_symbol:nnn{'-}{\mathbin}{"02212}% hyphen to minus
447   \um_remap_symbol:nnn{'*}{\mathbin}{"02217}% text asterisk to "centred as-
      terisk"
448   \bool_if:NF \g_um_literal_colon_bool {
449     \um_remap_symbol:nnn{'\:}{\mathrel}{"02236}% colon to ratio (i.e., punct to rel)
450   }
451   \if@um@literal
452     \um_remap_symbol:nnn {\um@usv@Nabla}{\mathord}{\um@usv@Nabla}
453     \um_remap_symbol:nnn {\um@usv@itNabla}{\mathord}{\um@usv@itNabla}
454     \um_remap_symbol:nnn {\um@usv@partial}{\mathord}{\um@usv@partial}
455     \um_remap_symbol:nnn {\um@usv@itpartial}{\mathord}{\um@usv@itpartial}
456   \else
457     \um_remap_symbol:nnn {\um@usv@Nabla,\um@usv@itNabla}{\mathord}{\um_Nabla_up_or_it_usv}
458     \um_remap_symbol:nnn {\um@usv@partial,\um@usv@itpartial}{\mathord}{\um_partial_up_or_it_usv}
459   \fi

```

Some of these in the `bfliteral` block may be redundant, but that's okay:

```

460 \if@um@bfliteral
461   \um_remap_symbol:nnn {\um@usv@bfNabla} {\mathord}{\um@usv@bfNabla}
462   \um_remap_symbol:nnn {\um@usv@bfitNabla} {\mathord}{\um@usv@bfitNabla}
463   \um_remap_symbol:nnn {\um@usv@bfsfNabla} {\mathord}{\um@usv@bfsfNabla}
464   \um_remap_symbol:nnn {\um@usv@bfsfitNabla} {\mathord}{\um@usv@bfsfitNabla}
465   \um_remap_symbol:nnn {\um@usv@bfpartial} {\mathord}{\um@usv@bfpartial}
466   \um_remap_symbol:nnn {\um@usv@bfitpartial} {\mathord}{\um@usv@bfitpartial}
467   \um_remap_symbol:nnn {\um@usv@bfsfpartial} {\mathord}{\um@usv@bfsfpartial}
468   \um_remap_symbol:nnn {\um@usv@bfsfitpartial} {\mathord}{\um@usv@bfsfitpartial}
469 \else
470   \um_remap_symbol:nnn {\um@usv@bfNabla,\um@usv@bfitNabla} {\mathord}{\um@bfNabla_up_or_it_usv}
471   \um_remap_symbol:nnn {\um@usv@bfsfNabla,\um@usv@bfsfitNabla} {\mathord}{\um@bfsfNabla_up_or_it_usv}
472   \um_remap_symbol:nnn {\um@usv@bfpartial,\um@usv@bfitpartial} {\mathord}{\um@bfpartial_up_or_it_usv}
473   \um_remap_symbol:nnn {\um@usv@bfsfpartial,\um@usv@bfsfitpartial} {\mathord}{\um@bfsfpartial_up_or_it_usv}
474 \fi
475 }
```

Where `\um_remap_symbol:nnn` is defined to be one of these two, depending on the range setup:

```

476 \cs_new:Nn \um_remap_symbol_parse:nnn {
477   \um@parse@term {#3} {\@nil} {#2} {
478     \um_remap_symbol_noparse:nnn {#1} {#2} {#3}
479   }
480 }
481 \cs_new:Nn \um_remap_symbol_noparse:nnn {
482   \clist_map_inline:nn {#1} {
483     \um_set_mathcode:nnnn {##1} {#2} {\um_symfont_tl} {#3}
484   }
485 }
```

### 5.3.2 Active math characters

There are more math active chars later in the subscript/superscript section. But they don't need to be able to be typeset directly.

`\um_setup_mathactives:`

```

486 \cs_new:Nn \um_setup_mathactives: {
487   \um_make_mathactive:nNN {"2032} \primesingle \mathord
488 }
```

`\um_make_mathactive:nNN` Makes #1 a mathactive char, and gives cs #2 the meaning of mathchar #1 with class #3. You are responsible for giving active #1 a particular meaning!

```

489 \cs_new:Nn \um_make_mathactive:nNN {
490   \XeTeXmathchardef #2 = "\mathchar@type #3
491   \csname sym\um_symfont_tl\endcsname
```

```

492             #1 \scan_stop:
493 \XeTeXmathcodenum #1 = "1FFFFF \scan_stop:
494 }

```

### 5.3.3 Maths alphabets' character mapping

We want it to be convenient for users to actually type in maths. The ASCII Latin characters should be used for italic maths, and the text Greek characters should be used for upright/italic (depending on preference) Greek, if desired.

`\um_setup_alphanum:` All symbols input that aren't defined directly in `unicode-math-table`.

```

495 \cs_set:Nn \um_setup_alphanum: {
496   \ifx\um@char@range\@empty
497     \um_map_chars_numbers:nn {\um@usv@num}{\um@usv@num}

```

#### Normal weight

```

498   \if@um@literal
499     \um_setup_literals:
500   \else
501     \um_setup_Latin:
502     \um_setup_latin:
503     \um_setup_Greek:
504     \um_setup_greek:
505   \fi

```

#### Bold

```

506   \if@um@bfliteral
507     \um_setup_bf_literals:
508   \else
509     \if@um@bfupLatin
510       \um_map_chars_latin:nn {\um@usv@bfupLatin,\um@usv@bfitLatin}{\um@usv@bfupLatin}
511     \else
512       \um_map_chars_latin:nn {\um@usv@bfupLatin,\um@usv@bfitLatin}{\um@usv@bfitLatin}
513     \fi
514     \if@um@bfuplatin
515       \um_map_chars_latin:nn {\um@usv@bfuplatin,\um@usv@bfitlatin}{\um@usv@bfuplatin}
516     \else
517       \um_map_chars_latin:nn {\um@usv@bfuplatin,\um@usv@bfitlatin}{\um@usv@bfitlatin}
518     \fi
519     \if@um@bfupGreek
520       \um_map_chars_greek:nn {\um@usv@bfupGreek,\um@usv@bfitGreek}{\um@usv@bfupGreek}
521     \um_map_char:nn {\um@usv@bfvarTheta,\um@usv@bfitvarTheta}{\um@usv@bfvarTheta}
522     \else
523       \um_map_chars_greek:nn {\um@usv@bfupGreek,\um@usv@bfitGreek}{\um@usv@bfitGreek}
524     \um_map_char:nn {\um@usv@bfvarTheta,\um@usv@bfitvarTheta}{\um@usv@bfitvarTheta}

```

```

525 \fi
526 \if@um@bfupgreek
527 \um_map_chars_greek:nn {\um@usv@bfupgreek,\um@usv@bfitgreek}{\um@usv@bfupgreek}
528 \um_map_char:nn {\um@usv@bfvarepsilon,\um@usv@bfitvarepsilon}{\um@usv@bfvarepsilon}
529 \um_map_char:nn {\um@usv@bfvartheta,\um@usv@bfitvartheta}{\um@usv@bfvartheta}
530 \um_map_char:nn {\um@usv@bfvarkappa,\um@usv@bfitvarkappa}{\um@usv@bfvarkappa}
531 \um_map_char:nn {\um@usv@bfvarphi,\um@usv@bfitvarphi}{\um@usv@bfvarphi}
532 \um_map_char:nn {\um@usv@bfvarrho,\um@usv@bfitvarrho}{\um@usv@bfvarrho}
533 \um_map_char:nn {\um@usv@bfvarpi,\um@usv@bfitvarpi}{\um@usv@bfvarpi}
534 \else
535 \um_map_chars_greek:nn {\um@usv@bfupgreek,\um@usv@bfitgreek}{\um@usv@bfitgreek}
536 \um_map_char:nn {\um@usv@bfvarepsilon,\um@usv@bfitvarepsilon}{\um@usv@bfitvarepsilon}
537 \um_map_char:nn {\um@usv@bfvartheta,\um@usv@bfitvartheta}{\um@usv@bfitvartheta}
538 \um_map_char:nn {\um@usv@bfvarkappa,\um@usv@bfitvarkappa}{\um@usv@bfitvarkappa}
539 \um_map_char:nn {\um@usv@bfvarphi,\um@usv@bfitvarphi}{\um@usv@bfitvarphi}
540 \um_map_char:nn {\um@usv@bfvarrho,\um@usv@bfitvarrho}{\um@usv@bfitvarrho}
541 \um_map_char:nn {\um@usv@bfvarpi,\um@usv@bfitvarpi}{\um@usv@bfitvarpi}
542 \fi
543 \fi
544 \else
: TODO : what is supposed to happen here?
545 \fi
546 }

```

### 5.3.4 Functions for setting up the maths alphabets

`\um_mathmap_noparse:Nnn` #1 : Maths alphabet, *e.g.*, `\mathbb`  
#2 : Input slot(s), *e.g.*, the slot for ‘A’ (comma separated)  
#3 : Output slot, *e.g.*, the slot for ‘A’  
Adds `\um_set_mathcode:nnnn` declarations to the specified maths alphabet’s definition (*e.g.*, `\um@mathscr`). Uses `\um@addto@mathmap` (below) to expand the name of the current symbol font.

```

547 \cs_set:Nn \um_mathmap_noparse:Nnn {
548   \clist_map_inline:nn {#2} {
549     \exp_args:No \um@addto@mathmap \um_symfont_tl {##1}{#1}{#3}
550   }
551 }

```

`\um_mathmap_parse:Nnn` #1 : Maths alphabet, *e.g.*, `\mathbb`  
#2 : Input slot(s), *e.g.*, the slot for ‘A’ (comma separated)  
#3 : Output slot, *e.g.*, the slot for ‘A’  
When `\um@parse@term` is executed, it populates the `\um@char@num@range` macro with slot numbers corresponding to the specified range. This range is used to conditionally add `\um_set_mathcode:nnnn` declarations to the maths alphabet definition (*e.g.*, `\um@mathscr`).

```

552 \cs_set:Nn \um_mathmap_parse:Nnn {
553   \clist_map_inline:Nn \um@char@num@range {
554     \ifnum##1=#3\relax
555       \clist_map_inline:nn {#2} {
556         \exp_args:No \um@addto@mathmap \um_symfont_tl {####1}{#1}{#3}
557       }
558     \fi
559   }
560 }

```

`\um@addto@mathmap` #1 : Math symbol font, always/usually the expansion of `\um_symfont_tl`  
 #2 : Input slot, *e.g.*, the slot for ‘A’  
 #3 : Maths alphabet, *e.g.*, `\mathbb`  
 #4 : Output slot, *e.g.*, the slot for ‘A’  
 This macro is used so that `\um_symfont_tl` can be expanded before entering the `\g@addto@macro` command.

```

561 \newcommand\um@addto@mathmap[4]{
562   \expandafter\g@addto@macro
563   \csname um_setup_\cs_to_str:N #3:\endcsname{
564     \um_set_mathcode:nnnn{#2}{\mathalpha}{#1}{#4}
565   }
566 }

```

## 5.4 (Big) operators





























Turns out that  $\text{\XeTeX}$  is clever enough to deal with big operators for us automatically with `\XeTeXmathchardef`. Amazing!

However, the limits aren’t set automatically; that is, we want to define, a la Plain  $\text{\TeX}$  *etc.*, `\def\int{\\intop\nolimits}`, so there needs to be a transformation from `\int` to `\intop` during the expansion of `\UnicodeMathSymbol` in the appropriate contexts.

Following is a table of every math operator (`\mathop`) defined in `unicode-math-table.tex`, from which a subset need to be flagged for `\nolimits` adjustments. The limits behaviour as specified by `unicode-math` are shown (with grey ‘scripts’).

USV	Ex.	Macro	Description
U+02140	$\sum\limits_0^1$	<code>\Bbbsum</code>	DOUBLE-STRUCK N-ARY SUMMATION
U+0220F	$\prod\limits_0^1$	<code>\prod</code>	PRODUCT OPERATOR
U+02210	$\coprod\limits_0^1$	<code>\coprod</code>	COPRODUCT OPERATOR

U+02211	$\sum_{01}^1$	<code>\sum</code>	SUMMATION OPERATOR
U+0222B	$\int_0^1$	<code>\int</code>	INTEGRAL OPERATOR
U+0222C	$\iint_0^1$	<code>\iint</code>	DOUBLE INTEGRAL OPERATOR
U+0222D	$\iiint_0^1$	<code>\iiint</code>	TRIPLE INTEGRAL OPERATOR
U+0222E	$\oint_0^1$	<code>\oint</code>	CONTOUR INTEGRAL OPERATOR
U+0222F	$\oiint_0^1$	<code>\oiint</code>	DOUBLE CONTOUR INTEGRAL OPERATOR
U+02230	$\oiiint_0^1$	<code>\oiiint</code>	TRIPLE CONTOUR INTEGRAL OPERATOR
U+02231	$\int_0^1$	<code>\intclockwise</code>	CLOCKWISE INTEGRAL
U+02232	$\oint_0^1$	<code>\varointclockwise</code>	CONTOUR INTEGRAL, CLOCKWISE
U+02233	$\oint_0^1$	<code>\ointctrackwise</code>	CONTOUR INTEGRAL, ANTICLOCKWISE
U+022C0	$\bigwedge_{01}^1$	<code>\bigwedge</code>	LOGICAL OR OPERATOR
U+022C1	$\bigvee_{01}^1$	<code>\bigvee</code>	LOGICAL AND OPERATOR
U+022C2	$\bigcap_{01}^1$	<code>\bigcap</code>	INTERSECTION OPERATOR
U+022C3	$\bigcup_{01}^1$	<code>\bigcup</code>	UNION OPERATOR
U+027D5	$\Join_{01}^1$	<code>\leftouterjoin</code>	LEFT OUTER JOIN
U+027D6	$\Join_{01}^1$	<code>\rightouterjoin</code>	RIGHT OUTER JOIN
U+027D7	$\Join_{01}^1$	<code>\fullouterjoin</code>	FULL OUTER JOIN
U+027D8	$\Uparrow_{01}^1$	<code>\biguparrow</code>	LARGE UP TACK
U+027D9	$\Downarrow_{01}^1$	<code>\bigdownarrow</code>	LARGE DOWN TACK
U+029F8	$\big/_{01}^1$	<code>\xsol</code>	BIG SOLIDUS
U+029F9	$\big\backslash_{01}^1$	<code>\xbsol</code>	BIG REVERSE SOLIDUS
U+02A00	$\bigodot_{01}^1$	<code>\bigodot</code>	N-ARY CIRCLED DOT OPERATOR
U+02A01	$\bigoplus_{01}^1$	<code>\bigoplus</code>	N-ARY CIRCLED PLUS OPERATOR
U+02A02	$\bigotimes_{01}^1$	<code>\bigotimes</code>	N-ARY CIRCLED TIMES OPERATOR
U+02A03	$\bigcup_{01}^1 \cdot$	<code>\bigcupdot</code>	N-ARY UNION OPERATOR WITH DOT
U+02A04	$\bigcup_{01}^1 +$	<code>\bigcupplus</code>	N-ARY UNION OPERATOR WITH PLUS

U+02A05		\bigsqcap	N-ARY SQUARE INTERSECTION OPERATOR
U+02A06		\bigsqcup	N-ARY SQUARE UNION OPERATOR
U+02A07		\conjquant	TWO LOGICAL AND OPERATOR
U+02A08		\disjquant	TWO LOGICAL OR OPERATOR
U+02A09		\bigtimes	N-ARY TIMES OPERATOR
U+02A0B		\sumint	SUMMATION WITH INTEGRAL
U+02A0C		\iiint	QUADRUPLE INTEGRAL OPERATOR
U+02A0D		\intbar	FINITE PART INTEGRAL
U+02A0E		\intBar	INTEGRAL WITH DOUBLE STROKE
U+02A0F		\fint	INTEGRAL AVERAGE WITH SLASH
U+02A10		\cirfnint	CIRCULATION FUNCTION
U+02A11		\awint	ANTICLOCKWISE INTEGRATION
U+02A12		\rppointint	LINE INTEGRATION WITH RECTANGULAR PATH AROUND POLE
U+02A13		\scpointint	LINE INTEGRATION WITH SEMICIRCULAR PATH AROUND POLE
U+02A14		\npointint	LINE INTEGRATION NOT INCLUDING THE POLE
U+02A15		\oint	INTEGRAL AROUND A POINT OPERATOR
U+02A16		\sqint	QUATERNION INTEGRAL OPERATOR
U+02A17		\intlarhk	INTEGRAL WITH LEFTWARDS ARROW WITH HOOK
U+02A18		\intx	INTEGRAL WITH TIMES SIGN
U+02A19		\intcap	INTEGRAL WITH INTERSECTION
U+02A1A		\intcup	INTEGRAL WITH UNION
U+02A1B		\upint	INTEGRAL WITH OVERBAR
U+02A1C		\lowint	INTEGRAL WITH UNDERBAR
U+02A1D		\Join	JOIN
U+02A1E		\bigtriangleleft	LARGE LEFT TRIANGLE OPERATOR
U+02A1F		\zcmp	Z NOTATION SCHEMA COMPOSITION
U+02A20		\zpipe	Z NOTATION SCHEMA PIPING
U+02A21		\zproject	Z NOTATION SCHEMA PROJECTION



U+02AFC	1 0	$\biginterleave$	LARGE TRIPLE VERTICAL BAR OPERATOR
U+02AFF	1 0	$\bigtalloblong$	N-ARY WHITE VERTICAL BAR

---

`\um@nolimits` This macro is a sequence containing those maths operators that require a `\nolimits` suffix. This list is used when processing `unicode-math-table.tex` to define such commands automatically (see the macro `\um@set@mathsymbol` on page 20). I’ve chosen essentially just the operators that look like integrals; hopefully a better mathematician can help me out here. I’ve a feeling that it’s more useful *not* to include the multiple integrals such as  $\int\int\int$ , but that might be a matter of preference.

```

567 \def\um@nolimits{
568   \@elt\int\@elt\iiint\@elt\iiint\@elt\iiint\@elt\oint\@elt\oint\@elt\oiint
569   \@elt\intclockwise\@elt\varointclockwise\@elt\ointctrclockwise\@elt\sumint
570   \@elt\intbar\@elt\intBar\@elt\oint\@elt\cirfnint\@elt\awint\@elt\rppoint
571   \@elt\scpolint\@elt\ntpolint\@elt\pointint\@elt\sqint\@elt\intlarhk\@elt\intx
572   \@elt\intcap\@elt\intcup\@elt\upint\@elt\lowint
573 }

```

`\addnolimits` This macro appends material to the macro containing the list of operators that don’t take limits. See example following for usage. Note at present that this command must have taken effect before `\setmathfont`.

```

574 \newcommand\addnolimits[1]{
575   \expandafter\def\expandafter\um@nolimits\expandafter{\um@nolimits\@elt#1}
576 }

```

`\removenolimits` Can this macro be given a better name? It removes (globally) an item from the `nolimits` list. See example following for usage.

```

577 \def\removenolimits#1{
578   \begingroup
579     \def\@elt##1{
580       \ifx##1#1\else
581         \noexpand\@elt\noexpand##1
582       \fi}
583     \xdef\um@nolimits{\um@nolimits}
584   \endgroup
585 }

```

## 5.5 Radicals

The radical for square root is organised in `\um@set@mathsymbol` on page ?? . I think it’s the only radical ever. (Actually, there is also `\cuberoot` and `\fourthroot`, but they don’t seem to behave as proper radicals.)

Also, what about right-to-left square roots?

`\um@radicals` We organise radicals in the same way as `nolimits-operators`; that is, in a comma-list.

```
586 \def\um@radicals{\sqrt}
```

$$\sqrt[2]{1 + \sqrt[3]{1+x}}$$

```
\setmathfont{Cambria Math}
\[\sqrt[2]{1+\sqrt[3]{1+x}}\]
```

## 5.6 Delimiters

`\left` We redefine the primitive to be preceded by `\mathopen`; this gives much better spacing in cases such as `\sin\left....` Courtesy of Frank Mittelbach:

<http://www.latex-project.org/cgi-bin/ltxbugs2html?pr=latex/3853&prlatex/3754>

```
587 \let\left@primitive\left
```

```
588 \def\left{\mathopen{}\left@primitive}
```

No re-definition is made for `\right` because I don't believe it to be necessary.

Some symbols that aren't `mathopen`/`mathclose` still need to have delimiter codes assigned.

Set up `delcodes` so that slashes and things can grow if the font supports it. This is just inserted here so the documentation works. It will be generalised soon.

```
589 \XeTeXdelcode"002F =4 "002F % ord
```

```
590 \XeTeXdelcode"005C =4 "005C % ord
```

```
591 \XeTeXdelcode"2044 =4 "2044 % bin
```

```
592 \XeTeXdelcode"2215 =4 "2215 % bin
```

```
593 \XeTeXdelcode"2216 =4 "2216 % bin
```

```
594 \XeTeXdelcode"29F5 =4 "29F5 % bin
```

Here are all `\mathopen` characters:

USV	Ex.	Macro	Description
U+00028	(	<code>\lparen</code>	LEFT PARENTHESIS
U+0005B	[	<code>\lbrack</code>	LEFT SQUARE BRACKET
U+0007B	{	<code>\lbrace</code>	LEFT CURLY BRACKET
U+0007C		<code>\lvert</code>	VERTICAL BAR
U+02016		<code>\lVert</code>	DOUBLE VERTICAL BAR
U+0221A	√	<code>\sqrt</code>	RADICAL
U+0221B	∛	<code>\cuberoot</code>	CUBE ROOT
U+0221C	∜	<code>\fourthroot</code>	FOURTH ROOT
U+02308	⌈	<code>\lceil</code>	LEFT CEILING
U+0230A	⌊	<code>\lfloor</code>	LEFT FLOOR
U+0231C	⌒	<code>\ulcorner</code>	UPPER LEFT CORNER

U+0231E	⏟	<code>\llcorner</code>	LOWER LEFT CORNER LIGHT LEFT TORTOISE SHELL BRACKET
U+02772	⎵	<code>\lbrbrak</code>	ORNAMENT
U+027C5	⎴	<code>\lbag</code>	LEFT S-SHAPED BAG DELIMITER
U+027CC	⎵	<code>\longdivision</code>	LONG DIVISION MATHEMATICAL LEFT WHITE SQUARE
U+027E6	⎵	<code>\lBrack</code>	BRACKET
U+027E8	⎵	<code>\langle</code>	MATHEMATICAL LEFT ANGLE BRACKET MATHEMATICAL LEFT DOUBLE ANGLE
U+027EA	⎵	<code>\lAngle</code>	BRACKET MATHEMATICAL LEFT WHITE TORTOISE
U+027EC	⎵	<code>\Lbrbrak</code>	SHELL BRACKET
U+02983	⎵	<code>\lBrace</code>	LEFT WHITE CURLY BRACKET
U+02985	⎵	<code>\lParen</code>	LEFT WHITE PARENTHESIS
U+02987	⎵	<code>\llparenthesis</code>	Z NOTATION LEFT IMAGE BRACKET
U+02989	⎵	<code>\llangle</code>	Z NOTATION LEFT BINDING BRACKET
U+0298B	⎵	<code>\lbrackubar</code>	LEFT SQUARE BRACKET WITH UNDERBAR LEFT SQUARE BRACKET WITH TICK IN TOP
U+0298D	⎵	<code>\lbrackultick</code>	CORNER LEFT SQUARE BRACKET WITH TICK IN
U+0298F	⎵	<code>\lbracklltick</code>	BOTTOM CORNER
U+02991	⎵	<code>\langledot</code>	LEFT ANGLE BRACKET WITH DOT
U+02993	⎵	<code>\lparenless</code>	LEFT ARC LESS-THAN BRACKET
U+02997	⎵	<code>\lblkbrbrak</code>	LEFT BLACK TORTOISE SHELL BRACKET
U+029D8	⎵	<code>\lvzigzag</code>	LEFT WIGGLY FENCE
U+029DA	⎵	<code>\Lvzigzag</code>	LEFT DOUBLE WIGGLY FENCE
U+029FC	⎵	<code>\lcurvyangle</code>	LEFT POINTING CURVED ANGLE BRACKET
U+03014	⎵	<code>\lbrbrak</code>	LEFT BROKEN BRACKET
U+03018	⎵	<code>\Lbrbrak</code>	LEFT WHITE TORTOISE SHELL BRACKET

And `\mathclose`:

USV	Ex.	Macro	Description
U+00029	)	<code>\rparen</code>	RIGHT PARENTHESIS
U+0005D	]	<code>\rbrack</code>	RIGHT SQUARE BRACKET
U+0007C		<code>\rvert</code>	VERTICAL BAR
U+0007D	}	<code>\rbrace</code>	RIGHT CURLY BRACKET
U+02016		<code>\rVert</code>	DOUBLE VERTICAL BAR
U+02309	]̂	<code>\rceil</code>	RIGHT CEILING
U+0230B	]̇	<code>\rfloor</code>	RIGHT FLOOR
U+0231D	⏟̂	<code>\urcorner</code>	UPPER RIGHT CORNER
U+0231F	⏟̇	<code>\lrcorner</code>	LOWER RIGHT CORNER LIGHT RIGHT TORTOISE SHELL BRACKET
U+02773	⎶	<code>\rbrbrak</code>	ORNAMENT
U+027C6	⎴	<code>\rbag</code>	RIGHT S-SHAPED BAG DELIMITER

U+027E7	⌋	\rBrack	MATHEMATICAL RIGHT WHITE SQUARE BRACKET
U+027E9	⌋	\rangle	MATHEMATICAL RIGHT ANGLE BRACKET MATHEMATICAL RIGHT DOUBLE ANGLE
U+027EB	⌋	\rAngle	BRACKET MATHEMATICAL RIGHT WHITE TORTOISE
U+027ED		\Rbrbrak	SHELL BRACKET
U+02984	⌋	\rBrace	RIGHT WHITE CURLY BRACKET
U+02986	⌋	\rParen	RIGHT WHITE PARENTHESIS
U+02988	⌋	\rrparenthesis	Z NOTATION RIGHT IMAGE BRACKET
U+0298A	⌋	\rrangle	Z NOTATION RIGHT BINDING BRACKET
U+0298C	⌋	\rbrackubar	RIGHT SQUARE BRACKET WITH UNDERBAR RIGHT SQUARE BRACKET WITH TICK IN
U+0298E	⌋	\rbracklrtick	BOTTOM CORNER RIGHT SQUARE BRACKET WITH TICK IN TOP
U+02990	⌋	\rbrackurtick	CORNER
U+02992	⌋	\rangledot	RIGHT ANGLE BRACKET WITH DOT
U+02994	⌋	\rpangtr	RIGHT ARC GREATER-THAN BRACKET
U+02998	⌋	\rblkrbrak	RIGHT BLACK TORTOISE SHELL BRACKET
U+029D9	⌋	\rvzigzag	RIGHT WIGGLY FENCE
U+029DB	⌋	\Rvzigzag	RIGHT DOUBLE WIGGLY FENCE
U+029FD	⌋	\rcurvyangle	RIGHT POINTING CURVED ANGLE BRACKET
U+03015		\rbrbrak	RIGHT BROKEN BRACKET
U+03019		\Rbrbrak	RIGHT WHITE TORTOISE SHELL BRACKET

## 5.7 Maths accents

Maths accents should just work *if they are available in the font*.

USV	Ex.	Macro	Description
U+00300	˘	\grave	GRAVE ACCENT
U+00301	ˆ	\acute	ACUTE ACCENT
U+00302	ˆ	\hat	CIRCUMFLEX ACCENT
U+00303	˜	\tilde	TILDE
U+00304	ˉ	\bar	MACRON
U+00305	ˆ	\overbar	OVERBAR EMBELLISHMENT
U+00306	˘	\breve	BREVE
U+00307	˙	\dot	DOT ABOVE
U+00308	¨	\ddot	DIERESIS
U+00309	ˆ	\ovhook	COMBINING HOOK ABOVE
U+0030A	ˆ	\ocirc	RING
U+0030C	ˇ	\check	CARON
U+00310	ˆ	\candra	CANDRABINDU (NON-SPACING)
U+00312	ˆ	\turnedcomma	COMBINING TURNED COMMA ABOVE

U+00313	$\acute{x}$	<code>\osmooth</code>	GREEK PSILI (SMOOTH BREATHING) (NON-SPACING)
U+00314	$\grave{x}$	<code>\orough</code>	GREEK DASIA (ROUGH BREATHING) (NON-SPACING)
U+00315	$\mathring{x}$	<code>\ocommatopright</code>	COMBINING COMMA ABOVE RIGHT
U+0031A	$\mathring{x}$	<code>\droang</code>	LEFT ANGLE ABOVE (NON-SPACING) COMBINING LONG SOLIDUS OVERLAY
U+00338	$\not x$	<code>\not</code>	
U+020D0	$\overleftarrow{x}$	<code>\leftharpoonaccent</code>	COMBINING LEFT HARPOON ABOVE
U+020D1	$\overrightarrow{x}$	<code>\rightharpoonaccent</code>	COMBINING RIGHT HARPOON ABOVE
U+020D2	$\overline{x}$	<code>\vertoverlay</code>	COMBINING LONG VERTICAL LINE OVERLAY
U+020D6	$\overleftarrow{x}$	<code>\overleftarrow</code>	COMBINING LEFT ARROW ABOVE
U+020D7	$\overrightarrow{x}$	<code>\overrightarrow</code>	COMBINING RIGHT ARROW ABOVE
U+020DB	$\ddot{x}$	<code>\dddot</code>	COMBINING THREE DOTS ABOVE
U+020DC	$\ddot{x}$	<code>\ddddot</code>	COMBINING FOUR DOTS ABOVE
U+020E1	$\overleftrightarrow{x}$	<code>\overleftrightharpoon</code>	COMBINING LEFT RIGHT ARROW ABOVE
U+020E7	$\mathfrak{A}$	<code>\annuity</code>	COMBINING ANNUITY SYMBOL
U+020E8	$\mathring{x}$	<code>\threeunderdot</code>	COMBINING TRIPLE UNDERDOT
U+020E9	$\overbrace{x}$	<code>\widebridgeabove</code>	COMBINING WIDE BRIDGE ABOVE COMBINING RIGHTWARDS HARPOON WITH
U+020EC	$\mathfrak{A}$	<code>\underrightharpoondown</code>	BARB DOWNWARDS COMBINING LEFTWARDS HARPOON WITH
U+020ED	$\mathfrak{A}$	<code>\underleftharpoondown</code>	BARB DOWNWARDS
U+020EE	$\mathfrak{A}$	<code>\underleftarrow</code>	COMBINING LEFT ARROW BELOW
U+020EF	$\mathfrak{A}$	<code>\underrightarrow</code>	COMBINING RIGHT ARROW BELOW
U+020F0	$\mathfrak{A}$	<code>\asteraccent</code>	COMBINING ASTERISK ABOVE

---

## 6 Font features

`\um@zf@feature` Use the same method as `fontspec` for feature definition (*i.e.*, using `xkeyval`) but with a conditional to restrict the scope of these features to unicode-math commands.

```

595 \newcommand\um@zf@feature[2]{
596   \define@key[zf]{options}{#1}[]{}
597   \if@um@fontspec@feature
598     #2
599   \else
600     \PackageError{fontspec/unicode-math}
601       {The ‘#1’ font feature can only be used for maths fonts}
602       {The feature you tried to use can only be in commands
603         like \protect\setmathfont}
604   \fi
605 }
```

```
606 }
```

## 6.1 OpenType maths font features

```
607 \um@zf@feature{ScriptStyle}{
608   \zf@update@ff{+ssty=0}
609 }
610 \um@zf@feature{ScriptScriptStyle}{
611   \zf@update@ff{+ssty=1}
612 }
```

## 6.2 Script and scriptscript font options

```
613 \define@cmdkey[um]{options}[um@]{ScriptFeatures}{}
614 \define@cmdkey[um]{options}[um@]{ScriptScriptFeatures}{}
615 \define@cmdkey[um]{options}[um@]{ScriptFont}{}
616 \define@cmdkey[um]{options}[um@]{ScriptScriptFont}{}

```

## 6.3 Range processing

The ‘ALL’ branch here is deprecated and happens automatically.

```
617 \define@choicekey+[um]{options}{Range}[\@tempa\@tempb]{ALL}{
618   \ifcase\@tempb\relax
619     \global\let\um@char@range\@empty
620   \fi
621 }{
622   \xdef\um@char@range{#1}
623 }
```

Pretty basic comma separated range processing. Donald Arseneau’s selectp package has a cleverer technique.

```
\um@parse@term #1 : unicode character slot
                #2 : control sequence (character macro)
                #3 : control sequence (math type)
                #4 : code to execute
```

This macro expands to #4 if any of its arguments are contained in the commalist `\um@char@range`. This list can contain either character ranges (for checking with #1) or control sequences. These latter can either be the command name of a specific character, *or* the math type of one (*e.g.*, `\mathbin`).

Character ranges are passed to `\um@parse@range`, which accepts input in the form shown in table 11.

Start by iterating over the commalist, ignoring empties, and initialising the scratch conditional:

```
624 \newcommand\um@parse@term[4]{
625   \clist_map_variable:NNn \um@char@range \@ii {
626     \unless\ifx\@ii\@empty
627       \@tempswafalse
```

Table 11: Ranges accepted by `\um@parse@range`.

Input	Range
$x$	$r = x$
$x-$	$r \geq x$
$-y$	$r \leq y$
$x-y$	$x \leq r \leq y$

Match to either the character macro (`\alpha`) or the math type (`\mathbin`):

```

628     \expandafter\um@firstchar\expandafter{\@ii}
629     \ifx\@tempa\um@backslash
630         \expandafter\ifx\@ii#2\relax
631             \@tempswatrue
632         \else
633             \expandafter\ifx\@ii#3\relax
634                 \@tempswatrue
635             \fi
636         \fi

```

Otherwise, we have a number range, which is passed to another macro:

```

637     \else
638         \expandafter\um@parse@range\@ii-\@marker-\@nil#1\@nil
639     \fi

```

If we have a match, execute the code! It also populates the `\um@char@num@range` macro, which is used when defining `\mathbf` (*etc.*) `\mathchar` remappings.

```

640     \if@tempswa
641         \ifx\um@char@num@range\@empty
642             \g@addto@macro\um@char@num@range{#1}
643         \else
644             \g@addto@macro\um@char@num@range{, #1}
645         \fi
646         #4%
647     \fi
648 \fi
649 }
650 }
651 \def\um@firstof#1#2\@nil{#1}
652 \edef\um@backslash{\expandafter\um@firstof\string\string\@nil}
653 \def\um@firstchar#1{\edef\@tempa{\expandafter\um@firstof\string#1\@nil}}

```

'1' or '\a' or '\b' is included '1' or '\b' or '\c' is included '3' or '\a' or '\b' is included '3' or '\a' or '\b' is included

```
\def\um@char@range{\a,2-4,\c}
\um@parse@term{1}{\a}{\b}
{\a' or '\string'a' or '\string'b' is included}
\um@parse@term{1}{\b}{\c}
{\b' or '\string'b' or '\string'c' is included}
\um@parse@term{3}{\a}{\b}
{\a' or '\string'a' or '\string'b' is included}
```

\um@parse@range Weird syntax. As shown previously in table 11, this macro can be passed four different input types via \um@parse@term.

```
654 \def\um@parse@range#1-#2-#3\@nil#4\@nil{
655   \def\@tempa{#1}
656   \def\@tempb{#2}

Range       $r = x$ 
C-list input \@ii=X
Macro input \um@parse@range X-\@marker-\@nil#1\@nil
Arguments   $\textcolor{red}{\#1}-\textcolor{blue}{\#2}-\textcolor{green}{\#3} = \textcolor{red}{X}-\@marker-\{\}$ 

657   \expandafter\ifx\expandafter\@marker\@tempb\relax
658     \ifnum#4=#1\relax
659       \@tempswatruetrue
660     \fi
661   \else

Range       $r \geq x$ 
C-list input \@ii=X-
Macro input \um@parse@range X--\@marker-\@nil#1\@nil
Arguments   $\textcolor{red}{\#1}-\textcolor{blue}{\#2}-\textcolor{green}{\#3} = \textcolor{red}{X}-\{\}-\@marker-$ 

662   \ifx\@empty\@tempb
663     \ifnum#4>\numexpr#1-1\relax
664       \@tempswatruetrue
665     \fi
666   \else

Range       $r \leq y$ 
C-list input \@ii=-Y
Macro input \um@parse@range -Y-\@marker-\@nil#1\@nil
Arguments   $\textcolor{red}{\#1}-\textcolor{blue}{\#2}-\textcolor{green}{\#3} = \{\}-\textcolor{red}{Y}-\@marker-$ 

667   \ifx\@empty\@tempa
668     \ifnum#4<\numexpr#2+1\relax
669       \@tempswatruetrue
670     \fi

Range       $x \leq r \leq y$ 
C-list input \@ii=X-Y
Macro input \um@parse@range X-Y-\@marker-\@nil#1\@nil
Arguments   $\textcolor{red}{\#1}-\textcolor{blue}{\#2}-\textcolor{green}{\#3} = \textcolor{red}{X}-\textcolor{blue}{Y}-\@marker-$ 
```



```

671         \else
672             \ifnum#4>\numexpr#1-1\relax
673             \ifnum#4<\numexpr#2+1\relax
674                 \@tempwattrue
675             \fi
676         \fi
677     \fi
678 \fi
679 \fi
680 }

\um_map_char:nn #1 : Number of iterations
                #2 : Starting input char(s)
                #3 : Starting output char
                Loops through character ranges setting \mathcode.
681 \cs_set:Nn \um_map_chars_range:nnn {
682     \clist_map_variable:nnN {#2} \l_um_input_num {
683         \prg_stepwise_variable:nnnN{0}{1}{#1} \l_um_incr_num {
684             \um_set_mathcode:nnnn
685             {\numexpr \l_um_incr_num+ \l_um_input_num \relax}
686             {\mathalpha}{\um_symfont_tl}
687             {\numexpr \l_um_incr_num + #3 \relax}
688         }
689     }
690 }
691 \cs_set:Nn \um_map_chars_latin:nn {
692     \um_map_chars_range:nnn {25}{#1}{#2}
693 }
694 \cs_set:Nn \um_map_chars_greek:nn {
695     \um_map_chars_range:nnn {24}{#1}{#2}
696 }
697 \cs_set:Nn \um_map_chars_numbers:nn {
698     \um_map_chars_range:nnn {9}{#1}{#2}
699 }
700 \cs_set:Nn \um_map_char:nn {
701     \um_map_chars_range:nnn {0}{#1}{#2}
702 }

```

```

\um_set_mathalphabet_char:Nnnn #1 : Maths alphabet
                                #2 : Input char(s)
                                #3 : Output char
                                Loops through character ranges setting \mathcode.
703 \cs_set:Npn \exp_args:Nnff {\::n\::f\::f\:::}
704 \cs_new:Nn \um_set_mathalphabet_char:Nnn {
705     \clist_map_variable:nnN {#2} \l_um_input_num {
706         \exp_args:Nnff \um_mathmap:Nnn {#1}

```

```

707     {\number\numexpr\l_um_input_num\relax} {\number\numexpr#3\relax}
708   }
709 }

\um_set_mathalph_range:Nnn [(\textit{Number of iterations})] #1 : Maths alphabet
#2 : Starting input char(s)
#3 : Starting output char
Loops through character ranges setting \mathcode.

710 \cs_new:Nn \um_set_mathalph_range:nNnn {
711   \clist_map_variable:nNn {#3} \l_um_input_num {
712     \prg_stepwise_variable:nnnNn {0}{1}{#1} \l_um_inc_num {
713       \exp_args:Nnff \um_mathmap:Nnn {#2}
714         {\number\numexpr \l_um_inc_num + \l_um_input_num \relax}
715         {\number\numexpr \l_um_inc_num + #4 \relax}
716     }
717   }
718 }
719 \cs_new:Nn \um_set_mathalphabet_numbers:Nnn {
720   \um_set_mathalph_range:nNnn {9}{#1}{#2}{#3}
721 }
722 \cs_new:Nn \um_set_mathalphabet_latin:Nnn {
723   \um_set_mathalph_range:nNnn {25}{#1}{#2}{#3}
724 }
725 \cs_new:Nn \um_set_mathalphabet_greek:Nnn {
726   \um_set_mathalph_range:nNnn {24}{#1}{#2}{#3}
727 }



---



BCDBCDEABCDEF

\ExplSyntaxOn
{\um_map_chars_range:nnn{3}{'\A,'\D}{'\B}
$ABCEFG$} $ABCEFG$



---



```

## 6.4 Resolving Greek symbol name control sequences

`\um@resolve@greek` This macro defines `\Alpha...``\omega` as their corresponding unicode (mathematical italic) character. Remember that the mapping to upright or italic happens with the `mathcode` definitions, whereas these macros just stand for the literal unicode characters.

```

728 \AtBeginDocument{\um@resolve@greek}
729 \newcommand\um@resolve@greek{
730   \def\Alpha{\mitAlpha}
731   \def\Beta{\mitBeta}
732   \def\Gamma{\mitGamma}
733   \def\Delta{\mitDelta}
734   \def\Epsilon{\mitEpsilon}

```

```

735 \def\Zeta{\mitZeta}
736 \def\Eta{\mitEta}
737 \def\Theta{\mitTheta}
738 \def\Iota{\mitIota}
739 \def\Kappa{\mitKappa}
740 \def\Lambda{\mitLambda}
741 \def\Mu{\mitMu}
742 \def\Nu{\mitNu}
743 \def\Xi{\mitXi}
744 \def\Omicron{\mitOmicron}
745 \def\Pi{\mitPi}
746 \def\Rho{\mitRho}
747 \def\varTheta{\mitvarTheta}
748 \def\Sigma{\mitSigma}
749 \def\Tau{\mitTau}
750 \def\Upsilon{\mitUpsilon}
751 \def\Phi{\mitPhi}
752 \def\Chi{\mitChi}
753 \def\Psi{\mitPsi}
754 \def\Omega{\mitOmega}

```

#### Lowercase:

```

755 \def\alpha{\mitalpha}
756 \def\beta{\mitbeta}
757 \def\gamma{\mitgamma}
758 \def\delta{\mitdelta}
759 \def\epsilon{
760   \bool_if:NTF \g_um_texgreek_bool {\mitvarepsilon}{\mitepsilon}
761 }
762 \def\zeta{\mitzeta}
763 \def\eta{\miteta}
764 \def\theta{\mittheta}
765 \def\iota{\mitiota}
766 \def\kappa{\mitkappa}
767 \def\lambda{\mitlambda}
768 \def\mu{\mitmu}
769 \def\nu{\mitnu}
770 \def\xi{\mitxi}
771 \def\omicron{\mitomicron}
772 \def\pi{\mitpi}
773 \def\rho{\mitrho}
774 \def\varsigma{\mitvarsigma}
775 \def\sigma{\mitsigma}
776 \def\tau{\mittau}
777 \def\upsilon{\mitupsilon}
778 \def\phi{
779   \bool_if:NTF \g_um_texgreek_bool {\mitvarphi}{\mitphi}

```

```

780 }
781 \def\chi{\mitchi}
782 \def\psi{\mitpsi}
783 \def\omega{\mitomega}
784 \def\varepsilon{
785   \bool_if:NTF \g_um_texgreek_bool {\mitepsilon}{\mitvarepsilon}
786 }
787 \def\vartheta{\mitvartheta}
788 \def\varkappa{\mitvarkappa}
789 \def\varphi{
790   \bool_if:NTF \g_um_texgreek_bool {\mitphi}{\mitvarphi}
791 }
792 \def\varrho{\mitvarrho}
793 \def\varpi{\mitvarpi}
794 }

```

## 6.5 Setting up the mappings

\um\_setup\_literals: : TODO : other literal symbols

```

795 \cs_set:Nn \um_setup_literals: {
796   \um_map_chars_latin:nn {\um@usv@upLatin}{\um@usv@upLatin}
797   \um_map_chars_latin:nn {\um@usv@itLatin}{\um@usv@itLatin}
798   \um_map_chars_latin:nn {\um@usv@itlatin}{\um@usv@itlatin}
799   \um_map_char:nn {\um@usv@ith}{\um@usv@ith}
800   \um_map_chars_latin:nn {\um@usv@uplatin}{\um@usv@uplatin}
801   \um_map_chars_greek:nn {\um@usv@upGreek}{\um@usv@upGreek}
802   \um_map_char:nn {\um@usv@varTheta}{\um@usv@varTheta}
803   \um_map_chars_greek:nn {\um@usv@itGreek}{\um@usv@itGreek}
804   \um_map_chars_greek:nn {\um@usv@upgreek}{\um@usv@upgreek}
805 }

```

\um\_setup\_bf\_literals: TODO: other literal symbols

```

806 \cs_set:Nn \um_setup_bf_literals: {
807   \um_map_chars_latin:nn {\um@usv@bfupLatin}{\um@usv@bfupLatin}
808   \um_map_chars_latin:nn {\um@usv@bfuplatin}{\um@usv@bfuplatin}
809   \um_map_chars_latin:nn {\um@usv@bfitLatin}{\um@usv@bfitLatin}
810   \um_map_chars_latin:nn {\um@usv@bfitlatin}{\um@usv@bfitlatin}
811   \um_map_chars_greek:nn {\um@usv@bfupGreek}{\um@usv@bfupGreek}
812   \um_map_chars_greek:nn {\um@usv@bfupgreek}{\um@usv@bfupgreek}
813   \um_map_chars_greek:nn {\um@usv@bfitGreek}{\um@usv@bfitGreek}
814   \um_map_chars_greek:nn {\um@usv@bfitgreek}{\um@usv@bfitgreek}
815 }

```

\um\_setup\_Latin:

```

816 \cs_set:Nn \um_setup_Latin: {
817   \if@um@upLatin

```

```

818 \um_map_chars_latin:nn {\um@usv@upLatin,\um@usv@itLatin}{\um@usv@upLatin}
819 \else
820 \um_map_chars_latin:nn {\um@usv@upLatin,\um@usv@itLatin}{\um@usv@itLatin}
821 \fi
822 }

```

\um\_setup\_latin: Don't overlook 'h', which maps to U+210E: PLANCK CONSTANT instead of the expected U+1D455: MATHEMATICAL ITALIC SMALL H.

```

823 \cs_set:Nn \um_setup_latin: {
824   \if@um@uplatin
825     \um_map_chars_latin:nn {\um@usv@uplatin,\um@usv@itlatin}{\um@usv@uplatin}
826     \um_map_char:nn {\um@usv@ith}{`\h}
827   \else
828     \um_map_chars_latin:nn {\um@usv@uplatin,\um@usv@itlatin}{\um@usv@itlatin}
829     \um_map_char:nn {\h,\um@usv@ith}{\um@usv@ith}
830   \fi
831 }

```

\um\_setup\_greek:

```

832 \cs_set:Nn \um_setup_greek: {
833   \if@um@upgreek
834     \um_map_chars_greek:nn {\um@usv@upgreek,\um@usv@itgreek}{\um@usv@upgreek}
835     \um_map_char:nn {\um@usv@varTheta,"1D6F3}{\um@usv@varTheta}
836   \else
837     \um_map_chars_greek:nn {\um@usv@upgreek,\um@usv@itgreek}{\um@usv@itgreek}
838     \um_map_char:nn {\um@usv@varTheta}{\um@usv@itvarTheta}
839   \fi
840 }

```

\um\_setup\_greek:

```

841 \cs_set:Nn \um_setup_greek: {
842   \if@um@upgreek
843     \um_map_chars_greek:nn {\um@usv@upgreek,\um@usv@itgreek}{\um@usv@upgreek}
844     \um_map_char:nn {\um@usv@varepsilon,\um@usv@itvarepsilon}{\um@usv@varepsilon}
845     \um_map_char:nn {\um@usv@vartheta,\um@usv@itvartheta}{\um@usv@vartheta}
846     \um_map_char:nn {\um@usv@varkappa,\um@usv@itvarkappa}{\um@usv@varkappa}
847     \um_map_char:nn {\um@usv@varphi,\um@usv@itvarphi}{\um@usv@varphi}
848     \um_map_char:nn {\um@usv@varrho,\um@usv@itvarrho}{\um@usv@varrho}
849     \um_map_char:nn {\um@usv@varpi,\um@usv@itvarpi}{\um@usv@varpi}
850   \else
851     \um_map_chars_greek:nn {\um@usv@upgreek,\um@usv@itgreek}{\um@usv@itgreek}
852     \um_map_char:nn {\um@usv@varepsilon,\um@usv@itvarepsilon}{\um@usv@itvarepsilon}
853     \um_map_char:nn {\um@usv@vartheta,\um@usv@itvartheta}{\um@usv@itvartheta}
854     \um_map_char:nn {\um@usv@varkappa,\um@usv@itvarkappa}{\um@usv@itvarkappa}
855     \um_map_char:nn {\um@usv@varphi,\um@usv@itvarphi}{\um@usv@itvarphi}
856     \um_map_char:nn {\um@usv@varrho,\um@usv@itvarrho}{\um@usv@itvarrho}

```

```

857 \um_map_char:nn {\um@usv@varpi,\um@usv@itvarpi}{\um@usv@itvarpi}
858 \fi
859 }

```

## 7 Maths alphabets mapping definitions

Algorithm for setting alphabet fonts. By default, when Range is empty, we are in *implicit* mode. If Range contains the name of the math alphabet, we are in *explicit* mode and do things slightly differently.

Implicit mode:

- Try and set all of the alphabet shapes.
- Check for the first glyph of the uppercase Latin alphabet to detect if the font supports each alphabet shape. (This doesn't work to distinguish Latin/Greek but we hope all maths fonts will have at least them!)
- For alphabets that do exist, overwrite whatever's already there.
- For alphabets that are not supported, *do nothing*. (This includes leaving the old alphabet definition in place.)

Explicit mode:

- Only set the alphabets specified.
- Check for the first glyph of the uppercase Latin alphabet to detect if the font contains the alphabet shape in the unicode math plane.
- For unicode math alphabets, overwrite whatever's already there.
- Otherwise, use the ASCII letters instead.

```

860 \cs_new:Nn \um_setup_alphabets: {
861   \um_setup_math_alphabet:nn {up}   {}{latin, Latin, greek, Greek}
862   \um_setup_math_alphabet:n {it}    {}
863   \um_setup_math_alphabet:n {bb}    {}
864   \um_setup_math_alphabet:nn {scr}  {}{latin, Latin}
865   \um_setup_math_alphabet:nn {frak} {}{latin, Latin}
866   \um_setup_math_alphabet:n {sf}    {}
867   \um_setup_math_alphabet:n {sfup}  {}
868   \um_setup_math_alphabet:n {sfit}  {}
869   \um_setup_math_alphabet:n {tt}    {}
870   \um_setup_math_alphabet:n {bf}    {}
871   \um_setup_math_alphabet:n {bfup}  {}
872   \um_setup_math_alphabet:n {bfit}  {}
873   \um_setup_math_alphabet:n {bfscr} {}
874   \um_setup_math_alphabet:n {bffrak}

```

```

875 \um_setup_math_alphabet:n {bfsf }
876 \um_setup_math_alphabet:n {bfsfup}
877 \um_setup_math_alphabet:n {bfsfit}
878 }

```

\um\_setup\_math\_alphabet:nn #1 : Math font family name (e.g., ‘sf’)

#2 : Math alphabets, comma separated of {latin, Latin, greek, Greek, num}

First check that at least one of the alphabets for the font shape is defined, and then then loop through them defining the individual ranges.

```

879 \cs_new:Nn \um_setup_math_alphabet:nn {
880   \clist_map_inline:nn {#2} {
881     \um_glyph_if_exist:nT {\csname um@usv@#1##1 \endcsname}{
882       \um_maybe_init_alphabet:n {#1}
883       \um_prepare_alph:n {#1}
884       \clist_map_break:
885     }
886   }
887   \clist_map_inline:nn {#2} {
888     \um_glyph_if_exist:nTF {\csname um@usv@#1##1 \endcsname}{
889       \use:c {um_config_math#1_##1:}
890     }{
891       \PackageWarningNoLine{unicode-math}{^^J\space\space\space\space
892         Math~ alphabet~
893         \@backslashchar math#1~
894         (\tl_use:c{g_um_math_alphabet_name_#1_tl})~
895         not~ found~ in~ font~
896         \fontname\um@font}
897     }
898   }
899 }
900 \tl_set:Nn \g_um_math_alphabet_name_latin_tl {Latin, lowercase}
901 \tl_set:Nn \g_um_math_alphabet_name_Latin_tl {Latin, uppercase}
902 \tl_set:Nn \g_um_math_alphabet_name_greek_tl {Greek, lowercase}
903 \tl_set:Nn \g_um_math_alphabet_name_Greek_tl {Greek, uppercase}
904 \tl_set:Nn \g_um_math_alphabet_name_num_tl {Numerals}

905 \cs_new:Nn \um_setup_math_alphabet:n {
906   \um_glyph_if_exist:nTF {\csname um@usv@#1Latin \endcsname}{
907     \um_maybe_init_alphabet:n {#1}
908     \um_prepare_alph:n {#1}
909     \use:c {um_config_math#1:}
910   }{
911     \PackageWarningNoLine{unicode-math}{^^J\space\space\space\space
912       Math~ alphabet~ \@backslashchar math#1~ not~ found~ in~ font~ \font-
913       name\um@font}
914     \cs_if_exist:cT {um_fix_math#1:} {
915       \use:c {um_fix_math#1:}

```

```

915     }
916   }
917 }
918 \cs_set:Nn \um_fix_mathtt: {
919   \SetMathAlphabet\mathtt{normal}\encodingdefault\ttdefault\mddefault\updefault
920 }
921 \cs_set:Nn \um_init_alphabet:n {
922   \cs_set_eq:cN {um_setup_math#1:} \prg_do_nothing:
923 }

```

`\um_glyph_if_exist:nTF` : TODO: Generalise for arbitrary fonts! `\um@font` is not always the one used for a specific glyph!!

```

924 \prg_new_conditional:Nnn \um_glyph_if_exist:n {p,TF,T,F} {
925   \tex_iffontchar:D \um@font #1 \scan_stop: \prg_return_true: \else: \prg_return_false: \fi:
926 }

```

`\um_prepare_alph:n` If `\mathXY` hasn't been (re-)declared yet, then define it in terms of unicode-math definitions. Use `\bgroup/\egroup` so s'scripts scan the whole thing.

```

927 \cs_new:Nn \um_prepare_alph:n {
928   \cs_if_exist:cF {um_math#1:n} {
929     \cs_set:cpn {um_math#1:n} ##1 {
930       \use:c {um_setup_math#1:} ##1 \egroup
931     }
932     \cs_set_protected:cpn {math#1} {
933       \bgroup
934       \mode_if_math:F {
935         \egroup\expandafter
936         \non@alpherr\expandafter{\csname math#1\endcsname\space}
937       }
938       \use:c {um_math#1:n}
939     }
940   }
941 }

```

: TODO : nested alphabets?

## 7.1 Non-bold math alphabets

### 7.1.1 Upright: `\mathup`

Takes both upright and italic characters to be typeset as upright symbols.

```

942 \cs_new:Npn \um_config_mathup_Latin: {
943   \um_set_mathalphabet_latin:Nnn{\mathup}{\um@usv@upLatin,\um@usv@itLatin}{\um@usv@upLatin}
944 }
945 \cs_new:Npn \um_config_mathup_latin: {
946   \um_set_mathalphabet_latin:Nnn{\mathup}{\um@usv@uplatin,\um@usv@itlatin}{\um@usv@uplatin}

```



```

947 \um_set_mathalphabet_char:Nnn{\mathup}{\um@usv@ith} {\`h}
948 }
949 \cs_new:Npn \um_config_mathup_Greek: {
950 \um_set_mathalphabet_greek:Nnn{\mathup}{\um@usv@upGreek,\um@usv@itGreek}{\um@usv@upGreek}
951 \um_set_mathalphabet_char:Nnn{\mathup}{\um@usv@Nabla,\um@usv@itNabla}{\um@usv@Nabla}
952 \um_set_mathalphabet_char:Nnn{\mathup}{\um@usv@varTheta,\um@usv@itvarTheta}{\um@usv@varTheta}
953 }
954 \cs_new:Npn \um_config_mathup_greek: {
955 \um_set_mathalphabet_greek:Nnn{\mathup}{\um@usv@upgreek,\um@usv@itgreek}{\um@usv@upgreek}
956 \um_set_mathalphabet_char:Nnn{\mathup}{\um@usv@partial,\um@usv@itpartial}{\um@usv@partial}
957 \um_set_mathalphabet_char:Nnn{\mathup}{\um@usv@varepsilon,\um@usv@itvarepsilon}{\um@usv@varepsilon}
958 \um_set_mathalphabet_char:Nnn{\mathup}{\um@usv@vartheta,\um@usv@itvartheta}{\um@usv@vartheta}
959 \um_set_mathalphabet_char:Nnn{\mathup}{\um@usv@varkappa,\um@usv@itvarkappa}{\um@usv@varkappa}
960 \um_set_mathalphabet_char:Nnn{\mathup}{\um@usv@varphi,\um@usv@itvarphi}{\um@usv@varphi}
961 \um_set_mathalphabet_char:Nnn{\mathup}{\um@usv@varrho,\um@usv@itvarrho}{\um@usv@varrho}
962 \um_set_mathalphabet_char:Nnn{\mathup}{\um@usv@varpi,\um@usv@itvarpi}{\um@usv@varpi}
963 }

```

### 7.1.2 Italic: \mathit

Roman:

```

964 \cs_new:Npn \um_config_mathit: {
965 \um_set_mathalphabet_latin:Nnn{\mathit}{\um@usv@upLatin,\um@usv@itLatin}{\um@usv@itLatin}
966 \um_set_mathalphabet_latin:Nnn{\mathit}{\um@usv@uplatin,\um@usv@itlatin}{\um@usv@itlatin}
967 \um_set_mathalphabet_char:Nnn{\mathit}{\`h,\um@usv@ith}{\um@usv@ith}

```

Greek:

```

968 \um_set_mathalphabet_greek:Nnn{\mathit}{\um@usv@upGreek,\um@usv@itGreek}{\um@usv@itGreek}
969 \um_set_mathalphabet_greek:Nnn{\mathit}{\um@usv@upgreek,\um@usv@itgreek}{\um@usv@itgreek}
970 \um_set_mathalphabet_char:Nnn{\mathit}{\um@usv@Nabla,\um@usv@itNabla}{\um@usv@itNabla}
971 \um_set_mathalphabet_char:Nnn{\mathit}{\um@usv@partial,\um@usv@itpartial}{\um@usv@itpartial}
972 \um_set_mathalphabet_char:Nnn{\mathit}{\um@usv@varTheta,\um@usv@itvarTheta}{\um@usv@itvarTheta}
973 \um_set_mathalphabet_char:Nnn{\mathit}{\um@usv@varepsilon,\um@usv@itvarepsilon}{\um@usv@itvarepsilon}
974 \um_set_mathalphabet_char:Nnn{\mathit}{\um@usv@vartheta,\um@usv@itvartheta}{\um@usv@itvartheta}
975 \um_set_mathalphabet_char:Nnn{\mathit}{\um@usv@varkappa,\um@usv@itvarkappa}{\um@usv@itvarkappa}
976 \um_set_mathalphabet_char:Nnn{\mathit}{\um@usv@varphi,\um@usv@itvarphi}{\um@usv@itvarphi}
977 \um_set_mathalphabet_char:Nnn{\mathit}{\um@usv@varrho,\um@usv@itvarrho}{\um@usv@itvarrho}
978 \um_set_mathalphabet_char:Nnn{\mathit}{\um@usv@varpi,\um@usv@itvarpi}{\um@usv@itvarpi}
979 }

```

### 7.1.3 Blackboard or double-struck: \mathbb

```

980 \cs_new:Npn \um_config_mathbb: {
981 \um_set_mathalphabet_numbers:Nnn{\mathbb}{\um@usv@num}{\um@usv@bbnum}
982 \um_set_mathalphabet_latin:Nnn{\mathbb}{\um@usv@upLatin,\um@usv@itLatin}{\um@usv@bbLatin}
983 \um_set_mathalphabet_char:Nnn{\mathbb}{\`C,"1D436}{\`"2102}
984 \um_set_mathalphabet_char:Nnn{\mathbb}{\`H,"1D43B}{\`"210D}

```

```

985 \um_set_mathalphabet_char:Nnn{\mathbb}{`\N,"1D441}{ "2115}
986 \um_set_mathalphabet_char:Nnn{\mathbb}{`\P,"1D443}{ "2119}
987 \um_set_mathalphabet_char:Nnn{\mathbb}{`\Q,"1D444}{ "211A}
988 \um_set_mathalphabet_char:Nnn{\mathbb}{`\R,"1D445}{ "211D}
989 \um_set_mathalphabet_char:Nnn{\mathbb}{`\Z,"1D44D} { "2124}
990 \um_set_mathalphabet_latin:Nnn{\mathbb}{\um@usv@uplatin,\um@usv@itlatin}{\um@usv@bblatin}
991 \um_set_mathalphabet_char:Nnn{\mathbb}{\um@usv@ith} { "1D559}
992 }

```

#### 7.1.4 Script or caligraphic: `\mathscr` and `\mathcal`

```

993 \cs_new:Npn \um_config_mathscr_Latin: {
994   \um_set_mathalphabet_latin:Nnn \mathscr {\um@usv@uplatin,\um@usv@itlatin}{\um@usv@scrLatin}
995   \um_set_mathalphabet_char:Nnn \mathscr {\`\B,"1D435}{ "212C}
996   \um_set_mathalphabet_char:Nnn \mathscr {\`\E,"1D438}{ "2130}
997   \um_set_mathalphabet_char:Nnn \mathscr {\`\F,"1D439}{ "2131}
998   \um_set_mathalphabet_char:Nnn \mathscr {\`\H,"1D43B}{ "210B}
999   \um_set_mathalphabet_char:Nnn \mathscr {\`\I,"1D43C}{ "2110}
1000  \um_set_mathalphabet_char:Nnn \mathscr {\`\L,"1D43F}{ "2112}
1001  \um_set_mathalphabet_char:Nnn \mathscr {\`\M,"1D440}{ "2133}
1002  \um_set_mathalphabet_char:Nnn \mathscr {\`\R,"1D445}{ "211B}
1003 }
1004 \cs_new:Npn \um_config_mathscr_latin: {
1005   \um_set_mathalphabet_latin:Nnn \mathscr {\um@usv@uplatin,\um@usv@itlatin}{\um@usv@scrLatin}
1006   \um_set_mathalphabet_char:Nnn \mathscr {\`\e,"1D452}{ "212F}
1007   \um_set_mathalphabet_char:Nnn \mathscr {\`\g,"1D454}{ "210A}
1008   \um_set_mathalphabet_char:Nnn \mathscr {\`\o,"1D45C}{ "2134}
1009   \um_set_mathalphabet_char:Nnn \mathscr {\um@usv@ith} { "1D4BD}
1010 }

```

#### 7.1.5 Fraktur or fraktur or blackletter: `\mathfrak`

```

1011 \cs_new:Npn \um_config_mathfrak_Latin: {
1012   \um_set_mathalphabet_latin:Nnn \mathfrak {\um@usv@uplatin,\um@usv@itlatin}{\um@usv@frakLatin}
1013   \um_set_mathalphabet_char:Nnn \mathfrak {\`\C,"1D436}{ "212D}
1014   \um_set_mathalphabet_char:Nnn \mathfrak {\`\H,"1D43B}{ "210C}
1015   \um_set_mathalphabet_char:Nnn \mathfrak {\`\I,"1D43C}{ "2111}
1016   \um_set_mathalphabet_char:Nnn \mathfrak {\`\R,"1D445}{ "211C}
1017   \um_set_mathalphabet_char:Nnn \mathfrak {\`\Z,"1D44D}{ "2128}
1018 }
1019 \cs_new:Npn \um_config_mathfrak_latin: {
1020   \um_set_mathalphabet_latin:Nnn \mathfrak {\um@usv@uplatin,\um@usv@itlatin}{\um@usv@frakLatin}
1021   \um_set_mathalphabet_char:Nnn \mathfrak {\um@usv@ith} { "1D525}
1022 }

```

### 7.1.6 Sans serif: \mathsf

<p>0123456789</p> <p>ABCDEFGHIJKLMNOPQRSTUVWXYZ</p> <p>abcdefghijklmnopqrstuvwxyz</p>	<pre>\$\mathsf{0123456789}\$ \\ \$\mathsf{ABCDEFGHIJKLMNOPQRSTUVWXYZ}\$ \\ \$\mathsf{abcdefghijklmnopqrstuvwxyz}\$ \\</pre>
---	---

```

1023 \cs_new:Npn \um_config_mathsf: {
1024   \bool_if:NTF \g_um_sfliteral_bool {
1025     \um_set_mathalphabet_numbers:Nnn{\mathsf}{\um@usv@enum}{\um@usv@sfnum}
1026     \um_set_mathalphabet_latin:Nnn{\mathsf}{\um@usv@upLatin}{\um@usv@sfupLatin}
1027     \um_set_mathalphabet_latin:Nnn{\mathsf}{\um@usv@uplatin}{\um@usv@sfuplatin}
1028     \um_set_mathalphabet_latin:Nnn{\mathsf}{\um@usv@itLatin}{\um@usv@sfitLatin}
1029     \um_set_mathalphabet_latin:Nnn{\mathsf}{\um@usv@itlatin}{\um@usv@sfitlatin}
1030     \um_set_mathalphabet_char:Nnn \mathsf {\um@usv@ith} {"1D629}
1031   }{
1032     \bool_if:NTF \g_um_upsans_bool {
1033       \um_set_mathalphabet_numbers:Nnn \mathsf {\um@usv@enum}{\um@usv@sfnum}
1034       \um_set_mathalphabet_latin:Nnn \mathsf {\um@usv@upLatin,\um@usv@itLatin}{\um@usv@sfupLatin}
1035       \um_set_mathalphabet_latin:Nnn \mathsf {\um@usv@uplatin,\um@usv@itlatin}{\um@usv@sfuplatin}
1036       \um_set_mathalphabet_char:Nnn \mathsf {\um@usv@ith} {"1D5C1}
1037     }{
1038       \um_set_mathalphabet_numbers:Nnn \mathsf {\um@usv@enum}{\um@usv@sfnum}
1039       \um_set_mathalphabet_latin:Nnn \mathsf {\um@usv@upLatin,\um@usv@itLatin}{\um@usv@sfitLatin}
1040       \um_set_mathalphabet_latin:Nnn \mathsf {\um@usv@uplatin,\um@usv@itlatin}{\um@usv@sfitlatin}
1041       \um_set_mathalphabet_char:Nnn \mathsf {\um@usv@ith} {"1D629}
1042     }
1043   }
1044 }
```

### 7.1.7 Sans serif upright: \mathsfup

```

1045 \cs_new:Npn \um_config_mathsfup: {
1046   \um_set_mathalphabet_numbers:Nnn{\mathsfup}{\um@usv@enum}{\um@usv@sfnum}
1047   \um_set_mathalphabet_latin:Nnn{\mathsfup}{\um@usv@upLatin,\um@usv@itLatin}{\um@usv@sfupLatin}
1048   \um_set_mathalphabet_latin:Nnn{\mathsfup}{\um@usv@uplatin,\um@usv@itlatin}{\um@usv@sfuplatin}
1049   \um_set_mathalphabet_char:Nnn \mathsfup {\um@usv@ith} {"1D5C1}
1050 }
```

### 7.1.8 Sans serif italic: \mathsfit

Map the numbers like that because it seems sensible.

```

1051 \cs_new:Npn \um_config_mathsfit: {
1052   \um_set_mathalphabet_numbers:Nnn{\mathsfit}{\um@usv@enum}{\um@usv@sfnum}
1053   \um_set_mathalphabet_latin:Nnn{\mathsfit}{\um@usv@upLatin,\um@usv@itLatin}{\um@usv@sfitLatin}
1054   \um_set_mathalphabet_latin:Nnn{\mathsfit}{\um@usv@uplatin,\um@usv@itlatin}{\um@usv@sfitlatin}
1055   \um_set_mathalphabet_char:Nnn \mathsfit {\um@usv@ith} {"1D629}
```

1056 }

### 7.1.9 Typewriter or monospaced: `\mathtt`

```
1057 \cs_new:Npn \um_config_mathtt: {  
1058   \um_set_mathalphabet_numbers:Nnn{\mathtt}{\um@usv@num}{\um@usv@ttnum}  
1059   \um_set_mathalphabet_latin:Nnn{\mathtt}{\um@usv@upLatin,\um@usv@itLatin}{\um@usv@ttLatin}  
1060   \um_set_mathalphabet_latin:Nnn{\mathtt}{\um@usv@uplatin,\um@usv@itlatin}{\um@usv@ttlLatin}  
1061   \um_set_mathalphabet_char:Nnn \mathtt {\um@usv@ith} {"1D691}  
1062 }
```

## 7.2 Bold math alphabets

### 7.2.1 Bold: `\mathbf`

**0123456789**  
**ABCDEFGHIJKLMNOPQRSTUVWXYZ**  
**abcdefghijklmnopqrstuvwxyz**  
**ΑΒΓΔΕΖΗΘΙΚΑΜΝΞΟΠΡΣΤΥΦΧΨΩ**  
**Θ**  
**αβγδεζηθικλμνξοπρστυφχψω**  
**εθκφρ**

```
 $\mathbf{0123456789}$   
 $\mathbf{ABCDEFGHIJKLMNOPQRSTUVWXYZ}$   
 $\mathbf{abcdefghijklmnopqrstuvwxyz}$   
 $\mathbf{\Theta}$   
 $\mathbf{\alpha\beta\gamma\delta\epsilon\zeta\eta\theta\iota\kappa\lambda\mu\nu\xi\omicron\rho\sigma\tau\upsilon\phi\chi\psi\omega}$   
 $\mathbf{\epsilon\theta\kappa\phi\rho}$ 
```

```
1063 \cs_new:Npn \um_config_mathbf: {  
1064   \um_set_mathalphabet_numbers:Nnn{\mathbf}{\um@usv@num}{\um@usv@bfnum}  
1065   \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@Digamma}"1D7CA}  
1066   \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@edigamma}"1D7CB}  
1067   \if@um@bfliteral  
1068     \um_set_mathalphabet_latin:Nnn{\mathbf}{\um@usv@upLatin}{\um@usv@bfupLatin}  
1069     \um_set_mathalphabet_latin:Nnn{\mathbf}{\um@usv@itLatin}{\um@usv@bfitLatin}  
1070     \um_set_mathalphabet_latin:Nnn{\mathbf}{\um@usv@uplatin}{\um@usv@bfuplatin}  
1071     \um_set_mathalphabet_latin:Nnn{\mathbf}{\um@usv@itlatin}{\um@usv@bfitlatin}  
1072     \um_set_mathalphabet_greek:Nnn{\mathbf}{\um@usv@upGreek}{\um@usv@bfupGreek}  
1073     \um_set_mathalphabet_greek:Nnn{\mathbf}{\um@usv@itGreek}{\um@usv@bfitGreek}  
1074     \um_set_mathalphabet_greek:Nnn{\mathbf}{\um@usv@upgreek}{\um@usv@bfupgreek}  
1075     \um_set_mathalphabet_greek:Nnn{\mathbf}{\um@usv@itgreek}{\um@usv@bfitgreek}  
1076     \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@ith}{\um@usv@bfith}  
1077     \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@varTheta}{\um@usv@bfvarTheta}  
1078     \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@Nabla}{\um@usv@bfNabla}  
1079     \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@Digamma}{\um@usv@bfDigamma}  
1080     \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@partial}{\um@usv@bfpartial}  
1081     \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@varepsilon}{\um@usv@bfvarepsilon}  
1082     \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@vartheta}{\um@usv@bfvartheta}  
1083     \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@varkappa}{\um@usv@bfvarkappa}  
1084     \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@varphi}{\um@usv@bfvarphi}
```

```

1085 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@varrho}{\um@usv@bfvarrho}
1086 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@varpi}{\um@usv@bfvarpi}
1087 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@digamma}{\um@usv@bfdigamma}
1088 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@itvarTheta}{\um@usv@bfitvarTheta}
1089 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@itNabla}{\um@usv@bfitNabla}
1090 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@itpartial}{\um@usv@bfitpartial}
1091 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@itvarepsilon}{\um@usv@bfitvarepsilon}
1092 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@itvartheta}{\um@usv@bfitvartheta}
1093 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@itvarkappa}{\um@usv@bfitvarkappa}
1094 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@itvarphi}{\um@usv@bfitvarphi}
1095 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@itvarrho}{\um@usv@bfitvarrho}
1096 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@itvarpi}{\um@usv@bfitvarpi}
1097 \else
1098 \ifum@bfupLatin
1099 \um_set_mathalphabet_latin:Nnn{\mathbf}{\um@usv@upLatin,\um@usv@itLatin}{\um@usv@bfupLatin}
1100 \else
1101 \um_set_mathalphabet_latin:Nnn{\mathbf}{\um@usv@upLatin,\um@usv@itLatin}{\um@usv@bfitLatin}
1102 \fi
1103 \ifum@bfuplatin
1104 \um_set_mathalphabet_latin:Nnn{\mathbf}{\um@usv@uplatin,\um@usv@itlatin}{\um@usv@bfuplatin}
1105 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@ith}{\um@usv@bfuph}
1106 \else
1107 \um_set_mathalphabet_latin:Nnn{\mathbf}{\um@usv@uplatin,\um@usv@itlatin}{\um@usv@bfitlatin}
1108 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@ith}{\um@usv@bfith}
1109 \fi
1110 \ifum@bfupGreek
1111 \um_set_mathalphabet_greek:Nnn{\mathbf}{\um@usv@upGreek,\um@usv@itGreek}{\um@usv@bfupGreek}
1112 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@varTheta,\um@usv@itvarTheta}{\um@usv@bfvarT}
1113 \else
1114 \um_set_mathalphabet_greek:Nnn{\mathbf}{\um@usv@upGreek,\um@usv@itGreek}{\um@usv@bfitGreek}
1115 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@varTheta,\um@usv@itvarTheta}{\um@usv@bfitva}
1116 \fi
1117 \ifum@bfupgreek
1118 \um_set_mathalphabet_greek:Nnn{\mathbf}{\um@usv@upgreek,\um@usv@itgreek}{\um@usv@bfupgreek}
1119 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@varepsilon,\um@usv@itvarepsilon}{\um@usv@bf}
1120 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@vartheta,\um@usv@itvartheta}{\um@usv@bfvart}
1121 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@varkappa,\um@usv@itvarkappa}{\um@usv@bfvark}
1122 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@varphi,\um@usv@itvarphi}{\um@usv@bfvarphi}
1123 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@varrho,\um@usv@itvarrho}{\um@usv@bfvarrho}
1124 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@varpi,\um@usv@itvarpi}{\um@usv@bfvarpi}
1125 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@partial,\um@usv@itpartial}{\um@usv@bfpartia}
1126 \else
1127 \um_set_mathalphabet_greek:Nnn{\mathbf}{\um@usv@upgreek,\um@usv@itgreek}{\um@usv@bfitgreek}
1128 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@varepsilon,\um@usv@itvarepsilon}{\um@usv@bf}
1129 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@vartheta,\um@usv@itvartheta}{\um@usv@bfitva}
1130 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@varkappa,\um@usv@itvarkappa}{\um@usv@bfitva}

```

```

1131 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@varphi,\um@usv@itvarphi}{\um@usv@bfitvarphi}
1132 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@varrho,\um@usv@itvarrho}{\um@usv@bfitvarrho}
1133 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@varpi,\um@usv@itvarpi}{\um@usv@bfitvarpi}
1134 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@partial,\um@usv@itpartial}{\um@usv@bfitpart
1135 \fi
1136 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@Nabla,\um@usv@itNabla}{\um@bfitNabla_up_or_it
1137 \um_set_mathalphabet_char:Nnn{\mathbf}{\um@usv@partial,\um@usv@itpartial}{\um@bfitpartial_up_
1138 \fi
1139 }

```

## 7.2.2 Bold Italic: `\mathbfi`

```

1140 \cs_new:Npn \um_config_mathbfif: {
1141   \um_set_mathalphabet_numbers:Nnn{\mathbfi}{\um@usv@enum}{\um@usv@bfnun}
1142   \um_set_mathalphabet_latin:Nnn{\mathbfi}{\um@usv@upLatin,\um@usv@itLatin}{\um@usv@bfitLatin}
1143   \um_set_mathalphabet_latin:Nnn{\mathbfi}{\um@usv@uplatin,\um@usv@itlatin}{\um@usv@bfitlatin}
1144   \um_set_mathalphabet_char:Nnn{\mathbfi}{\um@usv@ith} {"1D489}
1145   \um_set_mathalphabet_greek:Nnn{\mathbfi}{\um@usv@upGreek,\um@usv@itGreek}{\um@usv@bfitGreek}
1146   \um_set_mathalphabet_greek:Nnn{\mathbfi}{\um@usv@upgreek,\um@usv@itgreek}{\um@usv@bfitgreek}
1147   \um_set_mathalphabet_char:Nnn{\mathbfi}{\um@usv@varTheta,\um@usv@itvarTheta}{\um@usv@bfitvar}
1148   \um_set_mathalphabet_char:Nnn{\mathbfi}{\um@usv@Nabla,\um@usv@itNabla}{\um@usv@bfitNabla}
1149   \um_set_mathalphabet_char:Nnn{\mathbfi}{\um@usv@partial,\um@usv@itpartial}{\um@usv@bfitpart}
1150   \um_set_mathalphabet_char:Nnn{\mathbfi}{\um@usv@varepsilon,\um@usv@itvarepsilon}{\um@usv@bf}
1151   \um_set_mathalphabet_char:Nnn{\mathbfi}{\um@usv@vartheta,\um@usv@itvartheta}{\um@usv@bfitvar}
1152   \um_set_mathalphabet_char:Nnn{\mathbfi}{\um@usv@varkappa,\um@usv@itvarkappa}{\um@usv@bfitvar}
1153   \um_set_mathalphabet_char:Nnn{\mathbfi}{\um@usv@varphi,\um@usv@itvarphi}{\um@usv@bfitvarphi}
1154   \um_set_mathalphabet_char:Nnn{\mathbfi}{\um@usv@varrho,\um@usv@itvarrho}{\um@usv@bfitvarrho}
1155   \um_set_mathalphabet_char:Nnn{\mathbfi}{\um@usv@varpi,\um@usv@itvarpi}{\um@usv@bfitvarpi}
1156 }

```

## 7.2.3 Bold Italic: `\mathbfup`

```

1157 \cs_new:Npn \um_config_mathbfup: {
1158   \um_set_mathalphabet_numbers:Nnn{\mathbfup}{\um@usv@enum}{\um@usv@bfnun}
1159   \um_set_mathalphabet_latin:Nnn{\mathbfup}{\um@usv@upLatin,\um@usv@itLatin}{\um@usv@bfupLatin}
1160   \um_set_mathalphabet_latin:Nnn{\mathbfup}{\um@usv@uplatin,\um@usv@itlatin}{\um@usv@bfuplatin}
1161   \um_set_mathalphabet_char:Nnn{\mathbfup}{\um@usv@ith} {"1D421}
1162   \um_set_mathalphabet_greek:Nnn{\mathbfup}{\um@usv@upGreek,\um@usv@itGreek}{\um@usv@bfupGreek}
1163   \um_set_mathalphabet_greek:Nnn{\mathbfup}{\um@usv@upgreek,\um@usv@itgreek}{\um@usv@bfupgreek}
1164   \um_set_mathalphabet_char:Nnn{\mathbfup}{\um@usv@varTheta,\um@usv@itvarTheta}{\um@usv@bfvarTh}
1165   \um_set_mathalphabet_char:Nnn{\mathbfup}{\um@usv@Nabla,\um@usv@itNabla}{\um@usv@bfNabla}
1166   \um_set_mathalphabet_char:Nnn{\mathbfup}{\um@usv@partial,\um@usv@itpartial}{\um@usv@bfpartial}
1167   \um_set_mathalphabet_char:Nnn{\mathbfup}{\um@usv@varepsilon,\um@usv@itvarepsilon}{\um@usv@bf}
1168   \um_set_mathalphabet_char:Nnn{\mathbfup}{\um@usv@vartheta,\um@usv@itvartheta}{\um@usv@bfvarth}
1169   \um_set_mathalphabet_char:Nnn{\mathbfup}{\um@usv@varkappa,\um@usv@itvarkappa}{\um@usv@bfvarka}
1170   \um_set_mathalphabet_char:Nnn{\mathbfup}{\um@usv@varphi,\um@usv@itvarphi}{\um@usv@bfvarphi}
1171   \um_set_mathalphabet_char:Nnn{\mathbfup}{\um@usv@varrho,\um@usv@itvarrho}{\um@usv@bfvarrho}
1172   \um_set_mathalphabet_char:Nnn{\mathbfup}{\um@usv@varpi,\um@usv@itvarpi}{\um@usv@bfvarpi}

```

1173 }

#### 7.2.4 Bold fractur or fraktur or blackletter: `\mathbffrak`

```
1174 \cs_new:Npn \um_config_mathbffrak: {
1175   \um_set_mathalphabet_numbers:Nnn{\mathbffrak}{\um@usv@num}{\um@usv@bfnun}
1176   \um_set_mathalphabet_latin:Nnn{\mathbffrak}{\um@usv@upLatin, \um@usv@itLatin, \um@usv@frakLatin}
1177   \um_set_mathalphabet_latin:Nnn{\mathbffrak}{\um@usv@uplatin, \um@usv@itlatin, \um@usv@fraklatin}
1178   \um_set_mathalphabet_char:Nnn{\mathbffrak}{\um@usv@ith} {"1D58D}
1179 }
```

#### 7.2.5 Bold script or calligraphic: `\mathbfscr`

```
1180 \cs_new:Npn \um_config_mathbfscr: {
1181   \um_set_mathalphabet_numbers:Nnn{\mathbfscr}{\um@usv@num}{\um@usv@bfnun}
1182   \um_set_mathalphabet_latin:Nnn{\mathbfscr}{\um@usv@upLatin, \um@usv@itLatin}{\um@usv@bfscrLatin}
1183   \um_set_mathalphabet_latin:Nnn{\mathbfscr}{\um@usv@uplatin, \um@usv@itlatin}{\um@usv@bfscrlatin}
1184   \um_set_mathalphabet_char:Nnn{\mathbfscr}{\um@usv@ith} {"1D4F1}
1185 }
```

#### 7.2.6 Bold sans serif: `\mathbfsf`

0123456789  
 ABCDEFGHIJKLMNOPQRSTUVWXYZ  
 abcdefghijklmnopqrstuvwxyz  
 ΑΒΓΔΕΖΗΘΙΚΛΜΝΞΟΠΡΣΤΥΦΧΨΩ Θ  
 αβγδεζηθικλμνξοπρστυφχψω εδκφρϖ

```
\setmathfont{STIXGeneral-Bold}
$\mathbfsf{0123456789}$ \\\
$\mathbfsf{ABCDEFGHIJKLMNOPQRSTUVWXYZ}$ \\\
$\mathbfsf{abcdefghijklmnopqrstuvwxyz}$ \\\
$\mathbfsf{ }$ \quad
$\mathbfsf{ }$ \\\
$\mathbfsf{ }$ \quad
$\mathbfsf{ }$ \\\
```

These use the sans-style settings rather than bold-style.  
 Numbers (always upright) and letters:

```
1186 \cs_new:Npn \um_config_mathbfsf: {
1187   \bool_if:NTF \g_um_sf_literal_bool {
1188     \um_set_mathalphabet_numbers:Nnn \mathbfsf {\um@usv@num}{\um@usv@bfsfnum}
1189     \um_set_mathalphabet_latin:Nnn \mathbfsf {\um@usv@upLatin}{\um@usv@bfsfupLatin}
1190     \um_set_mathalphabet_latin:Nnn \mathbfsf {\um@usv@uplatin}{\um@usv@bfsfuplatin}
1191     \um_set_mathalphabet_latin:Nnn \mathbfsf {\um@usv@itLatin}{\um@usv@bfsfitLatin}
1192     \um_set_mathalphabet_latin:Nnn \mathbfsf {\um@usv@itlatin}{\um@usv@bfsfitlatin}
1193     \um_set_mathalphabet_char:Nnn \mathbfsf{\um@usv@ith} {"1D65D}
1194     \um_set_mathalphabet_greek:Nnn \mathbfsf {\um@usv@upGreek}{\um@usv@bfsfupGreek}
1195     \um_set_mathalphabet_greek:Nnn \mathbfsf {\um@usv@upgreek}{\um@usv@bfsfupgreek}
1196     \um_set_mathalphabet_greek:Nnn \mathbfsf {\um@usv@itGreek}{\um@usv@bfsfitGreek}
1197     \um_set_mathalphabet_greek:Nnn \mathbfsf {\um@usv@itgreek}{\um@usv@bfsfitgreek}
1198     \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@varTheta} {"1D767}
1199     \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@Nabla} {"1D76F}
1200     \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@partial} {"1D789}
1201     \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@varepsilon} {"1D78A}
1202     \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@vartheta} {"1D78B}
```

```

1203 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@varkappa}{1D78C}
1204 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@varphi}{1D78D}
1205 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@varrho}{1D78E}
1206 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@varpi}{1D78F}
1207 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@varTheta}{1D7A1}
1208 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@itNabla}{\um@usv@bfsfitNabla}
1209 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@itpartial}{\um@usv@bfsfitpartial}
1210 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@itvarepsilon}{1D7C4}
1211 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@itvartheta}{1D7C5}
1212 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@itvarkappa}{1D7C6}
1213 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@itvarphi}{1D7C7}
1214 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@itvarrho}{1D7C8}
1215 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@itvarpi}{1D7C9}
1216 }{
1217 \bool_if:NTF \g_um_upsans_bool {
1218 \um_set_mathalphabet_numbers:Nnn \mathbfsf {\um@usv@enum}{\um@usv@bfsfnum}
1219 \um_set_mathalphabet_latin:Nnn \mathbfsf {\um@usv@upLatin,\um@usv@itLatin}{\um@usv@bfsfup
1220 \um_set_mathalphabet_latin:Nnn \mathbfsf {\um@usv@uplatin,\um@usv@itlatin}{\um@usv@bfsfup
1221 \um_set_mathalphabet_char:Nnn \mathbfsf{\um@usv@ith} {1D5F5}
1222 \um_set_mathalphabet_greek:Nnn \mathbfsf {\um@usv@upGreek,\um@usv@itGreek}{\um@usv@bfsfup
1223 \um_set_mathalphabet_greek:Nnn \mathbfsf {\um@usv@upgreek,\um@usv@itgreek}{\um@usv@bfsfup
1224 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@varTheta,\um@usv@itvarTheta}{1D767}
1225 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@Nabla,\um@usv@itNabla}{1D76F}
1226 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@partial,\um@usv@itpartial}{1D789}
1227 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@varepsilon,\um@usv@itvarepsilon}{1D78A}
1228 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@vartheta,\um@usv@itvartheta}{1D78B}
1229 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@varkappa,\um@usv@itvarkappa}{1D78C}
1230 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@varphi,\um@usv@itvarphi}{1D78D}
1231 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@varrho,\um@usv@itvarrho}{1D78E}
1232 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@varpi,\um@usv@itvarpi}{1D78F}
1233 }{
1234 \um_set_mathalphabet_numbers:Nnn \mathbfsf {\um@usv@enum}{\um@usv@bfsfnum}
1235 \um_set_mathalphabet_latin:Nnn \mathbfsf {\um@usv@upLatin,\um@usv@itLatin}{\um@usv@bfsfit
1236 \um_set_mathalphabet_latin:Nnn \mathbfsf {\um@usv@uplatin,\um@usv@itlatin}{\um@usv@bfsfit
1237 \um_set_mathalphabet_char:Nnn \mathbfsf{\um@usv@ith} {1D65D}
1238 \um_set_mathalphabet_greek:Nnn \mathbfsf {\um@usv@upGreek,\um@usv@itGreek}{\um@usv@bfsfit
1239 \um_set_mathalphabet_greek:Nnn \mathbfsf {\um@usv@upgreek,\um@usv@itgreek}{\um@usv@bfsfit
1240 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@varTheta}{1D7A1}
1241 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@Nabla,\um@usv@itNabla}{\um@usv@bfsfitNab
1242 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@partial,\um@usv@itpartial}{\um@usv@bfsf
1243 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@varepsilon,\um@usv@itvarepsilon}{1D7C4}
1244 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@vartheta,\um@usv@itvartheta}{1D7C5}
1245 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@varkappa,\um@usv@itvarkappa}{1D7C6}
1246 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@varphi,\um@usv@itvarphi}{1D7C7}
1247 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@varrho,\um@usv@itvarrho}{1D7C8}
1248 \um_set_mathalphabet_char:Nnn \mathbfsf {\um@usv@varpi,\um@usv@itvarpi}{1D7C9} }

```



```

1249 }
1250 }

```

### 7.2.7 Bold upright sans serif: `\mathbfsfup`

```

1251 \cs_new:Npn \um_config_mathbfsfup: {
1252   \um_set_mathalphabet_numbers:Nnn{\mathbfsfup}{\um@usv@enum}{\um@usv@bfsfnum}
1253   \um_set_mathalphabet_latin:Nnn{\mathbfsfup}{\um@usv@upLatin,\um@usv@itLatin}{\um@usv@bfsfupLa
1254   \um_set_mathalphabet_latin:Nnn{\mathbfsfup}{\um@usv@uplatin,\um@usv@itlatin}{\um@usv@bfsfupla
1255   \um_set_mathalphabet_char:Nnn \mathbfsfup {\um@usv@ith} {"1D5F5}
1256   \um_set_mathalphabet_greek:Nnn{\mathbfsfup}{\um@usv@upGreek,\um@usv@itGreek}{\um@usv@bfsfupGr
1257   \um_set_mathalphabet_greek:Nnn{\mathbfsfup}{\um@usv@upgreek,\um@usv@itgreek}{\um@usv@bfsfupgr
1258   \um_set_mathalphabet_char:Nnn{\mathbfsfup}{\um@usv@varTheta,\um@usv@itvarTheta}{ "1D767}
1259   \um_set_mathalphabet_char:Nnn{\mathbfsfup}{\um@usv@Nabla,\um@usv@itNabla}{ "1D76F}
1260   \um_set_mathalphabet_char:Nnn{\mathbfsfup}{\um@usv@partial,\um@usv@itpartial}{ "1D789}
1261   \um_set_mathalphabet_char:Nnn{\mathbfsfup}{\um@usv@varepsilon,\um@usv@itvarepsilon}{ "1D78A}
1262   \um_set_mathalphabet_char:Nnn{\mathbfsfup}{\um@usv@vartheta,\um@usv@itvartheta}{ "1D78B}
1263   \um_set_mathalphabet_char:Nnn{\mathbfsfup}{\um@usv@varkappa,\um@usv@itvarkappa}{ "1D78C}
1264   \um_set_mathalphabet_char:Nnn{\mathbfsfup}{\um@usv@varphi,\um@usv@itvarphi}{ "1D78D}
1265   \um_set_mathalphabet_char:Nnn{\mathbfsfup}{\um@usv@varrho,\um@usv@itvarrho}{ "1D78E}
1266   \um_set_mathalphabet_char:Nnn{\mathbfsfup}{\um@usv@varpi,\um@usv@itvarpi}{ "1D78F}
1267 }

```

### 7.2.8 Bold italic sans serif: `\mathbfsfit`

```

1268 \cs_new:Npn \um_config_mathbfsfit: {
1269   \um_set_mathalphabet_numbers:Nnn{\mathbfsfit}{\um@usv@enum}{\um@usv@bfsfnum}
1270   \um_set_mathalphabet_latin:Nnn{\mathbfsfit}{\um@usv@upLatin,\um@usv@itLatin}{\um@usv@bfsfitLa
1271   \um_set_mathalphabet_latin:Nnn{\mathbfsfit}{\um@usv@uplatin,\um@usv@itlatin}{\um@usv@bfsfitla
1272   \um_set_mathalphabet_char:Nnn \mathbfsfit {\um@usv@ith} {"1D65D}
1273   \um_set_mathalphabet_greek:Nnn{\mathbfsfit}{\um@usv@upGreek,\um@usv@itGreek}{\um@usv@bfsfitGr
1274   \um_set_mathalphabet_greek:Nnn{\mathbfsfit}{\um@usv@upgreek,\um@usv@itgreek}{\um@usv@bfsfitgr
1275   \um_set_mathalphabet_char:Nnn{\mathbfsfit}{\um@usv@varTheta}{ "1D7A1}
1276   \um_set_mathalphabet_char:Nnn{\mathbfsfit}{\um@usv@Nabla,\um@usv@itNabla}{\um@usv@bfsfitNabla
1277   \um_set_mathalphabet_char:Nnn{\mathbfsfit}{\um@usv@partial,\um@usv@itpartial}{\um@usv@bfsfitp
1278   \um_set_mathalphabet_char:Nnn{\mathbfsfit}{\um@usv@varepsilon,\um@usv@itvarepsilon}{ "1D7C4}
1279   \um_set_mathalphabet_char:Nnn{\mathbfsfit}{\um@usv@vartheta,\um@usv@itvartheta}{ "1D7C5}
1280   \um_set_mathalphabet_char:Nnn{\mathbfsfit}{\um@usv@varkappa,\um@usv@itvarkappa}{ "1D7C6}
1281   \um_set_mathalphabet_char:Nnn{\mathbfsfit}{\um@usv@varphi,\um@usv@itvarphi}{ "1D7C7}
1282   \um_set_mathalphabet_char:Nnn{\mathbfsfit}{\um@usv@varrho,\um@usv@itvarrho}{ "1D7C8}
1283   \um_set_mathalphabet_char:Nnn{\mathbfsfit}{\um@usv@varpi,\um@usv@itvarpi}{ "1D7C9}
1284 }

```

## 7.3 Definitions of the math symbols

Here we define every unicode math codepoint an equivalent macro name. The two are equivalent, in a `\let\xyz=^^^1234` kind of way.

`\um@scancharlet` We need to do some trickery to transform the `\UnicodeMathSymbol` argument  
`\um@scanactivedef` "ABCDEF into the X<sub>Y</sub>TeX 'caret input' form `^^^^^abcdef`. It is *very important* that  
the argument has five characters. Otherwise we need to change the number of `^`  
chars.

To do this, turn `^` into a regular 'other' character and define the macro to  
perform the lowercasing and `\let`. `\scantokens` changes the carets back into their  
original meaning after the group has ended and `^`'s catcode returns to normal.

```
1285 \begingroup
1286   \char_make_other:N \^
1287   \cs_gset:Npn \um@scancharlet#1="#2\@nil {
1288     \lowercase{
1289       \scantokens{\global\let#1=^^^^^#2}
1290     }
1291   }
```

Making `^` the right catcode isn't strictly necessary right now but it helps to future  
proof us with, e.g., `breqn`.

```
1292   \gdef\um@scanactivedef"#1\@nil#2{
1293     \lowercase{
1294       \tl_rescan:nn{
1295         \ExplSyntaxOn
1296         \char_make_math_superscript:N\^
1297       }{
1298         \global\def^^^^^#1{#2}
1299       }
1300     }
1301   }
1302 \endgroup
```

Now give `\UnicodeMathSymbol` a definition in terms of `\um@scancharlet` and  
we're good to go. Make sure `#` is an 'other' so that we don't get confused with  
`\mathoctothorpe`.

```
1303 \begingroup
1304   \def\UnicodeMathSymbol#1#2#3#4{
1305     \um@scancharlet#2=#1\@nil
1306   }
1307   \char_make_other:N \#
1308   \@input{unicode-math-table.tex}
1309 \endgroup
```

Fix `\backslash`:

```
1310 \group_begin:
1311   \lccode`\*='\
1312   \char_make_escape:N \|
1313   \char_make_other:N \
1314   |lowercase{
1315 |group_end: |let|backslash=*
```

## 8 Epilogue

Lots of little things to tidy up.

### 8.0.1 Primes

We need a new ‘prime’ algorithm. Unicode math has four pre-drawn prime glyphs.

```
U+2032: PRIME (\primesingle): x'
U+2033: DOUBLE PRIME (\primedouble): x''
U+2034: TRIPLE PRIME (\primetripel): x'''
U+2057: QUADRUPLE PRIME (\primequadruple): x''''
```

As you can see, they’re all drawn at the correct height without being superscripted. However, in a correctly behaviour OpenType font with the MATH table, we also see different behaviour after the ssty feature is applied:

```
U+2032: PRIME in the ‘scriptstyle’ font: xʹ
```

The shrinking and offsetting is done as it is turned into a superscript. This means, luckily, that by default things work nicely for single primes. We can write `x\primesingle` or `x^\primesingle` and get: `xʹ` and `xʹ`. To support single primes, then, things are easier than in L<sup>A</sup>T<sub>E</sub>X; we can just map ‘ to \prime and not worry about it.

However, it would be nice to use the pre-composed primes above if they exist in the font; consider `x'''` vs. `x'''`. Our algorithm is

- Prime encountered; pcount=1.
- Scan ahead; if prime: pcount:=pcount+1; repeat.
- If not prime, stop scanning.
- If pcount=1, \prime, end.
- If pcount=2, check \primedouble; if it exists, use it, end; if not, goto last step.
- Ditto pcount=3 & \primetripel.
- Ditto pcount=4 & \primequadruple.
- If pcount>4 or the glyph doesn’t exist, insert pcount \primes with \primekern between each.

```
1316 \muskip_new:N \g_um_primekern_muskip
1317 \muskip_gset:Nn \g_um_primekern_muskip { -\thinmuskip/2 }% arbitrary
1318 \num_new:N \l_um_primecount_num
```

```

1319 \cs_new:Nn \um_nprimes:n {
1320   ^{
1321     \primesingle
1322     \prg_replicate:nn {#1-1} { \mskip \g_um_primekern_muskip \primesingle }
1323   }
1324 }
1325 \cs_new:Nn \um_nprimes_select:n {
1326   \prg_case_int:nnn {#1}{
1327     {1} { ^{\primesingle} }
1328     {2} {
1329       \um_glyph_if_exist:nTF {"2033} { ^{\primedouble} } {\um_nprimes:n {#1}}
1330     }
1331     {3} {
1332       \um_glyph_if_exist:nTF {"2034} { ^{\primetriple} } {\um_nprimes:n {#1}}
1333     }
1334     {4} {
1335       \um_glyph_if_exist:nTF {"2057} { ^{\primequadruple} } {\um_nprimes:n {#1}}
1336     }
1337   }{
1338     \um_nprimes:n {#1}
1339   }
1340 }

```

Scanning is more annoying than you'd think because we want to support all three of \prime, ', and the unicode prime. And \ifx doesn't work with mathactive chars.

```

1341 \cs_new:Nn \um_scanprime: {
1342   \num_zero:N \l_um_primecount_num
1343   \um_scanprime_collect:
1344 }
1345 \cs_new:Nn \um_scanprime_collect: {
1346   \num_incr:N \l_um_primecount_num
1347   \peek_meaning_remove:NTF ' {
1348     \um_scanprime_collect:
1349   }{
1350     \peek_meaning_remove:NTF \um_scanprime: {
1351       \um_scanprime_collect:
1352     }{
1353       \peek_meaning_remove:NTF ^^^^2032 {
1354         \um_scanprime_collect:
1355       }{
1356         \um_nprimes_select:n {\l_um_primecount_num}
1357       }
1358     }
1359   }
1360 }

```

```

1361 \cs_set_eq:NN \prime \um_scanprime:
1362 \group_begin:
1363   \char_make_active:N \prime
1364   \char_make_active:n {"2032}
1365   \cs_gset_eq:NN \prime \um_scanprime:
1366   \cs_gset_eq:NN \prime \um_scanprime:
1367 \group_end:

```

## 8.0.2 Unicode radicals

Undo the damage made to `\sqrt`:

```

1368 \DeclareRobustCommand\sqrt{\@ifnextchar[\@sqrt\sqrtsign}

```

`\r@@t` #1 : A mathstyle (for `\mathpalette`)  
 #2 : Leading superscript for the sqrt sign  
 A re-implementation of L<sup>A</sup>T<sub>E</sub>X's hard-coded n-root sign using the appropriate `\fontdimens`.

```

1369 \def\r@@t#1#2{
1370   \setbox\z@\hbox{$\mathstyle #1\sqrtsign{#2}$}
1371   \um@scaled@apply{#1}{\kern}{\fontdimen63\um@font}
1372   \raise \dimexpr(
1373     \um@fontdimen@percent{65}{\um@font}\ht\z@-
1374     \um@fontdimen@percent{65}{\um@font}\dp\z@
1375   )\relax
1376   \copy \rootbox
1377   \um@scaled@apply{#1}{\kern}{\fontdimen64\um@font}
1378   \box \z@
1379 }

```

## 8.0.3 Unicode sub- and super-scripts

The idea here is to enter a scanning state after a superscript or subscript is encountered. If subsequent superscripts or subscripts (resp.) are found, they are lumped together. Each sub/super has a corresponding regular size glyph which is used by X<sub>Y</sub>L<sup>A</sup>T<sub>E</sub>X to typeset the results; this means that the actual subscript/superscript glyphs are never seen in the output document — they are only used as input characters.

Open question: should the superscript-like ‘modifiers’ (U+1D2C: MODIFIER CAPITAL LETTER A and on) be included here?

First, the setup of each mathactive char:

```

1380 \prop_new:N \g_um_supers_prop
1381 \prop_new:N \g_um_subs_prop
1382 \cs_generate_variant:Nn \prop_gput:Nnn {Nxn}
1383 \cs_generate_variant:Nn \prop_get:NnN {cxN}
1384 \cs_generate_variant:Nn \prop_if_in:NnTF {cx}

```

```

1385
1386 \group_begin:
1387
1388 % Populate a property list with superscript characters; their mean-
1389 % ing as their key,
1390 % for reasons that will become apparent soon, and their replace-
1391 % ment as each key's value.
1392 % Then make the superscript active and bind it to the scanning function.
1393 %
1394 % \cs{scantokens} makes this process much simpler since we can acti-
1395 % vate the char
1396 % and assign its meaning in one step.
1397 \cs_set:Nn \um_setup_active_superscript:nn {
1398   \prop_gput:Nxn \g_um_supers_prop {\meaning #1} {#2}
1399   \char_make_active:n {'#1}
1400   \global\XeTeXmathcodenum '#1 = "1FFFFF \scan_stop:
1401   \scantokens{
1402     \cs_gset:Npn #1 {
1403       \tl_set:Nn \l_um_ss_chain_tl {#2}
1404       \cs_set_eq:NN \um_sub_or_super:n \sp
1405       \tl_set:Nn \l_um_tmpa_tl {supers}
1406       \um_scan_sscript:
1407     }
1408   }
1409 }
1410
1411 \um_setup_active_superscript:nn {^^^2070} {0}
1412 \um_setup_active_superscript:nn {^^^00b9} {1}
1413 \um_setup_active_superscript:nn {^^^00b2} {2}
1414 \um_setup_active_superscript:nn {^^^00b3} {3}
1415 \um_setup_active_superscript:nn {^^^2074} {4}
1416 \um_setup_active_superscript:nn {^^^2075} {5}
1417 \um_setup_active_superscript:nn {^^^2076} {6}
1418 \um_setup_active_superscript:nn {^^^2077} {7}
1419 \um_setup_active_superscript:nn {^^^2078} {8}
1420 \um_setup_active_superscript:nn {^^^2079} {9}
1421 \um_setup_active_superscript:nn {^^^207a} {+}
1422 \um_setup_active_superscript:nn {^^^207b} {-}
1423 \um_setup_active_superscript:nn {^^^207c} {=}
1424 \um_setup_active_superscript:nn {^^^207d} {(}
1425 \um_setup_active_superscript:nn {^^^207e} {)}
1426 \um_setup_active_superscript:nn {^^^2071} {i}
1427 \um_setup_active_superscript:nn {^^^207f} {n}
1428
1429 % Ditto above.
1430 \cs_set:Nn \um_setup_active_subscript:nn {

```

```

1428 \prop_gput:Nxn \g_um_subs_prop    {\meaning #1} {#2}
1429 \char_make_active:n {\`#1}
1430 \global\XeTeXmathcodenum `#1 = "1FFFFF \scan_stop:
1431 \scantokens{
1432   \cs_gset:Npn #1 {
1433     \tl_set:Nn \l_um_ss_chain_tl {#2}
1434     \cs_set_eq:NN \um_sub_or_super:n \sb
1435     \tl_set:Nn \l_um_tmpa_tl {subs}
1436     \um_scan_sscript:
1437   }
1438 }
1439 }
1440
1441 \um_setup_active_subscript:nn {^^^2080} {0}
1442 \um_setup_active_subscript:nn {^^^2081} {1}
1443 \um_setup_active_subscript:nn {^^^2082} {2}
1444 \um_setup_active_subscript:nn {^^^2083} {3}
1445 \um_setup_active_subscript:nn {^^^2084} {4}
1446 \um_setup_active_subscript:nn {^^^2085} {5}
1447 \um_setup_active_subscript:nn {^^^2086} {6}
1448 \um_setup_active_subscript:nn {^^^2087} {7}
1449 \um_setup_active_subscript:nn {^^^2088} {8}
1450 \um_setup_active_subscript:nn {^^^2089} {9}
1451 \um_setup_active_subscript:nn {^^^208a} {+}
1452 \um_setup_active_subscript:nn {^^^208b} {-}
1453 \um_setup_active_subscript:nn {^^^208c} {=}
1454 \um_setup_active_subscript:nn {^^^208d} {(}
1455 \um_setup_active_subscript:nn {^^^208e} {)}
1456 \um_setup_active_subscript:nn {^^^2090} {a}
1457 \um_setup_active_subscript:nn {^^^2091} {e}
1458 \um_setup_active_subscript:nn {^^^1d62} {i}
1459 \um_setup_active_subscript:nn {^^^2092} {o}
1460 \um_setup_active_subscript:nn {^^^1d63} {r}
1461 \um_setup_active_subscript:nn {^^^1d64} {u}
1462 \um_setup_active_subscript:nn {^^^1d65} {v}
1463 \um_setup_active_subscript:nn {^^^2093} {x}
1464 \um_setup_active_subscript:nn {^^^1d66} {\beta}
1465 \um_setup_active_subscript:nn {^^^1d67} {\gamma}
1466 \um_setup_active_subscript:nn {^^^1d68} {\rho}
1467 \um_setup_active_subscript:nn {^^^1d69} {\phi}
1468 \um_setup_active_subscript:nn {^^^1d6a} {\chi}
1469
1470 \group_end:
1471
1472 % The scanning command, evident in its purpose:
1473 \cs_new:Nn \um_scan_sscript: {

```

```

1474 \um_scan_sscript:TF {
1475   \um_scan_sscript:
1476 }{
1477   \um_sub_or_super:n {\l_um_ss_chain_tl}
1478 }
1479 }
1480
1481 % The main theme here is stolen from the source to the various \cs{peek_} func-
1482   tions.
1483 % Consider this function as simply boilerplate:
1484 \cs_new:Nn \um_scan_sscript:TF {
1485   \tl_set:Nx \l_peek_true_aux_tl { \exp_not:n{ #1 } }
1486   \tl_set_eq:NN \l_peek_true_tl \c_peek_true_remove_next_tl
1487   \tl_set:Nx \l_peek_false_tl { \exp_not:n{\group_align_safe_end: #2}}
1488   \group_align_safe_begin:
1489   \peek_after:NN \um_peek_execute_branches_ss:
1490 }
1491
1492 % We do not skip spaces when scanning ahead, and we explicitly wish to
1493 % bail out on encountering a space or a brace.
1494 \cs_new:Npn \um_peek_execute_branches_ss: {
1495   \bool_if:nTF {
1496     \token_if_eq_catcode_p:NN \l_peek_token \c_group_begin_token ||
1497     \token_if_eq_catcode_p:NN \l_peek_token \c_group_end_token ||
1498     \token_if_eq_meaning_p:NN \l_peek_token \c_space_token
1499   } { \l_peek_false_tl }
1500   { \um_peek_execute_branches_ss_aux: }
1501 }
1502
1503 % This is the actual comparison code.
1504 % Because the peeking has already tokenised the next token,
1505 % it's too late to extract its charcode directly. Instead,
1506 % we look at its meaning, which remains a 'character' even
1507 % though it is itself math-active. If the character is ever
1508 % made fully active, this will break our assumptions!
1509 %
1510 % If the char's meaning exists as a property list key, we
1511 % build up a chain of sub-/superscripts and iterate. (If not, exit and
1512 % typeset what we've already collected.)
1513 \cs_new:Nn \um_peek_execute_branches_ss_aux: {
1514   \prop_if_in:cxTF
1515     {g_um_\l_um_tmpa_tl _prop}
1516     {\meaning\l_peek_token}
1517   {
1518     \prop_get:cxN

```



```

1519         {g_um_\l_um_tmpa_tl _prop}
1520         {\meaning\l_peek_token}
1521         \l_um_tmpb_tl
1522         \tl_put_right:NV \l_um_ss_chain_tl \l_um_tmpb_tl
1523         \l_peek_true_tl
1524     }
1525     {\l_peek_false_tl}
1526 }

```

#### 8.0.4 Synonyms and all the rest

We need to change L<sup>A</sup>T<sub>E</sub>X's idea of the font used to typeset things like `\sin` and `\cos`:

```

1527 \def\operator@font{\um_setup_mathup:}
1528 \def\to{\rightarrow}
1529 \def\vec{\overrightarrow}
1530 \def\le{\leq}
1531 \def\ge{\geq}
1532 \def\neq{\neq}

```

Define `\colon` as a `mathpunct` ':'. This is wrong: it should be U+003A: COLON instead!

```

1533 \ifpackageloaded{amsmath}{
1534   % define their own colon, perhaps I should just steal it.
1535 }{
1536   \cs_set_protected:Npn \colon {
1537     \bool_if:NTF \g_um_literal_colon_bool {:} { \mathpunct{:} }
1538   }
1539 }

```

`\mathcal`

```

1540 \def\mathcal{\mathscr}

```

`\mathrm`

```

1541 \def\mathrm{\mathup}

```

#### 8.0.5 Compatibility

Note that `amsmath` will always be loaded before `unicode-math`. (Conflicts occur if you try it the other way around.)

- Since the mathcode of `\-` is greater than eight bits, this piece of `\AtBeginDocument` code from `amsmath` dies if we try and set the `maths` font in the preamble:

```

1542 \ifpackageloaded{amsmath}{
1543   \tl_remove_in:Nn \@begindocumenthook {

```

```

1544         \mathchardef\std@minus\mathcode`\-\relax
1545         \mathchardef\std@equal\mathcode`\=\relax
1546     }
1547 }{}

```

- This code is to improve the output of alphabetic symbols in text of operator names (`\sin`, `\cos`, etc.). Just comment out the offending lines for now:

```

1548     \ifpackageloaded{amsopn}{
1549         \cs_set:Npn \newmcodes@ {
1550             \mathcode`\'39
1551             \mathcode`\*42
1552             \mathcode`\."613A%
1553             % \ifnum\mathcode`\- =45 \else
1554             %     \mathchardef\std@minus\mathcode`\-\relax
1555             % \fi
1556             \mathcode`\-45
1557             \mathcode`\ /47
1558             \mathcode`\:"603A\relax
1559         }
1560     }{}

```

Octothorpe is an odd one:

```

1561 \AtBeginDocument{
1562     \def\#{\mode_if_math:TF{\mathoctothorpe}{\char'\#}}
1563 }

```

Overriding amsmath definitions:

```

1564 \AtBeginDocument{
1565     \def\@cdots{\mathinner{\cdots}}
1566 }

```

Interaction with beamer:

```

1567 \ifclassloaded{beamer}{
1568     \ifbeamer@suppressreplacements\else
1569         \PackageWarningNoLine{unicode-math}{
1570             Disabling~ beamer's~ math~ setup.^J
1571             Please~ load~ beamer~ with~ the~ [professionalfonts]~ class~ option
1572         }
1573         \beamer@suppressreplacementstrue
1574     \fi
1575 }{}

```

The end.

```

1576 \ExplSyntaxOff

```

## File II

# STIX table data extraction

The source for the  $\TeX$  names for the very large number of mathematical glyphs are provided via Barbara Beeton's table file for the stix project ([ams.org/STIX](http://ams.org/STIX)). A version is located at <http://www.ams.org/STIX/bnb/stix-tbl.asc> but check <http://www.ams.org/STIX/> for more up-to-date info.

This table is converted into a form suitable for reading by  $\XeTeX$ , and then hand-edited by the author; the result is `unicode-math-table.tex`.

A single file is produced containing all (more than 3298) symbols. Future optimisations might include generating various (possibly overlapping) subsets so not all definitions must be read just to redefine a small range of symbols. Performance for now seems to be acceptable without such measures.

```
1 #!/bin/sh
2
3 cat stix-tbl.txt |
4 awk '
```

If the USV isn't repeated (TODO: check this is valid!) and the entry isn't one of the weird ones in the big block at the end of the stix table (TODO: check that out!)...

```
5 {if (usv != substr($0,2,5) && substr($0,2,1) != " ")
6     {usv = substr($0,2,5);
7       texname = substr($0,84,25);
8       class = substr($0,57,1);
9       description = tolower(substr($0,233,350));
```

If the USV has a macro name, which isn't `\text...`, and isn't a single character macro (e.g., `\#`, `\S`, ...), and has a class, and it isn't reserved (*i.e.*, doubled up with a previously assigned glyph):

```
10     if (texname ~ /[\\]/ &&
11         substr(texname,0,5) != "\\text" &&
12         substr(texname,0,4) != "\\ipa" &&
13         substr(texname,0,5) != "\\tone" &&
14         substr(texname,3,1) != " " &&
15         class != " " &&
16         description !~ /<reserved>/ )
```

Print the actual entry corresponding to the unicode character:

```
17     print "\\UnicodeMathSymbol{"\"\" \"
18         usv "}{" \"
19         texname "}{" \"
20         class "}{" \"
21         description "%}";
22     }}" - |
```

Now replace the STIX class abbreviations with their T<sub>E</sub>X macro names.

```
23 sed -e ' s/{N}/{\mathord}/ ' \
```

A ‘fence’ defined by the STIX table is something like `\vert`; in X<sub>E</sub>T<sub>E</sub>X this is just a `\mathord` that will grow with the magic of `\XeTeXmathchardef`.

```
24 -e ' s/{F}/{\mathord}/ ' \
25 -e ' s/{A}/{\mathalpha}/ ' \
26 -e ' s/{D}/{\mathaccent}/ ' \
27 -e ' s/{P}/{\mathpunct}/ ' \
28 -e ' s/{B}/{\mathbin}/ ' \
29 -e ' s/{R}/{\mathrel}/ ' \
30 -e ' s/{L}/{\mathop}/ ' \
31 -e ' s/{O}/{\mathopen}/ ' \
32 -e ' s/{C}/{\mathclose}/ ' \
```

Fixing up a couple of things in the STIX table.

```
33 -e ' s/{\string^}/ ' > unicode-math.tex
```

## A Documenting maths support in the NFSS

### A.1 Overview

In the following,  $\langle NFSS\ decl. \rangle$  stands for something like  $\{T1\}\{lmr\}\{m\}\{n\}$ .

**Maths symbol fonts** Fonts for symbols:  $\alpha$ ,  $\leq$ ,  $\rightarrow$

```
\DeclareSymbolFont{\name}\langle NFSS decl. \rangle
```

Declares a named maths font such as operators from which symbols are defined with `\DeclareMathSymbol`.

**Maths alphabet fonts** Fonts for  $ABC-xyz$ ,  $\mathfrak{ABC}-\mathcal{XZ}$ , etc.

```
\DeclareMathAlphabet{\cmd}\langle NFSS decl. \rangle
```

For commands such as `\mathbf`, accessed through maths mode that are unaffected by the current text font, and which are used for alphabetic symbols in the ASCII range.

```
\DeclareSymbolFontAlphabet{\cmd}\{\name\}
```

Alternative (and optimisation) for `\DeclareMathAlphabet` if a single font is being used for both alphabetic characters (as above) and symbols.

**Maths ‘versions’** Different maths weights can be defined with the following, switched in text with the `\mathversion{\maths version}` command.

```
\SetSymbolFont{\name}\{\maths version\}\langle NFSS decl. \rangle
```

```
\SetMathAlphabet{\cmd}\{\maths version\}\langle NFSS decl. \rangle
```

**Maths symbols** Symbol definitions in maths for both characters (=) and macros (`\eqdef`): `\DeclareMathSymbol{<symbol>}{<type>}{<named font>}{<slot>}` This is the macro that actually defines which font each symbol comes from and how they behave.

Delimiters and radicals use wrappers around  $\TeX$ 's `\delimiter`/`\radical` primitives, which are re-designed in  $\XTeX$ . The syntax used in  $\LaTeX$ 's NFSS is therefore not so relevant here.

**Delimiters** A special class of maths symbol which enlarge themselves in certain contexts.

```
\DeclareMathDelimiter{<symbol>}{<type>}{<sym. font>}{<slot>}{<sym. font>}{<slot>}
```

**Radicals** Similar to delimiters (`\DeclareMathRadical` takes the same syntax) but behave 'weirdly'. `\sqrt` might very well be the only one.

In those cases, glyph slots in *two* symbol fonts are required; one for the small ('regular') case, the other for situations when the glyph is larger. This is not the case in  $\XTeX$ .

Accents are not included yet.

**Summary** For symbols, something like:

```
\def\DeclareMathSymbol#1#2#3#4{
  \global\mathchardef#1"\mathchar@type#2
  \expandafter\hexnumber@\csname sym#2\endcsname
  {\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}}
```

For characters, something like:

```
\def\DeclareMathSymbol#1#2#3#4{
  \global\mathcode`#1"\mathchar@type#2
  \expandafter\hexnumber@\csname sym#2\endcsname
  {\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}}
```

## File III

# $\XTeX$ math font dimensions

These are the extended `\fontdimens` available for suitable fonts in  $\XTeX$ . Note that  $\LuaTeX$  takes an alternative route, and this package will eventually provide a wrapper interface to the two (I hope).

\fontdimen	Dimension name	Description
10	SCRIPTPERCENTSCALEDOWN	Percentage of scaling down for script level 1. Suggested value: 80%.
11	SCRIPTSCRIPTPERCENTSCALE-DOWN	Percentage of scaling down for script level 2 (ScriptScript). Suggested value: 60%.
12	DELIMITEDSUBFORMULAMIN-HEIGHT	Minimum height required for a delimited expression to be treated as a subformula. Suggested value: normal line height $\times$ 1.5.
13	DISPLAYOPERATORMINHEIGHT	Minimum height of n-ary operators (such as integral and summation) for formulas in display mode.
14	MATHLEADING	White space to be left between math formulas to ensure proper line spacing. For example, for applications that treat line gap as a part of line ascender, formulas with ink going above (os2.sTypoAscender + os2.sTypoLineGap – MathLeading) or with ink going below os2.sTypoDescender will result in increasing line height.
15	AXISHEIGHT	Axis height of the font.
16	ACCENTBASEHEIGHT	Maximum (ink) height of accent base that does not require raising the accents. Suggested: x-height of the font (os2.sxHeight) plus any possible overshoots.
17	FLATTENEDACCENTBASE-HEIGHT	Maximum (ink) height of accent base that does not require flattening the accents. Suggested: cap height of the font (os2.sCapHeight).
18	SUBSCRIPTSHIFTDOWN	The standard shift down applied to subscript elements. Positive for moving in the downward direction. Suggested: os2.ySubscriptYOffset.
19	SUBSCRIPTTOPMAX	Maximum allowed height of the (ink) top of subscripts that does not require moving subscripts further down. Suggested: $/5$ x-height.

\fontdimen	Dimension name	Description
20	SUBSCRIPTBASELINEDROPMIN	Minimum allowed drop of the baseline of subscripts relative to the (ink) bottom of the base. Checked for bases that are treated as a box or extended shape. Positive for subscript baseline dropped below the base bottom.
21	SUPERSCRIPSHIFTUP	Standard shift up applied to superscript elements. Suggested: $os2.ySuperscriptYOffset$ .
22	SUPERSCRIPSHIFTUPCRAMPED	Standard shift of superscripts relative to the base, in cramped style.
23	SUPERSCRIPBOTTOMMIN	Minimum allowed height of the (ink) bottom of superscripts that does not require moving subscripts further up. Suggested: $\frac{1}{4}$ x-height.
24	SUPERSCRIPBASELINEDROP-MAX	Maximum allowed drop of the baseline of superscripts relative to the (ink) top of the base. Checked for bases that are treated as a box or extended shape. Positive for superscript baseline below the base top.
25	SUBSUPERSCRIPGAPMIN	Minimum gap between the superscript and subscript ink. Suggested: $4 \times$ default rule thickness.
26	SUPERSCRIPBOTTOMMAX-WITHSUBSCRIPT	The maximum level to which the (ink) bottom of superscript can be pushed to increase the gap between superscript and subscript, before subscript starts being moved down. Suggested: $\frac{1}{5}$ x-height.
27	SPACEAFTERSCRIP	Extra white space to be added after each subscript and superscript. Suggested: 0.5pt for a 12 pt font.
28	UPPERLIMITGAPMIN	Minimum gap between the (ink) bottom of the upper limit, and the (ink) top of the base operator.
29	UPPERLIMITBASELINERISEMIN	Minimum distance between baseline of upper limit and (ink) top of the base operator.
30	LOWERLIMITGAPMIN	Minimum gap between (ink) top of the lower limit, and (ink) bottom of the base operator.

\fontdimen	Dimension name	Description
31	LOWERLIMITBASELINEDROP-MIN	Minimum distance between baseline of the lower limit and (ink) bottom of the base operator.
32	STACKTOPSHIFTUP	Standard shift up applied to the top element of a stack.
33	STACKTOPDISPLAYSTYLESHIFT-UP	Standard shift up applied to the top element of a stack in display style.
34	STACKBOTTOMSHIFTDOWN	Standard shift down applied to the bottom element of a stack. Positive for moving in the downward direction.
35	STACKBOTTOMDISPLAYSTYLE-SHIFTDOWN	Standard shift down applied to the bottom element of a stack in display style. Positive for moving in the downward direction.
36	STACKGAPMIN	Minimum gap between (ink) bottom of the top element of a stack, and the (ink) top of the bottom element. Suggested: 3×default rule thickness.
37	STACKDISPLAYSTYLEGAPMIN	Minimum gap between (ink) bottom of the top element of a stack, and the (ink) top of the bottom element in display style. Suggested: 7×default rule thickness.
38	STRETCHSTACKTOPSHIFTUP	Standard shift up applied to the top element of the stretch stack.
39	STRETCHSTACKBOTTOMSHIFT-DOWN	Standard shift down applied to the bottom element of the stretch stack. Positive for moving in the downward direction.
40	STRETCHSTACKGAPABOVEMIN	Minimum gap between the ink of the stretched element, and the (ink) bottom of the element above. Suggested: UpperLimitGapMin
41	STRETCHSTACKGAPBELOWMIN	Minimum gap between the ink of the stretched element, and the (ink) top of the element below. Suggested: LowerLimitGapMin.
42	FRACTIONNUMERATORSHIFTUP	Standard shift up applied to the numerator.
43	FRACTIONNUMERATOR-DISPLAYSTYLESHIFTUP	Standard shift up applied to the numerator in display style. Suggested: StackTopDisplayStyleShiftUp.



\fontdimen	Dimension name	Description
44	FRACTIONDENOMINATORSHIFT-DOWN	Standard shift down applied to the denominator. Positive for moving in the downward direction.
45	FRACTIONDENOMINATOR-DISPLAYSTYLESHIFTDOWN	Standard shift down applied to the denominator in display style. Positive for moving in the downward direction. Suggested: StackBottomDisplayStyleShiftDown.
46	FRACTIONNUMERATORGAP-MIN	Minimum tolerated gap between the (ink) bottom of the numerator and the ink of the fraction bar. Suggested: default rule thickness
47	FRACTIONNUMDISPLAYSTYLE-GAPMIN	Minimum tolerated gap between the (ink) bottom of the numerator and the ink of the fraction bar in display style. Suggested: 3×default rule thickness.
48	FRACTIONRULETHICKNESS	Thickness of the fraction bar. Suggested: default rule thickness.
49	FRACTIONDENOMINATORGAP-MIN	Minimum tolerated gap between the (ink) top of the denominator and the ink of the fraction bar. Suggested: default rule thickness
50	FRACTIONDENOMDISPLAY-STYLEGAPMIN	Minimum tolerated gap between the (ink) top of the denominator and the ink of the fraction bar in display style. Suggested: 3×default rule thickness.
51	SKEWEDFRACTION-HORIZONTALGAP	Horizontal distance between the top and bottom elements of a skewed fraction.
52	SKEWEDFRACTIONVERTICAL-GAP	Vertical distance between the ink of the top and bottom elements of a skewed fraction.
53	OVERBARVERTICALGAP	Distance between the overbar and the (ink) top of the base. Suggested: 3×default rule thickness.
54	OVERBARRULETHICKNESS	Thickness of overbar. Suggested: default rule thickness.
55	OVERBAREXTRAASCENDER	Extra white space reserved above the overbar. Suggested: default rule thickness.

\fontdimen	Dimension name	Description
56	UNDERBARVERTICALGAP	Distance between underbar and (ink) bottom of the base. Suggested: 3×default rule thickness.
57	UNDERBARRULETHICKNESS	Thickness of underbar. Suggested: default rule thickness.
58	UNDERBAREXTRADESCENDER	Extra white space reserved below the underbar. Always positive. Suggested: default rule thickness.
59	RADICALVERTICALGAP	Space between the (ink) top of the expression and the bar over it. Suggested: 1¼ default rule thickness.
60	RADICALDISPLAYSTYLE- VERTICALGAP	Space between the (ink) top of the expression and the bar over it. Suggested: default rule thickness + ¼ x-height.
61	RADICALRULETHICKNESS	Thickness of the radical rule. This is the thickness of the rule in designed or constructed radical signs. Suggested: default rule thickness.
62	RADICALEXTRAASCENDER	Extra white space reserved above the radical. Suggested: RadicalRuleThickness.
63	RADICALKERNBEFOREDEGREE	Extra horizontal kern before the degree of a radical, if such is present. Suggested: 5/18 of em.
64	RADICALKERNAFTERDEGREE	Negative kern after the degree of a radical, if such is present. Suggested: −10/18 of em.
65	RADICALDEGREEBOTTOM- RAISEPERCENT	Height of the bottom of the radical degree, if such is present, in proportion to the ascender of the radical sign. Suggested: 60%.

## Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols	
\"	17
\#	1307, 1562
\'	1363, 1550
\*	447, 1311, 1551
\-	446, 1544, 1553, 1554, 1556
\.	1552
\/	1557
\:	449, 1558
\:::	703
\::f	703
\::n	703
\=	1545
\DeclareMathDelimiter	295
\DeclareMathSizes	260
\backslashchar	893, 912
\begindocumenthook	1543
\ecclvi	320
\ecdots	1565
\elt	568–572, 575, 579, 581
\empty	371,
	372, 409, 496, 619, 626, 641, 662, 667
\ifclassloaded	1567
\ifnextchar	1368
\ifpackageloaded	1533, 1542, 1548
\ii	625, 626, 628, 630, 633, 638
\input	426, 1308
\marker	638, 657
\nil	329,
	477, 638, 651–654, 1287, 1292, 1305
\preamblecmds	304
\sqrt	1368
\tempa	120, 167, 193, 202, 220, 238,
	246, 382, 398, 617, 629, 653, 655, 667
\tempb	120, 121, 167, 168,
	193, 194, 202, 203, 220, 221, 238,
	239, 246, 247, 617, 618, 656, 657, 662
\tempswafalse	627
\tempswattrue	631, 634, 659, 664, 669, 674
\um@bfliteraltrue	162, 187
\um@bfupGreekfalse	126, 169
\um@bfupGreektrue	139, 152, 175, 181
\um@bfupLatinfalse	129, 172
\um@bfupLatintrue	142, 155, 178, 184
\um@bfupgreekfalse	127, 140, 170, 176
\um@bfupgreektrue	153, 182
\um@bfuplatinfalse	130, 173
\um@bfuplatintrue	143, 156, 179, 185
\um@fontspec@featuretrue	373
\um@literaltrue	161
\um@ot@math@true	401
\um@upGreekfalse	122
\um@upGreektrue	135, 148
\um@upLatinfalse	124, 137
\um@upLatintrue	150
\um@upNablafalse	131, 206
\um@upNablatrie	144, 157, 204
\um@upgreekfalse	123, 136
\um@upgreektrue	149
\um@uplatinfalse	125, 138, 151
\um@uppartialfalse	.....
	128, 141, 171, 177, 224
\um@uppartialtrue	154, 183, 222
\xDeclareMathDelimiter	296
\xxDeclareMathDelimiter	294
\	10–13, 17, 23–33, 1311, 1313
\^	33, 1286, 1296
\	1312
Numbers	
\0	23
\_	17–20, 23–32
A	
\A	24
\a	25
\addnolimits	<u>574</u>
\addtoversion	<u>267</u>
\alloc@	320

\Alpha .....	730	\clist_map_inline:nn .....	
\alpha .....	755	.....	482, 548, 555, 880, 887
\alpha@elt .....	271	\clist_map_variable:NNn .....	625
\alpha@list .....	270	\clist_map_variable:nNn ..	682, 705, 711
\AtBeginDocument .....	728, 1561, 1564	\colon .....	1536
\awint .....	570	\copy .....	1376
<b>B</b>		\cs .....	1392, 1481
\B .....	995	\cs_generate_variant:Nn ...	1382–1384
\beamer@suppresreplacementstrue	1573	\cs_gset:cpn .....	334, 344
\begingroup .....	326, 578, 1285, 1303	\cs_gset:Npn ..	347, 352, 1287, 1399, 1432
\Beta .....	731	\cs_gset:Npx .....	357
\beta .....	756, 1464	\cs_gset_eq:NN .....	1365, 1366
\bgroup .....	933	\cs_if_exist:cF .....	928
\bool_if:NF .....	448	\cs_if_exist:cT .....	913
\bool_if:NTF .....	760, 779, 785, 790, 1024, 1032, 1187, 1217, 1537	\cs_new:Nn .....	433, 445, 476, 481, 486, 489, 704, 710, 719, 722, 725, 860, 879, 905, 927, 1319, 1325, 1341, 1345, 1473, 1483, 1513
\bool_if:nTF .....	1494	\cs_new:Npn	942, 945, 949, 954, 964, 980, 993, 1004, 1011, 1019, 1023, 1045, 1051, 1057, 1063, 1140, 1157, 1174, 1180, 1186, 1251, 1268, 1493
\bool_new:N .....	22, 190, 191, 245	\cs_set:cpn .....	929
\bool_set_false:N .....	...	\cs_set:Nn .....	209, 227, 366, 437, 440, 495, 547, 552, 681, 691, 694, 697, 700, 795, 806, 816, 823, 832, 841, 918, 921, 1394, 1427
... 132, 133, 159, 164, 195, 240, 250		\cs_set:Npn .....	703, 1549
\bool_set_true:N .....	145, 146, 158, 163, 197, 199, 242, 248	\cs_set_eq:cN .....	922
\box .....	1378	\cs_set_eq:NN .....	412–415, 419–422, 1361, 1401, 1434
<b>C</b>		\cs_set_protected:cpn .....	932
\C .....	983, 1013	\cs_set_protected:Npn .....	1536
\c_group_begin_token .....	1495	\cs_to_str:N .....	329, 334, 344, 563
\c_group_end_token .....	1496	\csname .....	323, 329, 332, 335, 367, 374, 491, 563, 881, 888, 906, 936
\c_peek_true_remove_next_tl ...	1485	<b>D</b>	
\c_space_token .....	1497	\DeclareDocumentCommand .....	369
\cdots .....	1565	\DeclareMathAccent .....	288
\cdp@elt .....	258	\DeclareMathAlphabet .....	284
\cdp@list .....	257	\DeclareMathDelimiter .....	293
\char .....	1562	\DeclareMathRadical .....	299
\char_make_active:N .....	1363	\DeclareMathSizes .....	259
\char_make_active:n	327, 1364, 1396, 1429	\DeclareMathSymbol .....	290
\char_make_escape:N .....	1312	\DeclareMathVersion .....	264, 376
\char_make_math_superscript:N ..	1296	\DeclareRobustCommand .....	1368
\char_make_other:N ...	1286, 1307, 1313		
\chardef .....	320		
\Chi .....	752		
\chi .....	781, 1468		
\cirfnint .....	570		
\clist_map_break: .....	884		
\clist_map_inline:Nn .....	553		

<code>\DeclareSymbolFont</code> . . . . .	277, 424
<code>\DeclareSymbolFontAlphabet</code> . . . . .	301
<code>\DeclareSymbolFontAlphabet@</code> . . . . .	302
<code>\def</code> . . . . .	23–118, 306, 309, 320, 322, 324, 375, 567, 575, 577, 579, 586, 588, 651, 653–656, 730–759, 762–778, 781–784, 787–789, 792, 793, 1298, 1304, 1369, 1527–1532, 1540, 1541, 1562, 1565
<code>\define@choicekey</code> . . . . .	119, 167, 192, 202, 220, 238, 246, 617
<code>\define@cmdkey</code> . . . . .	613–616
<code>\define@key</code> . . . . .	596
<code>\define@mathalphabet</code> . . . . .	265
<code>\define@mathgroup</code> . . . . .	266
<code>\Delta</code> . . . . .	733
<code>\delta</code> . . . . .	758
<code>\dimexpr</code> . . . . .	307, 400, 1372
<code>\do</code> . . . . .	304
<code>\dorestore@version</code> . . . . .	274
<code>\dp</code> . . . . .	1374
<b>E</b>	
<code>\E</code> . . . . .	996
<code>\e</code> . . . . .	1006
<code>\edef</code> . . . . .	382, 652, 653
<code>\egroup</code> . . . . .	930, 935
<code>\else</code> . . . . .	214, 232, 312, 315, 341, 345, 350, 355, 358, 402, 416, 456, 469, 500, 508, 511, 516, 522, 534, 544, 580, 599, 632, 637, 643, 661, 666, 671, 819, 827, 836, 850, 1097, 1100, 1106, 1113, 1126, 1553, 1568
<code>\else:</code> . . . . .	925
<code>\encodingdefault</code> . . . . .	425, 919
<code>\endcsname</code> . . . . .	323, 329, 332, 335, 367, 374, 491, 563, 881, 888, 906, 936
<code>\endgroup</code> . . . . .	330, 584, 1302, 1309
<code>\Epsilon</code> . . . . .	734
<code>\epsilon</code> . . . . .	759
<code>\Eta</code> . . . . .	736
<code>\eta</code> . . . . .	763
<code>\etex_iffontchar:D</code> . . . . .	925
<code>\ExecuteOptionsX</code> . . . . .	253
<code>\exp_args:Nnff</code> . . . . .	703, 706, 713
<code>\exp_args:No</code> . . . . .	549, 556
<code>\exp_not:n</code> . . . . .	1484, 1486
<code>\expandafter</code> . . . . .	323, 331, 336, 338, 342, 562, 575, 628, 630, 633, 638, 652, 653, 657, 935, 936
<code>\ExplSyntaxOff</code> . . . . .	1576
<code>\ExplSyntaxOn</code> . . . . .	6, 1295
<b>F</b>	
<code>\F</code> . . . . .	997
<code>\f@size</code> . . . . .	374
<code>\fi</code> . . . . .	165, 188, 200, 207, 218, 225, 236, 243, 251, 317, 318, 339, 360–364, 408, 423, 459, 474, 505, 513, 518, 525, 542, 543, 545, 558, 582, 604, 620, 635, 636, 639, 645, 647, 648, 660, 665, 670, 675–679, 821, 830, 839, 858, 1102, 1109, 1116, 1135, 1138, 1555, 1574
<code>\fi:</code> . . . . .	925
<code>\fint</code> . . . . .	570
<code>\font</code> . . . . .	399
<code>\fontdimen</code> . . . . .	307, 400, 1371, 1377
<code>\fontname</code> . . . . .	896, 912
<b>G</b>	
<code>\g</code> . . . . .	1007
<code>\g@addto@macro</code> . . . . .	562, 642, 644
<code>\g_um_literal_colon_bool</code> . . . . .	245, 248, 250, 448, 1537
<code>\g_um_math_alphabet_name_Greek_tl</code> . . . . .	903
<code>\g_um_math_alphabet_name_greek_tl</code> . . . . .	902
<code>\g_um_math_alphabet_name_Latin_tl</code> . . . . .	901
<code>\g_um_math_alphabet_name_latin_tl</code> . . . . .	900
<code>\g_um_math_alphabet_name_num_tl</code> . . . . .	904
<code>\g_um_primekern_muskip</code> . . . . .	1316, 1317, 1322
<code>\g_um_sfliteral_bool</code> . . . . .	163, 191, 199, 1024, 1187
<code>\g_um_subs_prop</code> . . . . .	1381, 1428
<code>\g_um_supers_prop</code> . . . . .	1380, 1395
<code>\g_um_texgreek_bool</code> . . . . .	22, 133, 146, 159, 164, 240, 242, 760, 779, 785, 790
<code>\g_um_upsans_bool</code> . . . . .	132, 145, 158, 190, 195, 197, 1032, 1217
<code>\Gamma</code> . . . . .	732
<code>\gamma</code> . . . . .	757, 1465
<code>\gdef</code> . . . . .	1292
<code>\ge</code> . . . . .	1531
<code>\geq</code> . . . . .	1531

<code>\get@cdp</code> .....	283	<code>\int</code> .....	568
<code>\glb@currsiz</code> .....	370	<code>\intBar</code> .....	570
<code>\global</code> .....	328, 331, 348, 349, 353, 354, 359, 619, 1289, 1298, 1397, 1430	<code>\intbar</code> .....	570
<code>\group@elt</code> .....	279	<code>\intcap</code> .....	572
<code>\group@list</code> .....	278	<code>\intclockwise</code> .....	569
<code>\group_align_safe_begin:</code> .....	1487	<code>\intcup</code> .....	572
<code>\group_align_safe_end:</code> .....	1486	<code>\intlarhk</code> .....	571
<code>\group_begin:</code> .....	1310, 1362, 1386	<code>\intx</code> .....	571
<code>\group_end:</code> .....	1367, 1470	<code>\Iota</code> .....	738
<b>H</b>		<code>\iota</code> .....	765
<code>\H</code> .....	984, 998, 1014	<b>K</b>	
<code>\h</code> .....	826, 829, 947, 967	<code>\Kappa</code> .....	739
<code>\hbox</code> .....	1370	<code>\kappa</code> .....	766
<code>\ht</code> .....	1373	<code>\kern</code> .....	1371, 1377
<b>I</b>		<b>L</b>	
<code>\I</code> .....	999, 1015	<code>\L</code> .....	1000
<code>\if@tempwa</code> .....	640	<code>\l_peek_false_tl</code> ....	1486, 1499, 1525
<code>\if@um@bfliteral</code> ....	15, 460, 506, 1067	<code>\l_peek_token</code> ...	1495–1497, 1516, 1520
<code>\if@um@bfupGreek</code> .....	16, 519, 1110	<code>\l_peek_true_aux_tl</code> .....	1484
<code>\if@um@bfupgreek</code> .....	17, 526, 1117	<code>\l_peek_true_tl</code> .....	1485, 1523
<code>\if@um@bfupLatin</code> .....	18, 509, 1098	<code>\l_um_inc_num</code> .....	712, 714, 715
<code>\if@um@bfuplatin</code> .....	19, 514, 1103	<code>\l_um_incr_num</code> .....	683, 685, 687
<code>\if@um@fontspec@feature</code> .....	8, 597	<code>\l_um_input_num</code> 682, 685, 705, 707, 711, 714	
<code>\if@um@literal</code> .....	10, 451, 498	<code>\l_um_primecount_num</code> .....	
<code>\if@um@ot@math</code> .....	9	.....	1318, 1342, 1346, 1356
<code>\if@um@upGreek</code> .....	11, 833	<code>\l_um_script_features_tl</code> ....	377, 388
<code>\if@um@upgreek</code> .....	12, 842	<code>\l_um_script_font_tl</code> .....	379, 387
<code>\if@um@upLatin</code> .....	13, 817	<code>\l_um_ss_chain_tl</code> 1400, 1433, 1477, 1522	
<code>\if@um@uplatin</code> .....	14, 824	<code>\l_um_sscript_features_tl</code> ...	378, 392
<code>\if@um@upNabla</code> .....	20, 210	<code>\l_um_sscript_font_tl</code> .....	380, 391
<code>\if@um@uppartial</code> .....	21, 228	<code>\l_um_tmpa_tl</code> ...	1402, 1435, 1515, 1519
<code>\ifbeamer@suppressreplacements</code> .	1568	<code>\l_um_tmpb_tl</code> .....	1521, 1522
<code>\ifcase</code> 121, 168, 194, 203, 221, 239, 247, 618		<code>\Lambda</code> .....	740
<code>\ifdim</code> .....	400	<code>\lambda</code> .....	767
<code>\ifin@</code> .....	337, 343	<code>\lccode</code> .....	1311
<code>\ifnum</code> .. 554, 658, 663, 668, 672, 673, 1553		<code>\le</code> .....	1530
<code>\ifx</code> .....	310, 313, 325, 346, 351, 356, 409, 496, 580, 626, 629, 630, 633, 641, 657, 662, 667	<code>\left</code> .....	587
<code>\iiiint</code> .....	568	<code>\left@primitive</code> .....	587, 588
<code>\iiint</code> .....	568	<code>\leq</code> .....	1530
<code>\iint</code> .....	568	<code>\let</code> .....	321, 370–372, 587, 619, 1289
<code>\in@</code> .....	336, 342	<code>\lowercase</code> .....	1288, 1293
<code>\init@restore@version</code> .....	273	<code>\lowint</code> .....	572
		<b>M</b>	
		<code>\M</code> .....	1001

<code>\m@th</code> .....	1370	<code>\mitalpha</code> .....	755
<code>\mathaccent</code> .....	356	<code>\mitBeta</code> .....	731
<code>\mathalpha</code> .....	564, 686	<code>\mitbeta</code> .....	756
<code>\mathbb</code> .....	981–991	<code>\mitChi</code> .....	752
<code>\mathbf</code> .....	1064–1066, 1068–1096, 1099, 1101, 1104, 1105, 1107, 1108, 1111, 1112, 1114, 1115, 1118–1125, 1127–1134, 1136, 1137	<code>\mitchi</code> .....	781
<code>\mathbffrac</code> .....	1175–1178	<code>\mitDelta</code> .....	733
<code>\mathbf fit</code> .....	1141–1155	<code>\mitdelta</code> .....	758
<code>\mathbf fscr</code> .....	1181–1184	<code>\mitEpsilon</code> .....	734
<code>\mathbf fsf</code> .....	1188–1215, 1218–1232, 1234–1248	<code>\mitepsilon</code> .....	760, 785
<code>\mathbf fsfit</code> .....	1269–1283	<code>\mitEta</code> .....	736
<code>\mathbf fsfup</code> .....	1252–1266	<code>\miteta</code> .....	763
<code>\mathbf fup</code> .....	1158–1172	<code>\mitGamma</code> .....	732
<code>\mathbin</code> .....	446, 447	<code>\mitgamma</code> .....	757
<code>\mathcal</code> .....	1540	<code>\mitIota</code> .....	738
<code>\mathchar@type</code> .....	300, 333, 347, 349, 352, 354, 357, 359, 367, 490	<code>\mitiota</code> .....	765
<code>\mathchardef</code> .....	1544, 1545, 1554	<code>\mitKappa</code> .....	739
<code>\mathclose</code> .....	351	<code>\mitkappa</code> .....	766
<code>\mathcode</code> .....	328, 1544, 1545, 1550–1554, 1556–1558	<code>\mitLambda</code> .....	740
<code>\mathfrac</code> .....	1012–1017, 1020, 1021	<code>\mitlambda</code> .....	767
<code>\mathgroup</code> .....	320	<code>\mitMu</code> .....	741
<code>\mathinner</code> .....	1565	<code>\mitmu</code> .....	768
<code>\mathit</code> .....	965–978	<code>\mitNu</code> .....	742
<code>\mathoctothorpe</code> .....	1562	<code>\mitnu</code> .....	769
<code>\mathop</code> .....	325	<code>\mitOmega</code> .....	754
<code>\mathopen</code> .....	346, 588	<code>\mitomega</code> .....	783
<code>\mathord</code> .....	452–455, 457, 458, 461–468, 470–473, 487	<code>\mitOmicron</code> .....	744
<code>\mathpunct</code> .....	1537	<code>\mitomicron</code> .....	771
<code>\mathrel</code> .....	449	<code>\mitPhi</code> .....	751
<code>\mathrm</code> .....	1541	<code>\mitphi</code> .....	779, 790
<code>\mathscr</code> ....	994–1002, 1005–1009, 1540	<code>\mitPi</code> .....	745
<code>\mathsf</code> 1025–1030, 1033–1036, 1038–1041		<code>\mitpi</code> .....	772
<code>\mathsf fit</code> .....	1052–1055	<code>\mitPsi</code> .....	753
<code>\mathsf fup</code> .....	1046–1049	<code>\mitpsi</code> .....	782
<code>\mathhtt</code> .....	919, 1058–1061	<code>\mitRho</code> .....	746
<code>\mathup</code> .....	943, 946, 947, 950–952, 955–962, 1541	<code>\mitrho</code> .....	773
<code>\mddefault</code> .....	425, 919	<code>\mitSigma</code> .....	748
<code>\meaning</code> .....	1395, 1428, 1516, 1520	<code>\mitsigma</code> .....	775
<code>\mitAlpha</code> .....	730	<code>\mitTau</code> .....	749
		<code>\mittau</code> .....	776
		<code>\mitTheta</code> .....	737
		<code>\mittheta</code> .....	764
		<code>\mitUpsilon</code> .....	750
		<code>\mitupsilon</code> .....	777
		<code>\mitvarepsilon</code> .....	760, 785
		<code>\mitvarkappa</code> .....	788
		<code>\mitvarphi</code> .....	779, 790

\mitvarpi .....	793	<b>O</b>	
\mitvarrho .....	792	\o .....	1008
\mitvarsigma .....	774	\oiint .....	568
\mitvarTheta .....	747	\oiint .....	568
\mitvartheta .....	787	\oint .....	568
\mitXi .....	743	\ointctrclockwise .....	569
\mitxi .....	770	\Omega .....	754
\mitZeta .....	735	\omega .....	783
\mitzeta .....	762	\Omicron .....	744
\mode_if_math:F .....	934	\omicron .....	771
\mode_if_math:TF .....	1562	\operator@font .....	1527
\mskip .....	1322	\or .....	134, 147, 160, 174, 180, 186, 196, 198, 205, 223, 241, 249
\Mu .....	741	\overrightarrow .....	1529
\mu .....	768	<b>P</b>	
\muskip_gset:Nn .....	1317	\P .....	986
\muskip_new:N .....	1316	\PackageError .....	600
<b>N</b>		\PackageInfo .....	411
\N .....	985	\PackageWarningNoLine .....	403, 891, 911, 1569
\ne .....	1532	\peek_after:NN .....	1488
\neq .....	1532	\peek_meaning_remove:NTF .....	1347, 1350, 1353
\new@mathalphabet .....	285	\Phi .....	751
\new@mathgroup .....	256, 320, 321	\phi .....	778, 1467
\new@mathversion .....	276	\Pi .....	745
\new@symbolfont .....	280	\pi .....	772
\newcommand .....	561, 574, 595, 624, 729	\pointint .....	571
\newcounter .....	7	\prg_case_int:nnn .....	1326
\newfam .....	321	\prg_do_nothing: .....	922
\newif .....	8–21	\prg_new_conditional:Nnn .....	924
\newmathalphabet .....	261	\prg_replicate:nn .....	1322
\newmathalphabet@@ .....	262	\prg_return_false: .....	925
\newmathalphabet@@@ .....	263	\prg_return_true: .....	925
\newmcodes@ .....	1549	\prg_stepwise_variable:nnnNn .....	683, 712
\noexpand .....	382, 581	\prime .....	1361
\nolimits .....	338	\primedouble .....	1329
\non@alpherr .....	936	\primequadruple .....	1335
\npolint .....	571	\primesingle .....	487, 1321, 1322, 1327
\Nu .....	742	\primetripel .....	1332
\nu .....	769	\process@table .....	275
\num_incr:N .....	1346	\ProcessOptionsX .....	254
\num_new:N .....	1318	\prop_get:cxN .....	1518
\num_zero:N .....	1342	\prop_get:NnN .....	1383
\number .....	707, 714, 715	\prop_gput:Nnn .....	1382
\numexpr .....	663, 668, 672, 673, 685, 687, 707, 714, 715	\prop_gput:Nxn .....	1395, 1428
		\prop_if_in:cxTF .....	1514



<code>\prop_if_in:NnTF</code> .....	1384	<code>\SetSymbolFont</code> .....	281
<code>\prop_new:N</code> .....	1380, 1381	<code>\SetSymbolFont@</code> .....	282
<code>\protect</code> .....	603	<code>\sf@size</code> .....	386, 390
<code>\ProvidesPackage</code> .....	1	<code>\Sigma</code> .....	748
<code>\Psi</code> .....	753	<code>\sigma</code> .....	775
<code>\psi</code> .....	782	<code>\sp</code> .....	1401
<b>Q</b>		<code>\space</code> .....	891, 911, 936
<code>\Q</code> .....	987	<code>\sqint</code> .....	571
<b>R</b>		<code>\sqrt</code> .....	586, 1368
<code>\R</code> .....	988, 1002, 1016	<code>\sqrtsign</code> .....	1368, 1370
<code>\r@t</code> .....	<u>1369</u>	<code>\std@equal</code> .....	1545
<code>\raise</code> .....	1372	<code>\std@minus</code> .....	1544, 1554
<code>\relax</code> .....	121, 168, 194, 203, 221, 239, 247, 307, 325, 328, 333, 344, 346–349, 351–354, 356, 357, 359, 367, 370, 399, 400, 554, 618, 630, 633, 657, 658, 663, 668, 672, 673, 685, 687, 707, 714, 715, 1375, 1544, 1545, 1554, 1558	<code>\stepcounter</code> .....	417
<code>\removenolimits</code> .....	<u>577</u>	<code>\string</code> .....	332, 335, 652, 653
<code>\RequirePackage</code> .....	3–5	<code>\strip@pt</code> .....	307
<code>\restore@mathversion</code> .....	272	<code>\sumint</code> .....	569
<code>\Rho</code> .....	746	<b>T</b>	
<code>\rho</code> .....	773, 1466	<code>\Tau</code> .....	749
<code>\rightarrow</code> .....	1528	<code>\tau</code> .....	776
<code>\rootbox</code> .....	1376	<code>\tf@size</code> .....	385, 386
<code>\rppolint</code> .....	570	<code>\Theta</code> .....	737
<b>S</b>		<code>\theta</code> .....	764
<code>\sb</code> .....	1434	<code>\theum@fam</code> .....	418
<code>\scan_stop:</code> ....	492, 493, 925, 1397, 1430	<code>\thinmuskip</code> .....	1317
<code>\scantokens</code> .....	1289, 1398, 1431	<code>\tl_map_inline:nn</code> .....	255
<code>\scpolint</code> .....	571	<code>\tl_put_right:NV</code> .....	1522
<code>\scriptscriptstyle</code> .....	313	<code>\tl_remove_in:Nn</code> .....	304, 1543
<code>\scriptstyle</code> .....	310	<code>\tl_rescan:nn</code> .....	1294
<code>\set@mathdelimiter</code> .....	298	<code>\tl_set:Nn</code> .....	211–213, 215–217, 229–231, 233–235, 377–380, 410, 900–904, 1400, 1402, 1433, 1435
<code>\set@mathaccent</code> .....	289	<code>\tl_set:Nx</code> .....	418, 1484, 1486
<code>\set@mathchar</code> .....	291	<code>\tl_set_eq:NN</code> .....	1485
<code>\set@mathdelimiter</code> .....	297	<code>\tl_use:c</code> .....	894
<code>\set@mathsymbol</code> .....	292	<code>\to</code> .....	1528
<code>\setbox</code> .....	1370	<code>\token_if_eq_catcode_p:NN</code> ..	1495, 1496
<code>\setkeys</code> .....	381	<code>\token_if_eq_meaning_p:NN</code> ..	1497
<code>\SetMathAlphabet</code> .....	286, 919	<code>\ttdefault</code> .....	919
<code>\SetMathAlphabet@</code> .....	287	<b>U</b>	
<code>\setmathfont</code> .....	<u>369</u> , 603	<code>\um@addto@mathmap</code> .....	549, 556, <u>561</u>
		<code>\um@backslash</code> .....	629, 652
		<code>\um@char@num@range</code> .....	372, 553, 641, 642, 644
		<code>\um@char@range</code> .....	371, 409, 496, 619, 622, 625
		<code>\um@firstchar</code> .....	628, 653
		<code>\um@firstof</code> .....	651–653

$\backslash\mathrm{um@font}$ . . . . .	311, 314, 399, 400, 896, 912, 925, 1371, 1373, 1374, 1377
$\backslash\mathrm{um@fontdimen@percent}$ . . . . .	. . . . . 306, 311, 314, 1373, 1374
$\backslash\mathrm{um@mathsymbol}$ . . . . .	322, 438
$\backslash\mathrm{um@mversion}$ . . . . .	375, 376
$\backslash\mathrm{um@nolimits}$ . . . . .	336, 567, 575, 583
$\backslash\mathrm{um@parse@range}$ . . . . .	638, 654
$\backslash\mathrm{um@parse@term}$ . . . . .	441, 477, 624
$\backslash\mathrm{um@radicals}$ . . . . .	342, 586
$\backslash\mathrm{um@resolve@greek}$ . . . . .	728
$\backslash\mathrm{um@scaled@apply}$ . . . . .	309, 1371, 1377
$\backslash\mathrm{um@scanactivedef}$ . . . . .	329, 1285
$\backslash\mathrm{um@scancharlet}$ . . . . .	1285, 1305
$\backslash\mathrm{um@set@mathsymbol}$ . . . . .	323, 324
$\backslash\mathrm{um@usv@bbLatin}$ . . . . .	33, 982
$\backslash\mathrm{um@usv@bblatin}$ . . . . .	34, 990
$\backslash\mathrm{um@usv@bbnum}$ . . . . .	32, 981
$\backslash\mathrm{um@usv@bfDigamma}$ . . . . .	82, 1079
$\backslash\mathrm{um@usv@bfdigamma}$ . . . . .	89, 1087
$\backslash\mathrm{um@usv@bffrakLatin}$ . . . . .	58, 1176
$\backslash\mathrm{um@usv@bffraklatin}$ . . . . .	59, 1177
$\backslash\mathrm{um@usv@bfitGreek}$ . . . . .	. 56, 520, 523, 813, 1073, 1114, 1145
$\backslash\mathrm{um@usv@bfitgreek}$ . . . . .	. 57, 527, 535, 814, 1075, 1127, 1146
$\backslash\mathrm{um@usv@bfith}$ . . . . .	99, 1076, 1108
$\backslash\mathrm{um@usv@bfitLatin}$ . . . . .	. 54, 510, 512, 809, 1069, 1101, 1142
$\backslash\mathrm{um@usv@bfitlatin}$ . . . . .	. 55, 515, 517, 810, 1071, 1107, 1143
$\backslash\mathrm{um@usv@bfitNabla}$ . . . . .	. . . . . 110, 216, 462, 470, 1089, 1148
$\backslash\mathrm{um@usv@bfitpartial}$ . . . . .	116, 234, 466, 472, 1090, 1134, 1149
$\backslash\mathrm{um@usv@bfitvarepsilon}$ . . . . .	. . . . . 101, 528, 536, 1091, 1128, 1150
$\backslash\mathrm{um@usv@bfitvarkappa}$ . . . . .	. . . . . 103, 530, 538, 1093, 1130, 1152
$\backslash\mathrm{um@usv@bfitvarphi}$ . . . . .	. . . . . 104, 531, 539, 1094, 1131, 1153
$\backslash\mathrm{um@usv@bfitvarpi}$ . . . . .	. . . . . 106, 533, 541, 1096, 1133, 1155
$\backslash\mathrm{um@usv@bfitvarrho}$ . . . . .	. . . . . 105, 532, 540, 1095, 1132, 1154
$\backslash\mathrm{um@usv@bfitvarTheta}$ . . . . .	. . . . . 100, 521, 524, 1088, 1115, 1147
$\backslash\mathrm{um@usv@bfitvartheta}$ . . . . .	. . . . . 102, 529, 537, 1092, 1129, 1151
$\backslash\mathrm{um@usv@bfLatin}$ . . . . .	50
$\backslash\mathrm{um@usv@bfNabla}$ . . . . .	. . . . . 109, 212, 461, 470, 1078, 1165
$\backslash\mathrm{um@usv@bfnum}$ . . . . .	. . . . . 48, 1064, 1141, 1158, 1175, 1181
$\backslash\mathrm{um@usv@bfpartial}$ . . . . .	115, 230, 465, 472, 1080, 1125, 1166
$\backslash\mathrm{um@usv@bfscrLatin}$ . . . . .	60, 1182
$\backslash\mathrm{um@usv@bfscrlatin}$ . . . . .	61, 1183
$\backslash\mathrm{um@usv@bfsfitGreek}$ . . . . .	70, 1196, 1238, 1273
$\backslash\mathrm{um@usv@bfsfitgreek}$ . . . . .	71, 1197, 1239, 1274
$\backslash\mathrm{um@usv@bfsfitLatin}$ . . . . .	68, 1191, 1235, 1270
$\backslash\mathrm{um@usv@bfsfitlatin}$ . . . . .	69, 1192, 1236, 1271
$\backslash\mathrm{um@usv@bfsfitNabla}$ . . . . .	112, 217, 464, 471, 1208, 1241, 1276
$\backslash\mathrm{um@usv@bfsfitpartial}$ . . . . .	118, 235, 468, 473, 1209, 1242, 1277
$\backslash\mathrm{um@usv@bfsfLatin}$ . . . . .	64
$\backslash\mathrm{um@usv@bfsfNabla}$ . . . . .	111, 213, 463, 471
$\backslash\mathrm{um@usv@bfsfnum}$ . . . . .	. . . . . 62, 1188, 1218, 1234, 1252, 1269
$\backslash\mathrm{um@usv@bfsfpartial}$ . . . . .	117, 231, 467, 473
$\backslash\mathrm{um@usv@bfsfupGreek}$ . . . . .	66, 1194, 1222, 1256
$\backslash\mathrm{um@usv@bfsfupgreek}$ . . . . .	67, 1195, 1223, 1257
$\backslash\mathrm{um@usv@bfsfupLatin}$ . . . . .	63, 1189, 1219, 1253
$\backslash\mathrm{um@usv@bfsfuplatin}$ . . . . .	65, 1190, 1220, 1254
$\backslash\mathrm{um@usv@bfupGreek}$ . . . . .	. 52, 520, 523, 811, 1072, 1111, 1162
$\backslash\mathrm{um@usv@bfupgreek}$ . . . . .	. 53, 527, 535, 812, 1074, 1118, 1163
$\backslash\mathrm{um@usv@bfuph}$ . . . . .	98, 1105
$\backslash\mathrm{um@usv@bfupLatin}$ . . . . .	. 49, 510, 512, 807, 1068, 1099, 1159
$\backslash\mathrm{um@usv@bfuplatin}$ . . . . .	. 51, 515, 517, 808, 1070, 1104, 1160
$\backslash\mathrm{um@usv@bfvarepsilon}$ . . . . .	. . . . . 83, 528, 536, 1081, 1119, 1167
$\backslash\mathrm{um@usv@bfvarkappa}$ . . . . .	. . . . . 85, 530, 538, 1083, 1121, 1169
$\backslash\mathrm{um@usv@bfvarphi}$ . . . . .	. . . . . 86, 531, 539, 1084, 1122, 1170

$\backslash\mathrm{um@usv@bfvarpi}$ . . . . .	$\backslash\mathrm{um@usv@itvarphi}$ . . . . .
88, 533, 541, 1086, 1124, 1172	95, 847, 855,
$\backslash\mathrm{um@usv@bfvarrho}$ . . . . .	960, 976, 1094, 1122, 1131, 1153,
87, 532, 540, 1085, 1123, 1171	1170, 1213, 1230, 1246, 1264, 1281
$\backslash\mathrm{um@usv@bfvartheta}$ . . . . .	$\backslash\mathrm{um@usv@itvarpi}$ . . . . .
81, 521, 524, 1077, 1112, 1164	97, 849, 857,
$\backslash\mathrm{um@usv@bfvarthetaeta}$ . . . . .	962, 978, 1096, 1124, 1133, 1155,
84, 529, 537, 1082, 1120, 1168	1172, 1215, 1232, 1248, 1266, 1283
$\backslash\mathrm{um@usv@Digamma}$ . . . . .	$\backslash\mathrm{um@usv@itvarrho}$ . . . . .
73, 1065, 1079	96, 848, 856,
$\backslash\mathrm{um@usv@digamma}$ . . . . .	961, 977, 1095, 1123, 1132, 1154,
80, 1066, 1087	1171, 1214, 1231, 1247, 1265, 1282
$\backslash\mathrm{um@usv@frakLatin}$ . . . . .	$\backslash\mathrm{um@usv@itvarthetaeta}$ . . . . .
37, 1012, 1176	91, 838, 952, 972, 1088,
$\backslash\mathrm{um@usv@fraklatin}$ . . . . .	1112, 1115, 1147, 1164, 1224, 1258
38, 1020, 1177	$\backslash\mathrm{um@usv@itvarthetaeta}$ . . . . .
$\backslash\mathrm{um@usv@itGreek}$ . . . . .	93, 845, 853,
30, 803, 834, 837,	958, 974, 1092, 1120, 1129, 1151,
950, 968, 1073, 1111, 1114, 1145,	1168, 1211, 1228, 1244, 1262, 1279
1162, 1196, 1222, 1238, 1256, 1273	$\backslash\mathrm{um@usv@Nabla}$ . . . . .
$\backslash\mathrm{um@usv@itgreek}$ . . . . .	107, 211, 452,
31, 843, 851,	457, 951, 970, 1078, 1136, 1148,
955, 969, 1075, 1118, 1127, 1146,	1165, 1199, 1225, 1241, 1259, 1276
1163, 1197, 1223, 1239, 1257, 1274	$\backslash\mathrm{um@usv@enum}$ . . . . .
$\backslash\mathrm{um@usv@ith}$ . . . . .	23, 497,
90, 799, 826, 829, 947,	981, 1025, 1033, 1038, 1046, 1052,
967, 991, 1009, 1021, 1030, 1036,	1058, 1064, 1141, 1158, 1175,
1041, 1049, 1055, 1061, 1076,	1181, 1188, 1218, 1234, 1252, 1269
1105, 1108, 1144, 1161, 1178,	$\backslash\mathrm{um@usv@partial}$ 113, 229, 454, 458, 956,
1184, 1193, 1221, 1237, 1255, 1272	971, 1080, 1125, 1134, 1137, 1149,
$\backslash\mathrm{um@usv@itLatin}$ 28, 797, 818, 820, 943,	1166, 1200, 1226, 1242, 1260, 1277
965, 982, 994, 1012, 1028, 1034,	$\backslash\mathrm{um@usv@scrLatin}$ . . . . .
1039, 1047, 1053, 1059, 1069,	35, 994
1099, 1101, 1142, 1159, 1176,	$\backslash\mathrm{um@usv@scrLatin}$ . . . . .
1182, 1191, 1219, 1235, 1253, 1270	36, 1005
$\backslash\mathrm{um@usv@itLatin}$ 29, 798, 825, 828, 946,	$\backslash\mathrm{um@usv@sfitLatin}$ . . . . .
966, 990, 1005, 1020, 1029, 1035,	43, 1028, 1039, 1053
1040, 1048, 1054, 1060, 1071,	$\backslash\mathrm{um@usv@sfitLatin}$ . . . . .
1104, 1107, 1143, 1160, 1177,	44, 1029, 1040, 1054
1183, 1192, 1220, 1236, 1254, 1271	$\backslash\mathrm{um@usv@sfLatin}$ . . . . .
$\backslash\mathrm{um@usv@itNabla}$ . . . . .	41
108, 215, 453,	$\backslash\mathrm{um@usv@sfnum}$ . . . . .
457, 951, 970, 1089, 1136, 1148,	39, 1025, 1033, 1038, 1046, 1052
1165, 1208, 1225, 1241, 1259, 1276	$\backslash\mathrm{um@usv@sfupLatin}$ . . . . .
$\backslash\mathrm{um@usv@itpartial}$ . . . . .	40, 1026, 1034, 1047
114, 233, 455, 458, 956,	$\backslash\mathrm{um@usv@sfupLatin}$ . . . . .
971, 1090, 1125, 1134, 1137, 1149,	42, 1027, 1035, 1048
1166, 1209, 1226, 1242, 1260, 1277	$\backslash\mathrm{um@usv@ttLatin}$ . . . . .
$\backslash\mathrm{um@usv@itvarepsilon}$ . . . . .	46, 1059
92, 844, 852,	$\backslash\mathrm{um@usv@ttlLatin}$ . . . . .
957, 973, 1091, 1119, 1128, 1150,	47, 1060
1167, 1210, 1227, 1243, 1261, 1278	$\backslash\mathrm{um@usv@ttnum}$ . . . . .
$\backslash\mathrm{um@usv@itvarkappa}$ . . . . .	45, 1058
94, 846, 854,	$\backslash\mathrm{um@usv@upGreek}$ . . . . .
959, 975, 1093, 1121, 1130, 1152,	26, 801, 834, 837,
1169, 1212, 1229, 1245, 1263, 1280	950, 968, 1072, 1111, 1114, 1145,
	1162, 1194, 1222, 1238, 1256, 1273
	$\backslash\mathrm{um@usv@upgreek}$ . . . . .
	27, 804, 843, 851,
	955, 969, 1074, 1118, 1127, 1146,
	1163, 1195, 1223, 1239, 1257, 1274
	$\backslash\mathrm{um@usv@upLatin}$ 24, 796, 818, 820, 943,
	965, 982, 994, 1012, 1026, 1034,
	1039, 1047, 1053, 1059, 1068,

1099, 1101, 1142, 1159, 1176, 1182, 1189, 1219, 1235, 1253, 1270	\um_config_mathfrak_latin: . . . . . 1019
\um@usv@uplatin 25, 800, 825, 828, 946, 966, 990, 1005, 1020, 1027, 1035, 1040, 1048, 1054, 1060, 1070, 1104, 1107, 1143, 1160, 1177, 1183, 1190, 1220, 1236, 1254, 1271	\um_config_mathit: . . . . . 964
\um@usv@varepsilon . . . 74, 844, 852, 957, 973, 1081, 1119, 1128, 1150, 1167, 1201, 1227, 1243, 1261, 1278	\um_config_mathscr_Latin: . . . . . 993
\um@usv@varkappa . . . . 76, 846, 854, 959, 975, 1083, 1121, 1130, 1152, 1169, 1203, 1229, 1245, 1263, 1280	\um_config_mathscr_latin: . . . . . 1004
\um@usv@varphi . . . . . 77, 847, 855, 960, 976, 1084, 1122, 1131, 1153, 1170, 1204, 1230, 1246, 1264, 1281	\um_config_mathsf: . . . . . 1023
\um@usv@varpi . . . . . 79, 849, 857, 962, 978, 1086, 1124, 1133, 1155, 1172, 1206, 1232, 1248, 1266, 1283	\um_config_mathsfitt: . . . . . 1051
\um@usv@varrho . . . . . 78, 848, 856, 961, 977, 1085, 1123, 1132, 1154, 1171, 1205, 1231, 1247, 1265, 1282	\um_config_mathsfup: . . . . . 1045
\um@usv@varTheta 72, 802, 835, 838, 952, 972, 1077, 1112, 1115, 1147, 1164, 1198, 1207, 1224, 1240, 1258, 1275	\um_config_mathhtt: . . . . . 1057
\um@usv@vartheta . . . . 75, 845, 853, 958, 974, 1082, 1120, 1129, 1151, 1168, 1202, 1228, 1244, 1262, 1279	\um_config_mathup_Greek: . . . . . 949
\um@zf@feature . . . . . 595, 607, 610	\um_config_mathup_greek: . . . . . 954
\um_bfNabla_up_or_it_usv . . . . . . . . . . 212, 216, 470, 1136	\um_config_mathup_Latin: . . . . . 942
\um_bfpartial_up_or_it_usv . . . . . . . . . . 230, 234, 472, 1137	\um_config_mathup_latin: . . . . . 945
\um_bfsfNabla_up_or_it_usv 213, 217, 471	\um_fix_mathtt: . . . . . 918
\um_bfsfpartial_up_or_it_usv . . . . . . . . . . 231, 235, 473	\um_glyph_if_exist:n . . . . . 924
\um_config_mathbb: . . . . . 980	\um_glyph_if_exist:nT . . . . . 881
\um_config_mathbf: . . . . . 1063	\um_glyph_if_exist:nTF . . . . . . . . . 888, 906, 924, 1329, 1332, 1335
\um_config_mathbffrak: . . . . . 1174	\um_init_alphabet:n . . . . . 415, 921
\um_config_mathbffit: . . . . . 1140	\um_make_mathactive:nNN . . . . 487, 489
\um_config_mathbfscr: . . . . . 1180	\um_map_char:nn . . . . . 521, 524, 528–533, 536–541, 700, 799, 802, 826, 829, 835, 838, 844–849, 852–857
\um_config_mathbfsf: . . . . . 1186	\um_map_char:nn_ . . . . . 681
\um_config_mathbfsfit: . . . . . 1268	\um_map_chars_greek:nn . . . . . . . . 520, 523, 527, 535, 694, 801, 803, 804, 811–814, 834, 837, 843, 851
\um_config_mathbfsfup: . . . . . 1251	\um_map_chars_latin:nn . . . . . 510, 512, 515, 517, 691, 796–798, 800, 807–810, 818, 820, 825, 828
\um_config_mathbfup: . . . . . 1157	\um_map_chars_numbers:nn . . . . 497, 697
\um_config_mathfrak_Latin: . . . . 1011	\um_map_chars_range:nnn . . . . . . . . . . 681, 692, 695, 698, 701
	\um_mathmap:Nnn . . . . 413, 420, 706, 713
	\um_mathmap_noparse:Nnn . . . . 413, 547
	\um_mathmap_parse:Nnn . . . . 420, 552
	\um_maybe_init_alphabet:n . . . . . . . . . . 415, 422, 882, 907
	\um_Nabla_up_or_it_usv . . 211, 215, 457
	\um_nprimes:n 1319, 1329, 1332, 1335, 1338
	\um_nprimes_select:n . . . . 1325, 1356
	\um_partial_up_or_it_usv . 229, 233, 458
	\um_peek_execute_branches_ss: . . . . . . . . 1488, 1493
	\um_peek_execute_branches_ss_aux: . . . . . 1500, 1513
	\um_prepare_alph:n . . . . 883, 908, 927

<code>\um_process_symbol_noparse:nnnn</code> ..	1183, 1189–1192, 1219, 1220,
..... 412, <u>437</u>	1235, 1236, 1253, 1254, 1270, 1271
<code>\um_process_symbol_parse:nnnn</code> 419, <u>437</u>	<code>\um_set_mathalphabet_numbers:Nnn</code> .
<code>\um_remap_symbol:nnn</code> .....	..... 719,
..... 414, 421, 446, 447, 449,	981, 1025, 1033, 1038, 1046, 1052,
452–455, 457, 458, 461–468, 470–473	1058, 1064, 1141, 1158, 1175,
<code>\um_remap_symbol_noparse:nnn</code> 414, <u>445</u>	1181, 1188, 1218, 1234, 1252, 1269
<code>\um_remap_symbol_parse:nnn</code> 421, <u>445</u> , 476	<code>\um_set_mathcode:nnnn</code> <u>366</u> , 483, 564, 684
<code>\um_remap_symbols:</code> ..... 428, <u>445</u>	<code>\um_setup_active_subscript:nn</code> ...
<code>\um_scan_sscript:</code> 1403, 1436, 1473, 1475	..... 1427, 1441–1468
<code>\um_scan_sscript:TF</code> ..... 1474, 1483	<code>\um_setup_active_superscript:nn</code> ..
<code>\um_scanprime:</code> .....	..... 1394, 1408–1424
..... 1341, 1350, 1361, 1365, 1366	<code>\um_setup_alphabets:</code> ..... 431, 860
<code>\um_scanprime_collect:</code> .....	<code>\um_setup_alphanum:</code> ..... 430, <u>495</u>
..... 1343, 1345, 1348, 1351, 1354	<code>\um_setup_bf_literals:</code> ..... 507, 806
<code>\um_set_mathalph_range:Nnn</code> ..... <u>710</u>	<code>\um_setup_Greek:</code> ..... 503, <u>832</u>
<code>\um_set_mathalph_range:nNnn</code> .....	<code>\um_setup_greek:</code> ..... 504, <u>841</u>
..... 710, 720, 723, 726	<code>\um_setup_Latin:</code> ..... 501, <u>816</u>
<code>\um_set_mathalphabet_char:Nnn</code> ...	<code>\um_setup_latin:</code> ..... 502, <u>823</u>
... 704, 947, 951, 952, 956–962,	<code>\um_setup_literals:</code> ..... 499, <u>795</u>
967, 970–978, 983–989, 991,	<code>\um_setup_math_alphabet:n</code> .....
995–1002, 1006–1009, 1013–1017,	..... 862, 863, 866–877, 905
1021, 1030, 1036, 1041, 1049,	<code>\um_setup_math_alphabet:nn</code> .....
1055, 1061, 1065, 1066,	..... 861, 864, 865, <u>879</u>
1076–1096, 1105, 1108, 1112,	<code>\um_setup_mathactives:</code> ..... 429, <u>486</u>
1115, 1119–1125, 1128–1134,	<code>\um_setup_mathup:</code> ..... 1527
1136, 1137, 1144, 1147–1155,	<code>\um_setup_nabla:</code> ..... 209, 434
1161, 1164–1172, 1178, 1184,	<code>\um_setup_partial:</code> ..... 227, 435
1193, 1198–1215, 1221,	<code>\um_setup_shapes:</code> ..... 427, 433
1224–1232, 1237, 1240–1248,	<code>\um_sub_or_super:n</code> ... 1401, 1434, 1477
1255, 1258–1266, 1272, 1275–1283	<code>\um_symfont_tl</code> ..... 410,
<code>\um_set_mathalphabet_char:Nnnn</code> .. <u>703</u>	418, 424, 438, 483, 491, 549, 556, 686
<code>\um_set_mathalphabet_greek:Nnn</code> ..	<code>\UnicodeMathSymbol</code> ..... 412, 419, 1304
..... 725, 950, 955,	<code>\unless</code> ..... 626
968, 969, 1072–1075, 1111, 1114,	<code>\updefault</code> ..... 425, 919
1118, 1127, 1145, 1146, 1162,	<code>\upint</code> ..... 572
1163, 1194–1197, 1222, 1223,	<code>\Upsilon</code> ..... 750
1238, 1239, 1256, 1257, 1273, 1274	<code>\upsilon</code> ..... 777
<code>\um_set_mathalphabet_latin:Nnn</code> ..	<code>\use:c</code> ..... 889, 909, 914, 930, 938
..... 722, 943, 946, 965, 966,	<code>\use_none:n</code> ..... 422
982, 990, 994, 1005, 1012, 1020,	
1026–1029, 1034, 1035, 1039,	<b>V</b>
1040, 1047, 1048, 1053, 1054,	<code>\varepsilon</code> ..... 784
1059, 1060, 1068–1071, 1099,	<code>\varkappa</code> ..... 788
1101, 1104, 1107, 1142, 1143,	<code>\varointclockwise</code> ..... 569
1159, 1160, 1176, 1177, 1182,	<code>\varphi</code> ..... 789
	<code>\varpi</code> ..... 793

