

Experimental unicode mathematical typesetting: The unicode-math package

Will Robertson

2009/10/30 v0.4

Abstract

Warning! This package is experimental and subject to change without regard for backwards compatibility. Performance issues may be encountered until algorithms are refined.

This package is intended to be a complete implementation of unicode maths for \LaTeX using the \XeTeX (and later, \LuaTeX) typesetting engines. With this package, changing maths fonts will be as easy as changing text fonts — not that there are many unicode maths fonts yet.

Maths input is simplified with unicode since literal glyphs may be entered instead of control sequences.

Contents

1	Introduction	3	7.2	Setting math chars, math codes, etc.	29
2	Acknowledgements	3	7.3	The main <code>\setmathfont</code> macro	31
3	Getting started	3	7.4	(Big) operators	37
3.1	Package options	3	7.5	Radicals	40
4	Unicode maths font setup	4	7.6	Delimiters	41
4.1	Using multiple fonts	5	7.7	Maths accents	43
4.2	Script and scriptscript fonts/features	6	8	Font features	44
5	Maths input	6	8.1	OpenType maths font features	44
5.1	Math ‘style’	6	8.2	Script and scriptscript font options	44
5.2	Bold style	7	8.3	Range processing	45
5.3	Sans serif style	8	8.4	Resolving Greek symbol name control sequences	51
5.4	All (the rest) of the mathematical alphabets	9	9	Maths alphabets mapping definitions	52
5.5	Miscellanea	10	9.1	Alphabets	56
I	The unicode-math package	16	10	Definitions of the math symbols	70
6	Things we need	16	11	Epilogue	71
6.1	Options	24	12	stix table data extraction	84
6.2	Overcoming <code>\@on-</code> lypreamble	28	A	Documenting maths support in the NFSS	85
7	Fundamentals	29	B	X_YTeX math font dimensions	87
7.1	Enlarging the number of maths families	29			

1 Introduction

This document describes the unicode-math package, which is an *experimental* implementation of a macro to unicode glyph encoding for mathematical characters. Its intended use is for \XeTeX , although it is conjectured that some effect could be spent to create a cross-format package that would also work with \LuaTeX .

Users who desire to specify maths alphabets only (Greek and Latin letters) may wish to use Andrew Moschou’s mathspec package instead.

2 Acknowledgements

Many thanks to Microsoft for developing OpenType math as part of Office 2007; Jonathan Kew for implementing unicode math support in \XeTeX ; Barbara Beeton for her prodigious effort compiling the definitive list of unicode math glyphs and their \LaTeX names (inventing them where necessary), and also for her thoughtful replies to my sometimes incessant questions. Ross Moore and Chris Rowley have provided moral and technical support from the very early days with great insight into the issues we face trying to extend and use \TeX in the future. Apostolos Syropoulos, Joel Salomon, and Khaled Hosny have been fantastic beta testers.

3 Getting started

Load unicode-math as a regular \LaTeX package. It should be loaded after any other maths or font-related package in case it needs to overwrite their definitions. Here’s an example:

```
\usepackage{amsmath} % if desired
\usepackage{unicode-math}
\setmathfont{Cambria Math}
```

3.1 Package options

Package options may be set when the package is loaded or at any later stage with the `\unimathsetup` command. Therefore, the following two examples are equivalent:

```
\usepackage[math-style=TeX]{unicode-math}
% OR
\usepackage{unicode-math}
\unimathsetup{math-style=TeX}
```

Table 1: Package options.

Option	Description	See...
<code>math-style</code>	Style of letters	section §5.1
<code>bold-style</code>	Style of bold letters	section §5.2
<code>sans-style</code>	Style of sans serif letters	section §5.3
<code>nabla</code>	Style of the nabla symbol	section §5.5.1
<code>partial</code>	Style of the partial symbol	section §5.5.2
<code>vargreek-shape</code>	Style of phi and epsilon	section §5.5.3
<code>colon</code>	Behaviour of <code>\colon</code>	section §5.5.6
<code>slash-delimiter</code>	Glyph to use for ‘stretchy’ slash	section §5.5.7

Note, however, that some package options affects how maths is initialised and changing an option such as `math-style` will not take effect until a new maths font is set up.

Package options may *also* be used when declaring new maths fonts, passed via options to the `\setmathfont` command. Therefore, the following two examples are equivalent:

```
\unimathsetup{math-style=TeX}
\setmathfont{Cambria Math}
% OR
\setmathfont[math-style=TeX]{Cambria Math}
```

A short list of package options is shown in table 1. See following sections for more information.

4 Unicode maths font setup

In the ideal case, a single unicode font will contain all maths glyphs we need. The file `unicode-math-table.tex` (based on Barbara Beeton’s `stix` table) provides the mapping between unicode maths glyphs and macro names (all 3298 — or however many — of them!). A single command

```
\setmathfont[<font features>]{<font name>}
```

implements this for every every symbol and alphabetic variant. That means `x` to x , `\xi` to ξ , `\leq` to \leq , etc., `\mathcal{H}` to \mathcal{H} and so on, all for unicode glyphs within a single font.

This package deals well with unicode characters for maths input. This includes using literal Greek letters in formulae, resolving to upright or italic depending on preference.

Font features specific to `unicode-math` are shown in table 2. Package options (see table 1) may also be used. Other `fontspec` features are also valid.

Table 2: Maths font options.

Option	Description	See...
<code>range</code>	Style of letters	section §4.1
<code>script-font</code>	Font to use for sub- and super-scripts	section §4.2
<code>script-features</code>	Font features for sub- and super-scripts	section §4.2
<code>sscript-font</code>	Font to use for nested sub- and super-scripts	section §4.2
<code>sscript-features</code>	Font features for nested sub- and super-scripts	section §4.2

4.1 Using multiple fonts

There will probably be few cases where a single unicode maths font suffices (simply due to glyph coverage). The upcoming `srix` font comes to mind as a possible exception. It will therefore be necessary to delegate specific unicode ranges of glyphs to separate fonts:

```
\setmathfont[range=<unicode range>,<font features>]{<font name>}
```

where *<unicode range>* is a comma-separated list of unicode slots and ranges such as `{"27D0-"27EB", "27FF", "295B-"297F"}`. You may also use the macro for accessing the glyph, such as `\int`, or whole collection of symbols with the same math type, such as `\mathopen`, or complete math alphabets such as `\mathbb`. (Only numerical slots, however, can be used in ranged declarations.)

4.1.1 Control over maths alphabets

Exact control over maths alphabets can be somewhat involved. Here is the current plan.

- `[range=\mathbb]` to use the font for ‘bb’ letters only.
- `[range=\mathbfsfit/{greek,Greek}]` for Greek lowercase and uppercase only (with `latin`, `Latin`, `num` as well for Latin lower-/upper-case and numbers).
- `[range=\mathsf->\mathbfsfit]` to map to different output alphabet(s) (which is rather useless right now but will become less useless in the future).

And now the trick. If a particular math alphabet is not defined in the font, fall back onto the lower-base plane (i.e., upright) glyphs. Therefore, to use an ASCII-encoded fractur font, for example, write

```
\setmathfont[range=\mathfrak]{SomeFrakturFont}
```

and because the math plane fractur glyphs will be missing, unicode-math will know to use the ASCII ones instead. If necessary (but why?) this behaviour can be forced with `[range=\mathfrac->\mathup]`.

4.2 Script and scriptscript fonts/features

Cambria Math uses OpenType font features to activate smaller optical sizes for scriptsize and scriptscriptsize symbols (the B and C , respectively, in A_{B_C}). Other fonts will possibly use entirely separate fonts.

Not yet implemented: Both of these options must be taken into account. I hope this will be mostly automatic from the users' points of view. The `+ssty` feature can be detected and applied automatically, and appropriate optical size information embedded in the fonts will ensure this latter case. Fine tuning should be possible automatically with `fontspec` options. We might have to wait until MnMath, for example, before we really know.

5 Maths input

X_YTeX's unicode support allows maths input through two methods. Like classical TeX, macros such as `\alpha`, `\sum`, `\pm`, `\leq`, and so on, provide verbose access to the entire repertoire of characters defined by unicode. The literal characters themselves may be used instead, for more readable input files.

5.1 Math 'style'

Classically, TeX uses italic lowercase Greek letters and *upright* uppercase Greek letters for variables in mathematics. This is contrary to the ISO standards of using italic forms for both upper- and lowercase. Furthermore, the French (contrary again, *quelle surprise*) have been known to use upright uppercase *Latin* letters as well as upright upper- and lowercase Greek. Finally, it is not unknown to use upright letters for all characters, as seen in the Euler fonts.

The unicode-math package accommodates these possibilities with an interface heavily inspired by Walter Schmidt's `lucimatx` package: a package option `math-style` that takes one of four arguments: `TeX`, `ISO`, `French`, or `upright` (case insensitive).

The philosophy behind the interface to the mathematical alphabet symbols lies in L^ATeX's attempt of separating content and formatting. Because input source text may come from a variety of places, the upright and 'mathematical' italic Latin and Greek alphabets are *unified* from the point of view of having a specified meaning in the source text. That is, to get a mathematical ' x ', either the ascii ('keyboard') letter `x` may be typed, or the actual unicode character may be used. Similarly for Greek letters. The upright or italic forms are then chosen based on the `math-style` package option.

If glyphs are desired that do not map as per the package option (for example, an upright ' g ' is desired but typing `g` yields ' g '), *markup* is required to specify this; to follow from the example: `\mathup{g}`. Maths alphabets commands such as `\mathup` are detailed later.

Table 3: Effects of the `math-style` package option.

Package option	Example	
	Latin	Greek
<code>math-style=ISO</code>	(a, z, B, X)	$(\alpha, \beta, \Gamma, \Xi)$
<code>math-style=TeX</code>	(a, z, B, X)	$(\alpha, \beta, \Gamma, \Xi)$
<code>math-style=French</code>	(a, z, B, X)	$(\alpha, \beta, \Gamma, \Xi)$
<code>math-style=upright</code>	(a, z, B, X)	$(\alpha, \beta, \Gamma, \Xi)$

Alternative interface However, some users may not like this convention of normalising their input. For them, an upright x is an upright ‘ x ’ and that’s that. (This will be the case when obtaining source text from copy/pasting PDF or Microsoft Word documents, for example.) For these users, the `literal` option to `math-style` will effect this behaviour.

The `math-style` options’ effects are shown in brief in table 3.

5.2 Bold style

Similar as in the previous section, ISO standards differ somewhat to \TeX ’s conventions (and classical typesetting) for ‘boldness’ in mathematics. In the past, it has been customary to use bold *upright* letters to denote things like vectors and matrices. For example, $\mathbf{M} = (M_x, M_y, M_z)$. Presumably, this was due to the relatively scarcity of bold italic fonts in the pre-digital typesetting era. It has been suggested that *italic* bold symbols are used nowadays instead.

Bold Greek letters have simply been bold variant glyphs of their regular weight, as in $\xi = (\xi_r, \xi_\varphi, \xi_\theta)$. Confusingly, the syntax in \LaTeX has been different for these two examples: `\mathbf{f}` in the former (‘ \mathbf{M} ’), and `\bm` (or `\boldsymbol`, deprecated) in the latter (‘ ξ ’).

In `unicode-math`, the `\mathbf{f}` command works directly with both Greek and Latin maths alphabet characters and depending on package option either switches to upright for Latin letters (`bold-style=TeX`) as well or keeps them italic (`bold-style=ISO`).

To match the package options for non-bold characters, for `bold-style=upright` all bold characters are upright, and `bold-style=literal` does not change the upright/italic shape of the letter.

Upright and italic bold mathematical letters input as direct unicode characters are normalised with the same rules. For example, with `bold-style=TeX`, a literal bold italic latin character will be typeset upright.

Note that `bold-style` is independent of `math-style`, although if the former is not specified then sensible defaults are chosen based on the latter.

The `bold-style` options’ effects are shown in brief in table 4.

Table 4: Effects of the `bold-style` package option.

Package option	Example	
	Latin	Greek
<code>bold-style=ISO</code>	$(\mathbf{a}, \mathbf{z}, \mathbf{B}, \mathbf{X})$	$(\alpha, \beta, \Gamma, \Xi)$
<code>bold-style=TeX</code>	$(\mathbf{a}, \mathbf{z}, \mathbf{B}, \mathbf{X})$	$(\alpha, \beta, \Gamma, \Xi)$
<code>bold-style=upright</code>	$(\mathbf{a}, \mathbf{z}, \mathbf{B}, \mathbf{X})$	$(\alpha, \beta, \Gamma, \Xi)$

5.3 Sans serif style

Unicode contains upright and italic, medium and bold mathematical alphabet characters. These may be explicitly selected with the `\mathsfup`, `\mathsfit`, `\mathbfsup`, and `\mathbfsfit` commands discussed in section §5.4.

How should the generic `\mathsf` behave? Unlike bold, sans serif is used much more sparingly in mathematics. I’ve seen recommendations to typeset tensors in sans serif italic or sans serif italic bold (e.g., examples in the `isomath` and `mattens` packages). But L^AT_EX’s `\mathsf` is *upright* sans serif.

Therefore I reluctantly add the package options `[sans-style=upright]` and `[sans-style=italic]` to control the behaviour of `\mathsf`. The `upright` style sets up the command to use the seemingly-useless upright sans serif, including Greek; the `italic` style switches to using italic in both Latin and Greek alphabets. In other words, this option simply changes the meaning of `\mathsf` to either `\mathsfup` or `\mathsfit`, respectively. Please let me know if more granular control is necessary here.

There is also a `[sans-style=literal]` setting, set automatically with `[math-style=literal]`, which retains the uprightness of the input characters used when selecting the sans serif output.

5.3.1 What about bold sans serif?

While you might want your bold upright and your sans serif italic, I don’t believe you’d also want your bold sans serif upright (or all vice versa, if that’s even conceivable). Therefore, bold sans serif follows from the setting for sans serif; it is completely independent of the setting for bold.

In other words, `\mathbfsf` is `\mathbfsup` or `\mathbfsfit` based on `[sans-style=upright]` or `[sans-style=italic]`, respectively. And `[sans-style=literal]` causes `\mathbfsf` to retain the same italic or upright shape as the input, and turns it bold sans serif.

Note well! There is no medium-weight sans serif Greek alphabet in unicode; therefore, `\mathsf{\alpha}` does not make sense (simply produces ‘ α ’) while `\mathbfsf{\alpha}` gives ‘ α ’.

Table 5: Mathematical alphabets defined in unicode. Black dots indicate an alphabet exists in the font specified; grey dots indicate shapes that should always be taken from the upright font even in the italic style. See main text for description of `\mathbbit`.

Font				Alphabet		
Style	Shape	Series	Switch	Latin	Greek	Numerals
Serif	Upright	Normal	<code>\mathup</code>	•	•	•
		Bold	<code>\mathbfup</code>	•	•	•
	Italic	Normal	<code>\mathit</code>	•	•	•
		Bold	<code>\mathbfit</code>	•	•	•
Sans serif	Upright	Normal	<code>\mathsfup</code>	•		•
	Italic	Normal	<code>\mathsfit</code>	•		•
	Upright	Bold	<code>\mathsfbfup</code>	•	•	•
	Italic	Bold	<code>\mathsfbfit</code>	•	•	•
Typewriter	Upright	Normal	<code>\mathtt</code>	•		•
Double-struck	Upright	Normal	<code>\mathbb</code>	•		•
	Italic	Normal	<code>\mathbbit</code>	•		
Script	Upright	Normal	<code>\mathscr</code>	•		
		Bold	<code>\matbfscr</code>	•		
Fraktur	Upright	Normal	<code>\mathfrak</code>	•		
		Bold	<code>\mathbffrac</code>	•		

5.4 All (the rest) of the mathematical alphabets

Unicode contains separate codepoints for most if not all variations of alphabet shape one may wish to use in mathematical notation. The complete list is shown in table 5. Some of these have been covered in the previous sections.

At present, the math font switching commands do not nest; therefore if you want sans serif bold, you must write `\mathsfbf{...}` rather than `\mathbf{\mathsf{...}}`. This may change in the future.

5.4.1 Double-struck

The double-struck alphabet (also known as ‘blackboard bold’) consists of upright Latin letters $\{a-z, A-Z\}$, numerals $\mathbb{0}-\mathbb{9}$, summation symbol $\mathbb{\Sigma}$, and four Greek letters only: $\{\mathbb{V}, \mathbb{W}, \mathbb{F}, \mathbb{M}\}$.

While `\mathbb{\sum}` does produce a double-struck summation symbol, its limits aren’t properly aligned (see section §??). Therefore, either the literal character or the control sequence `\Bbbsum` are recommended instead.

There are also five Latin *italic* double-struck letters: $\mathbb{D}, \mathbb{d}, \mathbb{I}, \mathbb{i}, \mathbb{J}$. These can be accessed (if not with their literal characters or control sequences) with the `\mathbbit`

Table 6: The various forms of nabla.

Description		Glyph
Upright	Serif	∇
	Bold serif	∇
	Bold sans	∇
Italic	Serif	∇
	Bold serif	∇
	Bold sans	∇

alphabet switch, but note that only those five letters will give the expected output.

5.5 Miscellanea

5.5.1 Nabla

The symbol ∇ comes in the six forms shown in table 6. We want an individual option to specify whether we want upright or italic nabla by default (when either upright or italic nabla is used in the source). \TeX classically uses an upright nabla, but iso standards differ (I think). The package options `nabla=upright` and `nabla=italic` switch between the two choices, and `nabla=literal` respects the shape of the input character. This is then inherited through `\mathbf`; `\mathit` and `\mathup` can be used to force one way or the other.

`nabla=italic` is implicit when using `math-style=ISO` and `nabla=upright` follows both `math-style=TeX` and `math-style=French`. `nabla=literal` is activated by default after `math-style=literal`.

5.5.2 Partial

The same applies to the symbols `u+2202` partial differential and `u+1D715` math italic partial differential.

At time of writing, both the Cambria Math and STIX fonts display these two glyphs in the same italic style, but this is hopefully a bug that will be corrected in the future — the ‘plain’ partial differential should really have an upright shape.

Use the `partial=upright` or `partial=italic` package options to specify which one you would like, or `partial=literal` to have the same character used in the output as was used for the input. The default is (always, unless someone requests and argues otherwise) `partial=italic`.¹ `partial=literal` is activated following `math-style=literal`.

See table 7 for the variations on the partial differential symbol.

¹A good argument would revolve around some international standards body recommending upright over italic. I just don’t have the time right now to look it up.

Table 7: The various forms of the partial differential. Note that in the fonts used to display these glyphs, the first upright partial is incorrectly shown in an italic style.

Description		Glyph
Regular	Upright	∂
	Italic	∂
Bold	Upright	∂
	Italic	∂
Sans bold	Upright	
	Italic	

5.5.3 Epsilon and phi: ε vs. ϵ and φ vs. ϕ

\TeX defines `\epsilon` to look like ϵ and `\varepsilon` to look like ε . The Unicode glyph directly after delta and before zeta is ‘epsilon’ and looks like ε ; there is a subsequent variant of epsilon that looks like ϵ . This creates a problem. People who use unicode input won’t want their glyphs transforming; \TeX users will be confused that what they think as ‘normal epsilon’ is actual the ‘variant epsilon’. And the same problem exists for ‘phi’.

We have a package option to control this behaviour. With `\vargreek-shape=TeX`, `\phi` and `\epsilon` produce ϕ and ε and `\varphi` and `\varepsilon` produce ϕ and ϵ . With `\vargreek-shape=unicode`, these symbols are swapped. Note, however, that unicode characters are not affected by this option. That is, no remapping occurs of the characters/glyphs, only the control sequences.

The package default is to use `\vargreek-shape=TeX`.

5.5.4 Primes

Primes (x') may be input in several ways. You may use any combination of ASCII straight quote (‘), unicode prime U+2032 (’), and `\prime`; when multiple primes occur next to each other, they chain together to form double, triple, or quadruple primes if the font contains pre-drawn glyphs. These may also be accessed with `\dprime`, `\trprime`, and `\qprime`, respectively.

If the font does not contain the pre-drawn glyphs or more than four primes are used, the single prime glyph is used multiple times with a negative kern to get the spacing right. There is no user interface to adjust this negative kern yet (because I haven’t decided what it should look like); if you need to, write something like this:

```
\ExplSyntaxOn
\muskip_gset:Nn \g_um_primekern_muskip { -\thinmuskip/2 }
\ExplSyntaxOff
```

A 0 1 2 3 4 5 6 7 8 9 + - = () i n Z

Figure 1: The unicode superscripts supported as input characters. These are the literal glyphs from Charis SIL, not the output seen when used for maths input. The ‘A’ and ‘Z’ are to provide context for the size and location of the superscript glyphs.

A 0 1 2 3 4 5 6 7 8 9 + - = () a e i o r u v x β γ ρ ϕ χ Z

Figure 2: The unicode subscripts supported as input characters. See note from figure 1.

Backwards or reverse primes behave in exactly the same way; use any of `ASCII` back tick (```), unicode reverse prime `U+2035` (`'`), or `\backprime` to access it. Multiple backwards primes can also be called with `\backdprime`, `\backtrprime`, and `\backqprime`.

If you ever need to enter the straight quote `'` or the backtick ``` in maths mode, these glyphs can be accessed with `\mathstraightquote` and `\mathbacktick`.

5.5.5 Unicode subscripts and superscripts

You may, if you wish, use unicode subscripts and superscripts in your source document. For basic expressions, the use of these characters can make the input more readable. Adjacent sub- or super-scripts will be concatenated into a single expression.

The range of subscripts and superscripts supported by this package are shown in figures 1 and 2. Please request more if you think it is appropriate.

5.5.6 Colon

The colon is one of the few confusing characters of unicode maths. In \TeX , `:` is defined as a colon with relation spacing: `'a : b'`. While `\colon` is defined as a colon with punctuation spacing: `'a:b'`.

In unicode, `U+003A` colon is defined as a punctuation symbol, while `U+2236` ratio is the colon-like symbol used in mathematics to denote ratios and other things.

This breaks the usual straightforward mapping from control sequence to unicode input character to (the same) unicode glyph.

To preserve input compatibility, we remap the `ASCII` input character `':'` to `U+2236`. Typing a literal `U+2236` char will result in the same output. If `amsmath` is loaded, then the definition of `\colon` is inherited from there (it looks like a

Table 8: Slashes and backslashes.

Slot	Name	Glyph	Command
U+002F	SOLIDUS	/	<code>\solidus</code>
U+2044	FRACTION SLASH	/	<code>\fracslash</code>
U+2215	DIVISION SLASH	/	<code>\slash</code>
U+29F8	BIG SOLIDUS	/	<code>\xsol</code>
U+005C	REVERSE SOLIDUS	\	<code>\backslash</code>
U+2216	SET MINUS	\	<code>\smallsetminus</code>
U+29F5	REVERSE SOLIDUS OPERATOR	\	<code>\setminus</code>
U+29F9	BIG REVERSE SOLIDUS	\	<code>\xbsol</code>

punctuation colon with additional space around it). Otherwise, `\colon` is made to output a colon with `\mathpunct` spacing.

The package option `colon=literal` forces ASCII input ‘:’ to be printed as `\mathcolon` instead.

5.5.7 Slashes and backslashes

There are several slash-like symbols defined in unicode. The complete list is shown in table 8.

In regular \LaTeX we can write `\left\slash...\right\backslash` and so on and obtain extensible delimiter-like symbols. Not all of the unicode slashes are suitable for this (and do not have the font support to do it).

Slash Of U+2044 fraction slash, TR25 says that it is:

...used to build up simple fractions in running text...however parsers of mathematical texts should be prepared to handle fraction slash when it is received from other sources.

U+2215 division slash should be used when division is represented without a built-up fraction; $\pi \approx 22/7$, for example.

U+29F8 big solidus is a ‘big operator’ (like Σ).

Backslash The U+005C reverse solidus character `\backslash` is used for denoting double cosets: $A \backslash B$. (So I’m led to believe.) It may be used as a ‘stretchy’ delimiter if supported by the font.

MathML uses U+2216 set minus like this: $A \setminus B$.² The \LaTeX command name `\smallsetminus` is used for backwards compatibility.

²§4.4.5.11 <http://www.w3.org/TR/MathML3/>

Presumably, u+29F5 reverse solidus operator is intended to be used in a similar way, but it could also (perhaps?) be used to represent ‘inverse division’: $\pi \approx 7 \setminus 22$.³ The L^AT_EX name for this character is `\setminus`.

Finally, u+29F9 big reverse solidus is a ‘big operator’ (like Σ).

How to use all of these things Unfortunately, font support for the above characters/glyphs is rather inconsistent. In Cambria Math, the only slash that grows (say when writing

$$\left[\begin{array}{cc} a & b \\ c & d \end{array} \right] / \left[\begin{array}{cc} 1 & 1 \\ 1 & 0 \end{array} \right])$$

is the `FRACTION SLASH`, which we just established above is sort of only supposed to be used in text.

Of the above characters, the following are allowed to be used after `\left`, `\middle`, and `\right`:

- `\solidus`;
- `\fracdash`;
- `\slash`; and,
- `\backslash` (the only reverse slash).

However, we assume that there is only *one* stretchy slash in the font; this is assumed by default to be u+002F solidus. Writing `\left/` or `\left\slash` or `\leftfracdash` will all result in the same stretchy delimiter being used.

The delimiter used can be changed with the `slash-delimiter` package option. Allowed values are `ascii`, `frac`, and `div`, corresponding to the respective unicode slots.

For example: as mentioned above, Cambria Math’s stretchy slash is u+2044 fraction slash. When using Cambria Math, then `unicode-math` should be loaded with the `slash-delimiter=frac` option. (This should be a font option rather than a package option, but it will change soon.)

5.5.8 Pre-drawn fraction characters

Pre-drawn fractions u+00BC – u+00BE , u+2150 – u+215E are not suitable for use in mathematics output. However, they can be useful as input characters to abbreviate common fractions.

$\frac{1}{4}$ $\frac{1}{2}$ $\frac{3}{4}$ $\frac{1}{3}$ $\frac{2}{3}$ $\frac{1}{5}$ $\frac{2}{5}$ $\frac{3}{5}$ $\frac{4}{5}$ $\frac{1}{6}$ $\frac{5}{6}$ $\frac{1}{8}$ $\frac{3}{8}$ $\frac{5}{8}$ $\frac{7}{8}$

For example, instead of writing ‘`\tfrac{12}{x}`’, it’s more readable to have ‘ $\frac{12}{x}$ ’ in the source instead.

³This is valid syntax in the Octave and Matlab programming languages, in which it means matrix inverse pre-multiplication. I.e., $A \setminus B \equiv A^{-1}B$.

Slot	Command	Glyph	Glyph	Command	Slot
U+00B7	<code>\cdotp</code>	.			
U+22C5	<code>\cdot</code>	.			
U+2219	<code>\vysmbkcircle</code>	•	◦	<code>\vysmwhtcircle</code>	U+2218
U+2022	<code>\smbkcircle</code>	•	◦	<code>\smwhtcircle</code>	U+25E6
U+2981	<code>\mdsmbkcircle</code>	●	◉	<code>\mdsmwhtcircle</code>	U+26AC
U+26AB	<code>\mdbkcircle</code>	●	◯	<code>\mdwhtcircle</code>	U+26AA
U+25CF	<code>\mdlgbkcircle</code>	●	◯	<code>\mdlgwhtcircle</code>	U+25CB
U+2B24	<code>\lgbkcircle</code>	●	◯	<code>\lgwhtcircle</code>	U+25EF

Table 9: Filled and hollow unicode circles.

If the `\tfrac` command exists (i.e., if `amsmath` is loaded or you have specially defined `\tfrac` for this purpose), it will be used to typeset the fractions. If not, regular `\frac` will be used. The command to use (`\tfrac` or `\frac`) can be forced either way with the package option `active-frac=small` or `active-frac=normalsize`, respectively.

5.5.9 Circles

Unicode defines a large number of different types of circles for a variety of mathematical purposes. There are thirteen alone just considering the all white and all black ones, shown in table 9.

L^AT_EX defines considerably fewer: `\circ` and `\bigcirc` for white; `\bullet` for black. This package maps those commands to `\vysmwhtcircle`, `\mdlgwhtcircle`, and `\smbkcircle`, respectively.

5.5.10 Triangles

While there aren't as many different sizes of triangle as there are circle, there's some important distinctions to make between a few similar characters. Namely, Δ and \triangle and Δ and Δ . See table 10 for the full summary.

These triangles all have different intended meanings. Note for backwards compatibility with T_EX, U+25B3 has *two* different mappings in unicode-math. `\bigtriangleup` is intended as a binary operator whereas `\triangle` is intended to be used as a letter-like symbol.

But you're better off if you're using the latter form to indicate an increment to use the glyph intended for this purpose: Δx .

Finally, given that Δ and Δ are provided for you already, it is better off to only use upright Greek Delta Δ if you're actually using it as a symbolic entity such as a variable on its own.

Slot	Command	Glyph	Class
U+25B5	<code>\vartriangle</code>	\triangle	binary
U+25B3	<code>\bigtriangleup</code>	\bigtriangleup	binary
U+25B3	<code>\triangle</code>	\triangle	ordinary
U+2206	<code>\increment</code>	Δ	ordinary
U+0394	<code>\mathup\Delta</code>	Δ	ordinary

Table 10: Different upwards pointing triangles.

5.5.11 Normalising some input characters

I believe all variant forms should be used as legal input that is normalised to a consistent output glyph, because we want to be fault-tolerant in the input. Here are the duplicates:

U+251 latin small letter alpha
 U+25B latin small letter epsilon
 U+263 latin small letter gamma
 U+269 latin small letter iota
 U+278 latin small letter phi
 U+28A latin small letter upsilon
 U+190 latin capital letter epsilon
 U+194 latin capital letter gamma
 U+196 latin capital letter iota
 U+1B1 latin capital letter upsilon

(Not yet implemented.)

File I

The unicode-math package

This is the package.

```

1 \ProvidesPackage{unicode-math}
2 [2009/10/30 v0.4 Unicode maths in XeLaTeX]
```

6 Things we need

Packages


```

3 \RequirePackage{expl3}[2009/08/12]
4 \RequirePackage{xparse}[2009/08/31]
5 \RequirePackage{fontspec}

   Start using LATEX3 — finally!
6 \ExplSyntaxOn
7 \@ifclassloaded{memoir}{
8   \cs_set_eq:NN \um_after_pkg:nn \AtEndPackage
9 }{
10  \RequirePackage{scrfile}
11  \cs_set_eq:NN \um_after_pkg:nn \AfterPackage
12 }

```

Extra expl3 variants

```

13 \cs_generate_variant:Nn \tl_put_right:Nn {cx}
14 \cs_generate_variant:Nn \seq_if_in:NnTF {NV}
15 \cs_generate_variant:Nn \prop_gput:Nnn {Nxn}
16 \cs_generate_variant:Nn \prop_get:NnN {cxN}
17 \cs_generate_variant:Nn \prop_if_in:NnTF {cx}

```

Conditionals

```

18 \bool_new:N \l_um_fontspec_feature_bool
19 \bool_new:N \l_um_ot_math_bool
20 \bool_new:N \l_um_init_bool
21 \bool_new:N \l_um_implicit_alph_bool

```

For math-style:

```

22 \bool_new:N \g_um_literal_bool
23 \bool_new:N \g_um_upLatin_bool
24 \bool_new:N \g_um_uplatin_bool
25 \bool_new:N \g_um_upGreek_bool
26 \bool_new:N \g_um_upgreek_bool

```

For bold-style:

```

27 \bool_new:N \g_um_bfliteral_bool
28 \bool_new:N \g_um_bfupLatin_bool
29 \bool_new:N \g_um_bfuplatin_bool
30 \bool_new:N \g_um_bfupGreek_bool
31 \bool_new:N \g_um_bfupgreek_bool

```

For sans-style:

```

32 \bool_new:N \g_um_upsans_bool
33 \bool_new:N \g_um_sfliteral_bool

```

For assorted package options:

```

34 \bool_new:N \g_um_upNabla_bool
35 \bool_new:N \g_um_uppartial_bool

```

```

36 \bool_new:N \g_um_literal_Nabla_bool
37 \bool_new:N \g_um_literal_partial_bool
38 \bool_new:N \g_um_texgreek_bool
39 \bool_new:N \l_um_smallfrac_bool
40 \bool_new:N \g_um_literal_colon_bool

```

Variables

```

41 \int_new:N \g_um_fam_int

42 \tl_set:Nn \g_um_math_alphabet_name_latin_tl {Latin,~lowercase}
43 \tl_set:Nn \g_um_math_alphabet_name_Latin_tl {Latin,~uppercase}
44 \tl_set:Nn \g_um_math_alphabet_name_greek_tl {Greek,~lowercase}
45 \tl_set:Nn \g_um_math_alphabet_name_Greek_tl {Greek,~uppercase}
46 \tl_set:Nn \g_um_math_alphabet_name_num_tl {Numerals}
47 \tl_set:Nn \g_um_math_alphabet_name_misc_tl {Misc.}

```

6.0.12 Alphabet unicode positions

Before we begin, let's define the positions of the various unicode alphabets so that our code is a little more readable.⁴

Rather than 'readable', in the end, this makes the code more extensible.

```

48 \cs_new:Nn \usv_set:nnn {
49   \tl_set:cn { \um_to_usv:nn {#1}{#2} } {#3}
50 }
51 \cs_new:Nn \um_to_usv:nn { g_um_#1_#2_usv }

```

Alphabets

```

52 \usv_set:nnn {up}{num}{48}
53 \usv_set:nnn {up}{Latin}{65}
54 \usv_set:nnn {up}{latin}{97}
55 \usv_set:nnn {up}{Greek}{"391}
56 \usv_set:nnn {up}{greek}{"3B1}
57 \usv_set:nnn {it}{Latin}{"1D434}
58 \usv_set:nnn {it}{latin}{"1D44E}
59 \usv_set:nnn {it}{Greek}{"1D6E2}
60 \usv_set:nnn {it}{greek}{"1D6FC}
61 \usv_set:nnn {bb}{num}{"1D7D8}
62 \usv_set:nnn {bb}{Latin}{"1D538}
63 \usv_set:nnn {bb}{latin}{"1D552}
64 \usv_set:nnn {scr}{Latin}{"1D49C}
65 \usv_set:nnn {scr}{latin}{"1D4B6}
66 \usv_set:nnn {frak}{Latin}{"1D504}
67 \usv_set:nnn {frak}{latin}{"1D51E}
68 \usv_set:nnn {sf}{num}{"1D7E2}

```

⁴'u.s.v.' stands for 'unicode scalar value'.

69 \usv_set:nnn {sfup}{num}{1D7E2}
 70 \usv_set:nnn {sfit}{num}{1D7E2}
 71 \usv_set:nnn {sfup}{Latin}{1D5A0}
 72 \usv_set:nnn {sf}{Latin}{1D5A0}
 73 \usv_set:nnn {sfup}{latin}{1D5BA}
 74 \usv_set:nnn {sf}{latin}{1D5BA}
 75 \usv_set:nnn {sfit}{Latin}{1D608}
 76 \usv_set:nnn {sfit}{latin}{1D622}
 77 \usv_set:nnn {tt}{num}{1D7F6}
 78 \usv_set:nnn {tt}{Latin}{1D670}
 79 \usv_set:nnn {tt}{latin}{1D68A}

Bold:

80 \usv_set:nnn {bf}{num}{1D7CE}
 81 \usv_set:nnn {bfup}{num}{1D7CE}
 82 \usv_set:nnn {bfit}{num}{1D7CE}
 83 \usv_set:nnn {bfup}{Latin}{1D400}
 84 \usv_set:nnn {bfup}{latin}{1D41A}
 85 \usv_set:nnn {bfup}{Greek}{1D6A8}
 86 \usv_set:nnn {bfup}{greek}{1D6C2}
 87 \usv_set:nnn {bfit}{Latin}{1D468}
 88 \usv_set:nnn {bfit}{latin}{1D482}
 89 \usv_set:nnn {bfit}{Greek}{1D71C}
 90 \usv_set:nnn {bfit}{greek}{1D736}
 91 \usv_set:nnn {bffrak}{Latin}{1D56C}
 92 \usv_set:nnn {bffrak}{latin}{1D586}
 93 \usv_set:nnn {bfscr}{Latin}{1D4D0}
 94 \usv_set:nnn {bfscr}{latin}{1D4EA}
 95 \usv_set:nnn {bfsf}{num}{1D7EC}
 96 \usv_set:nnn {bfsfup}{num}{1D7EC}
 97 \usv_set:nnn {bfsfit}{num}{1D7EC}
 98 \usv_set:nnn {bfsfup}{Latin}{1D5D4}
 99 \usv_set:nnn {bfsfup}{latin}{1D5EE}
 100 \usv_set:nnn {bfsfup}{Greek}{1D756}
 101 \usv_set:nnn {bfsfup}{greek}{1D770}
 102 \usv_set:nnn {bfsfit}{Latin}{1D63C}
 103 \usv_set:nnn {bfsfit}{latin}{1D656}
 104 \usv_set:nnn {bfsfit}{Greek}{1D790}
 105 \usv_set:nnn {bfsfit}{greek}{1D7AA}

106 \usv_set:nnn {bfsf}{Latin}{\bool_if:NTF \g_um_upLatin_bool \g_um_bfsfup_Latin_usv \g_um_bfsf
 107 \usv_set:nnn {bfsf}{latin}{\bool_if:NTF \g_um_upLatin_bool \g_um_bfsfup_latin_usv \g_um_bfsf
 108 \usv_set:nnn {bfsf}{Greek}{\bool_if:NTF \g_um_upGreek_bool \g_um_bfsfup_Greek_usv \g_um_bfsf
 109 \usv_set:nnn {bfsf}{greek}{\bool_if:NTF \g_um_upgreek_bool \g_um_bfsfup_greek_usv \g_um_bfsf
 110 \usv_set:nnn {bf}{Latin}{\bool_if:NTF \g_um_bfupLatin_bool \g_um_bfup_Latin_usv \g_um_bfit_L
 111 \usv_set:nnn {bf}{latin}{\bool_if:NTF \g_um_bfuplatin_bool \g_um_bfup_latin_usv \g_um_bfit_L
 112 \usv_set:nnn {bf}{Greek}{\bool_if:NTF \g_um_bfupGreek_bool \g_um_bfup_Greek_usv \g_um_bfit_G
 113 \usv_set:nnn {bf}{greek}{\bool_if:NTF \g_um_bfupgreek_bool \g_um_bfup_greek_usv \g_um_bfit_g

Greek variants:

```
114 \usv_set:nnn {up}{varTheta}{\3F4}
115 \usv_set:nnn {up}{Digamma}{\3DC}
116 \usv_set:nnn {up}{varepsilon}{\3F5}
117 \usv_set:nnn {up}{vartheta}{\3D1}
118 \usv_set:nnn {up}{varkappa}{\3F0}
119 \usv_set:nnn {up}{varphi}{\3D5}
120 \usv_set:nnn {up}{varrho}{\3F1}
121 \usv_set:nnn {up}{varpi}{\3D6}
122 \usv_set:nnn {up}{digamma}{\3DD}
```

Bold:

```
123 \usv_set:nnn {bfup}{varTheta}{\1D6B9}
124 \usv_set:nnn {bfup}{Digamma}{\1D7CA}
125 \usv_set:nnn {bfup}{varepsilon}{\1D6DC}
126 \usv_set:nnn {bfup}{vartheta}{\1D6DD}
127 \usv_set:nnn {bfup}{varkappa}{\1D6DE}
128 \usv_set:nnn {bfup}{varphi}{\1D6DF}
129 \usv_set:nnn {bfup}{varrho}{\1D6E0}
130 \usv_set:nnn {bfup}{varpi}{\1D6E1}
131 \usv_set:nnn {bfup}{digamma}{\1D7CB}
```

Italic Greek variants:

```
132 \usv_set:nnn {it}{varTheta}{\1D6F3}
133 \usv_set:nnn {it}{varepsilon}{\1D716}
134 \usv_set:nnn {it}{vartheta}{\1D717}
135 \usv_set:nnn {it}{varkappa}{\1D718}
136 \usv_set:nnn {it}{varphi}{\1D719}
137 \usv_set:nnn {it}{varrho}{\1D71A}
138 \usv_set:nnn {it}{varpi}{\1D71B}
```

Bold italic:

```
139 \usv_set:nnn {bfit}{varTheta}{\1D72D}
140 \usv_set:nnn {bfit}{varepsilon}{\1D750}
141 \usv_set:nnn {bfit}{vartheta}{\1D751}
142 \usv_set:nnn {bfit}{varkappa}{\1D752}
143 \usv_set:nnn {bfit}{varphi}{\1D753}
144 \usv_set:nnn {bfit}{varrho}{\1D754}
145 \usv_set:nnn {bfit}{varpi}{\1D755}
```

Bold sans:

```
146 \usv_set:nnn {bfsfup}{varTheta}{\1D767}
147 \usv_set:nnn {bfsfup}{varepsilon}{\1D78A}
148 \usv_set:nnn {bfsfup}{vartheta}{\1D78B}
149 \usv_set:nnn {bfsfup}{varkappa}{\1D78C}
150 \usv_set:nnn {bfsfup}{varphi}{\1D78D}
151 \usv_set:nnn {bfsfup}{varrho}{\1D78E}
152 \usv_set:nnn {bfsfup}{varpi}{\1D78F}
```

Bold sans italic:

```

153 \usv_set:nnn {bfsfit}{varTheta} {"1D7A1}
154 \usv_set:nnn {bfsfit}{varepsilon} {"1D7C4}
155 \usv_set:nnn {bfsfit}{vartheta} {"1D7C5}
156 \usv_set:nnn {bfsfit}{varkappa} {"1D7C6}
157 \usv_set:nnn {bfsfit}{varphi} {"1D7C7}
158 \usv_set:nnn {bfsfit}{varrho} {"1D7C8}
159 \usv_set:nnn {bfsfit}{varpi} {"1D7C9}

```

Nabla:

```

160 \usv_set:nnn {up} {Nabla} {"02207}
161 \usv_set:nnn {it} {Nabla} {"1D6FB}
162 \usv_set:nnn {bfup} {Nabla} {"1D6C1}
163 \usv_set:nnn {bfif} {Nabla} {"1D735}
164 \usv_set:nnn {bfsfup} {Nabla} {"1D76F}
165 \usv_set:nnn {bfsfit} {Nabla} {"1D7A9}

```

Partial:

```

166 \usv_set:nnn {up} {partial} {"02202}
167 \usv_set:nnn {it} {partial} {"1D715}
168 \usv_set:nnn {bfup} {partial} {"1D6DB}
169 \usv_set:nnn {bfif} {partial} {"1D74F}
170 \usv_set:nnn {bfsfup} {partial} {"1D789}
171 \usv_set:nnn {bfsfit} {partial} {"1D7C3}

```

Exceptions These are need for mapping with the exceptions in other alphabets:
(coming up)

```

172 \usv_set:nnn {up}{B}{`\B}
173 \usv_set:nnn {up}{C}{`\C}
174 \usv_set:nnn {up}{D}{`\D}
175 \usv_set:nnn {up}{E}{`\E}
176 \usv_set:nnn {up}{F}{`\F}
177 \usv_set:nnn {up}{H}{`\H}
178 \usv_set:nnn {up}{I}{`\I}
179 \usv_set:nnn {up}{L}{`\L}
180 \usv_set:nnn {up}{M}{`\M}
181 \usv_set:nnn {up}{N}{`\N}
182 \usv_set:nnn {up}{P}{`\P}
183 \usv_set:nnn {up}{Q}{`\Q}
184 \usv_set:nnn {up}{R}{`\R}
185 \usv_set:nnn {up}{Z}{`\Z}

186 \usv_set:nnn {it}{B} {"1D435}
187 \usv_set:nnn {it}{C} {"1D436}
188 \usv_set:nnn {it}{D} {"1D437}
189 \usv_set:nnn {it}{E} {"1D438}
190 \usv_set:nnn {it}{F} {"1D439}

```

```

191 \usv_set:nnn {it}{H}{1D43B}
192 \usv_set:nnn {it}{I}{1D43C}
193 \usv_set:nnn {it}{L}{1D43F}
194 \usv_set:nnn {it}{M}{1D440}
195 \usv_set:nnn {it}{N}{1D441}
196 \usv_set:nnn {it}{P}{1D443}
197 \usv_set:nnn {it}{Q}{1D444}
198 \usv_set:nnn {it}{R}{1D445}
199 \usv_set:nnn {it}{Z}{1D44D}

200 \usv_set:nnn {up}{d}{`d}
201 \usv_set:nnn {up}{e}{`e}
202 \usv_set:nnn {up}{g}{`g}
203 \usv_set:nnn {up}{h}{`h}
204 \usv_set:nnn {up}{i}{`i}
205 \usv_set:nnn {up}{j}{`j}
206 \usv_set:nnn {up}{o}{`o}

207 \usv_set:nnn {it}{d}{1D451}
208 \usv_set:nnn {it}{e}{1D452}
209 \usv_set:nnn {it}{g}{1D454}
210 \usv_set:nnn {it}{h}{0210E}
211 \usv_set:nnn {it}{i}{1D456}
212 \usv_set:nnn {it}{j}{1D457}
213 \usv_set:nnn {it}{o}{1D45C}

```

Latin ‘h’:

```

214 \usv_set:nnn {bb} {h}{1D559}
215 \usv_set:nnn {tt} {h}{1D691}
216 \usv_set:nnn {scr} {h}{1D4BD}
217 \usv_set:nnn {frak} {h}{1D525}
218 \usv_set:nnn {bfup} {h}{1D421}
219 \usv_set:nnn {bfit} {h}{1D489}
220 \usv_set:nnn {sfup} {h}{1D5C1}
221 \usv_set:nnn {sfit} {h}{1D629}
222 \usv_set:nnn {bffrak}{h}{1D58D}
223 \usv_set:nnn {bfscr} {h}{1D4F1}
224 \usv_set:nnn {bfsfup}{h}{1D5F5}
225 \usv_set:nnn {bfsfit}{h}{1D65D}

```

Dotless ‘i’ and ‘j’:

```

226 \usv_set:nnn {up}{dotlessi}{00131}
227 \usv_set:nnn {up}{dotlessj}{00237}
228 \usv_set:nnn {it}{dotlessi}{1D6A4}
229 \usv_set:nnn {it}{dotlessj}{1D6A5}

```

Blackboard:

```

230 \usv_set:nnn {bb}{C}{2102}
231 \usv_set:nnn {bb}{H}{210D}

```

232 \usv_set:nnn {bb}{N}{ "2115}
 233 \usv_set:nnn {bb}{P}{ "2119}
 234 \usv_set:nnn {bb}{Q}{ "211A}
 235 \usv_set:nnn {bb}{R}{ "211D}
 236 \usv_set:nnn {bb}{Z}{ "2124}
 237 \usv_set:nnn {up}{Pi} {"003A0}
 238 \usv_set:nnn {up}{pi} {"003C0}
 239 \usv_set:nnn {up}{Gamma} {"00393}
 240 \usv_set:nnn {up}{gamma} {"003B3}
 241 \usv_set:nnn {up}{summation}{ "02211}
 242 \usv_set:nnn {it}{Pi} {"1D6F1}
 243 \usv_set:nnn {it}{pi} {"1D70B}
 244 \usv_set:nnn {it}{Gamma} {"1D6E4}
 245 \usv_set:nnn {it}{gamma} {"1D6FE}
 246 \usv_set:nnn {bb}{Pi} {"0213F}
 247 \usv_set:nnn {bb}{pi} {"0213C}
 248 \usv_set:nnn {bb}{Gamma} {"0213E}
 249 \usv_set:nnn {bb}{gamma} {"0213D}
 250 \usv_set:nnn {bb}{summation}{ "02140}

Italic blackboard:

251 \usv_set:nnn {bbi}{D}{ "2145}
 252 \usv_set:nnn {bbi}{d}{ "2146}
 253 \usv_set:nnn {bbi}{e}{ "2147}
 254 \usv_set:nnn {bbi}{i}{ "2148}
 255 \usv_set:nnn {bbi}{j}{ "2149}

Script exceptions:

256 \usv_set:nnn {scr}{B}{ "212C}
 257 \usv_set:nnn {scr}{E}{ "2130}
 258 \usv_set:nnn {scr}{F}{ "2131}
 259 \usv_set:nnn {scr}{H}{ "210B}
 260 \usv_set:nnn {scr}{I}{ "2110}
 261 \usv_set:nnn {scr}{L}{ "2112}
 262 \usv_set:nnn {scr}{M}{ "2133}
 263 \usv_set:nnn {scr}{R}{ "211B}
 264 \usv_set:nnn {scr}{e}{ "212F}
 265 \usv_set:nnn {scr}{g}{ "210A}
 266 \usv_set:nnn {scr}{o}{ "2134}

Fraktur exceptions:

267 \usv_set:nnn {frak}{C}{ "212D}
 268 \usv_set:nnn {frak}{H}{ "210C}
 269 \usv_set:nnn {frak}{I}{ "2111}
 270 \usv_set:nnn {frak}{R}{ "211C}
 271 \usv_set:nnn {frak}{Z}{ "2128}

Complete u.s.v. ranges These might be needed (with a whole bunch more) later:

```

272 \tl_new:Nn \g_um_mathup_latin_usv_range_tl {\a-\z}
273 \tl_new:Nn \g_um_mathup_Latin_usv_range_tl {\A-\Z}
274 \tl_new:Nn \g_um_mathup_greek_usv_range_tl {"3B1-"3C9,"3F5,"3D1,"3F0,"3D5,"3F1,"3D6,"3DD}
275 \tl_new:Nn \g_um_mathup_Greek_usv_range_tl {"391-"3A9,"3F4,"3DC}
276 \tl_new:Nn \g_um_mathup_num_usv_range_tl {\0-\9}
277 \tl_new:Nn \g_um_mathit_latin_usv_range_tl {"1D44E-"1D467,\g_um_it_h_usv}
278 \tl_new:Nn \g_um_mathit_Latin_usv_range_tl {"1D434-"1D44C}
279 \tl_new:Nn \g_um_mathit_greek_usv_range_tl {"1D6FC-"1D714,"1D716-1D71B}
280 \tl_new:Nn \g_um_mathit_Greek_usv_range_tl {"1D6E2-"1D6FA}

```

6.1 Options

xkeyval's package support is used here. I'll switch over to l3keys2e at some stage.

`\unimathsetup` This macro can be used in lieu of or later to override options declared when the package is loaded.

```

281 \DeclareDocumentCommand \unimathsetup {m} {
282   \setkeys{unicode-math.sty}{#1}
283 }

```

math-style

```

284 \define@choicekey*{unicode-math.sty}
285   {math-style}[\@tempa\@tempb]{iso,tex,french,upright,literal}{
286   \bool_set_false:N \g_um_literal_bool
287   \ifcase\@tempb\relax
288     \bool_set_false:N \g_um_upGreek_bool
289     \bool_set_false:N \g_um_upgreek_bool
290     \bool_set_false:N \g_um_upLatin_bool
291     \bool_set_false:N \g_um_uplatin_bool
292     \setkeys{unicode-math.sty}{
293       bold-style=iso,
294       sans-style=italic,
295       nabla=italic,
296       partial=italic,
297     }
298   \or
299     \bool_set_true:N \g_um_upGreek_bool
300     \bool_set_false:N \g_um_upgreek_bool
301     \bool_set_false:N \g_um_upLatin_bool
302     \bool_set_false:N \g_um_uplatin_bool
303     \setkeys{unicode-math.sty}{
304       bold-style=tex,
305       sans-style=upright,
306       nabla=upright,

```



```

307     partial=italic,
308   }
309 \or
310   \bool_set_true:N \g_um_upGreek_bool
311   \bool_set_true:N \g_um_upgreek_bool
312   \bool_set_true:N \g_um_upLatin_bool
313   \bool_set_false:N \g_um_uplatin_bool
314   \setkeys{unicode-math.sty}{
315     bold-style=upright,
316     sans-style=upright,
317     nabla=upright,
318     partial=upright,
319   }
320 \or
321   \bool_set_true:N \g_um_upGreek_bool
322   \bool_set_true:N \g_um_upgreek_bool
323   \bool_set_true:N \g_um_upLatin_bool
324   \bool_set_true:N \g_um_uplatin_bool
325   \setkeys{unicode-math.sty}{
326     bold-style=upright,
327     sans-style=upright,
328     nabla=upright,
329     partial=upright,
330   }
331 \or
332   \bool_set_true:N \g_um_literal_bool
333   \setkeys{unicode-math.sty}{
334     bold-style=literal,
335     sans-style=literal,
336     colon=literal,
337     nabla=literal,
338     partial=literal,
339   }
340 \fi
341 }

```

bold-style

```

342 \define@choicekey*{unicode-math.sty}{bold-style}[\@tempa\@tempb]{iso,tex,upright,literal}{
343   \bool_set_false:N \g_um_bfliteral_bool
344   \ifcase\@tempb\relax
345     \bool_set_false:N \g_um_bfupGreek_bool
346     \bool_set_false:N \g_um_bfupgreek_bool
347     \bool_set_false:N \g_um_bfupLatin_bool
348     \bool_set_false:N \g_um_bfuplatin_bool
349   \or
350     \bool_set_true:N \g_um_bfupGreek_bool

```

```

351 \bool_set_false:N \g_um_bfupgreek_bool
352 \bool_set_true:N \g_um_bfupLatin_bool
353 \bool_set_true:N \g_um_bfuplatin_bool
354 \or
355 \bool_set_true:N \g_um_bfupGreek_bool
356 \bool_set_true:N \g_um_bfupgreek_bool
357 \bool_set_true:N \g_um_bfupLatin_bool
358 \bool_set_true:N \g_um_bfuplatin_bool
359 \or
360 \bool_set_true:N \g_um_bfliteral_bool
361 \fi
362 }

```

sans-style

```

363 \define@choicekey*{unicode-math.sty}
364 {sans-style}[\@tempa\@tempb]{italic,upright,literal}{
365 \ifcase\@tempb\relax
366 \bool_set_false:N \g_um_upsans_bool
367 \or
368 \bool_set_true:N \g_um_upsans_bool
369 \or
370 \bool_set_true:N \g_um_sfliteral_bool
371 \fi
372 }

```

Nabla and partial

```

373 \define@choicekey*{unicode-math.sty}{nabla}[\@tempa\@tempb]{upright,italic,literal}{
374 \bool_set_false:N \g_um_literal_Nabla_bool
375 \ifcase\@tempb
376 \bool_set_true:N \g_um_upNabla_bool
377 \or
378 \bool_set_false:N \g_um_upNabla_bool
379 \or
380 \bool_set_true:N \g_um_literal_Nabla_bool
381 \fi
382 }

383 \define@choicekey*{unicode-math.sty}{partial}[\@tempa\@tempb]{upright,italic,literal}{
384 \bool_set_false:N \g_um_literal_partial_bool
385 \ifcase\@tempb
386 \bool_set_true:N \g_um_uppartial_bool
387 \or
388 \bool_set_false:N \g_um_uppartial_bool
389 \or
390 \bool_set_true:N \g_um_literal_partial_bool
391 \fi

```

```
392 }
```

Epsilon and phi shapes

```
393 \define@choicekey*{unicode-math.sty}{vargreek-shape}[\@tempa\@tempb]{unicode,TeX}{
394   \ifcase\@tempb
395     \bool_set_false:N \g_um_texgreek_bool
396   \or
397     \bool_set_true:N \g_um_texgreek_bool
398   \fi
399 }
```

Colon style

```
400 \define@choicekey*{unicode-math.sty}{colon}[\@tempa\@tempb]{literal,TeX}{
401   \ifcase\@tempb
402     \bool_set_true:N \g_um_literal_colon_bool
403   \or
404     \bool_set_false:N \g_um_literal_colon_bool
405   \fi
406 }
```

Slash delimiter style

```
407 \define@choicekey*{unicode-math.sty}{slash-delimiter}[\@tempa\@tempb]{ascii,frac,div}{
408   \ifcase\@tempb
409     \tl_set:Nn \g_um_slash_delimiter_usv {"002F}
410   \or
411     \tl_set:Nn \g_um_slash_delimiter_usv {"2044}
412   \or
413     \tl_set:Nn \g_um_slash_delimiter_usv {"2215}
414   \fi
415 }
```

Active fraction style

```
416 \define@choicekey*{unicode-math.sty}{active-fraction}[\@tempa\@tempb]{small,normalsize}{
417   \ifcase\@tempb
418     \cs_if_exist:NTF \tfrac {
419       \bool_set_true:N \l_um_smallfrac_bool
420     }{
421       \PackageWarning{unicode-math}{Small~ fraction~ command~ \pro-
422         tect\tfrac\space not~ defined.~ Perhaps~ load~ amsmath?}
423       \bool_set_false:N \l_um_smallfrac_bool
424     }
425   \or
426     \bool_set_false:N \l_um_smallfrac_bool
427   \fi
428 }
```

```

427 \um_setup_active_frac:
428 }

```

Debug/tracing

```

429 \define@choicekey*{unicode-math.sty}{trace}[\@tempa\@tempb]{on,off}{
430   \ifcase\@tempb
431     \cs_set:Nn \um_debug:n { \typeout{##1} }
432   \or
433     \cs_set:Nn \um_debug:n { }
434   \fi
435 }

436 \ExecuteOptionsX{math-style=TeX,slash-delimiter=ascii,trace=off}
437 \AtEndOfPackage{
438   \cs_if_exist:NT \tfrac {
439     \unimathsetup{active-frac=small}
440   }
441 }
442 \ProcessOptionsX

```

6.2 Overcoming \@onlypreamble

The requirement of only setting up the maths fonts in the preamble is now removed. The following list might be overly ambitious.

```

443 \tl_map_inline:nn {
444   \new@mathgroup\cdp@list\cdp@elt\DeclareMathSizes
445   \@DeclareMathSizes\newmathalphabet\newmathalphabet@@\newmathalphabet@@@
446   \DeclareMathVersion\define@mathalphabet\define@mathgroup\addtoversion
447   \version@list\version@elt\alpha@list\alpha@elt
448   \restore@mathversion\init@restore@version\dorestore@version\process@table
449   \new@mathversion\DeclareSymbolFont\group@list\group@elt
450   \new@symbolfont\SetSymbolFont\SetSymbolFont@\get@cdp
451   \DeclareMathAlphabet\new@mathalphabet\SetMathAlphabet\SetMathAlphabet@
452   \DeclareMathAccent\set@mathaccent\DeclareMathSymbol\set@mathchar
453   \set@mathsymbol\DeclareMathDelimiter\@xxDeclareMathDelimiter
454   \@DeclareMathDelimiter\@xDeclareMathDelimiter\set@mathdelimiter
455   \set@@mathdelimiter\DeclareMathRadical\mathchar@type
456   \DeclareSymbolFontAlphabet\DeclareSymbolFontAlphabet@
457 }{
458   \tl_remove_in:Nn \@preamblecmds {\do#1}
459 }

```

7 Fundamentals

7.1 Enlarging the number of maths families

To start with, we've got a power of two as many `\fams` as before. So (from `ltxssbas.dtx`) we want to redefine

```
460 \def\new@mathgroup{\alloc@8\mathgroup\chardef\@cclvi}
461 \let\newfam\new@mathgroup
```

This is sufficient for L^AT_EX's `\DeclareSymbolFont`-type commands to be able to define 256 named maths fonts.

7.2 Setting math chars, math codes, etc.

```
\um_set_mathsymbol:nNNn #1 : A LATEX symbol font, e.g., operators
#2 : Symbol macro, e.g., \alpha
#3 : Type, e.g., \mathalpha
#4 : Slot, e.g., "221E"
```

There are a bunch of tests to perform to process the various characters. The following assignments should all be fairly straightforward.

```
462 \cs_set:Nn \um_set_mathsymbol:nNNn {
463   \prg_case_tl:Nnn #3 {
464     \mathop {
465       \um_set_big_operator:nnn {#1} {#2} {#4}
466     }
467     \mathopen {
468       \tl_if_in:NnTF \l_um_radicals_tl {#2} {
469         \cs_gset:cpx {\cs_to_str:N #2 sign} { \um_radical:nn {#1} {#4} }
470       }{
471         \um_set_delcode:n {#4}
472         \um_set_mathcode:nnn {#4} \mathopen {#1}
473         \cs_gset:Npx #2 { \um_delimiter:Nnn \mathopen {#1} {#4} }
474       }
475     }
476     \mathclose {
477       \um_set_delcode:n {#4}
478       \um_set_mathcode:nnn {#4} \mathclose {#1}
479       \cs_gset:Npx #2 { \um_delimiter:Nnn \mathclose {#1} {#4} }
480     }
481     \mathfence {
482       \um_set_mathcode:nnn {#4} {#3} {#1}
483       \um_set_delcode:n {#4}
484       \cs_gset:cpx {l \cs_to_str:N #2} { \um_delimiter:Nnn \math-
open {#1} {#4} }
485       \cs_gset:cpx {r \cs_to_str:N #2} { \um_delimiter:Nnn \math-
close {#1} {#4} }
```

```

486 }
487 \mathaccent {
488   \cs_gset:Npx #2 { \um_accent:Nnn #3 {#1} {#4} }
489 }
490 }{
491   \um_set_mathcode:nnn {#4} {#3} {#1}
492 }
493 }

```

`\um_set_big_operator:nnn` #1 : Symbol font name
 #2 : Macro to assign
 #3 : Glyph slot

In the examples following, say we're defining for the symbol `\sum` (Σ). In order for literal unicode characters to be used in the source and still have the correct limits behaviour, big operators are made math-active. This involves three steps:

- The active math char is defined to expand to the macro `\sum_sym`. (Later, the control sequence `\sum` will be assigned the math char.)
- Declare the plain old mathchardef for the control sequence `\sumop`. (This follows the convention of L^AT_EX/amsmath.)
- Define `\sum_sym` as `\sumop`, followed by `\nolimits` if necessary.

Whether the `\nolimits` suffix is inserted is controlled by the token list `\l_um_nolimits_tl`, which contains a list of such characters. This list is checked dynamically to allow it to be updated mid-document.

Examples of expansion, by default, for two big operators:

$(\sum \rightarrow) \Sigma \rightarrow \sum_{\text{sym}} \rightarrow \sumop_{\text{nolimits}}$
 $(\int \rightarrow) \int \rightarrow \int_{\text{sym}} \rightarrow \intop$

```

494 \cs_new:Nn \um_set_big_operator:nnn {
495   \group_begin:
496     \char_make_active:n {#3}
497     \char_gmake_mathactive:n {#3}
498     \um@scanactivedef #3 \@nil { \csname\cs_to_str:N #2 _sym\endcsname }
499   \group_end:
500   \um_set_mathchar:cNnn {\cs_to_str:N #2 op} \mathop {#1} {#3}
501   \cs_gset:cpx { \cs_to_str:N #2 _sym } {
502     \exp_not:c { \cs_to_str:N #2 op }
503     \exp_not:n { \tl_if_in:NnT \l_um_nolimits_tl {#2} \nolimits }
504   }
505 }

```

```

\um_set_mathcode:nnnn
\um_set_mathcode:nnn 506 \cs_set:Nn \um_set_mathcode:nnnn {
\um_set_mathchar:NNnn
\um_set_mathchar:cNnn
\um_radical:nn
\um_delimiter:Nnn
\um_accent:Nnn

```

```

507 \XeTeXmathcode \intexpr_eval:n {#1} =
508 \mathchar@type#2 \csname sym#3\endcsname \intexpr_eval:n {#4} \scan_stop:
509 }
510 \cs_set:Nn \um_set_mathcode:nnn {
511 \XeTeXmathcode \intexpr_eval:n {#1} =
512 \mathchar@type#2 \csname sym#3\endcsname \intexpr_eval:n {#1} \scan_stop:
513 }
514 \cs_set:Nn \um_set_mathchar:NNnn {
515 \XeTeXmathchardef #1 =
516 \mathchar@type#2 \csname sym#3\endcsname \intexpr_eval:n {#4} \scan_stop:
517 }
518 \cs_new:Nn \um_radical:nn {
519 \XeTeXradical \csname sym#1\endcsname #2 \scan_stop:
520 }
521 \cs_new:Nn \um_delimiter:Nnn {
522 \XeTeXdelimiter \mathchar@type#1 \csname sym#2\endcsname #3 \scan_stop:
523 }
524 \cs_new:Nn \um_accent:Nnn {
525 \XeTeXmathaccent \mathchar@type#1 \csname sym#2\endcsname #3 \scan_stop:
526 }
527 \cs_generate_variant:Nn \um_set_mathchar:NNnn {c}

\char_gmake_mathactive:N
\char_gmake_mathactive:n
528 \cs_new:Nn \char_gmake_mathactive:N {
529 \global\XeTeXmathcodenum `#1 = "1FFFFF \scan_stop:
530 }
531 \cs_new:Nn \char_gmake_mathactive:n {
532 \global\XeTeXmathcodenum #1 = "1FFFFF \scan_stop:
533 }

```

7.3 The main `\setmathfont` macro

Using a range including large character sets such as `\mathrel`, `\mathalpha`, *etc.*, is *very slow*! I hope to improve the performance somehow.

`\setmathfont` [**#1**]: font features

#2 : font name

```

534 \DeclareDocumentCommand \setmathfont { O{} m } {

```

- Erase any conception L^AT_EX has of previously defined math symbol fonts; this allows `\DeclareSymbolFont` at any point in the document.

```

535 \let\glb@currsizel\relax

```

- To start with, assume we're defining the font for every math symbol character.

```

536 \bool_set_true:N \l_um_init_bool
537 \seq_clear:N \l_um_char_range_seq
538 \clist_clear:N \l_um_char_num_range_clist

```

- Grab the current size information (is this robust enough? Maybe it should be preceded by `\normalsize`).

```

539 \csname S@\f@size\endcsname

```

- Set the name of the math version being defined. (obviously more needs to be done here!)

```

540 \tl_set:Nn \l_um_mversion_tf {normal}
541 \DeclareMathVersion{\l_um_mversion_tf}

```

Define default font features for the script and scriptscript font.

```

542 \tl_set:Nn \l_um_script_features_tl {ScriptStyle}
543 \tl_set:Nn \l_um_sscript_features_tl {ScriptScriptStyle}
544 \tl_set:Nn \l_um_script_font_tl {#2}
545 \tl_set:Nn \l_um_sscript_font_tl {#2}

```

Use `fontspec` to select a font to use. The macro `\S@{size}` contains the definitions of the sizes used for maths letters, subscripts and subsubscripts in `\tf@size`, `\sf@size`, and `\ssf@size`, respectively.

```

546 \setkeys*{unicode-math.sty}{#1}
547 \cs_set:Npx \um_tmp: {
548   \exp_not:N \setkeys*[um]{options}{\exp_not:V \XKV@rm}
549 }
550 \um_tmp:
551 \um_fontspec_select_font:n {#2}

```

Check for the correct number of `\fontdimens`:

```

552 %% \ifdim \dimexpr\fontdimen9\l_um_font*65536\relax =65pt\relax
553 %% \bool_set_true:N \l_um_ot_math_bool
554 %% \else
555 %% \bool_set_false:N \l_um_ot_math_bool
556 %% \PackageWarningNoLine{unicode-math}{
557 %%   The~ font~ '#2' ~is~ not~ a~ valid~ OpenType~ maths~ font.~
558 %%   Some~ maths~ features~ will~ not~ be~ available~ or~ behave~
559 %%   in~ a~ substandard~ manner
560 %% }
561 %% \fi

```

If we're defining the full unicode math repertoire, then we skip all the parsing processing needed if we're only defining a subset.

- Math symbols are defined with `\UnicodeMathSymbol`; see section §7.3.1 for the individual definitions


```

562 \bool_if:NTF \l_um_init_bool {
563   \tl_set:Nn \um_symfont_tl {um_allsym}
564   \PackageInfo{unicode-math}{Defining~ the~ default~ maths~ font~ as~ '#2'}
565   \cs_set_eq:NN \UnicodeMathSymbol \um_process_symbol_noparse:nnnn
566   \cs_set_eq:NN \um_mathmap:Nnn \um_mathmap_noparse:Nnn
567   \cs_set_eq:NN \um_remap_symbol:nnn \um_remap_symbol_noparse:nnn
568   \cs_set_eq:NN \um_maybe_init_alphabet:n \um_init_alphabet:n
569   \cs_set_eq:NN \um_map_char:nn \um_map_char_noparse:nn
570 }{
571   \int_incr:N \g_um_fam_int
572   \tl_set:Nx \um_symfont_tl {um_fam\int_use:N\g_um_fam_int}
573   \cs_set_eq:NN \UnicodeMathSymbol \um_process_symbol_parse:nnnn
574   \cs_set_eq:NN \um_mathmap:Nnn \um_mathmap_parse:Nnn
575   \cs_set_eq:NN \um_remap_symbol:nnn \um_remap_symbol_parse:nnn
576   \cs_set_eq:NN \um_maybe_init_alphabet:n \use_none:n
577   \cs_set_eq:NN \um_map_char:nn \um_map_char_parse:nn
578 }

```

Now defined `\um_symfont_tl` as the L^AT_EX math font to access everything:

```

579 \DeclareSymbolFont{\um_symfont_tl}
580   {\encodingdefault}{\zf@family}{\mddefault}{\updefault}

```

And now we input every single maths char. See File 12 for the source to `unicode-math.tex` which is used to create `unicode-math-table.tex`.

```

581 \@input{unicode-math-table.tex}
582 \cs_set_eq:NN \UnicodeMathSymbol \use_none:nnnn

```

Finally,

- Remap symbols that don't take their natural mathcode
- Activate any symbols that need to be math-active
- Assign delimiter codes for symbols that need to grow
- Setup the maths alphabets (`\mathbf` etc.)

```

583 \um_remap_symbols:
584 \um_setup_mathactives:
585 \um_setup_delcodes:
586 \um_setup_alphabets:
587 }

```

`\um_fontspec_select_font:` Select the font with `\fontspec` and define `\l_um_font` from it.

```

588 \cs_new:Nn \um_fontspec_select_font:n {
589   \cs_set:Npx \um_tmp: {
590     \exp_not:N \fontspec [
591       BoldFont = {}, ItalicFont = {},
592       Script = Math,

```

```

593     SizeFeatures = {
594       {Size = \tf@size-} ,
595       {Size = \sf@size-\tf@size ,
596         Font = \l_um_script_font_tl ,
597         \l_um_script_features_tl
598       } ,
599       {Size = -\sf@size ,
600         Font = \l_um_sscript_font_tl ,
601         \l_um_sscript_features_tl
602       }
603     },
604     \XKV@rm
605   ]{#1}
606 }
607 \group_begin:
608   \bool_set_true:N \l_um_fontspec_feature_bool
609   \um_tmp:
610 \group_end:
611 \font\l_um_font=\fontname
612   \csname\f@encoding/\zf@family/\mddefault/\updefault/\f@size\endcsname
613 }

```

7.3.1 Functions for setting up symbols with mathcodes

`\um_process_symbol_noparse:nnnn` If the range font feature has been used, then only a subset of the unicode glyphs
`\um_process_symbol_parse:nnnn` are to be defined. See section §8.3 for the code that enables this.

```

614 \cs_set:Nn \um_process_symbol_noparse:nnnn {
615   \um_set_mathsymbol:nNNn {\um_symfont_tl} #2#3{#1}
616 }
617 \cs_set:Nn \um_process_symbol_parse:nnnn {
618   \um@parse@term{#1}{#2}{#3}{
619     \um_process_symbol_noparse:nnnn{#1}{#2}{#3}{#4}
620   }
621 }

```

`\um_remap_symbols:` This function is used to define the mathcodes for those chars which should be
`\um_remap_symbol_noparse:nnn` mapped to a different glyph than themselves.
`\um_remap_symbol_parse:nnn`

```

622 \cs_new:Nn \um_remap_symbols: {
623   \um_remap_symbol:nnn{\-}{\mathbin}{"02212}% hyphen to minus
624   \um_remap_symbol:nnn{\*}{\mathbin}{"02217}% text asterisk to "cen-
        tred asterisk"
625   \bool_if:NF \g_um_literal_colon_bool {
626     \um_remap_symbol:nnn{\:}{\mathrel}{"02236}% colon to ratio (i.e., punct to rel)
627   }
628 }

```

Where `\um_remap_symbol:nnn` is defined to be one of these two, depending on the range setup:

```

629 \cs_new:Nn \um_remap_symbol_parse:nnn {
630   \um@parse@term {#3} {\@nil} {#2} {
631     \um_remap_symbol_noparse:nnn {#1} {#2} {#3}
632   }
633 }
634 \cs_new:Nn \um_remap_symbol_noparse:nnn {
635   \clist_map_inline:nn {#1} {
636     \um_set_mathcode:nnnn {##1} {#2} {\um_symfont_tl} {#3}
637   }
638 }

```

7.3.2 Active math characters

There are more math active chars later in the subscript/superscript section. But they don't need to be able to be typeset directly.

`\um_setup_mathactives:`

```

639 \cs_new:Nn \um_setup_mathactives: {
640   \um_make_mathactive:nNN {"2032} \um_prime_single_mchar \mathord
641   \um_make_mathactive:nNN {"2033} \um_prime_double_mchar \mathord
642   \um_make_mathactive:nNN {"2034} \um_prime_triple_mchar \mathord
643   \um_make_mathactive:nNN {"2057} \um_prime_quad_mchar \mathord
644   \um_make_mathactive:nNN {"2035} \um_backprime_single_mchar \mathord
645   \um_make_mathactive:nNN {"2036} \um_backprime_double_mchar \mathord
646   \um_make_mathactive:nNN {"2037} \um_backprime_triple_mchar \mathord
647   \um_make_mathactive:nNN {\`\' } \mathstraightquote \mathord
648   \um_make_mathactive:nNN {\`\` } \mathbacktick \mathord
649 }

```

`\um_make_mathactive:nNN` : TODO : hook into range feature Makes #1 a mathactive char, and gives cs #2 the meaning of mathchar #1 with class #3. You are responsible for giving active #1 a particular meaning!

```

650 \cs_new:Nn \um_make_mathactive:nNN {
651   \um_set_mathchar:NNnn #2 #3 {\um_symfont_tl} {#1}
652   \char_gmake_mathactive:n {#1}
653 }

```

7.3.3 Delimiter codes

Some symbols that aren't `\mathopen/``\mathclose` still need to have delimiter codes assigned. The list of vertical arrows may be incomplete. On the other hand, many fonts won't support them all being stretchy. And some of them are probably not meant to stretch, either. But adding them here doesn't hurt.

`\um_setup_delcodes:`

```
654 \cs_new:Nn \um_setup_delcodes: {  
655   \um_set_delcode:nn {\`\/} {\g_um_slash_delimiter_usv}  
656   \um_set_delcode:nn {"2044} {\g_um_slash_delimiter_usv} % fracslash  
657   \um_set_delcode:nn {"2215} {\g_um_slash_delimiter_usv} % divslash  
658   \um_set_delcode:n {"005C} % backslash  
659   \um_set_delcode:nn {\`\<} {"27E8} % angle brackets with ascii notation  
660   \um_set_delcode:nn {\`>} {"27E9} % angle brackets with ascii notation  
661   \um_set_delcode:n {"2191} % up arrow  
662   \um_set_delcode:n {"2193} % down arrow  
663   \um_set_delcode:n {"2195} % updown arrow  
664   \um_set_delcode:n {"219F} % up arrow twohead  
665   \um_set_delcode:n {"21A1} % down arrow twohead  
666   \um_set_delcode:n {"21A5} % up arrow from bar  
667   \um_set_delcode:n {"21A7} % down arrow from bar  
668   \um_set_delcode:n {"21A8} % updown arrow from bar  
669   \um_set_delcode:n {"21BE} % up harpoon right  
670   \um_set_delcode:n {"21BF} % up harpoon left  
671   \um_set_delcode:n {"21C2} % down harpoon right  
672   \um_set_delcode:n {"21C3} % down harpoon left  
673   \um_set_delcode:n {"21C5} % arrows up down  
674   \um_set_delcode:n {"21F5} % arrows down up  
675   \um_set_delcode:n {"21C8} % arrows up up  
676   \um_set_delcode:n {"21CA} % arrows down down  
677   \um_set_delcode:n {"21D1} % double up arrow  
678   \um_set_delcode:n {"21D3} % double down arrow  
679   \um_set_delcode:n {"21D5} % double updown arrow  
680   \um_set_delcode:n {"21DE} % up arrow double stroke  
681   \um_set_delcode:n {"21DF} % down arrow double stroke  
682   \um_set_delcode:n {"21E1} % up arrow dashed  
683   \um_set_delcode:n {"21E3} % down arrow dashed  
684   \um_set_delcode:n {"21E7} % up white arrow  
685   \um_set_delcode:n {"21E9} % down white arrow  
686   \um_set_delcode:n {"21EA} % up white arrow from bar  
687   \um_set_delcode:n {"21F3} % updown white arrow  
688 }
```

`\um_set_delcode:nn` : TODO : hook into range feature

```
\um_set_delcode:n  
689 \cs_new:Nn \um_set_delcode:nn {  
690   \XeTeXdelcode#1 = \csname sym\um_symfont_tl\endcsname #2  
691 }  
692 \cs_new:Nn \um_set_delcode:n {  
693   \XeTeXdelcode#1 = \csname sym\um_symfont_tl\endcsname #1  
694 }
```

7.3.4 Maths alphabets' character mapping

7.3.5 Functions for setting up the maths alphabets

`\um_mathmap_noparse:Nnn` #1 : Maths alphabet, *e.g.*, `\mathbb`
 #2 : Input slot(s), *e.g.*, the slot for 'A' (comma separated)
 #3 : Output slot, *e.g.*, the slot for 'A'
 Adds `\um_set_mathcode:nnnn` declarations to the specified maths alphabet's definition.

```
695 \cs_set:Nn \um_mathmap_noparse:Nnn {
696   \clist_map_inline:nn {#2} {
697     \tl_put_right:cx {um_setup_\cs_to_str:N #1:} {
698       \um_set_mathcode:nnnn{##1}{\mathalpha}{\um_symfont_tl}{#3}
699     }
700   }
701 }
```

`\um_mathmap_parse:Nnn` #1 : Maths alphabet, *e.g.*, `\mathbb`
 #2 : Input slot(s), *e.g.*, the slot for 'A' (comma separated)
 #3 : Output slot, *e.g.*, the slot for 'A'
 When `\um@parse@term` is executed, it populates the `\l_um_char_num_range_clist` macro with slot numbers corresponding to the specified range. This range is used to conditionally add `\um_set_mathcode:nnnn` declarations to the maths alphabet definition.

```
702 \cs_set:Nn \um_mathmap_parse:Nnn {
703   \clist_if_in:NnT \l_um_char_num_range_clist {#3} {
704     \um_mathmap_noparse:Nnn {#1}{#2}{#3}
705   }
706 }
```

7.4 (Big) operators





























Turns out that \XeTeX is clever enough to deal with big operators for us automatically with `\XeTeXmathchardef`. Amazing!






However, the limits aren't set automatically; that is, we want to define, a la Plain \TeX *etc.*, `\def\int{\intop\nolimits}`, so there needs to be a transformation from `\int` to `\intop` during the expansion of `\UnicodeMathSymbol` in the appropriate contexts.


Following is a table of every math operator (`\mathop`) defined in `unicode-math-table.tex`, from which a subset need to be flagged for `\nolimits` adjustments. The limits behaviour as specified by `unicode-math` are shown (with grey 'scripts').

USV	Ex.	Macro	Description
-----	-----	-------	-------------

U+02140	$\sum\limits_0^1$	<code>\Bbbsum</code>	DOUBLE-STRUCK N-ARY SUMMATION
U+0220F	$\prod\limits_0^1$	<code>\prod</code>	PRODUCT OPERATOR
U+02210	$\coprod\limits_0^1$	<code>\coprod</code>	COPRODUCT OPERATOR
U+02211	$\sum\limits_0^1$	<code>\sum</code>	SUMMATION OPERATOR
U+0222B	$\int\limits_0^1$	<code>\int</code>	INTEGRAL OPERATOR
U+0222C	$\iint\limits_0^1$	<code>\iint</code>	DOUBLE INTEGRAL OPERATOR
U+0222D	$\iiint\limits_0^1$	<code>\iiint</code>	TRIPLE INTEGRAL OPERATOR
U+0222E	$\oint\limits_0^1$	<code>\oint</code>	CONTOUR INTEGRAL OPERATOR
U+0222F	$\oiint\limits_0^1$	<code>\oiint</code>	DOUBLE CONTOUR INTEGRAL OPERATOR
U+02230	$\oiiint\limits_0^1$	<code>\oiiint</code>	TRIPLE CONTOUR INTEGRAL OPERATOR
U+02231	$\int\limits_0^1$	<code>\intclockwise</code>	CLOCKWISE INTEGRAL
U+02232	$\oint\limits_0^1$	<code>\varointclockwise</code>	CONTOUR INTEGRAL, CLOCKWISE
U+02233	$\oint\limits_0^1$	<code>\ointctrcclockwise</code>	CONTOUR INTEGRAL, ANTICLOCKWISE
U+022C0	$\bigwedge\limits_0^1$	<code>\bigwedge</code>	LOGICAL OR OPERATOR
U+022C1	$\bigvee\limits_0^1$	<code>\bigvee</code>	LOGICAL AND OPERATOR
U+022C2	$\bigcap\limits_0^1$	<code>\bigcap</code>	INTERSECTION OPERATOR
U+022C3	$\bigcup\limits_0^1$	<code>\bigcup</code>	UNION OPERATOR
U+027D5	$\Join\limits_0^1$	<code>\leftouterjoin</code>	LEFT OUTER JOIN
U+027D6	$\Join\limits_0^1$	<code>\rightouterjoin</code>	RIGHT OUTER JOIN
U+027D7	$\Join\limits_0^1$	<code>\fullouterjoin</code>	FULL OUTER JOIN
U+027D8	$\bot\limits_0^1$	<code>\bigbot</code>	LARGE UP TACK
U+027D9	$\top\limits_0^1$	<code>\bigtop</code>	LARGE DOWN TACK
U+029F8	\big/\limits_0^1	<code>\xsol</code>	BIG SOLIDUS
U+029F9	$\big\backslash\limits_0^1$	<code>\xbsol</code>	BIG REVERSE SOLIDUS
U+02A00	$\bigodot\limits_0^1$	<code>\bigodot</code>	N-ARY CIRCLED DOT OPERATOR
U+02A01	$\bigoplus\limits_0^1$	<code>\bigoplus</code>	N-ARY CIRCLED PLUS OPERATOR

U+02A02		<code>\bigotimes</code>	N-ARY CIRCLED TIMES OPERATOR
U+02A03		<code>\bigcupdot</code>	N-ARY UNION OPERATOR WITH DOT
U+02A04		<code>\biguplus</code>	N-ARY UNION OPERATOR WITH PLUS
U+02A05		<code>\bigsqcap</code>	N-ARY SQUARE INTERSECTION OPERATOR
U+02A06		<code>\bigsqcup</code>	N-ARY SQUARE UNION OPERATOR
U+02A07		<code>\conjquant</code>	TWO LOGICAL AND OPERATOR
U+02A08		<code>\disjquant</code>	TWO LOGICAL OR OPERATOR
U+02A09		<code>\bigtimes</code>	N-ARY TIMES OPERATOR
U+02A0B		<code>\sumint</code>	SUMMATION WITH INTEGRAL
U+02A0C		<code>\iiint</code>	QUADRUPLE INTEGRAL OPERATOR
U+02A0D		<code>\intbar</code>	FINITE PART INTEGRAL
U+02A0E		<code>\intBar</code>	INTEGRAL WITH DOUBLE STROKE
U+02A0F		<code>\fint</code>	INTEGRAL AVERAGE WITH SLASH
U+02A10		<code>\circfnint</code>	CIRCULATION FUNCTION
U+02A11		<code>\awint</code>	ANTICLOCKWISE INTEGRATION LINE INTEGRATION WITH RECTANGULAR
U+02A12		<code>\rppolint</code>	PATH AROUND POLE LINE INTEGRATION WITH SEMICIRCULAR
U+02A13		<code>\scpolint</code>	PATH AROUND POLE LINE INTEGRATION NOT INCLUDING THE
U+02A14		<code>\npolint</code>	POLE
U+02A15		<code>\pointint</code>	INTEGRAL AROUND A POINT OPERATOR
U+02A16		<code>\sqint</code>	QUATERNION INTEGRAL OPERATOR INTEGRAL WITH LEFTWARDS ARROW WITH
U+02A17		<code>\intlarhk</code>	HOOK
U+02A18		<code>\intx</code>	INTEGRAL WITH TIMES SIGN
U+02A19		<code>\intcap</code>	INTEGRAL WITH INTERSECTION
U+02A1A		<code>\intcup</code>	INTEGRAL WITH UNION
U+02A1B		<code>\upint</code>	INTEGRAL WITH OVERBAR
U+02A1C		<code>\lowint</code>	INTEGRAL WITH UNDERBAR
U+02A1D		<code>\Join</code>	JOIN
U+02A1E		<code>\bigtriangleleft</code>	LARGE LEFT TRIANGLE OPERATOR

U+02A1F		<code>\zcmp</code>	Z NOTATION SCHEMA COMPOSITION
U+02A20		<code>\zpipe</code>	Z NOTATION SCHEMA PIPING
U+02A21		<code>\zproject</code>	Z NOTATION SCHEMA PROJECTION
U+02AFC		<code>\biginterleave</code>	LARGE TRIPLE VERTICAL BAR OPERATOR
U+02AFF		<code>\bigtalloblong</code>	N-ARY WHITE VERTICAL BAR

`\l_um_nolimits_tl` This macro is a sequence containing those maths operators that require a `\nolimits` suffix. This list is used when processing `unicode-math-table.tex` to define such commands automatically (see the macro `\um_set_mathsymbol:nNNn`). I've chosen essentially just the operators that look like integrals; hopefully a better mathematician can help me out here. I've a feeling that it's more useful *not* to include the multiple integrals such as , but that might be a matter of preference.

```

707 \tl_new:Nn \l_um_nolimits_tl {
708   \int\iint\iiint\iiint\oint\oiint\oiint
709   \intclockwise\varointclockwise\ointctrlockwise\sumint
710   \intbar\intBar\oint\circfnint\awint\rppolint
711   \scpolint\ncpolint\pointint\sqint\intlarhk\intx
712   \intcap\intcup\upint\lowint
713 }

```

`\addnolimits` This macro appends material to the macro containing the list of operators that don't take limits.

```

714 \DeclareDocumentCommand \addnolimits {m} {
715   \tl_put_right:Nn \l_um_nolimits_tl {#1}
716 }

```

`\removenolimits` Can this macro be given a better name? It removes an item from the `nolimits` list.

```

717 \DeclareDocumentCommand \removenolimits {m} {
718   \tl_remove_all_in:Nn \l_um_nolimits_tl {#1}
719 }

```

7.5 Radicals

The radical for square root is organised in `\um_set_mathsymbol:nNNn` on page ?? . I think it's the only radical ever. (Actually, there is also `\cuberoot` and `\fourthroot`, but they don't seem to behave as proper radicals.)

Also, what about right-to-left square roots?

`\um@radicals` We organise radicals in the same way as `nolimits`-operators; that is, in a comma-list.

```

720 \tl_new:Nn \l_um_radicals_tl {\sqrt}

```


$$\sqrt[2]{1 + \sqrt[3]{1+x}}$$

`\setmathfont{Cambria Math}`
`\[\sqrt[2]{1+\sqrt[3]{1+x}} \]`

7.6 Delimiters

`\left` We redefine the primitive to be preceded by `\mathopen`; this gives much better spacing in cases such as `\sin\left....` Courtesy of Frank Mittelbach:
<http://www.latex-project.org/cgi-bin/ltxbugs2html?pr=latex/3853&prlatex/3754>

```
721 \let\left@primitive\left
722 \def\left{\mathopen{}\left@primitive}
```

No re-definition is made for `\right` because it's not necessary.
 Here are all `\mathopen` characters:

USV	Ex.	Macro	Description
U+00028	(<code>\lparen</code>	LEFT PARENTHESIS
U+0005B	[<code>\lbrack</code>	LEFT SQUARE BRACKET
U+0007B	{	<code>\lbrace</code>	LEFT CURLY BRACKET
U+0221A	√	<code>\sqrt</code>	RADICAL
U+0221B	∛	<code>\cuberoot</code>	CUBE ROOT
U+0221C	∜	<code>\fourthroot</code>	FOURTH ROOT
U+02308	⌈	<code>\lceil</code>	LEFT CEILING
U+0230A	⌋	<code>\lfloor</code>	LEFT FLOOR
U+0231C	⌵	<code>\ulcorner</code>	UPPER LEFT CORNER
U+0231E	⌷	<code>\llcorner</code>	LOWER LEFT CORNER
			LIGHT LEFT TORTOISE SHELL BRACKET
U+02772		<code>\lbrbrak</code>	ORNAMENT
U+027C5	⌢	<code>\lbag</code>	LEFT S-SHAPED BAG DELIMITER
U+027CC)	<code>\longdivision</code>	LONG DIVISION
			MATHEMATICAL LEFT WHITE SQUARE
U+027E6	⌌	<code>\lBrack</code>	BRACKET
U+027E8	⟨	<code>\langle</code>	MATHEMATICAL LEFT ANGLE BRACKET
			MATHEMATICAL LEFT DOUBLE ANGLE
U+027EA	⟨⟨	<code>\lAngle</code>	BRACKET
			MATHEMATICAL LEFT WHITE TORTOISE
U+027EC		<code>\Lbrbrak</code>	SHELL BRACKET
U+02983	⌈	<code>\lBrace</code>	LEFT WHITE CURLY BRACKET
U+02985	(<code>\lParen</code>	LEFT WHITE PARENTHESIS
U+02987	⌈	<code>\llparenthesis</code>	Z NOTATION LEFT IMAGE BRACKET
U+02989	⟨	<code>\llangle</code>	Z NOTATION LEFT BINDING BRACKET

U+0298B		<code>\lbrackubar</code>	LEFT SQUARE BRACKET WITH UNDERBAR LEFT SQUARE BRACKET WITH TICK IN TOP
U+0298D		<code>\lbrackultick</code>	CORNER LEFT SQUARE BRACKET WITH TICK IN
U+0298F		<code>\lbracklltick</code>	BOTTOM CORNER
U+02991		<code>\langedot</code>	LEFT ANGLE BRACKET WITH DOT
U+02993		<code>\lparenless</code>	LEFT ARC LESS-THAN BRACKET
U+02995		<code>\lparengtr</code>	DOUBLE LEFT ARC GREATER-THAN BRACKET
U+02997		<code>\lblkbrbrak</code>	LEFT BLACK TORTOISE SHELL BRACKET
U+029D8		<code>\lvzigzag</code>	LEFT WIGGLY FENCE
U+029DA		<code>\lvzigzag</code>	LEFT DOUBLE WIGGLY FENCE
U+029FC		<code>\lcurvyangle</code>	LEFT POINTING CURVED ANGLE BRACKET
U+03014		<code>\lbrbrak</code>	LEFT BROKEN BRACKET
U+03018		<code>\Lbrbrak</code>	LEFT WHITE TORTOISE SHELL BRACKET

And `\mathclose`:













USV	Ex.	Macro	Description
U+00029)	<code>\rparen</code>	RIGHT PARENTHESIS
U+0005D]	<code>\rbrack</code>	RIGHT SQUARE BRACKET
U+0007D	}	<code>\rbrace</code>	RIGHT CURLY BRACKET
U+02309	⌈	<code>\rceil</code>	RIGHT CEILING
U+0230B	⌋	<code>\rfloor</code>	RIGHT FLOOR
U+0231D	⌮	<code>\urcorner</code>	UPPER RIGHT CORNER
U+0231F	⌭	<code>\lrcorner</code>	LOWER RIGHT CORNER LIGHT RIGHT TORTOISE SHELL BRACKET
U+02773	⌞	<code>\rbrbrak</code>	ORNAMENT
U+027C6	⌘	<code>\rbag</code>	RIGHT S-SHAPED BAG DELIMITER MATHEMATICAL RIGHT WHITE SQUARE
U+027E7	⌚	<code>\rBrack</code>	BRACKET
U+027E9	⌘	<code>\rangle</code>	MATHEMATICAL RIGHT ANGLE BRACKET MATHEMATICAL RIGHT DOUBLE ANGLE
U+027EB	⌞	<code>\rAngle</code>	BRACKET MATHEMATICAL RIGHT WHITE TORTOISE
U+027ED	⌞	<code>\Rbrbrak</code>	SHELL BRACKET
U+02984	⌚	<code>\rBrace</code>	RIGHT WHITE CURLY BRACKET
U+02986	⌞	<code>\rParen</code>	RIGHT WHITE PARENTHESIS
U+02988	⌞	<code>\rrparenthesis</code>	Z NOTATION RIGHT IMAGE BRACKET
U+0298A	⌞	<code>\rrangle</code>	Z NOTATION RIGHT BINDING BRACKET
U+0298C	⌋	<code>\rbrackubar</code>	RIGHT SQUARE BRACKET WITH UNDERBAR RIGHT SQUARE BRACKET WITH TICK IN
U+0298E	⌋	<code>\rbracklrtick</code>	BOTTOM CORNER RIGHT SQUARE BRACKET WITH TICK IN TOP
U+02990	⌋	<code>\rbrackurtick</code>	CORNER
U+02992	⌞	<code>\rangedot</code>	RIGHT ANGLE BRACKET WITH DOT

U+02994	➤	\rparengtr	RIGHT ARC GREATER-THAN BRACKET
U+02996	➤➤	\Rparenless	DOUBLE RIGHT ARC LESS-THAN BRACKET
U+02998)	\rblkrbrak	RIGHT BLACK TORTOISE SHELL BRACKET
U+029D9	⋈	\rvzigzag	RIGHT WIGGLY FENCE
U+029DB	⋈⋈	\Rvzigzag	RIGHT DOUBLE WIGGLY FENCE
U+029FD	➤	\rcurvyangle	RIGHT POINTING CURVED ANGLE BRACKET
U+03015		\rbrbrak	RIGHT BROKEN BRACKET
U+03019		\Rbrbrak	RIGHT WHITE TORTOISE SHELL BRACKET

7.7 Maths accents

Maths accents should just work *if they are available in the font*.

USV	Ex.	Macro	Description
U+00300	̃	\grave	GRAVE ACCENT
U+00301	́	\acute	ACUTE ACCENT
U+00302	̂	\hat	CIRCUMFLEX ACCENT
U+00303	̃	\tilde	TILDE
U+00304	̄	\bar	MACRON
U+00305	̅	\overbar	OVERBAR EMBELLISHMENT
U+00306	̇	\breve	BREVE
U+00307	̈	\dot	DOT ABOVE
U+00308	̉	\ddot	DIERESIS
U+00309	̊	\ovhook	COMBINING HOOK ABOVE
U+0030A	̋	\ocirc	RING
U+0030C	̌	\check	CARON
U+00310	̍	\candra	CANDRABINDU (NON-SPACING)
U+00312	̎	\oturnedcomma	COMBINING TURNED COMMA ABOVE GREEK PSILI (SMOOTH BREATHING)
U+00313	̏	\osmooth	(NON-SPACING) GREEK DASIA (ROUGH BREATHING)
U+00314	̐	\orough	(NON-SPACING)
U+00315	̑	\ocommatopright	COMBINING COMMA ABOVE RIGHT
U+0031A	̒	\droang	LEFT ANGLE ABOVE (NON-SPACING) UNDER TILDE ACCENT (MULTIPLE
U+00330	̣	\wideutilde	CHARACTERS AND NON-SPACING)
U+00331	̤	\underbar	COMBINING MACRON BELOW
U+00338	̥	\not	COMBINING LONG SOLIDUS OVERLAY
U+020D0	̦	\leftharpoonaccent	COMBINING LEFT HARPOON ABOVE
U+020D1	̧	\rightharpoonaccent	COMBINING RIGHT HARPOON ABOVE
U+020D2	̨	\vertoverlay	COMBINING LONG VERTICAL LINE OVERLAY
U+020D6	̩	\overleftarrow	COMBINING LEFT ARROW ABOVE

U+020D7		<code>\vec</code>	COMBINING RIGHT ARROW ABOVE
U+020DB		<code>\dddot</code>	COMBINING THREE DOTS ABOVE
U+020DC		<code>\ddddot</code>	COMBINING FOUR DOTS ABOVE
U+020E1		<code>\overleftrightharpoonarrow</code>	COMBINING LEFT RIGHT ARROW ABOVE
U+020E7		<code>\annuity</code>	COMBINING ANNUITY SYMBOL
U+020E8		<code>\threunderdot</code>	COMBINING TRIPLE UNDERDOT
U+020E9		<code>\widebridgeabove</code>	COMBINING WIDE BRIDGE ABOVE
U+020EC		<code>\underrightharpoonowdown</code>	BARB DOWNWARDS COMBINING LEFTWARDS HARPOON WITH
U+020ED		<code>\underleftharpoonowdown</code>	BARB DOWNWARDS
U+020EE		<code>\underleftarrow</code>	COMBINING LEFT ARROW BELOW
U+020EF		<code>\underrightarrow</code>	COMBINING RIGHT ARROW BELOW
U+020F0		<code>\asteraccent</code>	COMBINING ASTERISK ABOVE

8 Font features

`\um@zf@feature` Use the same method as `fontspec` for feature definition (*i.e.*, using `xkeyval`) but with a conditional to restrict the scope of these features to unicode-math commands.

```

723 \newcommand\um@zf@feature[2]{
724   \define@key[zf]{options}{#1}[] {
725     \bool_if:NTF \l_um_fontspec_feature_bool {
726       #2
727     } {
728       \PackageError{fontspec/unicode-math}
729         {The '#1' font feature can only be used for maths fonts}
730         {The feature you tried to use can only be in commands
731           like \protect\setmathfont}
732     }
733   }
734 }
```

8.1 OpenType maths font features

```

735 \um@zf@feature{ScriptStyle}{
736   \zf@update@ff{+ssty=0}
737 }
738 \um@zf@feature{ScriptScriptStyle}{
739   \zf@update@ff{+ssty=1}
740 }
```

8.2 Script and scriptscript font options

```

741 \define@cmdkey[um]{options}[um@]{script-features}{{}}
```

```

742 \define@cmdkey[um]{options}[um@]{sscript-features}{}
743 \define@cmdkey[um]{options}[um@]{script-font}{}
744 \define@cmdkey[um]{options}[um@]{sscript-font}{}

```

8.3 Range processing

The ‘ALL’ branch here is deprecated and happens automatically.

```

745 \seq_new:N \l_um_mathalph_seq
746 \seq_new:N \l_um_char_range_seq
747 \define@key[um]{options}{range}{
748   \bool_set_false:N \l_um_init_bool
749   \seq_clear:N \l_um_char_range_seq
750   \seq_clear:N \l_um_mathalph_seq
751   \clist_map_inline:nn {#1} {
752     \um_if_mathalph_decl:nTF {##1} {
753       \seq_put_right:Nx \l_um_mathalph_seq {
754         { \exp_not:V \l_um_tmpa_tl }
755         { \exp_not:V \l_um_tmpb_tl }
756         { \exp_not:V \l_um_tmpc_tl }
757       }
758     }{
759       \seq_put_right:Nn \l_um_char_range_seq {##1}
760     }
761   }
762 }
763 \prg_new_conditional:Nnn \um_if_mathalph_decl:n {TF} {
764   \tl_set:Nn \l_um_tmpa_tl {#1}
765   \tl_set:Nn \l_um_tmpb_tl {}
766   \tl_set:Nn \l_um_tmpc_tl {}
767   \tl_if_in:NnT \l_um_tmpa_tl {->} {
768     \exp_after:wN \um_split_arrow:w \l_um_tmpa_tl \q_nil
769   }
770   \tl_if_in:NnT \l_um_tmpa_tl {/#} {
771     \exp_after:wN \um_split_slash:w \l_um_tmpa_tl \q_nil
772   }
773   \seq_if_in:NVTF \g_um_mathalph_seq \l_um_tmpa_tl {
774     \prg_return_true:
775   }{
776     \prg_return_false:
777   }
778 }
779 \cs_set:Npn \um_split_arrow:w #1->#2 \q_nil {
780   \tl_set:Nn \l_um_tmpa_tl {#1}
781   \tl_set:Nn \l_um_tmpc_tl {#2}
782 }
783 \cs_set:Npn \um_split_slash:w #1/#2 \q_nil {
784   \tl_set:Nn \l_um_tmpa_tl {#1}

```

```

785 \tl_set:Nn \l_um_tmpb_tl {#2}
786 }

```

Pretty basic comma separated range processing. Donald Arseneau's selectp package has a cleverer technique.

```

\um@parse@term #1 : unicode character slot
                #2 : control sequence (character macro)
                #3 : control sequence (math type)
                #4 : code to execute

```

This macro expands to #4 if any of its arguments are contained in \l_um_char_range_seq. This list can contain either character ranges (for checking with #1) or control sequences. These latter can either be the command name of a specific character, or the math type of one (e.g., \mathbin).

Character ranges are passed to \um@parse@range, which accepts input in the form shown in table 15.

Table 15: Ranges accepted by \um@parse@range.

Input	Range
x	$r = x$
x-	$r \geq x$
-y	$r \leq y$
x-y	$x \leq r \leq y$

Start by iterating over the commalist, ignoring empties, and initialising the scratch conditional:

```

787 \newcommand\um@parse@term[4]{
788   \seq_map_variable:Nn \l_um_char_range_seq \@ii {
789     \unless\ifx\@ii\@empty
790       \@tempswafalse

```

Match to either the character macro (\alpha) or the math type (\mathbin):

```

791   \expandafter\um@firstchar\expandafter{\@ii}
792   \ifx\@tempa\um@backslash
793     \expandafter\ifx\@ii#2\relax
794       \@tempswatrue
795   \else
796     \expandafter\ifx\@ii#3\relax
797       \@tempswatrue
798   \fi
799 \fi

```

Otherwise, we have a number range, which is passed to another macro:

```

800   \else
801     \expandafter\um@parse@range\@ii-\@marker-\@nil#1\@nil
802   \fi

```

If we have a match, execute the code! It also populates the `\l_um_char_num_range_clist` macro, which is used when defining `\mathbf` (*etc.*) `\mathchar` remappings.

```

803     \if@tempswa
804         \clist_put_right:Nx \l_um_char_num_range_clist { \int-
      expr_eval:n {#1} }
805     #4
806     \fi
807     \fi
808 }
809 }
810 \def\um@firstof#1#2\@nil{#1}
811 \edef\um@backslash{\expandafter\um@firstof\string\string\@nil}
812 \def\um@firstchar#1{\edef\@tempa{\expandafter\um@firstof\string#1\@nil}}

```

`\um@parse@range` Weird syntax. As shown previously in table 15, this macro can be passed four different input types via `\um@parse@term`.

```

813 \def\um@parse@range#1-#2-#3\@nil#4\@nil{
814     \def\@tempa{#1}
815     \def\@tempb{#2}

```

Range	$r = x$
C-list input	<code>\@ii=X</code>
Macro input	<code>\um@parse@range X-\@marker-\@nil#1\@nil</code>
Arguments	$\textcolor{red}{\#1}-\textcolor{blue}{\#2}-\textcolor{green}{\#3} = \textcolor{red}{X}-\textcolor{blue}{\@marker}-\textcolor{green}{\{}}$

```

816     \expandafter\ifx\expandafter\@marker\@tempb\relax
817         \intexpr_compare:nT {#4=#1} \@tempswatrue
818     \else

```

Range	$r \geq x$
C-list input	<code>\@ii=X-</code>
Macro input	<code>\um@parse@range X--\@marker-\@nil#1\@nil</code>
Arguments	$\textcolor{red}{\#1}-\textcolor{blue}{\#2}-\textcolor{green}{\#3} = \textcolor{red}{X}-\textcolor{blue}{\{}}-\textcolor{green}{\@marker}-$

```

819     \ifx\@empty\@tempb
820         \intexpr_compare:nT {#4>#1-1} \@tempswatrue
821     \else

```

Range	$r \leq y$
C-list input	<code>\@ii=-Y</code>
Macro input	<code>\um@parse@range -Y-\@marker-\@nil#1\@nil</code>
Arguments	$\textcolor{red}{\#1}-\textcolor{blue}{\#2}-\textcolor{green}{\#3} = \textcolor{red}{\{}}-\textcolor{blue}{Y}-\textcolor{green}{\@marker}-$

```

822     \ifx\@empty\@tempa
823         \intexpr_compare:nT {#4<#2+1} \@tempswatrue

```

Range	$x \leq r \leq y$
C-list input	<code>\@ii=X-Y</code>
Macro input	<code>\um@parse@range X-Y-\@marker-\@nil#1\@nil</code>
Arguments	$\textcolor{red}{\#1}-\textcolor{blue}{\#2}-\textcolor{green}{\#3} = \textcolor{red}{X}-\textcolor{blue}{Y}-\textcolor{green}{\@marker}-$

```

824         \else
825             \intexpr_compare:nT {#4>#1-1} {
826                 \intexpr_compare:nT {#4<#2+1} \@tempswattrue
827             }
828         \fi
829     \fi
830 \fi
831 }

\um_map_char:nn #1 : Starting input char (single)
                #2 : Starting output char
                Loops through character ranges setting \mathcode.
832 \cs_set:Nn \um_map_chars_range:nnn {
833     \prg_stepwise_inline:nnnn {0}{1}{#1-1} {
834         \um_map_char:nn {#2+##1}{#3+##1}
835     }
836 }
837 \cs_new:Nn \um_map_char_noparse:nn {
838     \um_set_mathcode:nnnn {#1}{\mathalpha}{\um_symfont_tl}{#2}
839 }
840 \cs_new:Nn \um_map_char_parse:nn {
841     \um@parse@term {#1} {\@nil} {\mathalpha} {
842         \um_map_char_noparse:nn {#1}{#2}
843     }
844 }
845 \cs_set:Nn \um_map_chars_Latin:nn {
846     \clist_map_inline:nn {#1} {
847         \um_map_chars_range:ncc {26} { \um_to_usv:nn{##1}{Latin} }
848         { \um_to_usv:nn {#2}{Latin} }
849     }
850 }
851 \cs_set:Nn \um_map_chars_latin:nn {
852     \clist_map_inline:nn {#1} {
853         \um_map_chars_range:ncc {26} { \um_to_usv:nn{##1}{latin} }
854         { \um_to_usv:nn {#2}{latin} }
855     }
856 }
857 \cs_set:Nn \um_map_chars_greek:nn {
858     \clist_map_inline:nn {#1} {
859         \um_map_chars_range:ncc {25} { \um_to_usv:nn {##1} {greek} }
860         { \um_to_usv:nn {#2} {greek} }
861         \um_map_char_single:cc { \um_to_usv:nn {##1} {varepsilon} }
862         { \um_to_usv:nn {#2} {varepsilon} }
863         \um_map_char_single:cc { \um_to_usv:nn {##1} {vartheta} }
864         { \um_to_usv:nn {#2} {vartheta} }
865         \um_map_char_single:cc { \um_to_usv:nn {##1} {varkappa} }

```



```

866         { \um_to_usv:nn {#2} {varkappa} }
867     \um_map_char_single:cc { \um_to_usv:nn {##1} {varphi} }
868         { \um_to_usv:nn {#2} {varphi} }
869     \um_map_char_single:cc { \um_to_usv:nn {##1} {varrho} }
870         { \um_to_usv:nn {#2} {varrho} }
871     \um_map_char_single:cc { \um_to_usv:nn {##1} {varpi} }
872         { \um_to_usv:nn {#2} {varpi} }
873 }
874 }
875 \cs_set:Nn \um_map_chars_Greek:nn {
876     \clist_map_inline:nn {#1} {
877         \um_map_chars_range:ncc {25} { \um_to_usv:nn{##1}{Greek} }
878             { \um_to_usv:nn {#2}{Greek} }
879         \um_map_char_single:cc { \um_to_usv:nn{##1}{varTheta} }
880             { \um_to_usv:nn {#2}{varTheta} }
881     }
882 }
883 \cs_set:Nn \um_map_chars_numbers:nn {
884     \um_map_chars_range:ncc {10} { \um_to_usv:nn{#1}{num} }
885         { \um_to_usv:nn{#2}{num} }
886 }
887 \cs_set:Nn \um_map_single:nnn {
888     \clist_map_inline:nn {#2} {
889         \um_map_char_single:cc { \um_to_usv:nn{##1}{#1} }
890             { \um_to_usv:nn {#3}{#1} }
891     }
892 }
893 \cs_set:Nn \um_map_char_single:nn { \um_map_char:nn {#1}{#2} }
894 \cs_generate_variant:Nn \um_map_char_single:nn {cc}
895 \cs_generate_variant:Nn \um_map_chars_range:nnn {ncc}

```

`\um_set_mathalphabet_char:Nnn` **#1** : Maths alphabet
#2 : Input char (single)
#3 : Output char
 Loops through character ranges setting `\mathcode`.

```

896 \cs_new:Nn \um_set_mathalphabet_char:Nnn {
897     \um_mathmap:Nnn {#1} {#2} {#3}
898 }

```

`\um_set_mathalph_range:Nnn` [*(Number of iterations)*] **#1** : Maths alphabet
#2 : Starting input char (single)
#3 : Starting output char
 Loops through character ranges setting `\mathcode`.

```

899 \cs_new:Nn \um_set_mathalph_range:nNnn {
900     \prg_stepwise_inline:nnnn {0}{1}{#1-1} {
901         \um_mathmap:Nnn {#2} { ##1 + #3 } { ##1 + #4 }

```

```

902 }
903 }
904 \cs_new:Nn \um_set_mathalphabet_pos:Nnnn {
905   \cs_if_exist:cT { \um_to_usv:nn {#4}{#2} } {
906     \clist_map_inline:nn {#3} {
907       \um_set_mathalphabet_char:Ncc #1 { \um_to_usv:nn {##1} {#2} }
908       { \um_to_usv:nn {#4} {#2} }
909     }
910   }
911 }
912 \cs_new:Nn \um_set_mathalphabet_numbers:Nnn {
913   \clist_map_inline:nn {#2} {
914     \um_set_mathalph_range:nNcc {10} #1 { \um_to_usv:nn {##1} {num} }
915     { \um_to_usv:nn {#3} {num} }
916   }
917 }
918 \cs_new:Nn \um_set_mathalphabet_Latin:Nnn {
919   \clist_map_inline:nn {#2} {
920     \um_set_mathalph_range:nNcc {26} #1 { \um_to_usv:nn {##1} {Latin} }
921     { \um_to_usv:nn {#3} {Latin} }
922   }
923 }
924 \cs_new:Nn \um_set_mathalphabet_latin:Nnn {
925   \clist_map_inline:nn {#2} {
926     \um_set_mathalph_range:nNcc {26} #1 { \um_to_usv:nn {##1} {latin} }
927     { \um_to_usv:nn {#3} {latin} }
928     \um_set_mathalphabet_char:Ncc #1 { \um_to_usv:nn {##1} {h} }
929     { \um_to_usv:nn {#3} {h} }
930   }
931 }
932 \cs_new:Nn \um_set_mathalphabet_Greek:Nnn {
933   \clist_map_inline:nn {#2} {
934     \um_set_mathalph_range:nNcc {25} #1 { \um_to_usv:nn {##1} {Greek} }
935     { \um_to_usv:nn {#3} {Greek} }
936     \um_set_mathalphabet_char:Ncc #1 { \um_to_usv:nn {##1} {varTheta} }
937     { \um_to_usv:nn {#3} {varTheta} }
938   }
939 }
940 \cs_new:Nn \um_set_mathalphabet_greek:Nnn {
941   \clist_map_inline:nn {#2} {
942     \um_set_mathalph_range:nNcc {25} #1 { \um_to_usv:nn {##1} {greek} }
943     { \um_to_usv:nn {#3} {greek} }
944     \um_set_mathalphabet_char:Ncc #1 { \um_to_usv:nn {##1} {varepsilon} }
945     { \um_to_usv:nn {#3} {varepsilon} }
946     \um_set_mathalphabet_char:Ncc #1 { \um_to_usv:nn {##1} {vartheta} }
947     { \um_to_usv:nn {#3} {vartheta} }

```

```

948 \um_set_mathalphabet_char:Ncc #1 { \um_to_usv:nn {##1} {varkappa} }
949 { \um_to_usv:nn {#3} {varkappa} }
950 \um_set_mathalphabet_char:Ncc #1 { \um_to_usv:nn {##1} {varphi} }
951 { \um_to_usv:nn {#3} {varphi} }
952 \um_set_mathalphabet_char:Ncc #1 { \um_to_usv:nn {##1} {varrho} }
953 { \um_to_usv:nn {#3} {varrho} }
954 \um_set_mathalphabet_char:Ncc #1 { \um_to_usv:nn {##1} {varpi} }
955 { \um_to_usv:nn {#3} {varpi} }
956 }
957 }
958 \cs_generate_variant:Nn \um_set_mathalphabet_char:Nnn {Ncc}
959 \cs_generate_variant:Nn \um_set_mathalph_range:nNnn {nNcc}

```

8.4 Resolving Greek symbol name control sequences

`\um_resolve_greek:` This macro defines `\Alpha...``\omega` as their corresponding unicode (mathematical italic) character. Remember that the mapping to upright or italic happens with the mathcode definitions, whereas these macros just stand for the literal unicode characters.

```

960 \AtBeginDocument{\um_resolve_greek:}
961 \cs_new:Nn \um_resolve_greek: {
962   \clist_map_inline:nn {
963     Alpha,Beta,Gamma,Delta,Epsilon,Zeta,Eta,Theta,Iota,Kappa,Lambda,
964     alpha,beta,gamma,delta,          zeta,eta,theta,iota,kappa,lambda,
965     Mu,Nu,Xi,Omicron,Pi,Rho,Sigma,Tau,Upsilon,Phi,Chi,Psi,Omega,
966     mu,nu,xi,omicron,pi,rho,sigma,tau,upsilon,    chi,psi,omega,
967     varTheta,
968     varsigma,vartheta,varkappa,varrho,varpi
969   }{
970     \tl_set:cx {##1} { \exp_not:c { mit ##1 } }
971   }
972   \tl_set:Nn \epsilon {
973     \bool_if:NTF \g_um_texgreek_bool \mitvarepsilon \mitepsilon
974   }
975   \tl_set:Nn \phi {
976     \bool_if:NTF \g_um_texgreek_bool \mitvarphi \mitphi
977   }
978   \tl_set:Nn \varepsilon {
979     \bool_if:NTF \g_um_texgreek_bool \mitepsilon \mitvarepsilon
980   }
981   \tl_set:Nn \varphi {
982     \bool_if:NTF \g_um_texgreek_bool \mitphi \mitvarphi
983   }
984 }

```

9 Maths alphabets mapping definitions

Algorithm for setting alphabet fonts. By default, when `range` is empty, we are in *implicit* mode. If `range` contains the name of the math alphabet, we are in *explicit* mode and do things slightly differently.

Implicit mode:

- Try and set all of the alphabet shapes.
- Check for the first glyph of each alphabet to detect if the font supports each alphabet shape.
- For alphabets that do exist, overwrite whatever's already there.
- For alphabets that are not supported, *do nothing*. (This includes leaving the old alphabet definition in place.)

Explicit mode:

- Only set the alphabets specified.
- Check for the first glyph of the alphabet to detect if the font contains the alphabet shape in the unicode math plane.
- For unicode math alphabets, overwrite whatever's already there.
- Otherwise, use the ASCII letters instead.

9.0.1 Macros

`\um_prepare_alph:n` Define the high level math alphabet macros (`\mathit`, etc.) in terms of unicode-math definitions. Use `\bgroup/\egroup` so s'scripts scan the whole thing.

```
985 \cs_new:Nn \um_prepare_alph:n {  
986   \cs_set:cpn {um_#1:n} ##1 {  
987     \use:c {um_setup_#1:} ##1 \egroup  
988   }  
989   \cs_set_protected:cpx {#1} {  
990     \exp_not:n{  
991       \bgroup  
992       \mode_if_math:F {  
993         \egroup\expandafter  
994         \non@alpherr\expandafter{\csname #1\endcsname\space}  
995       }  
996     }  
997     \exp_not:c {um_#1:n}  
998   }  
999 }
```

This is every math alphabet known to unicode-math:

`\g_um_mathalph_seq`

```

1000 \seq_new:N \g_um_mathalph_seq
1001 \tl_map_inline:nn {
1002   \mathup\mathit\mathbb\mathbbit
1003   \mathscr\mathfrak\mathtt
1004   \mathsf\mathsfup\mathsfit
1005   \mathbf\mathbfup\mathbfit
1006   \mathbfscr\mathbffrak
1007   \mathbfsf\mathbfsfup\mathbfsfit
1008 }{
1009   \seq_put_right:Nn \g_um_mathalph_seq {#1}
1010   \exp_args:Nf \um_prepare_alph:n {\cs_to_str:N #1}
1011 }

1012 \seq_new:N \g_um_default_mathalph_seq
1013 \clist_map_inline:nn {
1014   {\mathup    } {latin, Latin, greek, Greek, num, misc} {\mathup    } ,
1015   {\mathit    } {latin, Latin, greek, Greek, misc}     {\mathit    } ,
1016   {\mathbb    } {latin, Latin, num, misc}               {\mathbb    } ,
1017   {\mathbbit  } {misc}                                 {\mathbbit  } ,
1018   {\mathscr   } {latin, Latin}                         {\mathscr   } ,
1019   {\mathfrak  } {latin, Latin}                         {\mathfrak  } ,
1020   {\mathtt    } {latin, Latin, num}                     {\mathtt    } ,
1021   {\mathsfup  } {latin, Latin, num}                     {\mathsfup  } ,
1022   {\mathsfit  } {latin, Latin}                         {\mathsfit  } ,
1023   {\mathbfup  } {latin, Latin, greek, Greek, num, misc} {\mathbfup  } ,
1024   {\mathbfit  } {latin, Latin, greek, Greek, misc}     {\mathbfit  } ,
1025   {\mathbfscr } {latin, Latin}                         {\mathbfscr } ,
1026   {\mathbffrak} {latin, Latin}                         {\mathbffrak} ,
1027   {\mathbfsfup} {latin, Latin, greek, Greek, num, misc} {\mathbfsfup} ,
1028   {\mathbfsfit} {latin, Latin, greek, Greek, misc}     {\mathbfsfit}
1029 }{
1030   \seq_put_right:Nn \g_um_default_mathalph_seq {#1}
1031 }

```

`\um_setup_alphabets:` Variables:

```

1032 \seq_new:N \l_um_missing_alph_seq
1033 \cs_new:Nn \um_setup_alphabets: {
1034   \seq_clear:N \l_um_missing_alph_seq
1035   \seq_if_empty:NTF \l_um_mathalph_seq {
1036     (trace) \um_debug:n {Setup~ alphabets:~ implicit~ mode}
1037     \seq_set_eq:NN \l_um_mathalph_seq \g_um_default_mathalph_seq
1038     \bool_set_true:N \l_um_implicit_alph_bool
1039     \um_maybe_init_alphabet:n {sf}
1040     \um_maybe_init_alphabet:n {bf}

```

```

1041 \um_maybe_init_alphabet:n {bfsf}
1042 }{
1043 (trace) \um_debug:n {Setup~ alphabets:~ explicit~ mode}
1044 \bool_set_false:N \l_um_implicit_alph_bool
1045 \cs_set_eq:NN \um_mathmap:Nnn \um_mathmap_noparse:Nnn
1046 }
1047 \seq_map_inline:Nn \l_um_mathalph_seq {
1048 \tl_set:No \l_um_tmpa_tl { \use_i:nnn ##1 }
1049 \tl_set:No \l_um_tmpb_tl { \use_ii:nnn ##1 }
1050 \tl_set:No \l_um_remap_alphabet_tl { \use_iii:nnn ##1 }
1051 \tl_if_empty:NTF \l_um_remap_alphabet_tl {
1052 \tl_set:Nx \l_um_remap_alphabet_tl {\exp_after:wN \token_to_str:N \l_um_tmpa_tl}
1053 }{
1054 \tl_set:Nx \l_um_remap_alphabet_tl {\exp_after:wN \token_to_str:N \l_um_remap_alphabet_tl}
1055 }
1056 \tl_set:Nx \l_um_remap_alphabet_tl {\exp_after:wN \use_none:nnnnn \l_um_remap_alphabet_tl}
1057 \tl_if_empty:NT \l_um_tmpb_tl {
1058 \cs_set_eq:NN \um_maybe_init_alphabet:n \um_init_alphabet:n
1059 \tl_set:Nn \l_um_tmpb_tl { latin, Latin, greek, Greek, num, misc }
1060 }
1061 \um_setup_math_alphabet:VVV \l_um_tmpa_tl \l_um_tmpb_tl \l_um_remap_alphabet_tl
1062 }
1063 \um_warn_missing_alphabets:
1064 }

1065 \cs_new:Nn \um_warn_missing_alphabets: {
1066 \seq_if_empty:NF \l_um_missing_alph_seq {
1067 \typeout{
1068 Package~unicode-math~Warning:~
1069 missing~math~alphabets~in~font~ \fontname\l_um_font
1070 }
1071 \seq_map_inline:Nn \l_um_missing_alph_seq {
1072 \typeout{\space\space\space\space##1}
1073 }
1074 }
1075 }

```

`\um_setup_math_alphabet:Nnn` **#1** : Math font family name (e.g., `\mathbb`)

#2 : Math alphabets, comma separated of {latin, Latin, greek, Greek, num}

#3 : Math alphabets output string (usually same as input `bb`)

First check that at least one of the alphabets for the font shape is defined, and then loop through them defining the individual ranges.

```

1076 \cs_new:Nn \um_setup_math_alphabet:Nnn {
1077 \tl_set:Nx \l_um_tmpa_tl {\cs_to_str:N #1}
1078 \tl_set:Nx \l_um_tmpb_tl {\exp_after:wN \use_none:nnnn \l_um_tmpa_tl}
1079 \clist_map_inline:nn {#2} {
1080 \cs_if_exist:cT {um_config_ \l_um_tmpa_tl _##1:n} {

```

```

1081 \tl_if_eq:nnTF {##1}{misc} {
1082   \exp_args:NV \um_maybe_init_alphabet:n \l_um_tmpb_tl
1083   \clist_map_break:
1084 }{
1085   \um_glyph_if_exist:cT { \um_to_usv:nn {#3}{##1} }{
1086     \exp_args:NV \um_maybe_init_alphabet:n \l_um_tmpb_tl
1087     \clist_map_break:
1088   }
1089 }
1090 }
1091 }
1092 \clist_map_inline:nn {#2} {
1093   \cs_if_exist:cT {um_config_ \l_um_tmpa_tl _##1:n} {
1094     \tl_if_eq:nnTF {##1}{misc} {
1095 (trace) \um_debug:n {Setup~ alphabet::~ \l_um_tmpa_tl\space {##1}}
1096     \use:c {um_config_ \l_um_tmpa_tl _##1:n} {#3}
1097   }{
1098     \um_glyph_if_exist:cTF { \um_to_usv:nn {#3}{##1} } {
1099 (trace) \um_debug:n {Setup~ alphabet::~ \l_um_tmpa_tl\space {##1}}
1100     \use:c {um_config_ \l_um_tmpa_tl _##1:n} {#3}
1101   }{
1102     \bool_if:NTF \l_um_implicit_alph_bool {
1103       \seq_put_right:Nx \l_um_missing_alph_seq {
1104         \@backslashchar
1105         \l_um_tmpa_tl\space(\tl_use:c{g_um_math_alphabet_name_##1_tl})
1106       }
1107     }{
1108       \use:c {um_config_ \l_um_tmpa_tl _##1:n} {up}
1109     }
1110   }
1111 }
1112 }
1113 }
1114 }
1115 \cs_generate_variant:Nn \um_setup_math_alphabet:Nnn {NV,VVV}

1116 \cs_set:Nn \um_init_alphabet:n {
1117 (trace) \um_debug:n {Initialiasing~\@backslashchar math#1}
1118 \cs_set_eq:cN {um_setup_math#1:} \prg_do_nothing:
1119 }

```

\um_glyph_if_exist:nTF : TODO: Generalise for arbitrary fonts! \um@font is not always the one used for a specific glyph!!

```

1120 \prg_new_conditional:Nnn \um_glyph_if_exist:n {p,TF,T,F} {
1121   \etex_iffontchar:D \l_um_font #1 \scan_stop:
1122   \prg_return_true:
1123 }

```

```

1124     \prg_return_false:
1125     \fi:
1126   }
1127   \cs_generate_variant:Nn \um_glyph_if_exist_p:n {c}
1128   \cs_generate_variant:Nn \um_glyph_if_exist:nTF {c}
1129   \cs_generate_variant:Nn \um_glyph_if_exist:nT  {c}
1130   \cs_generate_variant:Nn \um_glyph_if_exist:nF  {c}

```

9.1 Alphabets

9.1.1 Upright: \mathup

```

1131 \cs_new:Nn \um_config_mathup_num:n {
1132   \um_map_chars_numbers:nn {up}{#1}
1133   \um_set_mathalphabet_numbers:Nnn \mathup {up}{#1}
1134 }
1135 \cs_new:Nn \um_config_mathup_Latin:n {
1136   \bool_if:NTF \g_um_literal_bool {
1137     \um_map_chars_Latin:nn {up} {#1}
1138   }{
1139     \bool_if:NT \g_um_upLatin_bool {
1140       \um_map_chars_Latin:nn {up,it} {#1}
1141     }
1142   }
1143   \um_set_mathalphabet_Latin:Nnn \mathup {up,it}{#1}
1144 }
1145 \cs_new:Nn \um_config_mathup_latin:n {
1146   \bool_if:NTF \g_um_literal_bool {
1147     \um_map_chars_latin:nn {up} {#1}
1148   }{
1149     \bool_if:NT \g_um_uplatin_bool {
1150       \um_map_chars_latin:nn {up,it} {#1}
1151       \um_map_single:nnn {h} {up,it} {#1}
1152       \um_map_single:nnn {dotlessi} {up,it} {#1}
1153       \um_map_single:nnn {dotlessj} {up,it} {#1}
1154     }
1155   }
1156   \um_set_mathalphabet_latin:Nnn \mathup {up,it}{#1}
1157 }
1158 \cs_new:Nn \um_config_mathup_Greek:n {
1159   \bool_if:NTF \g_um_literal_bool {
1160     \um_map_chars_Greek:nn {up}{#1}
1161   }{
1162     \bool_if:NT \g_um_upGreek_bool {
1163       \um_map_chars_Greek:nn {up,it}{#1}
1164     }
1165   }

```



```

1166 \um_set_mathalphabet_Greek:Nnn \mathup {up,it}{#1}
1167 }
1168 \cs_new:Nn \um_config_mathup_greek:n {
1169   \bool_if:NTF \g_um_literal_bool {
1170     \um_map_chars_greek:nn {up} {#1}
1171   }{
1172     \bool_if:NT \g_um_upgreek_bool {
1173       \um_map_chars_greek:nn {up,it} {#1}
1174     }
1175   }
1176   \um_set_mathalphabet_greek:Nnn \mathup {up,it} {#1}
1177 }
1178 \cs_new:Nn \um_config_mathup_misc:n {
1179   \bool_if:NTF \g_um_literal_Nabla_bool {
1180     \um_map_single:nnn {Nabla}{up}{up}
1181   }{
1182     \bool_if:NT \g_um_upNabla_bool {
1183       \um_map_single:nnn {Nabla}{up,it}{up}
1184     }
1185   }
1186   \bool_if:NTF \g_um_literal_partial_bool {
1187     \um_map_single:nnn {partial}{up}{up}
1188   }{
1189     \bool_if:NT \g_um_uppartial_bool {
1190       \um_map_single:nnn {partial}{up,it}{up}
1191     }
1192   }
1193   \um_set_mathalphabet_pos:Nnnn \mathup {partial} {up,it} {#1}
1194   \um_set_mathalphabet_pos:Nnnn \mathup {Nabla} {up,it} {#1}
1195   \um_set_mathalphabet_pos:Nnnn \mathup {dotlessi} {up,it} {#1}
1196   \um_set_mathalphabet_pos:Nnnn \mathup {dotlessj} {up,it} {#1}
1197 }

```

9.1.2 Italic: \mathit

```

1198 \cs_new:Nn \um_config_mathit_Latin:n {
1199   \bool_if:NTF \g_um_literal_bool {
1200     \um_map_chars_Latin:nn {it} {#1}
1201   }{
1202     \bool_if:NF \g_um_upLatin_bool {
1203       \um_map_chars_Latin:nn {up,it} {#1}
1204     }
1205   }
1206   \um_set_mathalphabet_Latin:Nnn \mathit {up,it}{#1}
1207 }
1208 \cs_new:Nn \um_config_mathit_latin:n {
1209   \bool_if:NTF \g_um_literal_bool {

```

```

1210 \um_map_chars_latin:nn {it} {#1}
1211 \um_map_single:nnn {h}{it}{#1}
1212 }{
1213 \bool_if:NF \g_um_uplatin_bool {
1214 \um_map_chars_latin:nn {up,it} {#1}
1215 \um_map_single:nnn {h}{up,it}{#1}
1216 \um_map_single:nnn {dotlessi}{up,it}{#1}
1217 \um_map_single:nnn {dotlessj}{up,it}{#1}
1218 }
1219 }
1220 \um_set_mathalphabet_latin:Nnn \mathit {up,it} {#1}
1221 \um_set_mathalphabet_pos:Nnnn \mathit {dotlessi} {up,it} {#1}
1222 \um_set_mathalphabet_pos:Nnnn \mathit {dotlessj} {up,it} {#1}
1223 }
1224 \cs_new:Nn \um_config_mathit_Greek:n {
1225 \bool_if:NTF \g_um_literal_bool {
1226 \um_map_chars_Greek:nn {it}{#1}
1227 }{
1228 \bool_if:NF \g_um_upGreek_bool {
1229 \um_map_chars_Greek:nn {up,it}{#1}
1230 }
1231 }
1232 \um_set_mathalphabet_Greek:Nnn \mathit {up,it}{#1}
1233 }
1234 \cs_new:Nn \um_config_mathit_greek:n {
1235 \bool_if:NTF \g_um_literal_bool {
1236 \um_map_chars_greek:nn {it} {#1}
1237 }{
1238 \bool_if:NF \g_um_upgreek_bool {
1239 \um_map_chars_greek:nn {it,up} {#1}
1240 }
1241 }
1242 \um_set_mathalphabet_greek:Nnn \mathit {up,it} {#1}
1243 }
1244 \cs_new:Nn \um_config_mathit_misc:n {
1245 \bool_if:NTF \g_um_literal_Nabla_bool {
1246 \um_map_single:nnn {Nabla}{it}{it}
1247 }{
1248 \bool_if:NF \g_um_upNabla_bool {
1249 \um_map_single:nnn {Nabla}{up,it}{it}
1250 }
1251 }
1252 \bool_if:NTF \g_um_literal_partial_bool {
1253 \um_map_single:nnn {partial}{it}{it}
1254 }{
1255 \bool_if:NF \g_um_uppartial_bool {

```

```

1256     \um_map_single:nnn {partial}{up,it}{it}
1257   }
1258 }
1259 \um_set_mathalphabet_pos:Nnnn \mathit {partial} {up,it}{#1}
1260 \um_set_mathalphabet_pos:Nnnn \mathit {Nabla} {up,it}{#1}
1261 }

```

9.1.3 Blackboard or double-struck: `\mathbb` and `\mathbbbit`

```

1262 \cs_new:Nn \um_config_mathbb_latin:n {
1263   \um_set_mathalphabet_latin:Nnn \mathbb {up,it}{#1}
1264 }
1265 \cs_new:Nn \um_config_mathbb_Latin:n {
1266   \um_set_mathalphabet_Latin:Nnn \mathbb {up,it}{#1}
1267   \um_set_mathalphabet_pos:Nnnn \mathbb {C} {up,it} {#1}
1268   \um_set_mathalphabet_pos:Nnnn \mathbb {H} {up,it} {#1}
1269   \um_set_mathalphabet_pos:Nnnn \mathbb {N} {up,it} {#1}
1270   \um_set_mathalphabet_pos:Nnnn \mathbb {P} {up,it} {#1}
1271   \um_set_mathalphabet_pos:Nnnn \mathbb {Q} {up,it} {#1}
1272   \um_set_mathalphabet_pos:Nnnn \mathbb {R} {up,it} {#1}
1273   \um_set_mathalphabet_pos:Nnnn \mathbb {Z} {up,it} {#1}
1274 }
1275 \cs_new:Nn \um_config_mathbb_num:n {
1276   \um_set_mathalphabet_numbers:Nnn \mathbb {up}{#1}
1277 }
1278 \cs_new:Nn \um_config_mathbb_misc:n {
1279   \um_set_mathalphabet_pos:Nnnn \mathbb {Pi} {up,it} {#1}
1280   \um_set_mathalphabet_pos:Nnnn \mathbb {pi} {up,it} {#1}
1281   \um_set_mathalphabet_pos:Nnnn \mathbb {Gamma} {up,it} {#1}
1282   \um_set_mathalphabet_pos:Nnnn \mathbb {gamma} {up,it} {#1}
1283   \um_set_mathalphabet_pos:Nnnn \mathbb {summation} {up} {#1}
1284 }
1285 \cs_new:Nn \um_config_mathbbbit_misc:n {
1286   \um_set_mathalphabet_pos:Nnnn \mathbbbit {D} {up,it} {#1}
1287   \um_set_mathalphabet_pos:Nnnn \mathbbbit {d} {up,it} {#1}
1288   \um_set_mathalphabet_pos:Nnnn \mathbbbit {e} {up,it} {#1}
1289   \um_set_mathalphabet_pos:Nnnn \mathbbbit {i} {up,it} {#1}
1290   \um_set_mathalphabet_pos:Nnnn \mathbbbit {j} {up,it} {#1}
1291 }

```

9.1.4 Script or caligraphic: `\mathscr` and `\mathcal`

```

1292 \cs_new:Nn \um_config_mathscr_Latin:n {
1293   \um_set_mathalphabet_Latin:Nnn \mathscr {up,it}{#1}
1294   \um_set_mathalphabet_pos:Nnnn \mathscr {B}{up,it}{#1}
1295   \um_set_mathalphabet_pos:Nnnn \mathscr {E}{up,it}{#1}
1296   \um_set_mathalphabet_pos:Nnnn \mathscr {F}{up,it}{#1}
1297   \um_set_mathalphabet_pos:Nnnn \mathscr {H}{up,it}{#1}
1298   \um_set_mathalphabet_pos:Nnnn \mathscr {I}{up,it}{#1}

```

```

1299 \um_set_mathalphabet_pos:Nnnn \mathscr {L}{up,it}{#1}
1300 \um_set_mathalphabet_pos:Nnnn \mathscr {M}{up,it}{#1}
1301 \um_set_mathalphabet_pos:Nnnn \mathscr {R}{up,it}{#1}
1302 }
1303 \cs_new:Nn \um_config_mathscr_latin:n {
1304 \um_set_mathalphabet_latin:Nnn \mathscr {up,it}{#1}
1305 \um_set_mathalphabet_pos:Nnnn \mathscr {e}{up,it}{#1}
1306 \um_set_mathalphabet_pos:Nnnn \mathscr {g}{up,it}{#1}
1307 \um_set_mathalphabet_pos:Nnnn \mathscr {o}{up,it}{#1}
1308 }

```

9.1.5 Fraktur or fraktur or blackletter: `\mathfrak`

```

1309 \cs_new:Nn \um_config_mathfrak_Latin:n {
1310 \um_set_mathalphabet_Latin:Nnn \mathfrak {up,it}{#1}
1311 \um_set_mathalphabet_pos:Nnnn \mathfrak {C}{up,it}{#1}
1312 \um_set_mathalphabet_pos:Nnnn \mathfrak {H}{up,it}{#1}
1313 \um_set_mathalphabet_pos:Nnnn \mathfrak {I}{up,it}{#1}
1314 \um_set_mathalphabet_pos:Nnnn \mathfrak {R}{up,it}{#1}
1315 \um_set_mathalphabet_pos:Nnnn \mathfrak {Z}{up,it}{#1}
1316 }
1317 \cs_new:Nn \um_config_mathfrak_latin:n {
1318 \um_set_mathalphabet_latin:Nnn \mathfrak {up,it}{#1}
1319 }

```

9.1.6 Sans serif upright: `\mathsfup`

```

1320 \cs_new:Nn \um_config_mathsfup_num:n {
1321 \um_set_mathalphabet_numbers:Nnn \mathsf {up}{#1}
1322 \um_set_mathalphabet_numbers:Nnn \mathsfup {up}{#1}
1323 }
1324 \cs_new:Nn \um_config_mathsfup_Latin:n {
1325 \bool_if:NTF \g_um_sfliteral_bool {
1326 \um_map_chars_Latin:nn {sfup} {#1}
1327 \um_set_mathalphabet_Latin:Nnn \mathsf {up}{#1}
1328 }{
1329 \bool_if:NT \g_um_upsans_bool {
1330 \um_map_chars_Latin:nn {sfup,sfit} {#1}
1331 \um_set_mathalphabet_Latin:Nnn \mathsf {up,it}{#1}
1332 }
1333 }
1334 \um_set_mathalphabet_Latin:Nnn \mathsfup {up,it}{#1}
1335 }
1336 \cs_new:Nn \um_config_mathsfup_latin:n {
1337 \bool_if:NTF \g_um_sfliteral_bool {
1338 \um_map_chars_latin:nn {sfup} {#1}
1339 \um_set_mathalphabet_latin:Nnn \mathsf {up}{#1}
1340 }{
1341 \bool_if:NT \g_um_upsans_bool {

```

```

1342     \um_map_chars_latin:nn {sfup,sfit} {#1}
1343     \um_set_mathalphabet_latin:Nnn \mathsf {up,it}{#1}
1344   }
1345 }
1346 \um_set_mathalphabet_latin:Nnn \mathsfup {up,it}{#1}
1347 }

```

9.1.7 Sans serif italic: `\mathsf`

```

1348 \cs_new:Nn \um_config_mathsf_Latin:n {
1349   \bool_if:NTF \g_um_sfliteral_bool {
1350     \um_map_chars_Latin:nn {sf} {#1}
1351     \um_set_mathalphabet_Latin:Nnn \mathsf {it}{#1}
1352   }{
1353     \bool_if:NF \g_um_upsans_bool {
1354       \um_map_chars_Latin:nn {sfup,sf} {#1}
1355       \um_set_mathalphabet_Latin:Nnn \mathsf {up,it}{#1}
1356     }
1357   }
1358   \um_set_mathalphabet_Latin:Nnn \mathsf {it}{#1}
1359 }
1360 \cs_new:Nn \um_config_mathsf_latin:n {
1361   \bool_if:NTF \g_um_sfliteral_bool {
1362     \um_map_chars_latin:nn {sf} {#1}
1363     \um_set_mathalphabet_latin:Nnn \mathsf {it}{#1}
1364   }{
1365     \bool_if:NF \g_um_upsans_bool {
1366       \um_map_chars_latin:nn {sfup,sf} {#1}
1367       \um_set_mathalphabet_latin:Nnn \mathsf {up,it}{#1}
1368     }
1369   }
1370   \um_set_mathalphabet_latin:Nnn \mathsf {it}{#1}
1371 }

```

9.1.8 Typewriter or monospaced: `\mathtt`

```

1372 \cs_new:Nn \um_config_mathtt_num:n {
1373   \um_set_mathalphabet_numbers:Nnn \mathtt {up}{#1}
1374 }
1375 \cs_new:Nn \um_config_mathtt_Latin:n {
1376   \um_set_mathalphabet_Latin:Nnn \mathtt {up,it}{#1}
1377 }
1378 \cs_new:Nn \um_config_mathtt_latin:n {
1379   \um_set_mathalphabet_latin:Nnn \mathtt {up,it}{#1}
1380 }

```

9.1.9 Bold Italic: `\mathbf`

```

1381 \cs_new:Nn \um_config_mathbf_Latin:n {

```

```

1382 \bool_if:NF \g_um_bfupLatin_bool {
1383   \um_map_chars_Latin:nn {bfup,bfit} {#1}
1384 }
1385 \um_set_mathalphabet_Latin:Nnn \mathbfit {up,it}{#1}
1386 \bool_if:NTF \g_um_bfliteral_bool {
1387   \um_map_chars_Latin:nn {bfit} {#1}
1388   \um_set_mathalphabet_Latin:Nnn \mathbf {it}{#1}
1389 }{
1390   \bool_if:NF \g_um_bfupLatin_bool {
1391     \um_map_chars_Latin:nn {bfup,bfit} {#1}
1392     \um_set_mathalphabet_Latin:Nnn \mathbf {up,it}{#1}
1393   }
1394 }
1395 }
1396 \cs_new:Nn \um_config_mathbfit_latin:n {
1397   \bool_if:NF \g_um_bfuplatin_bool {
1398     \um_map_chars_latin:nn {bfup,bfit} {#1}
1399   }
1400   \um_set_mathalphabet_latin:Nnn \mathbfit {up,it}{#1}
1401   \bool_if:NTF \g_um_bfliteral_bool {
1402     \um_map_chars_latin:nn {bfit} {#1}
1403     \um_set_mathalphabet_latin:Nnn \mathbf {it}{#1}
1404   }{
1405     \bool_if:NF \g_um_bfuplatin_bool {
1406       \um_map_chars_latin:nn {bfup,bfit} {#1}
1407       \um_set_mathalphabet_latin:Nnn \mathbf {up,it}{#1}
1408     }
1409   }
1410 }
1411 \cs_new:Nn \um_config_mathbfit_greek:n {
1412   \um_set_mathalphabet_greek:Nnn \mathbfit {up,it}{#1}
1413   \bool_if:NTF \g_um_bfliteral_bool {
1414     \um_map_chars_greek:nn {bfit}{#1}
1415     \um_set_mathalphabet_greek:Nnn \mathbf {it}{#1}
1416   }{
1417     \bool_if:NF \g_um_bfupGreek_bool {
1418       \um_map_chars_greek:nn {bfup,bfit}{#1}
1419       \um_set_mathalphabet_greek:Nnn \mathbf {up,it}{#1}
1420     }
1421   }
1422 }
1423 \cs_new:Nn \um_config_mathbfit_greek:n {
1424   \um_set_mathalphabet_greek:Nnn \mathbfit {up,it} {#1}
1425   \bool_if:NTF \g_um_bfliteral_bool {
1426     \um_map_chars_greek:nn {bfit} {#1}
1427     \um_set_mathalphabet_greek:Nnn \mathbf {it} {#1}

```

```

1428 }{
1429   \bool_if:NF \g_um_bfupgreek_bool {
1430     \um_map_chars_greek:nn {bfit,bfup} {#1}
1431     \um_set_mathalphabet_greek:Nnn \mathbf {up,it} {#1}
1432   }
1433 }
1434 }
1435 \cs_new:Nn \um_config_mathbfit_misc:n {
1436   \bool_if:NTF \g_um_literal_Nabla_bool {
1437     \um_map_single:nnn {Nabla}{bfit}{#1}
1438   }{
1439     \bool_if:NF \g_um_upNabla_bool {
1440       \um_map_single:nnn {Nabla}{bfup,bfit}{#1}
1441     }
1442   }
1443   \bool_if:NTF \g_um_literal_partial_bool {
1444     \um_map_single:nnn {partial}{bfit}{#1}
1445   }{
1446     \bool_if:NF \g_um_uppartial_bool {
1447       \um_map_single:nnn {partial}{bfup,bfit}{#1}
1448     }
1449   }
1450   \um_set_mathalphabet_pos:Nnnn \mathbfit {partial} {up,it}{#1}
1451   \um_set_mathalphabet_pos:Nnnn \mathbfit {Nabla} {up,it}{#1}
1452   \bool_if:NTF \g_um_literal_partial_bool {
1453     \um_set_mathalphabet_pos:Nnnn \mathbf {partial} {it}{#1}
1454   }{
1455     \bool_if:NF \g_um_uppartial_bool {
1456       \um_set_mathalphabet_pos:Nnnn \mathbf {partial} {up,it}{#1}
1457     }
1458   }
1459   \bool_if:NTF \g_um_literal_Nabla_bool {
1460     \um_set_mathalphabet_pos:Nnnn \mathbf {Nabla} {it}{#1}
1461   }{
1462     \bool_if:NF \g_um_upNabla_bool {
1463       \um_set_mathalphabet_pos:Nnnn \mathbf {Nabla} {up,it}{#1}
1464     }
1465   }
1466 }

```

9.1.10 Bold Upright: `\mathbfup`

```

1467 \cs_new:Nn \um_config_mathbfup_num:n {
1468   \um_set_mathalphabet_numbers:Nnn \mathbf {up}{#1}
1469   \um_set_mathalphabet_numbers:Nnn \mathbfup {up}{#1}
1470 }
1471 \cs_new:Nn \um_config_mathbfup_Latin:n {

```

```

1472 \bool_if:NT \g_um_bfupLatin_bool {
1473   \um_map_chars_Latin:nn {bfup,bfit} {#1}
1474 }
1475 \um_set_mathalphabet_Latin:Nnn \mathbfup {up,it}{#1}
1476 \bool_if:NTF \g_um_bfliteral_bool {
1477   \um_map_chars_Latin:nn {bfup} {#1}
1478   \um_set_mathalphabet_Latin:Nnn \mathbf {up}{#1}
1479 }{
1480   \bool_if:NT \g_um_bfupLatin_bool {
1481     \um_map_chars_Latin:nn {bfup,bfit} {#1}
1482     \um_set_mathalphabet_Latin:Nnn \mathbf {up,it}{#1}
1483   }
1484 }
1485 }
1486 \cs_new:Nn \um_config_mathbfup_latin:n {
1487   \bool_if:NT \g_um_bfuplatin_bool {
1488     \um_map_chars_latin:nn {bfup,bfit} {#1}
1489   }
1490   \um_set_mathalphabet_latin:Nnn \mathbfup {up,it}{#1}
1491   \bool_if:NTF \g_um_bfliteral_bool {
1492     \um_map_chars_latin:nn {bfup} {#1}
1493     \um_set_mathalphabet_latin:Nnn \mathbf {up}{#1}
1494   }{
1495     \bool_if:NT \g_um_bfuplatin_bool {
1496       \um_map_chars_latin:nn {bfup,bfit} {#1}
1497       \um_set_mathalphabet_latin:Nnn \mathbf {up,it}{#1}
1498     }
1499   }
1500 }
1501 \cs_new:Nn \um_config_mathbfup_greek:n {
1502   \um_set_mathalphabet_greek:Nnn \mathbfup {up,it}{#1}
1503   \bool_if:NTF \g_um_bfliteral_bool {
1504     \um_map_chars_greek:nn {bfup}{#1}
1505     \um_set_mathalphabet_greek:Nnn \mathbf {up}{#1}
1506   }{
1507     \bool_if:NT \g_um_bfupGreek_bool {
1508       \um_map_chars_greek:nn {bfup,bfit}{#1}
1509       \um_set_mathalphabet_greek:Nnn \mathbf {up,it}{#1}
1510     }
1511   }
1512 }
1513 \cs_new:Nn \um_config_mathbfup_greek:n {
1514   \um_set_mathalphabet_greek:Nnn \mathbfup {up,it} {#1}
1515   \bool_if:NTF \g_um_bfliteral_bool {
1516     \um_map_chars_greek:nn {bfup} {#1}
1517     \um_set_mathalphabet_greek:Nnn \mathbf {up} {#1}

```



```

1518 }{
1519   \bool_if:NT \g_um_bfupgreek_bool {
1520     \um_map_chars_greek:nn {bfup,bfit} {#1}
1521     \um_set_mathalphabet_greek:Nnn \mathbf {up,it} {#1}
1522   }
1523 }
1524 }
1525 \cs_new:Nn \um_config_mathbfup_misc:n {
1526   \bool_if:NTF \g_um_literal_Nabla_bool {
1527     \um_map_single:nnn {Nabla}{bfup}{#1}
1528   }{
1529     \bool_if:NT \g_um_upNabla_bool {
1530       \um_map_single:nnn {Nabla}{bfup,bfit}{#1}
1531     }
1532   }
1533   \bool_if:NTF \g_um_literal_partial_bool {
1534     \um_map_single:nnn {partial}{bfup}{#1}
1535   }{
1536     \bool_if:NT \g_um_uppartial_bool {
1537       \um_map_single:nnn {partial}{bfup,bfit}{#1}
1538     }
1539   }
1540   \um_set_mathalphabet_pos:Nnnn \mathbfup {partial} {up,it}{#1}
1541   \um_set_mathalphabet_pos:Nnnn \mathbfup {Nabla} {up,it}{#1}
1542   \um_set_mathalphabet_pos:Nnnn \mathbfup {digamma} {up}{#1}
1543   \um_set_mathalphabet_pos:Nnnn \mathbfup {Digamma} {up}{#1}
1544   \um_set_mathalphabet_pos:Nnnn \mathbf {digamma} {up}{#1}
1545   \um_set_mathalphabet_pos:Nnnn \mathbf {Digamma} {up}{#1}
1546   \bool_if:NTF \g_um_literal_partial_bool {
1547     \um_set_mathalphabet_pos:Nnnn \mathbf {partial} {up}{#1}
1548   }{
1549     \bool_if:NT \g_um_uppartial_bool {
1550       \um_set_mathalphabet_pos:Nnnn \mathbf {partial} {up,it}{#1}
1551     }
1552   }
1553   \bool_if:NTF \g_um_literal_Nabla_bool {
1554     \um_set_mathalphabet_pos:Nnnn \mathbf {Nabla} {up}{#1}
1555   }{
1556     \bool_if:NT \g_um_upNabla_bool {
1557       \um_set_mathalphabet_pos:Nnnn \mathbf {Nabla} {up,it}{#1}
1558     }
1559   }
1560 }

```

9.1.11 Bold fractur or fraktur or blackletter: `\mathbffrak`

```

1561 \cs_new:Nn \um_config_mathbffrak_Latin:n {

```

```

1562 \um_set_mathalphabet_Latin:Nnn \mathbffrak {up,it}{#1}
1563 }
1564 \cs_new:Nn \um_config_mathbffrak_latin:n {
1565   \um_set_mathalphabet_latin:Nnn \mathbffrak {up,it}{#1}
1566 }

```

9.1.12 Bold script or calligraphic: `\mathbfscr`

```

1567 \cs_new:Nn \um_config_mathbfscr_Latin:n {
1568   \um_set_mathalphabet_Latin:Nnn \mathbfscr {up,it}{#1}
1569 }
1570 \cs_new:Nn \um_config_mathbfscr_latin:n {
1571   \um_set_mathalphabet_latin:Nnn \mathbfscr {up,it}{#1}
1572 }

```

9.1.13 Bold upright sans serif: `\mathbfsfup`

```

1573 \cs_new:Nn \um_config_mathbfsfup_num:n {
1574   \um_set_mathalphabet_numbers:Nnn \mathbfsf {up}{#1}
1575   \um_set_mathalphabet_numbers:Nnn \mathbfsfup {up}{#1}
1576 }
1577 \cs_new:Nn \um_config_mathbfsfup_Latin:n {
1578   \bool_if:NTF \g_um_sfliteral_bool {
1579     \um_map_chars_Latin:nn {bfsfup} {#1}
1580     \um_set_mathalphabet_Latin:Nnn \mathbfsf {up}{#1}
1581   }{
1582     \bool_if:NT \g_um_upsans_bool {
1583       \um_map_chars_Latin:nn {bfsfup,bfsfit} {#1}
1584       \um_set_mathalphabet_Latin:Nnn \mathbfsf {up,it}{#1}
1585     }
1586   }
1587   \um_set_mathalphabet_Latin:Nnn \mathbfsfup {up,it}{#1}
1588 }
1589 \cs_new:Nn \um_config_mathbfsfup_latin:n {
1590   \bool_if:NTF \g_um_sfliteral_bool {
1591     \um_map_chars_latin:nn {bfsfup} {#1}
1592     \um_set_mathalphabet_latin:Nnn \mathbfsf {up}{#1}
1593   }{
1594     \bool_if:NT \g_um_upsans_bool {
1595       \um_map_chars_latin:nn {bfsfup,bfsfit} {#1}
1596       \um_set_mathalphabet_latin:Nnn \mathbfsf {up,it}{#1}
1597     }
1598   }
1599   \um_set_mathalphabet_latin:Nnn \mathbfsfup {up,it}{#1}
1600 }
1601 \cs_new:Nn \um_config_mathbfsfup_Greek:n {
1602   \bool_if:NTF \g_um_sfliteral_bool {
1603     \um_map_chars_Greek:nn {bfsfup}{#1}
1604     \um_set_mathalphabet_Greek:Nnn \mathbfsf {up}{#1}

```

```

1605 }{
1606   \bool_if:NT \g_um_upsans_bool {
1607     \um_map_chars_Greek:nn {bfsfup,bfsfit}{#1}
1608     \um_set_mathalphabet_Greek:Nnn \mathbfsf {up,it}{#1}
1609   }
1610 }
1611 \um_set_mathalphabet_Greek:Nnn \mathbfsfup {up,it}{#1}
1612 }
1613 \cs_new:Nn \um_config_mathbfsfup_greek:n {
1614   \bool_if:NTF \g_um_sfliteral_bool {
1615     \um_map_chars_greek:nn {bfsfup} {#1}
1616     \um_set_mathalphabet_greek:Nnn \mathbfsf {up} {#1}
1617   }{
1618     \bool_if:NT \g_um_upsans_bool {
1619       \um_map_chars_greek:nn {bfsfup,bfsfit} {#1}
1620       \um_set_mathalphabet_greek:Nnn \mathbfsf {up,it} {#1}
1621     }
1622   }
1623   \um_set_mathalphabet_greek:Nnn \mathbfsfup {up,it} {#1}
1624 }
1625 \cs_new:Nn \um_config_mathbfsfup_misc:n {
1626   \bool_if:NTF \g_um_literal_Nabla_bool {
1627     \um_map_single:nnn {Nabla}{bfsfup}{#1}
1628   }{
1629     \bool_if:NT \g_um_upNabla_bool {
1630       \um_map_single:nnn {Nabla}{bfsfup,bfsfit}{#1}
1631     }
1632   }
1633   \bool_if:NTF \g_um_literal_partial_bool {
1634     \um_map_single:nnn {partial}{bfsfup}{#1}
1635   }{
1636     \bool_if:NT \g_um_uppartial_bool {
1637       \um_map_single:nnn {partial}{bfsfup,bfsfit}{#1}
1638     }
1639   }
1640   \um_set_mathalphabet_pos:Nnnn \mathbfsfup {partial} {up,it}{#1}
1641   \um_set_mathalphabet_pos:Nnnn \mathbfsfup {Nabla} {up,it}{#1}
1642   \bool_if:NTF \g_um_literal_partial_bool {
1643     \um_set_mathalphabet_pos:Nnnn \mathbfsf {partial} {up}{#1}
1644   }{
1645     \bool_if:NT \g_um_uppartial_bool {
1646       \um_set_mathalphabet_pos:Nnnn \mathbfsf {partial} {up,it}{#1}
1647     }
1648   }
1649   \bool_if:NTF \g_um_literal_Nabla_bool {
1650     \um_set_mathalphabet_pos:Nnnn \mathbfsf {Nabla} {up}{#1}

```

```

1651 }{
1652   \bool_if:NT \g_um_upNabla_bool {
1653     \um_set_mathalphabet_pos:Nnnn \mathbfsf {Nabla} {up,it}{#1}
1654   }
1655 }
1656 }

```

9.1.14 Bold italic sans serif: \mathbfsfit

```

1657 \cs_new:Nn \um_config_mathbfsfit_Latin:n {
1658   \bool_if:NTF \g_um_sfliteral_bool {
1659     \um_map_chars_Latin:nn {bfsfit} {#1}
1660     \um_set_mathalphabet_Latin:Nnn \mathbfsf {it}{#1}
1661   }{
1662     \bool_if:NF \g_um_upsans_bool {
1663       \um_map_chars_Latin:nn {bfsfup,bfsfit} {#1}
1664       \um_set_mathalphabet_Latin:Nnn \mathbfsf {up,it}{#1}
1665     }
1666   }
1667   \um_set_mathalphabet_Latin:Nnn \mathbfsfit {up,it}{#1}
1668 }
1669 \cs_new:Nn \um_config_mathbfsfit_latin:n {
1670   \bool_if:NTF \g_um_sfliteral_bool {
1671     \um_map_chars_latin:nn {bfsfit} {#1}
1672     \um_set_mathalphabet_latin:Nnn \mathbfsf {it}{#1}
1673   }{
1674     \bool_if:NF \g_um_upsans_bool {
1675       \um_map_chars_latin:nn {bfsfup,bfsfit} {#1}
1676       \um_set_mathalphabet_latin:Nnn \mathbfsf {up,it}{#1}
1677     }
1678   }
1679   \um_set_mathalphabet_latin:Nnn \mathbfsfit {up,it}{#1}
1680 }
1681 \cs_new:Nn \um_config_mathbfsfit_Greek:n {
1682   \bool_if:NTF \g_um_sfliteral_bool {
1683     \um_map_chars_Greek:nn {bfsfit}{#1}
1684     \um_set_mathalphabet_Greek:Nnn \mathbfsf {it}{#1}
1685   }{
1686     \bool_if:NF \g_um_upsans_bool {
1687       \um_map_chars_Greek:nn {bfsfup,bfsfit}{#1}
1688       \um_set_mathalphabet_Greek:Nnn \mathbfsf {up,it}{#1}
1689     }
1690   }
1691   \um_set_mathalphabet_Greek:Nnn \mathbfsfit {up,it}{#1}
1692 }
1693 \cs_new:Nn \um_config_mathbfsfit_greek:n {
1694   \bool_if:NTF \g_um_sfliteral_bool {

```

```

1695 \um_map_chars_greek:nn {bfsfit} {#1}
1696 \um_set_mathalphabet_greek:Nnn \mathbfsf {it} {#1}
1697 }{
1698 \bool_if:NF \g_um_upsans_bool {
1699 \um_map_chars_greek:nn {bfsfup,bfsfit} {#1}
1700 \um_set_mathalphabet_greek:Nnn \mathbfsf {up,it} {#1}
1701 }
1702 }
1703 \um_set_mathalphabet_greek:Nnn \mathbfsfit {up,it} {#1}
1704 }
1705 \cs_new:Nn \um_config_mathbfsfit_misc:n {
1706 \bool_if:NTF \g_um_literal_Nabla_bool {
1707 \um_map_single:nnn {Nabla}{bfsfit}{#1}
1708 }{
1709 \bool_if:NF \g_um_upNabla_bool {
1710 \um_map_single:nnn {Nabla}{bfsfup,bfsfit}{#1}
1711 }
1712 }
1713 \bool_if:NTF \g_um_literal_partial_bool {
1714 \um_map_single:nnn {partial}{bfsfit}{#1}
1715 }{
1716 \bool_if:NF \g_um_uppartial_bool {
1717 \um_map_single:nnn {partial}{bfsfup,bfsfit}{#1}
1718 }
1719 }
1720 \um_set_mathalphabet_pos:Nnnn \mathbfsfit {partial} {up,it}{#1}
1721 \um_set_mathalphabet_pos:Nnnn \mathbfsfit {Nabla} {up,it}{#1}
1722 \bool_if:NTF \g_um_literal_partial_bool {
1723 \um_set_mathalphabet_pos:Nnnn \mathbfsf {partial} {it}{#1}
1724 }{
1725 \bool_if:NF \g_um_uppartial_bool {
1726 \um_set_mathalphabet_pos:Nnnn \mathbfsf {partial} {up,it}{#1}
1727 }
1728 }
1729 \bool_if:NTF \g_um_literal_Nabla_bool {
1730 \um_set_mathalphabet_pos:Nnnn \mathbfsf {Nabla} {it}{#1}
1731 }{
1732 \bool_if:NF \g_um_upNabla_bool {
1733 \um_set_mathalphabet_pos:Nnnn \mathbfsf {Nabla} {up,it}{#1}
1734 }
1735 }
1736 }

```

10 Definitions of the math symbols

Here we define every unicode math codepoint an equivalent macro name. The two are equivalent, in a `\let\xyz=^^^^1234` kind of way.

`\um@scancharlet` We need to do some trickery to transform the `\UnicodeMathSymbol` argument `\um@scanactivedef` "ABCDEF into the X_YTeX ‘caret input’ form `^^^^^abcdef`. It is *very important* that the argument has five characters. Otherwise we need to change the number of ^ chars.

To do this, turn ^ into a regular ‘other’ character and define the macro to perform the lowercasing and `\let`. `\scantokens` changes the carets back into their original meaning after the group has ended and ^’s catcode returns to normal.

```

1737 \begingroup
1738   \char_make_other:N \^
1739   \cs_gset:Npn \um@scancharlet#1="#2\@nil {
1740     \lowercase{
1741       \tl_rescan:nn {
1742         \char_make_other:N \{
1743         \char_make_other:N \}
1744         \char_make_other:N \&
1745         \char_make_other:N \%
1746         \char_make_other:N \$
1747       }{
1748         \global\let#1=^^^^^#2
1749     }
1750   }
1751 }

```

Making ^ the right catcode isn’t strictly necessary right now but it helps to future proof us with, e.g., `breqn`.

```

1752 \gdef\um@scanactivedef"#1\@nil#2{
1753   \lowercase{
1754     \tl_rescan:nn{
1755       \ExplSyntaxOn
1756       \char_make_math_superscript:N\^
1757     }{
1758       \global\def^^^^^#1{#2}
1759     }
1760   }
1761 }
1762 \endgroup

```

Now give `\UnicodeMathSymbol` a definition in terms of `\um@scancharlet` and we’re good to go. Make sure # is an ‘other’ so that we don’t get confused with `\mathoctothorpe`.

```

1763 \AtBeginDocument{

```

```

1764 \group_begin:
1765   \char_make_math_superscript:N\^
1766   \def\UnicodeMathSymbol#1#2#3#4{
1767     \bool_if:nF { \cs_if_eq_p:NN #3 \mathaccent ||
1768                 \cs_if_eq_p:NN #3 \mathopen  ||
1769                 \cs_if_eq_p:NN #3 \mathclose } {
1770       \um@scancharlet#2=#1\@nil\ignorespaces
1771     }
1772   }
1773   \char_make_other:N \#
1774   \@input{unicode-math-table.tex}
1775 \group_end:
1776 }

```

Fix `\backslash`, which is defined as the escape char character above:

```

1777 \group_begin:
1778   \lccode`\*=`\
1779   \char_make_escape:N \
1780   \char_make_other:N \
1781   |lowercase{
1782     |AtBeginDocument{
1783       |let|backslash=*
1784     }
1785   }
1786 |group_end:

```

Fix `\backslash`:

11 Epilogue

Lots of little things to tidy up.

11.0.15 Primes

We need a new ‘prime’ algorithm. Unicode math has four pre-drawn prime glyphs.

```

u+2032 prime (\prime):  $x'$ 
u+2033 double prime (\dprime):  $x''$ 
u+2034 triple prime (\trprime):  $x'''$ 
u+2057 quadruple prime (\qprime):  $x''''$ 

```

As you can see, they’re all drawn at the correct height without being superscripted. However, in a correctly behaving OpenType font, we also see different behaviour after the `ssty` feature is applied:

$x' \quad x'' \quad x''' \quad x''''$

The glyphs are now ‘full size’ so that when placed inside a superscript, their shape will match the originally sized ones. Many thanks to Ross Mills of Tiro Typeworks for originally pointing out this behaviour.

In regular L^AT_EX, primes can be entered with the straight quote character ', and multiple straight quotes chain together to produce multiple primes. Better results can be achieved in unicode-math by chaining multiple single primes into a pre-drawn multi-prime glyph; consider x''' vs. x''' .

For unicode maths, we wish to conserve this behaviour and augment it with the possibility of adding any combination of unicode prime or any of the n -prime characters. E.g., the user might copy-paste a double prime from another source and then later type another single prime after it; the output should be the triple prime.

Our algorithm is:

- Prime encountered; pcount=1.
- Scan ahead; if prime: pcount:=pcount+1; repeat.
- If not prime, stop scanning.
- If pcount=1, \prime, end.
- If pcount=2, check \dprime; if it exists, use it, end; if not, goto last step.
- Ditto pcount=3 & \trprime.
- Ditto pcount=4 & \qprime.
- If pcount>4 or the glyph doesn't exist, insert pcount \primes with \primekern between each.

```

1787 \muskip_new:N \g_um_primekern_muskip
1788 \muskip_gset:Nn \g_um_primekern_muskip { -\thinmuskip/2 }% arbitrary
1789 \num_new:N \l_um_primecount_num

1790 \cs_new:Nn \um_nprimes:Nn {
1791   ^{
1792     #1
1793     \prg_replicate:nn {#2-1} { \mskip \g_um_primekern_muskip #1 }
1794   }
1795 }
1796 \cs_new:Nn \um_nprimes_select:nn {
1797   \prg_case_int:nnn {#2}{
1798     {1} { ^{#1} }
1799     {2} {
1800       \um_glyph_if_exist:nTF {"2033} { ^{\um_prime_double_mchar} } {\um_nprimes:Nn #1 {#2}}
1801     }
1802     {3} {
1803       \um_glyph_if_exist:nTF {"2034} { ^{\um_prime_triple_mchar} } {\um_nprimes:Nn #1 {#2}}
1804     }
1805     {4} {
1806       \um_glyph_if_exist:nTF {"2057} { ^{\um_prime_quad_mchar} } {\um_nprimes:Nn #1 {#2}}

```



```

1807     }
1808   }{
1809     \um_nprimes:Nn #1 {#2}
1810   }
1811 }
1812 \cs_new:Nn \um_nbackprimes_select:nn {
1813   \prg_case_int:nnn {#2}{
1814     {1} { ^{#1} }
1815     {2} {
1816       \um_glyph_if_exist:nTF {"2033} { ^{\um_backprime_double_mchar} } {\um_nprimes:Nn #1 {#2}}
1817     }
1818     {3} {
1819       \um_glyph_if_exist:nTF {"2034} { ^{\um_backprime_triple_mchar} } {\um_nprimes:Nn #1 {#2}}
1820     }
1821   }{
1822     \um_nprimes:Nn #1 {#2}
1823   }
1824 }

```

Scanning is annoying because I’m too lazy to do it for the general case.

```

1825 \cs_new:Nn \um_scan_prime: {
1826   \num_zero:N \l_um_primecount_num
1827   \um_scanprime_collect:N \um_prime_single_mchar
1828 }
1829 \cs_new:Nn \um_scan_dprime: {
1830   \num_set:Nn \l_um_primecount_num {1}
1831   \um_scanprime_collect:N \um_prime_single_mchar
1832 }
1833 \cs_new:Nn \um_scan_trprime: {
1834   \num_set:Nn \l_um_primecount_num {2}
1835   \um_scanprime_collect:N \um_prime_single_mchar
1836 }
1837 \cs_new:Nn \um_scan_qprime: {
1838   \num_set:Nn \l_um_primecount_num {3}
1839   \um_scanprime_collect:N \um_prime_single_mchar
1840 }
1841 \cs_new:Nn \um_scanprime_collect:N {
1842   \num_incr:N \l_um_primecount_num
1843   \peek_meaning_remove:NTF ' {
1844     \um_scanprime_collect:N #1
1845   }{
1846     \peek_meaning_remove:NTF \um_scan_prime: {
1847       \um_scanprime_collect:N #1
1848     }{
1849       \peek_meaning_remove:NTF ^^^2032 {
1850         \um_scanprime_collect:N #1
1851       }{

```

```

1852     \peek_meaning_remove:NTF \um_scan_dprime: {
1853         \num_incr:N \l_um_primecount_num
1854         \um_scanprime_collect:N #1
1855     }{
1856         \peek_meaning_remove:NTF ^^^^2033 {
1857             \num_incr:N \l_um_primecount_num
1858             \um_scanprime_collect:N #1
1859         }{
1860             \peek_meaning_remove:NTF \um_scan_trprime: {
1861                 \num_add:Nn \l_um_primecount_num {2}
1862                 \um_scanprime_collect:N #1
1863             }{
1864                 \peek_meaning_remove:NTF ^^^^2034 {
1865                     \num_add:Nn \l_um_primecount_num {2}
1866                     \um_scanprime_collect:N #1
1867                 }{
1868                     \peek_meaning_remove:NTF \um_scan_qprime: {
1869                         \num_add:Nn \l_um_primecount_num {3}
1870                         \um_scanprime_collect:N #1
1871                     }{
1872                         \peek_meaning_remove:NTF ^^^^2057 {
1873                             \num_add:Nn \l_um_primecount_num {3}
1874                             \um_scanprime_collect:N #1
1875                         }{
1876                             \um_nprimes_select:nn {#1} {\l_um_primecount_num}
1877                         }
1878                     }
1879                 }
1880             }
1881         }
1882     }
1883 }
1884 }
1885 }
1886 }
1887 \cs_new:Nn \um_scan_backprime: {
1888     \num_zero:N \l_um_primecount_num
1889     \um_scanbackprime_collect:N \um_backprime_single_mchar
1890 }
1891 \cs_new:Nn \um_scan_backdprime: {
1892     \num_set:Nn \l_um_primecount_num {1}
1893     \um_scanbackprime_collect:N \um_backprime_single_mchar
1894 }
1895 \cs_new:Nn \um_scan_backtrprime: {
1896     \num_set:Nn \l_um_primecount_num {2}
1897     \um_scanbackprime_collect:N \um_backprime_single_mchar

```

```

1898 }
1899 \cs_new:Nn \um_scanbackprime_collect:N {
1900   \num_incr:N \l_um_primecount_num
1901   \peek_meaning_remove:NTF ` {
1902     \um_scanbackprime_collect:N #1
1903   }{
1904     \peek_meaning_remove:NTF \um_scan_backprime: {
1905       \um_scanbackprime_collect:N #1
1906     }{
1907       \peek_meaning_remove:NTF ^^^^2035 {
1908         \um_scanbackprime_collect:N #1
1909       }{
1910         \peek_meaning_remove:NTF \um_scan_backdprime: {
1911           \num_incr:N \l_um_primecount_num
1912           \um_scanbackprime_collect:N #1
1913         }{
1914           \peek_meaning_remove:NTF ^^^^2036 {
1915             \num_incr:N \l_um_primecount_num
1916             \um_scanbackprime_collect:N #1
1917           }{
1918             \peek_meaning_remove:NTF \um_scan_backtrprime: {
1919               \num_add:Nn \l_um_primecount_num {2}
1920               \um_scanbackprime_collect:N #1
1921             }{
1922               \peek_meaning_remove:NTF ^^^^2037 {
1923                 \num_add:Nn \l_um_primecount_num {2}
1924                 \um_scanbackprime_collect:N #1
1925               }{
1926                 \um_nbackprimes_select:nn {#1} {\l_um_primecount_num}
1927               }
1928             }
1929           }
1930         }
1931       }
1932     }
1933   }
1934 }

1935 \AtBeginDocument {
1936   \cs_set_eq:NN \prime      \um_scan_prime:
1937   \cs_set_eq:NN \drime      \um_scan_dprime:
1938   \cs_set_eq:NN \trprime    \um_scan_trprime:
1939   \cs_set_eq:NN \qprime     \um_scan_qprime:
1940   \cs_set_eq:NN \backprime   \um_scan_backprime:
1941   \cs_set_eq:NN \backdprime  \um_scan_backdprime:
1942   \cs_set_eq:NN \backtrprime \um_scan_backtrprime:
1943 }

```

```

1944 \group_begin:
1945   \char_make_active:N \ '
1946   \char_make_active:N \ `
1947   \char_make_active:n {"2032}
1948   \char_make_active:n {"2033}
1949   \char_make_active:n {"2034}
1950   \char_make_active:n {"2057}
1951   \char_make_active:n {"2035}
1952   \char_make_active:n {"2036}
1953   \char_make_active:n {"2037}
1954   \AtBeginDocument{
1955     \cs_set_eq:NN ' \um_scan_prime:
1956     \cs_set_eq:NN ^^^^2032 \um_scan_prime:
1957     \cs_set_eq:NN ^^^^2033 \um_scan_dprime:
1958     \cs_set_eq:NN ^^^^2034 \um_scan_trprime:
1959     \cs_set_eq:NN ^^^^2057 \um_scan_qprime:
1960     \cs_set_eq:NN ` \um_scan_backprime:
1961     \cs_set_eq:NN ^^^^2035 \um_scan_backprime:
1962     \cs_set_eq:NN ^^^^2036 \um_scan_backdprime:
1963     \cs_set_eq:NN ^^^^2037 \um_scan_backtrprime:
1964   }
1965 \group_end:

```

11.0.16 Unicode radicals

`\r@@t` #1 : A mathstyle (for `\mathpalette`)
 #2 : Leading superscript for the sqrt sign
 A re-implementation of L^AT_EX's hard-coded n-root sign using the appropriate `\fontdimens`.

```

1966 \cs_set_nopar:Npn \r@@t #1#2 {
1967   \setbox\z@\hbox{$\mathstyle #1\sqrtsign{#2}$}
1968   \um_mathstyle_scale:Nnn{#1}{\kern}{\fontdimen63\l_um_font}
1969   \raise \dimexpr(
1970     \um_fontdimen_to_percent:nn{65}{\l_um_font}\ht\z@-
1971     \um_fontdimen_to_percent:nn{65}{\l_um_font}\dp\z@
1972   )\relax
1973   \copy \rootbox
1974   \um_mathstyle_scale:Nnn{#1}{\kern}{\fontdimen64\l_um_font}
1975   \box \z@
1976 }

```

`\um_fontdimen_to_percent:nn` #1 : Font dimen number
 #2 : Font 'variable'
`\fontdimens` 10, 11, and 65 aren't actually dimensions, they're percentage values given in units of sp. This macro takes a font dimension number and outputs the decimal value of the associated parameter.

```

1977 \cs_new:Nn \um_fontdimen_to_percent:nn {
1978   0.\strip@pt\dimexpr\fontdimen#1#2 *65536\relax
1979 }

```

`\um_mathstyle_scale:Nnn` #1 : A math style (`\scriptstyle`, say)
 #2 : Macro that takes a non-delimited length argument (like `\kern`)
 #3 : Length control sequence to be scaled according to the math style
 This macro is used to scale the lengths reported by `\fontdimen` according to the scale factor for script- and scriptscript-size objects.

```

1980 \cs_new:Nn \um_mathstyle_scale:Nnn {
1981   \ifx#1\scriptstyle
1982     #2\um_fontdimen_to_percent:nn{10}\l_um_font#3
1983   \else
1984     \ifx#1\scriptscriptstyle
1985       #2\um_fontdimen_to_percent:nn{11}\l_um_font#3
1986     \else
1987       #2#3
1988     \fi
1989   \fi
1990 }

```

11.0.17 Unicode sub- and super-scripts

The idea here is to enter a scanning state after a superscript or subscript is encountered. If subsequent superscripts or subscripts (resp.) are found, they are lumped together. Each sub/super has a corresponding regular size glyph which is used by \XeTeX to typeset the results; this means that the actual subscript/superscript glyphs are never seen in the output document — they are only used as input characters.

Open question: should the superscript-like ‘modifiers’ (U+1D2C modifier capital letter a and on) be included here?

First, the setup of each mathactive char:

```

1991 \prop_new:N \g_um_supers_prop
1992 \prop_new:N \g_um_subs_prop
1993
1994 \group_begin:
1995
1996 % Populate a property list with superscript characters; their mean-
1997 % ing as their key,
1998 % for reasons that will become apparent soon, and their replace-
1999 % ment as each key's value.
2000 % Then make the superscript active and bind it to the scanning function.
2001 %
2002 % \cs{scantokens} makes this process much simpler since we can acti-
2003 % vate the char

```

```

2001 % and assign its meaning in one step.
2002 \cs_set:Nn \um_setup_active_superscript:nn {
2003   \prop_gput:Nxn \g_um_supers_prop   {\meaning #1} {#2}
2004   \char_make_active:N #1
2005   \char_gmake_mathactive:N #1
2006   \scantokens{
2007     \cs_gset:Npn #1 {
2008       \tl_set:Nn \l_um_ss_chain_tl {#2}
2009       \cs_set_eq:NN \um_sub_or_super:n \sp
2010       \tl_set:Nn \l_um_tmpa_tl {supers}
2011       \um_scan_sscript:
2012     }
2013   }
2014 }
2015
2016 \um_setup_active_superscript:nn {^^^2070} {0}
2017 \um_setup_active_superscript:nn {^^^00b9} {1}
2018 \um_setup_active_superscript:nn {^^^00b2} {2}
2019 \um_setup_active_superscript:nn {^^^00b3} {3}
2020 \um_setup_active_superscript:nn {^^^2074} {4}
2021 \um_setup_active_superscript:nn {^^^2075} {5}
2022 \um_setup_active_superscript:nn {^^^2076} {6}
2023 \um_setup_active_superscript:nn {^^^2077} {7}
2024 \um_setup_active_superscript:nn {^^^2078} {8}
2025 \um_setup_active_superscript:nn {^^^2079} {9}
2026 \um_setup_active_superscript:nn {^^^207a} {+}
2027 \um_setup_active_superscript:nn {^^^207b} {-}
2028 \um_setup_active_superscript:nn {^^^207c} {=}
2029 \um_setup_active_superscript:nn {^^^207d} {(}
2030 \um_setup_active_superscript:nn {^^^207e} {)}
2031 \um_setup_active_superscript:nn {^^^2071} {i}
2032 \um_setup_active_superscript:nn {^^^207f} {n}
2033
2034 % Ditto above.
2035 \cs_set:Nn \um_setup_active_subscript:nn {
2036   \prop_gput:Nxn \g_um_subs_prop   {\meaning #1} {#2}
2037   \char_make_active:N #1
2038   \char_gmake_mathactive:N #1
2039   \scantokens{
2040     \cs_gset:Npn #1 {
2041       \tl_set:Nn \l_um_ss_chain_tl {#2}
2042       \cs_set_eq:NN \um_sub_or_super:n \sb
2043       \tl_set:Nn \l_um_tmpa_tl {subs}
2044       \um_scan_sscript:
2045     }
2046   }

```

```

2047 }
2048
2049 \um_setup_active_subscript:nn {^^^2080} {0}
2050 \um_setup_active_subscript:nn {^^^2081} {1}
2051 \um_setup_active_subscript:nn {^^^2082} {2}
2052 \um_setup_active_subscript:nn {^^^2083} {3}
2053 \um_setup_active_subscript:nn {^^^2084} {4}
2054 \um_setup_active_subscript:nn {^^^2085} {5}
2055 \um_setup_active_subscript:nn {^^^2086} {6}
2056 \um_setup_active_subscript:nn {^^^2087} {7}
2057 \um_setup_active_subscript:nn {^^^2088} {8}
2058 \um_setup_active_subscript:nn {^^^2089} {9}
2059 \um_setup_active_subscript:nn {^^^208a} {+}
2060 \um_setup_active_subscript:nn {^^^208b} {-}
2061 \um_setup_active_subscript:nn {^^^208c} {=}
2062 \um_setup_active_subscript:nn {^^^208d} {(}
2063 \um_setup_active_subscript:nn {^^^208e} {)}
2064 \um_setup_active_subscript:nn {^^^2090} {a}
2065 \um_setup_active_subscript:nn {^^^2091} {e}
2066 \um_setup_active_subscript:nn {^^^1d62} {i}
2067 \um_setup_active_subscript:nn {^^^2092} {o}
2068 \um_setup_active_subscript:nn {^^^1d63} {r}
2069 \um_setup_active_subscript:nn {^^^1d64} {u}
2070 \um_setup_active_subscript:nn {^^^1d65} {v}
2071 \um_setup_active_subscript:nn {^^^2093} {x}
2072 \um_setup_active_subscript:nn {^^^1d66} {\beta}
2073 \um_setup_active_subscript:nn {^^^1d67} {\gamma}
2074 \um_setup_active_subscript:nn {^^^1d68} {\rho}
2075 \um_setup_active_subscript:nn {^^^1d69} {\phi}
2076 \um_setup_active_subscript:nn {^^^1d6a} {\chi}
2077
2078 \group_end:
2079
2080 % The scanning command, evident in its purpose:
2081 \cs_new:Nn \um_scan_sscript: {
2082   \um_scan_sscript:TF {
2083     \um_scan_sscript:
2084   }{
2085     \um_sub_or_super:n {\l_um_ss_chain_tl}
2086   }
2087 }
2088
2089 % The main theme here is stolen from the source to the vari-
2090 % ous \cs{peek_} functions.
2091 % Consider this function as simply boilerplate:
2092 \cs_new:Nn \um_scan_sscript:TF {

```

```

2092 \tl_set:Nx \l_peek_true_aux_tl { \exp_not:n{ #1 } }
2093 \tl_set_eq:NN \l_peek_true_tl \c_peek_true_remove_next_tl
2094 \tl_set:Nx \l_peek_false_tl {\exp_not:n{\group_align_safe_end: #2}}
2095 \group_align_safe_begin:
2096   \peek_after:NN \um_peek_execute_branches_ss:
2097 }
2098
2099 % We do not skip spaces when scanning ahead, and we explicitly wish to
2100 % bail out on encountering a space or a brace.
2101 \cs_new:Npn \um_peek_execute_branches_ss: {
2102   \bool_if:nTF {
2103     \token_if_eq_catcode_p:NN \l_peek_token \c_group_begin_token ||
2104     \token_if_eq_catcode_p:NN \l_peek_token \c_group_end_token ||
2105     \token_if_eq_meaning_p:NN \l_peek_token \c_space_token
2106   }
2107   { \l_peek_false_tl }
2108   { \um_peek_execute_branches_ss_aux: }
2109 }
2110
2111 % This is the actual comparison code.
2112 % Because the peeking has already tokenised the next token,
2113 % it's too late to extract its charcode directly. Instead,
2114 % we look at its meaning, which remains a `character' even
2115 % though it is itself math-active. If the character is ever
2116 % made fully active, this will break our assumptions!
2117 %
2118 % If the char's meaning exists as a property list key, we
2119 % build up a chain of sub-/superscripts and iterate. (If not, exit and
2120 % typeset what we've already collected.)
2121 \cs_new:Nn \um_peek_execute_branches_ss_aux: {
2122   \prop_if_in:cxTF
2123     {g_um_\l_um_tmpa_tl _prop}
2124     {\meaning\l_peek_token}
2125   {
2126     \prop_get:cxN
2127       {g_um_\l_um_tmpa_tl _prop}
2128       {\meaning\l_peek_token}
2129     \l_um_tmpb_tl
2130     \tl_put_right:NV \l_um_ss_chain_tl \l_um_tmpb_tl
2131     \l_peek_true_tl
2132   }
2133   {\l_peek_false_tl}
2134 }

```


11.0.18 Active fractions

Active fractions can be setup independently of any maths font definition; all it requires is a mapping from the unicode input chars to the relevant \LaTeX fraction declaration.

```
2135 \cs_new:Nn \um_setup_active_frac: {
2136   \group_begin:
2137   \um_define_active_frac:Nw ^^^^2152 1/{10}
2138   \um_define_active_frac:Nw ^^^^2151 1/9
2139   \um_define_active_frac:Nw ^^^^215b 1/8
2140   \um_define_active_frac:Nw ^^^^2150 1/7
2141   \um_define_active_frac:Nw ^^^^2159 1/6
2142   \um_define_active_frac:Nw ^^^^2155 1/5
2143   \um_define_active_frac:Nw ^^^^00bc 1/4
2144   \um_define_active_frac:Nw ^^^^2153 1/3
2145   \um_define_active_frac:Nw ^^^^215c 3/8
2146   \um_define_active_frac:Nw ^^^^2156 2/5
2147   \um_define_active_frac:Nw ^^^^00bd 1/2
2148   \um_define_active_frac:Nw ^^^^2157 3/5
2149   \um_define_active_frac:Nw ^^^^215d 5/8
2150   \um_define_active_frac:Nw ^^^^2154 2/3
2151   \um_define_active_frac:Nw ^^^^00be 3/4
2152   \um_define_active_frac:Nw ^^^^2158 4/5
2153   \um_define_active_frac:Nw ^^^^215a 5/6
2154   \um_define_active_frac:Nw ^^^^215e 7/8
2155   \group_end:
2156 }
2157 \cs_new:Npn \um_define_active_frac:Nw #1 #2/#3 {
2158   \char_make_active:n {\`#1}
2159   \char_gmake_mathactive:N #1
2160   \tl_rescan:nn {
2161     \ExplSyntaxOn
2162   }{
2163     \cs_gset:Npx #1 {
2164       \bool_if:NTF \l_um_smallfrac_bool {\exp_not:N\tfrac} {\exp_not:N\frac}
2165       {#2} {#3}
2166     }
2167   }
2168 }
```

11.0.19 Synonyms and all the rest

We need to change \LaTeX 's idea of the font used to typeset things like `\sin` and `\cos`:

```
2169 \def\operator@font{\um_setup_mathup:}
```

```

2170 \def\to{\rightarrow}
2171 \def\overrightarrow{\vec}
2172 \def\le{\leq}
2173 \def\ge{\geq}
2174 \def\neq{\neq}
2175 \def\triangle{\mathord{\bigtriangleup}}
2176 \def\bigcirc{\mdlgwhtcircle}
2177 \def\circ{\vysmwhtcircle}
2178 \def\bullet{\smblkcircle}
2179 \def\mathyen{\yen}
2180 \def\mathsterling{\sterling}

```

`\colon` Define `\colon` as a mathpunct ‘:’. This is wrong: it should be `u+003A` colon instead! We hope no-one will notice.

```

2181 \@ifpackageloaded{amsmath}{
2182   % define their own colon, perhaps I should just steal it. (It does look much bet-
2183   % ter.)
2184   }{
2185     \cs_set_protected:Npn \colon {
2186       \bool_if:NTF \g_um_literal_colon_bool { : } { \mathpunct{:} }
2187     }
2188   }

```

`\mathcal`

```

2188 \def\mathcal{\mathscr}

```

`\mathrm`

```

2189 \def\mathrm{\mathup}
2190 \let\mathfence\mathord

```

`\digamma` I might end up just changing these in the table.

```

\Digamma 2191 \def\digamma{\updigamma}
2192 \def\Digamma{\upDigamma}

```

11.0.20 Compatibility

`\um_patch_pkg:nn` #1 : package
#2 : code

If `<package>` is loaded either already or later in the preamble, `<code>` is executed (after the package is loaded in the latter case).

```

2193 \cs_new:Nn \um_patch_pkg:nn {
2194   \@ifpackageloaded {#1} {
2195     #2
2196   }{
2197     \um_after_pkg:nn {#1} {#2}
2198   }
2199 }

```

url Simply need to get url in a state such that when it switches to math mode and enters ASCII characters, the maths setup (i.e., unicode-math) doesn't remap the symbols into Plane 1. Which is, of course, what `\mathup` is doing.

This is the same as writing, e.g., `\def\UrlFont{\ttfamily\um_setup_mathup:}` but activates automatically so old documents that might change the `\url` font still work correctly.

```
2200 \um_patch_pkg:n {url} {
2201   \tl_put_left:Nn \Url@FormatString { \um_setup_mathup: }
2202   \tl_put_right:Nn \UrlSpecials {
2203     \do\`{\mathchar`\` }
2204     \do\'\{\mathchar`\' }
2205     \do\$\{\mathchar`\$ }
2206     \do\&\{\mathchar`\& }
2207   }
2208 }
```

amsmath Since the mathcode of `\-` is greater than eight bits, this piece of `\AtBeginDocument` code from `amsmath` dies if we try and set the maths font in the preamble:

```
2209 \um_patch_pkg:n {amsmath} {
2210   \tl_remove_in:Nn \@begindocumenthook {
2211     \mathchardef\std@minus\mathcode`\-\relax
2212     \mathchardef\std@equal\mathcode`\=\relax
2213   }
2214   \def\std@minus{\XeTeXmathcharnum\XeTeXmathcodenum`\-\relax}
2215   \def\std@equal{\XeTeXmathcharnum\XeTeXmathcodenum`\=\relax}
2216   \def\@cdots{\mathinner{\cdots}}
2217   \cs_set_eq:NN \dotsb@ \cdots
2218 }
```

amsopn This code is to improve the output of alphabetic symbols in text of operator names (`\sin`, `\cos`, etc.). Just comment out the offending lines for now:

```
2219 \um_patch_pkg:n {amsopn} {
2220   \cs_set:Npn \newmcodes@ {
2221     \mathcode`\'39\scan_stop:
2222     \mathcode`\*42\scan_stop:
2223     \mathcode`\."613A\scan_stop:
2224     %% \ifnum\mathcode`\-=45 \else
2225     %%   \mathchardef\std@minus\mathcode`\-\relax
2226     %% \fi
2227     \mathcode`\-45\scan_stop:
2228     \mathcode`\ /47\scan_stop:
2229     \mathcode`\:"603A\scan_stop:
2230   }
2231 }
```

Symbols `\mathinner` items:

```
2232 \cs_set:Npn \mathellipsis {\mathinner{\unicodeellipsis}}
2233 \cs_set:Npn \cdots {\mathinner{\unicodcdots}}
```

Accents

```
2234 \AtBeginDocument{
2235   \def\widehat{\hat}
2236   \def\widetilde{\tilde}
2237 }
```

beamer

```
2238 \@ifclassloaded{beamer}{
2239   \ifbeamer@suppressreplacements\else
2240     \PackageWarningNoLine{unicode-math}{
2241       Disabling~ beamer's~ math~ setup.^{^}
2242       Please~ load~ beamer~ with~ the~ [professionalfonts]~ class~ option
2243     }
2244     \beamer@suppressreplacementstrue
2245   \fi
2246 }{}
    The end.
2247 \ExplSyntaxOff
```

12 stix table data extraction

The source for the \TeX names for the very large number of mathematical glyphs are provided via Barbara Beeton's table file for the `stix` project (ams.org/STIX). A version is located at <http://www.ams.org/STIX/bnb/stix-tbl.asc> but check <http://www.ams.org/STIX/> for more up-to-date info.

This table is converted into a form suitable for reading by \XeTeX , and then hand-edited by the author; the result is `unicode-math-table.tex`.

A single file is produced containing all (more than 3298) symbols. Future optimisations might include generating various (possibly overlapping) subsets so not all definitions must be read just to redefine a small range of symbols. Performance for now seems to be acceptable without such measures.

```
2248 #!/bin/sh
2249
2250 cat stix-tbl.txt |
2251 awk '
```

If the USV isn't repeated (TODO: check this is valid!) and the entry isn't one of the weird ones in the big block at the end of the `stix` table (TODO: check that out!)...

```
2252 {if (usv != substr($0,2,5) && substr($0,2,1) != " ")
2253     {usv = substr($0,2,5);
2254     texname = substr($0,84,25);
2255     class = substr($0,57,1);
2256     description = tolower(substr($0,233,350));
```

If the USV has a macro name, which isn't `\text...`, and isn't a single character macro (e.g., `\#`, `\S`, ...), and has a class, and it isn't reserved (*i.e.*, doubled up with a previously assigned glyph):

```

2257     if (texname ~ /[\\]/ &&
2258         substr(texname,0,5) != "\\text" &&
2259         substr(texname,0,4) != "\\ipa" &&
2260         substr(texname,0,5) != "\\tone" &&
2261         substr(texname,3,1) != " " &&
2262         class != " " &&
2263         description !~ /<reserved>/ )

```

Print the actual entry corresponding to the unicode character:

```

2264     print "\\UnicodeMathSymbol{"\" \" \
2265         usv "{" \" \
2266         texname "{" \" \
2267         class "{" \" \
2268         description "%";
2269   } }' - |
```

Now replace the STIX class abbreviations with their T_EX macro names.

```
2270 sed -e ' s/{N}/{\\mathord}/ ' \
```

A ‘fence’ defined by the `stix` table is something like `\vert`; in \LaTeX this is just a `\mathord` that will grow with the magic of `\XeTeXmathchardef`.

```

2271 -e ' s/{F}/{\\mathord}/ ' \
2272 -e ' s/{A}/{\\mathalpha}/ ' \
2273 -e ' s/{D}/{\\mathaccent}/ ' \
2274 -e ' s/{P}/{\\mathpunct}/ ' \
2275 -e ' s/{B}/{\\mathbin}/ ' \
2276 -e ' s/{R}/{\\mathrel}/ ' \
2277 -e ' s/{L}/{\\mathop}/ ' \
2278 -e ' s/{O}/{\\mathopen}/ ' \
2279 -e ' s/{C}/{\\mathclose}/ ' \

```

Fixing up a couple of things in the STIX table.

```
2280 -e ' s/\^/\\string^/ ' > unicode-math.tex
```

A Documenting maths support in the NFSS

In the following, $\langle NFSS\ decl. \rangle$ stands for something like $\{T1\}\{1mr\}\{m\}\{n\}$.

Maths symbol fonts Fonts for symbols: α , \leq , \rightarrow

`\DeclareSymbolFont{<name>}{NFSS decl.}`

Declares a named maths font such as operators from which symbols are defined with `\DeclareMathSymbol`.

Maths alphabet fonts Fonts for $ABC-xyz$, $\mathfrak{ABC}-\mathcal{XYZ}$, etc.

`\DeclareMathAlphabet{<cmd>}{NFSS decl.}`

For commands such as `\mathbf`, accessed through maths mode that are unaffected by the current text font, and which are used for alphabetic symbols in the ASCII range.

`\DeclareSymbolFontAlphabet{<cmd>}{<name>}`

Alternative (and optimisation) for `\DeclareMathAlphabet` if a single font is being used for both alphabetic characters (as above) and symbols.

Maths ‘versions’ Different maths weights can be defined with the following, switched in text with the `\mathversion{<maths version>}` command.

`\SetSymbolFont{<name>}{<maths version>}{NFSS decl.}`

`\SetMathAlphabet{<cmd>}{<maths version>}{NFSS decl.}`

Maths symbols Symbol definitions in maths for both characters (=) and macros (`\eqdef`): `\DeclareMathSymbol{<symbol>}{<type>}{<named font>}{<slot>}` This is the macro that actually defines which font each symbol comes from and how they behave.

Delimiters and radicals use wrappers around T_EX’s `\delimiter`/`\radical` primitives, which are re-designed in X_YT_EX. The syntax used in L^AT_EX’s NFSS is therefore not so relevant here.

Delimiters A special class of maths symbol which enlarge themselves in certain contexts.

`\DeclareMathDelimiter{<symbol>}{<type>}{<sym.font>}{<slot>}{<sym.font>}{<slot>}`

Radicals Similar to delimiters (`\DeclareMathRadical` takes the same syntax) but behave ‘weirdly’. `\sqrt` might very well be the only one.

In those cases, glyph slots in *two* symbol fonts are required; one for the small (‘regular’) case, the other for situations when the glyph is larger. This is not the case in X_YT_EX.

Accents are not included yet.

Summary For symbols, something like:

```
\def\DeclareMathSymbol#1#2#3#4{
  \global\mathchardef#1"\mathchar@type#2
  \expandafter\hexnumber@\csname sym#2\endcsname
  {\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}}
```

For characters, something like:

```
\def\DeclareMathSymbol#1#2#3#4{
  \global\mathcode`#1"\mathchar@type#2
  \expandafter\hexnumber@\csname sym#2\endcsname
  {\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}}
```

B X_YTeX math font dimensions

These are the extended `\fontdimen`s available for suitable fonts in X_YTeX. Note that LuaTeX takes an alternative route, and this package will eventually provide a wrapper interface to the two (I hope).

<code>\fontdimen</code>	Dimension name	Description
10	<code>SCRIPTPERCENTSCALEDOWN</code>	Percentage of scaling down for script level 1. Suggested value: 80%.
11	<code>SCRIPTSCRIPTPERCENTSCALEDOWN</code>	Percentage of scaling down for script level 2 (ScriptScript). Suggested value: 60%.
12	<code>DELIMITEDSUBFORMULAMINHEIGHT</code>	Minimum height required for a delimited expression to be treated as a subformula. Suggested value: normal line height \times 1.5.
13	<code>DISPLAYOPERATORMINHEIGHT</code>	Minimum height of n-ary operators (such as integral and summation) for formulas in display mode.
14	<code>MATHLEADING</code>	White space to be left between math formulas to ensure proper line spacing. For example, for applications that treat line gap as a part of line ascender, formulas with ink going above (<code>os2.sTypoAscender</code> + <code>os2.sTypoLineGap</code> – <code>MathLeading</code>) or with ink going below <code>os2.sTypoDescender</code> will result in increasing line height.
15	<code>AXISHEIGHT</code>	Axis height of the font.

\fontdimen	Dimension name	Description
16	ACCENTBASEHEIGHT	Maximum (ink) height of accent base that does not require raising the accents. Suggested: x-height of the font (os2.sxHeight) plus any possible overshots.
17	FLATTENEDACCENTBASE-HEIGHT	Maximum (ink) height of accent base that does not require flattening the accents. Suggested: cap height of the font (os2.sCapHeight).
18	SUBSCRIPTSHIFTDOWN	The standard shift down applied to subscript elements. Positive for moving in the downward direction. Suggested: os2.ySubscriptYOffset.
19	SUBSCRIPTTOPMAX	Maximum allowed height of the (ink) top of subscripts that does not require moving subscripts further down. Suggested: $\frac{1}{5}$ x-height.
20	SUBSCRIPTBASELINEDROPMIN	Minimum allowed drop of the baseline of subscripts relative to the (ink) bottom of the base. Checked for bases that are treated as a box or extended shape. Positive for subscript baseline dropped below the base bottom.
21	SUPERSCRIPSHIFTUP	Standard shift up applied to superscript elements. Suggested: os2.ySuperscriptYOffset.
22	SUPERSCRIPSHIFTUPCRAMPED	Standard shift of superscripts relative to the base, in cramped style.
23	SUPERSCRIPBOTTOMMIN	Minimum allowed height of the (ink) bottom of superscripts that does not require moving subscripts further up. Suggested: $\frac{1}{4}$ x-height.
24	SUPERSCRIPBASELINEDROP-MAX	Maximum allowed drop of the baseline of superscripts relative to the (ink) top of the base. Checked for bases that are treated as a box or extended shape. Positive for superscript baseline below the base top.
25	SUBSUPERSCRIPGAPMIN	Minimum gap between the superscript and subscript ink. Suggested: 4×default rule thickness.

\fontdimen	Dimension name	Description
26	SUPERSCRIPBTOTTOMMAX- WITHSUBSCRIPT	The maximum level to which the (ink) bottom of superscript can be pushed to increase the gap between superscript and subscript, before subscript starts being moved down. Suggested: $\frac{1}{5}$ x-height.
27	SPACEAFTERSRIPT	Extra white space to be added after each subscript and superscript. Suggested: 0.5pt for a 12 pt font.
28	UPPERLIMITGAPMIN	Minimum gap between the (ink) bottom of the upper limit, and the (ink) top of the base operator.
29	UPPERLIMITBASELINERISEMIN	Minimum distance between baseline of upper limit and (ink) top of the base operator.
30	LOWERLIMITGAPMIN	Minimum gap between (ink) top of the lower limit, and (ink) bottom of the base operator.
31	LOWERLIMITBASELINEDROP- MIN	Minimum distance between baseline of the lower limit and (ink) bottom of the base operator.
32	STACKTOPSHIFTUP	Standard shift up applied to the top element of a stack.
33	STACKTOPDISPLAYSTYLESHIFT- UP	Standard shift up applied to the top element of a stack in display style.
34	STACKBOTTOMSHIFTDOWN	Standard shift down applied to the bottom element of a stack. Positive for moving in the downward direction.
35	STACKBOTTOMDISPLAYSTYLE- SHIFTDOWN	Standard shift down applied to the bottom element of a stack in display style. Positive for moving in the downward direction.
36	STACKGAPMIN	Minimum gap between (ink) bottom of the top element of a stack, and the (ink) top of the bottom element. Suggested: $3 \times$ default rule thickness.
37	STACKDISPLAYSTYLEGAPMIN	Minimum gap between (ink) bottom of the top element of a stack, and the (ink) top of the bottom element in display style. Suggested: $7 \times$ default rule thickness.
38	STRETCHSTACKTOPSHIFTUP	Standard shift up applied to the top element of the stretch stack.

\fontdimen	Dimension name	Description
39	STRETCHSTACKBOTTOMSHIFT- DOWN	Standard shift down applied to the bottom element of the stretch stack. Positive for moving in the downward direction.
40	STRETCHSTACKGAPABOVEMIN	Minimum gap between the ink of the stretched element, and the (ink) bottom of the element above. Suggested: UpperLimitGapMin
41	STRETCHSTACKGAPBELOWMIN	Minimum gap between the ink of the stretched element, and the (ink) top of the element below. Suggested: LowerLimitGapMin.
42	FRACTIONNUMERATORSHIFTUP	Standard shift up applied to the numerator.
43	FRACTIONNUMERATOR- DISPLAYSTYLESHIFTUP	Standard shift up applied to the numerator in display style. Suggested: StackTopDisplayStyleShiftUp.
44	FRACTIONDENOMINATORSHIFT- DOWN	Standard shift down applied to the denominator. Positive for moving in the downward direction.
45	FRACTIONDENOMINATOR- DISPLAYSTYLESHIFTDOWN	Standard shift down applied to the denominator in display style. Positive for moving in the downward direction. Suggested: StackBottomDisplayStyleShiftDown.
46	FRACTIONNUMERATORGAP- MIN	Minimum tolerated gap between the (ink) bottom of the numerator and the ink of the fraction bar. Suggested: default rule thickness
47	FRACTIONNUMDISPLAYSTYLE- GAPMIN	Minimum tolerated gap between the (ink) bottom of the numerator and the ink of the fraction bar in display style. Suggested: 3×default rule thickness.
48	FRACTIONRULETHICKNESS	Thickness of the fraction bar. Suggested: default rule thickness.
49	FRACTIONDENOMINATORGAP- MIN	Minimum tolerated gap between the (ink) top of the denominator and the ink of the fraction bar. Suggested: default rule thickness

\fontdimen	Dimension name	Description
50	FRACTIONDENOMDISPLAY- STYLEGAPMIN	Minimum tolerated gap between the (ink) top of the denominator and the ink of the fraction bar in display style. Suggested: 3×default rule thickness.
51	SKewedFRACTION- HORIZONTALGAP	Horizontal distance between the top and bottom elements of a skewed fraction.
52	SKewedFRACTIONVERTICAL- GAP	Vertical distance between the ink of the top and bottom elements of a skewed fraction.
53	OVERBARVERTICALGAP	Distance between the overbar and the (ink) top of the base. Suggested: 3×default rule thickness.
54	OVERBARRULETHICKNESS	Thickness of overbar. Suggested: default rule thickness.
55	OVERBAREXTRAASCENDER	Extra white space reserved above the overbar. Suggested: default rule thickness.
56	UNDERBARVERTICALGAP	Distance between underbar and (ink) bottom of the base. Suggested: 3×default rule thickness.
57	UNDERBARRULETHICKNESS	Thickness of underbar. Suggested: default rule thickness.
58	UNDERBAREXTRADESCENDER	Extra white space reserved below the underbar. Always positive. Suggested: default rule thickness.
59	RADICALVERTICALGAP	Space between the (ink) top of the expression and the bar over it. Suggested: 1¼ default rule thickness.
60	RADICALDISPLAYSTYLE- VERTICALGAP	Space between the (ink) top of the expression and the bar over it. Suggested: default rule thickness + ¼ x-height.
61	RADICALRULETHICKNESS	Thickness of the radical rule. This is the thickness of the rule in designed or constructed radical signs. Suggested: default rule thickness.
62	RADICALEXTRAASCENDER	Extra white space reserved above the radical. Suggested: RadicalRuleThickness.
63	RADICALKERNBEFOREDEGREE	Extra horizontal kern before the degree of a radical, if such is present. Suggested: 5/18 of em.

\fontdimen	Dimension name	Description
64	RADICALKERNAFTERDEGREE	Negative kern after the degree of a radical, if such is present. Suggested: –10/18 of em.
65	RADICALDEGREEBOTTOM- RAISEPERCENT	Height of the bottom of the radical degree, if such is present, in proportion to the ascender of the radical sign. Suggested: 60%.

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols			
\"	2264	\\	1778, 1780, 2257–2260, 2264, 2270–2280
\#	1773	\{	1742
\\$	1746, 2205	\}	1743
\%	1745	\^	1738, 1756, 1765, 2280
\&	1744, 2206	\`	648, 1946, 2203
\'	647, 1945, 2204, 2221	\	1779
*	624, 1778, 2222	Numbers	
\-	623, 2211, 2214, 2224, 2225, 2227	\0	276
\.	2223	\9	276
\/	655, 2228		
\:	626, 2229		
\<	659	_	2264–2267, 2270–2279
\=	2212, 2215	A	
\>	660	\A	273
\@DeclareMathDelimiter	454	\a	272
\@DeclareMathSizes	445	\addnolimits	<u>714</u>
\@backslashchar	1104, 1117	\addtoversion	446
\@begindocumenthook	2210	\AfterPackage	11
\@ccclvi	460	\alloc@	460
\@cdots	2216	\alpha@elt	447
\@empty	789, 819, 822	\alpha@list	447
\@ifclassloaded	7, 2238	\AtBeginDocument	
\@ifpackageloaded	2181, 2194	960, 1763, 1935, 1954, 2234
\@ii	788, 789, 791, 793, 796, 801	\AtEndOfPackage	437
\@input	581, 1774	\AtEndPackage	8
\@marker	801, 816	\awint	710
\@nil	498, 630,	B	
801, 810–813, 841, 1739, 1752, 1770		\B	172
\@preamblecmds	458	\backdprime	1941
\@tempa	285, 342, 364, 373, 383, 393,	\backprime	1940
400, 407, 416, 429, 792, 812, 814, 822		\backtrprime	1942
\@tempb	285,	\beamer@suppressreplacementstrue	2244
287, 342, 344, 364, 365, 373, 375,		\begingroup	1737
383, 385, 393, 394, 400, 401, 407,		\beta	2072
408, 416, 417, 429, 430, 815, 816, 819		\bgroup	991
\@tempswafalse	790	\bigcirc	2176
\@tempswattrue	794, 797, 817, 820, 823, 826	\bigtriangleup	2175
\@xDeclareMathDelimiter	454		
\@xxDeclareMathDelimiter	453		

\bool_if:NF	444
625, 1202, 1213, 1228, 1238, 1248,	
1255, 1353, 1365, 1382, 1390,	
1397, 1405, 1417, 1429, 1439,	
1446, 1455, 1462, 1662, 1674,	
1686, 1698, 1709, 1716, 1725, 1732	
\bool_if:nF	1767
\bool_if:NT	
.. 1139, 1149, 1162, 1172, 1182,	
1189, 1329, 1341, 1472, 1480,	
1487, 1495, 1507, 1519, 1529,	
1536, 1549, 1556, 1582, 1594,	
1606, 1618, 1629, 1636, 1645, 1652	
\bool_if:NTF	
106–113, 562, 725, 973, 976, 979,	
982, 1102, 1136, 1146, 1159, 1169,	
1179, 1186, 1199, 1209, 1225,	
1235, 1245, 1252, 1325, 1337,	
1349, 1361, 1386, 1401, 1413,	
1425, 1436, 1443, 1452, 1459,	
1476, 1491, 1503, 1515, 1526,	
1533, 1546, 1553, 1578, 1590,	
1602, 1614, 1626, 1633, 1642,	
1649, 1658, 1670, 1682, 1694,	
1706, 1713, 1722, 1729, 2164, 2185	
\bool_if:nTF	2102
\bool_new:N	18–40
\bool_set_false:N	
286, 288–291, 300–302, 313, 343,	
345–348, 351, 366, 374, 378, 384,	
388, 395, 404, 422, 425, 555, 748, 1044	
\bool_set_true:N	
..... 299, 310–312, 321–324,	
332, 350, 352, 353, 355–358, 360,	
368, 370, 376, 380, 386, 390,	
397, 402, 419, 536, 553, 608, 1038	
\box	1975
\bullet	2178
C	
\C	173
\c_group_begin_token	2103
\c_group_end_token	2104
\c_peek_true_remove_next_tl ...	2093
\c_space_token	2105
\cdots	2216, 2217, 2233
\cdp@elt	444
\cdp@list	444
\char_gmake_mathactive:N	
..... 528, 2005, 2038, 2159	
\char_gmake_mathactive:n 497, 528, 652	
\char_make_active:N	
..... 1945, 1946, 2004, 2037	
\char_make_active:n 496, 1947–1953, 2158	
\char_make_escape:N	1779
\char_make_math_superscript:N ...	
..... 1756, 1765	
\char_make_other:N	
..... 1738, 1742–1746, 1773, 1780	
\chardef	460
\chi	2076
\circ	2177
\cirfnint	710
\clist_clear:N	538
\clist_if_in:NnT	703
\clist_map_break:	1083, 1087
\clist_map_inline:nn	
..... 635, 696, 751, 846,	
852, 858, 876, 888, 906, 913, 919,	
925, 933, 941, 962, 1013, 1079, 1092	
\clist_put_right:Nx	804
\colon	2181
\copy	1973
\cs	2000, 2089
\cs_generate_variant:Nn 13–17, 527,	
894, 895, 958, 959, 1115, 1127–1130	
\cs_gset:cpx	469, 484, 485, 501
\cs_gset:Npn	1739, 2007, 2040
\cs_gset:Npx	473, 479, 488, 2163
\cs_if_eq_p:NN	1767–1769
\cs_if_exist:cT	905, 1080, 1093
\cs_if_exist:NT	438
\cs_if_exist:NTF	418
\cs_new:Nn	
. 48, 51, 494, 518, 521, 524, 528,	
531, 588, 622, 629, 634, 639, 650,	
654, 689, 692, 837, 840, 896, 899,	
904, 912, 918, 924, 932, 940, 961,	
985, 1033, 1065, 1076, 1131, 1135,	
1145, 1158, 1168, 1178, 1198,	
1208, 1224, 1234, 1244, 1262,	
1265, 1275, 1278, 1285, 1292,	
1303, 1309, 1317, 1320, 1324,	

1336, 1348, 1360, 1372, 1375, 1378, 1381, 1396, 1411, 1423, 1435, 1467, 1471, 1486, 1501, 1513, 1525, 1561, 1564, 1567, 1570, 1573, 1577, 1589, 1601, 1613, 1625, 1657, 1669, 1681, 1693, 1705, 1790, 1796, 1812, 1825, 1829, 1833, 1837, 1841, 1887, 1891, 1895, 1899, 1977, 1980, 2081, 2091, 2121, 2135, 2193	\def 460, 722, 810, 812–815, 1758, 1766, 2169–2180, 2188, 2189, 2191, 2192, 2214–2216, 2235, 2236
\cs_new:Npn 2101, 2157	\define@choicekey 284, 342, 363, 373, 383, 393, 400, 407, 416, 429
\cs_set:cpn 986	\define@cmdkey 741–744
\cs_set:Nn	\define@key 724, 747
431, 433, 462, 506, 510, 514, 614, 617, 695, 702, 832, 845, 851, 857, 875, 883, 887, 893, 1116, 2002, 2035	\define@mathalphabet 446
\cs_set:Npn .. 779, 783, 2220, 2232, 2233	\define@mathgroup 446
\cs_set:Npx 547, 589	\Digamma 2191
\cs_set_eq:cN 1118	\digamma 2191
\cs_set_eq:NN 8, 11, 565–569, 573–577, 582, 1045, 1058, 1936–1942, 1955–1963, 2009, 2042, 2217	\dimexpr 552, 1969, 1978
\cs_set_nopar:Npn 1966	\do 458, 2203–2206
\cs_set_protected:cpx 989	\dorestore@version 448
\cs_set_protected:Npn 2184	\dotsb@ 2217
\cs_to_str:N 469, 484, 485, 498, 500–502, 697, 1010, 1077	\dp 1971
\csname 498, 508, 512, 516, 519, 522, 525, 539, 612, 690, 693, 994	\drime 1937
D	E
\D 174	\E 175
\d 200	\e 201
\DeclareDocumentCommand 281, 534, 714, 717	\edef 811, 812
\DeclareMathAccent 452	\egroup 987, 993
\DeclareMathAlphabet 451	\else 554, 795, 800, 818, 821, 824, 1983, 1986, 2224, 2239
\DeclareMathDelimiter 453	\else: 1123
\DeclareMathRadical 455	\encodingdefault 580
\DeclareMathSizes 444	\endcsname 498, 508, 512, 516, 519, 522, 525, 539, 612, 690, 693, 994
\DeclareMathSymbol 452	\endgroup 1762
\DeclareMathVersion 446, 541	\epsilon 972
\DeclareSymbolFont 449, 579	\etex_iffontchar:D 1121
\DeclareSymbolFontAlphabet 456	\ExecuteOptionsX 436
\DeclareSymbolFontAlphabet@ 456	\exp_after:wN 768, 771, 1052, 1054, 1056, 1078

F	
\F	176
\f@encoding	612
\f@size	539, 612
\fi 340, 361, 371, 381, 391, 398, 405, 414, 426, 434, 561, 798, 799, 802, 806, 807, 828–830, 1988, 1989, 2226, 2245	
\fi:	1125
\fint	710
\font	611
\fontdimen	552, 1968, 1974, 1978
\fontname	611, 1069
\fontspec	590
\frac	2164
G	
\g	202
\g_um_bfit_Greek_usv	112
\g_um_bfit_greek_usv	113
\g_um_bfit_Latin_usv	110
\g_um_bfit_latin_usv	111
\g_um_bfliteral_bool	27, 343, 360, 1386, 1401, 1413, 1425, 1476, 1491, 1503, 1515
\g_um_bfsfit_Greek_usv	108
\g_um_bfsfit_greek_usv	109
\g_um_bfsfit_Latin_usv	106
\g_um_bfsfit_latin_usv	107
\g_um_bfsfup_Greek_usv	108
\g_um_bfsfup_greek_usv	109
\g_um_bfsfup_Latin_usv	106
\g_um_bfsfup_latin_usv	107
\g_um_bfup_Greek_usv	112
\g_um_bfup_greek_usv	113
\g_um_bfup_Latin_usv	110
\g_um_bfup_latin_usv	111
\g_um_bfupGreek_bool	30, 112, 345, 350, 355, 1417, 1507
\g_um_bfupgreek_bool	31, 113, 346, 351, 356, 1429, 1519
\g_um_bfupLatin_bool	28, 110, 347, 352, 357, 1382, 1390, 1472, 1480
\g_um_bfuplatin_bool	29, 111, 348, 353, 358, 1397, 1405, 1487, 1495
\g_um_default_mathalph_seq	1012, 1030, 1037
\g_um_fam_int	41, 571, 572
\g_um_it_h_usv	277
\g_um_literal_bool	22, 286, 332, 1136, 1146, 1159, 1169, 1199, 1209, 1225, 1235
\g_um_literal_colon_bool	40, 402, 404, 625, 2185
\g_um_literal_Nabla_bool	36, 374, 380, 1179, 1245, 1436, 1459, 1526, 1553, 1626, 1649, 1706, 1729
\g_um_literal_partial_bool ..	37, 384, 390, 1186, 1252, 1443, 1452, 1533, 1546, 1633, 1642, 1713, 1722
\g_um_math_alphabet_name_Greek_tl	45
\g_um_math_alphabet_name_greek_tl	44
\g_um_math_alphabet_name_Latin_tl	43
\g_um_math_alphabet_name_latin_tl	42
\g_um_math_alphabet_name_misc_tl	47
\g_um_math_alphabet_name_num_tl .	46
\g_um_mathalph_seq	773, 1000
\g_um_mathit_Greek_usv_range_tl .	280
\g_um_mathit_greek_usv_range_tl .	279
\g_um_mathit_Latin_usv_range_tl .	278
\g_um_mathit_latin_usv_range_tl .	277
\g_um_mathup_Greek_usv_range_tl .	275
\g_um_mathup_greek_usv_range_tl .	274
\g_um_mathup_Latin_usv_range_tl .	273
\g_um_mathup_latin_usv_range_tl .	272
\g_um_mathup_num_usv_range_tl ...	276
\g_um_primekern_muskip	1787, 1788, 1793
\g_um_sfliteral_bool .	33, 370, 1325, 1337, 1349, 1361, 1578, 1590, 1602, 1614, 1658, 1670, 1682, 1694
\g_um_slash_delimiter_usv	409, 411, 413, 655–657
\g_um_subs_prop	1992, 2036
\g_um_supers_prop	1991, 2003
\g_um_texgreek_bool	38, 395, 397, 973, 976, 979, 982
\g_um_upGreek_bool	25, 108, 288, 299, 310, 321, 1162, 1228
\g_um_upgreek_bool	26, 109, 289, 300, 311, 322, 1172, 1238

\g_um_upLatin_bool	23, 106, 290, 301, 312, 323, 1139, 1202
\g_um_uplatin_bool	24, 107, 291, 302, 313, 324, 1149, 1213
\g_um_upNabla_bool	34, 376, 378, 1182, 1248, 1439, 1462, 1529, 1556, 1629, 1652, 1709, 1732
\g_um_uppartial_bool	35, 386, 388, 1189, 1255, 1446, 1455, 1536, 1549, 1636, 1645, 1716, 1725
\g_um_upsans_bool	32, 366, 368, 1329, 1341, 1353, 1365, 1582, 1594, 1606, 1618, 1662, 1674, 1686, 1698
\gamma	2073
\gdef	1752
\ge	2173
\geq	2173
\get@cdp	450
\glb@currsize	535
\global	529, 532, 1748, 1758
\group@elt	449
\group@list	449
\group_align_safe_begin:	2095
\group_align_safe_end:	2094
\group_begin:	495, 607, 1764, 1777, 1944, 1994, 2136
\group_end:	499, 610, 1775, 1965, 2078, 2155
H	
\H	177
\h	203
\hat	2235
\hbox	1967
\ht	1970
I	
\I	178
\i	204
\if@tempwa	803
\ifbeamer@suppressreplacements	2239
\ifcase	287, 344, 365, 375, 385, 394, 401, 408, 417, 430
\ifdim	552
\ifnum	2224
\ifx	789, 792, 793, 796, 816, 819, 822, 1981, 1984
\ignorespaces	1770
\iiiint	708
\iiint	708
\iint	708
\init@restore@version	448
\int	708
\int_incr:N	571
\int_new:N	41
\int_use:N	572
\intBar	710
\intbar	710
\intcap	712
\intclockwise	709
\intcup	712
\intexpr_compare:nT	817, 820, 823, 825, 826
\intexpr_eval:n	507, 508, 511, 512, 516, 804
\intlarhk	711
\intx	711
J	
\j	205
K	
\kern	1968, 1974
L	
\L	179
\l_peek_false_tl	2094, 2107, 2133
\l_peek_token	2103–2105, 2124, 2128
\l_peek_true_aux_tl	2092
\l_peek_true_tl	2093, 2131
\l_um_char_num_range_clist	538, 703, 804
\l_um_char_range_seq	537, 746, 749, 759, 788
\l_um_font	552, 611, 1069, 1121, 1968, 1970, 1971, 1974, 1982, 1985
\l_um_fontspec_feature_bool	18, 608, 725
\l_um_implicit_alph_bool	21, 1038, 1044, 1102
\l_um_init_bool	20, 536, 562, 748
\l_um_mathalph_seq	745, 750, 753, 1035, 1037, 1047

<code>\mathsf{fit}</code>	1004, 1022, 1358, 1370	<code>\oiint</code>	708
<code>\mathsf{fup}</code>	1004, 1021, 1322, 1334, 1346	<code>\oint</code>	708
<code>\mathsterling</code>	2180	<code>\ointctrclockwise</code>	709
<code>\mathstraightquote</code>	647	<code>\operator@font</code>	2169
<code>\mathtt</code>	1003, 1020, 1373, 1376, 1379	<code>\or</code>	298, 309, 320, 331, 349, 354, 359, 367, 369, 377, 379, 387, 389, 396, 403, 410, 412, 424, 432
<code>\mathup</code>	1002, 1014, 1133, 1143, 1156, 1166, 1176, 1193–1196, 2189	<code>\overrightarrow</code>	2171
<code>\mathyen</code>	2179	P	
<code>\mddefault</code>	580, 612	<code>\P</code>	182
<code>\mdlgwhtcircle</code>	2176	<code>\PackageError</code>	728
<code>\meaning</code>	2003, 2036, 2124, 2128	<code>\PackageInfo</code>	564
<code>\mitepsilon</code>	973, 979	<code>\PackageWarning</code>	421
<code>\mitphi</code>	976, 982	<code>\PackageWarningNoLine</code>	556, 2240
<code>\mitvarepsilon</code>	973, 979	<code>\peek_after:NN</code>	2096
<code>\mitvarphi</code>	976, 982	<code>\peek_meaning_remove:NTF</code>	1843, 1846, 1849, 1852, 1856, 1860, 1864, 1868, 1872, 1901, 1904, 1907, 1910, 1914, 1918, 1922
<code>\mode_if_math:F</code>	992	<code>\phi</code>	975, 2075
<code>\mskip</code>	1793	<code>\pointint</code>	711
<code>\muskip_gset:Nn</code>	1788	<code>\prg_case_int:nnn</code>	1797, 1813
<code>\muskip_new:N</code>	1787	<code>\prg_case_tl:Nnn</code>	463
N		<code>\prg_do_nothing:</code>	1118
<code>\N</code>	181	<code>\prg_new_conditional:Nnn</code>	763, 1120
<code>\ne</code>	2174	<code>\prg_replicate:nn</code>	1793
<code>\neq</code>	2174	<code>\prg_return_false:</code>	776, 1124
<code>\new@mathalphabet</code>	451	<code>\prg_return_true:</code>	774, 1122
<code>\new@mathgroup</code>	444, 460, 461	<code>\prg_stepwise_inline:nnnn</code>	833, 900
<code>\new@mathversion</code>	449	<code>\prime</code>	1936
<code>\new@symbolfont</code>	450	<code>\process@table</code>	448
<code>\newcommand</code>	723, 787	<code>\ProcessOptionsX</code>	442
<code>\newfam</code>	461	<code>\prop_get:cxN</code>	2126
<code>\newmathalphabet</code>	445	<code>\prop_get:NnN</code>	16
<code>\newmathalphabet@@</code>	445	<code>\prop_gput:Nnn</code>	15
<code>\newmathalphabet@@@</code>	445	<code>\prop_gput:Nxn</code>	2003, 2036
<code>\newmcodes@</code>	2220	<code>\prop_if_in:cxTF</code>	2122
<code>\nolimits</code>	503	<code>\prop_if_in:NnTF</code>	17
<code>\non@alpherr</code>	994	<code>\prop_new:N</code>	1991, 1992
<code>\nopolint</code>	711	<code>\protect</code>	421, 731
<code>\num_add:Nn</code>	1861, 1865, 1869, 1873, 1919, 1923	<code>\ProvidesPackage</code>	1
<code>\num_incr:N</code>	1842, 1853, 1857, 1900, 1911, 1915	Q	
<code>\num_new:N</code>	1789	<code>\Q</code>	183
<code>\num_set:Nn</code>	1830, 1834, 1838, 1892, 1896	<code>\q_nil</code>	768, 771, 779, 783
<code>\num_zero:N</code>	1826, 1888		
O			
<code>\o</code>	206		

<code>\qprime</code>	1939	<code>\SetSymbolFont</code>	450
R		<code>\SetSymbolFont@</code>	450
<code>\R</code>	184	<code>\sf@size</code>	595, 599
<code>\r@@t</code>	1966	<code>\smbkcircle</code>	2178
<code>\raise</code>	1969	<code>\sp</code>	2009
<code>\relax</code>	287, 344, 365, 535, 552, 793, 796, 816, 1972, 1978, 2211, 2212, 2214, 2215, 2225	<code>\space</code> ...	421, 994, 1072, 1095, 1099, 1105
<code>\removenolimits</code>	717	<code>\sqint</code>	711
<code>\RequirePackage</code>	3–5, 10	<code>\sqrt</code>	720
<code>\restore@mathversion</code>	448	<code>\sqrtsign</code>	1967
<code>\rho</code>	2074	<code>\std@equal</code>	2212, 2215
<code>\rightarrow</code>	2170	<code>\std@minus</code>	2211, 2214, 2225
<code>\rootbox</code>	1973	<code>\sterling</code>	2180
<code>\rppolint</code>	710	<code>\string</code>	811, 812
S		<code>\strip@pt</code>	1978
<code>\sb</code>	2042	<code>\sumint</code>	709
<code>\scan_stop:</code> 508, 512, 516, 519, 522, 525, 529, 532, 1121, 2221–2223, 2227–2229		T	
<code>\scantokens</code>	2006, 2039	<code>\tf@size</code>	594, 595
<code>\scpolint</code>	711	<code>\tfrac</code>	418, 421, 438, 2164
<code>\scriptscriptstyle</code>	1984	<code>\thinmuskip</code>	1788
<code>\scriptstyle</code>	1981	<code>\tilde</code>	2236
<code>\seq_clear:N</code>	537, 749, 750, 1034	<code>\tl_if_empty:NT</code>	1057
<code>\seq_if_empty:NF</code>	1066	<code>\tl_if_empty:NTF</code>	1051
<code>\seq_if_empty:NTF</code>	1035	<code>\tl_if_eq:nnTF</code>	1081, 1094
<code>\seq_if_in:NnTF</code>	14	<code>\tl_if_in:NnT</code>	503, 767, 770
<code>\seq_if_in:NVTF</code>	773	<code>\tl_if_in:NnTF</code>	468
<code>\seq_map_inline:Nn</code>	1047, 1071	<code>\tl_map_inline:nn</code>	443, 1001
<code>\seq_map_variable:NNn</code>	788	<code>\tl_new:Nn</code>	272–280, 707, 720
<code>\seq_new:N</code> ...	745, 746, 1000, 1012, 1032	<code>\tl_put_left:Nn</code>	2201
<code>\seq_put_right:Nn</code> ...	759, 1009, 1030	<code>\tl_put_right:cx</code>	697
<code>\seq_put_right:Nx</code>	753, 1103	<code>\tl_put_right:Nn</code>	13, 715, 2202
<code>\seq_set_eq:NN</code>	1037	<code>\tl_put_right:NV</code>	2130
<code>\set@@mathdelimiter</code>	455	<code>\tl_remove_all_in:Nn</code>	718
<code>\set@mathaccent</code>	452	<code>\tl_remove_in:Nn</code>	458, 2210
<code>\set@mathchar</code>	452	<code>\tl_rescan:nn</code>	1741, 1754, 2160
<code>\set@mathdelimiter</code>	454	<code>\tl_set:cn</code>	49
<code>\set@mathsymbol</code>	453	<code>\tl_set:cx</code>	970
<code>\setbox</code>	1967	<code>\tl_set:Nn</code>	42–47, 409, 411, 413, 540, 542–545, 563, 764–766, 780, 781, 784, 785, 972, 975, 978, 981, 1059, 2008, 2010, 2041, 2043
<code>\setkeys</code>	282, 292, 303, 314, 325, 333, 546, 548	<code>\tl_set:No</code>	1048–1050
<code>\SetMathAlphabet</code>	451	<code>\tl_set:Nx</code>	572, 1052, 1054, 1056, 1077, 1078, 2092, 2094
<code>\SetMathAlphabet@</code>	451	<code>\tl_set_eq:NN</code>	2093
<code>\setmathfont</code>	534, 731	<code>\tl_use:c</code>	1105
		<code>\to</code>	2170

\token_if_eq_catcode_p:NN	2103, 2104	\um_config_mathbfsfup_num:n	1573
\token_if_eq_meaning_p:NN	2105	\um_config_mathbfup_Greek:n	1501
\token_to_str:N	1052, 1054	\um_config_mathbfup_greek:n	1513
\triangle	2175	\um_config_mathbfup_Latin:n	1471
\trprime	1938	\um_config_mathbfup_latin:n	1486
\typeout	431, 1067, 1072	\um_config_mathbfup_misc:n	1525
U			
\um@backslash	792, 811	\um_config_mathbfup_num:n	1467
\um@firstchar	791, 812	\um_config_mathfrak_Latin:n	1309
\um@firstof	810–812	\um_config_mathfrak_latin:n	1317
\um@parse@range	801, <u>813</u>	\um_config_mathit_Greek:n	1224
\um@parse@term	618, 630, <u>787</u> , 841	\um_config_mathit_greek:n	1234
\um@radicals	<u>720</u>	\um_config_mathit_Latin:n	1198
\um@scanactivedef	498, <u>1737</u>	\um_config_mathit_latin:n	1208
\um@scancharlet	<u>1737</u> , 1770	\um_config_mathit_misc:n	1244
\um@zf@feature	<u>723</u> , 735, 738	\um_config_mathscr_Latin:n	1292
\um_accent:Nnn	488, <u>506</u>	\um_config_mathscr_latin:n	1303
\um_after_pkg:nn	8, 11, 2197	\um_config_mathsf_Latin:n	1348
\um_backprime_double_mchar	645, 1816	\um_config_mathsf_latin:n	1360
\um_backprime_single_mchar	644, 1889, 1893, 1897	\um_config_mathsfup_Latin:n	1324
\um_backprime_triple_mchar	646, 1819	\um_config_mathsfup_latin:n	1336
\um_config_mathbb_Latin:n	1265	\um_config_mathsfup_num:n	1320
\um_config_mathbb_latin:n	1262	\um_config_mathhtt_Latin:n	1375
\um_config_mathbb_misc:n	1278	\um_config_mathhtt_latin:n	1378
\um_config_mathbb_num:n	1275	\um_config_mathhtt_num:n	1372
\um_config_mathbbit_misc:n	1285	\um_config_mathup_Greek:n	1158
\um_config_mathbffrak_Latin:n	1561	\um_config_mathup_greek:n	1168
\um_config_mathbffrak_latin:n	1564	\um_config_mathup_Latin:n	1135
\um_config_mathbfit_Greek:n	1411	\um_config_mathup_latin:n	1145
\um_config_mathbfit_greek:n	1423	\um_config_mathup_misc:n	1178
\um_config_mathbfit_Latin:n	1381	\um_config_mathup_num:n	1131
\um_config_mathbfit_latin:n	1396	\um_debug:n	431, 433, 1036, 1043, 1095, 1099, 1117
\um_config_mathbfit_misc:n	1435	\um_define_active_frac:Nw	2137–2154, 2157
\um_config_mathbfscr_Latin:n	1567	\um_delimiter:Nnn	473, 479, 484, 485, <u>506</u>
\um_config_mathbfscr_latin:n	1570	\um_fontdimen_to_percent:nn	1970, 1971, <u>1977</u> , 1982, 1985
\um_config_mathbfsfit_Greek:n	1681	\um_fontspec_select_font:	588
\um_config_mathbfsfit_greek:n	1693	\um_fontspec_select_font:n	551, 588
\um_config_mathbfsfit_Latin:n	1657	\um_glyph_if_exist:cT	1085
\um_config_mathbfsfit_latin:n	1669	\um_glyph_if_exist:cTF	1098
\um_config_mathbfsfit_misc:n	1705	\um_glyph_if_exist:n	1120
\um_config_mathbfsfup_Greek:n	1601	\um_glyph_if_exist:nF	1130
\um_config_mathbfsfup_greek:n	1613	\um_glyph_if_exist:nT	1129
\um_config_mathbfsfup_Latin:n	1577	\um_glyph_if_exist:nTF	1120, 1800, 1803, 1806, 1816, 1819
\um_config_mathbfsfup_latin:n	1589		
\um_config_mathbfsfup_misc:n	1625		

<code>\um_glyph_if_exist_p:n</code>	1127	<code>\um_maybe_init_alphabet:n</code>	
<code>\um_if_mathalph_decl:n</code>	763		568, 576, 1039–1041, 1058, 1082, 1086
<code>\um_if_mathalph_decl:nTF</code>	752	<code>\um_nbackprimes_select:nn</code> ..	1812, 1926
<code>\um_init_alphabet:n</code> ..	568, 1058, 1116	<code>\um_nprimes:Nn</code>	1790, 1800,
<code>\um_make_mathactive:nNN</code> ..	640–648, 650		1803, 1806, 1809, 1816, 1819, 1822
<code>\um_map_char:nn</code>	569, 577, 834, 893	<code>\um_nprimes_select:nn</code>	1796, 1876
<code>\um_map_char:nn</code>	832	<code>\um_patch_pkg:nn</code> ..	2193, 2200, 2209, 2219
<code>\um_map_char_noparse:nn</code> ..	569, 837, 842	<code>\um_peek_execute_branches_ss:</code> ...	
<code>\um_map_char_parse:nn</code>	577, 840		2096, 2101
<code>\um_map_char_single:cc</code>		<code>\um_peek_execute_branches_ss_aux:</code>	
	861, 863, 865, 867, 869, 871, 879, 889		2108, 2121
<code>\um_map_char_single:nn</code>	893, 894	<code>\um_prepare_alph:n</code>	985, 1010
<code>\um_map_chars_Greek:nn</code> ..	875, 1160,	<code>\um_prime_double_mchar</code>	641, 1800
	1163, 1226, 1229, 1414, 1418,	<code>\um_prime_quad_mchar</code>	643, 1806
	1504, 1508, 1603, 1607, 1683, 1687	<code>\um_prime_single_mchar</code>	
<code>\um_map_chars_greek:nn</code> ..	857, 1170,		640, 1827, 1831, 1835, 1839
	1173, 1236, 1239, 1426, 1430,	<code>\um_prime_triple_mchar</code>	642, 1803
	1516, 1520, 1615, 1619, 1695, 1699	<code>\um_process_symbol_noparse:nnnn</code> ..	
<code>\um_map_chars_Latin:nn</code>			565, 614
	845, 1137, 1140,	<code>\um_process_symbol_parse:nnnn</code>	573, 614
	1200, 1203, 1326, 1330, 1350,	<code>\um_radical:nn</code>	469, 506
	1354, 1383, 1387, 1391, 1473,	<code>\um_remap_symbol:nnn</code>	
	1477, 1481, 1579, 1583, 1659, 1663		567, 575, 623, 624, 626
<code>\um_map_chars_latin:nn</code>		<code>\um_remap_symbol_noparse:nnn</code>	567, 622
	851, 1147, 1150,	<code>\um_remap_symbol_parse:nnn</code>	
	1210, 1214, 1338, 1342, 1362,		575, 622, 629
	1366, 1398, 1402, 1406, 1488,	<code>\um_remap_symbols:</code>	583, 622
	1492, 1496, 1591, 1595, 1671, 1675	<code>\um_resolve_greek:</code>	960
<code>\um_map_chars_numbers:nn</code> ..	883, 1132	<code>\um_scan_backdprime:</code>	
<code>\um_map_chars_range:ncc</code>			1891, 1910, 1941, 1962
	847, 853, 859, 877, 884	<code>\um_scan_backprime:</code>	
<code>\um_map_chars_range:nnn</code>	832, 895		1887, 1904, 1940, 1960, 1961
<code>\um_map_single:nnn</code>		<code>\um_scan_backtrprime:</code>	
	887, 1151–1153, 1180, 1183,		1895, 1918, 1942, 1963
	1187, 1190, 1211, 1215–1217,	<code>\um_scan_dprime:</code> ..	1829, 1852, 1937, 1957
	1246, 1249, 1253, 1256, 1437,	<code>\um_scan_prime:</code>	
	1440, 1444, 1447, 1527, 1530,		1825, 1846, 1936, 1955, 1956
	1534, 1537, 1627, 1630, 1634,	<code>\um_scan_qprime:</code> ..	1837, 1868, 1939, 1959
	1637, 1707, 1710, 1714, 1717	<code>\um_scan_sscript:</code> ..	2011, 2044, 2081, 2083
<code>\um_mathmap:Nnn</code> ..	566, 574, 897, 901, 1045	<code>\um_scan_sscript:TF</code>	2082, 2091
<code>\um_mathmap_noparse:Nnn</code>		<code>\um_scan_trprime:</code> ..	1833, 1860, 1938, 1958
	566, 695, 704, 1045	<code>\um_scanbackprime_collect:N</code>	
<code>\um_mathmap_parse:Nnn</code>	574, 702		1889, 1893, 1897, 1899, 1902,
<code>\um_mathstyle_scale:Nnn</code>			1905, 1908, 1912, 1916, 1920, 1924
	1968, 1974, 1980	<code>\um_scanprime_collect:N</code>	
			1827, 1831, 1835,

1839, 1841, 1844, 1847, 1850, 1854, 1858, 1862, 1866, 1870, 1874	\um_set_mathchar:NNnn 506, 651
\um_set_big_operator:nnn ... 465, 494	\um_set_mathcode:nnn 472, 478, 482, 491, 506
\um_set_delcode:n 471, 477, 483, 658, 661–687, 689	\um_set_mathcode:nnnn 506, 636, 698, 838
\um_set_delcode:nn 655–657, 659, 660, 689	\um_set_mathsymbols:nNnn 462, 615
\um_set_mathalph_range:nNcc 914, 920, 926, 934, 942	\um_setup_active_frac: 427, 2135
\um_set_mathalph_range:Nnn 899	\um_setup_active_subscript:nn 2035, 2049–2076
\um_set_mathalph_range:nNnn 899, 959	\um_setup_active_superscript:nn 2002, 2016–2032
\um_set_mathalphabet_char:Ncc 907, 928, 936, 944, 946, 948, 950, 952, 954	\um_setup_alphabets: 586, 1032
\um_set_mathalphabet_char:Nnn 896, 958	\um_setup_delcodes: 585, 654
\um_set_mathalphabet_Greek:Nnn 932, 1166, 1232, 1412, 1415, 1419, 1502, 1505, 1509, 1604, 1608, 1611, 1684, 1688, 1691	\um_setup_math_alphabet:Nnn ... 1076
\um_set_mathalphabet_greek:Nnn 940, 1176, 1242, 1424, 1427, 1431, 1514, 1517, 1521, 1616, 1620, 1623, 1696, 1700, 1703	\um_setup_math_alphabet:VVV ... 1061
\um_set_mathalphabet_Latin:Nnn .. 918, 1143, 1206, 1266, 1293, 1310, 1327, 1331, 1334, 1351, 1355, 1358, 1376, 1385, 1388, 1392, 1475, 1478, 1482, 1562, 1568, 1580, 1584, 1587, 1660, 1664, 1667	\um_setup_mathactives: 584, 639
\um_set_mathalphabet_latin:Nnn .. 924, 1156, 1220, 1263, 1304, 1318, 1339, 1343, 1346, 1363, 1367, 1370, 1379, 1400, 1403, 1407, 1490, 1493, 1497, 1565, 1571, 1592, 1596, 1599, 1672, 1676, 1679	\um_setup_mathup: 2169, 2201
\um_set_mathalphabet_numbers:Nnn 912, 1133, 1276, 1321, 1322, 1373, 1468, 1469, 1574, 1575	\um_split_arrow:w 768, 779
\um_set_mathalphabet_pos:Nnnn 904, 1193–1196, 1221, 1222, 1259, 1260, 1267–1273, 1279–1283, 1286–1290, 1294–1301, 1305–1307, 1311–1315, 1450, 1451, 1453, 1456, 1460, 1463, 1540–1545, 1547, 1550, 1554, 1557, 1640, 1641, 1643, 1646, 1650, 1653, 1720, 1721, 1723, 1726, 1730, 1733	\um_split_slash:w 771, 783
\um_set_mathchar:cNnn 500, 506	\um_sub_or_super:n .. 2009, 2042, 2085
	\um_symfont_tl 563, 572, 579, 615, 636, 651, 690, 693, 698, 838
	\um_tmp: 547, 550, 589, 609
	\um_to_usv:nn 49, 51, 847, 848, 853, 854, 859–872, 877–880, 884, 885, 889, 890, 905, 907, 908, 914, 915, 920, 921, 926–929, 934–937, 942–955, 1085, 1098
	\um_warn_missing_alphabets: 1063, 1065
	\unicodedots 2233
	\unicodeellipsis 2232
	\UnicodeMathSymbol . 565, 573, 582, 1766
	\unimathsetup 281, 439
	\unless 789
	\updefault 580, 612
	\upDigamma 2192
	\updigamma 2191
	\upint 712
	\Url@FormatString 2201
	\UrlSpecials 2202
	\use:c 987, 1096, 1100, 1108
	\use_i:nnn 1048
	\use_ii:nnn 1049
	\use_iii:nnn 1050
	\use_none:n 576
	\use_none:nnnn 582, 1078
	\use_none:nnnnn 1056

<code>\usv_set:nnn</code>	48, 52–271	<code>\XeTeXmathaccent</code>	525
V		<code>\XeTeXmathchardef</code>	515
<code>\varepsilon</code>	978	<code>\XeTeXmathcharnum</code>	2214, 2215
<code>\varointclockwise</code>	709	<code>\XeTeXmathcode</code>	507, 511
<code>\varphi</code>	981	<code>\XeTeXmathcodenum</code> .	529, 532, 2214, 2215
<code>\vec</code>	2171	<code>\XeTeXradical</code>	519
<code>\version@elt</code>	447	<code>\XKV@rm</code>	548, 604
<code>\version@list</code>	447	Y	
<code>\vysmwhtcircle</code>	2177	<code>\yen</code>	2179
W		Z	
<code>\widehat</code>	2235	<code>\Z</code>	185, 273
<code>\widetilde</code>	2236	<code>\z</code>	272
X		<code>\z@</code>	1967, 1970, 1971, 1975
<code>\XeTeXdelcode</code>	690, 693	<code>\zf@family</code>	580, 612
<code>\XeTeXdelimiter</code>	522	<code>\zf@update@ff</code>	736, 739