

Introduction to C++

Meng-Hsun Tsai
CSIE, NCKU

```
#include <iostream>
using namespace std;
int main()
{
    cout << "Hello NCKU CSIE 106!!" << endl;
    return 0;
}
```

First Program in C++: Printing a Line of Text

```
1 #include <iostream>    // for using cout
2 using namespace std;   // avoid repeating "std::"
3
4 int main()
5 {
6     std::cout << "Hello ";
7     cout << "NCKU " << "CSIE 106!!" << endl;
8     return 0;
9 }
```

```
> g++ -o hello hello.cpp
> ./hello
Hello NCKU CSIE 106!!
>
```

Where is *iostream*?

- In Cygwin

- > `find /usr -name iostream`

- `/usr/lib/gcc/i686-pc-cygwin/3.4.4/include/c++/iostream`

- `/usr/lib/gcc/i686-pc-mingw32/3.4.4/include/c++/iostream`

- In FreeBSD

- > `find /usr -name iostream`

- `/usr/include/c++/4.2/iostream`

What's Inside *iostream*?

```
> cat /usr/include/c++/4.2/iostream
// Standard iostream objects -*- C++ -*-
...
#include <ostream>
#include <istream>
namespace std
{
    extern istream cin;          ///< Linked to standard input
    extern ostream cout;        ///< Linked to standard output
    extern ostream cerr;        ///< Linked to standard error (unbuffered)
    extern ostream clog;        ///< Linked to standard error (buffered)
} // namespace std
...
```

A Simple Example using *#include*

included_file.h

```
1 std::cout << "included_file !\n";
```

including_file.cpp

```
1 #include <iostream>
2 int main()
3 {
4 #include "included_file.h"
5     std::cout << "including_file !\n";
6     return 0;
7 }
```

```
> g++ -o including_file including_file.cpp
> ./including_file
included_file !
including_file !
```

Output of Preprocessor

```
$ g++ -E including_file.cpp
namespace std
{
# 63 "/usr/lib/gcc/i686-pc-cygwin/3.4.4/include/c++/iostream" 3
    extern istream cin;
    extern ostream cout;
...
# 2 "including_file.cpp" 2
int main()
{
# 1 "included_file.h" 1
    std::cout << "included_file !\n" ;
# 5 "including_file.cpp" 2
    std::cout << "including_file !\n" ;
    return 0;
}
```

From g++'s man page:

-E **Stop after the
preprocessing stage;
do not run the compiler.**

Using #ifdef to Turn on/off Debugging Messages

```
1 #include <iostream>
2 #include <cstring>
3 int main(int argc, char ** argv)
4 {
5     #ifdef DEBUG
6         std::cout << argv[1] << "\n";
7     #endif
8     std::cout << strlen(argv[1]);
9     return 0;
10 }
```

```
> g++ -o str_len str_len.cpp
> ./str_len NCKU
4
> g++ -DDEBUG -o str_len str_len.cpp
> ./str_len NCKU
NCKU
4
```

Preprocessor Directive

- A **preprocessor directive** is a message to the C++ preprocessor.
- Lines that begin with **#** are processed by the preprocessor before the program is compiled.
- **#include <iostream>** notifies the preprocessor to include in the program the contents of the **input/output stream header file <iostream>**.
- Must be included for any program that outputs data to the screen or inputs data from the keyboard using C++-style stream input/output.

Comments and *using* Declaration

- `//` indicates that the remainder of each line is a **comment**.
 - You insert comments to **document your programs and to help other people read and understand them**.
 - Comments are ignored by the C++ compiler and **do not cause any machine-language object code to be generated**.
- You also may use C's style in which a comment—possibly **containing many lines**—begins with `/*` and ends with `*/`.
- **using declaration** eliminates the need to repeat the `std::` prefix.

Getting Return Value in Unix

```
> cat return_minus1.cpp
int main()
{
    return -1;
}
> g++ -o return_minus1 return_minus1.cpp
> echo $?
0
> ./return_minus1
> echo $?
255
> echo $?
0
```

The *cout* Object

- When a `COUT` statement executes, it sends a stream of characters to the **standard output stream object**—`std::cout`—which is normally “connected” to the screen.
- The notation `std::cout` specifies that we are using a name, in this case `COUT`, that belongs to “**namespace**” `std`.
- The `<<` operator is referred to as the **stream insertion operator**. The value to the operator’s right, the right **operand**, is inserted in the output stream.

The *endl* Stream Manipulator

- `std::endl` is a so-called **stream manipulator**.
- The name `endl` is an abbreviation for “end line” and belongs to namespace `std`.
- The `std::endl` stream manipulator outputs a newline, then “**flushes the output buffer.**”
 - This simply means that, on some systems where outputs accumulate in the machine until there are enough to “make it worthwhile” to display them on the screen, `std::endl` forces any accumulated outputs to be displayed at that moment.
 - This can be important when the outputs are prompting the user for an action, such as entering data.

Adding Two Integers

```
1 #include <iostream>
2 using namespace std;
3 int main()
4 {
5     int num1, num2;
6     cout << "Please enter the first number: ";
7     cin >> num1;
8     cout << "Please enter the second number: ";
9     cin >> num2;
10    cout << "Sum of the two numbers are: " << num1 + num2 << endl;
11    return 0;
12 }
```

> ./add

Please enter the first number: 3

Please enter the second number: 5

Sum of the two numbers are: 8

The *cin* Object

- A `cin` statement uses the **input stream object `cin`** (of namespace `std`) and the **stream extraction operator, `>>`**, to obtain a value from the keyboard.
- When the computer executes an input statement that places a value in an `int` variable, it **waits** for the user to enter a value for variable `num1`.
- The computer **converts** the character representation of the number to an integer and assigns this **value**) to the variable `num1`.