

Schink Stories System Email Report

Generated: 2026-06-12

Scope: source-code inventory of emails the Shink-Stories application can send from this checkout. This report does not verify live Resend/Supabase provider logs or published template contents.

Executive Summary

The system sends email through two providers:

- Resend transactional email API at `https://api.resend.com/emails`.
- Supabase Auth email flows for password recovery, email change confirmation, and a possible signup-confirmation fallback.

There are 16 distinct email send paths/families in the current source:

- 12 Resend template-based customer/admin emails.
- 2 Resend inline internal/admin emails.
- 2 definite Supabase Auth emails.
- 1 possible Supabase Auth signup confirmation fallback, only when the admin create-user endpoint is unavailable and Supabase confirmation is enabled.

Most customer-facing Resend emails use published template IDs. Two internal emails still use inline HTML/text payloads: the contact-form notification to the site inbox and the internal store-order paid notification.

Configuration

Primary config is under Resend in `Shink/appsettings.json`.

Default local values:

- `FromEmail`: `no-reply@example.com`
- `ToEmail`: `support@example.com`
- `BillingManageUrl`: `https://www.schink.co.za/intekening-en-betaling`

Root-level `appsettings.json` also contains Resend defaults used by the repository root context:

- `FromEmail`: `no-reply@prioritybit.co.za`
- `ToEmail`: `vanderwaltluan@gmail.com`

Production may override these through environment/app-service configuration, so treat these as code defaults rather than confirmed live values.

Configured Resend templates:

Area	Template setting	Current default ID
Contact auto-reply	<code>Templates.Contact.AutoReplyTemplateId</code>	<code>shink-contact-auto-reply</code>
Store customer confirmation	<code>Templates.StoreOrder.CustomerConfirmationTemplateId</code>	<code>shink-store-order-confirmation</code>
Subscription payment recovery day 1	<code>Templates.SubscriptionPaymentRecovery.Day1TemplateId</code>	<code>shink-subscription-recovery-day-1</code>
Subscription payment recovery day 3	<code>Templates.SubscriptionPaymentRecovery.Day3TemplateId</code>	<code>shink-subscription-recovery-day-3</code>
Subscription payment recovery day 5	<code>Templates.SubscriptionPaymentRecovery.Day5TemplateId</code>	<code>shink-subscription-recovery-day-5</code>
Subscription confirmation	<code>Templates.SubscriptionNotifications.ConfirmationTemplateId</code>	<code>shink-subscription-confirmation</code>
Subscription ended	<code>Templates.SubscriptionNotifications.EndedTemplateId</code>	<code>shink-subscription-ended</code>
Admin ops alert	<code>Templates.AdminOps.AlertTemplateId</code>	<code>shink-admin-ops-alert</code>
Abandoned checkout hour 1	<code>Templates.AbandonedCartRecovery.Hour1TemplateId</code>	<code>efdf7097-0981-457f-b7d6-a9091faef8c2</code>

Area	Template setting	Current default ID
Abandoned checkout hour 24	Templates.AbandonedCartRecovery.Hour24TemplateId	1583ea05-da74-4a85-816e-f456db34b46d
Abandoned checkout day 7	Templates.AbandonedCartRecovery.Day7TemplateId	4dda903a-7a33-45c4-bdbf-616cd0e2cb96

Email Inventory

Contact Form: Internal Notification

- Provider: Resend.
- Template: none. Inline HTML/text payload.
- Trigger: POST /api/contact after validation/rate limiting.
- Recipient: configured Resend:ToEmail.
- Sender: configured Resend:FromEmail.
- Reply-to: visitor email address.
- Subject: Kontakvorm: {subject}.
- Data included: name, email, subject, message.
- Failure behavior: throws if Resend is not configured or the send is rejected, causing the contact request to fail.
- Source: Shink/Services/ResendContactEmailService.cs:20, Shink/Services/ResendContactEmailService.cs:34, Shink/Program.cs:3187.

Contact Form: Customer Auto-Reply

- Provider: Resend.
- Template: shink-contact-auto-reply.
- Trigger: sent immediately after the internal contact-form notification succeeds.
- Recipient: visitor email address.
- Sender: configured Resend:FromEmail.
- Reply-to: configured support inbox.
- Variables: CONTACT_NAME_HTML, CONTACT_NAME_TEXT, CONTACT_SUBJECT_HTML, CONTACT_SUBJECT_TEXT, SUPPORT_EMAIL, SITE_URL.
- Idempotency key: hash of email, name, subject, and message.
- Failure behavior: logs warning and does not fail the original contact submission.
- Source: Shink/Services/ResendContactEmailService.cs:62, Shink/Services/ResendContactEmailService.cs:65, Shink/Services/ResendContactEmailService.cs:82.

Store Order: Internal Paid-Order Notification

- Provider: Resend.
- Template: none. Inline HTML/text payload.
- Trigger: store order payment changes to paid.
- Recipient: configured Resend:ToEmail.
- Sender: configured Resend:FromEmail.
- Reply-to: customer email.
- Subject: Store bestelling betaal: {quantity} items ({orderReference}).
- Data included: order reference, item lines, total, customer name/email/phone, delivery address, notes.
- Failure behavior: logs warning. Caller catches and logs, then continues.
- Source: Shink/Services/ResendStoreOrderNotificationService.cs:20, Shink/Services/ResendStoreOrderNotificationService.cs:47, Shink/Program.cs:4900.

Store Order: Customer Confirmation

- Provider: Resend.
- Template: shink-store-order-confirmation.
- Trigger: store order payment changes to paid.

- Recipient: customer email.
- Sender: configured Resend:FromEmail.
- Reply-to: configured support inbox.
- Variables: CUSTOMER_NAME_HTML, CUSTOMER_NAME_TEXT, ORDER_REFERENCE, ORDER_ITEMS_HTML, ORDER_ITEMS_TEXT, ORDER_TOTAL, DELIVERY_ADDRESS_HTML, DELIVERY_ADDRESS_TEXT.
- Idempotency key: store-order-confirmation/{orderReference}.
- Failure behavior: logs warning. Caller catches and logs, then continues.
- Source: Shink/Services/ResendStoreOrderNotificationService.cs:109, Shink/Services/ResendStoreOrderNotificationService.cs:128, Shink/Program.cs:4925.

Abandoned Checkout Recovery: Hour 1

- Provider: Resend.
- Template: configured AbandonedCartRecovery.Hour1TemplateId.
- Trigger: checkout is initialized for a subscription or store order and a valid customer email/reference/checkout URL exists.
- Recipient: customer email.
- Sender: configured Resend:FromEmail.
- Reply-to: configured support inbox if set.
- Schedule: 1 hour after recovery creation.
- Variables: CUSTOMER_NAME, ITEM_NAME, ITEM_SUMMARY, CART_TOTAL, CHECKOUT_URL, OPTOUT_URL, SUPPORT_EMAIL.
- Idempotency key: abandoned-cart/{recoveryId}/hour1.
- Cancellation: scheduled messages can be cancelled when recovery is resolved or opted out.
- Source: Shink/Services/SupabaseAbandonedCartRecoveryService.cs:39, Shink/Services/SupabaseAbandonedCartRecoveryService.cs:445, Shink/Services/SupabaseAbandonedCartRecoveryService.cs:754.

Abandoned Checkout Recovery: Hour 24

- Provider: Resend.
- Template: configured AbandonedCartRecovery.Hour24TemplateId.
- Trigger: same recovery sequence as hour 1.
- Recipient: customer email.
- Schedule: 24 hours after recovery creation.
- Variables: same as abandoned checkout hour 1.
- Idempotency key: abandoned-cart/{recoveryId}/hour24.
- Source: Shink/Services/SupabaseAbandonedCartRecoveryService.cs:452.

Abandoned Checkout Recovery: Day 7

- Provider: Resend.
- Template: configured AbandonedCartRecovery.Day7TemplateId.
- Trigger: same recovery sequence as hour 1.
- Recipient: customer email.
- Schedule: 7 days after recovery creation.
- Variables: same as abandoned checkout hour 1.
- Idempotency key: abandoned-cart/{recoveryId}/day7.
- Source: Shink/Services/SupabaseAbandonedCartRecoveryService.cs:459.

Subscription Payment Recovery: Day 1 Immediate Email

- Provider: Resend.
- Template: shrink-subscription-recovery-day-1.
- Trigger: failed subscription payment recovery reaches the customer-email stage. Paystack flows first defer customer emails for one next-day follow-up retry when eligible.
- Recipient: subscriber email.
- Sender: configured Resend:FromEmail.
- Reply-to: configured support inbox if set.
- Schedule: immediate when the sequence starts.
- Variables: CUSTOMER_NAME, BILLING_URL, RECOVERY_URL, RECOVERY_ACTION_LABEL, RECOVERY_CONTEXT, PLAN_NAME, PAYMENT_PROVIDER.
- Idempotency key: {recoveryId}:day1 for automatic sequence, custom admin key for manual sends.
- Source: Shink/Services/ResendSubscriptionPaymentRecoveryEmailService.cs:24, Shink/Services/ResendSubscriptionPaymentRecoveryEmailService.cs:149, Shink/Services/SupabaseSubscriptionLedgerService.cs:5966.

Subscription Payment Recovery: Day 3 Warning Email

- Provider: Resend.
- Template: shrink-subscription-recovery-day-3.
- Trigger: automatic payment recovery sequence.
- Recipient: subscriber email.
- Schedule: first failed timestamp plus 2 days.
- Variables: same as day 1 recovery email.
- Idempotency key: {recoveryId}:day3.
- Cancellation: cancelled when the payment recovery resolves.
- Source: Shink/Services/ResendSubscriptionPaymentRecoveryEmailService.cs:46, Shink/Services/ResendSubscriptionPaymentRecoveryEmailService.cs:158.

Subscription Payment Recovery: Day 5 Suspension Email

- Provider: Resend.
- Template: shrink-subscription-recovery-day-5.
- Trigger: automatic payment recovery sequence.
- Recipient: subscriber email.
- Schedule: first failed timestamp plus 4 days.
- Variables: same as day 1 recovery email.
- Idempotency key: {recoveryId}:day5.
- Cancellation: cancelled when the payment recovery resolves.
- Source: Shink/Services/ResendSubscriptionPaymentRecoveryEmailService.cs:52, Shink/Services/ResendSubscriptionPaymentRecoveryEmailService.cs:168.

Admin-Triggered Payment Recovery Email

- Provider: Resend.
- Template: day 1 recovery template, shrink-subscription-recovery-day-1.
- Trigger 1: admin clicks Send recovery email for an active recovery row.
- Trigger 2: admin clicks Send subscription recovery for a currently failed subscription.
- Recipient: subscriber email.
- Schedule: immediate.

- Variables: same as day 1 recovery email, with a Paystack recovery URL/action when resolved.
- Audit events: `recovery.email_sent` or `recovery.subscription_manual_sent`.
- Source: `Shink/Services/SupabaseAdminManagementService.cs:848`,
`Shink/Services/SupabaseAdminManagementService.cs:924`, `Shink/Components/Pages/Admin.razor:3158`.

Subscription Confirmation

- Provider: Resend.
- Template: `shink-subscription-confirmation`.
- Trigger: paid subscription is confirmed in the subscription ledger flow.
- Recipient: subscriber email.
- Sender: configured `Resend:FromEmail`.
- Reply-to: configured support inbox if set.
- Variables: `CUSTOMER_NAME_HTML`, `CUSTOMER_NAME_TEXT`, `PLAN_NAME_HTML`, `PLAN_NAME_TEXT`, `AMOUNT`, `BILLING_LABEL_HTML`, `BILLING_LABEL_TEXT`, `NEXT_RENEWAL_DATE`, `PAYMENT_PROVIDER_HTML`, `PAYMENT_PROVIDER_TEXT`, `PAYMENT_REFERENCE_HTML`, `PAYMENT_REFERENCE_TEXT`, `BILLING_URL`, `SUPPORT_EMAIL`.
- Idempotency key: `subscription-confirmation/{hash(subscriptionId)}`.
- Side effect: also sends an admin ops alert about the confirmed subscription.
- Source: `Shink/Services/ResendSubscriptionNotificationEmailService.cs:23`,
`Shink/Services/SupabaseSubscriptionLedgerService.cs:6075`.

Subscription Ended Confirmation

- Provider: Resend.
- Template: `shink-subscription-ended`.
- Trigger: subscription access ends/cancels/expires through ledger flows.
- Recipient: subscriber email.
- Variables: `CUSTOMER_NAME_HTML`, `CUSTOMER_NAME_TEXT`, `PLAN_NAME_HTML`, `PLAN_NAME_TEXT`, `STATUS_LABEL_HTML`, `STATUS_LABEL_TEXT`, `ACCESS_MESSAGE_HTML`, `ACCESS_MESSAGE_TEXT`, `ENDED_AT`, `BILLING_URL`, `SUPPORT_EMAIL`.
- Idempotency key: `subscription-ended/{hash(subscriptionId/idempotencySuffix)}`.
- Side effect: also sends an admin ops alert about the ended subscription.
- Source: `Shink/Services/ResendSubscriptionNotificationEmailService.cs:66`,
`Shink/Services/SupabaseSubscriptionLedgerService.cs:6119`.

Admin Ops Alert

- Provider: Resend.
- Template: `shink-admin-ops-alert`.
- Trigger: operational subscription/payment conditions in the ledger, including payment recovery started/skipped, subscription confirmed, subscription ended, and other ledger warnings/errors.
- Recipient: configured `Resend:ToEmail`.
- Variables: `ALERT_TITLE_HTML`, `ALERT_TITLE_TEXT`, `ALERT_SEVERITY`, `ALERT_SUMMARY_HTML`, `ALERT_SUMMARY_TEXT`, `ALERT_DETAILS_HTML`, `ALERT_DETAILS_TEXT`, `EVENT_REFERENCE_HTML`, `EVENT_REFERENCE_TEXT`, `OCCURRED_AT`, `ACTION_URL`.
- Idempotency key: `admin-ops-alert/{hash(alertKey)}`.
- Source: `Shink/Services/ResendSubscriptionNotificationEmailService.cs:107`,
`Shink/Services/SupabaseSubscriptionLedgerService.cs:6157`.

Password Reset / Recovery

- Provider: Supabase Auth, not Resend.
- Trigger 1: public POST `/api/auth/password-reset/request`.

- Trigger 2: admin subscriber detail Send password reset.
- Trigger 3: admin bulk selected subscribers Send reset.
- Recipient: account/subscriber email.
- Template: Supabase Auth recovery email template configured in Supabase, not in this repo.
- Redirect target: public flow uses /herstel-wagwoord; admin flow currently builds /reset-password.
- Audit: admin reset writes auth.password_reset_sent; public reset does not write the same app audit row.
- Source: Shink/Program.cs:2120, Shink/Services/SupabaseAuthService.cs:202, Shink/Services/SupabaseAdminManagementService.cs:770, Shink/Components/Pages/Admin.razor:214.

Email Address Change Confirmation

- Provider: Supabase Auth, not Resend.
- Trigger: signed-in user submits an email change from /intekening-en-betaling.
- Recipient: Supabase-controlled confirmation email(s). Depending on Supabase project settings, this can require confirmation on the new email and sometimes both old/new addresses.
- Template: Supabase Auth email-change template configured in Supabase, not in this repo.
- Redirect target: /intekening-en-betaling?emailChange=complete&emailChangeState=...
- Source: Shink/Program.cs:2199, Shink/Services/SupabaseAuthService.cs:410, Shink/Services/SupabaseAuthService.cs:928.

Possible Signup Confirmation Fallback

- Provider: Supabase Auth, not Resend.
- Trigger: public signup only if the Supabase admin create-user endpoint is unavailable.
- Normal current path: when Supabase:SecretKey is configured, signup calls the admin create-user endpoint with email_confirm: true, which creates a confirmed user and should not require a confirmation email.
- Fallback path: if admin create-user is not available, the code posts to auth/v1/signup; Supabase may send its configured confirmation email depending on project Auth settings.
- Source: Shink/Services/SupabaseAuthService.cs:130, Shink/Services/SupabaseAuthService.cs:139, Shink/Services/SupabaseAuthService.cs:775.

Trigger Map

Trigger	Emails sent
Visitor submits contact form	Internal contact notification, then contact auto-reply
Store Paystack order becomes paid	Internal paid-order notification, customer order confirmation
Subscription checkout starts but is not completed	Abandoned checkout hour 1, hour 24, day 7 sequence
Store checkout starts but is not completed	Abandoned checkout hour 1, hour 24, day 7 sequence
Subscription payment fails and recovery proceeds	Subscription payment recovery day 1, day 3, day 5; admin ops alert
Admin manually sends active recovery	Subscription payment recovery day 1 template
Admin manually sends recovery for failed subscription	Subscription payment recovery day 1 template
Paid subscription is confirmed	Customer subscription confirmation, admin ops alert
Subscription access ends	Customer subscription ended confirmation, admin ops alert
User requests password reset	Supabase Auth recovery email
Admin sends password reset	Supabase Auth recovery email
User requests email address change	Supabase Auth email-change confirmation email(s)
Public signup fallback without admin create-user	Possible Supabase Auth signup confirmation

Non-Email Notification Paths

The codebase also contains in-app notification services and UI notification-center code. Those are not email sends and are excluded from this report.

Payment providers such as Paystack/PayFast may send their own receipts outside this app, but this report only covers emails initiated by the Shink-Stories system code.

Notes and Risks

- The report is source-based. It does not confirm which Resend templates are published in the live Resend account or which Supabase Auth templates are active.
- Two Resend sends are inline payloads, not published Resend templates: contact-form internal notification and store paid-order internal notification.
- The admin password reset link is built as `/reset-password`, while the public reset page/route is `/herstel-wagwoord`; this may be intentional legacy compatibility, but it is worth verifying before relying on admin resets.
- Abandoned-checkout recovery templates are UUIDs in `Shink/appsettings.json`, while `root appsettings.json` does not include those abandoned-checkout template IDs.
- Customer-facing recovery emails use idempotency keys and store/cancel scheduled Resend message IDs where applicable, which helps avoid duplicate recovery sequences.