Internet Peering


Andrej Šišila, Marián Vachalík

Obsah

1.1	Topológia				
1.2	Úlohy		5		
	1.2.1	Použiť IGP IS–IS (L2 only) single area dizajn, priame p2p			
		prepojenia	5		
	1.2.2	Zabezpečiť plnú konektivitu prostredníctvom iBGP alebo			
		eBGP protokolov pre zákaznícké a internetové smerovacie			
		záznamy	15		
	1.2.3	Distribúcia internetových statických smerovacích záznamov			
		z AS3401, AS4502 a zákaznických smerovacích záznamov z			
		AS65001, AS5005, AS330	15		
	1.2.4	Prepísať privátne AS65001	15		
	1.2.5	Sumarizácia	15		
	1.2.6	Kontrola, či interné ISP adresy nie sú propagované	15		
	1.2.7	Kontrola konektivity medzi zákazníckymi a internetovými			
		smerovacími záznamami	15		
	1.2.8	ISP politika	15		
	1.2.9	Definovať vlastnú politiku – použiť community, commu-			
		nity alter LP, AS-PATH filtering, prepending, atd'	15		
	1.2.10	Primárne linky R3–R8, R4–R10	15		
	1.2.11	Distribuovať iba default, AS5005 a peering prefixy do AS65001	15		
	1.2.12	AS5005 nesme byť nikdy transit	15		
	1.2.13	Peering iba pre ISP1 a ISP2, nie pre prefixy naučené z Ups-			
		tream ISP	15		
	1.2.14	Overiť funkčnosť nastavenia politiky vhodnými výpadkami			
		liniek a smerovačov	15		
	1.2.15	Overiť, či je možné odkloniť celú prevádzku (upstream, do-			
		wnstream) na linke R4-R10 v prípade plánovanej údržby			
		(linka musí byť plne funkčna a BGP spojenie propaguje všetky			
		prefixy)	15		

1.1 Topológia

Budeme konfigurovať smerovacie protokoly BGP a IS-IS na topológií, ktorá je znázornená na obrázku 1. Vrámci autonómnych systémov sme konfigurovali smerovacie protokoly IS-IS a BGP (iBGP). Medzi autonómnymi systémami sme konfigurovali len BGP (eBGP). IP adresácia je uvedená v tabuľke 1 a dopĺňa grafické znázornenie topológie na obrázku 1. Sieť medzi smerovačmi R1 a R5 nemá mať masku "/48" ale "/30".



Obr. 1: Topológia BGP

Tabuľka 1: IP adresácia

Smerovač	Rozhranie	<u>(a 1: IP adresácia</u> IP adresa	Maska
Smerovac			IVIASKA
	Fa0/0	200.110.255.249	
D1	Fa0/1	64.34.255.253	
R1	S1/0	200.33.255.253	255 255 255 255
	Lo0	10.255.255.1	255.255.255
	Lo1	64.34.1.1	
	Fa0/0	200.110.255.250	
De	Fa0/1.23	10.110.23.2	
R2	Fa0/1.24	10.110.24.2	
	S1/0	200.110.255.253	255 255 255 255
	Lo0	10.255.255.2	255.255.255
	Fa0/0	200.110.255.241	
R3	Fa0/1.23	10.110.23.3	
	Fa0/1.34	10.110.34.3	
	Lo0	10.255.255.3	255.255.255.255
	Fa0/0	200.110.255.237	
	Fa0/1.24	10.110.24.4	
R4	Fa0/1.34	10.110.34.4	
	S1/0	200.110.255.245	
	Lo0	10.255.255.4	255.255.255.255
	Fa0/0	200.33.255.249	
	Fa0/1	10.100.15.2	
R5	S1/0	200.110.255.254	
	Lo0	10.255.255.5	255.255.255
	Lo1	128.45.5.1	
	Fa0/0	200.33.255.250	
	Fa0/1	10.110.67.6	
R6	S1/0	200.33.255.254	
	Lo0	10.255.255.6	255.255.255.255
	Lo1	200.33.6.1	
	Fa0/1	10.110.67.7	
D7	S1/1	200.33.255.245	
R7	Lo0	10.255.255.7	255.255.255.255
	Lo1	200.33.7.1	
	Fa0/0	200.110.255.242	
Do	Fa0/1	10.110.89.8	
R8	Lo0	10.255.255.8	255.255.255.255
	Lo1	200.110.12.1	
	Fa0/0	200.110.255.238	
DO.	Fa0/1	10.110.89.9	
R9	Lo0	10.255.255.9	255.255.255.255
	Lo1	200.110.13.1	
	S1/0	200.110.255.246	
D40	S1/1	200.33.255.246	
R10	Lo0	10.255.255.10	255.255.255.255
	Lo1	223.255.255.1	
			<u> </u>

1.2 Úlohy

1.2.1 Použif IGP IS—IS (L2 only) single area dizajn, priame p2p prepojenia

Popis

Dohodli sme sa, že vnútri autonómneho systému budeme používať iba smerovací protokol IS-IS. Medzi autonómnymi systémami používame smerovací protokol BGP. Subrozhranie ".13" a VLAN 13 sme premenovali na ".23" a VLAN 23, lebo sieť je medzi smerovačmi R2 a R3 (23), a nie medzi R1 a R3 (13).

Konfigurácia

```
R1
ena
conf t
hostname R1
no ip domain-lookup
username admin privil 15 secret admin
line con 0
  login local
  logging syn
  exec-time 120
line vty 0 15
  privilege level 15
  no login
int f0/0
  ip addr 200.110.255.249 255.255.255.252
 no shut
int f0/1
  ip addr 64.34.255.253 255.255.255.252
  no shut
int s1/0
  ip addr 200.33.255.253 255.255.255.252
  no shut
int lo0
  ip addr 10.255.255.1 255.255.255
  no shut
int lo1
  ip addr 64.34.1.1 255.255.255.0
  no shut
router bgp 3401
  neighbor 64.34.255.254 remote-as 4502
  neighbor 200.33.255.254 remote-as 330
  neighbor 200.110.255.250 remote-as 110
  network 10.255.255.1 mask 255.255.255.255
  no auto-summary
  no sync
  bgp log-neighbor-changes
```

```
R2
ena
conf t
hostname R2
no ip domain-lookup
username admin privil 15 secret admin
line con 0
  login local
  logging syn
  exec-time 120
line vty 0 15
  privilege level 15
  no login
int f0/0
  ip addr 200.110.255.250 255.255.255.252
  no shut
int f0/1
  no ip add
  isis network point-to-point
  no sh
int f0/1.23
  encap dot1q 23
  ip addr 10.110.23.2 255.255.255.0
  ip router isis
int f0/1.24
  encap dot1q 24
  ip addr 10.110.24.2 255.255.255.0
  ip router isis
int s1/0
  ip addr 200.110.255.253 255.255.255.252
  no shut
int 100
  ip addr 10.255.255.2 255.255.255
  ip router isis
  no shut
router isis
  net 49.0001.0102.5525.5002.00
  passive-interface lo0
 passive-interface f0/0
 redistribute static
  redistribute connected
  is-type level-2
 metric-style wide
  exit
router bgp 110
  neighbor 10.255.255.3 remote-as 110
  neighbor 10.255.255.3 update-source lo0
  neighbor 10.255.255.4 remote-as 110
```

```
neighbor 10.255.255.4 update-source lo0
neighbor 200.110.255.249 remote-as 3401
neighbor 200.110.255.254 remote-as 4502
network 10.255.255.2 mask 255.255.255.255
no auto-summary
no sync
bgp log-neighbor-changes
```

```
R3
ena
conf t
hostname R3
no ip domain-lookup
username admin privil 15 secret admin
line con 0
  login local
  logging syn
  exec-time 120
line vty 0 15
  privilege level 15
  no login
int f0/0
  ip addr 200.110.255.241 255.255.255.252
  no shut
int f0/1
  no ip addr
  isis network point-to-point
  no shut
int f0/1.23
  encap dot1q 23
  ip addr 10.110.23.3 255.255.255.0
  ip router isis
int f0/1.34
  encap dot1q 34
  ip addr 10.110.34.3 255.255.255.0
  ip router isis
int 100
  ip addr 10.255.255.3 255.255.255.255
  ip router isis
  no shut
router isis
  net 49.0001.0102.5525.5003.00
  passive-interface 100
  passive-interface f0/0
  redistribute static
  redistribute connected
  is-type level-2
  metric-style wide
  exit
```

```
router bgp 110
  neighbor 10.255.255.2 remote-as 110
  neighbor 10.255.255.2 update-source lo0
  neighbor 10.255.255.4 remote-as 110
  neighbor 10.255.255.4 update-source lo0
  neighbor 200.110.255.242 remote-as 65001
 network 10.255.255.3 mask 255.255.255.255
 no auto-summary
 no sync
 bgp log-neighbor-changes
R4
ena
conf t
hostname R4
no ip domain-lookup
username admin privil 15 secret admin
line con 0
  login local
  logging syn
  exec-time 120
line vty 0 15
 privilege level 15
  no login
int f0/0
  ip addr 200.110.255.237 255.255.252
  no shut
int f0/1
  no ip addr
  isis network point-to-point
  no sh
int f0/1.24
  encap dot1q 24
  ip addr 10.110.24.4 255.255.255.0
  ip router isis
int f0/1.34
  encap dot1q 34
  ip addr 10.110.34.4 255.255.255.0
  ip router isis
int s1/0
  ip addr 200.110.255.245 255.255.255.252
  no shut
int lo0
  ip addr 10.255.255.4 255.255.255.255
  ip router isis
  no shut
router isis
```

net 49.0001.0102.5525.5004.00

```
passive-interface 100
  passive-interface f0/0
  passive-interface s1/0
  redistribute static
  redistribute connected
  is-type level-2
  metric-style wide
  exit
router bgp 110
  neighbor 10.255.255.2 remote-as 110
  neighbor 10.255.255.2 update-source lo0
  neighbor 10.255.255.3 remote-as 110
  neighbor 10.255.255.3 update-source lo0
  neighbor 200.110.255.238 remote-as 65001
  neighbor 200.110.255.246 remote-as 5005
  network 10.255.255.4 mask 255.255.255.255
  no auto-summary
  no sync
  bgp log-neighbor-changes
R5
ena
conf t
hostname R5
no ip domain-lookup
username admin privil 15 secret admin
line con 0
  login local
  logging syn
  exec-time 120
line vty 0 15
 privilege level 15
  no login
int f0/0
  ip addr 200.33.255.249 255.255.255.252
  no shut
int f0/1
  ip addr 64.34.255.254 255.255.255.252
 no shut
int s1/0
  ip addr 200.110.255.254 255.255.255.252
 no shut
int lo0
  ip addr 10.255.255.5 255.255.255
  no shut
int lo1
  ip addr 128.45.5.1 255.255.255.0
  no shut
router bgp 4502
  neighbor 200.33.255.250 remote-as 330
```

```
neighbor 200.110.255.253 remote-as 110 neighbor 64.34.255.253 remote-as 3401 network 10.255.255.5 mask 255.255.255.255 no auto-summary no sync bgp log-neighbor-changes
```

```
R6
ena
conf t
hostname R6
no ip domain-lookup
username admin privil 15 secret admin
line con 0
  login local
  logging syn
  exec-time 120
line vty 0 15
  privilege level 15
  no login
int f0/0
  ip addr 200.33.255.250 255.255.255.252
  no shut
int f0/1
  ip addr 10.110.67.6 255.255.255.0
  ip router isis
  isis network point-to-point
  no shut
int s1/0
  ip addr 200.33.255.254 255.255.255.252
  no shut
int 100
  ip addr 10.255.255.6 255.255.255.255
  ip router isis
  no shut
int lo1
  ip add 200.33.6.1 255.255.255.0
  ip router isis
router isis
  net 49.0001.0102.5525.5006.00
  passive-interface 100
  passive-interface lo1
 passive-interface f0/0
 passive-interface s1/0
 redistribute static
  redistribute connected
  is-type level-2
 metric-style wide
```

```
exit
router bgp 330
  neighbor 10.255.255.7 remote-as 330
  neighbor 10.255.255.7 update-source lo0
  neighbor 200.33.255.253 remote-as 3401
  neighbor 200.33.255.249 remote-as 4502
  network 10.255.255.6 mask 255.255.255.255
  no auto-summary
 no sync
  bgp log-neighbor-changes
R7
ena
conf t
hostname R7
no ip domain-lookup
username admin privil 15 secret admin
line con 0
  login local
  logging syn
  exec-time 120
line vty 0 15
 privilege level 15
  no login
int f0/1
  ip addr 10.110.67.7 255.255.255.0
  ip router isis
  isis network point-to-point
  no shut
int s1/1
  ip addr 200.33.255.245 255.255.255.252
  no shut
int 100
  ip addr 10.255.255.7 255.255.255
  ip router isis
 no shut
int lo1
  ip addr 200.33.7.1 255.255.255.0
  ip router isis
  no shut
router isis
  net 49.0001.0102.5525.5007.00
  passive-interface 100
  passive-interface lo1
 passive-interface s1/1
  redistribute static
  redistribute connected
  is-type level-2
  metric-style wide
```

```
exit
router bgp 330
  neighbor 10.255.255.6 remote-as 330
  neighbor 10.255.255.6 update-source lo0
  neighbor 200.33.255.246 remote-as 5005
  network 10.255.255.7 mask 255.255.255.255
 no auto-summary
  no sync
  bgp log-neighbor-changes
R8
ena
conf t
hostname R8
no ip domain-lookup
username admin privil 15 secret admin
line con 0
  login local
  logging syn
  exec-time 120
line vty 0 15
 privilege level 15
  no login
int f0/0
  ip addr 200.110.255.242 255.255.255.252
  no shut
int f0/1
  ip addr 10.110.89.8 255.255.255.0
  Ip router isis
  isis network point-to-point
  no shut
int 100
  ip addr 10.255.255.8 255.255.255.255
  ip router isis
  no shut
int lo1
  ip add 200.110.12.1 255.255.255.0
  ip router isis
router isis
  net 49.0001.0102.5525.5008.00
  passive-interface 100
  passive-interface lo1
 passive-interface f0/0
  redistribute static
 redistribute connected
  is-type level-2
 metric-style wide
```

exit

```
router bgp 65001
neighbor 10.255.255.9 remote-as 65001
neighbor 10.255.255.9 update-source lo0
neighbor 200.110.255.241 remote-as 110
network 10.255.255.8 mask 255.255.255.255
network 200.110.12.0 mask 255.255.255.0
no auto-summary
no sync
bgp log-neighbor-changes
```

```
R9
ena
conf t
hostname R9
no ip domain-lookup
username admin privil 15 secret admin
line con 0
  login local
  logging syn
  exec-time 120
line vty 0 15
 privilege level 15
  no login
int f0/0
  ip addr 200.110.255.238 255.255.255.252
  no sh
int f0/1
  ip addr 10.110.89.9 255.255.255.0
  ip router isis
  isis network point-to-point
  no shut
int 100
  ip addr 10.255.255.9 255.255.255.255
  ip router isis
  no shut
int lo1
  ip addr 200.110.13.1 255.255.255.0
  ip router isis
 no shut
router isis
  net 49.0001.0102.5525.5009.00
  passive-interface lo0
 passive-interface lo1
 passive-interface f0/0
  redistribute static
  redistribute connected
  is-type level-2
```

```
metric-style wide
exit
router bgp 65001
neighbor 10.255.255.8 remote-as 65001
neighbor 10.255.255.8 update-source lo0
neighbor 200.110.255.237 remote-as 110
network 10.255.255.9 mask 255.255.255
network 200.110.13.0 mask 255.255.255.0
no auto-summary
no sync
bgp log-neighbor-changes

R10
ena
conf t
```

bgp log-neighbor-changes

Overenie

- 1.2.2 Zabezpečiť plnú konektivitu prostredníctvom iBGP alebo eBGP protokolov pre zákaznícké a internetové smerovacie záznamy
- 1.2.3 Distribúcia internetových statických smerovacích záznamov z AS3401, AS4502 a zákaznických smerovacích záznamov z AS65001, AS5005, AS330
- 1.2.4 Prepísať privátne AS65001
- 1.2.5 Sumarizácia
- 1.2.6 Kontrola, či interné ISP adresy nie sú propagované
- 1.2.7 Kontrola konektivity medzi zákazníckymi a internetovými smerovacími záznamami
- 1.2.8 ISP politika
- 1.2.9 Definovať vlastnú politiku použiť community, community alter LP, AS-PATH filtering, prepending, atď
- 1.2.10 Primárne linky R3-R8, R4-R10
- 1.2.11 Distribuovať iba default, AS5005 a peering prefixy do AS65001
- 1.2.12 AS5005 nesme byf nikdy transit
- 1.2.13 Peering iba pre ISP1 a ISP2, nie pre prefixy naučené z Upstream ISP
- 1.2.14 Overiť funkčnosť nastavenia politiky vhodnými výpadkami liniek a smerovačov
- 1.2.15 Overiť, či je možné odkloniť celú prevádzku (upstream, downstream) na linke R4-R10 v prípade plánovanej údržby (linka musí byť plne funkčna a BGP spojenie propaguje všetky prefixy)