245--Lab - Administración de archivos de registro

En esta práctica se muestra como checar el archivo de registro referente a la seguridad del sistema, así como el uso del comando *lastlog* para ver detalles del último inicio de sesión de los usuarios.

Revisar el archivo de registro de la seguridad

El archivo de registro /var/log/secure almacena información de autenticación para distribuciones derivadas de Red Hat.

Para verificar el contenido ejecutar *sudo less /tmp/log/secure*

```
ec2-user@ip-10-0-10-205:~/companyA
[ec2-user@ip-10-0-10-205 companyA]$ sudo less /tmp/log/secure
Aug 23 03:47:13 centos7 sshd[3283]: Invalid user guest from 193.201.224.218
Aug 23 03:47:13 centos7 sshd[3283]: input_userauth_request: invalid user guest [preauth]
Aug 23 03:47:13 centos7 sshd[3283]: pam_unix(sshd:auth): check pass; user unknown
Aug 23 03:47:13 centos7 sshd[3283]: pam_unix(sshd:auth): authentication failure; logname= uid=0 euid=0 tty=ssh
ruser= rhost=193.201.224.218
Aug 23 03:47:15 centos7 sshd[3283]: Failed password for invalid user guest from 193.201.224.218 port 13181 ssh2
Aug 23 03:47:16 centos7 sshd[3283]: pam_unix(sshd:auth): check pass; user unknown
Aug 23 03:47:17 centos7 sshd[3283]: Failed password for invalid user guest from 193.201.224.218 port 13181 ssh2
Aug 23 03:47:18 centos7 sshd[3283]: pam_unix(sshd:auth): check pass; user unknown
Aug 23 03:47:20 centos7 sshd[3283]: Failed password for invalid user guest from 193.201.224.218 port 13181 ssh2
Aug 23 03:47:24 centos7 sshd[3283]: pam_unix(sshd:auth): check pass; user unknown
Aug 23 03:47:25 centos7 sshd[3283]: Failed password for invalid user guest from 193.201.224.218 port 13181 ssh2
Aug 23 03:47:26 centos7 sshd[3283]: pam_unix(sshd:auth): check pass; user unknown
Aug 23 03:47:27 centos7 sshd[3283]: Failed password for invalid user guest from 193.201.224.218 port 13181 ssh2
Aug 23 03:47:27 centos7 sshd[3283]: pam_unix(sshd:auth): check pass; user unknown
Aug 23 03:47:29 centos7 sshd[3283]: Failed password for invalid user guest from 193.201.224.218 port 13181 ssh2
Aug 23 03:47:29 centos7 sshd[3283]: Disconnecting: Too many authentication failures for guest [preauth]
Aug 23 03:47:13 centos7 sshd[3283]: Invalid user guest from 193.201.224.218
Aug 23 03:52:40 centos7 sshd[5160]: Invalid user acc from 193.201.224.218
Aug 23 03:52:45 centos7 sshd[5243]: Invalid user adam from 193.201.224.218
Aug 23 03:52:53 centos7 sshd[5312]: Invalid user adfexc from 193.201.224.218
Aug 23 03:53:45 centos7 sshd[5494]: Invalid user admin2 from 193.201.224.218
Aug 23 03:53:45 centos7 sshd[5494]: pam_unix(sudo:session): session opened for user root by (uid=0)
Aug 23 03:53:45 centos7 sshd[5494]: pam_succeed_if(sudo:session): 'uid' resolves to '0'
Aug 23 03:53:45 centos7 sshd[5494]: pam_succeed_if(sudo:session): 'user' resolves to 'root'
Aug 23 03:53:45 centos7 sshd[5494]: pam_succeed_if(sudo:session): 'ruser' resolves to 'telegraf'
Aug 23 03:53:45 centos7 sshd[5494]: pam_unix(sudo:session): session closed for user root
```

Podemos ver los intentos fallidos de autenticación con la IP de origen y el puerto.

El comando *less* es un visor de archivos de texto que permite navegar por el contenido de un archivo de forma interactiva.

Para salir de *less* teclear q.

Ahora verificamos el último inicio de sesión de cada uno de los usuarios del sistema con el comando *lastlog*

```
ec2-user@ip-10-0-10-205:~/companyA
[ec2-user@ip-10-0-10-205 companyA]$ sudo lastlog
Username         Port     From             Latest
root                                       **Never logged in**
bin                                        **Never logged in**
daemon                                     **Never logged in**
adm                                        **Never logged in**
lp                                         **Never logged in**
sync                                       **Never logged in**
shutdown                                   **Never logged in**
halt                                       **Never logged in**
mail                                       **Never logged in**
operator                                   **Never logged in**
games                                      **Never logged in**
ftp                                        **Never logged in**
nobody                                     **Never logged in**
systemd-network                            **Never logged in**
dbus                                       **Never logged in**
rpc                                        **Never logged in**
libstoragemgmt                             **Never logged in**
sshd                                       **Never logged in**
rpcuser                                    **Never logged in**
nfsnobody                                  **Never logged in**
ec2-instance-connect                           **Never logged in**
postfix                                    **Never logged in**
rngd                                       **Never logged in**
chrony                                     **Never logged in**
tcpdump                                    **Never logged in**
ec2-user         pts/0    187.175.31.44    Mon Dec 22 21:45:46 +0000 2025
ljuan                                      **Never logged in**
mmajor                                     **Never logged in**
mjackson                                   **Never logged in**
eowusu                                     **Never logged in**
nwolf                                      **Never logged in**
arosalez                                   **Never logged in**
jdoe                                       **Never logged in**
psantos                                    **Never logged in**
smartinez                                  **Never logged in**
ssarkar                                    **Never logged in**
```

Notar que el único usuario que ha iniciado sesión es ec2-user.

Desafío adicional

¿Qué información se puede extraer para fines de negocio?

En la instancia se ha registrado (como IP de origen) la dirección IP pública de mi máquina de Windows desde la que me conecté:

```
C:\Users\ckaro>curl ifconfig.me
187.175.31.44
```

Saber la dirección IP de alguien que intenta forzar el acceso al servidor puede ser útil para defensa e inteligencia de amenazas. La utilidad más directa es poder bloquear el origen de manera selectiva, mediante un firewall.

Asimismo, conocer la IP de origen de los usuarios que acceden a nuestros servicios puede aportar un valor estratégico significativo para el negocio.

Algunas aplicaciones pueden ser:

- **Geolocalización y personalización.-** A través de bases de datos de geolocalización (GeoIP), puedes saber en qué país, ciudad o región se encuentra el cliente.
- **Seguridad y prevención de fraude.-** Se pueden detectar comportamientos sospechosos y así bloqueas las IPs. También se pueden definir controles de acceso.
- **Identificación de empresas**.- Muchas empresas tienen rangos de IP fijos. Existen herramientas que analizan la IP de los visitantes para verificar de donde provienen.