
rinoh^{type}

Reference Guide

Release 0.5.4

Contents

5	Chapter 1: rinoh
7	Chapter 2: Sphinx Builder
8	Legacy Configuration Variables
11	Chapter 3: Style Sheets
11	Included Style Sheets
11	Default Matcher
17	Element Style Classes
89	Chapter 4: Standard Document Templates
89	Article
91	Book
95	Chapter 5: API Documentation
95	Attribute (<code>rinoh.attribute</code>)
96	Color (<code>rinoh.color</code>)
96	Dimension (<code>rinoh.dimension</code>)
97	Document (<code>rinoh.document</code>)
98	Drawing Primitives (<code>rinoh.draw</code>)
99	Flowable (<code>rinoh.flowable</code>)
101	Fonts and Typefaces (<code>rinoh.font</code>)
103	Images and Figures (<code>rinoh.image</code>)
105	Index (<code>rinoh.index</code>)
105	Language (<code>rinoh.language</code>)
110	Number (<code>rinoh.number</code>)
111	Paper sizes (<code>rinoh.paper</code>)
112	Paragraph (<code>rinoh.paragraph</code>)
116	Cross-References and Fields (<code>rinoh.reference</code>)
117	Structure (<code>rinoh.structure</code>)
120	Strings (<code>rinoh.strings</code>)
120	Style (<code>rinoh.style</code>)
122	Tables (<code>rinoh.table</code>)

123 Templates (`rinoh.template`)

133 **Python Module Index**

135 **Index**

Render a structured document to PDF.

```
usage: rinoh [-h] [-f FORMAT] [-o OPTION=VALUE] [-t NAME or FILENAME]
             [-s NAME or FILENAME] [-O FILENAME or DIRECTORY] [-p PAPER] [-i]
             [--list-templates] [--list-stylesheets] [--list-fonts]
             [FILENAME]
             [--list-formats] [--list-options FRONTEND] [--version] [--docs]
             [input]
```

input

the document to render

-h, --help

show this help message and exit

-f <format>, --format <format>

the format of the input file (default: autodetect)

-o <option=value>, --option <option=value>

options to be passed to the input file reader

-t <name or filename>, --template <name or filename>

the document template or template configuration file to use (default: article)

-s <name or filename>, --stylesheet <name or filename>

the style sheet used to style the document elements (default: the template's default)

-O <filename or directory>, --output <filename or directory>

write the PDF output to FILENAME or to an existing DIRECTORY with a filename derived from the input filename (default: the current working directory)

-p <paper>, --paper <paper>

the paper size to render to (default: the template's default)

-i, --install-resources

automatically install missing resources (fonts, templates, style sheets) from PyPI

--list-templates

list the installed document templates and exit

--list-stylesheets

list the installed style sheets and exit

--list-fonts <filename>
list the installed fonts or, if FILENAME is given, write a PDF file displaying all the fonts

--list-formats
list the supported input formats and exit

--list-options <frontend>
list the options supported by the given frontend and exit

--version
show program's version number and exit

--docs
open the online documentation in the default browser

`rinoh.frontend.sphinx` is a Sphinx extension module. It provides a Sphinx builder with the name *rinoh*. The builder recognizes the following `conf.py` options. Of these, only `rinoh_documents` (or `latex_documents`) is required.

rinoh_documents

Determines which PDF documents to build. Its format is a list of dictionaries, one for each document to be generated. The supported keys for these dictionaries are listed below. Two of them are required:

doc (required)

String that specifies the name of the master document (typically `index`).

target (required)

The name of the target PDF file without the extension.

The following keys allow overriding the content included on the document's title page and page headers/footers (depending on the template and its configuration). The values for text content can be plain text or `StyledText`.

logo (no default)

Path (absolute or relative to the location of the `conf.py` file) to an image file, typically included on the title page.

title (default: "project documentation")

The title of the document.

subtitle (default: "Release release")

Subtitle of the document.

author (default: "author")

The document's author.

date (default: determined from today and today_fmt)

The document (build) date.

The remaining keys control what is included in the document and the document template (configuration) to use.

toctree_only (default: False)

Must be `True` or `False`. If `true`, the document itself is not included in the output, only the documents referenced by it via TOC trees.

domain_indices (default: True)

If `true`, generate domain-specific indices in addition to the general index. It is equivalent to the `html_domain_indices` and `latex_domain_indices` configuration variables.

template (default: Book)

Determines the template used to render the document. It takes:

- the filename of a template configuration file,
- a `TemplateConfiguration` instance,

- the name of an installed template (see `rinoh --list-templates`), or
- a `DocumentTemplate` subclass

`rinoh_documents` will also accept other keys than those listed above. These items will be available as document metadata and can be used in a custom document template.

Example:

```
rinoh_documents = [
    dict(doc='index', target='manual', toctree_only=False,
         template='manual.rtt', logo='logo.pdf'),
    dict(doc='ref', target='reference', title='Reference Manual',
         template='reference.rtt', stamp='DRAFT'),
]
```

`rinoh_targets`

Limits rendering to the specified set of targets. This variable accepts either a list of strings or a string containing comma-separated values. The target names should match those set in `rinoh_documents`.

To render only the ‘manual’ target, you can set the following in `conf.py`:

```
rinoh_targets = ['manual']
```

The same can be achieved from the command line using the by using the string form with `sphinx-build -D`:

```
sphinx-build -b rinoh -D rinoh_targets="manual" source build
```

2.1 Legacy Configuration Variables

The configuration variables below are no longer supported. Instead, their functionality can now be configured per document in `rinoh_documents`.

`rinoh_template`

This configuration variable is **no longer supported** since the document template can be specified in `rinoh_documents` entries.

`rinoh_stylesheet`

This configuration variable is **no longer supported** since it is not obvious which style sheet will be used when the template configuration also specifies a style sheet. Please specify the style sheet to use in your template configuration file:

```
[TEMPLATE_CONFIGURATION]
name = My Book
template = book
stylesheet = my_stylesheet.rts
```

`rinoh_paper_size`

This configuration variable is **no longer supported** since it was not obvious which paper size was being used when the template configuration (`rinoh_template`) also specified a paper size. Please specify the `paper_size` to use in your template configuration file:

```
[TEMPLATE_CONFIGURATION]
name = My Book
template = book

[VARIABLES]
```



```
paper_size = A5
```

rinoh_logo

This configuration variable is **no longer supported** since the logo can be specified in the `rinoh_documents` entries.

rinoh_domain_indices

This configuration variable is **no longer supported** since the `domain_indices` can be specified in the `rinoh_documents` entries.

rinoh_metadata

This configuration variable is **no longer supported**. Metadata entries can now be added to `rinoh_documents` entries.

3.1 Included Style Sheets

These style sheets are included with rinohtype:

`rinohtype.stylesheets.sphinx`

Mostly a copy of the LaTeX style included with Sphinx

Entry point name: `sphinx`

`rinohtype.stylesheets.sphinx_article`

The Sphinx stylesheet adjusted for the article template

Entry point name: `sphinx_article`

`rinohtype.stylesheets.sphinx_base14`

The Sphinx stylesheet, but using the fonts from the PDF core set (yielding smaller PDF files)

Entry point name: `sphinx_base14`

Additional style sheets can be installed from PyPI. The installed style sheets can be listed using `rinohtype --list-stylesheets`.

3.2 Default Matcher

The default matcher provides the selectors for the styles used in the standard style sheets.

`rinohtype.stylesheets.matcher`

The default matcher defines the following styles

- title page rule: `HorizontalRuleStyle`
- title page logo: `FlowableStyle`
- title page title: `ParagraphStyle`
- title page subtitle: `ParagraphStyle`
- title page author: `ParagraphStyle`
- title page date: `ParagraphStyle`
- title page extra: `ParagraphStyle`
- front matter section title: `ParagraphStyle`
- body matter chapter label: `ParagraphStyle`
- body matter chapter number: `TextStyle`
- body matter chapter title: `ParagraphStyle`
- fallback: `TextStyle`
- italic: `TextStyle`

- **bold:** TextStyle
- **monospaced:** TextStyle
- **emphasis:** TextStyle
- **strong:** TextStyle
- **literal emphasis:** TextStyle
- **literal strong:** TextStyle
- **inline math:** TextStyle
- **inline definition:** TextStyle
- **quote:** TextStyle
- **file path:** TextStyle
- **keystrokes:** TextStyle
- **regular expression:** TextStyle
- **code with variable:** TextStyle
- **mail header:** TextStyle
- **MIME type:** TextStyle
- **newsgroup:** TextStyle
- **command:** TextStyle
- **make variable:** TextStyle
- **program:** TextStyle
- **man page:** TextStyle
- **window title:** TextStyle
- **UI control:** TextStyle
- **UI control accelerator:** TextStyle
- **menu cascade:** TextStyle
- **draft comment:** TextStyle
- **title reference:** TextStyle
- **error:** TextStyle
- **linked reference:** ReferenceStyle
- **external hyperlink:** TextStyle
- **broken hyperlink:** TextStyle
- **glossary inline definition:** TextStyle
- **body:** ParagraphStyle
- **code block:** ParagraphStyle
- **code block caption:** CaptionStyle
- **math block:** ParagraphStyle
- **graphviz code block:** ParagraphStyle
- **attribution:** ParagraphStyle
- **centered:** ParagraphStyle
- **line block:** ParagraphStyle
- **block quote:** GroupedFlowablesStyle
- **chapter:** SectionStyle
- **content chapter:** SectionStyle
- **heading level 1:** HeadingStyle
- **heading level 1 label:** TextStyle
- **unnumbered heading level 1:** HeadingStyle
- **heading level 2:** HeadingStyle
- **heading level 2 label:** TextStyle
- **unnumbered heading level 2:** HeadingStyle
- **heading level 3:** HeadingStyle
- **heading level 3 label:** TextStyle
- **unnumbered heading level 3:** HeadingStyle
- **heading level 4:** HeadingStyle
- **heading level 4 label:** TextStyle

- unnumbered heading level 4: HeadingStyle
- heading level 5: HeadingStyle
- heading level 5 label: TextStyle
- unnumbered heading level 5: HeadingStyle
- other heading levels: HeadingStyle
- appendix: SectionStyle
- appendix heading level 1: HeadingStyle
- appendix heading level 2: HeadingStyle
- appendix heading level 3: HeadingStyle
- appendix heading level 4: HeadingStyle
- appendix heading level 5: HeadingStyle
- title: ParagraphStyle
- prerequisites: GroupedFlowablesStyle
- prerequisites title: ParagraphStyle
- post requirement: GroupedFlowablesStyle
- abstract: GroupedFlowablesStyle
- abstract paragraph: ParagraphStyle
- example: GroupedFlowablesStyle
- example title: ParagraphStyle
- topic: GroupedFlowablesStyle
- topic title: ParagraphStyle
- rubric: ParagraphStyle
- sidebar: GroupedFlowablesStyle
- sidebar title: ParagraphStyle
- sidebar subtitle: ParagraphStyle
- list item label: ListItemLabelStyle
- list item body: GroupedFlowablesStyle
- list item paragraph: ParagraphStyle
- enumerated list: ListStyle
- enumerated list item: LabeledFlowableStyle
- enumerated list item label: ListItemLabelStyle
- nested enumerated list: ListStyle
- (table) enumerated list: ListStyle
- (table) enumerated list item: LabeledFlowableStyle
- (table) enumerated list item label: ListItemLabelStyle
- bulleted list: ListStyle
- compact bulleted list: ListStyle
- bulleted list item: LabeledFlowableStyle
- bulleted list item label: ListItemLabelStyle
- nested bulleted list: ListStyle
- (table) bulleted list: ListStyle
- (table) bulleted list item: LabeledFlowableStyle
- (table) bulleted list item label: ListItemLabelStyle
- steps list: ListStyle
- steps list title: ParagraphStyle
- steps list item: LabeledFlowableStyle
- steps list item label: ListItemLabelStyle
- unordered steps list: ListStyle
- unordered steps list title: ParagraphStyle
- unordered steps list item: LabeledFlowableStyle
- unordered steps list item label: ListItemLabelStyle
- choices list: ListStyle
- choices list item: LabeledFlowableStyle

- choices list item label: ListItemLabelStyle
- definition list: GroupedFlowablesStyle
- definition list item: LabeledFlowableStyle
- definition term: GroupedFlowablesStyle
- definition term paragraph: ParagraphStyle
- definition term classifier: TextStyle
- definition: GroupedFlowablesStyle
- definition paragraph: ParagraphStyle
- related links: GroupedFlowablesStyle
- related links section title: ParagraphStyle
- related links list: ListStyle
- related links list item: LabeledFlowableStyle
- related links list item label: ListItemLabelStyle
- related links list item paragraph: ReferencingParagraphStyle
- related link title reference: ReferenceStyle
- related link page reference: ReferenceStyle
- related link number reference: ReferenceStyle
- related link reference: ReferenceStyle
- versionmodified: TextStyle
- object description: LabeledFlowableStyle
- object signatures: GroupedFlowablesStyle
- object signature: ParagraphStyle
- object name: TextStyle
- additional name part: TextStyle
- object type: TextStyle
- object returns: TextStyle
- object parentheses: TextStyle
- object parameter list: TextStyle
- object parameter: TextStyle
- object parameter (no emphasis): TextStyle
- object brackets: TextStyle
- object optional parameter: TextStyle
- object annotation: TextStyle
- object description content: GroupedFlowablesStyle
- object description content paragraph: ParagraphStyle
- production list: GroupedFlowablesStyle
- production: LabeledFlowableStyle
- token name: ParagraphStyle
- token definition: ParagraphStyle
- field list: GroupedFlowablesStyle
- field list item: LabeledFlowableStyle
- field name: ParagraphStyle
- option list: GroupedFlowablesStyle
- option list item: LabeledFlowableStyle
- option: ParagraphStyle
- option string: TextStyle
- option argument: TextStyle
- admonition: AdmonitionStyle
- admonition title: ParagraphStyle
- admonition title paragraph: ParagraphStyle
- admonition inline title: TextStyle
- attention admonition: AdmonitionStyle
- attention admonition title: ParagraphStyle

- attention admonition title paragraph: ParagraphStyle
- attention admonition inline title: TextStyle
- caution admonition: AdmonitionStyle
- caution admonition title: ParagraphStyle
- caution admonition title paragraph: ParagraphStyle
- caution admonition inline title: TextStyle
- danger admonition: AdmonitionStyle
- danger admonition title: ParagraphStyle
- danger admonition title paragraph: ParagraphStyle
- danger admonition inline title: TextStyle
- error admonition: AdmonitionStyle
- error admonition title: ParagraphStyle
- error admonition title paragraph: ParagraphStyle
- error admonition inline title: TextStyle
- hint admonition: AdmonitionStyle
- hint admonition title: ParagraphStyle
- hint admonition title paragraph: ParagraphStyle
- hint admonition inline title: TextStyle
- important admonition: AdmonitionStyle
- important admonition title: ParagraphStyle
- important admonition title paragraph: ParagraphStyle
- important admonition inline title: TextStyle
- note admonition: AdmonitionStyle
- note admonition title: ParagraphStyle
- note admonition title paragraph: ParagraphStyle
- note admonition inline title: TextStyle
- tip admonition: AdmonitionStyle
- tip admonition title: ParagraphStyle
- tip admonition title paragraph: ParagraphStyle
- tip admonition inline title: TextStyle
- warning admonition: AdmonitionStyle
- warning admonition title: ParagraphStyle
- warning admonition title paragraph: ParagraphStyle
- warning admonition inline title: TextStyle
- seealso admonition: AdmonitionStyle
- seealso admonition title: ParagraphStyle
- seealso admonition title paragraph: ParagraphStyle
- seealso admonition inline title: TextStyle
- header: ParagraphStyle
- footer: ParagraphStyle
- footnote: NoteStyle
- footnote marker: NoteMarkerStyle
- footnote paragraph: ParagraphStyle
- footnote label: ParagraphStyle
- citation: NoteStyle
- citation marker: NoteMarkerStyle
- citation paragraph: ParagraphStyle
- citation label: ParagraphStyle
- image: FlowableStyle
- inline image: InlineFlowableStyle
- figure: FigureStyle
- figure image: FlowableStyle
- figure caption: CaptionStyle

- figure legend: `GroupedFlowablesStyle`
- figure legend paragraph: `ParagraphStyle`
- table of contents section: `SectionStyle`
- table of contents title: `HeadingStyle`
- table of contents: `TableOfContentsStyle`
- local table of contents: `TableOfContentsStyle`
- toc level 1: `TableOfContentsEntryStyle`
- toc level 2: `TableOfContentsEntryStyle`
- toc level 3: `TableOfContentsEntryStyle`
- L3 toc level 3: `TableOfContentsEntryStyle`
- toc entry number reference field: `ReferenceStyle`
- list of figures section: `SectionStyle`
- list of figures: `ListOfStyle`
- list of figures entry: `ListOfEntryStyle`
- list of tables section: `SectionStyle`
- list of tables: `ListOfStyle`
- list of tables entry: `ListOfEntryStyle`
- table: `TableStyle`
- table with caption: `TableWithCaptionStyle`
- table caption: `CaptionStyle`
- choices table: `TableStyle`
- table cell: `TableCellStyle`
- table body cell background on even row: `TableCellBackgroundStyle`
- table body cell background on odd row: `TableCellBackgroundStyle`
- table body cell paragraph: `ParagraphStyle`
- table first column paragraph: `ParagraphStyle`
- table body cell list item number: `ParagraphStyle`
- table head cell: `TableCellStyle`
- table head cell background: `TableCellBackgroundStyle`
- table head cell paragraph: `ParagraphStyle`
- table cell left border: `TableCellBorderStyle`
- table cell top border: `TableCellBorderStyle`
- table cell right border: `TableCellBorderStyle`
- table cell bottom border: `TableCellBorderStyle`
- table top border: `TableCellBorderStyle`
- table bottom border: `TableCellBorderStyle`
- table left border: `TableCellBorderStyle`
- table right border: `TableCellBorderStyle`
- table head cell left border: `TableCellBorderStyle`
- table head cell right border: `TableCellBorderStyle`
- table head bottom border: `TableCellBorderStyle`
- table head left border: `TableCellBorderStyle`
- table head right border: `TableCellBorderStyle`
- table body top border: `TableCellBorderStyle`
- table body left border: `TableCellBorderStyle`
- table body right border: `TableCellBorderStyle`
- horizontal rule: `HorizontalRuleStyle`
- index: `IndexStyle`
- index section label: `ParagraphStyle`
- level 1 index entry: `ParagraphStyle`
- level 2 index entry: `ParagraphStyle`
- level 3 index entry: `ParagraphStyle`
- level 4 index entry: `ParagraphStyle`

- domain index entry name: `TextStyle`

3.3 Element Style Classes

These are the style classes corresponding to each type of document element. For each style class, the supported style attributes are listed along with the values that can be assigned to them in a style sheet.

<code>draw.LineStyle</code>	Style class for <code>Line</code>
<code>draw.ShapeStyle</code>	Style class for <code>Shape</code>
<code>flowable.FlowableStyle</code>	Style class for <code>Flowable</code>
<code>flowable.LabeledFlowableStyle</code>	Style class for <code>LabeledFlowable</code>
<code>flowable.GroupedFlowablesStyle</code>	Style class for <code>GroupedFlowables</code>
<code>flowable.FloatStyle</code>	Style class for <code>Float</code>
<code>image.CaptionStyle</code>	Style class for <code>Caption</code>
<code>image.FigureStyle</code>	Style class for <code>Figure</code>
<code>index.IndexStyle</code>	Style class for <code>Index</code>
<code>paragraph.ParagraphStyle</code>	Style class for <code>Paragraph</code>
<code>text.TextStyle</code>	Style class for <code>Text</code>
<code>inline.InlineFlowableStyle</code>	Style class for <code>InlineFlowable</code>
<code>reference.ReferencingParagraphStyle</code>	Style class for <code>ReferencingParagraph</code>
<code>reference.NoteMarkerStyle</code>	Style class for <code>NoteMarker</code>
<code>structure.SectionStyle</code>	Style class for <code>Section</code>
<code>structure.HeadingStyle</code>	Style class for <code>Heading</code>
<code>structure.ListStyle</code>	Style class for <code>List</code>
<code>structure.ListItemLabelStyle</code>	Style class for <code>ListItemLabel</code>
<code>structure.TableOfContentsStyle</code>	Style class for <code>TableOfContents</code>
<code>structure.TableOfContentsEntryStyle</code>	Style class for <code>TableOfContentsEntry</code>
<code>structure.AdmonitionStyle</code>	Style class for <code>Admonition</code>
<code>structure.HorizontalRuleStyle</code>	Style class for <code>HorizontalRule</code>
<code>table.TableStyle</code>	Style class for <code>Table</code>
<code>table.TableCellStyle</code>	Style class for <code>TableCell</code>
<code>table.TableCellBorderStyle</code>	Style class for <code>TableCellBorder</code>
<code>table.TableCellBackgroundStyle</code>	Style class for <code>TableCellBackground</code>

3.3.1 LineStyle

```
class rinoh.draw.LineStyle ( base=None, **attributes )
```

Style class for `Line`

stroke

Width and color used to draw the line

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: 1pt, #000

hide
Suppress rendering this element (inherited from `Style`)
Accepts `Bool`: `true` or `false`
Default: `false`

3.3.2 ShapeStyle

class `rinoh.draw.ShapeStyle` (*base=None, **attributes*)
Style class for `Shape`

fill_color
Color to fill the shape
Accepts `Color`: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)
Default: `#e5e5e5`

stroke
Width and color used to draw the line (inherited from `LineStyle`)
Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,) *Default*: `1pt, #000`

hide
Suppress rendering this element (inherited from `Style`)
Accepts `Bool`: `true` or `false`
Default: `false`

3.3.3 FlowableStyle

class `rinoh.flowable.FlowableStyle` (*base=None, **attributes*)
Style class for `Flowable`

width
Width to render the flowable at
Accepts `FlowableWidth`: `auto`, `fill` or a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)
Default: `auto`

horizontal_align
Horizontal alignment of the flowable
Accepts `HorizontalAlignment`: `left`, `right`, `center`
Default: `left`

space_above
Vertical space preceding the flowable
Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)
Default: `0`

space_below
Vertical space following the flowable
Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)
Default: `0`

margin_left

Left margin

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable

Accepts Stroke: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable

Accepts Stroke: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders

Accepts Color: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break

Type of page break to insert before rendering this flowable

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from *Style*)

Accepts Bool: true or false

Default: false

3.3.4 LabeledFlowableStyle

```
class rinoh.flowable.LabeledFlowableStyle ( base=None, **attributes )
```

Style class for *LabeledFlowable*

label_min_width

Minimum label width

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 12pt

label_max_width

Maximum label width

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 80pt

label_spacing

Spacing between a label and the labeled flowable

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3pt

align_baselines

Line up the baselines of the label and the labeled flowable

Accepts Bool: true or false

Default: true

wrap_label

Wrap the label at *label_max_width*

Accepts Bool: true or false

Default: false

width

Width to render the flowable at (inherited from `FlowableStyle`)

Accepts `FlowableWidth`: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: auto

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts `Bool`: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts `Break`: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

3.3.5 GroupedFlowablesStyle

```
class rinoh.flowable.GroupedFlowablesStyle ( base=None, **attributes )
```

Style class for GroupedFlowables

width

Width to render the flowable at (inherited from FlowableStyle)

Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill (overrides FlowableStyle default)

title

Title to precede the flowables

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing

Spacing between flowables

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

horizontal_align

Horizontal alignment of the flowable (inherited from FlowableStyle)

Accepts HorizontalAlignment: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts Bool: true or false

Default: false

3.3.6 FloatStyle

```
class rinoh.flowable.FloatStyle ( base=None, **attributes )
```

Style class for Float

float

Float the flowable to the top or bottom of the page

Accepts Bool: true or false

Default: false

width

Width to render the flowable at (inherited from `FlowableStyle`)

Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: auto

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts HorizontalAlignment: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by

a comma (,)
Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)
Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)
Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)
Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)
Accepts Break: none, any, left, right, any restart, left restart, right restart
Default: None

hide

Suppress rendering this element (inherited from `Style`)
Accepts Bool: true or false
Default: false

3.3.7 CaptionStyle

class `rinoh.image.CaptionStyle` (*base=None, **attributes*)

Style class for `Caption`

number_format

How numbers are formatted (inherited from `ParagraphStyle`)
Accepts NumberFormat: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman
Default: number (overrides `ParagraphStyle` default)

numbering_level

At which section level to restart numbering (positive: absolute, negative: relative) (inherited from `ParagraphStyle`)
Accepts Integer: a natural number (positive integer)
Default: 1 (overrides `ParagraphStyle` default)

width

Width to render the flowable at (inherited from `ParagraphStyle`)
Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: fill

indent_first

Indentation of the first line of text (inherited from `ParagraphStyle`)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0pt

line_spacing

Spacing between the baselines of two successive lines of text (inherited from `ParagraphStyle`)

Accepts `LineSpacing`: a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: `<spacing type>(<arg1>, <arg2>, ...)`

Default: default

text_align

Alignment of text to the margins (inherited from `ParagraphStyle`)

Accepts `TextAlign`: left, right, center, justify

Default: justify

tab_stops

List of tab positions (inherited from `ParagraphStyle`)

Accepts `TabStopList`: a comma-separated list of tab stops. A tab stop is specified as `<position> [align] [fill string]`, where `position` (`Dimension`) is required and `align` (`TabAlign`) and `fill string` (string enclosed in quotes) are optional.

Default: (no value)

number_separator

Characters inserted between the number label of this element's parent and this element's own number label. If `None`, only show this item's number label. (inherited from `ParagraphStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: `'text string' (style name)`

Default: '.'

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts `Color`: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts `Break`: none, any, left, right, any restart, left restart, right restart

Default: None

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)

Accepts `Bool`: true or false

Default: false

typeface

Typeface to set the text in (inherited from `TextStyle`)

Accepts `Typeface`: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.

Default: Times

font_weight

Thickness of character outlines relative to their height (inherited from `TextStyle`)

Accepts `FontWeight`: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant

Slope style of the font (inherited from `TextStyle`)

Accepts `FontSlant`: upright, oblique, italic

Default: upright

font_width

Stretch of the characters (inherited from `TextStyle`)

Accepts `FontWidth`: ultra-condensed, extra-condensed, condensed,

semi-condensed, normal, medium, semi-expanded, expanded,
extra-expanded, ultra-expanded
Default: 5

font_size

Height of characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

Variant of the font (inherited from `TextStyle`)

Accepts `FontVariant`: normal, small capital, oldstyle figures

Default: normal

position

Vertical text position (inherited from `TextStyle`)

Accepts `TextPosition`: normal, superscript, subscript

Default: normal

kerning

Improve inter-letter spacing (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

ligatures

Run letters together where possible (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from `TextStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: 2

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from `TextStyle`)

Accepts `Locale`: locale identifier in the <language ID>_<region ID> format

Default: en_US

no_break_after

Prevent a line break after these words (inherited from `TextStyle`)

Accepts `NoBreakAfter`: language-default, or a space-separated list of words

Default: language-default

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

3.3.8 **FigureStyle**

```
class rinoh.image.FigureStyle ( base=None, **attributes )
```

Style class for `Figure`

float

Float the flowable to the top or bottom of the page (inherited from `FloatStyle`)

Accepts `Bool`: true or false

Default: false

width

Width to render the flowable at (inherited from `FlowableStyle`)

Accepts `FlowableWidth`: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: auto

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by

a comma (,)
Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)
Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)
Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)
Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)
Accepts Break: none, any, left, right, any restart, left restart, right restart
Default: None

hide

Suppress rendering this element (inherited from `Style`)
Accepts Bool: true or false
Default: false

title

Title to precede the flowables (inherited from `GroupedFlowablesStyle`)
Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

flowable_spacing

Spacing between flowables (inherited from `GroupedFlowablesStyle`)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

3.3.9 IndexStyle

class `rinoh.index.IndexStyle` (*base=None, **attributes*)
Style class for Index

initials

Group index entries based on their first letter
Accepts Bool: true or false
Default: true

width

Width to render the flowable at (inherited from `GroupedFlowablesStyle`)
Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: fill

title

Title to precede the flowables (inherited from `GroupedFlowablesStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing

Spacing between flowables (inherited from `GroupedFlowablesStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts `Bool`: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts `Break`: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

3.3.10 ParagraphStyle

```
class rinoh.paragraph.ParagraphStyle ( base=None, **attributes )
```

Style class for Paragraph

width

Width to render the flowable at (inherited from FlowableStyle)

Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill (overrides FlowableStyle default)

indent_first

Indentation of the first line of text

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

line_spacing

Spacing between the baselines of two successive lines of text

Accepts LineSpacing: a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

text_align

Alignment of text to the margins

Accepts TextAlign: left, right, center, justify

Default: justify

tab_stops

List of tab positions

Accepts TabStopList: a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position (Dimension) is required and align (TabAlign) and fill string (string enclosed in quotes) are optional.

Default: (no value)

number_format

How numbers are formatted (inherited from NumberStyle)

Accepts NumberFormat: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: None (overrides NumberStyle default)

number_separator

Characters inserted between the number label of this element's parent and this element's own number label. If None, only show this item's number label.

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: ' . '

numbering_level

At which section level to restart numbering (positive: absolute, negative: relative)

Accepts Integer: a natural number (positive integer)

Default: (no value)

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts `Bool`: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts Bool: true or false

Default: false

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)

Accepts `Bool`: true or false

Default: false

typeface

Typeface to set the text in (inherited from `TextStyle`)

Accepts `Typeface`: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.

Default: Times

font_weight

Thickness of character outlines relative to their height (inherited from `TextStyle`)

Accepts `FontWeight`: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant

Slope style of the font (inherited from `TextStyle`)

Accepts `FontSlant`: upright, oblique, italic

Default: upright

font_width

Stretch of the characters (inherited from `TextStyle`)

Accepts `FontWidth`: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size

Height of characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

Variant of the font (inherited from `TextStyle`)

Accepts `FontVariant`: normal, small capital, oldstyle figures

Default: normal

position

Vertical text position (inherited from `TextStyle`)

Accepts `TextPosition`: normal, superscript, subscript

Default: normal

kerning

Improve inter-letter spacing (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

ligatures

Run letters together where possible (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from `TextStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: 2

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from `TextStyle`)

Accepts `Locale`: locale identifier in the <language ID>_<region ID> format

Default: en_US

no_break_after

Prevent a line break after these words (inherited from `TextStyle`)

Accepts `NoBreakAfter`: language-default, or a space-separated list of words

Default: language-default

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

3.3.11 TextStyle

class `rinoh.text.TextStyle` (*base=None, **attributes*)

Style class for Text

typeface

Typeface to set the text in

Accepts `Typeface`: the name of a typeface. See `rinoh --list-fonts` for a list of

the available typefaces.

Default: Times

font_weight

Thickness of character outlines relative to their height

Accepts FontWeight: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant

Slope style of the font

Accepts FontSlant: upright, oblique, italic

Default: upright

font_width

Stretch of the characters

Accepts FontWidth: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size

Height of characters

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 10pt

font_color

Color of the font

Accepts Color: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

Variant of the font

Accepts FontVariant: normal, small capital, oldstyle figures

Default: normal

position

Vertical text position

Accepts TextPosition: normal, superscript, subscript

Default: normal

kerning

Improve inter-letter spacing

Accepts Bool: true or false

Default: true

ligatures

Run letters together where possible

Accepts Bool: true or false

Default: true

hyphenate

Allow words to be broken over two lines

Accepts Bool: true or false

Default: true

hyphen_chars

Minimum number of characters in a hyphenated part of a word

Accepts Integer: a natural number (positive integer)

Default: 2

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US'

Accepts Locale: locale identifier in the <language ID>_<region ID> format

Default: en_US

no_break_after

Prevent a line break after these words

Accepts NoBreakAfter: language-default, or a space-separated list of words

Default: language-default

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

hide

Suppress rendering this element (inherited from `Style`)

Accepts Bool: true or false

Default: false

3.3.12 InlineFlowableStyle

```
class rinoh.inline.InlineFlowableStyle ( base=None, **attributes )
```

Style class for `InlineFlowable`

baseline

The location of the flowable's baseline relative to the bottom edge

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

width

Width to render the flowable at (inherited from `FlowableStyle`)

Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: auto

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts HorizontalAlignment: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts Bool: true or false

Default: false

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

3.3.13 ReferencingParagraphStyle

class `rinoh.reference.ReferencingParagraphStyle` (*base=None, **attributes*)

Style class for `ReferencingParagraph`

text

The text content of this paragraph

Accepts `ReferenceText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: '{TITLE}'

width

Width to render the flowable at (inherited from `ParagraphStyle`)

Accepts `FlowableWidth`: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill

indent_first

Indentation of the first line of text (inherited from `ParagraphStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

line_spacing

Spacing between the baselines of two successive lines of text (inherited from `ParagraphStyle`)

Accepts `LineSpacing`: a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

text_align

Alignment of text to the margins (inherited from `ParagraphStyle`)

Accepts `TextAlign`: left, right, center, justify

Default: justify

tab_stops

List of tab positions (inherited from `ParagraphStyle`)

Accepts `TabStopList`: a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position (`Dimension`) is required and align (`TabAlign`) and fill string (string enclosed in quotes) are optional.

Default: (no value)

number_format

How numbers are formatted (inherited from `ParagraphStyle`)

Accepts `NumberFormat`: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: None

number_separator

Characters inserted between the number label of this element's parent and this element's own number label. If None, only show this item's number label. (inherited from `ParagraphStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text

string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: ' . '

numbering_level

At which section level to restart numbering (positive: absolute, negative: relative) (inherited from `ParagraphStyle`)
Accepts Integer: a natural number (positive integer)
Default: (no value)

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)
Accepts HorizontalAlignment: left, right, center
Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding

Padding (inherited from `FlowableStyle`)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)
Accepts `Bool`: true or false
Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)
Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)
Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)
Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)
Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)
Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)
Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)
Accepts `Break`: none, any, left, right, any restart, left restart, right restart
Default: None

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)
Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)

Accepts `Bool`: true or false

Default: false

typeface

Typeface to set the text in (inherited from `TextStyle`)

Accepts `Typeface`: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.

Default: Times

font_weight

Thickness of character outlines relative to their height (inherited from `TextStyle`)

Accepts `FontWeight`: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant

Slope style of the font (inherited from `TextStyle`)

Accepts `FontSlant`: upright, oblique, italic

Default: upright

font_width

Stretch of the characters (inherited from `TextStyle`)

Accepts `FontWidth`: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size

Height of characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

Variant of the font (inherited from `TextStyle`)

Accepts `FontVariant`: normal, small capital, oldstyle figures

Default: normal

position

Vertical text position (inherited from `TextStyle`)

Accepts `TextPosition`: normal, superscript, subscript

Default: normal

kerning

Improve inter-letter spacing (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

ligatures

Run letters together where possible (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from `TextStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: 2

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from `TextStyle`)

Accepts `Locale`: locale identifier in the <language ID>_<region ID> format

Default: en_US

no_break_after

Prevent a line break after these words (inherited from `TextStyle`)

Accepts `NoBreakAfter`: language-default, or a space-separated list of words

Default: language-default

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

3.3.14 NoteMarkerStyle

class rinoh.reference.**NoteMarkerStyle** (*base=None, **attributes*)

Style class for NoteMarker

type

How the reference should be displayed (inherited from `ReferenceStyle`)

Accepts `ReferenceType`: reference, number, title, page, custom

Default: number (overrides `ReferenceStyle` default)

link

Create a hyperlink to the reference target (inherited from `ReferenceStyle`)

Accepts `Bool`: true or false

Default: true

quiet

If the given reference type does not exist for the target, resolve to an empty string instead of making a fuss about it (inherited from `ReferenceStyle`)

Accepts `Bool`: true or false

Default: false

typeface

Typeface to set the text in (inherited from `TextStyle`)

Accepts `Typeface`: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.

Default: Times

font_weight

Thickness of character outlines relative to their height (inherited from `TextStyle`)

Accepts `FontWeight`: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant

Slope style of the font (inherited from `TextStyle`)

Accepts `FontSlant`: upright, oblique, italic

Default: upright

font_width

Stretch of the characters (inherited from `TextStyle`)

Accepts `FontWidth`: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size

Height of characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

Variant of the font (inherited from `TextStyle`)

Accepts `FontVariant`: normal, small capital, oldstyle figures

Default: normal

position

Vertical text position (inherited from `TextStyle`)

Accepts `TextPosition`: normal, superscript, subscript

Default: normal

kerning

Improve inter-letter spacing (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

ligatures

Run letters together where possible (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from `TextStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: 2

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from `TextStyle`)

Accepts `Locale`: locale identifier in the <language ID>_<region ID> format

Default: en_US

no_break_after

Prevent a line break after these words (inherited from `TextStyle`)

Accepts `NoBreakAfter`: language-default, or a space-separated list of words

Default: language-default

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

number_format

How numbers are formatted (inherited from `NumberStyle`)

Accepts `NumberFormat`: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: number

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)

Accepts `Bool`: true or false

Default: false

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

3.3.15 SectionStyle

```
class rinoh.structure.SectionStyle ( base=None, **attributes )
```

Style class for `Section`

show_in_toc

List this section in the table of contents

Accepts `Bool`: true or false

Default: true

width

Width to render the flowable at (inherited from `GroupedFlowablesStyle`)

Accepts `FlowableWidth`: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill

title

Title to precede the flowables (inherited from `GroupedFlowablesStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing

Spacing between flowables (inherited from `GroupedFlowablesStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts `Bool`: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts Bool: true or false

Default: false

3.3.16 HeadingStyle

```
class rinoh.structure.HeadingStyle ( base=None, **attributes )
```

Style class for Heading

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts `Bool`: true or false

Default: true (overrides `FlowableStyle` default)

numbering_level

At which section level to restart numbering (positive: absolute, negative: relative) (inherited from `ParagraphStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: -1 (overrides `ParagraphStyle` default)

width

Width to render the flowable at (inherited from `ParagraphStyle`)

Accepts `FlowableWidth`: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill

indent_first

Indentation of the first line of text (inherited from `ParagraphStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

line_spacing

Spacing between the baselines of two successive lines of text (inherited from `ParagraphStyle`)

Accepts `LineSpacing`: a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

text_align

Alignment of text to the margins (inherited from `ParagraphStyle`)

Accepts `TextAlign`: left, right, center, justify

Default: justify

tab_stops

List of tab positions (inherited from `ParagraphStyle`)

Accepts `TabStopList`: a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position (`Dimension`) is required and align (`TabAlign`) and fill string (string enclosed in quotes) are optional.

Default: (no value)

number_format

How numbers are formatted (inherited from `ParagraphStyle`)

Accepts `NumberFormat`: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: None

number_separator

Characters inserted between the number label of this element's parent and this element's own number label. If None, only show this item's number label. (inherited from `ParagraphStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: ' . '

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)

Accepts Bool: true or false

Default: false

typeface

Typeface to set the text in (inherited from `TextStyle`)

Accepts `Typeface`: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.

Default: Times

font_weight

Thickness of character outlines relative to their height (inherited from `TextStyle`)

Accepts `FontWeight`: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant

Slope style of the font (inherited from `TextStyle`)

Accepts `FontSlant`: upright, oblique, italic

Default: upright

font_width

Stretch of the characters (inherited from `TextStyle`)

Accepts `FontWidth`: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size

Height of characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

Variant of the font (inherited from `TextStyle`)

Accepts `FontVariant`: normal, small capital, oldstyle figures

Default: normal

position

Vertical text position (inherited from `TextStyle`)

Accepts `TextPosition`: normal, superscript, subscript

Default: normal

kerning

Improve inter-letter spacing (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

ligatures

Run letters together where possible (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)

Accepts `Bool`: `true` or `false`

Default: `true`

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from `TextStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: `2`

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from `TextStyle`)

Accepts `Locale`: locale identifier in the <language ID>_<region ID> format

Default: `en_US`

no_break_after

Prevent a line break after these words (inherited from `TextStyle`)

Accepts `NoBreakAfter`: language-default, or a space-separated list of words

Default: language-default

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: `true` or `false`

Default: `false`

3.3.17 ListStyle

```
class rinoh.structure.ListStyle ( base=None, **attributes )
```

Style class for `List`

ordered

This list is ordered or unordered

Accepts `Bool`: `true` or `false`

Default: `false`

bullet

Bullet to use in unordered lists

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in

braces: 'text string' (style name)
Default: '•'

width

Width to render the flowable at (inherited from `GroupedFlowablesStyle`)
Accepts `FlowableWidth`: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: fill

title

Title to precede the flowables (inherited from `GroupedFlowablesStyle`)
Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

flowable_spacing

Spacing between flowables (inherited from `GroupedFlowablesStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)
Accepts `HorizontalAlignment`: left, right, center
Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding

Padding (inherited from `FlowableStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts Bool: true or false

Default: false

number_format

How numbers are formatted (inherited from `NumberStyle`)

Accepts NumberFormat: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: number

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)

Accepts Bool: true or false

Default: false

3.3.18 ListItemLabelStyle

```
class rinoh.structure.ListItemLabelStyle ( base=None, **attributes )
```

Style class for ListItemLabel

width

Width to render the flowable at (inherited from `ParagraphStyle`)

Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill

indent_first

Indentation of the first line of text (inherited from `ParagraphStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

line_spacing

Spacing between the baselines of two successive lines of text (inherited from

ParagraphStyle)

Accepts LineSpacing: a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

text_align

Alignment of text to the margins (inherited from ParagraphStyle)

Accepts TextAlign: left, right, center, justify

Default: justify

tab_stops

List of tab positions (inherited from ParagraphStyle)

Accepts TabStopList: a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position (Dimension) is required and align (TabAlign) and fill string (string enclosed in quotes) are optional.

Default: (no value)

number_format

How numbers are formatted (inherited from ParagraphStyle)

Accepts NumberFormat: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: None

number_separator

Characters inserted between the number label of this element's parent and this element's own number label. If None, only show this item's number label. (inherited from ParagraphStyle)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: '.'

numbering_level

At which section level to restart numbering (positive: absolute, negative: relative) (inherited from ParagraphStyle)

Accepts Integer: a natural number (positive integer)

Default: (no value)

horizontal_align

Horizontal alignment of the flowable (inherited from FlowableStyle)

Accepts HorizontalAlignment: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false
Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)
Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)
Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)
Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)

Accepts Bool: true or false

Default: false

typeface

Typeface to set the text in (inherited from `TextStyle`)

Accepts Typeface: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.

Default: Times

font_weight

Thickness of character outlines relative to their height (inherited from `TextStyle`)

Accepts FontWeight: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant

Slope style of the font (inherited from `TextStyle`)

Accepts `FontSlant`: upright, oblique, italic

Default: upright

font_width

Stretch of the characters (inherited from `TextStyle`)

Accepts `FontWidth`: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size

Height of characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

Variant of the font (inherited from `TextStyle`)

Accepts `FontVariant`: normal, small capital, oldstyle figures

Default: normal

position

Vertical text position (inherited from `TextStyle`)

Accepts `TextPosition`: normal, superscript, subscript

Default: normal

kerning

Improve inter-letter spacing (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

ligatures

Run letters together where possible (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from `TextStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: 2

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from

TextStyle)
Accepts `Locale`: locale identifier in the <language ID>_<region ID> format
Default: en_US

no_break_after

Prevent a line break after these words (inherited from `TextStyle`)
Accepts `NoBreakAfter`: language-default, or a space-separated list of words
Default: language-default

before

Item to insert before this one (inherited from `InlineStyle`)
Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)
Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

hide

Suppress rendering this element (inherited from `Style`)
Accepts `Bool`: true or false
Default: false

3.3.19 TableOfContentsStyle

```
class rinoh.structure.TableOfContentsStyle ( base=None, **attributes )  
    Style class for TableOfContents
```

depth

The number of section levels to include in the table of contents
Accepts `Integer`: a natural number (positive integer)
Default: 3

width

Width to render the flowable at (inherited from `GroupedFlowablesStyle`)
Accepts `FlowableWidth`: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: fill

title

Title to precede the flowables (inherited from `GroupedFlowablesStyle`)
Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

flowable_spacing

Spacing between flowables (inherited from `GroupedFlowablesStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts `Bool`: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts Bool: true or false

Default: false

indent_first

Indentation of the first line of text (inherited from `ParagraphStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

line_spacing

Spacing between the baselines of two successive lines of text (inherited from `ParagraphStyle`)

Accepts `LineSpacing`: a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: `<spacing type>(<arg1>, <arg2>, ...)`
Default: default

text_align

Alignment of text to the margins (inherited from `ParagraphStyle`)

Accepts `TextAlign`: left, right, center, justify

Default: justify

tab_stops

List of tab positions (inherited from `ParagraphStyle`)

Accepts `TabStopList`: a comma-separated list of tab stops. A tab stop is specified as `<position> [align] [fill string]`, where `position` (`Dimension`) is required and `align` (`TabAlign`) and `fill string` (string enclosed in quotes) are optional.

Default: (no value)

number_format

How numbers are formatted (inherited from `ParagraphStyle`)

Accepts `NumberFormat`: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: None

number_separator

Characters inserted between the number label of this element's parent and this element's own number label. If None, only show this item's number label. (inherited from `ParagraphStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: `'text string' (style name)`

Default: '.'

numbering_level

At which section level to restart numbering (positive: absolute, negative: relative) (inherited from `ParagraphStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: (no value)

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: `'text string' (style name)`

Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: `'text string' (style name)`

Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)

Accepts `Bool`: true or false

Default: false

typeface

Typeface to set the text in (inherited from `TextStyle`)

Accepts `Typeface`: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.

Default: Times

font_weight

Thickness of character outlines relative to their height (inherited from `TextStyle`)

Accepts `FontWeight`: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant

Slope style of the font (inherited from `TextStyle`)

Accepts `FontSlant`: upright, oblique, italic

Default: upright

font_width

Stretch of the characters (inherited from `TextStyle`)

Accepts `FontWidth`: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size

Height of characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

Variant of the font (inherited from `TextStyle`)

Accepts `FontVariant`: normal, small capital, oldstyle figures

Default: normal

position

Vertical text position (inherited from `TextStyle`)

Accepts `TextPosition`: normal, superscript, subscript

Default: normal

kerning

Improve inter-letter spacing (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

ligatures

Run letters together where possible (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)

Accepts `Bool`: `true` or `false`

Default: `true`

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from `TextStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: `2`

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as `'en_US'` (inherited from `TextStyle`)

Accepts `Locale`: locale identifier in the `<language ID>_<region ID>` format

Default: `en_US`

no_break_after

Prevent a line break after these words (inherited from `TextStyle`)

Accepts `NoBreakAfter`: `language-default`, or a space-separated list of words

Default: `language-default`

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (`'` or `"`), optionally followed by a style name enclosed in braces: `'text string' (style name)`

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (`'` or `"`), optionally followed by a style name enclosed in braces: `'text string' (style name)`

Default: (no value)

3.3.20 TableOfContentsEntryStyle

```
class rinoh.structure.TableOfContentsEntryStyle ( base=None, **attributes )
```

Style class for `TableOfContentsEntry`

text

The text content of this paragraph (inherited from `ReferencingParagraphStyle`)

Accepts `ReferenceText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (`'` or `"`), optionally followed by a style name enclosed in braces: `'text string' (style name)`

Default: `'{NUMBER}' '\t' '{TITLE}' '\t' '{PAGE}'` (overrides `ReferencingParagraphStyle` default)

width

Width to render the flowable at (inherited from `ParagraphStyle`)

Accepts `FlowableWidth`: `auto`, `fill` or a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: `fill`

indent_first

Indentation of the first line of text (inherited from `ParagraphStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

line_spacing

Spacing between the baselines of two successive lines of text (inherited from `ParagraphStyle`)

Accepts `LineSpacing`: a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: `<spacing type>(<arg1>, <arg2>, ...)`

Default: default

text_align

Alignment of text to the margins (inherited from `ParagraphStyle`)

Accepts `TextAlign`: left, right, center, justify

Default: justify

tab_stops

List of tab positions (inherited from `ParagraphStyle`)

Accepts `TabStopList`: a comma-separated list of tab stops. A tab stop is specified as `<position> [align] [fill string]`, where `position` (`Dimension`) is required and `align` (`TabAlign`) and `fill string` (string enclosed in quotes) are optional.

Default: (no value)

number_format

How numbers are formatted (inherited from `ParagraphStyle`)

Accepts `NumberFormat`: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: None

number_separator

Characters inserted between the number label of this element's parent and this element's own number label. If None, only show this item's number label. (inherited from `ParagraphStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: `'text string' (style name)`

Default: ' . '

numbering_level

At which section level to restart numbering (positive: absolute, negative: relative) (inherited from `ParagraphStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: (no value)

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)

Accepts Bool: true or false

Default: false

typeface

Typeface to set the text in (inherited from `TextStyle`)

Accepts Typeface: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.

Default: Times

font_weight

Thickness of character outlines relative to their height (inherited from `TextStyle`)

Accepts `FontWeight`: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant

Slope style of the font (inherited from `TextStyle`)

Accepts `FontSlant`: upright, oblique, italic

Default: upright

font_width

Stretch of the characters (inherited from `TextStyle`)

Accepts `FontWidth`: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size

Height of characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

Variant of the font (inherited from `TextStyle`)

Accepts `FontVariant`: normal, small capital, oldstyle figures

Default: normal

position

Vertical text position (inherited from `TextStyle`)

Accepts `TextPosition`: normal, superscript, subscript

Default: normal

kerning

Improve inter-letter spacing (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

ligatures

Run letters together where possible (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from `TextStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: 2

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from `TextStyle`)

Accepts `Locale`: locale identifier in the <language ID>_<region ID> format

Default: en_US

no_break_after

Prevent a line break after these words (inherited from `TextStyle`)

Accepts `NoBreakAfter`: language-default, or a space-separated list of words

Default: language-default

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

3.3.21 AdmonitionStyle

```
class rinoh.structure.AdmonitionStyle ( base=None, **attributes )
```

Style class for Admonition

inline_title

Show the admonition's title inline with the body text, if possible

Accepts `Bool`: true or false

Default: true

width

Width to render the flowable at (inherited from `GroupedFlowablesStyle`)

Accepts `FlowableWidth`: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill

title

Title to precede the flowables (inherited from `GroupedFlowablesStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text

string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

flowable_spacing

Spacing between flowables (inherited from `GroupedFlowablesStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)
Accepts `HorizontalAlignment`: left, right, center
Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding

Padding (inherited from `FlowableStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts `Bool`: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts `Color`: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts `Break`: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

3.3.22 HorizontalRuleStyle

```
class rinoh.structure.HorizontalRuleStyle ( base=None, **attributes )
```

Style class for HorizontalRule

width

Width to render the flowable at (inherited from FlowableStyle)

Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: auto

horizontal_align

Horizontal alignment of the flowable (inherited from FlowableStyle)

Accepts HorizontalAlignment: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts `Bool`: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts `Break`: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

stroke

Width and color used to draw the line (inherited from `LineStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: 1pt, #000

3.3.23 **TableStyle**

```
class rinoh.table.TableStyle ( base=None, **attributes )
```

Style class for `Table`

column_widths

Absolute or relative widths of each column

Accepts ColumnWidths: a whitespace-delimited list of column widths; `Dimensions` (absolute width), integers (relative width) and/or 'auto' (automatic width)

Default: none

split_minimum_rows

The minimum number of rows to display when the table is split across pages

Accepts Integer: a natural number (positive integer)

Default: (no value)

repeat_head

Repeat the head when the table is split across pages

Accepts Bool: true or false

Default: false

width

Width to render the flowable at (inherited from `FlowableStyle`)

Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: auto

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts HorizontalAlignment: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by

a comma (,)
Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)
Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)
Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)
Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)
Accepts Break: none, any, left, right, any restart, left restart, right restart
Default: None

hide

Suppress rendering this element (inherited from `Style`)
Accepts Bool: true or false
Default: false

3.3.24 TableCellStyle

```
class rinoh.table.TableCellStyle ( base=None, **attributes )  
Style class for TableCell
```

vertical_align

Vertical alignment of the cell contents within the available space
Accepts VerticalAlign: top, middle, bottom
Default: middle

width

Width to render the flowable at (inherited from `GroupedFlowablesStyle`)
Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: fill

title

Title to precede the flowables (inherited from `GroupedFlowablesStyle`)
Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

flowable_spacing

Spacing between flowables (inherited from `GroupedFlowablesStyle`)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts `Bool`: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts Bool: true or false

Default: false

3.3.25 TableCellBorderStyle

```
class rinoh.table.TableCellBorderStyle ( base=None, **attributes )
```

Style class for `TableCellBorder`

stroke

Width and color used to draw the line (inherited from `LineStyle`)

Accepts Stroke: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none (overrides *LineStyle* default)

hide

Suppress rendering this element (inherited from *Style*)

Accepts Bool: true or false

Default: false

3.3.26 TableCellBackgroundStyle

```
class rinoh.table.TableCellBackgroundStyle ( base=None, **attributes )
```

Style class for TableCellBackground

fill_color

Color to fill the shape (inherited from *ShapeStyle*)

Accepts Color: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none (overrides *ShapeStyle* default)

stroke

Width and color used to draw the line (inherited from *LineStyle*)

Accepts Stroke: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none (overrides *LineStyle* default)

hide

Suppress rendering this element (inherited from *Style*)

Accepts Bool: true or false

Default: false

Rinohtype includes a number of document templates. These are configurable and therefore should cater for most documents.

4.1 Article

The article template consists of a title page, an optional table of contents and the body text. By default, it uses a single numbering style for all pages and the same template for even and odd pages.

```
class    rinoh.templates.article.Article ( document_tree, configuration=None,  
backend=None )
```

stylesheet

The stylesheet to use for styling document elements (inherited from `DocumentTemplate`)

Accepts `StyleSheet`: the name of an Section 3.1 or the filename of a stylesheet file (with the `.rts` extension)

Default: `sphinx_article` (= `rinoh.stylesheets.sphinx_article`) (overrides `DocumentTemplate` default)

table_of_contents

Show or hide the table of contents

Accepts `Bool`: `true` or `false`

Default: `true`

abstract_location

Where to place the abstract

Accepts `AbstractLocation`: `title`, `front_matter`

Default: `front_matter`

parts

The parts making up this document (inherited from `DocumentTemplate`)

Accepts `PartsList`: a space-separated list of document part template names

Default: `title front_matter contents` (overrides `DocumentTemplate` default)

language

The main language of the document (inherited from `DocumentTemplate`)

Accepts `Language`: the code of one of the supported languages

Default: `EN` (English)

strings

Strings to override standard element names (inherited from `DocumentTemplate`)

Accepts Strings: strings need to be entered in INI sections named after the `StringCollection` subclasses

Default: none

title

base: None

Type

`TitlePartTemplate`

front_matter

base: None

Overrides these defaults:

- `page_number_format = continue`

Type

`ArticleFrontMatter`

contents

base: None

Overrides these defaults:

- `page_number_format = continue`

Type

`ContentsPartTemplate`

page

base: None

Overrides these defaults:

- `page_size = $(paper_size)`

Type

`PageTemplate`

title_page

base: `page`

Overrides these defaults:

- `top_margin = 8cm`

Type

`TitlePageTemplate`

front_matter_page

base: `page`

Type

`PageTemplate`

contents_page

base: `page`

Type

`PageTemplate`

Configuration

alias of `rinoh.template.ArticleConfiguration`

ConfigurationFile

alias of `rinoh.template.ArticleConfigurationFile`

class rinoh.templates.article.AbstractLocation

Where to place the article's abstract

Accepts: title, front matter

4.2 Book

The book template consists of a title page, the table of contents, the body text and an index. The front matter pages are numbered using lowercase roman numerals. The template uses different templates for even and odd pages.

class `rinoh.templates.book.Book` (*document_tree*, *configuration=None*, *backend=None*)

stylesheet

The stylesheet to use for styling document elements (inherited from `DocumentTemplate`)

Accepts `StyleSheet`: the name of an Section 3.1 or the filename of a stylesheet file (with the `.rts` extension)

Default: `sphinx` (= `rinoh.stylesheets.sphinx`) (overrides `DocumentTemplate` default)

parts

The parts making up this document (inherited from `DocumentTemplate`)

Accepts `PartsList`: a space-separated list of document part template names

Default: `title front_matter contents back_matter` (overrides `DocumentTemplate` default)

language

The main language of the document (inherited from `DocumentTemplate`)

Accepts `Language`: the code of one of the supported languages

Default: `EN` (English)

strings

Strings to override standard element names (inherited from `DocumentTemplate`)

Accepts `Strings`: strings need to be entered in INI sections named after the `StringCollection` subclasses

Default: none

cover

base: None

Overrides these defaults:

- `drop_if_empty` = False
- `page_number_format` = None
- `end_at_page` = left

Type

`FixedDocumentPartTemplate`

title

base: None

Overrides these defaults:

- `page_number_format` = number

- `end_at_page = left`

Type

`TitlePartTemplate`

front_matter

base: None

Overrides these defaults:

- `flowables = [TableOfContentsSection(), ListOfFiguresSection(), ListOfTablesSection()]`
- `page_number_format = lowercase roman`
- `end_at_page = left`

Type

`FixedDocumentPartTemplate`

contents

base: None

Overrides these defaults:

- `page_number_format = number`
- `end_at_page = left`

Type

`ContentsPartTemplate`

back_matter

base: None

Overrides these defaults:

- `page_number_format = continue`
- `end_at_page = left`

Type

`BackMatterTemplate`

page

base: None

Overrides these defaults:

- `page_size = $(paper_size)`
- `left_margin = 1in`
- `right_margin = 1in`
- `top_margin = 1in`
- `bottom_margin = 1in`

Type

`PageTemplate`

cover_page

base: page

Type

`PageTemplate`

title_page

base: page

Type

TitlePageTemplate

front_matter_page

base: page

Overrides these defaults:

- header_footer_distance = 0
- header_text = None

Type

PageTemplate

front_matter_right_page

base: front_matter_page

Overrides these defaults:

- footer_text = '\t' '\t' '{PAGE_NUMBER}'
- chapter_header_text = None
- chapter_footer_text = '\t' '\t' '{PAGE_NUMBER}'
- chapter_title_height = 2.5in
- chapter_title_flowables = [<rinoh.paragraph.Paragraph object at 0x7fc322e772b0>]

Type

PageTemplate

front_matter_left_page

base: front_matter_page

Overrides these defaults:

- footer_text = '{PAGE_NUMBER}'

Type

PageTemplate

contents_page

base: page

Overrides these defaults:

- header_footer_distance = 0

Type

PageTemplate

contents_right_page

base: contents_page

Overrides these defaults:

- header_text = '\t' '\t' '{DOCUMENT_TITLE}' ', ' '{DOCUMENT_SUBTITLE}'
- footer_text = '{SECTION_NUMBER(2)}' '. ' '{SECTION_TITLE(2)}' '\t' '\t' '{PAGE_NUMBER}'
- chapter_header_text = None
- chapter_footer_text = '\t' '\t' '{PAGE_NUMBER}'
- chapter_title_height = 2.4in
- chapter_title_flowables = [<rinoh.paragraph.Paragraph object at 0x7fc322e764d0>, <rinoh.paragraph.Paragraph object at 0x7fc322e76380>]

Type

PageTemplate

contents_left_page

base: contents_page

Overrides these defaults:

- header_text = '{DOCUMENT_TITLE}' ', ' '{DOCUMENT_SUBTITLE}'
- footer_text = '{PAGE_NUMBER}' '\t' '\t' '{SectionTitles.chapter}' ' ' '{SECTION_NUMBER(1)}' ' '. ' '{SECTION_TITLE(1)}'

Type

PageTemplate

back_matter_page

base: page

Overrides these defaults:

- columns = 2
- header_footer_distance = 0

Type

PageTemplate

back_matter_right_page

base: back_matter_page

Overrides these defaults:

- header_text = '\t' '\t' '{DOCUMENT_TITLE}' ', ' '{DOCUMENT_SUBTITLE}'
- footer_text = '{SECTION_TITLE(1)}' '\t' '\t' '{PAGE_NUMBER}'
- chapter_header_text = None
- chapter_footer_text = '\t' '\t' '{PAGE_NUMBER}'
- chapter_title_height = 2.5in
- chapter_title_flowables = [<rinoh.paragraph.Paragraph object at 0x7fc322e772b0>]

Type

PageTemplate

back_matter_left_page

base: back_matter_page

Overrides these defaults:

- header_text = '{DOCUMENT_TITLE}' ', ' '{DOCUMENT_SUBTITLE}'
- footer_text = '{PAGE_NUMBER}' '\t' '\t' '{SECTION_TITLE(1)}'

Type

PageTemplate

Configuration

alias of rinoh.template.BookConfiguration

ConfigurationFile

alias of rinoh.template.BookConfigurationFile

Note

The API documentation is still incomplete.

5.1 Attribute (`rinoh.attribute`)

class `rinoh.attribute.AcceptNoneAttributeType`

Accepts 'none' (besides other values)

class `rinoh.attribute.OptionSet`

Accepts the values listed in values

Accepts:

class `rinoh.attribute.Attribute (accepted_type, default_value, description)`

Descriptor used to describe a style attribute

class `rinoh.attribute.OverrideDefault (default_value)`

Overrides the default value of an attribute defined in a superclass

class `rinoh.attribute.AttributesDictionary (base=None, **attributes)`

class `rinoh.attribute.RuleSet (name, base=None, source=None, **kwargs)`

find_source (*name*)

Find top-most ruleset where configuration *name* is defined

class `rinoh.attribute.RuleSetFile (filename, base=None, source=None, **kwargs)`

property location

Textual representation of this source

property root

Directory path for resolving paths relative to this source

class `rinoh.attribute.Bool`

Expresses a binary choice

class `rinoh.attribute.Integer`

Accepts natural numbers

exception `rinoh.attribute.ParseError`

5.2 Color (`rinoh.color`)

class `rinoh.color.Color` (*red, green, blue, alpha=1*)

Color defined by component values

Parameters

- **red** (*float*) – red component (0 .. 1)
- **blue** (*float*) – blue component (0 .. 1)
- **green** (*float*) – green component (0 .. 1)
- **alpha** (*float*) – opacity (0 .. 1)

property **rgba**

classmethod **parse_string** (*string, source*)

classmethod **doc_format** ()

class `rinoh.color.HexColor` (*string*)

Color defined as a hexadecimal string

Parameters

string (*str*) – #RGBA or #RRGGBBAA (# and A are optional)

class `rinoh.color.Gray` (*luminance, alpha=1*)

Shade of gray

Parameters

- **luminance** (*float*) – brightness (0 .. 1)
- **alpha** (*float*) – opacity (0 .. 1)

5.3 Dimension (`rinoh.dimension`)

Classes for expressing dimensions: lengths, widths, line thickness, etc.

Each dimension is expressed in terms of a unit. Several common units are defined here as constants. To create a new dimension, multiply number with a unit:

```
height = 100*PT
width = 50*PERCENT
```

Fractional dimensions are evaluated within the context they are defined in. For example, the width of a `Flowable` is evaluated with respect to the total width available to it.

class `rinoh.dimension.Dimension` (*value=0, unit=None*)

A simple dimension

Parameters

- **value** (*int or float*) – the magnitude of the dimension
- **unit** (*DimensionUnit*) – the unit this dimension is expressed in. Default: `PT`.

grow (*value*)

Grow this dimension (in-place)

The `value` is interpreted as a magnitude expressed in the same unit as this dimension.

Parameters

value (*int or float*) – the amount to add to the magnitude of this dimension

Returns

Dimension – this (growable) dimension itself

```
rinoh.dimension.PT = DimensionUnit(1.0, 'pt')
```

PostScript points

```
rinoh.dimension.PICA = DimensionUnit(12.0, 'pc')
```

computer pica

```
rinoh.dimension.INCH = DimensionUnit(72.0, 'in')
```

imperial/US inch

```
rinoh.dimension.MM = DimensionUnit(2.8346456692913384, 'mm')
```

millimeter

```
rinoh.dimension.CM = DimensionUnit(28.346456692913385, 'cm')
```

centimeter

```
rinoh.dimension.PERCENT = FractionUnit(100, '%')
```

fraction of 100

```
rinoh.dimension.QUARTERS = FractionUnit(4, '4')
```

fraction of 4

5.4 Document (`rinoh.document`)

```
class rinoh.document.DocumentTree ( flowables, options=None, style=None, source=None )
```

Holds the document's contents as a tree of flowables

Parameters

- **flowables** (*list [Flowable]*) – the list of top-level flowables
- **options** (*Reader*) – frontend-specific options

```
class rinoh.document.Document ( document_tree, stylesheet, language, strings=None, backend=None )
```

Renders a document tree to pages

Parameters

- **document_tree** (*DocumentTree*) – a tree of the document's contents
- **stylesheet** (*StyleSheet*) – style sheet used to style document elements
- **language** (*Language*) – the language to use for standard strings
- **strings** (*Strings*) – overrides localized strings provided by *language*
- **backend** – the backend used for rendering the document

```
render ( filename_root=None, file=None )
```

Render the document repeatedly until the output no longer changes due to cross-references that need some iterations to converge.

5.4.1 Pages

class `rinoh.document.Page (document_part, number, paper, orientation='portrait')`

A single page in a document.

A `Page` is a `Container`, so other containers can be added as children.

Parameters

- **document_part** (*DocumentPart*) – the document part this page is part of
- **number** (*int*) – the 1-based index of this page in the document part
- **paper** (*Paper*) – determines the dimensions of this page
- **orientation** (*PageOrientation*) – the orientation of this page

property `page`

Returns the page itself.

render ()

Render the contents of this container to its canvas.

Note that the rendered contents need to be `place()`d on the parent container's canvas before they become visible.

place ()

Place this container's canvas onto the parent container's canvas.

class `rinoh.document.PageOrientation`

Accepts: portrait, landscape

class `rinoh.document.PageType`

Accepts: left, right, any

class `rinoh.document.PageNumberFormat`

How (or if) page numbers are displayed

Accepts: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman, continue

5.5 Drawing Primitives (`rinoh.draw`)

class `rinoh.draw.Stroke (width, color)`

The display properties of a line

Parameters

- **width** (*Dimension*) – the width of the line
- **color** (*Color*) – the color of the line

class `rinoh.draw.Line (start, end, style=None, parent=None)`

Draws a line

Parameters

- **start** (*2-tuple*) – coordinates for the start point of the line
- **end** (*2-tuple*) – coordinates for the end point of the line

style_class

alias of `rinoh.draw.LineStyle`

```
class rinoh.draw.Shape ( style=None, parent=None )
    Base class for closed shapes

    style_class
        alias of rinoh.draw.ShapeStyle

class rinoh.draw.Polygon ( points, style=None, parent=None )

class rinoh.draw.Rectangle ( bottom_left, width, height, style=None, parent=None )
```

5.6 Flowable (rinoh.flowable)

```
class rinoh.flowable.Flowable ( align=None, width=None, id=None, style=None,
parent=None, source=None )
    A document element that can be “flowed” into a container on the page.
    A flowable can adapt to the width of the container, or it can horizontally align itself in
    the container.

    Parameters
        • align (HorizontalAlignment) – horizontal alignment of the flowable
        • width (FlowableWidth or DimensionBase) – the width of the flowable.

class rinoh.flowable.FlowableState ( flowable, _initial=True )
    Stores a flowable’s rendering state, which can be copied.
    This enables saving the rendering state at certain points in the rendering process, so
    rendering can later be resumed at those points, if needed.
```

5.6.1 No-Output Flowables

These flowables do not directly place anything on the page. All except `DummyFlowable` do have side-effects however. Some of these side-effects affect the rendering of the document in an indirect way.

```
class rinoh.flowable.DummyFlowable ( id=None, parent=None )
    A flowable that does not directly place anything on the page.
    Subclasses can produce side-effects to affect the output in another way.

class rinoh.flowable.AnchorFlowable ( id=None, parent=None )
    A dummy flowable that registers a destination anchor.
    Places a destination for the flowable’s ID at the current cursor position.

class rinoh.flowable.SetMetadataFlowable ( parent=None, **metadata )
    A dummy flowable that stores metadata in the document.
    The metadata is passed as keyword arguments. It will be available to other flowables
    during the rendering stage.

class rinoh.flowable.WarnFlowable ( message, parent=None )
    A dummy flowable that emits a warning during the rendering stage.

    Parameters
        • message (str) – the warning message to emit

class rinoh.flowable.PageBreak ( page_break='any' )
```

5.6.2 Labeled Flowables

```
class rinoh.flowable.LabeledFlowable ( label, flowable, id=None, style=None, parent=None )
```

A flowable with a label.

The flowable and the label are rendered side-by-side. If the label exceeds the *label_max_width* style attribute value, the flowable is rendered below the label.

Parameters

- **label** (*Flowable*) – the label for the flowable
- **flowable** (*Flowable*) – the flowable to label

style_class

alias of `rinoh.flowable.LabeledFlowableStyle`

prepare (*flowable_target*)

Determine number labels and register references with the document

render (*container, last_descender, state, label_column_width=None, space_below=0, **kwargs*)

Renders the flowable's content to *container*, with the flowable's top edge lining up with the container's cursor. *descender* is the descender height of the preceding line or *None*.

```
class rinoh.flowable.LabeledFlowableState ( flowable, content_flowable_state, _initial=True )
```

5.6.3 Grouping Flowables

```
class rinoh.flowable.GroupedFlowables ( align=None, width=None, id=None, style=None, parent=None, source=None )
```

Groups a list of flowables and renders them one below the other.

Makes sure that a flowable for which *keep_with_next* is enabled is not separated from the flowable that follows it.

Subclasses should implement `flowables()`.

style_class

alias of `rinoh.flowable.GroupedFlowablesStyle`

flowables (*container*)

Generator yielding the Flowables to group

render (*container, descender, state, first_line_only=False, **kwargs*)

Renders the flowable's content to *container*, with the flowable's top edge lining up with the container's cursor. *descender* is the descender height of the preceding line or *None*.

```
class rinoh.flowable.GroupedFlowablesState ( groupedflowables, flowables, first_flowable_state=None, _initial=True, _index=0 )
```

```
class rinoh.flowable.StaticGroupedFlowables ( flowables, align=None, width=None, id=None, style=None, parent=None, source=None )
```

Groups a static list of flowables.

Parameters

flowables (*iterable[Flowable]*) – the flowables to group

flowables (*container*)

Generator yielding the `Flowables` to group

build_document (*flowable_target*)

Set document metadata and populate front and back matter

prepare (*flowable_target*)

Determine number labels and register references with the document

class `rinoh.flowable.GroupedLabeledFlowables` (*align=None, width=None, id=None, style=None, parent=None, source=None*)

Groups a list of labeled flowables, lining them up.

render (*container, descender, state, **kwargs*)

Renders the flowable's content to *container*, with the flowable's top edge lining up with the container's cursor. *descender* is the descender height of the preceding line or *None*.

5.6.4 Floating Flowables

class `rinoh.flowable.Float` (*align=None, width=None, id=None, style=None, parent=None, source=None*)

A flowable that can optionally be placed elsewhere on the page.

If this flowable's *float* style attribute is set to `True`, it is not flowed in line with the surrounding flowables, but it is instead flowed into another container pointed to by the former's `Container.float_space` attribute.

This is typically used to place figures and tables at the top or bottom of a page, instead of in between paragraphs.

flow (*container, last_descender, state=None, **kwargs*)

Flow this flowable into *container* and return the vertical space consumed.

The flowable's contents are preceded by a vertical space with a height as specified in its style's *space_above* attribute. Similarly, the flowed content is followed by a vertical space with a height given by the *space_below* style attribute.

5.6.5 Styling Properties

class `rinoh.flowable.HorizontalAlignment`

Controls horizontal placement

Accepts: `left, right, center`

class `rinoh.flowable.FlowableWidth`

Controls the width of a flowable

Accepts: `auto, fill` or a numeric value followed by a unit (`pt, in, pc, mm, cm, %, /2, /4`)

5.7 Fonts and Typefaces (`rinoh.font`)

Classes for fonts and typefaces.

class `rinoh.font.Font` (*filename, weight, slant, width*)

A collection of glyphs in a particular style

This is a base class for classes that parse different font formats. See `rinoh.font.type1` and `rinoh.font.opentype`.

Parameters

- **filename** (*str*) – filename of the font file to load
- **weight** (*FontWeight*) – weight of the font
- **slant** (*FontSlant*) – slant of the font
- **width** (*FontWidth*) – width of the font

encoding

If no encoding is set for the `Font`, glyphs are addressed by glyph ID (and thus support more than 256 glyphs).

`get_glyph_metrics (char, variant)`

Return the glyph metrics for a particular character

If the glyph of requested font variant is not present in the font, the *normal* variant is returned instead. If that is not present either, an exception is raised.

Parameters

- **char** (*str of length 1*) – the character for which to find the glyph
- **variant** (*FontVariant*) – the variant of the glyph to return

Returns

GlyphMetrics – the requested glyph metrics

Raises

MissingGlyphException – when the requested glyph is not present in the font

`get_ligature (glyph, successor_glyph)`

Return the ligature to replace the given glyphs

If no ligature is defined in the font for the given glyphs, return `None`.

Parameters

- **glyph** (*GlyphMetrics*) – the first of the glyphs to combine
- **successor_glyph** (*GlyphMetrics*) – the second of the glyphs to combine

Returns

GlyphMetrics or *None* – the ligature to replace the given glyphs

`get_kerning (a, b)`

Look up the kerning for two glyphs

Parameters

- **a** (*GlyphMetrics*) – the first of the glyphs
- **b** (*GlyphMetrics*) – the second of the glyphs

Returns

float – the kerning value in font units

`class rino.h.font.Typeface (name, *fonts)`

A set of fonts that share common design features

The fonts collected in a typeface differ in weight, width and/or slant.

Parameters

***fonts** (*Font*) – the fonts that make up this typeface

`fonts ()`

Generator yielding all fonts of this typeface

Yields

Font – the next font in this typeface

get_font (*weight*=400, *slant*='upright', *width*=5)

Return the font matching or closest to the given style

If a font with the given weight, slant and width is available, return it. Otherwise, return the font that is closest in style.

Parameters

- **weight** (*FontWeight*) – weight of the font
- **slant** (*FontSlant*) – slant of the font
- **width** (*FontWidth*) – width of the font

Returns

Font – the requested font

class rinoh.font.style.**FontWeight**

Accepts: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

class rinoh.font.style.**FontSlant**

Accepts: upright, oblique, italic

class rinoh.font.style.**FontWidth**

Accepts: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

class rinoh.font.style.**FontVariant**

Accepts: normal, small capital, oldstyle figures

class rinoh.font.style.**TextPosition**

Accepts: normal, superscript, subscript

5.8 Images and Figures (**rinoh.image**)

class rinoh.image.**Image** (*filename_or_file*, *scale*=1.0, *width*=None, *height*=None, *dpi*=None, *rotate*=0, *limit_width*=<rinoh.dimension.Fraction object>, *align*=None, *id*=None, *style*=None, *parent*=None, *source*=None)

class rinoh.image.**InlineImage** (*filename_or_file*, *scale*=1.0, *width*=None, *height*=None, *dpi*=None, *rotate*=0, *baseline*=None, *id*=None, *style*=None, *parent*=None, *source*=None)

arguments

alias of rinoh.image.InlineImageArgs

class rinoh.image.**BackgroundImage** (*filename_or_file*, *scale*=1.0, *width*=None, *height*=None, *dpi*=None, *rotate*=0, *limit_width*=<rinoh.dimension.Fraction object>, *align*=None, *id*=None, *style*=None, *parent*=None, *source*=None)

Image to place in the background of a page

Takes the same arguments as Image.

arguments

alias of rinoh.image.ImageArgs

```
class rinoh.image.ImageArgs ( base=None, **attributes )
```

limit_width

Limit the image width when none of *scale*, *width* and *height* are given and the image would be wider than the container

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 100%

align

How to align the image within the page

Accepts HorizontalAlignment: left, right, center

Default: left

file_or_filename

Path to the image file (inherited from ImageArgsBase)

Accepts ImagePath: path to an image file enclosed in quotes

Default: none

scale

Scaling factor for the image (inherited from ImageArgsBase)

Accepts Scale: fit, fill or a float larger than 0

Default: fit

width

The width to scale the image to (inherited from ImageArgsBase)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: none

height

The height to scale the image to (inherited from ImageArgsBase)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: none

dpi

Overrides the DPI value set in the image (inherited from ImageArgsBase)

Accepts Integer: a natural number (positive integer)

Default: (no value)

rotate

Angle in degrees to rotate the image (inherited from ImageArgsBase)

Accepts Integer: a natural number (positive integer)

Default: (no value)

```
class rinoh.image.Scale
```

Scaling factor for images

Can be a numerical value where a value of 1 keeps the image's original size or one of values.

Accepts: fit, fill or a float larger than 0

```
class rinoh.image.Caption ( content, custom_label=None, align=None, width=None, id=None, style=None, parent=None, source=None )
```

style_class

alias of rinoh.image.CaptionStyle


```

class rinoh.image.Figure ( flowables, align=None, width=None, id=None, style=None,
parent=None, source=None )

    style_class
        alias of rinoh.image.FigureStyle

class rinoh.image.ListOfFiguresSection

    list_class
        alias of rinoh.image.ListOfFigures

class rinoh.image.ListOfFigures ( local=False, id=None, style=None, parent=None )

```

5.9 Index (`rinoh.index`)

```

class rinoh.index.IndexSection ( title=None, flowables=None, style=None )

class rinoh.index.Index ( id=None, style=None, parent=None )

    style_class
        alias of rinoh.index.IndexStyle

    flowables ( container )
        Generator yielding the Flowables to group

class rinoh.index.IndexLabel ( content, custom_label=None, align=None, width=None,
id=None, style=None, parent=None, source=None )

class rinoh.index.IndexTerm ( *levels )

class rinoh.index.InlineIndexTarget ( index_terms, *args, **kwargs )

    to_string ( flowable_target )
        Return the text content of this styled text.

class rinoh.index.IndexTarget ( index_terms, parent=None )

    flow ( container, last_descender, state=None, **kwargs )
        Flow this flowable into container and return the vertical space consumed.
        The flowable's contents are preceded by a vertical space with a height as specified in its
        style's space_above attribute. Similarly, the flowed content is followed by a vertical space
        with a height given by the space_below style attribute.

```

5.10 Language (`rinoh.language`)

```

class rinoh.language.Language ( code, name )
    Collects localized strings for a particular language

    Parameters
        • code (str) – short code identifying the language
        • name (str) – native name of the language

    languages
        Dictionary mapping codes to Languages

```

The following languages are supported:

```
rinoh.language.EN = Language('en', 'English')
```

Localized strings for English

SectionTitles

Contents

Table of Contents

List_of_figures

List of Figures

List_of_tables

List of Tables

Chapter

Chapter

Index

Index

AdmonitionTitles

Attention

Attention!

Caution

Caution!

Danger

!DANGER!

Error

Error

Hint

Hint

Important

Important

Note

Note

Tip Tip

Warning

Warning

Seealso

See also

```
rinoh.language.FR = Language('fr', 'Français')
```

Localized strings for Français

SectionTitles

Contents

Table des Matières

List_of_figures

Liste des Figures

List_of_tables
Liste des Tableaux

Chapter
Chapitre

Index
Index

AdmonitionTitles

Attention
Attention!

Caution
Prudence!

Danger
!DANGER!

Error
Erreur

Hint
Conseil

Important
Important

Note
Note

Tip Astuce

Warning
Avertissement

Seealso
Voir aussi

`rinoh.language.IT = Language('it', 'Italiano')`

Localized strings for Italiano

SectionTitles

Contents
Contenuti

List_of_figures
Elenco delle Figure

List_of_tables
Elenco delle Tabelle

Chapter
Capitolo

Index
Indice

AdmonitionTitles

Attention
 Attenzione!
 Caution
 Prudenza!
 Danger
 !PERICOLO!
 Error
 Errore
 Hint
 Consiglio
 Important
 Importante
 Note
 Nota
 Tip Suggestimento
 Warning
 Avvertimento
 Seealso
 Vedi anche

```
rinoh.language.NL = Language('nl', 'Nederlands')
```

Localized strings for Nederlands
 SectionTitles

Contents
 Inhoudsopgave
 List_of_figures
 Lijst van Figuren
 List_of_tables
 Lijst van Tabellen

Chapter
 Hoofdstuk

Index
 Index
 AdmonitionTitles

Attention
 Opgelet!

Caution
 Pas op!

Danger
 !GEVAAR!

Error
 Fout

Hint

Hint

Important

Belangrijk

Note

Noot

Tip Tip

Warning

Waarschuwing

Seealso

Zie ook

```
rinoh.language.PL = Language('pl', 'Polski')
```

Localized strings for Polski

SectionTitles

Contents

Spis Treści

List_of_figures

Spis Ilustracji

List_of_tables

Spis Tabel

Chapter

Rozdział

Index

Skorowidz

AdmonitionTitles

Attention

Uwaga!

Caution

Ostrożnie!

Danger

!NIEBEZPIECZEŃSTWO!

Error

Błąd

Hint

Wskazówka

Important

Ważne

Note

Notatka

Tip Porada

Warning

Ostrzeżenie

Seealso

Zobacz również

5.11 Number (`rinoh.number`)

class `rinoh.number.NumberFormat`

How (or if) numbers are displayed

Instead of a numbering format, it's possible to supply a custom label (`StyledText`) to show instead of the number.

Accepts: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

class `rinoh.number.Label (custom_label=None)`

Mixin class that formats a label

Parameters

custom_label (`StyledText`) – a frontend can supply a custom label to use instead of an automatically determined label (typically a number)

class `rinoh.number.LabelStyle (base=None, **attributes)`

Style class for `Label`

label_prefix

Text to prepend to the label

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified

Accepts `Bool`: true or false

Default: false

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

class `rinoh.number.NumberStyle (base=None, **attributes)`

Style class for `Number`

number_format

How numbers are formatted

Accepts `NumberFormat`: none, number, symbol, lowercase character,

uppercase character, lowercase roman, uppercase roman
Default: number

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)

Accepts `Bool`: true or false

Default: false

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

`rinoh.number.format_number (number, format)`

Format *number* according the given *format* (`NumberFormat`)

5.12 Paper sizes (rinoh.paper)

The `Paper` class and a number of predefined paper formats.

class `rinoh.paper.Paper (name, width, height)`

Defines a paper size.

Parameters

- **name** (*str*) – the name of this paper type
- **width** (*Dimension*) – the (portrait) width of this paper type
- **height** (*Dimension*) – the (portrait) height of this paper type

`rinoh.paper.A0 = Paper('A0', width=841*MM, height=1189*MM)`

`rinoh.paper.A1 = Paper('A1', width=594*MM, height=841*MM)`

`rinoh.paper.A2 = Paper('A2', width=420*MM, height=594*MM)`

`rinoh.paper.A3 = Paper('A3', width=297*MM, height=420*MM)`

`rinoh.paper.A4 = Paper('A4', width=210*MM, height=297*MM)`

`rinoh.paper.A5 = Paper('A5', width=148*MM, height=210*MM)`

`rinoh.paper.A6 = Paper('A6', width=105*MM, height=148*MM)`

`rinoh.paper.A7 = Paper('A7', width=74*MM, height=105*MM)`

```

rinoh.paper.A8 = Paper('A8', width=52*MM, height=74*MM)
rinoh.paper.A9 = Paper('A9', width=37*MM, height=52*MM)
rinoh.paper.A10 = Paper('A10', width=26*MM, height=37*MM)
rinoh.paper.LETTER = Paper('letter', width=8.5*INCH, height=11*INCH)
rinoh.paper.LEGAL = Paper('legal', width=8.5*INCH, height=14*INCH)
rinoh.paper.JUNIOR_LEGAL = Paper('junior legal', width=8*INCH, height=5*INCH)
rinoh.paper.LEDGER = Paper('ledger', width=17*INCH, height=11*INCH)
rinoh.paper.TABLOID = Paper('tabloid', width=11*INCH, height=17*INCH)

```

5.13 Paragraph (`rinoh.paragraph`)

```

class rinoh.paragraph.ParagraphBase ( custom_label=None, align=None, width=None,
id=None, style=None, parent=None, source=None )

```

Base class for paragraphs

A paragraph holds styled text and other line elements to be flowed into a container.

style_class

alias of `rinoh.paragraph.ParagraphStyle`

prepare (*flowable_target*)

Determine number labels and register references with the document

render (*container, descender, state, space_below=0, first_line_only=False*)

Typeset the paragraph

The paragraph is typeset in the given container starting below the current cursor position of the container. When the end of the container is reached, the rendering state is preserved to continue setting the rest of the paragraph when this method is called with a new container.

Parameters

- **container** (*Container*) – the container to render to
- **descender** (*float or None*) – descender height of the preceding line
- **state** (*ParagraphState*) – the state where rendering will continue
- **first_line_only** (*bool*) – typeset only the first line

```

class rinoh.paragraph.Paragraph ( content, custom_label=None, align=None, width=None,
id=None, style=None, parent=None, source=None )

```

```

class rinoh.paragraph.ParagraphState ( paragraph, words, nested_flowable_state=None,
_first_word=None, _initial=True )

```

5.13.1 Styled Text (`rinoh.text`)

```

class rinoh.text.StyledText ( id=None, style=None, parent=None, source=None )

```

Base class for text that has a `TextStyle` associated with it.

to_string (*flowable_target*)

Return the text content of this styled text.

is_script (*container*)
Returns *True* if this styled text is super/subscript.

script_level (*container*)
Nesting level of super/subscript.

height (*container*)
Font size after super/subscript size adjustment.

y_offset (*container*)
Vertical baseline offset (up is positive).

property items
The list of items in this *StyledText*.

style_class
alias of `rinoh.text.TextStyle`

class `rinoh.text.SingleStyledText` (*text*, *style=None*, *parent=None*, *source=None*)
Text with a single style applied

class `rinoh.text.MixedStyledText` (*text_or_items*, *id=None*, *style=None*, *parent=None*, *source=None*)
Concatenation of styled text

Parameters

- **text_or_items** (*str*, *StyledText* or iterable of these) – mixed styled text
- **style** – see *Styled*
- **parent** – see *DocumentElement*

prepare (*flowable_target*)
Determine number labels and register references with the document

append (*item*)
Append *item* (*StyledText* or *str*) to the end of this mixed-styled text.
The parent of *item* is set to this mixed-styled text.

property items
The list of items in this *StyledText*.

copy (*parent=None*)
Return a shallow copy of the list.

class `rinoh.text.Locale`
Selects a language

class `rinoh.text.NoBreakAfter` (*iterable=()*, */*)
List of words after which no line break will be allowed

5.13.2 Inline Elements (`rinoh.inline`)

`class rinoh.inline.InlineFlowable (baseline=None, id=None, style=None, parent=None, source=None)`

style_class

alias of `rinoh.inline.InlineFlowableStyle`

5.13.3 Styling Properties

`class rinoh.paragraph.TextAlign`

Text justification

Accepts: left, right, center, justify

Line Spacing

`class rinoh.paragraph.LineSpacing`

Base class for line spacing types

Line spacing is defined as the distance between the baselines of two consecutive lines of text in a paragraph.

advance (*line*, *last_descender*, *container*)

Return the distance between the descender of the previous line and the baseline of the current line.

`class rinoh.paragraph.DefaultSpacing`

The default line spacing as specified by the font.

advance (*line*, *last_descender*, *container*)

Return the distance between the descender of the previous line and the baseline of the current line.

`class rinoh.paragraph.ProportionalSpacing (factor)`

Line spacing proportional to the line height

Parameters

factor (*float*) – amount by which the line height is multiplied to obtain the line spacing

advance (*line*, *last_descender*, *container*)

Return the distance between the descender of the previous line and the baseline of the current line.

`class rinoh.paragraph.FixedSpacing (pitch, minimum=ProportionalSpacing(1.0))`

Fixed line spacing, with optional minimum spacing

Parameters

- **pitch** (*Dimension*) – the distance between the baseline of two consecutive lines of text
- **minimum** (*LineSpacing*) – the minimum line spacing to prevents lines with large fonts (or inline elements) from overlapping; set to `None` if no minimum is required, set to `None`

advance (*line*, *last_descender*, *container*)

Return the distance between the descender of the previous line and the baseline of

the current line.

class rinoh.paragraph.**Leading** (*leading*)

Line spacing determined by the space in between two lines

Parameters

leading (*Dimension*) – the space between the bottom of a line and the top of the next line of text

advance (*line, last_descender, container*)

Return the distance between the descender of the previous line and the baseline of the current line.

The following standard line spacings have been predefined:

rinoh.paragraph.**DEFAULT** = **DefaultSpacing()**

The default line spacing as specified by the font.

rinoh.paragraph.**STANDARD** = **ProportionalSpacing(1.2)**

Line spacing of 1.2 times the line height.

rinoh.paragraph.**SINGLE** = **ProportionalSpacing(1.0)**

Line spacing equal to the line height (no leading).

rinoh.paragraph.**DOUBLE** = **ProportionalSpacing(2.0)**

Line spacing of double the line height.

Tabulation

class rinoh.paragraph.**TabAlign**

Alignment of text with respect to a tab stop

Accepts: left, right, center

class rinoh.paragraph.**TabStop** (*position, align='left', fill=None*)

Horizontal position for aligning text of successive lines

Parameters

- **position** (*Dimension or Fraction*) – tab stop position
- **align** (*TabAlign*) – the alignment of text with respect to the tab stop position
- **fill** (*str*) – string pattern to fill the empty tab space with

get_position (*line_width*)

Return the absolute position of this tab stop.

class rinoh.paragraph.**TabStopList** (*iterable=(), /*)

List of tab stop positions (with alignment and fill string)

5.13.4 Rendering Internals

class rinoh.paragraph.**Glyph** (*metrics, width, char*)

class rinoh.paragraph.**GlyphsSpan** (*span, chars_to_glyphs, glyphs=[]*)

5.13.5 Miscellaneous Internals

class rinoh.paragraph.**HyphenatorStore**

5.14 Cross-References and Fields (`rinoh.reference`)

```
class rinoh.reference.Reference ( target_id, *args, **kwargs )

class rinoh.reference.ReferenceField ( type=None, custom_title=None, style=None,
parent=None, source=None )

class rinoh.reference.ReferenceText ( id=None, style=None, parent=None, source=None )

class rinoh.reference.ReferenceType
    Accepts: reference, number, title, page, custom

class rinoh.reference.ReferencingParagraph ( target_id_or_flowable, id=None,
style=None, parent=None )

    style_class
        alias of rinoh.reference.ReferencingParagraphStyle

    target_style ( document )
        Filter selection on the style attribute of the target flowable

    target_has_class ( document )
        Filter selection on a class of the target flowable

    target_has_classes ( document )
        Filter selection on a set of classes of the target flowable

    target_is_of_type ( document )
        Filter selection on the type of the target flowable

class rinoh.reference.Note ( flowable, id=None, style=None, parent=None )

    style_class
        alias of rinoh.reference.NoteStyle

    flow ( container, last_descender, state=None, footnote=False, **kwargs )
        Flow this flowable into container and return the vertical space consumed.
        The flowable's contents are preceded by a vertical space with a height as specified in its
        style's space_above attribute. Similarly, the flowed content is followed by a vertical space
        with a height given by the space_below style attribute.

class rinoh.reference.NoteMarkerBase ( custom_label=None, **kwargs )

    style_class
        alias of rinoh.reference.NoteMarkerStyle

    prepare ( flowable_target )
        Determine number labels and register references with the document

class rinoh.reference.NoteMarkerByID ( target_id, *args, **kwargs )

class rinoh.reference.NoteMarkerWithNote ( referenceable, type='number', **kwargs )

    prepare ( flowable_target )
        Determine number labels and register references with the document

class rinoh.reference.Field ( type, id=None, style=None, parent=None, source=None )
```

5.15 Structure (`rinoh.structure`)

5.15.1 Sections

class `rinoh.structure.Section` (*flowables*, *align=None*, *width=None*, *id=None*, *style=None*, *parent=None*, *source=None*)

A subdivision of a document

A section usually has a heading associated with it, which is optionally numbered.

class `rinoh.structure.Heading` (*content*, *custom_label=None*, *align=None*, *width=None*, *id=None*, *style=None*, *parent=None*, *source=None*)

The title for a section

Parameters

title (*StyledText*) – this heading’s text

style_class

alias of `rinoh.structure.HeadingStyle`

prepare (*container*)

Determine number labels and register references with the document

flow (*container*, *last_descender*, *state=None*, ***kwargs*)

Flow this flowable into *container* and return the vertical space consumed.

The flowable’s contents are preceded by a vertical space with a height as specified in its style’s *space_above* attribute. Similarly, the flowed content is followed by a vertical space with a height given by the *space_below* style attribute.

class `rinoh.structure.SectionTitles` (***strings*)

Collection of localized titles for common sections

contents

Title for the table of contents section

Type

`String`

list_of_figures

Title for the list of figures section

Type

`String`

list_of_tables

Title for the list of tables section

Type

`String`

chapter

Label for top-level sections

Type

`String`

index
 Title for the index section
 Type
 String

5.15.2 Lists

```
class rinoh.structure.List ( list_items, start_index=1, id=None, style=None, parent=None )

  style_class
    alias of rinoh.structure.ListStyle

class rinoh.structure.DefinitionList ( flowables, align=None, width=None, id=None, style=None, parent=None, source=None )
```

5.15.3 Table of Contents

```
class rinoh.structure.TableOfContentsSection

class rinoh.structure.TableOfContents ( local=False, id=None, style=None, parent=None )

  style_class
    alias of rinoh.structure.TableOfContentsStyle

  flowables ( container )
    Generator yielding the Flowables to group

class rinoh.structure.TableOfContentsEntry ( flowable, id=None, style=None, parent=None )

  style_class
    alias of rinoh.structure.TableOfContentsEntryStyle
```

5.15.4 Admonitions

```
class rinoh.structure.Admonition ( flowables, title=None, type=None, id=None, style=None, parent=None )

  style_class
    alias of rinoh.structure.AdmonitionStyle

  flowables ( container )
    Generator yielding the Flowables to group

class rinoh.structure.AdmonitionTitles ( **strings )
  Collection of localized titles for common admonitions

  attention
    Title for attention admonitions
    Type
    String
```

caution
 Title for caution admonitions
 Type
 String

danger
 Title for danger admonitions
 Type
 String

error
 Title for error admonitions
 Type
 String

hint
 Title for hint admonitions
 Type
 String

important
 Title for important admonitions
 Type
 String

note
 Title for note admonitions
 Type
 String

tip
 Title for tip admonitions
 Type
 String

warning
 Title for warning admonitions
 Type
 String

seealso
 Title for see-also admonitions
 Type
 String

5.15.5 Horizontal Rule

class rinoh.structure.**HorizontalRule** (*align=None, width=None, id=None, style=None, parent=None, source=None*)

style_class

alias of rinoh.structure.HorizontalRuleStyle

render (*container, descender, state, **kwargs*)

Renders the flowable's content to *container*, with the flowable's top edge lining up with the container's cursor. *descender* is the descender height of the preceding line or *None*.

5.16 Strings (rinoh.strings)

class rinoh.strings.**String** (*description*)

Descriptor used to describe a configurable string

Parameters

description (*str*) – a short description for this string

class rinoh.strings.**StringCollection** (***strings*)

A collection of related configurable strings

Subclasses

- AdmonitionTitles
- SectionTitles
- UserStrings

class rinoh.strings.**UserStrings** (***strings*)

Collection of user-specified strings

Unlike other string collections, these are not limited to a predefined set.

Attributes:

class rinoh.strings.**Strings** (**string_collections*)

Stores several StringCollections

class rinoh.strings.**StringField** (*strings_class, key, style=None, parent=None, source=None*)

Styled text that will be substituted with a configured string

The displayed string is either the localized string as determined by the language set for the document or the user-supplied string passed to the `TemplateConfiguration`.

5.17 Style (rinoh.style)

class rinoh.style.**Styled** (*id=None, style=None, parent=None, source=None*)

A document element who's style can be configured.

Parameters

style (*str, Style*) – the style to associate with this element. If *style* is a string, the corresponding style is lookup up in the document's style sheet by means of selectors.

style_class

The `Style` subclass that corresponds to this `Styled` subclass.

configuration_class = None**property has_id**

Filter selection on an ID of this `Styled`

property has_class

Filter selection on a class of this `Styled`

property has_classes

Filter selection on a set of classes of this `Styled`

class rinoh.style.Style (base=None, **attributes)

Dictionary storing style attributes.

The style attributes associated with this `Style` are specified as class attributes of type `Attribute`.

Style attributes can also be accessed as object attributes.

hide

Suppress rendering this element

Accepts Bool: true or false

Default: false

5.17.1 Style Sheet

class rinoh.style.StyleSheet (name, matcher=None, base=None, source=None, description=None, pygments_style=None, **user_options)

Dictionary storing a collection of related styles by name.

Styles stored in a `StyleSheet` can refer to their base style by name.

Parameters

- **name** (*str*) – a label for this style sheet
- **matcher** (*StyledMatcher*) – the matcher providing the selectors the styles contained in this style sheet map to. If no matcher is given and *base* is specified, the *base*'s matcher is used. If *base* is not set, the default matcher is used.
- **base** (*StyleSheet* or *str*) – the style sheet to extend
- **description** (*str*) – a short string describing this style sheet
- **pygments_style** (*str*) – the Pygments style to use for styling code blocks

get_selector (name)

Find a selector mapped to a style in this or a base style sheet.

Parameters

name (*str*) – a style name

Returns

Selector – the selector mapped to the style *name*

Raises

KeyError – if the style *name* was not found in this or a base style sheet

class rinoh.style.StyleSheetFile (filename, base=None, source=None, **kwargs)

Loads styles defined in a *.rts* file (INI format).

Parameters

filename (*str*) – the path to the style sheet file

`StyleSheetFile` takes the same optional arguments as `StyleSheet`. These can also be specified in the `[STYLESHEET]` section of the style sheet file. If an argument is specified in both places, the one passed as an argument overrides the one specified in the style sheet file.

class `rinoh.style.StyledMatcher` (*mapping_or_iterable=None*, ***kwargs*)

Dictionary mapping labels to selectors.

This matcher can be initialized in the same way as a `dict` by passing a mapping, an iterable and/or keyword arguments.

update (***F* [, *E*]) → *None*. Update *D* from dict/iterable *E* and *F*.

If *E* is present and has a `.keys()` method, then does: for *k* in *E*: *D*[*k*] = *E*[*k*] If *E* is present and lacks a `.keys()` method, then does: for *k*, *v* in *E*: *D*[*k*] = *v* In either case, this is followed by: for *k* in *F*: *D*[*k*] = *F*[*k*]

5.18 Tables (`rinoh.table`)

class `rinoh.table.Table` (*body*, *head=None*, *align=None*, *width=None*, *column_widths=None*, *id=None*, *style=None*, *parent=None*)

style_class

alias of `rinoh.table.TableStyle`

prepare (*flowable_target*)

Determine number labels and register references with the document

render (*container*, *last_descender*, *state*, *space_below=0*, ***kwargs*)

Renders the flowable's content to *container*, with the flowable's top edge lining up with the container's cursor. *descender* is the descender height of the preceding line or *None*.

class `rinoh.table.TableWithCaption` (*flowables*, *align=None*, *width=None*, *id=None*, *style=None*, *parent=None*, *source=None*)

style_class

alias of `rinoh.table.TableWithCaptionStyle`

class `rinoh.table.TableSection` (*rows*, *style=None*, *parent=None*)

prepare (*flowable_target*)

Determine number labels and register references with the document

class `rinoh.table.TableHead` (*rows*, *style=None*, *parent=None*)

class `rinoh.table.TableBody` (*rows*, *style=None*, *parent=None*)

class `rinoh.table.TableRow` (*cells*, *style=None*, *parent=None*)

prepare (*flowable_target*)

Determine number labels and register references with the document

get_rowspanned_columns ()

Return a dictionary mapping column indices to the number of columns spanned.

```

class rinoh.table.TableCell ( flowables, rowspan=1, colspan=1, id=None, style=None,
parent=None )

    style_class
        alias of rinoh.table.TableCellStyle

class rinoh.table.TableCellBorder ( rendered_cell, cell_height, position, style=None )

    style_class
        alias of rinoh.table.TableCellBorderStyle

class rinoh.table.TableCellBackground ( bottom_left, width, height, style=None,
parent=None )

    style_class
        alias of rinoh.table.TableCellBackgroundStyle

class rinoh.table.VerticalAlign
    Accepts: top, middle, bottom

class rinoh.table.ListOfTables ( local=False, id=None, style=None, parent=None )

class rinoh.table.ListOfTablesSection

    list_class
        alias of rinoh.table.ListOfTables

```

5.19 Templates (rinoh.template)

5.19.1 Documents

Document templates are created by subclassing `DocumentTemplate`, just like the Chapter 4 shipped with rinohtype.

```

class rinoh.template.DocumentTemplate ( document_tree, configuration=None,
backend=None )

```

Template for documents

Parameters

- **document_tree** (*DocumentTree*) – a tree of the document’s contents
- **configuration** (*TemplateConfiguration*) – configuration for this template
- **backend** – the backend used for rendering the document

language

The main language of the document

Accepts Language: the code of one of the supported languages

Default: EN (English)

strings

Strings to override standard element names

Accepts Strings: strings need to be entered in INI sections named after the `StringCollection` subclasses

Default: none

stylesheet

The stylesheet to use for styling document elements

Accepts `StyleSheet`: the name of an Section 3.1 or the filename of a stylesheet file (with the `.rts` extension)

Default: `sphinx (= rinoh.stylesheets.sphinx)`

parts

The parts making up this document

Accepts `PartsList`: a space-separated list of document part template names

Default: (empty list)

Configuration

alias of `rinoh.template.DocumentTemplateConfiguration`

ConfigurationFile

alias of `rinoh.template.DocumentTemplateConfigurationFile`

Document templates can be customized by setting values for the configuration attributes defined in a `DocumentTemplate` subclass in a `TemplateConfiguration`. An template configuration can be passed as *configuration* on template instantiation. However, it is better to make use of the `document` method, however.

class `rinoh.template.TemplateConfiguration` (*name*, *base=None*, *source=None*, *template=None*, *description=None*, ***options*)

Stores a configuration for a `DocumentTemplate`

Parameters

- **name** (*str*) – a label for this template configuration
- **base** (*TemplateConfiguration*) – the template configuration to extend
- **template** (*DocumentTemplateMeta* or *str*) – the document template to configure
- **description** (*str*) – a short string describing this style sheet
- ****options** – configuration values for the configuration attributes defined by the document `template`

template = None

The `DocumentTemplate` subclass to configure

document (*document_tree*, *backend=None*)

Create a `DocumentTemplate` object based on the given document tree and this template configuration

Parameters

- **document_tree** (*DocumentTree*) – tree of the document's contents
- **backend** – the backend to use when rendering the document

class `rinoh.template.PartsList` (**parts*)

Stores the names of the document part templates making up a document

Parameters

***parts** (*list[str]*) – the names of the document parts

5.19.2 Document Parts

class `rinoh.template.DocumentPart` (*template*, *document*, *flowables*, *last_number_format*)

Part of a document.

Parameters

- **template** (*DocumentPartTemplate*) – the template that determines

- the contents and style of this document part
- **document** (*Document*) – the document this part belongs to
- **flowables** (*list[Flowable]*) – the flowables to render in this document part

configuration_class

alias of `rinoh.template.DocumentPartTemplate`

add_page (*page*)

Append *page* (*Page*) to this *DocumentPart*.

new_page (*page_number*, *new_chapter*, ***kwargs*)

Called by `render()` with the *Chain*'s that need more
:class:`Container`'s. This method should create a new
:class:`Page` which contains a container associated with *chain*.

The document part templates which are listed by name in `DocumentTemplate.parts` are looked up as attributes of the `DocumentTemplate` subclass. They are instances of `DocumentPartTemplate` subclasses:

class `rinoh.template.DocumentPartTemplate` (*base=None*, ***attributes*)

A template that produces a document part

The document part is created given a set of flowables, and page templates. The latter are looked up in the `TemplateConfiguration` where this part template was.

page_number_prefix

Text to place in front of the page number.

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

page_number_format

The format for page numbers in this document part.

Accepts `PageNumberFormat`: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman, continue

Default: number

end_at_page

The type of page to end this document part on

Accepts `PageType`: left, right, any

Default: any

drop_if_empty

Exclude this part from the document if it is empty (no flowables)

Accepts `Bool`: true or false

Default: true

The following document part templates are used in the standard document templates:

class `rinoh.template.TitlePartTemplate` (*base=None*, ***attributes*)

The title page of a document.

drop_if_empty

Exclude this part from the document if it is empty (no flowables) (inherited from `DocumentPartTemplate`)

Accepts `Bool`: true or false

Default: false (overrides `DocumentPartTemplate` default)

page_number_prefix

Text to place in front of the page number. (inherited from `DocumentPartTemplate`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

page_number_format

The format for page numbers in this document part. (inherited from `DocumentPartTemplate`)

Accepts `PageNumberFormat`: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman, continue

Default: number

end_at_page

The type of page to end this document part on (inherited from `DocumentPartTemplate`)

Accepts `PageType`: left, right, any

Default: any

class `rinoh.template.ContentsPartTemplate` (*base=None, **attributes*)

The body of a document.

Renders all of the content present in the `DocumentTree` passed to the `DocumentTemplate`.

page_number_prefix

Text to place in front of the page number. (inherited from `DocumentPartTemplate`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

page_number_format

The format for page numbers in this document part. (inherited from `DocumentPartTemplate`)

Accepts `PageNumberFormat`: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman, continue

Default: number

end_at_page

The type of page to end this document part on (inherited from `DocumentPartTemplate`)

Accepts `PageType`: left, right, any

Default: any

drop_if_empty

Exclude this part from the document if it is empty (no flowables) (inherited from `DocumentPartTemplate`)

Accepts `Bool`: true or false

Default: true

class `rinoh.template.FixedDocumentPartTemplate` (*base=None, **attributes*)

A document part template that renders a fixed list of flowables

flowables

The list of flowables to include in this document part

Accepts `FlowablesList`: Python source code that represents a list of `Flowables`

Default: []

page_number_prefix

Text to place in front of the page number. (inherited from `DocumentPartTemplate`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

page_number_format

The format for page numbers in this document part. (inherited from `DocumentPartTemplate`)

Accepts `PageNumberFormat`: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman, continue

Default: number

end_at_page

The type of page to end this document part on (inherited from `DocumentPartTemplate`)

Accepts `PageType`: left, right, any

Default: any

drop_if_empty

Exclude this part from the document if it is empty (no flowables) (inherited from `DocumentPartTemplate`)

Accepts `Bool`: true or false

Default: true

5.19.3 Page Templates

The document templates make use of page templates:

```
class rinoh.template.PageTemplate ( base=None, **attributes )
```

header_footer_distance

Distance of the header and footer to the content area

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 14pt

columns

The number of columns for the body text

Accepts `Integer`: a natural number (positive integer)

Default: 1

column_spacing

The spacing between columns

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 1cm

header_text

The text to place in the page header

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: '{SECTION_NUMBER(1)}' ' ' '{SECTION_TITLE(1)}'

footer_text

The text to place in the page footer

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: '\t' '{PAGE_NUMBER}' '/' '{NUMBER_OF_PAGES}'

chapter_header_text

The text to place in the header on a page that starts a new chapter

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

chapter_footer_text

The text to place in the footer on a page that starts a new chapter

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

chapter_title_flowables

Generator that yields the flowables to represent the chapter title

Accepts `FlowablesList`: Python source code that represents a list of `Flowables`

Default: none

chapter_title_height

The height of the container holding the chapter title

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 150pt

page_size

The format of the pages in the document (inherited from `PageTemplateBase`)

Accepts `Paper`: the name of a Section 5.12 or <width> * <height> where width and height are `Dimensions`

Default: A4

page_orientation

The orientation of pages in the document (inherited from `PageTemplateBase`)

Accepts `PageOrientation`: portrait, landscape

Default: portrait

left_margin

The margin size on the left of the page (inherited from `PageTemplateBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

right_margin

The margin size on the right of the page (inherited from `PageTemplateBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

top_margin

The margin size at the top of the page (inherited from `PageTemplateBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

bottom_margin

The margin size at the bottom of the page (inherited from `PageTemplateBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

background

An image to place in the background of the page (inherited from `PageTemplateBase`)

Accepts `BackgroundImage`: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (`<keyword>=<value>`) that determine how the image is displayed

Default: none

after_break_background

An image to place in the background after a page break (inherited from `PageTemplateBase`)

Accepts `BackgroundImage`: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (`<keyword>=<value>`) that determine how the image is displayed

Default: none

```
class rinoh.template.TitlePageTemplate ( base=None, **attributes )
```

show_date

Show or hide the document's date

Accepts `Bool`: true or false

Default: true

show_author

Show or hide the document's author

Accepts `Bool`: true or false

Default: true

extra

Extra text to include on the title page below the title

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

page_size

The format of the pages in the document (inherited from `PageTemplateBase`)

Accepts `Paper`: the name of a Section 5.12 or `<width> * <height>` where width and height are `Dimensions`

Default: A4

page_orientation

The orientation of pages in the document (inherited from `PageTemplateBase`)

Accepts `PageOrientation`: portrait, landscape

Default: portrait

left_margin

The margin size on the left of the page (inherited from `PageTemplateBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

right_margin

The margin size on the right of the page (inherited from `PageTemplateBase`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

top_margin

The margin size at the top of the page (inherited from `PageTemplateBase`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

bottom_margin

The margin size at the bottom of the page (inherited from `PageTemplateBase`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

background

An image to place in the background of the page (inherited from `PageTemplateBase`)

Accepts BackgroundImage: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (`<keyword>=<value>`) that determine how the image is displayed

Default: none

after_break_background

An image to place in the background after a page break (inherited from `PageTemplateBase`)

Accepts BackgroundImage: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (`<keyword>=<value>`) that determine how the image is displayed

Default: none

The base class for these collects the common options:

```
class rinoh.template.PageTemplateBase ( base=None, **attributes )
```

page_size

The format of the pages in the document

Accepts Paper: the name of a Section 5.12 or `<width> * <height>` where width and height are Dimensions

Default: A4

page_orientation

The orientation of pages in the document

Accepts PageOrientation: portrait, landscape

Default: portrait

left_margin

The margin size on the left of the page

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

right_margin

The margin size on the right of the page

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

top_margin

The margin size at the top of the page

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

bottom_margin

The margin size at the bottom of the page

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

background

An image to place in the background of the page

Accepts BackgroundImage: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (<keyword>=<value>) that determine how the image is displayed

Default: none

after_break_background

An image to place in the background after a page break

Accepts BackgroundImage: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (<keyword>=<value>) that determine how the image is displayed

Default: none

Python Module Index

r

rhino

- rhino.attribute, 95
- rhino.color, 96
- rhino.dimension, 96
- rhino.document, 97
- rhino.draw, 98
- rhino.flowable, 99
- rhino.font, 101
- rhino.font.style, 103
- rhino.image, 103
- rhino.index, 105
- rhino.inline, 113
- rhino.language, 105
- rhino.number, 110
- rhino.paper, 111
- rhino.paragraph, 112
- rhino.reference, 116
- rhino.strings, 120
- rhino.structure, 117
- rhino.style, 120
- rhino.stylesheets, 11
- rhino.table, 122
- rhino.template, 123
- rhino.templates.article, 89
- rhino.templates.book, 91
- rhino.text, 112

Index

Symbols

- docs
 - rinoh command line option, 6
- format <format>
 - rinoh command line option, 5
- help
 - rinoh command line option, 5
- install-resources
 - rinoh command line option, 5
- list-fonts <filename>
 - rinoh command line option, 6
- list-formats
 - rinoh command line option, 6
- list-options <frontend>
 - rinoh command line option, 6
- list-stylesheets
 - rinoh command line option, 5
- list-templates
 - rinoh command line option, 5
- option <option=value>
 - rinoh command line option, 5
- output <filename or directory>
 - rinoh command line option, 5
- paper <paper>
 - rinoh command line option, 5
- stylesheet <name or filename>
 - rinoh command line option, 5
- template <name or filename>
 - rinoh command line option, 5
- version
 - rinoh command line option, 6
- f <format>
 - rinoh command line option, 5
- h
 - rinoh command line option, 5
- i
 - rinoh command line option, 5
- O <filename or directory>
 - rinoh command line option, 5
- o <option=value>
 - rinoh command line option, 5
- p <paper>

- rinoh command line option, 5
- s <name or filename>
 - rinoh command line option, 5
- t <name or filename>
 - rinoh command line option, 5

A

- A0 (in module rinoh.paper), 111
- A1 (in module rinoh.paper), 111
- A10 (in module rinoh.paper), 112
- A2 (in module rinoh.paper), 111
- A3 (in module rinoh.paper), 111
- A4 (in module rinoh.paper), 111
- A5 (in module rinoh.paper), 111
- A6 (in module rinoh.paper), 111
- A7 (in module rinoh.paper), 111
- A8 (in module rinoh.paper), 112
- A9 (in module rinoh.paper), 112
- abstract_location (rinoh.templates.article.Article attribute), 89
- AbstractLocation (class in rinoh.templates.article), 91
- AcceptNoneAttributeType (class in rinoh.attribute), 95
- add_page() (rinoh.template.DocumentPart method), 125
- Admonition (class in rinoh.structure), 118
- AdmonitionStyle (class in rinoh.structure), 78
- AdmonitionTitles (class in rinoh.structure), 118
- advance() (rinoh.paragraph.DefaultSpacing method), 114
- advance() (rinoh.paragraph.FixedSpacing method), 114
- advance() (rinoh.paragraph.Leading method), 115
- advance() (rinoh.paragraph.LineSpacing method), 114
- advance() (rinoh.paragraph.ProportionalSpacing method), 114
- after (rinoh.image.CaptionStyle attribute), 32
- after (rinoh.inline.InlineFlowableStyle attribute), 45
- after (rinoh.paragraph.ParagraphStyle attribute), 41
- after (rinoh.reference.NoteMarkerStyle attribute), 52
- after (rinoh.reference.ReferencingParagraphStyle attribute), 50
- after (rinoh.structure.HeadingStyle attribute), 60
- after (rinoh.structure.ListItemLabelStyle attribute), 68
- after (rinoh.structure.TableOfContentsEntryStyle attribute), 78
- after (rinoh.structure.TableOfContentsStyle attribute), 73
- after (rinoh.text.TextStyle attribute), 43
- after_break_background (rinoh.template.PageTemplate attribute), 129
- after_break_background (rinoh.template.PageTemplateBase attribute), 131
- after_break_background (rinoh.template.TitlePageTemplate attribute), 130
- align (rinoh.image.ImageArgs attribute), 104
- align_baselines (rinoh.flowable.LabeledFlowableStyle attribute), 20
- AnchorFlowable (class in rinoh.flowable), 99
- append() (rinoh.text.MixedStyledText method), 113
- arguments (rinoh.image.BackgroundImage attribute), 103
- arguments (rinoh.image.InlineImage attribute), 103
- Article (class in rinoh.templates.article), 89
- attention (rinoh.structure.AdmonitionTitles attribute), 118
- Attribute (class in rinoh.attribute), 95
- AttributesDictionary (class in rinoh.attribute), 95

B

- back_matter (rinoh.templates.book.Book attribute), 92
- back_matter_left_page (rinoh.templates.book.Book attribute), 94

back_matter_page (rinoh.templates.book.Book attribute), 94
 back_matter_right_page (rinoh.templates.book.Book attribute), 94
 background (rinoh.template.PageTemplate attribute), 129
 background (rinoh.template.PageTemplateBase attribute), 131
 background (rinoh.template.TitlePageTemplate attribute), 130
 background_color (rinoh.flowable.FloatStyle attribute), 27
 background_color (rinoh.flowable.FlowableStyle attribute), 20
 background_color (rinoh.flowable.GroupedFlowablesStyle attribute), 25
 background_color (rinoh.flowable.LabeledFlowableStyle attribute), 22
 background_color (rinoh.image.CaptionStyle attribute), 30
 background_color (rinoh.image.FigureStyle attribute), 34
 background_color (rinoh.index.IndexStyle attribute), 36
 background_color (rinoh.inline.InlineFlowableStyle attribute), 45
 background_color (rinoh.paragraph.ParagraphStyle attribute), 39
 background_color (rinoh.reference.ReferencingParagraphStyle attribute), 48
 background_color (rinoh.structure.AdmonitionStyle attribute), 80
 background_color (rinoh.structure.HeadingStyle attribute), 58
 background_color (rinoh.structure.HorizontalRuleStyle attribute), 82
 background_color (rinoh.structure.ListItemLabelStyle attribute), 66
 background_color (rinoh.structure.ListStyle attribute), 62
 background_color (rinoh.structure.SectionStyle attribute), 55
 background_color (rinoh.structure.TableOfContentsEntryStyle attribute), 76
 background_color (rinoh.structure.TableOfContentsStyle attribute), 70
 background_color (rinoh.table.TableCellStyle attribute), 87
 background_color (rinoh.table.TableStyle attribute), 85
 BackgroundImage (class in rinoh.image), 103
 baseline (rinoh.inline.InlineFlowableStyle attribute), 43
 before (rinoh.image.CaptionStyle attribute), 32
 before (rinoh.inline.InlineFlowableStyle attribute), 45
 before (rinoh.paragraph.ParagraphStyle attribute), 41
 before (rinoh.reference.NoteMarkerStyle attribute), 52
 before (rinoh.reference.ReferencingParagraphStyle attribute), 50
 before (rinoh.structure.HeadingStyle attribute), 60
 before (rinoh.structure.ListItemLabelStyle attribute), 68
 before (rinoh.structure.TableOfContentsEntryStyle attribute), 78
 before (rinoh.structure.TableOfContentsStyle attribute), 73
 before (rinoh.text.TextStyle attribute), 43
 Book (class in rinoh.templates.book), 91
 Bool (class in rinoh.attribute), 95
 border (rinoh.flowable.FloatStyle attribute), 26
 border (rinoh.flowable.FlowableStyle attribute), 19
 border (rinoh.flowable.GroupedFlowablesStyle attribute), 24
 border (rinoh.flowable.LabeledFlowableStyle attribute), 22
 border (rinoh.image.CaptionStyle attribute), 29
 border (rinoh.image.FigureStyle attribute), 33
 border (rinoh.index.IndexStyle attribute), 36
 border (rinoh.inline.InlineFlowableStyle attribute), 44
 border (rinoh.paragraph.ParagraphStyle attribute), 39
 border (rinoh.reference.ReferencingParagraphStyle attribute), 48
 border (rinoh.structure.AdmonitionStyle attribute), 80
 border (rinoh.structure.HeadingStyle attribute), 57
 border (rinoh.structure.HorizontalRuleStyle attribute), 82
 border (rinoh.structure.ListItemLabelStyle attribute), 65
 border (rinoh.structure.ListStyle attribute), 62
 border (rinoh.structure.SectionStyle attribute), 55
 border (rinoh.structure.TableOfContentsEntryStyle attribute), 75
 border (rinoh.structure.TableOfContentsStyle attribute), 70
 border (rinoh.table.TableCellStyle attribute), 87

border (rinoh.table.TableStyle attribute), 84
border_bottom (rinoh.flowable.FloatStyle attribute), 27
border_bottom (rinoh.flowable.FlowableStyle attribute), 20
border_bottom (rinoh.flowable.GroupedFlowablesStyle attribute), 24
border_bottom (rinoh.flowable.LabeledFlowableStyle attribute), 22
border_bottom (rinoh.image.CaptionStyle attribute), 29
border_bottom (rinoh.image.FigureStyle attribute), 34
border_bottom (rinoh.index.IndexStyle attribute), 36
border_bottom (rinoh.inline.InlineFlowableStyle attribute), 45
border_bottom (rinoh.paragraph.ParagraphStyle attribute), 39
border_bottom (rinoh.reference.ReferencingParagraphStyle attribute), 48
border_bottom (rinoh.structure.AdmonitionStyle attribute), 80
border_bottom (rinoh.structure.HeadingStyle attribute), 58
border_bottom (rinoh.structure.HorizontalRuleStyle attribute), 82
border_bottom (rinoh.structure.ListItemLabelStyle attribute), 66
border_bottom (rinoh.structure.ListStyle attribute), 62
border_bottom (rinoh.structure.SectionStyle attribute), 55
border_bottom (rinoh.structure.TableOfContentsEntryStyle attribute), 76
border_bottom (rinoh.structure.TableOfContentsStyle attribute), 70
border_bottom (rinoh.table.TableCellStyle attribute), 87
border_bottom (rinoh.table.TableStyle attribute), 85
border_left (rinoh.flowable.FloatStyle attribute), 26
border_left (rinoh.flowable.FlowableStyle attribute), 19
border_left (rinoh.flowable.GroupedFlowablesStyle attribute), 24
border_left (rinoh.flowable.LabeledFlowableStyle attribute), 22
border_left (rinoh.image.CaptionStyle attribute), 29
border_left (rinoh.image.FigureStyle attribute), 33
border_left (rinoh.index.IndexStyle attribute), 36
border_left (rinoh.inline.InlineFlowableStyle attribute), 45
border_left (rinoh.paragraph.ParagraphStyle attribute), 39
border_left (rinoh.reference.ReferencingParagraphStyle attribute), 48
border_left (rinoh.structure.AdmonitionStyle attribute), 80
border_left (rinoh.structure.HeadingStyle attribute), 58
border_left (rinoh.structure.HorizontalRuleStyle attribute), 82
border_left (rinoh.structure.ListItemLabelStyle attribute), 65
border_left (rinoh.structure.ListStyle attribute), 62
border_left (rinoh.structure.SectionStyle attribute), 55
border_left (rinoh.structure.TableOfContentsEntryStyle attribute), 75
border_left (rinoh.structure.TableOfContentsStyle attribute), 70
border_left (rinoh.table.TableCellStyle attribute), 87
border_left (rinoh.table.TableStyle attribute), 84
border_right (rinoh.flowable.FloatStyle attribute), 26
border_right (rinoh.flowable.FlowableStyle attribute), 19
border_right (rinoh.flowable.GroupedFlowablesStyle attribute), 24
border_right (rinoh.flowable.LabeledFlowableStyle attribute), 22
border_right (rinoh.image.CaptionStyle attribute), 29
border_right (rinoh.image.FigureStyle attribute), 33
border_right (rinoh.index.IndexStyle attribute), 36
border_right (rinoh.inline.InlineFlowableStyle attribute), 45
border_right (rinoh.paragraph.ParagraphStyle attribute), 39
border_right (rinoh.reference.ReferencingParagraphStyle attribute), 48
border_right (rinoh.structure.AdmonitionStyle attribute), 80
border_right (rinoh.structure.HeadingStyle attribute), 58
border_right (rinoh.structure.HorizontalRuleStyle attribute), 82
border_right (rinoh.structure.ListItemLabelStyle attribute), 65
border_right (rinoh.structure.ListStyle attribute), 62
border_right (rinoh.structure.SectionStyle attribute), 55
border_right (rinoh.structure.TableOfContentsEntryStyle attribute), 76

- border_right (rinoh.structure.TableOfContentsStyle attribute), 70
- border_right (rinoh.table.TableCellStyle attribute), 87
- border_right (rinoh.table.TableStyle attribute), 84
- border_top (rinoh.flowable.FloatStyle attribute), 26
- border_top (rinoh.flowable.FlowableStyle attribute), 20
- border_top (rinoh.flowable.GroupedFlowablesStyle attribute), 24
- border_top (rinoh.flowable.LabeledFlowableStyle attribute), 22
- border_top (rinoh.image.CaptionStyle attribute), 29
- border_top (rinoh.image.FigureStyle attribute), 33
- border_top (rinoh.index.IndexStyle attribute), 36
- border_top (rinoh.inline.InlineFlowableStyle attribute), 45
- border_top (rinoh.paragraph.ParagraphStyle attribute), 39
- border_top (rinoh.reference.ReferencingParagraphStyle attribute), 48
- border_top (rinoh.structure.AdmonitionStyle attribute), 80
- border_top (rinoh.structure.HeadingStyle attribute), 58
- border_top (rinoh.structure.HorizontalRuleStyle attribute), 82
- border_top (rinoh.structure.ListItemLabelStyle attribute), 66
- border_top (rinoh.structure.ListStyle attribute), 62
- border_top (rinoh.structure.SectionStyle attribute), 55
- border_top (rinoh.structure.TableOfContentsEntryStyle attribute), 76
- border_top (rinoh.structure.TableOfContentsStyle attribute), 70
- border_top (rinoh.table.TableCellStyle attribute), 87
- border_top (rinoh.table.TableStyle attribute), 84
- bottom_margin (rinoh.template.PageTemplate attribute), 129
- bottom_margin (rinoh.template.PageTemplateBase attribute), 131
- bottom_margin (rinoh.template.TitlePageTemplate attribute), 130
- build_document() (rinoh.flowable.StaticGroupedFlowables method), 101
- bullet (rinoh.structure.ListStyle attribute), 60

C

- Caption (class in rinoh.image), 104
- CaptionStyle (class in rinoh.image), 27
- caution (rinoh.structure.AdmonitionTitles attribute), 119
- chapter (rinoh.structure.SectionTitles attribute), 117
- chapter_footer_text (rinoh.template.PageTemplate attribute), 128
- chapter_header_text (rinoh.template.PageTemplate attribute), 128
- chapter_title_flowables (rinoh.template.PageTemplate attribute), 128
- chapter_title_height (rinoh.template.PageTemplate attribute), 128
- CM (in module rinoh.dimension), 97
- Color (class in rinoh.color), 96
- column_spacing (rinoh.template.PageTemplate attribute), 127
- column_widths (rinoh.table.TableStyle attribute), 83
- columns (rinoh.template.PageTemplate attribute), 127
- Configuration (rinoh.template.DocumentTemplate attribute), 124
- Configuration (rinoh.templates.article.Article attribute), 90
- Configuration (rinoh.templates.book.Book attribute), 94
- configuration_class (rinoh.style.Styled attribute), 121
- configuration_class (rinoh.template.DocumentPart attribute), 125
- ConfigurationFile (rinoh.template.DocumentTemplate attribute), 124
- ConfigurationFile (rinoh.templates.article.Article attribute), 91
- ConfigurationFile (rinoh.templates.book.Book attribute), 94
- contents (rinoh.structure.SectionTitles attribute), 117
- contents (rinoh.templates.article.Article attribute), 90
- contents (rinoh.templates.book.Book attribute), 92
- contents_left_page (rinoh.templates.book.Book attribute), 94
- contents_page (rinoh.templates.article.Article attribute), 90
- contents_page (rinoh.templates.book.Book attribute), 93

- contents_right_page (rinoh.templates.book.Book attribute), 93
- ContentsPartTemplate (class in rinoh.template), 126
- copy() (rinoh.text.MixedStyledText method), 113
- cover (rinoh.templates.book.Book attribute), 91
- cover_page (rinoh.templates.book.Book attribute), 92
- custom_label (rinoh.image.CaptionStyle attribute), 30
- custom_label (rinoh.number.LabelStyle attribute), 110
- custom_label (rinoh.number.NumberStyle attribute), 111
- custom_label (rinoh.paragraph.ParagraphStyle attribute), 40
- custom_label (rinoh.reference.NoteMarkerStyle attribute), 53
- custom_label (rinoh.reference.ReferencingParagraphStyle attribute), 49
- custom_label (rinoh.structure.HeadingStyle attribute), 58
- custom_label (rinoh.structure.ListItemLabelStyle attribute), 66
- custom_label (rinoh.structure.ListStyle attribute), 63
- custom_label (rinoh.structure.TableOfContentsEntryStyle attribute), 76
- custom_label (rinoh.structure.TableOfContentsStyle attribute), 71

D

- danger (rinoh.structure.AdmonitionTitles attribute), 119
- DEFAULT (in module rinoh.paragraph), 115
- DefaultSpacing (class in rinoh.paragraph), 114
- DefinitionList (class in rinoh.structure), 118
- depth (rinoh.structure.TableOfContentsStyle attribute), 68
- Dimension (class in rinoh.dimension), 96
- doc_format() (rinoh.color.Color class method), 96
- Document (class in rinoh.document), 97
- document() (rinoh.template.TemplateConfiguration method), 124
- DocumentPart (class in rinoh.template), 124
- DocumentPartTemplate (class in rinoh.template), 125
- DocumentTemplate (class in rinoh.template), 123
- DocumentTree (class in rinoh.document), 97
- DOUBLE (in module rinoh.paragraph), 115
- dpi (rinoh.image.ImageArgs attribute), 104
- drop_if_empty (rinoh.template.ContentsPartTemplate attribute), 126
- drop_if_empty (rinoh.template.DocumentPartTemplate attribute), 125
- drop_if_empty (rinoh.template.FixedDocumentPartTemplate attribute), 127
- drop_if_empty (rinoh.template.TitlePartTemplate attribute), 125
- DummyFlowable (class in rinoh.flowable), 99

E

- EN (in module rinoh.language), 106
- encoding (rinoh.font.Font attribute), 102
- end_at_page (rinoh.template.ContentsPartTemplate attribute), 126
- end_at_page (rinoh.template.DocumentPartTemplate attribute), 125
- end_at_page (rinoh.template.FixedDocumentPartTemplate attribute), 127
- end_at_page (rinoh.template.TitlePartTemplate attribute), 126
- error (rinoh.structure.AdmonitionTitles attribute), 119
- extra (rinoh.template.TitlePageTemplate attribute), 129

F

- Field (class in rinoh.reference), 116
- Figure (class in rinoh.image), 105
- FigureStyle (class in rinoh.image), 32
- file_or_filename (rinoh.image.ImageArgs attribute), 104
- fill_color (rinoh.draw.ShapeStyle attribute), 18
- fill_color (rinoh.table.TableCellBackgroundStyle attribute), 88
- find_source() (rinoh.attribute.RuleSet method), 95

FixedDocumentPartTemplate (class in rinoh.template), 126
 FixedSpacing (class in rinoh.paragraph), 114
 Float (class in rinoh.flowable), 101
 float (rinoh.flowable.FloatStyle attribute), 25
 float (rinoh.image.FigureStyle attribute), 32
 FloatStyle (class in rinoh.flowable), 25
 flow() (rinoh.flowable.Float method), 101
 flow() (rinoh.index.IndexTarget method), 105
 flow() (rinoh.reference.Note method), 116
 flow() (rinoh.structure.Heading method), 117
 Flowable (class in rinoh.flowable), 99
 flowable_spacing (rinoh.flowable.GroupedFlowablesStyle attribute), 23
 flowable_spacing (rinoh.image.FigureStyle attribute), 34
 flowable_spacing (rinoh.index.IndexStyle attribute), 35
 flowable_spacing (rinoh.structure.AdmonitionStyle attribute), 79
 flowable_spacing (rinoh.structure.ListStyle attribute), 61
 flowable_spacing (rinoh.structure.SectionStyle attribute), 53
 flowable_spacing (rinoh.structure.TableOfContentsStyle attribute), 68
 flowable_spacing (rinoh.table.TableCellStyle attribute), 85
 flowables (rinoh.template.FixedDocumentPartTemplate attribute), 126
 flowables() (rinoh.flowable.GroupedFlowables method), 100
 flowables() (rinoh.flowable.StaticGroupedFlowables method), 101
 flowables() (rinoh.index.Index method), 105
 flowables() (rinoh.structure.Admonition method), 118
 flowables() (rinoh.structure.TableOfContents method), 118
 FlowableState (class in rinoh.flowable), 99
 FlowableStyle (class in rinoh.flowable), 18
 FlowableWidth (class in rinoh.flowable), 101
 Font (class in rinoh.font), 101
 font_color (rinoh.image.CaptionStyle attribute), 31
 font_color (rinoh.paragraph.ParagraphStyle attribute), 40
 font_color (rinoh.reference.NoteMarkerStyle attribute), 51
 font_color (rinoh.reference.ReferencingParagraphStyle attribute), 49
 font_color (rinoh.structure.HeadingStyle attribute), 59
 font_color (rinoh.structure.ListItemLabelStyle attribute), 67
 font_color (rinoh.structure.TableOfContentsEntryStyle attribute), 77
 font_color (rinoh.structure.TableOfContentsStyle attribute), 72
 font_color (rinoh.text.TextStyle attribute), 42
 font_size (rinoh.image.CaptionStyle attribute), 31
 font_size (rinoh.paragraph.ParagraphStyle attribute), 40
 font_size (rinoh.reference.NoteMarkerStyle attribute), 51
 font_size (rinoh.reference.ReferencingParagraphStyle attribute), 49
 font_size (rinoh.structure.HeadingStyle attribute), 59
 font_size (rinoh.structure.ListItemLabelStyle attribute), 67
 font_size (rinoh.structure.TableOfContentsEntryStyle attribute), 77
 font_size (rinoh.structure.TableOfContentsStyle attribute), 72
 font_size (rinoh.text.TextStyle attribute), 42
 font_slant (rinoh.image.CaptionStyle attribute), 30
 font_slant (rinoh.paragraph.ParagraphStyle attribute), 40
 font_slant (rinoh.reference.NoteMarkerStyle attribute), 51
 font_slant (rinoh.reference.ReferencingParagraphStyle attribute), 49
 font_slant (rinoh.structure.HeadingStyle attribute), 59
 font_slant (rinoh.structure.ListItemLabelStyle attribute), 67
 font_slant (rinoh.structure.TableOfContentsEntryStyle attribute), 77
 font_slant (rinoh.structure.TableOfContentsStyle attribute), 72
 font_slant (rinoh.text.TextStyle attribute), 42
 font_variant (rinoh.image.CaptionStyle attribute), 31
 font_variant (rinoh.paragraph.ParagraphStyle attribute), 40

font_variant (rinoh.reference.NoteMarkerStyle attribute), 52
 font_variant (rinoh.reference.ReferencingParagraphStyle attribute), 49
 font_variant (rinoh.structure.HeadingStyle attribute), 59
 font_variant (rinoh.structure.ListItemLabelStyle attribute), 67
 font_variant (rinoh.structure.TableOfContentsEntryStyle attribute), 77
 font_variant (rinoh.structure.TableOfContentsStyle attribute), 72
 font_variant (rinoh.text.TextStyle attribute), 42
 font_weight (rinoh.image.CaptionStyle attribute), 30
 font_weight (rinoh.paragraph.ParagraphStyle attribute), 40
 font_weight (rinoh.reference.NoteMarkerStyle attribute), 51
 font_weight (rinoh.reference.ReferencingParagraphStyle attribute), 49
 font_weight (rinoh.structure.HeadingStyle attribute), 59
 font_weight (rinoh.structure.ListItemLabelStyle attribute), 66
 font_weight (rinoh.structure.TableOfContentsEntryStyle attribute), 77
 font_weight (rinoh.structure.TableOfContentsStyle attribute), 72
 font_weight (rinoh.text.TextStyle attribute), 42
 font_width (rinoh.image.CaptionStyle attribute), 30
 font_width (rinoh.paragraph.ParagraphStyle attribute), 40
 font_width (rinoh.reference.NoteMarkerStyle attribute), 51
 font_width (rinoh.reference.ReferencingParagraphStyle attribute), 49
 font_width (rinoh.structure.HeadingStyle attribute), 59
 font_width (rinoh.structure.ListItemLabelStyle attribute), 67
 font_width (rinoh.structure.TableOfContentsEntryStyle attribute), 77
 font_width (rinoh.structure.TableOfContentsStyle attribute), 72
 font_width (rinoh.text.TextStyle attribute), 42
 fonts() (rinoh.font.Typeface method), 102
 FontSlant (class in rinoh.font.style), 103
 FontVariant (class in rinoh.font.style), 103
 FontWeight (class in rinoh.font.style), 103
 FontWidth (class in rinoh.font.style), 103
 footer_text (rinoh.template.PageTemplate attribute), 128
 format_number() (in module rinoh.number), 111
 FR (in module rinoh.language), 106
 front_matter (rinoh.templates.article.Article attribute), 90
 front_matter (rinoh.templates.book.Book attribute), 92
 front_matter_left_page (rinoh.templates.book.Book attribute), 93
 front_matter_page (rinoh.templates.article.Article attribute), 90
 front_matter_page (rinoh.templates.book.Book attribute), 93
 front_matter_right_page (rinoh.templates.book.Book attribute), 93

G

get_font() (rinoh.font.Typeface method), 103
 get_glyph_metrics() (rinoh.font.Font method), 102
 get_kerning() (rinoh.font.Font method), 102
 get_ligature() (rinoh.font.Font method), 102
 get_position() (rinoh.paragraph.TabStop method), 115
 get_rowspanned_columns() (rinoh.table.TableRow method), 122
 get_selector() (rinoh.style.StyleSheet method), 121
 Glyph (class in rinoh.paragraph), 115
 GlyphsSpan (class in rinoh.paragraph), 115
 Gray (class in rinoh.color), 96
 GroupedFlowables (class in rinoh.flowable), 100
 GroupedFlowablesState (class in rinoh.flowable), 100
 GroupedFlowablesStyle (class in rinoh.flowable), 23
 GroupedLabeledFlowables (class in rinoh.flowable), 101
 grow() (rinoh.dimension.Dimension method), 96

H

has_class (rinoh.style.Styled property), 121
has_classes (rinoh.style.Styled property), 121
has_id (rinoh.style.Styled property), 121
header_footer_distance (rinoh.template.PageTemplate attribute), 127
header_text (rinoh.template.PageTemplate attribute), 127
Heading (class in rinoh.structure), 117
HeadingStyle (class in rinoh.structure), 55
height (rinoh.image.ImageArgs attribute), 104
height() (rinoh.text.StyledText method), 113
HexColor (class in rinoh.color), 96
hide (rinoh.draw.LineStyle attribute), 18
hide (rinoh.draw.ShapeStyle attribute), 18
hide (rinoh.flowable.FloatStyle attribute), 27
hide (rinoh.flowable.FlowableStyle attribute), 20
hide (rinoh.flowable.GroupedFlowablesStyle attribute), 25
hide (rinoh.flowable.LabeledFlowableStyle attribute), 22
hide (rinoh.image.CaptionStyle attribute), 32
hide (rinoh.image.FigureStyle attribute), 34
hide (rinoh.index.IndexStyle attribute), 36
hide (rinoh.inline.InlineFlowableStyle attribute), 45
hide (rinoh.number.LabelStyle attribute), 110
hide (rinoh.number.NumberStyle attribute), 111
hide (rinoh.paragraph.ParagraphStyle attribute), 39
hide (rinoh.reference.NoteMarkerStyle attribute), 53
hide (rinoh.reference.ReferencingParagraphStyle attribute), 50
hide (rinoh.structure.AdmonitionStyle attribute), 80
hide (rinoh.structure.HeadingStyle attribute), 60
hide (rinoh.structure.HorizontalRuleStyle attribute), 82
hide (rinoh.structure.ListItemLabelStyle attribute), 68
hide (rinoh.structure.ListStyle attribute), 63
hide (rinoh.structure.SectionStyle attribute), 55
hide (rinoh.structure.TableOfContentsEntryStyle attribute), 78
hide (rinoh.structure.TableOfContentsStyle attribute), 70
hide (rinoh.style.Style attribute), 121
hide (rinoh.table.TableCellBackgroundStyle attribute), 88
hide (rinoh.table.TableCellBorderStyle attribute), 88
hide (rinoh.table.TableCellStyle attribute), 87
hide (rinoh.table.TableStyle attribute), 85
hide (rinoh.text.TextStyle attribute), 43
hint (rinoh.structure.AdmonitionTitles attribute), 119
horizontal_align (rinoh.flowable.FloatStyle attribute), 25
horizontal_align (rinoh.flowable.FlowableStyle attribute), 18
horizontal_align (rinoh.flowable.GroupedFlowablesStyle attribute), 23
horizontal_align (rinoh.flowable.LabeledFlowableStyle attribute), 21
horizontal_align (rinoh.image.CaptionStyle attribute), 28
horizontal_align (rinoh.image.FigureStyle attribute), 32
horizontal_align (rinoh.index.IndexStyle attribute), 35
horizontal_align (rinoh.inline.InlineFlowableStyle attribute), 43
horizontal_align (rinoh.paragraph.ParagraphStyle attribute), 38
horizontal_align (rinoh.reference.ReferencingParagraphStyle attribute), 47
horizontal_align (rinoh.structure.AdmonitionStyle attribute), 79
horizontal_align (rinoh.structure.HeadingStyle attribute), 57
horizontal_align (rinoh.structure.HorizontalRuleStyle attribute), 81
horizontal_align (rinoh.structure.ListItemLabelStyle attribute), 64
horizontal_align (rinoh.structure.ListStyle attribute), 61
horizontal_align (rinoh.structure.SectionStyle attribute), 54

horizontal_align (rinoh.structure.TableOfContentsEntryStyle attribute), 74
 horizontal_align (rinoh.structure.TableOfContentsStyle attribute), 69
 horizontal_align (rinoh.table.TableCellStyle attribute), 86
 horizontal_align (rinoh.table.TableStyle attribute), 83
 HorizontalAlignment (class in rinoh.flowable), 101
 HorizontalRule (class in rinoh.structure), 120
 HorizontalRuleStyle (class in rinoh.structure), 81
 hyphen_chars (rinoh.image.CaptionStyle attribute), 31
 hyphen_chars (rinoh.paragraph.ParagraphStyle attribute), 41
 hyphen_chars (rinoh.reference.NoteMarkerStyle attribute), 52
 hyphen_chars (rinoh.reference.ReferencingParagraphStyle attribute), 50
 hyphen_chars (rinoh.structure.HeadingStyle attribute), 60
 hyphen_chars (rinoh.structure.ListItemLabelStyle attribute), 67
 hyphen_chars (rinoh.structure.TableOfContentsEntryStyle attribute), 78
 hyphen_chars (rinoh.structure.TableOfContentsStyle attribute), 73
 hyphen_chars (rinoh.text.TextStyle attribute), 43
 hyphen_lang (rinoh.image.CaptionStyle attribute), 31
 hyphen_lang (rinoh.paragraph.ParagraphStyle attribute), 41
 hyphen_lang (rinoh.reference.NoteMarkerStyle attribute), 52
 hyphen_lang (rinoh.reference.ReferencingParagraphStyle attribute), 50
 hyphen_lang (rinoh.structure.HeadingStyle attribute), 60
 hyphen_lang (rinoh.structure.ListItemLabelStyle attribute), 67
 hyphen_lang (rinoh.structure.TableOfContentsEntryStyle attribute), 78
 hyphen_lang (rinoh.structure.TableOfContentsStyle attribute), 73
 hyphen_lang (rinoh.text.TextStyle attribute), 43
 hyphenate (rinoh.image.CaptionStyle attribute), 31
 hyphenate (rinoh.paragraph.ParagraphStyle attribute), 41
 hyphenate (rinoh.reference.NoteMarkerStyle attribute), 52
 hyphenate (rinoh.reference.ReferencingParagraphStyle attribute), 50
 hyphenate (rinoh.structure.HeadingStyle attribute), 60
 hyphenate (rinoh.structure.ListItemLabelStyle attribute), 67
 hyphenate (rinoh.structure.TableOfContentsEntryStyle attribute), 77
 hyphenate (rinoh.structure.TableOfContentsStyle attribute), 73
 hyphenate (rinoh.text.TextStyle attribute), 42
 HyphenatorStore (class in rinoh.paragraph), 115

I

Image (class in rinoh.image), 103
 ImageArgs (class in rinoh.image), 104
 important (rinoh.structure.AdmonitionTitles attribute), 119
 INCH (in module rinoh.dimension), 97
 indent_first (rinoh.image.CaptionStyle attribute), 27
 indent_first (rinoh.paragraph.ParagraphStyle attribute), 37
 indent_first (rinoh.reference.ReferencingParagraphStyle attribute), 46
 indent_first (rinoh.structure.HeadingStyle attribute), 56
 indent_first (rinoh.structure.ListItemLabelStyle attribute), 63
 indent_first (rinoh.structure.TableOfContentsEntryStyle attribute), 74
 indent_first (rinoh.structure.TableOfContentsStyle attribute), 70
 Index (class in rinoh.index), 105
 index (rinoh.structure.SectionTitles attribute), 118
 IndexLabel (class in rinoh.index), 105
 IndexSection (class in rinoh.index), 105
 IndexStyle (class in rinoh.index), 34
 IndexTarget (class in rinoh.index), 105
 IndexTerm (class in rinoh.index), 105
 initials (rinoh.index.IndexStyle attribute), 34
 inline_title (rinoh.structure.AdmonitionStyle attribute), 78

InlineFlowable (class in rinoh.inline), 114
InlineFlowableStyle (class in rinoh.inline), 43
InlineImage (class in rinoh.image), 103
InlineIndexTarget (class in rinoh.index), 105
input
 rinoh command line option, 5
Integer (class in rinoh.attribute), 95
is_script() (rinoh.text.StyledText method), 113
IT (in module rinoh.language), 107
items (rinoh.text.MixedStyledText property), 113
items (rinoh.text.StyledText property), 113

J

JUNIOR_LEGAL (in module rinoh.paper), 112

K

keep_with_next (rinoh.flowable.FloatStyle attribute), 26
keep_with_next (rinoh.flowable.FlowableStyle attribute), 19
keep_with_next (rinoh.flowable.GroupedFlowablesStyle attribute), 24
keep_with_next (rinoh.flowable.LabeledFlowableStyle attribute), 22
keep_with_next (rinoh.image.CaptionStyle attribute), 29
keep_with_next (rinoh.image.FigureStyle attribute), 33
keep_with_next (rinoh.index.IndexStyle attribute), 36
keep_with_next (rinoh.inline.InlineFlowableStyle attribute), 44
keep_with_next (rinoh.paragraph.ParagraphStyle attribute), 38
keep_with_next (rinoh.reference.ReferencingParagraphStyle attribute), 48
keep_with_next (rinoh.structure.AdmonitionStyle attribute), 80
keep_with_next (rinoh.structure.HeadingStyle attribute), 56
keep_with_next (rinoh.structure.HorizontalRuleStyle attribute), 82
keep_with_next (rinoh.structure.ListItemLabelStyle attribute), 65
keep_with_next (rinoh.structure.ListStyle attribute), 62
keep_with_next (rinoh.structure.SectionStyle attribute), 54
keep_with_next (rinoh.structure.TableOfContentsEntryStyle attribute), 75
keep_with_next (rinoh.structure.TableOfContentsStyle attribute), 69
keep_with_next (rinoh.table.TableCellStyle attribute), 86
keep_with_next (rinoh.table.TableStyle attribute), 84
kerning (rinoh.image.CaptionStyle attribute), 31
kerning (rinoh.paragraph.ParagraphStyle attribute), 41
kerning (rinoh.reference.NoteMarkerStyle attribute), 52
kerning (rinoh.reference.ReferencingParagraphStyle attribute), 50
kerning (rinoh.structure.HeadingStyle attribute), 59
kerning (rinoh.structure.ListItemLabelStyle attribute), 67
kerning (rinoh.structure.TableOfContentsEntryStyle attribute), 77
kerning (rinoh.structure.TableOfContentsStyle attribute), 72
kerning (rinoh.text.TextStyle attribute), 42

L

Label (class in rinoh.number), 110
label_max_width (rinoh.flowable.LabeledFlowableStyle attribute), 20
label_min_width (rinoh.flowable.LabeledFlowableStyle attribute), 20
label_prefix (rinoh.image.CaptionStyle attribute), 30
label_prefix (rinoh.number.LabelStyle attribute), 110
label_prefix (rinoh.number.NumberStyle attribute), 111
label_prefix (rinoh.paragraph.ParagraphStyle attribute), 39
label_prefix (rinoh.reference.NoteMarkerStyle attribute), 53
label_prefix (rinoh.reference.ReferencingParagraphStyle attribute), 48
label_prefix (rinoh.structure.HeadingStyle attribute), 58

label_prefix (rinoh.structure.ListItemLabelStyle attribute), 66
 label_prefix (rinoh.structure.ListStyle attribute), 63
 label_prefix (rinoh.structure.TableOfContentsEntryStyle attribute), 76
 label_prefix (rinoh.structure.TableOfContentsStyle attribute), 71
 label_spacing (rinoh.flowable.LabeledFlowableStyle attribute), 20
 label_suffix (rinoh.image.CaptionStyle attribute), 30
 label_suffix (rinoh.number.LabelStyle attribute), 110
 label_suffix (rinoh.number.NumberStyle attribute), 111
 label_suffix (rinoh.paragraph.ParagraphStyle attribute), 40
 label_suffix (rinoh.reference.NoteMarkerStyle attribute), 53
 label_suffix (rinoh.reference.ReferencingParagraphStyle attribute), 49
 label_suffix (rinoh.structure.HeadingStyle attribute), 58
 label_suffix (rinoh.structure.ListItemLabelStyle attribute), 66
 label_suffix (rinoh.structure.ListStyle attribute), 63
 label_suffix (rinoh.structure.TableOfContentsEntryStyle attribute), 76
 label_suffix (rinoh.structure.TableOfContentsStyle attribute), 71
 LabeledFlowable (class in rinoh.flowable), 100
 LabeledFlowableState (class in rinoh.flowable), 100
 LabeledFlowableStyle (class in rinoh.flowable), 20
 LabelStyle (class in rinoh.number), 110
 Language (class in rinoh.language), 105
 language (rinoh.template.DocumentTemplate attribute), 123
 language (rinoh.templates.article.Article attribute), 89
 language (rinoh.templates.book.Book attribute), 91
 languages (rinoh.language.Language attribute), 105
 Leading (class in rinoh.paragraph), 115
 LEDGER (in module rinoh.paper), 112
 left_margin (rinoh.template.PageTemplate attribute), 128
 left_margin (rinoh.template.PageTemplateBase attribute), 130
 left_margin (rinoh.template.TitlePageTemplate attribute), 129
 LEGAL (in module rinoh.paper), 112
 LETTER (in module rinoh.paper), 112
 ligatures (rinoh.image.CaptionStyle attribute), 31
 ligatures (rinoh.paragraph.ParagraphStyle attribute), 41
 ligatures (rinoh.reference.NoteMarkerStyle attribute), 52
 ligatures (rinoh.reference.ReferencingParagraphStyle attribute), 50
 ligatures (rinoh.structure.HeadingStyle attribute), 59
 ligatures (rinoh.structure.ListItemLabelStyle attribute), 67
 ligatures (rinoh.structure.TableOfContentsEntryStyle attribute), 77
 ligatures (rinoh.structure.TableOfContentsStyle attribute), 72
 ligatures (rinoh.text.TextStyle attribute), 42
 limit_width (rinoh.image.ImageArgs attribute), 104
 Line (class in rinoh.draw), 98
 line_spacing (rinoh.image.CaptionStyle attribute), 28
 line_spacing (rinoh.paragraph.ParagraphStyle attribute), 37
 line_spacing (rinoh.reference.ReferencingParagraphStyle attribute), 46
 line_spacing (rinoh.structure.HeadingStyle attribute), 56
 line_spacing (rinoh.structure.ListItemLabelStyle attribute), 63
 line_spacing (rinoh.structure.TableOfContentsEntryStyle attribute), 74
 line_spacing (rinoh.structure.TableOfContentsStyle attribute), 70
 LineSpacing (class in rinoh.paragraph), 114
 LineStyle (class in rinoh.draw), 17
 link (rinoh.reference.NoteMarkerStyle attribute), 51
 List (class in rinoh.structure), 118
 list_class (rinoh.image.ListOfFiguresSection attribute), 105
 list_class (rinoh.table.ListOfTablesSection attribute), 123
 list_of_figures (rinoh.structure.SectionTitles attribute), 117
 list_of_tables (rinoh.structure.SectionTitles attribute), 117

ListItemLabelStyle (class in rinoh.structure), 63
ListOfFigures (class in rinoh.image), 105
ListOfFiguresSection (class in rinoh.image), 105
ListOfTables (class in rinoh.table), 123
ListOfTablesSection (class in rinoh.table), 123
ListStyle (class in rinoh.structure), 60
Locale (class in rinoh.text), 113
location (rinoh.attribute.RuleSetFile property), 95

M

margin_left (rinoh.flowable.FloatStyle attribute), 25
margin_left (rinoh.flowable.FlowableStyle attribute), 19
margin_left (rinoh.flowable.GroupedFlowablesStyle attribute), 23
margin_left (rinoh.flowable.LabeledFlowableStyle attribute), 21
margin_left (rinoh.image.CaptionStyle attribute), 28
margin_left (rinoh.image.FigureStyle attribute), 32
margin_left (rinoh.index.IndexStyle attribute), 35
margin_left (rinoh.inline.InlineFlowableStyle attribute), 44
margin_left (rinoh.paragraph.ParagraphStyle attribute), 38
margin_left (rinoh.reference.ReferencingParagraphStyle attribute), 47
margin_left (rinoh.structure.AdmonitionStyle attribute), 79
margin_left (rinoh.structure.HeadingStyle attribute), 57
margin_left (rinoh.structure.HorizontalRuleStyle attribute), 81
margin_left (rinoh.structure.ListItemLabelStyle attribute), 64
margin_left (rinoh.structure.ListStyle attribute), 61
margin_left (rinoh.structure.SectionStyle attribute), 54
margin_left (rinoh.structure.TableOfContentsEntryStyle attribute), 75
margin_left (rinoh.structure.TableOfContentsStyle attribute), 69
margin_left (rinoh.table.TableCellStyle attribute), 86
margin_left (rinoh.table.TableStyle attribute), 83
margin_right (rinoh.flowable.FloatStyle attribute), 26
margin_right (rinoh.flowable.FlowableStyle attribute), 19
margin_right (rinoh.flowable.GroupedFlowablesStyle attribute), 23
margin_right (rinoh.flowable.LabeledFlowableStyle attribute), 21
margin_right (rinoh.image.CaptionStyle attribute), 28
margin_right (rinoh.image.FigureStyle attribute), 33
margin_right (rinoh.index.IndexStyle attribute), 35
margin_right (rinoh.inline.InlineFlowableStyle attribute), 44
margin_right (rinoh.paragraph.ParagraphStyle attribute), 38
margin_right (rinoh.reference.ReferencingParagraphStyle attribute), 47
margin_right (rinoh.structure.AdmonitionStyle attribute), 79
margin_right (rinoh.structure.HeadingStyle attribute), 57
margin_right (rinoh.structure.HorizontalRuleStyle attribute), 81
margin_right (rinoh.structure.ListItemLabelStyle attribute), 65
margin_right (rinoh.structure.ListStyle attribute), 61
margin_right (rinoh.structure.SectionStyle attribute), 54
margin_right (rinoh.structure.TableOfContentsEntryStyle attribute), 75
margin_right (rinoh.structure.TableOfContentsStyle attribute), 69
margin_right (rinoh.table.TableCellStyle attribute), 86
margin_right (rinoh.table.TableStyle attribute), 84
matcher (in module rinoh.stylesheets), 11
MixedStyledText (class in rinoh.text), 113
MM (in module rinoh.dimension), 97
module
 rinoh.attribute, 95
 rinoh.color, 96
 rinoh.dimension, 96

- rinoh.document, 97
- rinoh.draw, 98
- rinoh.flowable, 99
- rinoh.font, 101
- rinoh.font.style, 103
- rinoh.image, 103
- rinoh.index, 105
- rinoh.inline, 113
- rinoh.language, 105
- rinoh.number, 110
- rinoh.paper, 111
- rinoh.paragraph, 112
- rinoh.reference, 116
- rinoh.strings, 120
- rinoh.structure, 117
- rinoh.style, 120
- rinoh.stylesheets, 11
- rinoh.table, 122
- rinoh.template, 123
- rinoh.templates.article, 89
- rinoh.templates.book, 91
- rinoh.text, 112

N

- new_page() (rinoh.template.DocumentPart method), 125
- NL (in module rinoh.language), 108
- no_break_after (rinoh.image.CaptionStyle attribute), 31
- no_break_after (rinoh.paragraph.ParagraphStyle attribute), 41
- no_break_after (rinoh.reference.NoteMarkerStyle attribute), 52
- no_break_after (rinoh.reference.ReferencingParagraphStyle attribute), 50
- no_break_after (rinoh.structure.HeadingStyle attribute), 60
- no_break_after (rinoh.structure.ListItemLabelStyle attribute), 68
- no_break_after (rinoh.structure.TableOfContentsEntryStyle attribute), 78
- no_break_after (rinoh.structure.TableOfContentsStyle attribute), 73
- no_break_after (rinoh.text.TextStyle attribute), 43
- NoBreakAfter (class in rinoh.text), 113
- Note (class in rinoh.reference), 116
- note (rinoh.structure.AdmonitionTitles attribute), 119
- NoteMarkerBase (class in rinoh.reference), 116
- NoteMarkerByID (class in rinoh.reference), 116
- NoteMarkerStyle (class in rinoh.reference), 51
- NoteMarkerWithNote (class in rinoh.reference), 116
- number_format (rinoh.image.CaptionStyle attribute), 27
- number_format (rinoh.number.NumberStyle attribute), 110
- number_format (rinoh.paragraph.ParagraphStyle attribute), 37
- number_format (rinoh.reference.NoteMarkerStyle attribute), 53
- number_format (rinoh.reference.ReferencingParagraphStyle attribute), 46
- number_format (rinoh.structure.HeadingStyle attribute), 56
- number_format (rinoh.structure.ListItemLabelStyle attribute), 64
- number_format (rinoh.structure.ListStyle attribute), 63
- number_format (rinoh.structure.TableOfContentsEntryStyle attribute), 74
- number_format (rinoh.structure.TableOfContentsStyle attribute), 71
- number_separator (rinoh.image.CaptionStyle attribute), 28
- number_separator (rinoh.paragraph.ParagraphStyle attribute), 37
- number_separator (rinoh.reference.ReferencingParagraphStyle attribute), 46
- number_separator (rinoh.structure.HeadingStyle attribute), 56
- number_separator (rinoh.structure.ListItemLabelStyle attribute), 64

- number_separator (rinoh.structure.TableOfContentsEntryStyle attribute), 74
- number_separator (rinoh.structure.TableOfContentsStyle attribute), 71
- NumberFormat (class in rinoh.number), 110
- numbering_level (rinoh.image.CaptionStyle attribute), 27
- numbering_level (rinoh.paragraph.ParagraphStyle attribute), 37
- numbering_level (rinoh.reference.ReferencingParagraphStyle attribute), 47
- numbering_level (rinoh.structure.HeadingStyle attribute), 56
- numbering_level (rinoh.structure.ListItemLabelStyle attribute), 64
- numbering_level (rinoh.structure.TableOfContentsEntryStyle attribute), 74
- numbering_level (rinoh.structure.TableOfContentsStyle attribute), 71
- NumberStyle (class in rinoh.number), 110

O

- OptionSet (class in rinoh.attribute), 95
- ordered (rinoh.structure.ListStyle attribute), 60
- OverrideDefault (class in rinoh.attribute), 95

P

- padding (rinoh.flowable.FloatStyle attribute), 26
- padding (rinoh.flowable.FlowableStyle attribute), 19
- padding (rinoh.flowable.GroupedFlowablesStyle attribute), 23
- padding (rinoh.flowable.LabeledFlowableStyle attribute), 21
- padding (rinoh.image.CaptionStyle attribute), 29
- padding (rinoh.image.FigureStyle attribute), 33
- padding (rinoh.index.IndexStyle attribute), 35
- padding (rinoh.inline.InlineFlowableStyle attribute), 44
- padding (rinoh.paragraph.ParagraphStyle attribute), 38
- padding (rinoh.reference.ReferencingParagraphStyle attribute), 47
- padding (rinoh.structure.AdmonitionStyle attribute), 79
- padding (rinoh.structure.HeadingStyle attribute), 57
- padding (rinoh.structure.HorizontalRuleStyle attribute), 81
- padding (rinoh.structure.ListItemLabelStyle attribute), 65
- padding (rinoh.structure.ListStyle attribute), 61
- padding (rinoh.structure.SectionStyle attribute), 54
- padding (rinoh.structure.TableOfContentsEntryStyle attribute), 75
- padding (rinoh.structure.TableOfContentsStyle attribute), 69
- padding (rinoh.table.TableCellStyle attribute), 86
- padding (rinoh.table.TableStyle attribute), 84
- padding_bottom (rinoh.flowable.FloatStyle attribute), 26
- padding_bottom (rinoh.flowable.FlowableStyle attribute), 19
- padding_bottom (rinoh.flowable.GroupedFlowablesStyle attribute), 24
- padding_bottom (rinoh.flowable.LabeledFlowableStyle attribute), 22
- padding_bottom (rinoh.image.CaptionStyle attribute), 29
- padding_bottom (rinoh.image.FigureStyle attribute), 33
- padding_bottom (rinoh.index.IndexStyle attribute), 36
- padding_bottom (rinoh.inline.InlineFlowableStyle attribute), 44
- padding_bottom (rinoh.paragraph.ParagraphStyle attribute), 38
- padding_bottom (rinoh.reference.ReferencingParagraphStyle attribute), 47
- padding_bottom (rinoh.structure.AdmonitionStyle attribute), 79
- padding_bottom (rinoh.structure.HeadingStyle attribute), 57
- padding_bottom (rinoh.structure.HorizontalRuleStyle attribute), 82
- padding_bottom (rinoh.structure.ListItemLabelStyle attribute), 65
- padding_bottom (rinoh.structure.ListStyle attribute), 62
- padding_bottom (rinoh.structure.SectionStyle attribute), 54
- padding_bottom (rinoh.structure.TableOfContentsEntryStyle attribute), 75
- padding_bottom (rinoh.structure.TableOfContentsStyle attribute), 69
- padding_bottom (rinoh.table.TableCellStyle attribute), 86

padding_bottom (rinoh.table.TableStyle attribute), 84
padding_left (rinoh.flowable.FloatStyle attribute), 26
padding_left (rinoh.flowable.FlowableStyle attribute), 19
padding_left (rinoh.flowable.GroupedFlowablesStyle attribute), 24
padding_left (rinoh.flowable.LabeledFlowableStyle attribute), 21
padding_left (rinoh.image.CaptionStyle attribute), 29
padding_left (rinoh.image.FigureStyle attribute), 33
padding_left (rinoh.index.IndexStyle attribute), 35
padding_left (rinoh.inline.InlineFlowableStyle attribute), 44
padding_left (rinoh.paragraph.ParagraphStyle attribute), 38
padding_left (rinoh.reference.ReferencingParagraphStyle attribute), 47
padding_left (rinoh.structure.AdmonitionStyle attribute), 79
padding_left (rinoh.structure.HeadingStyle attribute), 57
padding_left (rinoh.structure.HorizontalRuleStyle attribute), 81
padding_left (rinoh.structure.ListItemLabelStyle attribute), 65
padding_left (rinoh.structure.ListStyle attribute), 61
padding_left (rinoh.structure.SectionStyle attribute), 54
padding_left (rinoh.structure.TableOfContentsEntryStyle attribute), 75
padding_left (rinoh.structure.TableOfContentsStyle attribute), 69
padding_left (rinoh.table.TableCellStyle attribute), 86
padding_left (rinoh.table.TableStyle attribute), 84
padding_right (rinoh.flowable.FloatStyle attribute), 26
padding_right (rinoh.flowable.FlowableStyle attribute), 19
padding_right (rinoh.flowable.GroupedFlowablesStyle attribute), 24
padding_right (rinoh.flowable.LabeledFlowableStyle attribute), 21
padding_right (rinoh.image.CaptionStyle attribute), 29
padding_right (rinoh.image.FigureStyle attribute), 33
padding_right (rinoh.index.IndexStyle attribute), 35
padding_right (rinoh.inline.InlineFlowableStyle attribute), 44
padding_right (rinoh.paragraph.ParagraphStyle attribute), 38
padding_right (rinoh.reference.ReferencingParagraphStyle attribute), 47
padding_right (rinoh.structure.AdmonitionStyle attribute), 79
padding_right (rinoh.structure.HeadingStyle attribute), 57
padding_right (rinoh.structure.HorizontalRuleStyle attribute), 81
padding_right (rinoh.structure.ListItemLabelStyle attribute), 65
padding_right (rinoh.structure.ListStyle attribute), 62
padding_right (rinoh.structure.SectionStyle attribute), 54
padding_right (rinoh.structure.TableOfContentsEntryStyle attribute), 75
padding_right (rinoh.structure.TableOfContentsStyle attribute), 69
padding_right (rinoh.table.TableCellStyle attribute), 86
padding_right (rinoh.table.TableStyle attribute), 84
padding_top (rinoh.flowable.FloatStyle attribute), 26
padding_top (rinoh.flowable.FlowableStyle attribute), 19
padding_top (rinoh.flowable.GroupedFlowablesStyle attribute), 24
padding_top (rinoh.flowable.LabeledFlowableStyle attribute), 21
padding_top (rinoh.image.CaptionStyle attribute), 29
padding_top (rinoh.image.FigureStyle attribute), 33
padding_top (rinoh.index.IndexStyle attribute), 35
padding_top (rinoh.inline.InlineFlowableStyle attribute), 44
padding_top (rinoh.paragraph.ParagraphStyle attribute), 38
padding_top (rinoh.reference.ReferencingParagraphStyle attribute), 47
padding_top (rinoh.structure.AdmonitionStyle attribute), 79
padding_top (rinoh.structure.HeadingStyle attribute), 57
padding_top (rinoh.structure.HorizontalRuleStyle attribute), 81
padding_top (rinoh.structure.ListItemLabelStyle attribute), 65
padding_top (rinoh.structure.ListStyle attribute), 62
padding_top (rinoh.structure.SectionStyle attribute), 54
padding_top (rinoh.structure.TableOfContentsEntryStyle attribute), 75

padding_top (rinoh.structure.TableOfContentsStyle attribute), 69

padding_top (rinoh.table.TableCellStyle attribute), 86

padding_top (rinoh.table.TableStyle attribute), 84

Page (class in rinoh.document), 98

page (rinoh.document.Page property), 98

page (rinoh.templates.article.Article attribute), 90

page (rinoh.templates.book.Book attribute), 92

page_break (rinoh.flowable.FloatStyle attribute), 27

page_break (rinoh.flowable.FlowableStyle attribute), 20

page_break (rinoh.flowable.GroupedFlowablesStyle attribute), 25

page_break (rinoh.flowable.LabeledFlowableStyle attribute), 22

page_break (rinoh.image.CaptionStyle attribute), 30

page_break (rinoh.image.FigureStyle attribute), 34

page_break (rinoh.index.IndexStyle attribute), 36

page_break (rinoh.inline.InlineFlowableStyle attribute), 45

page_break (rinoh.paragraph.ParagraphStyle attribute), 39

page_break (rinoh.reference.ReferencingParagraphStyle attribute), 48

page_break (rinoh.structure.AdmonitionStyle attribute), 80

page_break (rinoh.structure.HeadingStyle attribute), 58

page_break (rinoh.structure.HorizontalRuleStyle attribute), 82

page_break (rinoh.structure.ListItemLabelStyle attribute), 66

page_break (rinoh.structure.ListStyle attribute), 63

page_break (rinoh.structure.SectionStyle attribute), 55

page_break (rinoh.structure.TableOfContentsEntryStyle attribute), 76

page_break (rinoh.structure.TableOfContentsStyle attribute), 70

page_break (rinoh.table.TableCellStyle attribute), 87

page_break (rinoh.table.TableStyle attribute), 85

page_number_format (rinoh.template.ContentsPartTemplate attribute), 126

page_number_format (rinoh.template.DocumentPartTemplate attribute), 125

page_number_format (rinoh.template.FixedDocumentPartTemplate attribute), 127

page_number_format (rinoh.template.TitlePartTemplate attribute), 126

page_number_prefix (rinoh.template.ContentsPartTemplate attribute), 126

page_number_prefix (rinoh.template.DocumentPartTemplate attribute), 125

page_number_prefix (rinoh.template.FixedDocumentPartTemplate attribute), 127

page_number_prefix (rinoh.template.TitlePartTemplate attribute), 126

page_orientation (rinoh.template.PageTemplate attribute), 128

page_orientation (rinoh.template.PageTemplateBase attribute), 130

page_orientation (rinoh.template.TitlePageTemplate attribute), 129

page_size (rinoh.template.PageTemplate attribute), 128

page_size (rinoh.template.PageTemplateBase attribute), 130

page_size (rinoh.template.TitlePageTemplate attribute), 129

PageBreak (class in rinoh.flowable), 99

PageNumberFormat (class in rinoh.document), 98

PageOrientation (class in rinoh.document), 98

PageTemplate (class in rinoh.template), 127

PageTemplateBase (class in rinoh.template), 130

PageType (class in rinoh.document), 98

Paper (class in rinoh.paper), 111

Paragraph (class in rinoh.paragraph), 112

ParagraphBase (class in rinoh.paragraph), 112

ParagraphState (class in rinoh.paragraph), 112

ParagraphStyle (class in rinoh.paragraph), 37

parse_string() (rinoh.color.Color class method), 96

ParseError, 95

parts (rinoh.template.DocumentTemplate attribute), 124

parts (rinoh.templates.article.Article attribute), 89

parts (rinoh.templates.book.Book attribute), 91

PartsList (class in rinoh.template), 124

PERCENT (in module `rinoh.dimension`), 97
 PICA (in module `rinoh.dimension`), 97
 PL (in module `rinoh.language`), 109
 place() (`rinoh.document.Page` method), 98
 Polygon (class in `rinoh.draw`), 99
 position (`rinoh.image.CaptionStyle` attribute), 31
 position (`rinoh.paragraph.ParagraphStyle` attribute), 40
 position (`rinoh.reference.NoteMarkerStyle` attribute), 52
 position (`rinoh.reference.ReferencingParagraphStyle` attribute), 49
 position (`rinoh.structure.HeadingStyle` attribute), 59
 position (`rinoh.structure.ListItemLabelStyle` attribute), 67
 position (`rinoh.structure.TableOfContentsEntryStyle` attribute), 77
 position (`rinoh.structure.TableOfContentsStyle` attribute), 72
 position (`rinoh.text.TextStyle` attribute), 42
 prepare() (`rinoh.flowable.LabeledFlowable` method), 100
 prepare() (`rinoh.flowable.StaticGroupedFlowables` method), 101
 prepare() (`rinoh.paragraph.ParagraphBase` method), 112
 prepare() (`rinoh.reference.NoteMarkerBase` method), 116
 prepare() (`rinoh.reference.NoteMarkerWithNote` method), 116
 prepare() (`rinoh.structure.Heading` method), 117
 prepare() (`rinoh.table.Table` method), 122
 prepare() (`rinoh.table.TableRow` method), 122
 prepare() (`rinoh.table.TableSection` method), 122
 prepare() (`rinoh.text.MixedStyledText` method), 113
 ProportionalSpacing (class in `rinoh.paragraph`), 114
 PT (in module `rinoh.dimension`), 97

Q

QUARTERS (in module `rinoh.dimension`), 97
 quiet (`rinoh.reference.NoteMarkerStyle` attribute), 51

R

Rectangle (class in `rinoh.draw`), 99
 Reference (class in `rinoh.reference`), 116
 ReferenceField (class in `rinoh.reference`), 116
 ReferenceText (class in `rinoh.reference`), 116
 ReferenceType (class in `rinoh.reference`), 116
 ReferencingParagraph (class in `rinoh.reference`), 116
 ReferencingParagraphStyle (class in `rinoh.reference`), 46
 render() (`rinoh.document.Document` method), 97
 render() (`rinoh.document.Page` method), 98
 render() (`rinoh.flowable.GroupedFlowables` method), 100
 render() (`rinoh.flowable.GroupedLabeledFlowables` method), 101
 render() (`rinoh.flowable.LabeledFlowable` method), 100
 render() (`rinoh.paragraph.ParagraphBase` method), 112
 render() (`rinoh.structure.HorizontalRule` method), 120
 render() (`rinoh.table.Table` method), 122
 repeat_head (`rinoh.table.TableStyle` attribute), 83
 rgba (`rinoh.color.Color` property), 96
 right_margin (`rinoh.template.PageTemplate` attribute), 128
 right_margin (`rinoh.template.PageTemplateBase` attribute), 130
 right_margin (`rinoh.template.TitlePageTemplate` attribute), 130
 rinoh command line option

- docs, 6
- format <format>, 5
- help, 5
- install-resources, 5

- list-fonts <filename>, 6
- list-formats, 6
- list-options <frontend>, 6
- list-stylesheets, 5
- list-templates, 5
- option <option=value>, 5
- output <filename or directory>, 5
- paper <paper>, 5
- stylesheet <name or filename>, 5
- template <name or filename>, 5
- version, 6
- f <format>, 5
- h, 5
- i, 5
- O <filename or directory>, 5
- o <option=value>, 5
- p <paper>, 5
- s <name or filename>, 5
- t <name or filename>, 5
- input, 5
- rinoh.attribute
 - module, 95
- rinoh.color
 - module, 96
- rinoh.dimension
 - module, 96
- rinoh.document
 - module, 97
- rinoh.draw
 - module, 98
- rinoh.flowable
 - module, 99
- rinoh.font
 - module, 101
- rinoh.font.style
 - module, 103
- rinoh.image
 - module, 103
- rinoh.index
 - module, 105
- rinoh.inline
 - module, 113
- rinoh.language
 - module, 105
- rinoh.number
 - module, 110
- rinoh.paper
 - module, 111
- rinoh.paragraph
 - module, 112
- rinoh.reference
 - module, 116
- rinoh.strings
 - module, 120
- rinoh.structure
 - module, 117
- rinoh.style
 - module, 120

- rinoh.stylesheets
 - module, 11
- rinoh.table
 - module, 122
- rinoh.template
 - module, 123
- rinoh.templates.article
 - module, 89
- rinoh.templates.book
 - module, 91
- rinoh.text
 - module, 112
- rinoh_documents
 - Sphinx builder configuration value, 7
- rinoh_domain_indices
 - Sphinx builder configuration value, 9
- rinoh_logo
 - Sphinx builder configuration value, 9
- rinoh_metadata
 - Sphinx builder configuration value, 9
- rinoh_paper_size
 - Sphinx builder configuration value, 8
- rinoh_stylesheet
 - Sphinx builder configuration value, 8
- rinoh_targets
 - Sphinx builder configuration value, 8
- rinoh_template
 - Sphinx builder configuration value, 8
- root (rinoh.attribute.RuleSetFile property), 95
- rotate (rinoh.image.ImageArgs attribute), 104
- RuleSet (class in rinoh.attribute), 95
- RuleSetFile (class in rinoh.attribute), 95

S

- Scale (class in rinoh.image), 104
- scale (rinoh.image.ImageArgs attribute), 104
- script_level() (rinoh.text.StyledText method), 113
- Section (class in rinoh.structure), 117
- SectionStyle (class in rinoh.structure), 53
- SectionTitles (class in rinoh.structure), 117
- seealso (rinoh.structure.AdmonitionTitles attribute), 119
- SetMetadataFlowable (class in rinoh.flowable), 99
- Shape (class in rinoh.draw), 99
- ShapeStyle (class in rinoh.draw), 18
- show_author (rinoh.template.TitlePageTemplate attribute), 129
- show_date (rinoh.template.TitlePageTemplate attribute), 129
- show_in_toc (rinoh.structure.SectionStyle attribute), 53
- SINGLE (in module rinoh.paragraph), 115
- SingleStyledText (class in rinoh.text), 113
- space_above (rinoh.flowable.FloatStyle attribute), 25
- space_above (rinoh.flowable.FlowableStyle attribute), 18
- space_above (rinoh.flowable.GroupedFlowablesStyle attribute), 23
- space_above (rinoh.flowable.LabeledFlowableStyle attribute), 21
- space_above (rinoh.image.CaptionStyle attribute), 28
- space_above (rinoh.image.FigureStyle attribute), 32
- space_above (rinoh.index.IndexStyle attribute), 35
- space_above (rinoh.inline.InlineFlowableStyle attribute), 44

- space_above (rinoh.paragraph.ParagraphStyle attribute), 38
- space_above (rinoh.reference.ReferencingParagraphStyle attribute), 47
- space_above (rinoh.structure.AdmonitionStyle attribute), 79
- space_above (rinoh.structure.HeadingStyle attribute), 57
- space_above (rinoh.structure.HorizontalRuleStyle attribute), 81
- space_above (rinoh.structure.ListItemLabelStyle attribute), 64
- space_above (rinoh.structure.ListStyle attribute), 61
- space_above (rinoh.structure.SectionStyle attribute), 54
- space_above (rinoh.structure.TableOfContentsEntryStyle attribute), 74
- space_above (rinoh.structure.TableOfContentsStyle attribute), 69
- space_above (rinoh.table.TableCellStyle attribute), 86
- space_above (rinoh.table.TableStyle attribute), 83
- space_below (rinoh.flowable.FloatStyle attribute), 25
- space_below (rinoh.flowable.FlowableStyle attribute), 18
- space_below (rinoh.flowable.GroupedFlowablesStyle attribute), 23
- space_below (rinoh.flowable.LabeledFlowableStyle attribute), 21
- space_below (rinoh.image.CaptionStyle attribute), 28
- space_below (rinoh.image.FigureStyle attribute), 32
- space_below (rinoh.index.IndexStyle attribute), 35
- space_below (rinoh.inline.InlineFlowableStyle attribute), 44
- space_below (rinoh.paragraph.ParagraphStyle attribute), 38
- space_below (rinoh.reference.ReferencingParagraphStyle attribute), 47
- space_below (rinoh.structure.AdmonitionStyle attribute), 79
- space_below (rinoh.structure.HeadingStyle attribute), 57
- space_below (rinoh.structure.HorizontalRuleStyle attribute), 81
- space_below (rinoh.structure.ListItemLabelStyle attribute), 64
- space_below (rinoh.structure.ListStyle attribute), 61
- space_below (rinoh.structure.SectionStyle attribute), 54
- space_below (rinoh.structure.TableOfContentsEntryStyle attribute), 75
- space_below (rinoh.structure.TableOfContentsStyle attribute), 69
- space_below (rinoh.table.TableCellStyle attribute), 86
- space_below (rinoh.table.TableStyle attribute), 83
- sphinx (in module rinoh.stylesheets), 11
- Sphinx builder configuration value
 - rinoh_documents, 7
 - rinoh_domain_indices, 9
 - rinoh_logo, 9
 - rinoh_metadata, 9
 - rinoh_paper_size, 8
 - rinoh_stylesheet, 8
 - rinoh_targets, 8
 - rinoh_template, 8
- sphinx_article (in module rinoh.stylesheets), 11
- sphinx_base14 (in module rinoh.stylesheets), 11
- split_minimum_rows (rinoh.table.TableStyle attribute), 83
- STANDARD (in module rinoh.paragraph), 115
- StaticGroupedFlowables (class in rinoh.flowable), 100
- String (class in rinoh.strings), 120
- StringCollection (class in rinoh.strings), 120
- StringField (class in rinoh.strings), 120
- Strings (class in rinoh.strings), 120
- strings (rinoh.template.DocumentTemplate attribute), 123
- strings (rinoh.templates.article.Article attribute), 89
- strings (rinoh.templates.book.Book attribute), 91
- Stroke (class in rinoh.draw), 98
- stroke (rinoh.draw.LineStyle attribute), 17
- stroke (rinoh.draw.ShapeStyle attribute), 18
- stroke (rinoh.structure.HorizontalRuleStyle attribute), 83

stroke (rinoh.table.TableCellBackgroundStyle attribute), 88
 stroke (rinoh.table.TableCellBorderStyle attribute), 87
 Style (class in rinoh.style), 121
 style_class (rinoh.draw.Line attribute), 98
 style_class (rinoh.draw.Shape attribute), 99
 style_class (rinoh.flowable.GroupedFlowables attribute), 100
 style_class (rinoh.flowable.LabeledFlowable attribute), 100
 style_class (rinoh.image.Caption attribute), 104
 style_class (rinoh.image.Figure attribute), 105
 style_class (rinoh.index.Index attribute), 105
 style_class (rinoh.inline.InlineFlowable attribute), 114
 style_class (rinoh.paragraph.ParagraphBase attribute), 112
 style_class (rinoh.reference.Note attribute), 116
 style_class (rinoh.reference.NoteMarkerBase attribute), 116
 style_class (rinoh.reference.ReferencingParagraph attribute), 116
 style_class (rinoh.structure.Admonition attribute), 118
 style_class (rinoh.structure.Heading attribute), 117
 style_class (rinoh.structure.HorizontalRule attribute), 120
 style_class (rinoh.structure.List attribute), 118
 style_class (rinoh.structure.TableOfContents attribute), 118
 style_class (rinoh.structure.TableOfContentsEntry attribute), 118
 style_class (rinoh.style.Styled attribute), 121
 style_class (rinoh.table.Table attribute), 122
 style_class (rinoh.table.TableCell attribute), 123
 style_class (rinoh.table.TableCellBackground attribute), 123
 style_class (rinoh.table.TableCellBorder attribute), 123
 style_class (rinoh.table.TableWithCaption attribute), 122
 style_class (rinoh.text.StyledText attribute), 113
 Styled (class in rinoh.style), 120
 StyledMatcher (class in rinoh.style), 122
 StyledText (class in rinoh.text), 112
 StyleSheet (class in rinoh.style), 121
 stylesheet (rinoh.template.DocumentTemplate attribute), 123
 stylesheet (rinoh.templates.article.Article attribute), 89
 stylesheet (rinoh.templates.book.Book attribute), 91
 StyleSheetFile (class in rinoh.style), 121

T

tab_stops (rinoh.image.CaptionStyle attribute), 28
 tab_stops (rinoh.paragraph.ParagraphStyle attribute), 37
 tab_stops (rinoh.reference.ReferencingParagraphStyle attribute), 46
 tab_stops (rinoh.structure.HeadingStyle attribute), 56
 tab_stops (rinoh.structure.ListItemLabelStyle attribute), 64
 tab_stops (rinoh.structure.TableOfContentsEntryStyle attribute), 74
 tab_stops (rinoh.structure.TableOfContentsStyle attribute), 71
 TabAlign (class in rinoh.paragraph), 115
 Table (class in rinoh.table), 122
 table_of_contents (rinoh.templates.article.Article attribute), 89
 TableBody (class in rinoh.table), 122
 TableCell (class in rinoh.table), 123
 TableCellBackground (class in rinoh.table), 123
 TableCellBackgroundStyle (class in rinoh.table), 88
 TableCellBorder (class in rinoh.table), 123
 TableCellBorderStyle (class in rinoh.table), 87
 TableCellStyle (class in rinoh.table), 85
 TableHead (class in rinoh.table), 122
 TableOfContents (class in rinoh.structure), 118

TableOfContentsEntry (class in rinoh.structure), 118
 TableOfContentsEntryStyle (class in rinoh.structure), 73
 TableOfContentsSection (class in rinoh.structure), 118
 TableOfContentsStyle (class in rinoh.structure), 68
 TableRow (class in rinoh.table), 122
 TableSection (class in rinoh.table), 122
 TableStyle (class in rinoh.table), 83
 TableWithCaption (class in rinoh.table), 122
 TABLOID (in module rinoh.paper), 112
 TabStop (class in rinoh.paragraph), 115
 TabStopList (class in rinoh.paragraph), 115
 target_has_class() (rinoh.reference.ReferencingParagraph method), 116
 target_has_classes() (rinoh.reference.ReferencingParagraph method), 116
 target_is_of_type() (rinoh.reference.ReferencingParagraph method), 116
 target_style() (rinoh.reference.ReferencingParagraph method), 116
 template (rinoh.template.TemplateConfiguration attribute), 124
 TemplateConfiguration (class in rinoh.template), 124
 text (rinoh.reference.ReferencingParagraphStyle attribute), 46
 text (rinoh.structure.TableOfContentsEntryStyle attribute), 73
 text_align (rinoh.image.CaptionStyle attribute), 28
 text_align (rinoh.paragraph.ParagraphStyle attribute), 37
 text_align (rinoh.reference.ReferencingParagraphStyle attribute), 46
 text_align (rinoh.structure.HeadingStyle attribute), 56
 text_align (rinoh.structure.ListItemLabelStyle attribute), 64
 text_align (rinoh.structure.TableOfContentsEntryStyle attribute), 74
 text_align (rinoh.structure.TableOfContentsStyle attribute), 71
 TextAlign (class in rinoh.paragraph), 114
 TextPosition (class in rinoh.font.style), 103
 TextStyle (class in rinoh.text), 41
 tip (rinoh.structure.AdmonitionTitles attribute), 119
 title (rinoh.flowable.GroupedFlowablesStyle attribute), 23
 title (rinoh.image.FigureStyle attribute), 34
 title (rinoh.index.IndexStyle attribute), 35
 title (rinoh.structure.AdmonitionStyle attribute), 78
 title (rinoh.structure.ListStyle attribute), 61
 title (rinoh.structure.SectionStyle attribute), 53
 title (rinoh.structure.TableOfContentsStyle attribute), 68
 title (rinoh.table.TableCellStyle attribute), 85
 title (rinoh.templates.article.Article attribute), 90
 title (rinoh.templates.book.Book attribute), 91
 title_page (rinoh.templates.article.Article attribute), 90
 title_page (rinoh.templates.book.Book attribute), 92
 TitlePageTemplate (class in rinoh.template), 129
 TitlePartTemplate (class in rinoh.template), 125
 to_string() (rinoh.index.InlineIndexTarget method), 105
 to_string() (rinoh.text.StyledText method), 112
 top_margin (rinoh.template.PageTemplate attribute), 128
 top_margin (rinoh.template.PageTemplateBase attribute), 131
 top_margin (rinoh.template.TitlePageTemplate attribute), 130
 type (rinoh.reference.NoteMarkerStyle attribute), 51
 Typeface (class in rinoh.font), 102
 typeface (rinoh.image.CaptionStyle attribute), 30
 typeface (rinoh.paragraph.ParagraphStyle attribute), 40
 typeface (rinoh.reference.NoteMarkerStyle attribute), 51
 typeface (rinoh.reference.ReferencingParagraphStyle attribute), 49
 typeface (rinoh.structure.HeadingStyle attribute), 59
 typeface (rinoh.structure.ListItemLabelStyle attribute), 66
 typeface (rinoh.structure.TableOfContentsEntryStyle attribute), 76

typeface (rinoh.structure.TableOfContentsStyle attribute), 72
typeface (rinoh.text.TextStyle attribute), 41

U

update() (rinoh.style.StyledMatcher method), 122
UserStrings (class in rinoh.strings), 120

V

vertical_align (rinoh.table.TableCellStyle attribute), 85
VerticalAlign (class in rinoh.table), 123

W

WarnFlowable (class in rinoh.flowable), 99
warning (rinoh.structure.AdmonitionTitles attribute), 119
width (rinoh.flowable.FloatStyle attribute), 25
width (rinoh.flowable.FlowableStyle attribute), 18
width (rinoh.flowable.GroupedFlowablesStyle attribute), 23
width (rinoh.flowable.LabeledFlowableStyle attribute), 21
width (rinoh.image.CaptionStyle attribute), 27
width (rinoh.image.FigureStyle attribute), 32
width (rinoh.image.ImageArgs attribute), 104
width (rinoh.index.IndexStyle attribute), 34
width (rinoh.inline.InlineFlowableStyle attribute), 43
width (rinoh.paragraph.ParagraphStyle attribute), 37
width (rinoh.reference.ReferencingParagraphStyle attribute), 46
width (rinoh.structure.AdmonitionStyle attribute), 78
width (rinoh.structure.HeadingStyle attribute), 56
width (rinoh.structure.HorizontalRuleStyle attribute), 81
width (rinoh.structure.ListItemLabelStyle attribute), 63
width (rinoh.structure.ListStyle attribute), 61
width (rinoh.structure.SectionStyle attribute), 53
width (rinoh.structure.TableOfContentsEntryStyle attribute), 73
width (rinoh.structure.TableOfContentsStyle attribute), 68
width (rinoh.table.TableCellStyle attribute), 85
width (rinoh.table.TableStyle attribute), 83
wrap_label (rinoh.flowable.LabeledFlowableStyle attribute), 21

Y

y_offset() (rinoh.text.StyledText method), 113