
rinoh^{type}

Release 0.5.0.dev1

Contents

7	Chapter 1: Introduction
7	Usage Examples
9	Chapter 2: Installation
9	Dependencies
11	Chapter 3: Quickstart
11	Command-Line Renderer
11	Sphinx Builder
12	High-level PDF Library
15	Chapter 4: Basic Document Styling
15	Style Sheets
17	Document Templates
21	Chapter 5: Element Styling
21	Document Tree
22	Selectors
24	Matchers
24	Style Sheets
27	Style Logs
29	Chapter 6: Document Templates
29	Subclassing a Template
30	Creating a Custom Template
31	Chapter 7: Reference
31	rinoh
32	Sphinx Builder
33	Style Sheets
105	Standard Document Templates
111	Chapter 8: API Documentation
111	Attribute (rinoh.attribute)
111	Color (rinoh.color)

112	Dimension (rinoh.dimension)
113	Document (rinoh.document)
114	Drawing Primitives (rinoh.draw)
115	Flowable (rinoh.flowable)
117	Fonts and Typefaces (rinoh.font)
119	Images and Figures (rinoh.image)
121	Index (rinoh.index)
121	Language (rinoh.language)
124	Number (rinoh.number)
125	Paper sizes (rinoh.paper)
125	Paragraph (rinoh.paragraph)
129	Cross-References and Fields (rinoh.reference)
130	Structure (rinoh.structure)
132	Strings (rinoh.strings)
133	Style (rinoh.style)
134	Tables (rinoh.table)
135	Templates (rinoh.template)

145 Chapter 9: Frequently Asked Questions

147 Chapter 10: Release History

147	Release 0.5.0-dev
148	Release 0.4.2 (2020-07-28)
149	Release 0.4.1 (2020-07-01)
149	Release 0.4.0 (2020-03-05)
151	Release 0.3.1 (2016-12-19)
151	Release 0.3.0 (2016-11-23)
154	Release 0.2.1 (2016-08-18)
154	Release 0.2.0 (2016-08-10)
156	Release 0.1.3 (2015-08-04)
156	Release 0.1.2 (2015-07-31)
156	Release 0.1.1 (2015-04-12)

157 Chapter : Python Module Index

159 Chapter : Index

Release v0.5.0.dev1. ([Release History](#))

rinoh type is a Python library that transforms a structured document into a professionally typeset PDF guided by a document template and style sheet. It can be used to create any kind of document, but its focus is on complex documents such as technical manuals.

Included with rinoh type is the rinoh command line tool that renders reStructuredText and Markdown (CommonMark) documents. Support for [DITA](#) is available in the commercially supported Pro version.

rinoh type also includes support for [Sphinx](#), which helps writing large structured documents and supports a multitude of different output formats including searchable HTML. rinoh type adds support to produce PDF output.

Here is a list of rinoh type's main features:

- a powerful page layout system supporting columns, running headers/footers, floatable elements and footnotes
- figures, large tables and automatically generated table of contents
- automatic numbering and cross-referencing of sections, figures and tables
- use one of the highly configurable included document templates or create your own custom template
- the intuitive style sheets make it easy to change the style of individual document elements
- modular design allowing for multiple frontends (such as reStructuredText, Markdown, DocBook, ...) and backends (PDF, SVG, bitmap, ...)
- handles OpenType, TrueType and Type1 fonts with support for advanced typographic features such as kerning, ligatures and small capitals
- embeds PDF, PNG and JPEG images, preserving transparency and color profiles
- easy to deploy; pure-Python with few dependencies
- built on Unicode; ready for non-latin languages

rinoh type is currently in a beta phase. We are working toward a first stable release.

rinoh type is open source software licensed under the [GNU AGPL 3.0](#). Practically, this means you are free to use it in open-source software, but not in (commercial) closed-source software. For the latter, you need to obtain a commercial license (see <http://www.opqode.com/rinoh>). We are also available for consultancy projects involving rinoh type, so don't hesitate to [contact us](#).

rinohype was initially conceived as a modern replacement for [LaTeX](#). An important goal in the design of rinohype is for documents to be much easier to customize than in LaTeX. By today's standards, the arcane TeX macro language upon which LaTeX is built makes customization unnecessarily difficult for one. Simply being built with Python makes rinohype already much easier to approach than TeX. Additionally, rinohype is built around the following core concepts to ensure customizability:

Document Templates These determine the page layout and (for longer documents) the different parts of your document. The templates included with rinohype are highly configurable and allow changing margins, headers, footers, chapter titles, etc. If this is not sufficient, a custom template can be created.

Style Sheets The CSS-inspired style sheets determine the look of individual document elements. A style sheet assigns style attributes to each type of document element. For example, a paragraph's style is determined by the typeface, font weight, size and color, horizontal alignment of text etc.

Structured Input rinohype renders a document from a document tree that does not describe any style aspects but only semantics. The style sheet maps specific style properties to the elements in this document tree. The document tree can be automatically generated from a structured document format such as `reStructuredText` and `CommonMark` using one of the included frontends, or it can be constructed manually.

rinohype is implemented as a Python package and doubles as a high-level PDF library. Its modular design makes it easy to to customize and extend for specific applications. Moreover, because rinohype's source code is open, all of its internals can be inspected and even modified, making it customizable at all levels.

1.1 Usage Examples

rinohype supports three modes of operation, which are discussed in more detail in the [Quickstart](#) guide. For each of these modes, you can choose to use one of the document templates included with rinohype or a third-party template available from PyPI and optionally customize it to your needs. Or you can create a custom template from scratch. The same is true for the style sheet used to style the document elements.

1.1.1 Command-Line Renderer

rinohype includes the `rinoh` command-line tool which renders structured text documents. Currently, `reStructuredText` and `CommonMark` documents are supported in the open-source version. Support for `DITA` is available in the commercially supported Pro version.

Rendering the reStructuredText demonstration article [demo.txt](#) (using the standard article template and style sheet) generates demo.pdf.

1.1.2 Sphinx Builder

Configuring rinohtype as a builder for Sphinx allows rendering a Sphinx project to PDF without the need for a LaTeX installation. This very document you are reading was rendered using rinohtype's Sphinx builder.

1.1.3 High-level PDF library

rinohtype can also be used as a Python library to generate PDF documents. Just like with rinohtype and the Sphinx builder, you can select which document template and style sheet to use.

Additionally, you need to supply a document tree. This document tree can be parsed from a structured document format such as reStructuredText by using one of the provided frontends or built manually using building blocks provided by rinohtype. You can also write a frontend for a custom format such as an XML dialect.

All of these approaches allow for parts of the content to be fetched from a database or other data sources. When parsing the document tree from a structured document format, a templating engine like [Jinja2](#) can be used.

Todo

sample documents

rinohype supports Python 3.3 and up. Use [pip](#) to install the latest version of rinohype and its dependencies:

```
pip install rinohype
```

If you plan on using rinohype as an alternative to LaTeX, you will want to install [Sphinx](#) as well:

```
pip install Sphinx
```

See [Sphinx Builder](#) in the [Quickstart](#) guide on how to render Sphinx documents with rinohype.

2.1 Dependencies

For parsing reStructuredText and CommonMark documents, rinohype depends on [docutils](#) and [recommonmark](#) respectively. pip takes care of these requirements automatically when you install rinohype.

If you want to include images other than PDF, PNG or JPEG, you need to install [Pillow](#) additionally.

This section gets you started quickly, discussing each of the three modes of operation introduced in [Introduction](#). If you want to customize the style of the PDF document, please refer to [Basic Document Styling](#) which introduces style sheets and document templates.

3.1 Command-Line Renderer

Installing rinohtype places the rinoh script in the PATH. This can be used to render structured documents such as [demo.txt](#) ([reStructuredText](#)):

```
rinoh --format reStructuredText demo.txt
```

After rendering finishes, you will find `demo.pdf` alongside the input file.

rinoh allows specifying the document template and style sheet to use when rendering the [reStructuredText](#) document. See its [command-line options](#) for details.

Two rendering passes are required to make sure that cross-references to page numbers are correct. After a document has been rendered, rinohtype will save the page reference data to a `.rtc` file. Provided the document (or the template or style sheet) doesn't change a lot, this can prevent the need to perform a second rendering pass.

3.2 Sphinx Builder

If your Sphinx project is already configured for the LaTeX builder, rinohtype will happily interpret [latex_documents](#). Otherwise, you need to set the [rinoh_documents](#) configuration option:

```
rinoh_documents = [('index',          # top-level file (index.rst)
                   'target',         # output (target.pdf)
                   'Document Title', # document title
                   'John A. Uthor')] # document author
```

Other configuration variables are optional and allow configuring the style of the generated PDF document. See [Sphinx Builder](#) for details.

When building the documentation, select the rinoh builder by passing it to the `sphinx-build -b` option:

```
sphinx-build -b rinoh . _build/rinoh
```

Note that, just like the rinoh command line tool, the Sphinx builder requires two [rendering passes](#).

3.3 High-level PDF Library

Note

The focus of rinohtype development is currently on the rinohtool and Sphinx builder. Use as a Python library is possible, but documentation may be lacking. Please be patient.

The most basic way to use rinohtype in an application is to hook up an included frontend, a document template and a style sheet:

```
from rinohtype.frontend.rst import ReStructuredTextReader
from rinohtype.templates import Article

# the parser builds a rinohtype document tree
parser = ReStructuredTextReader()
with open('my_document.rst') as file:
    document_tree = parser.parse(file)

# render the document to 'my_document.pdf'
document = Article(document_tree)
document.render('my_document')
```

This basic application can be customized to your specific requirements by customizing the document template, the style sheet and the way the document's content tree is built. The basics of document templates and style sheets are covered in later sections.

The document tree returned by the `ReStructuredTextReader` in the example above can also be built manually. A `DocumentTree` is simply a list of `Flowables`, which can have child elements. These children in turn can also have children, and so on; together they form a tree.

Here is an example document tree of a short article:

```
from rinohtype.document import DocumentTree
from rinohtype.style import *

document_tree = DocumentTree(
    [Paragraph('My Document', style='title'), # metadata!
     Section([Heading('First Section'),
               Paragraph('This is a paragraph with some '
                        + StyledText('emphasized text',
                                     style='emphasis')
                        + ' and an '
                        + InlineImage('image.pdf')),
               Section([Heading('A subsection'),
                        Paragraph('Another paragraph')
                       ])
              ]),
     Section([Heading('Second Section'),
               List([Paragraph('a list item'),
                     Paragraph('another list item')
                    ])
              ])
    ])
])
```

It is clear that this type of content is best parsed from a structured document format such as `reStructuredText` or XML. Manually building a document tree is well suited for short, custom

documents however.

rinohtype allows for fine-grained control over the style of its output. Most aspects of a document's style can be controlled by style sheet files and template configuration files which are being introduced in this chapter. These files are plain text files that are easy to create, read and modify.

4.1 Style Sheets

A style sheet defines the look of each element in a document. For each type of document element, the style sheet assign values to the style properties available for that element. Style sheets are stored in plain text files using the Windows INI1 format with the .rts extension. Below is an excerpt from the [Sphinx style sheet](#) included with rinohtype.

```
[STYLESHEET]
name=Sphinx
description=Mostly a copy of the LaTeX style included with Sphinx
pygments_style=friendly

[VARIABLES]
mono_typeface=TeX Gyre Cursor
serif_typeface=TeX Gyre Pagella
sans_typeface=TeX Gyre Heros
fallback_typeface=DejaVu Serif
thin_black_stroke=0.5pt, #000
blue=#20435c

[default:Paragraph]
typeface=$(serif_typeface)
font_weight=REGULAR
font_size=10pt
line_spacing=fixed(12pt, leading(0))
indent_first=0
space_above=0
space_below=0
text_align=JUSTIFY
kerning=True
ligatures=True
hyphen_lang=en_US
hyphen_chars=4

[fallback]
```

1 see Supported INI File Structure in [configparser](#)

```

typeface=$(fallback_typeface)

[body]
base=default
space_above=5pt
space_below=0
text_align=justify

[emphasis]
font_slant=italic

[strong]
font_weight=BOLD

[literal emphasis]
base=emphasis
typeface=$(mono_typeface)
hyphenate=False
ligatures=False

[literal strong]
base=strong
typeface=$(mono_typeface)
hyphenate=False
ligatures=False

[inline math]
base=monospaced

[quote]
font_slant=italic

```

Except for [STYLESHEET] and [VARIABLES], each configuration section in a style sheet determines the style of a particular type of document element. The emphasis style, for example, determines the look of emphasized text, which is displayed in an italic font. This is similar to how HTML's cascading style sheets work. In rinohtype however, document elements are identified by means of a descriptive label (such as emphasis) instead of a cryptic selector. rinohtype also makes use of selectors, but these are collected in a [matcher](#) which maps them to descriptive names to be used by many style sheets. Unless you are using rinohtype as a PDF library to create custom documents, the [default matcher](#) should cover your needs.

The following two subsections illustrate how to extend an existing style sheet and how to create a new, independent style sheet. For more in-depth information on style sheets, please refer to [Element Styling](#).

4.1.1 Extending an Existing Style Sheet

Starting from an existing style sheet, it is easy to make small changes to the style of individual document elements. The following style sheet file is based on the Sphinx stylesheet included with rinohtype.

```

[STYLESHEET]
name=My Style Sheet
description=Small tweaks made to the Sphinx style sheet
base=sphinx

[VARIABLES]

```



```
mono_typeface=Courier

[emphasis]
font_color=#00a

[strong]
base=DEFAULT_STYLE
font_color=#a00
```

By default, styles defined in a style sheet extend the corresponding style from the base style sheet. In this example, emphasized text will be set in an italic font (as configured in the [base style sheet](#)) and colored blue (#00a).

It is also possible to completely override a style definition. This can be done by setting the base of a style definition to `DEFAULT_STYLE` as illustrated by the strong style. This causes strongly emphasised text to be displayed in red (#a00) but not in a bold font as was defined in the [base style sheet](#) (the default for `font_weight` is Medium; see [TextStyle](#)). Refer to [Default Matcher](#) to find out which style attributes are accepted by each style (by following the hyperlink to the style class's documentation).

The style sheet also redefines the `mono_typeface` variable. This variable is used in the [base style sheet](#) in all style definitions where a monospaced font is desired. Redefining the variable in the derived style sheet affects all of these style definitions.

4.1.2 Starting from Scratch

If you don't specify a base style sheet in the `[STYLESHEET]` section, you create an independent style sheet. You should do this if you want to create a document style that is not based on an existing style sheet. If the style definition for a particular document element is not included in the style sheet, the default values for its style properties are used.

Todo

specifying a custom matcher for an INI style sheet

Unless a custom [StyledMatcher](#) is passed to [StyleSheetFile](#), the [default matcher](#) is used. Providing your own matcher offers even more customizability, but it is unlikely you will need this. See [Matchers](#).

Note

In the future, rinohtype will be able to generate an empty INI style sheet, listing all styles defined in the matcher with the supported style attributes along with the default values as comments. This generated style sheet can serve as a good starting point for developing a custom style sheet from scratch.

4.2 Document Templates

As with style sheets, you can choose to make use of a template provided by rinohtype and optionally customize it or you can create a custom template from scratch. This section discusses how you can configure an existing template. See [Document Templates](#) on how to create a custom template.

4.2.1 Configuring a Template

rinohytype provides a number of [Standard Document Templates](#). These can be customized by means of a template configuration file; a plain text file in the INI1 format with the .rtt extension. Here is an example configuration for the article template:

```
[TEMPLATE_CONFIGURATION]
name = my article configuration
template = article

parts =
    title
    ;front_matter
    contents
stylesheet = sphinx_base14
language = fr
abstract_location = title

[SectionTitles]
contents = 'Contents'

[AdmonitionTitles]
caution = 'Careful!'
warning = 'Please be warned'

[VARIABLES]
paper_size = A5

[title]
page_number_format = lowercase roman
end_at_page = left

[contents]
page_number_format = number

[title_page]
top_margin = 2cm
```

The `TEMPLATE_CONFIGURATION` sections collects global template options. Set `name` to provide a short label for your template configuration. `template` identifies the [document template](#) to configure.

All document templates consist of a number of document parts. The [Article](#) template defines three parts: `title`, `front_matter` and `contents`. The order of these parts can be changed (although that makes little sense for the article template), and individual parts can optionally be hidden by setting the `parts` configuration option. The configuration above hides the front matter part (commented out using a semicolon), for example.

The template configuration also specifies which style sheet is used for styling document elements. The `DocumentTemplate.stylesheet` option takes the name of an installed style sheet (see [rinoh --list-stylesheets](#)) or the filename of a stylesheet file (.rts).

The `language` option sets the default language for the document. It determines which language is used for standard document strings such as section and admonition titles.

The [Article](#) template defines two custom template options. The `abstract_location` option determines where the (optional) article abstract is placed, on the title page or in the front matter part. `table_of_contents` allows hiding the table of contents section. Empty document parts will not be

included in the document. When the table of contents section is suppressed and there is no abstract in the input document or `abstract_location` is set to `title`, the front matter document part will not appear in the PDF.

The standard document strings configured by the language option described above can be overridden by user-defined strings in the `SectionTitles` and `AdmonitionTitles` sections of the configuration file. For example, the default title for the table of contents section (Table of Contents) is replaced with Contents. The configuration also sets custom titles for the caution and warning admonitions.

The others sections in the configuration file are the `VARIABLES` section, followed by document part and page template sections. Similar to style sheets, the variables can be referenced in the template configuration sections. Here, the `paper_size` variable is set, which is being referenced by all page templates in Article (although indirectly through the page base page template).

For document part templates, `page_number_format` determines how page numbers are formatted. When a document part uses the same page number format as the preceding part, the numbering is continued.

The `DocumentPartTemplate.end_at_page` option controls at which page the document part ends. This is set to left for the title part in the example configuration to make the contents part start on a right page.

Each document part finds page templates by name. They will first look for specific left/right page templates by appending `_left_page` or `_right_page` to the document part name. If these page templates have not been defined in the template, it will look for the more general `<document part name>_page` template. Note that, if left and right page templates have been defined by the template (such as the book template), the configuration will need to override these, as they will have priority over the general page template defined in the configuration.

The example configuration only adjusts the top margin for the `TitlePageTemplate`, but many more aspects of the page templates are configurable. Refer to [Standard Document Templates](#) for details.

Todo

base for part template?

4.2.2 Using a Template Configuration File

A template configuration file can be specified when rendering using the command-line `rinoh` tool by passing it to the `--template` command-line option. When using the [Sphinx Builder](#), you can set the `rinoh_template` option in `conf.py`.

To render a document using this template configuration programatically, load the template file using `TemplateConfigurationFile`:

```
import sys
from pathlib import Path

from rinoh.frontend.rst import ReStructuredTextReader
from rinoh.template import TemplateConfigurationFile

# the parser builds a rinohtype document tree
parser = ReStructuredTextReader()
with open('my_document.rst') as file:
    document_tree = parser.parse(file)

# load the article template configuration file
script_path = Path(sys.path[0]).resolve()
```

```
config = TemplateConfigurationFile(script_path / 'my_article.rtt')

# render the document to 'my_document.pdf'
document = config.document(document_tree)
document.render('my_document')
```

The `TemplateConfigurationFile.document()` method creates a document instance with the template configuration applied. So if you want to render your document using a different template configuration, it suffices to load the new configuration file.

Refer to the [Article](#) documentation to discover all of the options accepted by it and the document part and page templates.

This section describes how styles defined in a style sheet are applied to document elements. Understanding how this works will help you when designing a custom style sheet.

rinohype's style sheets are heavily inspired by [CSS](#), but add some additional functionality. Similar to CSS, rinohype makes use of so-called selectors to select document elements in the document tree to style. Unlike CSS however, these selectors are not directly specified in a style sheet. Instead, all selectors are collected in a matcher where they are mapped to descriptive labels for the selected elements. A style sheet assigns style properties to these labels. Besides the usefulness of having these labels instead of the more cryptic selectors, a matcher can be reused by multiple style sheets, avoiding duplication.

Note

This section currently assumes some Python or general object-oriented programming knowledge. A future update will move Python-specific details to another section, making things more accessible for non-programmers.

5.1 Document Tree

A [Flowable](#) is a document element that is placed on a page. It is usually a part of a document tree. Flowables at one level in a document tree are rendered one below the other.

Here is schematic representation of an example document tree:

```
| - Section
|   | - Paragraph
|   \ - Paragraph
\ - Section
    | - Paragraph
    | - List
    |   | - ListItem
    |   |   | - Paragraph (item label; a number or bullet symbol)
    |   |   \ - StaticGroupedFlowables (item body)
    |   |       \ - Paragraph
    |   \ - ListItem
    |       \ - Paragraph
    |   \ - StaticGroupedFlowables
    |       \ - List
    |           | - ListItem
    |           |   \ - ...
    |           \ - ...
\ - Paragraph
```

This represents a document consisting of two sections. The first section contains two paragraphs. The second section contains a paragraph followed by a list and another paragraph. All of the elements in this tree are instances of [Flowable](#) subclasses.

[Section](#) and [List](#) are subclasses of [GroupedFlowables](#); they group a number of flowables. In the case of [List](#), these are always of the [ListItem](#) type. Each list item contains an item number (ordered list) or a bullet symbol (unordered list) and an item body. For simple lists, the item body is typically a single [Paragraph](#). The second list item contains a nested [List](#).

A [Paragraph](#) does not have any [Flowable](#) children. It is however the root node of a tree of inline elements. This is an example paragraph in which several text styles are combined:

```
Paragraph
|- SingleStyledText('Text with ')
|- MixedStyledText(style='emphasis')
|   |- SingleStyledText('multiple ')
|   \- MixedStyledText(style='strong')
|       |- SingleStyledText('nested ')
|       \- SingleStyledText('styles', style='small caps')
\-- SingleStyledText('.')
```

The visual representation of the words in this paragraph is determined by the applied style sheet. Read more about how this works in the next section.

Besides [SingleStyledText](#) and [MixedStyledText](#) elements (subclasses of [StyledText](#)), paragraphs can also contain [InlineFlowables](#). Currently, the only inline flowable is [InlineImage](#).

The common superclass for flowable and inline elements is [Styled](#), which indicates that these elements can be styled using the style sheets.

5.2 Selectors

Selectors in rinohtml select elements of a particular type. The class of a document element serves as a selector for all instances of the class (and its subclasses). The [Paragraph](#) class is a selector that matches all paragraphs in the document, for example:

```
Paragraph
```

As with [CSS selectors](#), elements can also be matched based on their context. For example, the following matches any paragraph that is a direct child of a list item or in other words, a list item label:

```
ListItem / Paragraph
```

Python's [ellipsis](#) can be used to match any number of levels of elements in the document tree. The following selector matches paragraphs at any level inside a table cell:

```
TableCell / ... / Paragraph
```

To help avoid duplicating selector definitions, context selectors can reference other selectors defined in the same [matcher](#) using [SelectorByName](#):

```
SelectorByName('definition term') / ... / Paragraph
```

Selectors can select all instances of [Styled](#) subclasses. These include [Flowable](#) and [StyledText](#), but also [TableSection](#), [TableRow](#), [Line](#) and [Shape](#). Elements of some of the latter classes only appear as children of other flowables (such as [Table](#)).

Similar to a HTML element's class attribute, [Styled](#) elements can have an optional style attribute which can be used when constructing a selector. This one selects all styled text elements with

the emphasis style, for example:

```
StyledText.like('emphasis')
```

The `Styled.like()` method can also match arbitrary attributes of elements by passing them as keyword arguments. This can be used to do more advanced things such as selecting the background objects on all odd rows of a table, limited to the cells not spanning multiple rows:

```
TableCell.like(row_index=slice(0, None, 2), rowspan=1) / TableCellBackground
```

The argument passed as `row_index` is a slice object that is used for extended indexing². To make this work, `TableCell.row_index` is an object with a custom `__eq__()` that allows comparison to a slice.

Rinohype borrows CSS's concept of [specificity](#) to determine the “winning” selector when multiple selectors match a given document element. Each part of a selector adds to the specificity of a selector. Roughly stated, the more specific selector will win. For example:

```
Listitem / Paragraph # specificity (0, 0, 0, 0, 2)
```

wins over:

```
Paragraph # specificity (0, 0, 0, 0, 1)
```

since it matches two elements instead of just one.

Specificity is represented as a 5-tuple. The last four elements represent the number of location (currently not used), style, attribute and class matches. Here are some selectors along with their specificity:

```
StyledText.like('emphasis') # specificity (0, 0, 1, 0, 1)
TableCell / ... / Paragraph # specificity (0, 0, 0, 0, 2)
TableCell.like(row_index=2, rowspan=1) # specificity (0, 0, 0, 2, 1)
```

Specificity ordering is the same as tuple ordering, so (0, 0, 1, 0, 0) wins over (0, 0, 0, 5, 0) and (0, 0, 0, 0, 3) for example. Only when the number of style matches are equal, the attributes match count is compared and so on.

In practice, the class match count is dependent on the element being matched. If the class of the element exactly matches the selector, the right-most specificity value is increased by 2. If the element's class is a subclass of the selector, it is only increased by 1.

The first element of the specificity tuple is the priority of the selector. For most selectors, the priority will have the default value of 0. The priority of a selector only needs to be set in some cases. For example, we want the `CodeBlock` selector to match a `CodeBlock` instance. However, because `CodeBlock` is a [Paragraph](#) subclass, another selector with a higher specificity will also match it:

```
CodeBlock # specificity (0, 0, 0, 0, 2)
DefinitionList / Definition / Paragraph # specificity (0, 0, 0, 0, 3)
```

To make sure the `CodeBlock` selector wins, we increase the priority of the `CodeBlock` selector by prepending it with a + sign:

```
+CodeBlock # specificity (1, 0, 0, 0, 2)
```

In general, you can use multiple + or - signs to adjust the priority:

```
++CodeBlock # specificity (2, 0, 0, 0, 2)
---CodeBlock # specificity (-3, 0, 0, 0, 2)
```

² Indexing a list like this `lst[slice(0, None, 2)]` is equivalent to `lst[0::2]`.

5.3 Matchers

At the most basic level, a [StyledMatcher](#) is a dictionary that maps labels to selectors:

```
matcher = StyledMatcher()
...
matcher['emphasis'] = StyledText.like('emphasis')
matcher['chapter'] = Section.like(level=1)
matcher['list item number'] = ListItem / Paragraph
matcher['nested line block'] = (GroupedFlowables.like('line block')
                               / GroupedFlowables.like('line block'))
...
```

Rinohype currently includes one matcher which defines labels for all common elements in documents:

```
from rinoh.stylesheets import matcher
```

5.4 Style Sheets

A [StyleSheet](#) takes a [StyledMatcher](#) to provide element labels to assign style properties to:

```
styles = StyleSheet('IEEE', matcher=matcher)
...
styles['strong'] = TextStyle(font_weight=BOLD)
styles['emphasis', font_slant=ITALIC)
styles['nested line block', margin_left=0.5*CM)
...
```

Each [Styled](#) has a [Style](#) class associated with it. For [Paragraph](#), this is [ParagraphStyle](#). These style classes determine which style attributes are accepted for the styled element. Because the style class can automatically be determined from the selector, it is possible to simply pass the style properties to the style sheet by calling the [StyleSheet](#) instance as shown above.

Style sheets are usually loaded from a .rts file using [StyleSheetFile](#). An example style sheet file is shown in [Style Sheets](#).

A style sheet file contains a number of sections, denoted by a section title enclosed in square brackets. There are two special sections:

- [STYLESHEET] describes global style sheet information (see [StyleSheetFile](#) for details)
- [VARIABLES] collects variables that can be referenced elsewhere in the style sheet

Other sections define the style for a document elements. The section titles correspond to the labels associated with selectors in the [StyledMatcher](#). Each entry in a section sets a value for a style attribute. The style for enumerated lists is defined like this, for example:

```
[enumerated list]
margin_left=8pt
space_above=5pt
space_below=5pt
ordered=true
flowable_spacing=5pt
number_format=NUMBER
```



```
label_suffix=') '
```

Since this is an enumerated list, `ordered` is set to `true`. `number_format` and `label_suffix` are set to produce list items labels of the style 1), 2), Other entries control margins and spacing. See [ListStyle](#) for the full list of accepted style attributes.

Todo

base stylesheets are specified by name ... entry points

5.4.1 Base Styles

It is possible to define styles which are not linked to a selector. These can be useful to collect common attributes in a base style for a set of style definitions. For example, the Sphinx style sheet defines the `header_footer` style to serve as a base for the header and footer styles:

```
[header_footer : Paragraph]
base=default
typeface=$(sans_typeface)
font_size=10pt
font_weight=BOLD
indent_first=0pt
tab_stops=50% CENTER, 100% RIGHT

[header]
base=header_footer
padding_bottom=2pt
border_bottom=$(thin_black_stroke)
space_below=24pt

[footer]
base=header_footer
padding_top=4pt
border_top=$(thin_black_stroke)
space_above=18pt
```

Because there is no selector associated with `header_footer`, the element type needs to be specified manually. This is done by adding the name of the relevant [Styled](#) subclass to the section name, using a colon (:) to separate it from the style name, optionally surrounded by spaces.

5.4.2 Custom Selectors

It is also possible to define new selectors directly in a style sheet file. This allows making tweaks to an existing style sheet without having to create a new [StyledMatcher](#). However, this should be used sparingly. If a great number of custom selectors are required, it is better to create a new [StyledMatcher](#).

The syntax for specifying a selector for a style is similar to that when constructing selectors in a Python source code (see [Matchers](#)), but with a number of important differences. A [Styled](#) subclass name followed by parentheses represents a simple class selector (without context). Arguments to be passed to `Styled.like()` can be included within the parentheses.

```
[special text : StyledText('special')]
font_color=#FF00FF

[accept button : InlineImage(filename='images/ok_button.png')]
```

```
baseline=20%
```

Even if no arguments are passed to the class selector, it is important that the class name is followed by parentheses. If the parentheses are omitted, the selector is not registered with the matcher and the style can only be used as a base style for other style definitions (see [Base Styles](#)).

As in Python source code, context selectors are constructed using forward slashes (/) and the ellipsis (...). Another selector can be referenced in a context selector by enclosing its name in single or double quotes.

```
[admonition title colon : Admonition / ... / StyledText('colon')]
font_size=10pt

[chapter title : LabeledFlowable('chapter title')]
label_spacing=1cm
align_baselines=false

[chapter title number : 'chapter title' / Paragraph('number')]
font_size=96pt
text_align=right
```

5.4.3 Variables

Variables can be used for values that are used in multiple style definitions. This example declares a number of typefaces to allow easily replacing the fonts in a style sheet:

```
[VARIABLES]
mono_typeface=TeX Gyre Cursor
serif_typeface=TeX Gyre Pagella
sans_typeface=TeX Gyre Heros
thin_black_stroke=0.5pt, #000
blue=#20435c
```

It also defines the `thin_black_stroke` line style for use in table and frame styles, and a specific color labelled `blue`. These variables can be referenced in style definitions as follows:

```
[code block]
typeface=$(mono_typeface)
font_size=9pt
text_align=LEFT
indent_first=0
space_above=6pt
space_below=4pt
border=$(thin_black_stroke)
padding_left=5pt
padding_top=1pt
padding_bottom=3pt
```

Another stylesheet can inherit (see below) from this one and easily replace fonts in the document by overriding the variables.

5.4.4 Style Attribute Resolution

The style system makes a distinction between text (inline) elements and flowables with respect to how attribute values are resolved.

Text elements by default inherit the properties from their parent. Take for example the emphasis style definition from the example above. The value for style properties other than `font_slant`

(which is defined in the emphasis style itself) will be looked up in the style definition corresponding to the parent element, which can be either another [StyledText](#) instance, or a [Paragraph](#). If the parent element is a [StyledText](#) that neither defines the style attribute, lookup proceeds recursively, moving up in the document tree.

For flowables, there is no fall-back to the parent's style by default. A base style can be specified explicitly however. If a style attribute is not present in a particular style definition, it is looked up in the base style. This can help avoid duplication of style information and the resulting maintenance difficulties. In the following example, the unnumbered heading level 1 style inherits all properties from heading level 1, overriding only the `number_format` attribute:

```
[heading level 1]
typeface=$(sans_typeface)
font_weight=BOLD
font_size=16pt
font_color=$(blue)
line_spacing=SINGLE
space_above=18pt
space_below=12pt
number_format=NUMBER
label_suffix=' '

[unnumbered heading level 1]
base=heading level 1
number_format=None
```

When a value for a particular style attribute is set nowhere in the style definition lookup hierarchy, its default value is returned. The default values for all style properties are defined in the class definition for each of the [Style](#) subclasses.

For text elements, it is possible to override the default behavior of falling back to the parent's style. Setting `base` to the label of a [TextStyle](#) or [ParagraphStyle](#) prevents fallback to the parent element's style.

For flowables, `base` can be set to `PARENT_STYLE` to enable fallback, but this requires that the current element type is the same or a subclass of the parent type, so it cannot be used for all styles.

5.5 Style Logs

When rendering a document, rinohtype will create a style log. It is written to disk using the same base name as the output file, but with a `.stylelog` extension. The information logged in the style log is invaluable when debugging your style sheet. It tells you which style maps to each element in the document.

The style log lists the document elements (as a tree) that have been rendered to each page, and for each element all matching styles are listed together with their specificity. No styles are listed when there aren't any selectors matching an element and the default values are used. The winning style is indicated with a `>` symbol. Styles that are not defined in the style sheet or its base(s) are marked with an `x`. If none of the styles are defined, rinohtype falls back to using the default style.

Here is an example excerpt from a style log:

```
...
Paragraph('January 03, 2012', style='title page date')
  > (0,0,1,0,2) title page date
    (0,0,0,0,2) body
      SingleStyledText('January 03, 2012')
```

```

----- page 3 -----
#### ChainedContainer('column1')
DocumentTree()
  Section(id='structural-elements')                demo.txt:62 <section>
    > (0,0,0,1,2) chapter
    Heading('1 Structural Elements')                demo.txt:62 <title>
      > (0,0,0,1,2) heading level 1
      (0,0,0,0,2) other heading levels
      MixedStyledText('1 Structural Elements')
      SingleStyledText('1')
      MixedStyledText(' ')
      SingleStyledText(' ')
      SingleStyledText('Structural Elements')
    Paragraph('A paragraph.')                      demo.txt:64 <paragraph>
      > (0,0,0,0,2) body
      MixedStyledText('A paragraph.')
      SingleStyledText('A paragraph.')
    List(style='bulleted')                         demo.txt:66 <bullet_list>
      > (0,0,1,0,2) bulleted list
      ListItem()
        x (0,0,1,0,4) bulleted list item
        > fallback to default style
      ListItemLabel('•')
        > (0,0,1,0,6) bulleted list item label
        (0,0,0,0,2) list item label
        MixedStyledText('•')
        SingleStyledText('')
        SingleStyledText('•')
      StaticGroupedFlowables()                    demo.txt:66 <list_item>
        > (0,0,0,0,3) list item body
    ...

```

When it is not possible to achieve a particular document style using one of the existing templates and a custom template configuration, you can create a new template. A new template is programmed in Python and therefore it is required that you are familiar with Python, or at least with general object-oriented programming.

6.1 Subclassing a Template

If you need to customize a template beyond what is possible by configuration, you can subclass a template class and override document part and page templates with custom templates. The following example subclasses [Article](#).

```
from rinoh.attribute import OverrideDefault
from rinoh.template import DocumentPartTemplate, PageTemplate
from rinoh.templates import Article

class BibliographyPartTemplate(DocumentPartTemplate):
    ...

class MyTitlePageTemplate(PageTemplate):
    ...

class MyArticle(Article):
    parts = OverrideDefault(['title', 'contents', 'bibliography'])

    # default document part templates
    bibliography = BibliographyPartTemplate()

    # default page templates
    title_page = MyTitlePageTemplate(base='page')
    bibliography_page = PageTemplate(base='page')
```

`MyArticle` extends the [Article](#) template, adding the extra bibliography document part, along with the page template `bibliography_page`. The new document part is included in `parts`, while also leaving out `front_matter` by default. Finally, the template also replaces the title page template with a custom one.

6.2 Creating a Custom Template

A new template can be created from scratch by subclassing [DocumentTemplate](#), defining all document parts, their templates and page templates.

The [Article](#) and [Book](#) templates are examples of templates that inherit directly from [DocumentTemplate](#). We will briefly discuss the article template. The [Article](#) template overrides the default style sheet and defines the two custom template attributes discussed in [Configuring a Template](#). The document parts [title](#), [front_matter](#) and [contents](#) are listed the in [parts](#) attribute and part templates for each are provided along with page templates:

```
class Article(DocumentTemplate):
    stylesheet = OverrideDefault(sphinx_article)
    table_of_contents = Attribute(Bool, True,
                                  'Show or hide the table of contents')
    abstract_location = Attribute(AbstractLocation, 'front matter',
                                  'Where to place the abstract')

    parts = OverrideDefault(['title', 'front_matter', 'contents'])

    # default document part templates
    title = TitlePartTemplate()
    front_matter = ArticleFrontMatter()
    contents = ContentsPartTemplate()

    # default page templates
    page = PageTemplate(page_size=Var('paper_size'))
    title_page = TitlePageTemplate(base='page',
                                   top_margin=8*CM)
    front_matter_page = PageTemplate(base='page')
    contents_page = PageTemplate(base='page')
```

The custom [ArticleFrontMatter](#) template reads the values for the two custom template attributes defined in [Article](#) to determine which flowables are included in the front matter:

```
class ArticleFrontMatter(DocumentPartTemplate):
    toc_section = TableOfContentsSection()

    def _flowables(self, document):
        meta = document.metadata
        abstract_loc = document.get_option('abstract_location')
        if ('abstract' in meta
            and abstract_loc == AbstractLocation.FRONT_MATTER):
            yield meta['abstract']
        if document.get_option('table_of_contents'):
            yield self.toc_section
```

Have a look at the [Book template source code](#) for an example of a slightly more complex template that defines separate templates for left and right pages.

7.1 rinoh

Render a structured document to PDF.

```
usage: rinoh [-h] [-f FORMAT] [-o OPTION=VALUE] [-t NAME or FILENAME]
             [-s NAME or FILENAME] [-O FILENAME or DIRECTORY] [-p PAPER] [-i]
             [--list-templates] [--list-stylesheets] [--list-fonts]
             [FILENAME]
             [--list-formats] [--list-options FRONTEND] [--version] [--docs]
             [input]
```

input the document to render

-h, --help show this help message and exit

-f <format>, --format <format>

the format of the input file (default: autodetect)

-o <option=value>, --option <option=value>

options to be passed to the input file reader

-t <name or filename>, --template <name or filename>

the document template or template configuration file to use (default: article)

-s <name or filename>, --stylesheet <name or filename>

the style sheet used to style the document elements (default: the template's default)

-O <filename or directory>, --output <filename or directory>

write the PDF output to FILENAME or to an existing DIRECTORY with a filename derived from the input filename (default: the current working directory)

-p <paper>, --paper <paper>

the paper size to render to (default: the template's default)

-i, --install-resources

automatically install missing resources (fonts, templates, style sheets) from PyPI

--list-templates list the installed document templates and exit

--list-stylesheets list the installed style sheets and exit

`--list-fonts <filename>`

list the installed fonts or, if `FILENAME` is given, write a PDF file displaying all the fonts

`--list-formats` list the supported input formats and exit

`--list-options <frontend>`

list the options supported by the given frontend and exit

`--version` show program's version number and exit

`--docs` open the online documentation in the default browser

7.2 Sphinx Builder

`rinoh.frontent.sphinx` is a Sphinx extension module. It provides a Sphinx builder with the name `rinoh`. The builder recognizes the following `conf.py` options. Of these, only `rinoh_documents` (or `latex_documents`) is required.

`rinoh_documents` Determines which PDF documents to build. Its format is a list of dictionaries, one for each document to be generated. Supported keys are:

doc (required) String that specifies the name of the master document (typically `index`).

target (required) The name of the target PDF file without the extension.

title (required) The title of the document.

author (required) The author of the document.

toctree_only (default: False) Must be `True` or `False`. If `true`, the document itself is not included in the output, only the documents referenced by it via TOC trees.

logo (default: None) Path (relative to the configuration directory) to an image file to use at the top of the title page.

domain_indices (default: True) If `true`, generate domain-specific indices in addition to the general index. It is equivalent to the `html_domain_indices` and `latex_domain_indices` configuration variables.

template (default: `Book`) Determines the template used to render the document. It takes:

- the filename of a [template configuration file](#),
- a `TemplateConfiguration` instance,
- the name of an installed template (see [rinoh --list-templates](#))
- a `DocumentTemplate` subclass

`rinoh_template` This configuration variable is no longer supported since the document template can be specified in `rinoh_documents`.

`rinoh_stylesheet` This configuration variable is no longer supported since it was not obvious which style sheet was being used when the template configuration (`rinoh_template`) also specified a style sheet. Please specify the style sheet to use in your [template configuration file](#):


```
[TEMPLATE_CONFIGURATION]
name = My Book
template = book
stylesheet = my_stylesheet.rts
```

Note

For some of the configuration variables listed below, rinohtype used to fall back to the corresponding variable for the LaTeX builder. This behavior was removed to make the configuration more transparent. Make sure to set the rino variables if you relied on this.

rino_paper_size This configuration variable is no longer supported since it was not obvious which paper size was being used when the template configuration (**rino_template**) also specified a paper size. Please specify the **paper_size** to use in your [template configuration file](#):

```
[TEMPLATE_CONFIGURATION]
name = My Book
template = book

[VARIABLES]
paper_size = A5
```

rino_logo This configuration variable is no longer supported since the logo can be specified in the [rino_documents](#).

rino_domain_indices

This configuration variable is no longer supported since the **domain_indices** can be specified in the [rino_documents](#).

rino_metadata A dictionary instance that provides additional configuration values to the document template, typically used on the title page and in page headers and footers (depending on the template and its configuration). The values supplied can be plain text or [StyledText](#). They are normally derived from other Sphinx configuration variables, but it can be useful to override them for PDF output. Supported keys:

title Overrides [project](#)

subtitle Overrides the default Sphinx subtitle containing the project's [release](#) string

author Overrides author

date Overrides the default date determined from [today](#) and [today_fmt](#)

7.3 Style Sheets

7.3.1 Included Style Sheets

These style sheets are included with rinohtype:

rino.stylesheets.sphinx

Mostly a copy of the LaTeX style included with Sphinx

Entry point name: sphinx

`rinoh.stylesheets.sphinx_article`

The Sphinx stylesheet adjusted for the article template

Entry point name: `sphinx_article`

`rinoh.stylesheets.sphinx_base14`

The Sphinx stylesheet, but using the fonts from the PDF core set (yielding smaller PDF files)

Entry point name: `sphinx_base14`

Additional style sheets can be installed from PyPI. The installed style sheets can be listed using `rinoh --list-stylesheets`.

7.3.2 Default Matcher

The default matcher provides the selectors for the styles used in the standard style sheets.

`rinoh.stylesheets.matcher`

The default matcher defines the following styles

- title page rule: `HorizontalRuleStyle`
- title page logo: `FlowableStyle`
- title page title: `ParagraphStyle`
- title page subtitle: `ParagraphStyle`
- title page author: `ParagraphStyle`
- title page date: `ParagraphStyle`
- title page extra: `ParagraphStyle`
- front matter section title: `ParagraphStyle`
- body matter chapter label: `ParagraphStyle`
- body matter chapter number: `TextStyle`
- body matter chapter title: `ParagraphStyle`
- fallback: `TextStyle`
- italic: `TextStyle`
- bold: `TextStyle`
- monospaced: `TextStyle`
- emphasis: `TextStyle`
- strong: `TextStyle`
- literal emphasis: `TextStyle`
- literal strong: `TextStyle`
- inline math: `TextStyle`
- quote: `TextStyle`

- file path: [TextStyle](#)
- keystrokes: [TextStyle](#)
- regular expression: [TextStyle](#)
- code with variable: [TextStyle](#)
- mail header: [TextStyle](#)
- MIME type: [TextStyle](#)
- newsgroup: [TextStyle](#)
- command: [TextStyle](#)
- make variable: [TextStyle](#)
- program: [TextStyle](#)
- man page: [TextStyle](#)
- window title: [TextStyle](#)
- UI control: [TextStyle](#)
- UI control accelerator: [TextStyle](#)
- menu cascade: [TextStyle](#)
- draft comment: [TextStyle](#)
- title reference: [TextStyle](#)
- error: [TextStyle](#)
- linked reference: [TextStyle](#)
- unlinked reference: [TextStyle](#)
- internal hyperlink: [TextStyle](#)
- external hyperlink: [TextStyle](#)
- broken hyperlink: [TextStyle](#)
- glossary inline definition: [TextStyle](#)
- body: [ParagraphStyle](#)
- code block: [ParagraphStyle](#)
- code block caption: [CaptionStyle](#)
- math block: [ParagraphStyle](#)
- attribution: [ParagraphStyle](#)
- centered: [ParagraphStyle](#)
- line block: [ParagraphStyle](#)
- block quote: [GroupedFlowablesStyle](#)

- chapter: [SectionStyle](#)
- heading level 1: [HeadingStyle](#)
- unnumbered heading level 1: [HeadingStyle](#)
- heading level 2: [HeadingStyle](#)
- unnumbered heading level 2: [HeadingStyle](#)
- heading level 3: [HeadingStyle](#)
- unnumbered heading level 3: [HeadingStyle](#)
- heading level 4: [HeadingStyle](#)
- unnumbered heading level 4: [HeadingStyle](#)
- heading level 5: [HeadingStyle](#)
- unnumbered heading level 5: [HeadingStyle](#)
- other heading levels: [HeadingStyle](#)
- appendix: [SectionStyle](#)
- appendix heading level 1: [HeadingStyle](#)
- appendix heading level 2: [HeadingStyle](#)
- appendix heading level 3: [HeadingStyle](#)
- appendix heading level 4: [HeadingStyle](#)
- appendix heading level 5: [HeadingStyle](#)
- title: [ParagraphStyle](#)
- prerequisites: [GroupedFlowablesStyle](#)
- prerequisites title: [ParagraphStyle](#)
- post requirement: [GroupedFlowablesStyle](#)
- abstract: [GroupedFlowablesStyle](#)
- abstract paragraph: [ParagraphStyle](#)
- example: [GroupedFlowablesStyle](#)
- example title: [ParagraphStyle](#)
- topic: [GroupedFlowablesStyle](#)
- topic title: [ParagraphStyle](#)
- rubric: [ParagraphStyle](#)
- sidebar: [GroupedFlowablesStyle](#)
- sidebar title: [ParagraphStyle](#)
- sidebar subtitle: [ParagraphStyle](#)

- list item label: [ListItemLabelStyle](#)
- list item body: [GroupedFlowablesStyle](#)
- list item paragraph: [ParagraphStyle](#)
- enumerated list: [ListStyle](#)
- enumerated list item: [LabeledFlowableStyle](#)
- enumerated list item label: [ListItemLabelStyle](#)
- nested enumerated list: [ListStyle](#)
- (table) enumerated list: [ListStyle](#)
- (table) enumerated list item: [LabeledFlowableStyle](#)
- (table) enumerated list item label: [ListItemLabelStyle](#)
- bulleted list: [ListStyle](#)
- compact bulleted list: [ListStyle](#)
- bulleted list item: [LabeledFlowableStyle](#)
- bulleted list item label: [ListItemLabelStyle](#)
- nested bulleted list: [ListStyle](#)
- (table) bulleted list: [ListStyle](#)
- (table) bulleted list item: [LabeledFlowableStyle](#)
- (table) bulleted list item label: [ListItemLabelStyle](#)
- steps list: [ListStyle](#)
- steps list title: [ParagraphStyle](#)
- steps list item: [LabeledFlowableStyle](#)
- steps list item label: [ListItemLabelStyle](#)
- unordered steps list: [ListStyle](#)
- unordered steps list title: [ParagraphStyle](#)
- unordered steps list item: [LabeledFlowableStyle](#)
- unordered steps list item label: [ListItemLabelStyle](#)
- choices list: [ListStyle](#)
- choices list item: [LabeledFlowableStyle](#)
- choices list item label: [ListItemLabelStyle](#)
- definition list: [GroupedFlowablesStyle](#)
- definition list item: [LabeledFlowableStyle](#)
- definition term: [GroupedFlowablesStyle](#)

- definition term paragraph: [ParagraphStyle](#)
- definition term classifier: [TextStyle](#)
- definition: [GroupedFlowablesStyle](#)
- definition paragraph: [ParagraphStyle](#)
- related links: [GroupedFlowablesStyle](#)
- related links section title: [ParagraphStyle](#)
- related links list: [ListStyle](#)
- related links list item: [LabeledFlowableStyle](#)
- related links list item label: [ListItemLabelStyle](#)
- related links list item paragraph: [ReferencingParagraphStyle](#)
- related link title reference: [TextStyle](#)
- related link page reference: [TextStyle](#)
- related link number reference: [TextStyle](#)
- related link reference: [TextStyle](#)
- versionmodified: [TextStyle](#)
- object description: [LabeledFlowableStyle](#)
- object signatures: [GroupedFlowablesStyle](#)
- object signature: [ParagraphStyle](#)
- object name: [TextStyle](#)
- additional name part: [TextStyle](#)
- object type: [TextStyle](#)
- object returns: [TextStyle](#)
- object parentheses: [TextStyle](#)
- object parameter list: [TextStyle](#)
- object parameter: [TextStyle](#)
- object parameter (no emphasis): [TextStyle](#)
- object brackets: [TextStyle](#)
- object optional parameter: [TextStyle](#)
- object annotation: [TextStyle](#)
- object description content: [GroupedFlowablesStyle](#)
- object description content paragraph: [ParagraphStyle](#)
- production list: [GroupedFlowablesStyle](#)

- production: [LabeledFlowableStyle](#)
- token name: [ParagraphStyle](#)
- token definition: [ParagraphStyle](#)
- field list: [GroupedFlowablesStyle](#)
- field list item: [LabeledFlowableStyle](#)
- field name: [ParagraphStyle](#)
- option list: [GroupedFlowablesStyle](#)
- option list item: [LabeledFlowableStyle](#)
- option: [ParagraphStyle](#)
- option string: [TextStyle](#)
- option argument: [TextStyle](#)
- admonition: [AdmonitionStyle](#)
- admonition title: [ParagraphStyle](#)
- admonition inline title: [TextStyle](#)
- attention admonition: [AdmonitionStyle](#)
- attention admonition title: [ParagraphStyle](#)
- attention admonition inline title: [TextStyle](#)
- caution admonition: [AdmonitionStyle](#)
- caution admonition title: [ParagraphStyle](#)
- caution admonition inline title: [TextStyle](#)
- danger admonition: [AdmonitionStyle](#)
- danger admonition title: [ParagraphStyle](#)
- danger admonition inline title: [TextStyle](#)
- error admonition: [AdmonitionStyle](#)
- error admonition title: [ParagraphStyle](#)
- error admonition inline title: [TextStyle](#)
- hint admonition: [AdmonitionStyle](#)
- hint admonition title: [ParagraphStyle](#)
- hint admonition inline title: [TextStyle](#)
- important admonition: [AdmonitionStyle](#)
- important admonition title: [ParagraphStyle](#)
- important admonition inline title: [TextStyle](#)

- note admonition: [AdmonitionStyle](#)
- note admonition title: [ParagraphStyle](#)
- note admonition inline title: [TextStyle](#)
- tip admonition: [AdmonitionStyle](#)
- tip admonition title: [ParagraphStyle](#)
- tip admonition inline title: [TextStyle](#)
- warning admonition: [AdmonitionStyle](#)
- warning admonition title: [ParagraphStyle](#)
- warning admonition inline title: [TextStyle](#)
- seealso admonition: [AdmonitionStyle](#)
- seealso admonition title: [ParagraphStyle](#)
- seealso admonition inline title: [TextStyle](#)
- header: [ParagraphStyle](#)
- footer: [ParagraphStyle](#)
- footnote marker: [NoteMarkerStyle](#)
- citation marker: [NoteMarkerStyle](#)
- footnote paragraph: [ParagraphStyle](#)
- footnote label: [ParagraphStyle](#)
- image: [FlowableStyle](#)
- inline image: [InlineFlowableStyle](#)
- figure: [FigureStyle](#)
- figure image: [FlowableStyle](#)
- figure caption: [CaptionStyle](#)
- figure legend: [GroupedFlowablesStyle](#)
- figure legend paragraph: [ParagraphStyle](#)
- table of contents section: [SectionStyle](#)
- table of contents title: [HeadingStyle](#)
- table of contents: [TableOfContentsStyle](#)
- local table of contents: [TableOfContentsStyle](#)
- toc level 1: [TableOfContentsEntryStyle](#)
- toc level 2: [TableOfContentsEntryStyle](#)
- toc level 3: [TableOfContentsEntryStyle](#)

- L3 toc level 3: [TableOfContentsEntryStyle](#)
- toc linked reference: [TextStyle](#)
- list of figures section: [SectionStyle](#)
- list of figures: [ListOfStyle](#)
- list of figures entry: [ListOfEntryStyle](#)
- list of tables section: [SectionStyle](#)
- list of tables: [ListOfStyle](#)
- list of tables entry: [ListOfEntryStyle](#)
- table: [TableStyle](#)
- table with caption: [TableWithCaptionStyle](#)
- table caption: [CaptionStyle](#)
- choices table: [TableStyle](#)
- table cell: [TableCellStyle](#)
- table body cell background on even row: [TableCellBackgroundStyle](#)
- table body cell background on odd row: [TableCellBackgroundStyle](#)
- table body cell paragraph: [ParagraphStyle](#)
- table first column paragraph: [ParagraphStyle](#)
- table body cell list item number: [ParagraphStyle](#)
- table head cell: [TableCellStyle](#)
- table head cell paragraph: [ParagraphStyle](#)
- table cell left border: [TableCellBorderStyle](#)
- table cell top border: [TableCellBorderStyle](#)
- table cell right border: [TableCellBorderStyle](#)
- table cell bottom border: [TableCellBorderStyle](#)
- table top border: [TableCellBorderStyle](#)
- table bottom border: [TableCellBorderStyle](#)
- table left border: [TableCellBorderStyle](#)
- table right border: [TableCellBorderStyle](#)
- table head cell left border: [TableCellBorderStyle](#)
- table head cell right border: [TableCellBorderStyle](#)
- table head bottom border: [TableCellBorderStyle](#)
- table head left border: [TableCellBorderStyle](#)

- table head right border: [TableCellBorderStyle](#)
- table body top border: [TableCellBorderStyle](#)
- table body left border: [TableCellBorderStyle](#)
- table body right border: [TableCellBorderStyle](#)
- horizontal rule: [HorizontalRuleStyle](#)
- index: [IndexStyle](#)
- index section label: [ParagraphStyle](#)
- level 1 index entry: [ParagraphStyle](#)
- level 2 index entry: [ParagraphStyle](#)
- level 3 index entry: [ParagraphStyle](#)
- level 4 index entry: [ParagraphStyle](#)
- domain index entry name: [TextStyle](#)

7.3.3 Element Style Classes

These are the style classes corresponding to each type of document element. For each style class, the supported style attributes are listed along with the values that can be assigned to them in a style sheet.

draw.LineStyle	Style class for Line
draw.ShapeStyle	Style class for Shape
flowable.FlowableStyle	Style class for Flowable
flowable.LabeledFlowableStyle	Style class for LabeledFlowable
flowable.GrouppedFlowablesStyle	Style class for GrouppedFlowables
flowable.FloatStyle	Style class for Float
image.CaptionStyle	Style class for Caption
image.FigureStyle	Style class for Figure
index.IndexStyle	Style class for Index
paragraph.ParagraphStyle	Style class for Paragraph
text.TextStyle	Style class for Text
inline.InlineFlowableStyle	Style class for InlineFlowable
reference.ReferencingParagraphStyle	Style class for ReferencingParagraph
reference.NoteMarkerStyle	Style class for NoteMarker
structure.SectionStyle	Style class for Section
structure.HeadingStyle	Style class for Heading
structure.ListStyle	Style class for List
structure.ListItemLabelStyle	Style class for ListItemLabel
structure.TableOfContentsStyle	Style class for TableOfContents
structure.TableOfContentsEntryStyle	Style class for TableOfContentsEntry
structure.AdmonitionStyle	Style class for Admonition
structure.HorizontalRuleStyle	Style class for HorizontalRule
table.TableStyle	Style class for Table

<code>table.TableCellStyle</code>	Style class for <code>TableCell</code>
<code>table.TableCellStyle</code>	Style class for <code>TableCellBorder</code>
<code>table.TableCellStyle</code>	Style class for <code>TableCellBackground</code>

LineStyle

```
class rinoh.draw.LineStyle ( base=None, **attributes )
```

Style class for `Line`

stroke Width and color used to draw the line

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: 1pt, #000

hide Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

ShapeStyle

```
class rinoh.draw.ShapeStyle ( base=None, **attributes )
```

Style class for `Shape`

fill_color Color to fill the shape

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #e5e5e5

stroke Width and color used to draw the line (inherited from `LineStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: 1pt, #000

hide Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

FlowableStyle

```
class rinoh.flowable.FlowableStyle ( base=None, **attributes )
```

Style class for `Flowable`

width Width to render the flowable at

Accepts `FlowableWidth`: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: auto

horizontal_align Horizontal alignment of the flowable

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above Vertical space preceding the flowable

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below Vertical space following the flowable

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

margin_left Left margin

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

margin_right Right margin

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding Padding

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_left Left padding

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_right Right padding

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_top Top padding

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_bottom Bottom padding

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

keep_with_next Keep this flowable and the next on the same page

Accepts **Bool**: true or false
 Default: false

border Border surrounding the flowable

Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)
 Default: none

border_left Border left of the flowable

Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)
 Default: none

border_right Border right of the flowable

Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the

stroke, separated by a comma (,)
 Default: none

border_top Border above the flowable
 Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)
 Default: none

border_bottom Border below the flowable
 Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)
 Default: none

background_color
 Color of the area within the flowable's borders
 Accepts **Color**: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: none

page_break Type of page break to insert before rendering this flowable
 Accepts **Break**: none, any, left, right
 Default: None

hide Suppress rendering this element (inherited from **Style**)
 Accepts **Bool**: true or false
 Default: false

LabeledFlowableStyle

```
class rinoh.flowable.LabeledFlowableStyle ( base=None, **attributes )
```

Style class for **LabeledFlowable**

label_min_width Minimum label width
 Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 12pt

label_max_width Maximum label width
 Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 80pt

label_spacing Spacing between a label and the labeled flowable
 Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 3pt

align_baselines Line up the baselines of the label and the labeled flowable
 Accepts **Bool**: true or false
 Default: true

wrap_label Wrap the label at label_max_width
 Accepts **Bool**: true or false
 Default: false

width Width to render the flowable at (inherited from [FlowableStyle](#))

Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: auto

horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))

Accepts [HorizontalAlignment](#): left, right, center

Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below Vertical space following the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left Left margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right Right margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding Padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left Left padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_right Right padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt,

in, pc, mm, cm, %, /4)
Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))
Accepts [Bool](#): true or false
Default: false

border Border surrounding the flowable (inherited from [FlowableStyle](#))
Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
Default: none

border_left Border left of the flowable (inherited from [FlowableStyle](#))
Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
Default: none

border_right Border right of the flowable (inherited from [FlowableStyle](#))
Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
Default: none

border_top Border above the flowable (inherited from [FlowableStyle](#))
Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
Default: none

border_bottom Border below the flowable (inherited from [FlowableStyle](#))
Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
Default: none

background_color
Color of the area within the flowable's borders (inherited from [FlowableStyle](#))
Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
Default: none

page_break Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))
Accepts [Break](#): none, any, left, right
Default: None

hide Suppress rendering this element (inherited from [Style](#))
Accepts [Bool](#): true or false
Default: false

GroupedFlowablesStyle

```
class rinoh.flowable.GroupedFlowablesStyle ( base=None, **attributes )
```

Style class for [GroupedFlowables](#)
width Overrides the default set in [FlowableStyle](#)

Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: fill

title Title to precede the flowables

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing Spacing between flowables

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))

Accepts [HorizontalAlignment](#): left, right, center

Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below Vertical space following the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left Left margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right Right margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding Padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left Left padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_right Right padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))

Accepts [Bool](#): true or false

Default: false

border Border surrounding the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_left Border left of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_right Border right of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_top Border above the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_bottom Border below the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from [FlowableStyle](#))

Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))

Accepts [Break](#): none, any, left, right

Default: None

hide Suppress rendering this element (inherited from [Style](#))

Accepts **Bool**: true or false

Default: false

FloatStyle

class rinoh.flowable.FloatStyle (base=None, **attributes)

Style class for **Float**

float Float the flowable to the top or bottom of the page

Accepts **Bool**: true or false

Default: false

width Width to render the flowable at (inherited from **FlowableStyle**)

Accepts **FlowableWidth**: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: auto

horizontal_align Horizontal alignment of the flowable (inherited from **FlowableStyle**)

Accepts **HorizontalAlignment**: left, right, center

Default: left

space_above Vertical space preceding the flowable (inherited from **FlowableStyle**)

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below Vertical space following the flowable (inherited from **FlowableStyle**)

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left Left margin (inherited from **FlowableStyle**)

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right Right margin (inherited from **FlowableStyle**)

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding Padding (inherited from **FlowableStyle**)

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left Left padding (inherited from **FlowableStyle**)

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_right Right padding (inherited from **FlowableStyle**)

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_top Top padding (inherited from **FlowableStyle**)
 Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_bottom Bottom padding (inherited from **FlowableStyle**)
 Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from **FlowableStyle**)
 Accepts **Bool**: true or false
 Default: false

border Border surrounding the flowable (inherited from **FlowableStyle**)
 Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)
 Default: none

border_left Border left of the flowable (inherited from **FlowableStyle**)
 Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)
 Default: none

border_right Border right of the flowable (inherited from **FlowableStyle**)
 Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)
 Default: none

border_top Border above the flowable (inherited from **FlowableStyle**)
 Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)
 Default: none

border_bottom Border below the flowable (inherited from **FlowableStyle**)
 Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)
 Default: none

background_color
 Color of the area within the flowable's borders (inherited from **FlowableStyle**)
 Accepts **Color**: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: none

page_break Type of page break to insert before rendering this flowable (inherited from **FlowableStyle**)
 Accepts **Break**: none, any, left, right

Default: None

hide Suppress rendering this element (inherited from [Style](#))

Accepts [Bool](#): true or false

Default: false

CaptionStyle

```
class rinoh.image.CaptionStyle ( base=None, **attributes )
```

Style class for [Caption](#)

numbering_level At which section level to restart numbering

Accepts [Integer](#): a natural number (positive integer)

Default: 1

number_separator

Characters inserted between the section number and the caption number

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: '.'

width Width to render the flowable at (inherited from [ParagraphStyle](#))

Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: fill

indent_first Indentation of the first line of text (inherited from [ParagraphStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0pt

line_spacing Spacing between the baselines of two successive lines of text (inherited from [ParagraphStyle](#))

Accepts [LineSpacing](#): a [predefined line spacing](#) type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

text_align Alignment of text to the margins (inherited from [ParagraphStyle](#))

Accepts [TextAlign](#): left, right, center, justify

Default: justify

tab_stops List of tab positions (inherited from [ParagraphStyle](#))

Accepts [TabStopList](#): a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position ([Dimension](#)) is required and align ([TabAlign](#)) and fill string (string enclosed in quotes) are optional.

Default: (no value)

horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))

Accepts [HorizontalAlignment](#): left, right, center

Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below Vertical space following the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left Left margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right Right margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding Padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left Left padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_right Right padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))

Accepts [Bool](#): true or false

Default: false

border Border surrounding the flowable (inherited from [FlowableStyle](#))

Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)
 Default: none

border_left Border left of the flowable (inherited from **FlowableStyle**)
 Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)
 Default: none

border_right Border right of the flowable (inherited from **FlowableStyle**)
 Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)
 Default: none

border_top Border above the flowable (inherited from **FlowableStyle**)
 Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)
 Default: none

border_bottom Border below the flowable (inherited from **FlowableStyle**)
 Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)
 Default: none

background_color
 Color of the area within the flowable's borders (inherited from **FlowableStyle**)
 Accepts **Color**: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: none

page_break Type of page break to insert before rendering this flowable (inherited from **FlowableStyle**)
 Accepts **Break**: none, any, left, right
 Default: None

typeface Typeface to set the text in (inherited from **TextStyle**)
 Accepts **Typeface**: the name of a typeface. See **rinoh --list-fonts** for a list of the available typefaces.
 Default: Times

font_weight Thickness of character outlines relative to their height (inherited from **TextStyle**)
 Accepts **FontWeight**: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black
 Default: 500

font_slant Slope style of the font (inherited from **TextStyle**)
 Accepts **FontSlant**: upright, oblique, italic
 Default: upright

font_width Stretch of the characters (inherited from **TextStyle**)
 Accepts **FontWidth**: ultra-condensed, extra-condensed,

condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size Height of characters (inherited from [TextStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 10pt

font_color Color of the font (inherited from [TextStyle](#))

Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant Variant of the font (inherited from [TextStyle](#))

Accepts [FontVariant](#): normal, small capital, oldstyle figures

Default: normal

position Vertical text position (inherited from [TextStyle](#))

Accepts [TextPosition](#): normal, superscript, subscript

Default: normal

kerning Improve inter-letter spacing (inherited from [TextStyle](#))

Accepts [Bool](#): true or false

Default: true

ligatures Run letters together where possible (inherited from [TextStyle](#))

Accepts [Bool](#): true or false

Default: true

hyphenate Allow words to be broken over two lines (inherited from [TextStyle](#))

Accepts [Bool](#): true or false

Default: true

hyphen_chars Minimum number of characters in a hyphenated part of a word (inherited from [TextStyle](#))

Accepts [Integer](#): a natural number (positive integer)

Default: 2

hyphen_lang Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from [TextStyle](#))

Accepts [Locale](#): locale identifier in the <language ID>_<region ID> format

Default: en_US

before Item to insert before this one (inherited from [InlineStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or '), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after Item to insert after this one (inherited from [InlineStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or '), optionally followed by a style

name enclosed in braces: 'text string' (style name)

Default: (no value)

number_format How numbers are formatted (inherited from [NumberStyle](#))

Accepts [NumberFormat](#): none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: number

label_prefix Text to prepend to the label (inherited from [LabelStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix Text to append to the label (inherited from [LabelStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label Use a custom label if specified (inherited from [LabelStyle](#))

Accepts [Bool](#): true or false

Default: false

hide Suppress rendering this element (inherited from [Style](#))

Accepts [Bool](#): true or false

Default: false

FigureStyle

```
class rinoh.image.FigureStyle ( base=None, **attributes )
```

Style class for [Figure](#)

float Float the flowable to the top or bottom of the page (inherited from [FloatStyle](#))

Accepts [Bool](#): true or false

Default: false

width Width to render the flowable at (inherited from [FlowableStyle](#))

Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: auto

horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))

Accepts [HorizontalAlignment](#): left, right, center

Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below Vertical space following the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left Left margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right Right margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding Padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left Left padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_right Right padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))

Accepts [Bool](#): true or false

Default: false

border Border surrounding the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_left Border left of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

`border_right` Border right of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

`border_top` Border above the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

`border_bottom` Border below the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

`background_color`

Color of the area within the flowable's borders (inherited from [FlowableStyle](#))

Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

`page_break` Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))

Accepts [Break](#): none, any, left, right

Default: None

`hide` Suppress rendering this element (inherited from [Style](#))

Accepts [Bool](#): true or false

Default: false

`title` Title to precede the flowables (inherited from [GroupedFlowablesStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or '), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

`flowable_spacing` Spacing between flowables (inherited from [GroupedFlowablesStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

IndexStyle

```
class rinoh.index.IndexStyle ( base=None, **attributes )
```

Style class for [Index](#)

`initials` Group index entries based on their first letter

Accepts [Bool](#): true or false

Default: true

`width` Width to render the flowable at (inherited from [GroupedFlowablesStyle](#))

Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: fill

title Title to precede the flowables (inherited from [GroupedFlowablesStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing Spacing between flowables (inherited from [GroupedFlowablesStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))

Accepts [HorizontalAlignment](#): left, right, center

Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below Vertical space following the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left Left margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right Right margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding Padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left Left padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_right Right padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in,

pc, mm, cm, %, /4)
Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))
Accepts [Bool](#): true or false
Default: false

border Border surrounding the flowable (inherited from [FlowableStyle](#))
Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
Default: none

border_left Border left of the flowable (inherited from [FlowableStyle](#))
Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
Default: none

border_right Border right of the flowable (inherited from [FlowableStyle](#))
Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
Default: none

border_top Border above the flowable (inherited from [FlowableStyle](#))
Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
Default: none

border_bottom Border below the flowable (inherited from [FlowableStyle](#))
Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
Default: none

background_color
Color of the area within the flowable's borders (inherited from [FlowableStyle](#))
Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
Default: none

page_break Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))
Accepts [Break](#): none, any, left, right
Default: None

hide Suppress rendering this element (inherited from [Style](#))

Accepts [Bool](#): true or false

Default: false

ParagraphStyle

class rinoh.paragraph.ParagraphStyle (base=None, **attributes)

Style class for [Paragraph](#)

width Overrides the default set in [FlowableStyle](#)

Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: fill

indent_first Indentation of the first line of text

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0pt

line_spacing Spacing between the baselines of two successive lines of text

Accepts [LineSpacing](#): a [predefined line spacing](#) type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

text_align Alignment of text to the margins

Accepts [TextAlign](#): left, right, center, justify

Default: justify

tab_stops List of tab positions

Accepts [TabStopList](#): a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position ([Dimension](#)) is required and align ([TabAlign](#)) and fill string (string enclosed in quotes) are optional.

Default: (no value)

horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))

Accepts [HorizontalAlignment](#): left, right, center

Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below Vertical space following the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left Left margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in,

pc, mm, cm, %, /4)
Default: 0

margin_right Right margin (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

padding Padding (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

padding_left Left padding (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

padding_right Right padding (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))
Accepts [Bool](#): true or false
Default: false

border Border surrounding the flowable (inherited from [FlowableStyle](#))
Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
Default: none

border_left Border left of the flowable (inherited from [FlowableStyle](#))
Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
Default: none

border_right Border right of the flowable (inherited from [FlowableStyle](#))
Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
Default: none

border_top Border above the flowable (inherited from [FlowableStyle](#))
Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the

stroke, separated by a comma (,)
 Default: none

border_bottom Border below the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

background_color
 Color of the area within the flowable's borders (inherited from [FlowableStyle](#))
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: none

page_break Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))
 Accepts Break: none, any, left, right
 Default: None

hide Suppress rendering this element (inherited from [Style](#))
 Accepts [Bool](#): true or false
 Default: false

typeface Typeface to set the text in (inherited from [TextStyle](#))
 Accepts [Typeface](#): the name of a typeface. See [rinoh --list-fonts](#) for a list of the available typefaces.
 Default: Times

font_weight Thickness of character outlines relative to their height (inherited from [TextStyle](#))
 Accepts [FontWeight](#): hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black
 Default: 500

font_slant Slope style of the font (inherited from [TextStyle](#))
 Accepts [FontSlant](#): upright, oblique, italic
 Default: upright

font_width Stretch of the characters (inherited from [TextStyle](#))
 Accepts [FontWidth](#): ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded
 Default: 5

font_size Height of characters (inherited from [TextStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 10pt

font_color Color of the font (inherited from [TextStyle](#))
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant Variant of the font (inherited from [TextStyle](#))
 Accepts [FontVariant](#): normal, small capital, oldstyle figures
 Default: normal

position Vertical text position (inherited from [TextStyle](#))
 Accepts [TextPosition](#): normal, superscript, subscript
 Default: normal

kerning Improve inter-letter spacing (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true

ligatures Run letters together where possible (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true

hyphenate Allow words to be broken over two lines (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true

hyphen_chars Minimum number of characters in a hyphenated part of a word (inherited from [TextStyle](#))
 Accepts [Integer](#): a natural number (positive integer)
 Default: 2

hyphen_lang Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from [TextStyle](#))
 Accepts [Locale](#): locale identifier in the <language ID>_<region ID> format
 Default: en_US

before Item to insert before this one (inherited from [InlineStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

after Item to insert after this one (inherited from [InlineStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

TextStyle

```
class rinoh.text.TextStyle ( base=None, **attributes )
```

Style class for Text

typeface Typeface to set the text in
 Accepts [Typeface](#): the name of a typeface. See [rinoh --list-fonts](#) for a list of the available typefaces.
 Default: Times

`font_weight` Thickness of character outlines relative to their height
 Accepts `FontWeight`: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black
 Default: 500

`font_slant` Slope style of the font
 Accepts `FontSlant`: upright, oblique, italic
 Default: upright

`font_width` Stretch of the characters
 Accepts `FontWidth`: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded
 Default: 5

`font_size` Height of characters
 Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 10pt

`font_color` Color of the font
 Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: #000

`font_variant` Variant of the font
 Accepts `FontVariant`: normal, small capital, oldstyle figures
 Default: normal

`position` Vertical text position
 Accepts `TextPosition`: normal, superscript, subscript
 Default: normal

`kerning` Improve inter-letter spacing
 Accepts `Bool`: true or false
 Default: true

`ligatures` Run letters together where possible
 Accepts `Bool`: true or false
 Default: true

`hyphenate` Allow words to be broken over two lines
 Accepts `Bool`: true or false
 Default: true

`hyphen_chars` Minimum number of characters in a hyphenated part of a word
 Accepts `Integer`: a natural number (positive integer)
 Default: 2

`hyphen_lang` Language to use for hyphenation. Accepts locale codes such as 'en_US'
 Accepts `Locale`: locale identifier in the <language ID>_<region>

ID> format

Default: en_US

before Item to insert before this one (inherited from [InlineStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after Item to insert after this one (inherited from [InlineStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

hide Suppress rendering this element (inherited from [Style](#))

Accepts [Bool](#): true or false

Default: false

InlineFlowableStyle

class rinoh.inline.InlineFlowableStyle (base=None, **attributes)

Style class for [InlineFlowable](#)

baseline The location of the flowable's baseline relative to the bottom edge

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0pt

width Width to render the flowable at (inherited from [FlowableStyle](#))

Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: auto

horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))

Accepts [HorizontalAlignment](#): left, right, center

Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below Vertical space following the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left Left margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

`margin_right` Right margin (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

`padding` Padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

`padding_left` Left padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

`padding_right` Right padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

`padding_top` Top padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

`padding_bottom` Bottom padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

`keep_with_next` Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))
 Accepts [Bool](#): true or false
 Default: false

`border` Border surrounding the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`border_left` Border left of the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`border_right` Border right of the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`border_top` Border above the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_bottom Border below the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

background_color
 Color of the area within the flowable's borders (inherited from [FlowableStyle](#))
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: none

page_break Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))
 Accepts [Break](#): none, any, left, right
 Default: None

hide Suppress rendering this element (inherited from [Style](#))
 Accepts [Bool](#): true or false
 Default: false

before Item to insert before this one (inherited from [InlineStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

after Item to insert after this one (inherited from [InlineStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

ReferencingParagraphStyle

class rinoh.reference.ReferencingParagraphStyle (base=None, **attributes)

Style class for [ReferencingParagraph](#)

text The text content of this paragraph

Accepts [ReferenceText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: '{TITLE}'

width Width to render the flowable at (inherited from [ParagraphStyle](#))

Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: fill

indent_first Indentation of the first line of text (inherited from [ParagraphStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0pt

line_spacing Spacing between the baselines of two successive lines of text (inherited from [ParagraphStyle](#))

Accepts [LineSpacing](#): a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

text_align Alignment of text to the margins (inherited from [ParagraphStyle](#))

Accepts [TextAlign](#): left, right, center, justify

Default: justify

tab_stops List of tab positions (inherited from [ParagraphStyle](#))

Accepts [TabStopList](#): a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position ([Dimension](#)) is required and align ([TabAlign](#)) and fill string (string enclosed in quotes) are optional.

Default: (no value)

horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))

Accepts [HorizontalAlignment](#): left, right, center

Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below Vertical space following the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left Left margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right Right margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding Padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left Left padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

`padding_right` Right padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

`padding_top` Top padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

`padding_bottom` Bottom padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

`keep_with_next` Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))
 Accepts [Bool](#): true or false
 Default: false

`border` Border surrounding the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`border_left` Border left of the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`border_right` Border right of the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`border_top` Border above the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`border_bottom` Border below the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`background_color`
 Color of the area within the flowable's borders (inherited from [FlowableStyle](#))
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: none

`page_break` Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))

Accepts Break: none, any, left, right
 Default: None

typeface Typeface to set the text in (inherited from [TextStyle](#))
 Accepts [Typeface](#): the name of a typeface. See [rinoh --list-fonts](#) for a list of the available typefaces.
 Default: Times

font_weight Thickness of character outlines relative to their height (inherited from [TextStyle](#))
 Accepts [FontWeight](#): hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black
 Default: 500

font_slant Slope style of the font (inherited from [TextStyle](#))
 Accepts [FontSlant](#): upright, oblique, italic
 Default: upright

font_width Stretch of the characters (inherited from [TextStyle](#))
 Accepts [FontWidth](#): ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded
 Default: 5

font_size Height of characters (inherited from [TextStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 10pt

font_color Color of the font (inherited from [TextStyle](#))
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: #000

font_variant Variant of the font (inherited from [TextStyle](#))
 Accepts [FontVariant](#): normal, small capital, oldstyle figures
 Default: normal

position Vertical text position (inherited from [TextStyle](#))
 Accepts [TextPosition](#): normal, superscript, subscript
 Default: normal

kerning Improve inter-letter spacing (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true

ligatures Run letters together where possible (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true

hyphenate Allow words to be broken over two lines (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false

Default: true

hyphen_chars Minimum number of characters in a hyphenated part of a word (inherited from [TextStyle](#))

Accepts [Integer](#): a natural number (positive integer)

Default: 2

hyphen_lang Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from [TextStyle](#))

Accepts [Locale](#): locale identifier in the <language ID>_<region ID> format

Default: en_US

before Item to insert before this one (inherited from [InlineStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after Item to insert after this one (inherited from [InlineStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

hide Suppress rendering this element (inherited from [Style](#))

Accepts [Bool](#): true or false

Default: false

NoteMarkerStyle

```
class rinoh.reference.NoteMarkerStyle ( base=None, **attributes )
```

Style class for NoteMarker

typeface Typeface to set the text in (inherited from [TextStyle](#))

Accepts [Typeface](#): the name of a typeface. See [rinoh --list-fonts](#) for a list of the available typefaces.

Default: Times

font_weight Thickness of character outlines relative to their height (inherited from [TextStyle](#))

Accepts [FontWeight](#): hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant Slope style of the font (inherited from [TextStyle](#))

Accepts [FontSlant](#): upright, oblique, italic

Default: upright

font_width Stretch of the characters (inherited from [TextStyle](#))

Accepts [FontWidth](#): ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size Height of characters (inherited from [TextStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 10pt

font_color Color of the font (inherited from [TextStyle](#))
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: #000

font_variant Variant of the font (inherited from [TextStyle](#))
 Accepts [FontVariant](#): normal, small capital, oldstyle figures
 Default: normal

position Vertical text position (inherited from [TextStyle](#))
 Accepts [TextPosition](#): normal, superscript, subscript
 Default: normal

kerning Improve inter-letter spacing (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true

ligatures Run letters together where possible (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true

hyphenate Allow words to be broken over two lines (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true

hyphen_chars Minimum number of characters in a hyphenated part of a word (inherited from [TextStyle](#))
 Accepts [Integer](#): a natural number (positive integer)
 Default: 2

hyphen_lang Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from [TextStyle](#))
 Accepts [Locale](#): locale identifier in the <language ID>_<region ID> format
 Default: en_US

before Item to insert before this one (inherited from [InlineStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

after Item to insert after this one (inherited from [InlineStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

hide Suppress rendering this element (inherited from [Style](#))

Accepts **Bool**: true or false
 Default: false

number_format How numbers are formatted (inherited from **NumberStyle**)
 Accepts **NumberFormat**: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman
 Default: number

label_prefix Text to prepend to the label (inherited from **LabelStyle**)
 Accepts **StyledText**: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or '), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

label_suffix Text to append to the label (inherited from **LabelStyle**)
 Accepts **StyledText**: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or '), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

custom_label Use a custom label if specified (inherited from **LabelStyle**)
 Accepts **Bool**: true or false
 Default: false

SectionStyle

`class rinoh.structure.SectionStyle (base=None, **attributes)`

Style class for **Section**

show_in_toc List this section in the table of contents

Accepts **Bool**: true or false

Default: true

width Width to render the flowable at (inherited from **GroupedFlowablesStyle**)

Accepts **FlowableWidth**: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: fill

title Title to precede the flowables (inherited from **GroupedFlowablesStyle**)

Accepts **StyledText**: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or '), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing Spacing between flowables (inherited from **GroupedFlowablesStyle**)

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

horizontal_align Horizontal alignment of the flowable (inherited from **FlowableStyle**)

Accepts [HorizontalAlignment](#): left, right, center
 Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

space_below Vertical space following the flowable (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

margin_left Left margin (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

margin_right Right margin (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding Padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_left Left padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_right Right padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))
 Accepts [Bool](#): true or false
 Default: false

border Border surrounding the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_left Border left of the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_right Border right of the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_top Border above the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_bottom Border below the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

background_color
 Color of the area within the flowable's borders (inherited from [FlowableStyle](#))
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: none

page_break Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))
 Accepts [Break](#): none, any, left, right
 Default: None

hide Suppress rendering this element (inherited from [Style](#))
 Accepts [Bool](#): true or false
 Default: false

HeadingStyle

```
class rinoh.structure.HeadingStyle ( base=None, **attributes )
```

Style class for [Heading](#)

number_separator

Characters inserted between the number label of the parent section and this section. If None, only show this section's number label.

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: '.'

keep_with_next Overrides the default set in [FlowableStyle](#)

Accepts [Bool](#): true or false

Default: true

width Width to render the flowable at (inherited from [ParagraphStyle](#))

Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: fill

indent_first Indentation of the first line of text (inherited from [ParagraphStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0pt

line_spacing Spacing between the baselines of two successive lines of text (inherited from [ParagraphStyle](#))

Accepts [LineSpacing](#): a [predefined line spacing](#) type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

text_align Alignment of text to the margins (inherited from [ParagraphStyle](#))

Accepts [TextAlign](#): left, right, center, justify

Default: justify

tab_stops List of tab positions (inherited from [ParagraphStyle](#))

Accepts [TabStopList](#): a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position ([Dimension](#)) is required and align ([TabAlign](#)) and fill string (string enclosed in quotes) are optional.

Default: (no value)

horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))

Accepts [HorizontalAlignment](#): left, right, center

Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below Vertical space following the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left Left margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right Right margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding Padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left Left padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_right Right padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

border Border surrounding the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_left Border left of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_right Border right of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_top Border above the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_bottom Border below the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

background_color Color of the area within the flowable's borders (inherited from [FlowableStyle](#))

Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))

Accepts Break: none, any, left, right

Default: None

typeface Typeface to set the text in (inherited from [TextStyle](#))

Accepts [Typeface](#): the name of a typeface. See [rinoh --list-fonts](#) for a list of the available typefaces.

Default: Times

font_weight Thickness of character outlines relative to their height (inherited from [TextStyle](#))

Accepts [FontWeight](#): hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant Slope style of the font (inherited from [TextStyle](#))

Accepts [FontSlant](#): upright, oblique, italic

Default: upright

font_width Stretch of the characters (inherited from [TextStyle](#))

Accepts [FontWidth](#): ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size Height of characters (inherited from [TextStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 10pt

font_color Color of the font (inherited from [TextStyle](#))

Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant Variant of the font (inherited from [TextStyle](#))

Accepts [FontVariant](#): normal, small capital, oldstyle figures

Default: normal

position Vertical text position (inherited from [TextStyle](#))

Accepts [TextPosition](#): normal, superscript, subscript

Default: normal

kerning Improve inter-letter spacing (inherited from [TextStyle](#))

Accepts [Bool](#): true or false
 Default: true

ligatures Run letters together where possible (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true

hyphenate Allow words to be broken over two lines (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true

hyphen_chars Minimum number of characters in a hyphenated part of a word (inherited from [TextStyle](#))
 Accepts [Integer](#): a natural number (positive integer)
 Default: 2

hyphen_lang Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from [TextStyle](#))
 Accepts [Locale](#): locale identifier in the <language ID>_<region ID> format
 Default: en_US

before Item to insert before this one (inherited from [InlineStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

after Item to insert after this one (inherited from [InlineStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

number_format How numbers are formatted (inherited from [NumberStyle](#))
 Accepts [NumberFormat](#): none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman
 Default: number

label_prefix Text to prepend to the label (inherited from [LabelStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

label_suffix Text to append to the label (inherited from [LabelStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

custom_label Use a custom label if specified (inherited from LabelStyle)

Accepts **Bool**: true or false

Default: false

hide Suppress rendering this element (inherited from Style)

Accepts **Bool**: true or false

Default: false

ListStyle

```
class rinoh.structure.ListStyle ( base=None, **attributes )
```

Style class for **List**

ordered This list is ordered or unordered

Accepts **Bool**: true or false

Default: false

bullet Bullet to use in unordered lists

Accepts **StyledText**: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: '•'

width Width to render the flowable at (inherited from **GroupedFlowablesStyle**)

Accepts **FlowableWidth**: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: fill

title Title to precede the flowables (inherited from **GroupedFlowablesStyle**)

Accepts **StyledText**: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing Spacing between flowables (inherited from **GroupedFlowablesStyle**)

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

horizontal_align Horizontal alignment of the flowable (inherited from **FlowableStyle**)

Accepts **HorizontalAlignment**: left, right, center

Default: left

space_above Vertical space preceding the flowable (inherited from **FlowableStyle**)

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below Vertical space following the flowable (inherited from **FlowableStyle**)

Accepts **Dimension**: a numeric value followed by a unit (pt, in,

pc, mm, cm, %, /4)
 Default: 0

margin_left Left margin (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

margin_right Right margin (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding Padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_left Left padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_right Right padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))
 Accepts [Bool](#): true or false
 Default: false

border Border surrounding the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_left Border left of the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_right Border right of the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the

stroke, separated by a comma (,)
 Default: none

border_top Border above the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_bottom Border below the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

background_color
 Color of the area within the flowable's borders (inherited from [FlowableStyle](#))
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: none

page_break Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))
 Accepts Break: none, any, left, right
 Default: None

hide Suppress rendering this element (inherited from [Style](#))
 Accepts [Bool](#): true or false
 Default: false

number_format How numbers are formatted (inherited from [NumberStyle](#))
 Accepts [NumberFormat](#): none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman
 Default: number

label_prefix Text to prepend to the label (inherited from [LabelStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

label_suffix Text to append to the label (inherited from [LabelStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

custom_label Use a custom label if specified (inherited from [LabelStyle](#))
 Accepts [Bool](#): true or false
 Default: false

ListItemLabelStyle

class rinoh.structure.ListItemLabelStyle (base=None, **attributes)

Style class for ListItemLabel

width Width to render the flowable at (inherited from [ParagraphStyle](#))

Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: fill

indent_first Indentation of the first line of text (inherited from [ParagraphStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0pt

line_spacing Spacing between the baselines of two successive lines of text (inherited from [ParagraphStyle](#))

Accepts [LineSpacing](#): a [predefined line spacing](#) type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

text_align Alignment of text to the margins (inherited from [ParagraphStyle](#))

Accepts [TextAlign](#): left, right, center, justify

Default: justify

tab_stops List of tab positions (inherited from [ParagraphStyle](#))

Accepts [TabStopList](#): a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position ([Dimension](#)) is required and align ([TabAlign](#)) and fill string (string enclosed in quotes) are optional.

Default: (no value)

horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))

Accepts [HorizontalAlignment](#): left, right, center

Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below Vertical space following the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left Left margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

`margin_right` Right margin (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

`padding` Padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

`padding_left` Left padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

`padding_right` Right padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

`padding_top` Top padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

`padding_bottom` Bottom padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

`keep_with_next` Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))
 Accepts [Bool](#): true or false
 Default: false

`border` Border surrounding the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`border_left` Border left of the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`border_right` Border right of the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`border_top` Border above the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_bottom Border below the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from [FlowableStyle](#))

Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))

Accepts [Break](#): none, any, left, right

Default: None

typeface Typeface to set the text in (inherited from [TextStyle](#))

Accepts [Typeface](#): the name of a typeface. See [rinoh --list-fonts](#) for a list of the available typefaces.

Default: Times

font_weight Thickness of character outlines relative to their height (inherited from [TextStyle](#))

Accepts [FontWeight](#): hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant Slope style of the font (inherited from [TextStyle](#))

Accepts [FontSlant](#): upright, oblique, italic

Default: upright

font_width Stretch of the characters (inherited from [TextStyle](#))

Accepts [FontWidth](#): ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size Height of characters (inherited from [TextStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 10pt

font_color Color of the font (inherited from [TextStyle](#))

Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant Variant of the font (inherited from [TextStyle](#))

Accepts [FontVariant](#): normal, small capital, oldstyle figures

Default: normal

position Vertical text position (inherited from [TextStyle](#))

Accepts [TextPosition](#): normal, superscript, subscript
Default: normal

kerning Improve inter-letter spacing (inherited from [TextStyle](#))
Accepts [Bool](#): true or false
Default: true

ligatures Run letters together where possible (inherited from [TextStyle](#))
Accepts [Bool](#): true or false
Default: true

hyphenate Allow words to be broken over two lines (inherited from [TextStyle](#))
Accepts [Bool](#): true or false
Default: true

hyphen_chars Minimum number of characters in a hyphenated part of a word (inherited from [TextStyle](#))
Accepts [Integer](#): a natural number (positive integer)
Default: 2

hyphen_lang Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from [TextStyle](#))
Accepts [Locale](#): locale identifier in the <language ID>_<region ID> format
Default: en_US

before Item to insert before this one (inherited from [InlineStyle](#))
Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or '), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

after Item to insert after this one (inherited from [InlineStyle](#))
Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or '), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

hide Suppress rendering this element (inherited from [Style](#))
Accepts [Bool](#): true or false
Default: false

label_prefix Text to prepend to the label (inherited from [LabelStyle](#))
Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or '), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

label_suffix Text to append to the label (inherited from [LabelStyle](#))
Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or '), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label Use a custom label if specified (inherited from [LabelStyle](#))

Accepts [Bool](#): true or false

Default: false

TableOfContentsStyle

class rinoh.structure.TableOfContentsStyle (base=None, **attributes)

Style class for [TableOfContents](#)

depth The number of section levels to include in the table of contents

Accepts [Integer](#): a natural number (positive integer)

Default: 3

width Width to render the flowable at (inherited from [GroupedFlowablesStyle](#))

Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: fill

title Title to precede the flowables (inherited from [GroupedFlowablesStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing Spacing between flowables (inherited from [GroupedFlowablesStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))

Accepts [HorizontalAlignment](#): left, right, center

Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below Vertical space following the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left Left margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right Right margin (inherited from [FlowableStyle](#))

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding Padding (inherited from **FlowableStyle**)
 Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_left Left padding (inherited from **FlowableStyle**)
 Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_right Right padding (inherited from **FlowableStyle**)
 Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_top Top padding (inherited from **FlowableStyle**)
 Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_bottom Bottom padding (inherited from **FlowableStyle**)
 Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from **FlowableStyle**)
 Accepts **Bool**: true or false
 Default: false

border Border surrounding the flowable (inherited from **FlowableStyle**)
 Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)
 Default: none

border_left Border left of the flowable (inherited from **FlowableStyle**)
 Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)
 Default: none

border_right Border right of the flowable (inherited from **FlowableStyle**)
 Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)
 Default: none

border_top Border above the flowable (inherited from **FlowableStyle**)
 Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)
 Default: none

border_bottom Border below the flowable (inherited from **FlowableStyle**)

Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)
 Default: none

background_color
 Color of the area within the flowable's borders (inherited from **FlowableStyle**)
 Accepts **Color**: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: none

page_break Type of page break to insert before rendering this flowable (inherited from **FlowableStyle**)
 Accepts **Break**: none, any, left, right
 Default: None

hide Suppress rendering this element (inherited from **Style**)
 Accepts **Bool**: true or false
 Default: false

indent_first Indentation of the first line of text (inherited from **ParagraphStyle**)
 Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0pt

line_spacing Spacing between the baselines of two successive lines of text (inherited from **ParagraphStyle**)
 Accepts **LineSpacing**: a **predefined line spacing** type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)
 Default: default

text_align Alignment of text to the margins (inherited from **ParagraphStyle**)
 Accepts **TextAlign**: left, right, center, justify
 Default: justify

tab_stops List of tab positions (inherited from **ParagraphStyle**)
 Accepts **TabStopList**: a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position (**Dimension**) is required and align (**TabAlign**) and fill string (string enclosed in quotes) are optional.
 Default: (no value)

typeface Typeface to set the text in (inherited from **TextStyle**)
 Accepts **Typeface**: the name of a typeface. See **rinoh --list-fonts** for a list of the available typefaces.
 Default: Times

font_weight Thickness of character outlines relative to their height (inherited from **TextStyle**)
 Accepts **FontWeight**: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant Slope style of the font (inherited from [TextStyle](#))

Accepts [FontSlant](#): upright, oblique, italic

Default: upright

font_width Stretch of the characters (inherited from [TextStyle](#))

Accepts [FontWidth](#): ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size Height of characters (inherited from [TextStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 10pt

font_color Color of the font (inherited from [TextStyle](#))

Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant Variant of the font (inherited from [TextStyle](#))

Accepts [FontVariant](#): normal, small capital, oldstyle figures

Default: normal

position Vertical text position (inherited from [TextStyle](#))

Accepts [TextPosition](#): normal, superscript, subscript

Default: normal

kerning Improve inter-letter spacing (inherited from [TextStyle](#))

Accepts [Bool](#): true or false

Default: true

ligatures Run letters together where possible (inherited from [TextStyle](#))

Accepts [Bool](#): true or false

Default: true

hyphenate Allow words to be broken over two lines (inherited from [TextStyle](#))

Accepts [Bool](#): true or false

Default: true

hyphen_chars Minimum number of characters in a hyphenated part of a word (inherited from [TextStyle](#))

Accepts [Integer](#): a natural number (positive integer)

Default: 2

hyphen_lang Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from [TextStyle](#))

Accepts [Locale](#): locale identifier in the <language ID>_<region ID> format

Default: en_US

before Item to insert before this one (inherited from [InlineStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or '), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after Item to insert after this one (inherited from [InlineStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or '), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

TableOfContentsEntryStyle

class rinoh.structure.TableOfContentsEntryStyle (base=None, **attributes)

Style class for [TableOfContentsEntry](#)

text Overrides the default set in [ReferencingParagraphStyle](#)

Accepts [ReferenceText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or '), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: '{NUMBER}' '\t' '{TITLE}' '\t' '{PAGE}'

width Width to render the flowable at (inherited from [ParagraphStyle](#))

Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: fill

indent_first Indentation of the first line of text (inherited from [ParagraphStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0pt

line_spacing Spacing between the baselines of two successive lines of text (inherited from [ParagraphStyle](#))

Accepts [LineSpacing](#): a [predefined line spacing](#) type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

text_align Alignment of text to the margins (inherited from [ParagraphStyle](#))

Accepts [TextAlign](#): left, right, center, justify

Default: justify

tab_stops List of tab positions (inherited from [ParagraphStyle](#))

Accepts [TabStopList](#): a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position ([Dimension](#)) is required and align ([TabAlign](#)) and fill string (string enclosed in quotes) are optional.

Default: (no value)

horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))

Accepts [HorizontalAlignment](#): left, right, center

Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

space_below Vertical space following the flowable (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

margin_left Left margin (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

margin_right Right margin (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding Padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_left Left padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_right Right padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))
 Accepts [Bool](#): true or false
 Default: false

border Border surrounding the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke,

separated by a comma (,)

Default: none

border_left Border left of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_right Border right of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_top Border above the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_bottom Border below the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from [FlowableStyle](#))

Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))

Accepts [Break](#): none, any, left, right

Default: None

typeface Typeface to set the text in (inherited from [TextStyle](#))

Accepts [Typeface](#): the name of a typeface. See [rinoh --list-fonts](#) for a list of the available typefaces.

Default: Times

font_weight Thickness of character outlines relative to their height (inherited from [TextStyle](#))

Accepts [FontWeight](#): hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant Slope style of the font (inherited from [TextStyle](#))

Accepts [FontSlant](#): upright, oblique, italic

Default: upright

font_width Stretch of the characters (inherited from [TextStyle](#))

Accepts [FontWidth](#): ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size Height of characters (inherited from [TextStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 10pt

font_color Color of the font (inherited from [TextStyle](#))

Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant Variant of the font (inherited from [TextStyle](#))

Accepts [FontVariant](#): normal, small capital, oldstyle figures

Default: normal

position Vertical text position (inherited from [TextStyle](#))

Accepts [TextPosition](#): normal, superscript, subscript

Default: normal

kerning Improve inter-letter spacing (inherited from [TextStyle](#))

Accepts [Bool](#): true or false

Default: true

ligatures Run letters together where possible (inherited from [TextStyle](#))

Accepts [Bool](#): true or false

Default: true

hyphenate Allow words to be broken over two lines (inherited from [TextStyle](#))

Accepts [Bool](#): true or false

Default: true

hyphen_chars Minimum number of characters in a hyphenated part of a word (inherited from [TextStyle](#))

Accepts [Integer](#): a natural number (positive integer)

Default: 2

hyphen_lang Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from [TextStyle](#))

Accepts [Locale](#): locale identifier in the <language ID>_<region ID> format

Default: en_US

before Item to insert before this one (inherited from [InlineStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after Item to insert after this one (inherited from [InlineStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

hide Suppress rendering this element (inherited from [Style](#))

Accepts [Bool](#): true or false

Default: false

AdmonitionStyle

```
class rinoh.structure.AdmonitionStyle ( base=None, **attributes )
```

Style class for [Admonition](#)

inline_title Show the admonition's title inline with the body text, if possible

Accepts [Bool](#): true or false

Default: true

width Width to render the flowable at (inherited from [GroupedFlowablesStyle](#))

Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: fill

title Title to precede the flowables (inherited from [GroupedFlowablesStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing Spacing between flowables (inherited from [GroupedFlowablesStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))

Accepts [HorizontalAlignment](#): left, right, center

Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below Vertical space following the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left Left margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right Right margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in,

pc, mm, cm, %, /4)
Default: 0

padding Padding (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

padding_left Left padding (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

padding_right Right padding (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))
Accepts [Bool](#): true or false
Default: false

border Border surrounding the flowable (inherited from [FlowableStyle](#))
Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
Default: none

border_left Border left of the flowable (inherited from [FlowableStyle](#))
Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
Default: none

border_right Border right of the flowable (inherited from [FlowableStyle](#))
Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
Default: none

border_top Border above the flowable (inherited from [FlowableStyle](#))
Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
Default: none

border_bottom Border below the flowable (inherited from [FlowableStyle](#))
Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of

the stroke, separated by a comma (,)
 Default: none

background_color
 Color of the area within the flowable's borders (inherited from [FlowableStyle](#))
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: none

page_break Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))
 Accepts Break: none, any, left, right
 Default: None

hide Suppress rendering this element (inherited from [Style](#))
 Accepts [Bool](#): true or false
 Default: false

HorizontalRuleStyle

```
class rinoh.structure.HorizontalRuleStyle ( base=None, **attributes )
```

Style class for [HorizontalRule](#)

width Width to render the flowable at (inherited from [FlowableStyle](#))
 Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: auto

horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))
 Accepts [HorizontalAlignment](#): left, right, center
 Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

space_below Vertical space following the flowable (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

margin_left Left margin (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

margin_right Right margin (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding Padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left Left padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_right Right padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))

Accepts [Bool](#): true or false

Default: false

border Border surrounding the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_left Border left of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_right Border right of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_top Border above the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_bottom Border below the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from [FlowableStyle](#))

Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))

Accepts Break: none, any, left, right

Default: None

hide Suppress rendering this element (inherited from [Style](#))

Accepts [Bool](#): true or false

Default: false

stroke Width and color used to draw the line (inherited from [LineStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: 1pt, #000

TableStyle

class rinoh.table.TableStyle (base=None, **attributes)

Style class for [Table](#)

column_widths Absolute or relative widths of each column

Accepts ColumnWidths: a whitespace-delimited list of column widths; [Dimensions](#) (absolute width), integers (relative width) and/or 'auto' (automatic width)

Default: none

split_minimum_rows

The minimum number of rows to display when the table is split across pages

Accepts [Integer](#): a natural number (positive integer)

Default: (no value)

repeat_head Repeat the head when the table is split across pages

Accepts [Bool](#): true or false

Default: false

width Width to render the flowable at (inherited from [FlowableStyle](#))

Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: auto

horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))

Accepts [HorizontalAlignment](#): left, right, center

Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

space_below Vertical space following the flowable (inherited from **FlowableStyle**)
 Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

margin_left Left margin (inherited from **FlowableStyle**)
 Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

margin_right Right margin (inherited from **FlowableStyle**)
 Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding Padding (inherited from **FlowableStyle**)
 Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_left Left padding (inherited from **FlowableStyle**)
 Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_right Right padding (inherited from **FlowableStyle**)
 Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_top Top padding (inherited from **FlowableStyle**)
 Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_bottom Bottom padding (inherited from **FlowableStyle**)
 Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from **FlowableStyle**)
 Accepts **Bool**: true or false
 Default: false

border Border surrounding the flowable (inherited from **FlowableStyle**)
 Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)
 Default: none

border_left Border left of the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_right Border right of the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_top Border above the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_bottom Border below the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

background_color
 Color of the area within the flowable's borders (inherited from [FlowableStyle](#))
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: none

page_break Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))
 Accepts [Break](#): none, any, left, right
 Default: None

hide Suppress rendering this element (inherited from [Style](#))
 Accepts [Bool](#): true or false
 Default: false

TableCellStyle

```
class rinoh.table.TableCellStyle ( base=None, **attributes )
```

Style class for [TableCell](#)

vertical_align Vertical alignment of the cell contents within the available space
 Accepts [VerticalAlign](#): top, middle, bottom
 Default: middle

width Width to render the flowable at (inherited from [GroupedFlowablesStyle](#))
 Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: fill

title Title to precede the flowables (inherited from [GroupedFlowablesStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style

name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing Spacing between flowables (inherited from [GroupedFlowablesStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))

Accepts [HorizontalAlignment](#): left, right, center

Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below Vertical space following the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left Left margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right Right margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding Padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left Left padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_right Right padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

`padding_bottom` Bottom padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

`keep_with_next` Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))
 Accepts [Bool](#): true or false
 Default: false

`border` Border surrounding the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`border_left` Border left of the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`border_right` Border right of the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`border_top` Border above the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`border_bottom` Border below the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`background_color`
 Color of the area within the flowable's borders (inherited from [FlowableStyle](#))
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: none

`page_break` Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))
 Accepts [Break](#): none, any, left, right
 Default: None

`hide` Suppress rendering this element (inherited from [Style](#))
 Accepts [Bool](#): true or false
 Default: false

TableCellBorderStyle

class rinoh.table.TableCellBorderStyle (base=None, **attributes)

Style class for [TableCellBorder](#)

stroke Overrides the default set in [LineStyle](#)

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

hide Suppress rendering this element (inherited from [Style](#))

Accepts [Bool](#): true or false

Default: false

TableCellBackgroundStyle

class rinoh.table.TableCellBackgroundStyle (base=None, **attributes)

Style class for [TableCellBackground](#)

fill_color Overrides the default set in [ShapeStyle](#)

Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

stroke Overrides the default set in [LineStyle](#)

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

hide Suppress rendering this element (inherited from [Style](#))

Accepts [Bool](#): true or false

Default: false

7.4 Standard Document Templates

Rinohtype includes a number of document templates. These are configurable and therefore should cater for most documents.

7.4.1 Article

The article template consists of a title page, an optional table of contents and the body text. By default, it uses a single numbering style for all pages and the same template for even and odd pages.

class rinoh.templates.article.Article (document_tree, configuration=None, backend=None)

stylesheet Overrides the default set in [DocumentTemplate](#)

Accepts [StyleSheet](#): the name of an [installed style sheet](#) or the file-name of a stylesheet file (with the .rts extension)

Default: sphinx_article (= [rinoh.stylesheets.sphinx_article](#))

table_of_contents Show or hide the table of contents

Accepts [Bool](#): true or false

Default: true

abstract_location Where to place the abstract
 Accepts [AbstractLocation](#): title, front matter
 Default: front matter

parts Overrides the default set in [DocumentTemplate](#)
 Accepts [PartsList](#): a space-separated list of document part template names
 Default: [title front_matter contents](#)

language The main language of the document (inherited from [DocumentTemplate](#))
 Accepts [Language](#): the code of one of the [supported languages](#)
 Default: [EN](#) (English)

strings Strings to override standard element names (inherited from [DocumentTemplate](#))
 Accepts [Strings](#): strings need to be entered in INI sections named after the [StringCollection](#) subclasses
 Default: none

title base: None
 Type [TitlePartTemplate](#)

front_matter base: None
 Type [ArticleFrontMatter](#)

contents base: None
 Type [ContentsPartTemplate](#)

page base: None
 Overrides these defaults:

- [page_size](#) = \$(paper_size)

Type [PageTemplate](#)

title_page base: [page](#)
 Overrides these defaults:

- [top_margin](#) = 8cm

Type [TitlePageTemplate](#)

front_matter_page
 base: [page](#)
 Type [PageTemplate](#)

contents_page base: [page](#)
 Type [PageTemplate](#)

Configuration alias of [rinoh.template.ArticleConfiguration](#)
 ConfigurationFile alias of [rinoh.template.ArticleConfigurationFile](#)

class [rinoh.templates.article.AbstractLocation](#)
 Where to place the article's abstract
 Accepts: title, front matter

7.4.2 Book

The book template consists of a title page, the table of contents, the body text and an index. The front matter pages are numbered using lowercase roman numerals. The template uses different templates for even and odd pages.

`class rinoh.templates.book.Book (document_tree, configuration=None, backend=None)`

`stylesheet` Overrides the default set in [DocumentTemplate](#)

Accepts [StyleSheet](#): the name of an [installed style sheet](#) or the file-name of a stylesheet file (with the .rts extension)

Default: sphinx (= [rinoh.stylesheets.sphinx](#))

`parts` Overrides the default set in [DocumentTemplate](#)

Accepts [PartsList](#): a space-separated list of document part template names

Default: [title front_matter contents back_matter](#)

`language` The main language of the document (inherited from [DocumentTemplate](#))

Accepts [Language](#): the code of one of the [supported languages](#)

Default: [EN](#) (English)

`strings` Strings to override standard element names (inherited from [DocumentTemplate](#))

Accepts [Strings](#): strings need to be entered in INI sections named after the [StringCollection](#) subclasses

Default: none

`cover base`: None

Overrides these defaults:

- [drop_if_empty](#) = False
- [page_number_format](#) = None
- [end_at_page](#) = left

Type [FixedDocumentPartTemplate](#)

`title base`: None

Overrides these defaults:

- [page_number_format](#) = number
- [end_at_page](#) = left

Type [TitlePartTemplate](#)

`front_matter base`: None

Overrides these defaults:

- [flowables](#) = [TableOfContentsSection(), ListOfFiguresSection(), ListOfTablesSection()]
- [page_number_format](#) = lowercase roman

- `end_at_page` = left

Type `FixedDocumentPartTemplate`

contents base: None

Overrides these defaults:

- `page_number_format` = number
- `end_at_page` = left

Type `ContentsPartTemplate`

back_matter base: None

Overrides these defaults:

- `page_number_format` = number
- `end_at_page` = left

Type `BackMatterTemplate`

page base: None

Overrides these defaults:

- `page_size` = \$(paper_size)
- `left_margin` = 1in
- `right_margin` = 1in
- `top_margin` = 1in
- `bottom_margin` = 1in

Type `PageTemplate`

cover_page base: `page`

Type `PageTemplate`

title_page base: `page`

Type `TitlePageTemplate`

front_matter_page

base: `page`

Overrides these defaults:

- `header_footer_distance` = 0
- `header_text` = None

Type `PageTemplate`

front_matter_right_page

base: `front_matter_page`

Overrides these defaults:

- `footer_text` = '\t' '\t' '{PAGE_NUMBER}'

- `chapter_header_text` = None
- `chapter_footer_text` = '\t\t' '{PAGE_NUMBER}'
- `chapter_title_height` = 2.5in
- `chapter_title_flowables` = [Paragraph[Field({SECTION_TITLE})]] (style=front matter section title)]

Type `PageTemplate`

`front_matter_left_page`

base: `front_matter_page`

Overrides these defaults:

- `footer_text` = '{PAGE_NUMBER}'

Type `PageTemplate`

`contents_page` base: `page`

Overrides these defaults:

- `header_footer_distance` = 0

Type `PageTemplate`

`contents_right_page`

base: `contents_page`

Overrides these defaults:

- `header_text` = '\t\t' '{DOCUMENT_TITLE}' ', ' '{DOCUMENT_SUBTITLE}'
- `footer_text` = '{SECTION_NUMBER}' '. ' '{SECTION_TITLE}' '\t\t' '{PAGE_NUMBER}'
- `chapter_header_text` = None
- `chapter_footer_text` = '\t\t' '{PAGE_NUMBER}'
- `chapter_title_height` = 2.4in
- `chapter_title_flowables` = [Paragraph[MixedStyledText[MixedStyledText[StringField(SectionTitles, 'chapter', style=None), SingleStyledText(' ', style=None)] (style=None), Field({SECTION_NUMBER})] (style=None)] (style=body matter chapter label), Paragraph[Field({SECTION_TITLE})] (style=body matter chapter title)]

Type `PageTemplate`

`contents_left_page`

base: `contents_page`

Overrides these defaults:

- `header_text` = '{DOCUMENT_TITLE}' ', ' '{DOCUMENT_SUBTITLE}'

- `footer_text` = '{PAGE_NUMBER}' '\t' '\t' '{SectionTitles.chapter}' ' ' '{SECTION_NUMBER}' '. ' '{SECTION_TITLE}'

Type [PageTemplate](#)

`back_matter_page`

base: [page](#)

Overrides these defaults:

- `columns` = 2
- `header_footer_distance` = 0

Type [PageTemplate](#)

`back_matter_right_page`

base: [back_matter_page](#)

Overrides these defaults:

- `header_text` = '\t' '\t' '{DOCUMENT_TITLE}' ', ' '{DOCUMENT_SUBTITLE}'
- `footer_text` = '{SECTION_TITLE}' '\t' '\t' '{PAGE_NUMBER}'
- `chapter_header_text` = None
- `chapter_footer_text` = '\t' '\t' '{PAGE_NUMBER}'
- `chapter_title_height` = 2.5in
- `chapter_title_flowables` = [Paragraph[Field({SECTION_TITLE})] (style=front matter section title)]

Type [PageTemplate](#)

`back_matter_left_page`

base: [back_matter_page](#)

Overrides these defaults:

- `header_text` = '{DOCUMENT_TITLE}' ', ' '{DOCUMENT_SUBTITLE}'
- `footer_text` = '{PAGE_NUMBER}' '\t' '\t' '{SECTION_TITLE}'

Type [PageTemplate](#)

Configuration alias of `rinoh.template.BookConfiguration`

ConfigurationFile alias of `rinoh.template.BookConfigurationFile`

Note

The API documentation is still incomplete.

8.1 Attribute ([rinoh.attribute](#))

class `rinoh.attribute.AcceptNoneAttributeType`

Accepts 'none' (besides other values)

class `rinoh.attribute.OptionSet`

Accepts the values listed in values

Accepts:

class `rinoh.attribute.Attribute` (`accepted_type`, `default_value`, `description`)

Descriptor used to describe a style attribute

class `rinoh.attribute.OverrideDefault` (`default_value`)

Overrides the default value of an attribute defined in a superclass

class `rinoh.attribute.AttributesDictionary` (`base=None`, `**attributes`)

class `rinoh.attribute.RuleSet` (`name`, `base=None`, `source=None`, `**kwargs`)

class `rinoh.attribute.RuleSetFile` (`filename`, `base=None`, `source=None`, `**kwargs`)

property location Textual representation of this source

property root Directory path for resolving paths relative to this source

class `rinoh.attribute.Bool`

Expresses a binary choice

class `rinoh.attribute.Integer`

Accepts natural numbers

exception `rinoh.attribute.ParseError`

8.2 Color ([rinoh.color](#))

class `rinoh.color.Color` (`red`, `green`, `blue`, `alpha=1`)

Color defined by component values

- Parameters
- red ([float](#)) – red component (0 .. 1)
 - blue ([float](#)) – blue component (0 .. 1)
 - green ([float](#)) – green component (0 .. 1)
 - alpha ([float](#)) – opacity (0 .. 1)

property `rgba`

classmethod `parse_string (string, source)`

classmethod `doc_format ()`

class `rinoh.color.HexColor (string)`

Color defined as a hexadecimal string

Parameters string ([str](#)) – #RGBA or #RRGGBBAA (# and A are optional)

class `rinoh.color.Gray (luminance, alpha=1)`

Shade of gray

- Parameters
- luminance ([float](#)) – brightness (0 .. 1)
 - alpha ([float](#)) – opacity (0 .. 1)

8.3 Dimension ([rinoh.dimension](#))

Classes for expressing dimensions: lengths, widths, line thickness, etc.

Each dimension is expressed in terms of a unit. Several common units are defined here as constants. To create a new dimension, multiply number with a unit:

```
height = 100*PT
width = 50*PERCENT
```

Fractional dimensions are evaluated within the context they are defined in. For example, the width of a Flowable is evaluated with respect to the total width available to it.

class `rinoh.dimension.Dimension (value=0, unit=None)`

A simple dimension

- Parameters
- value ([int](#) or [float](#)) – the magnitude of the dimension
 - unit (`DimensionUnit`) – the unit this dimension is expressed in. Default: [PT](#).

`grow (value)` Grow this dimension (in-place)

The value is interpreted as a magnitude expressed in the same unit as this dimension.

Parameters value ([int](#) or [float](#)) – the amount to add to the magnitude of this dimension

Returns [Dimension](#) – this (grewed) dimension itself

`rinoh.dimension.PT = DimensionUnit(1.0, 'pt')`

PostScript points


```

rinoh.dimension.PICA = DimensionUnit(12.0, 'pc')
                        computer pica
rinoh.dimension.INCH = DimensionUnit(72.0, 'in')
                        imperial/US inch
rinoh.dimension.MM = DimensionUnit(2.8346456692913384, 'mm')
                        millimeter
rinoh.dimension.CM = DimensionUnit(28.346456692913385, 'cm')
                        centimeter
rinoh.dimension.PERCENT = FractionUnit(100, '%')
                        fraction of 100
rinoh.dimension.QUARTERS = FractionUnit(4, '/4')
                        fraction of 4

```

8.4 Document (rinoh.document)

```

class rinoh.document.DocumentTree ( flowables, options=None )
    Holds the document's contents as a tree of flowables
    Parameters
        • flowables (list[Flowable]) – the list of top-level flowables
        • source_root (Path) – path used to locate images and include
          in logging and error and warnings.
        • options (Reader) – frontend-specific options

class rinoh.document.Document ( document_tree, stylesheet, language, strings=None,
                                backend=None )
    Renders a document tree to pages
    Parameters
        • document_tree (DocumentTree) – a tree of the document's
          contents
        • stylesheet (StyleSheet) – style sheet used to style document
          elements
        • language (Language) – the language to use for standard
          strings
        • strings (Strings) – overrides localized strings provided by
          language
        • backend – the backend used for rendering the document

    render ( filename_root=None, file=None )
        Render the document repeatedly until the output no
        longer changes due to cross-references that need some
        iterations to converge.

```

8.4.1 Pages

`class rinoh.document.Page (document_part, number, paper, orientation='portrait')`

A single page in a document.

A [Page](#) is a Container, so other containers can be added as children.

Parameters

- `document_part` ([DocumentPart](#)) – the document part this page is part of
- `number` ([int](#)) – the 1-based index of this page in the document part
- `paper` ([Paper](#)) – determines the dimensions of this page
- `orientation` ([PageOrientation](#)) – the orientation of this page

`property page` Returns the page itself.

`render ()` Render the contents of this container to its canvas.

Note that the rendered contents need to be [place\(\)](#) on the parent container's canvas before they become visible.

`place ()` Place this container's canvas onto the parent container's canvas.

`class rinoh.document.PageOrientation`

Accepts: portrait, landscape

`class rinoh.document.PageType`

Accepts: left, right, any

8.5 Drawing Primitives ([rinoh.draw](#))

`class rinoh.draw.Stroke (width, color)`

The display properties of a line

Parameters

- `width` ([Dimension](#)) – the width of the line
- `color` ([Color](#)) – the color of the line

`class rinoh.draw.Line (start, end, style=None, parent=None)`

Draws a line

Parameters

- `start` (2-tuple) – coordinates for the start point of the line
- `end` (2-tuple) – coordinates for the end point of the line

`style_class` alias of [rinoh.draw.LineStyle](#)

`class rinoh.draw.Shape (style=None, parent=None)`

Base class for closed shapes

`style_class` alias of [rinoh.draw.ShapeStyle](#)

`class rinoh.draw.Polygon (points, style=None, parent=None)`

`class rinoh.draw.Rectangle (bottom_left, width, height, style=None, parent=None)`

8.6 Flowable (rinoh.flowable)

`class rinoh.flowable.Flowable (align=None, width=None, id=None, style=None, parent=None, source=None)`

A document element that can be “flowed” into a container on the page.

A flowable can adapt to the width of the container, or it can horizontally align itself in the container.

Parameters

- align ([HorizontalAlignment](#)) – horizontal alignment of the flowable
- width ([FlowableWidth](#) or `DimensionBase`) – the width of the flowable.

`class rinoh.flowable.FlowableState (flowable, _initial=True)`

Stores a flowable’s rendering state, which can be copied.

This enables saving the rendering state at certain points in the rendering process, so rendering can later be resumed at those points, if needed.

8.6.1 No-Output Flowables

These flowables do not directly place anything on the page. All except [DummyFlowable](#) do have side-effects however. Some of these side-effects affect the rendering of the document in an indirect way.

`class rinoh.flowable.DummyFlowable (id=None, parent=None)`

A flowable that does not directly place anything on the page.

Subclasses can produce side-effects to affect the output in another way.

`class rinoh.flowable.AnchorFlowable (id=None, parent=None)`

A dummy flowable that registers a destination anchor.

Places a destination for the flowable’s ID at the current cursor position.

`class rinoh.flowable.SetMetadataFlowable (parent=None, **metadata)`

A dummy flowable that stores metadata in the document.

The metadata is passed as keyword arguments. It will be available to other flowables during the rendering stage.

`class rinoh.flowable.WarnFlowable (message, parent=None)`

A dummy flowable that emits a warning during the rendering stage.

Parameters message ([str](#)) – the warning message to emit

`class rinoh.flowable.PageBreak (page_break='any')`

8.6.2 Labeled Flowables

`class rinoh.flowable.LabeledFlowable (label, flowable, id=None, style=None, parent=None)`

A flowable with a label.

The flowable and the label are rendered side-by-side. If the label exceeds the `label_max_width` style attribute value, the flowable is rendered below the label.

- Parameters
- label ([Flowable](#)) – the label for the flowable
 - flowable ([Flowable](#)) – the flowable to label

style_class alias of [rinoh.flowable.LabeledFlowableStyle](#)

prepare (flowable_target)

Determine number labels and register references with the document

render (container, last_descender, state, label_column_width=None, space_below=0, **kwargs)

Renders the flowable's content to container, with the flowable's top edge lining up with the container's cursor. descender is the descender height of the preceding line or None.

class rinoh.flowable.LabeledFlowableState (flowable, content_flowable_state, _initial=True)

8.6.3 Grouping Flowables

class rinoh.flowable.GroupedFlowables (align=None, width=None, id=None, style=None, parent=None, source=None)

Groups a list of flowables and renders them one below the other.

Makes sure that a flowable for which keep_with_next is enabled is not separated from the flowable that follows it.

Subclasses should implement [flowables\(\)](#).

style_class alias of [rinoh.flowable.GroupedFlowablesStyle](#)

flowables (container)

Generator yielding the [Flowables](#) to group

render (container, descender, state, first_line_only=False, **kwargs)

Renders the flowable's content to container, with the flowable's top edge lining up with the container's cursor. descender is the descender height of the preceding line or None.

class rinoh.flowable.GroupedFlowablesState (groupedflowables, flowables, first_flowable_state=None, _initial=True, _index=0)

class rinoh.flowable.StaticGroupedFlowables (flowables, align=None, width=None, id=None, style=None, parent=None, source=None)

Groups a static list of flowables.

Parameters flowables (iterable[[Flowable](#)]) – the flowables to group

flowables (container)

Generator yielding the [Flowables](#) to group

build_document (flowable_target)

Set document metadata and populate front and back matter

prepare (flowable_target)

Determine number labels and register references with the document

```
class rinoh.flowable.GroupedLabeledFlowables ( align=None, width=None, id=None,
style=None, parent=None, source=None )
```

Groups a list of labeled flowables, lining them up.

```
render ( container, descender, state, **kwargs )
```

Renders the flowable's content to container, with the flowable's top edge lining up with the container's cursor. descender is the descender height of the preceding line or None.

8.6.4 Floating Flowables

```
class rinoh.flowable.Float ( align=None, width=None, id=None, style=None, parent=None,
source=None )
```

A flowable that can optionally be placed elsewhere on the page.

If this flowable's float style attribute is set to True, it is not flowed in line with the surrounding flowables, but it is instead flowed into another container pointed to by the former's Container.float_space attribute.

This is typically used to place figures and tables at the top or bottom of a page, instead of in between paragraphs.

```
flow ( container, last_descender, state=None, **kwargs )
```

Flow this flowable into container and return the vertical space consumed.

The flowable's contents are preceded by a vertical space with a height as specified in its style's space_above attribute. Similarly, the flowed content is followed by a vertical space with a height given by the space_below style attribute.

8.6.5 Styling Properties

```
class rinoh.flowable.HorizontalAlignment
```

Controls horizontal placement

Accepts: left, right, center

```
class rinoh.flowable.FlowableWidth
```

Controls the width of a flowable

Accepts: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

8.7 Fonts and Typefaces (rinoh.font)

Classes for fonts and typefaces.

```
class rinoh.font.Font ( filename, weight, slant, width )
```

A collection of glyphs in a particular style

This is a base class for classes that parse different font formats. See rinoh.font.type1 and rinoh.font.opentype.

Parameters

- filename (str) – filename of the font file to load

- weight ([FontWeight](#)) – weight of the font
- slant ([FontSlant](#)) – slant of the font
- width ([FontWidth](#)) – width of the font

encoding If no encoding is set for the [Font](#), glyphs are addressed by glyph ID (and thus support more than 256 glyphs).

`get_glyph (char, variant)`

Return the glyph for a particular character

If the glyph of requested font variant is not present in the font, the normal variant is returned instead. If that is not present either, an exception is raised.

Parameters

- char (str of length 1) – the character for which to find the glyph
- variant ([FontVariant](#)) – the variant of the glyph to return

Returns `GlyphMetrics` – the requested glyph

Raises `MissingGlyphException` – when the requested glyph is not present in the font

`get_ligature (glyph, successor_glyph)`

Return the ligature to replace the given glyphs

If no ligature is defined in the font for the given glyphs, return `None`.

Parameters

- glyph (`GlyphMetrics`) – the first of the glyphs to combine
- successor_glyph (`GlyphMetrics`) – the second of the glyphs to combine

Returns `GlyphMetrics` or `None` – the ligature to replace the given glyphs

`get_kerning (a, b)`

Look up the kerning for two glyphs

Parameters

- a (`GlyphMetrics`) – the first of the glyphs
- b (`GlyphMetrics`) – the second of the glyphs

Returns float – the kerning value in font units

`class rinoth.font.Typeface (name, *fonts)`

A set of fonts that share common design features

The fonts collected in a typeface differ in weight, width and/or slant.

Parameters *fonts ([Font](#)) – the fonts that make up this typeface

`fonts ()` Generator yielding all fonts of this typeface

Yields `Font` – the next font in this typeface

`get_font (weight=400, slant='upright', width=5)`

Return the font matching or closest to the given style

If a font with the given weight, slant and width is available, return it. Otherwise, return the font that is closest in style.

Parameters

- weight ([FontWeight](#)) – weight of the font
- slant ([FontSlant](#)) – slant of the font
- width ([FontWidth](#)) – width of the font

Returns Font – the requested font

`class rinoh.font.style.FontWeight`

Accepts: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

`class rinoh.font.style.FontSlant`

Accepts: upright, oblique, italic

`class rinoh.font.style.FontWidth`

Accepts: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

`class rinoh.font.style.FontVariant`

Accepts: normal, small capital, oldstyle figures

`class rinoh.font.style.TextPosition`

Accepts: normal, superscript, subscript

8.8 Images and Figures ([rinoh.image](#))

`class rinoh.image.Image (filename_or_file, scale=1.0, width=None, height=None, dpi=None, rotate=0, limit_width=<rinoh.dimension.Fraction object>, align=None, id=None, style=None, parent=None, source=None)`

`class rinoh.image.InlineImage (filename_or_file, scale=1.0, width=None, height=None, dpi=None, rotate=0, baseline=None, id=None, style=None, parent=None, source=None)`

arguments alias of `rinoh.image.InlineImageArgs`

`class rinoh.image.BackgroundImage (filename_or_file, scale=1.0, width=None, height=None, dpi=None, rotate=0, limit_width=<rinoh.dimension.Fraction object>, align=None, id=None, style=None, parent=None, source=None)`

Image to place in the background of a page

Takes the same arguments as [Image](#).

arguments alias of [rinoh.image.ImageArgs](#)

`class rinoh.image.ImageArgs (base=None, **attributes)`

`limit_width` Limit the image width when none of [scale](#), [width](#) and [height](#) are given and the image would be wider than the container

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 100%

align How to align the image within the page
 Accepts [HorizontalAlignment](#): left, right, center
 Default: left

file_or_filename Path to the image file (inherited from ImageArgsBase)
 Accepts [ImagePath](#): path to an image file enclosed in quotes
 Default: none

scale Scaling factor for the image (inherited from ImageArgsBase)
 Accepts [Scale](#): fit, fill or a float larger than 0
 Default: fit

width The width to scale the image to (inherited from ImageArgsBase)
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: none

height The height to scale the image to (inherited from ImageArgsBase)
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: none

dpi Overrides the DPI value set in the image (inherited from ImageArgsBase)
 Accepts [Integer](#): a natural number (positive integer)
 Default: (no value)

rotate Angle in degrees to rotate the image (inherited from ImageArgsBase)
 Accepts [Integer](#): a natural number (positive integer)
 Default: (no value)

class `rinoh.image.Scale`
 Scaling factor for images
 Can be a numerical value where a value of 1 keeps the image's original size or one of values.
 Accepts: fit, fill or a float larger than 0

class `rinoh.image.Caption` (`content`, `custom_label=None`, `id=None`, `style=None`, `parent=None`)
 style_class alias of [rinoh.image.CaptionStyle](#)
 prepare (`flowable_target`)
 Determine number labels and register references with the document

class `rinoh.image.Figure` (`flowables`, `align=None`, `width=None`, `id=None`, `style=None`, `parent=None`, `source=None`)
 style_class alias of [rinoh.image.FigureStyle](#)

class `rinoh.image.ListOfFiguresSection`
 list_class alias of [rinoh.image.ListOfFigures](#)

class `rinoh.image.ListOfFigures` (`local=False`, `id=None`, `style=None`, `parent=None`)

8.9 Index ([rinoh.index](#))

```
class rinoh.index.IndexSection ( title=None, flowables=None, style=None )
class rinoh.index.Index ( id=None, style=None, parent=None )
    style_class alias of rinoh.index.IndexStyle
    flowables ( container )
        Generator yielding the Flowables to group
class rinoh.index.IndexLabel ( text_or_items, id=None, style=None, parent=None, source=None )
class rinoh.index.IndexTerm ( *levels )
class rinoh.index.InlineIndexTarget ( index_terms, *args, **kwargs )
    to_string ( flowable_target )
        Return the text content of this styled text.
class rinoh.index.IndexTarget ( index_terms, parent=None )
    flow ( container, last_descender, state=None, **kwargs )
        Flow this flowable into container and return the vertical
        space consumed.
        The flowable's contents are preceded by a vertical space
        with a height as specified in its style's space_above
        attribute. Similarly, the flowed content is followed by a
        vertical space with a height given by the space_below style
        attribute.
```

8.10 Language ([rinoh.language](#))

```
class rinoh.language.Language ( code, name )
    Collects localized strings for a particular language
    Parameters
        • code (str) – short code identifying the language
        • name (str) – native name of the language
```

languages Dictionary mapping codes to [Languages](#)

The following languages are supported:

```
rinoh.language.EN = Language('en', 'English')
    Localized strings for English
    SectionTitles
    Contents Table of Contents
    List_of_figures List of Figures
    List_of_tables List of Tables
    Chapter Chapter
    Index Index
    AdmonitionTitles
```

Attention Attention!

Caution Caution!

Danger !DANGER!

Error Error

Hint Hint

Important Important

Note Note

Tip Tip

Warning Warning

Seealso See also

`rinoh.language.FR = Language('fr', 'Français')`

Localized strings for Français

SectionTitles

Contents Table des Matières

List_of_figures Liste des Figures

List_of_tables Liste des Tableaux

Chapter Chapitre

Index Index

AdmonitionTitles

Attention Attention!

Caution Prudence!

Danger !DANGER!

Error Erreur

Hint Conseil

Important Important

Note Note

Tip Astuce

Warning Avertissement

Seealso Voir aussi

`rinoh.language.IT = Language('it', 'Italiano')`

Localized strings for Italiano

SectionTitles

Contents Contenuti

List_of_figures Elenco delle Figure

List_of_tables Elenco delle Tabelle

Chapter Capitolo

Index Indice

AdmonitionTitles

Attention Attenzione!

Caution Prudenza!

Danger !PERICOLO!

Error Errore
 Hint Consiglio
 Important Importante
 Note Nota
 Tip Suggerimento
 Warning Avvertimento
 Seealso Vedi anche
 rinoh.language.NL = Language('nl', 'Nederlands')
 Localized strings for Nederlands
 SectionTitles
 Contents Inhoudsopgave
 List_of_figures Lijst van Figuren
 List_of_tables Lijst van Tabellen
 Chapter Hoofdstuk
 Index Index
 AdmonitionTitles
 Attention Opgelet!
 Caution Pas op!
 Danger !GEVAAR!
 Error Fout
 Hint Hint
 Important Belangrijk
 Note Noot
 Tip Tip
 Warning Waarschuwing
 Seealso Zie ook
 rinoh.language.PL = Language('pl', 'Polski')
 Localized strings for Polski
 SectionTitles
 Contents Spis Treści
 List_of_figures Spis Ilustracji
 List_of_tables Spis Tabel
 Chapter Rozdział
 Index Skorowidz
 AdmonitionTitles
 Attention Uwaga!
 Caution Ostrożnie!
 Danger !NIEBEZPIECZEŃSTWO!
 Error Błąd
 Hint Wskazówka
 Important Ważne

Note Notatka

Tip Porada

Warning Ostrzeżenie

Seealso Zobacz również

8.11 Number (rinoh.number)

Functions for formatting numbers:

- `format_number()`: Format a number according to a given style.

class rinoh.number.NumberFormat

How (or if) numbers are displayed

Accepts: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

class rinoh.number.NumberStyle (base=None, **attributes)

Style class for Number

number_format How numbers are formatted

Accepts `NumberFormat`: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: number

label_prefix Text to prepend to the label (inherited from LabelStyle)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or '), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix Text to append to the label (inherited from LabelStyle)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or '), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label Use a custom label if specified (inherited from LabelStyle)

Accepts `Bool`: true or false

Default: false

hide Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

class rinoh.number.NumberedParagraph (content, custom_label=None, id=None, style=None, parent=None)

style_class alias of rinoh.number.NumberedParagraphStyle

rinoh.number.format_number (number, format)

Format number according the given format (`NumberFormat`)

8.12 Paper sizes ([rinoh.paper](#))

The [Paper](#) class and a number of predefined paper formats.

`class rinoh.paper.Paper (name, width, height)`

Defines a paper size.

Parameters

- name ([str](#)) – the name of this paper type
- width ([Dimension](#)) – the (portrait) width of this paper type
- height ([Dimension](#)) – the (portrait) height of this paper type

```
rinoh.paper.A0 = Paper('A0', width=841*MM, height=1189*MM)
rinoh.paper.A1 = Paper('A1', width=594*MM, height=841*MM)
rinoh.paper.A2 = Paper('A2', width=420*MM, height=594*MM)
rinoh.paper.A3 = Paper('A3', width=297*MM, height=420*MM)
rinoh.paper.A4 = Paper('A4', width=210*MM, height=297*MM)
rinoh.paper.A5 = Paper('A5', width=148*MM, height=210*MM)
rinoh.paper.A6 = Paper('A6', width=105*MM, height=148*MM)
rinoh.paper.A7 = Paper('A7', width=74*MM, height=105*MM)
rinoh.paper.A8 = Paper('A8', width=52*MM, height=74*MM)
rinoh.paper.A9 = Paper('A9', width=37*MM, height=52*MM)
rinoh.paper.A10 = Paper('A10', width=26*MM, height=37*MM)
rinoh.paper.LETTER = Paper('letter', width=8.5*INCH, height=11*INCH)
rinoh.paper.LEGAL = Paper('legal', width=8.5*INCH, height=14*INCH)
rinoh.paper.JUNIOR_LEGAL = Paper('junior legal', width=8*INCH, height=5*INCH)
rinoh.paper.LEDGER = Paper('ledger', width=17*INCH, height=11*INCH)
rinoh.paper.TABLOID = Paper('tabloid', width=11*INCH, height=17*INCH)
```

8.13 Paragraph ([rinoh.paragraph](#))

`class rinoh.paragraph.ParagraphBase (align=None, width=None, id=None, style=None, parent=None, source=None)`

Base class for paragraphs

A paragraph is a collection of mixed-styled text that can be flowed into a container.

style_class alias of [rinoh.paragraph.ParagraphStyle](#)

`render (container, descender, state, space_below=0, first_line_only=False)`

Typeset the paragraph

The paragraph is typeset in the given container starting below the current cursor position of the container. When the end of the container is reached, the rendering state is preserved to continue setting the rest of the paragraph when this method is called with a new container.

Parameters

- container (Container) – the container to render to
- descender (float or None) – descender height of the preceding line
- state (ParagraphState) – the state where rendering will continue
- first_line_only (bool) – typeset only the first line

```
class rinoh.paragraph.Paragraph ( text_or_items, id=None, style=None, parent=None, source=None )
```

A paragraph of static text

Parameters

- text_or_items – see [MixedStyledText](#)
- style – see [Styled](#)
- parent – see [DocumentElement](#)

style_class alias of [rinoh.paragraph.ParagraphStyle](#)

```
class rinoh.paragraph.ParagraphState ( paragraph, words, nested_flowable_state=None, _first_word=None, _initial=True )
```

8.13.1 Styled Text ([rinoh.text](#))

```
class rinoh.text.StyledText ( id=None, style=None, parent=None, source=None )
```

Base class for text that has a [TextStyle](#) associated with it.

to_string (flowable_target)

Return the text content of this styled text.

is_script (container)

Returns True if this styled text is super/subscript.

script_level (container)

Nesting level of super/subscript.

height (container)

Font size after super/subscript size adjustment.

y_offset (container)

Vertical baseline offset (up is positive).

property items The list of items in this StyledText.

style_class alias of [rinoh.text.TextStyle](#)

```
class rinoh.text.SingleStyledText ( text, style=None, parent=None, source=None )
```

Text with a single style applied

```
class rinoh.text.MixedStyledText ( text_or_items, id=None, style=None, parent=None, source=None )
```

Concatenation of styled text

Parameters

- text_or_items (str, [StyledText](#) or iterable of these) – mixed

styled text

- style – see [Styled](#)
- parent – see `DocumentElement`

`prepare (flowable_target)`

Determine number labels and register references with the document

`append (item)` Append item ([StyledText](#) or `str`) to the end of this mixed-styled text.

The parent of item is set to this mixed-styled text.

property items The list of items in this `StyledText`.

`copy (parent=None)`

Return a shallow copy of the list.

class `rinoh.text.Locale`

Selects a language

8.13.2 Inline Elements ([rinoh.inline](#))

class `rinoh.inline.InlineFlowable` (`baseline=None`, `id=None`, `style=None`, `parent=None`, `source=None`)

`style_class` alias of [rinoh.inline.InlineFlowableStyle](#)

8.13.3 Styling Properties

class `rinoh.paragraph.TextAlign`

Text justification

Accepts: left, right, center, justify

Line Spacing

class `rinoh.paragraph.LineSpacing`

Base class for line spacing types

Line spacing is defined as the distance between the baselines of two consecutive lines of text in a paragraph.

`advance (line, last_descender, container)`

Return the distance between the descender of the previous line and the baseline of the current line.

class `rinoh.paragraph.DefaultSpacing`

The default line spacing as specified by the font.

`advance (line, last_descender, container)`

Return the distance between the descender of the previous line and the baseline of the current line.

class `rinoh.paragraph.ProportionalSpacing` (`factor`)

Line spacing proportional to the line height

Parameters `factor` ([float](#)) – amount by which the line height is multiplied to obtain the line spacing

advance (line, last_descender, container)

Return the distance between the descender of the previous line and the baseline of the current line.

class rinoh.paragraph.FixedSpacing (pitch, minimum=ProportionalSpacing(1.0))

Fixed line spacing, with optional minimum spacing

Parameters

- pitch ([Dimension](#)) – the distance between the baseline of two consecutive lines of text
- minimum ([LineSpacing](#)) – the minimum line spacing to prevents lines with large fonts (or inline elements) from overlapping; set to None if no minimum is required, set to None

advance (line, last_descender, container)

Return the distance between the descender of the previous line and the baseline of the current line.

class rinoh.paragraph.Leading (leading)

Line spacing determined by the space in between two lines

Parameters leading ([Dimension](#)) – the space between the bottom of a line and the top of the next line of text

advance (line, last_descender, container)

Return the distance between the descender of the previous line and the baseline of the current line.

The following standard line spacings have been predefined:

rinoh.paragraph.DEFAULT = DefaultSpacing()

The default line spacing as specified by the font.

rinoh.paragraph.STANDARD = ProportionalSpacing(1.2)

Line spacing of 1.2 times the line height.

rinoh.paragraph.SINGLE = ProportionalSpacing(1.0)

Line spacing equal to the line height (no leading).

rinoh.paragraph.DOUBLE = ProportionalSpacing(2.0)

Line spacing of double the line height.

Tabulation

class rinoh.paragraph.TabAlign

Alignment of text with respect to a tab stop

Accepts: left, right, center

class rinoh.paragraph.TabStop (position, align='left', fill=None)

Horizontal position for aligning text of successive lines

Parameters

- position ([Dimension](#) or [Fraction](#)) – tab stop position
- align ([TabAlign](#)) – the alignment of text with respect to the tab stop position
- fill ([str](#)) – string pattern to fill the empty tab space with

`get_position (line_width)`

Return the absolute position of this tab stop.

`class rinoh.paragraph.TabStopList (iterable=(), /)`

List of tab stop positions (with alignment and fill string)

8.13.4 Rendering Internals

`class rinoh.paragraph.Glyph (glyph, width, char)`

`class rinoh.paragraph.GlyphsSpan (span, chars_to_glyphs, glyphs_and_widths=[])`

8.13.5 Miscellaneous Internals

`class rinoh.paragraph.HyphenatorStore`

8.14 Cross-References and Fields ([rinoh.reference](#))

`class rinoh.reference.Reference (target_id, type='number', link=True, style=None, quiet=False, **kwargs)`

`class rinoh.reference.ReferenceField (type='number', link=True, quiet=False, style=None, parent=None, source=None)`

`class rinoh.reference.ReferenceText (id=None, style=None, parent=None, source=None)`

`class rinoh.reference.ReferenceType`

Accepts: reference, number, title, page

`class rinoh.reference.ReferenceParagraph (target_id_or_flowable, id=None, style=None, parent=None)`

`style_class` alias of [rinoh.reference.ReferenceParagraphStyle](#)

`target_style (document)`

Filter selection on the style attribute of the target flowable

`target_has_class (document)`

Filter selection on a class of the target flowable

`target_has_classes (document)`

Filter selection on a set of classes of the target flowable

`class rinoh.reference.Note (flowable, id=None, style=None, parent=None)`

`class rinoh.reference.RegisterNote (note, parent=None)`

`prepare (flowable_target)`

Determine number labels and register references with the document

`class rinoh.reference.NoteMarkerBase (custom_label=None, **kwargs)`

`style_class` alias of [rinoh.reference.NoteMarkerStyle](#)

`prepare (flowable_target)`

Determine number labels and register references with the document

`class rinoh.reference.NoteMarkerByID (target_id, type='number', link=True, style=None, quiet=False, **kwargs)`

```
class rinoh.reference.NoteMarkerWithNote ( referenceable, type='number', link=False,
style=None, **kwargs )
    prepare ( flowable_target )
        Determine number labels and register references with the
        document
class rinoh.reference.Field ( type, style=None )
```

8.15 Structure ([rinoh.structure](#))

8.15.1 Sections

```
class rinoh.structure.Section ( flowables, align=None, width=None, id=None, style=None,
parent=None, source=None )
    A subdivision of a document
    A section usually has a heading associated with it, which is optionally
    numbered.
class rinoh.structure.Heading ( title, custom_label=None, id=None, style=None, parent=None )
    The title for a section
    Parameters
        • title (StyledText) – the title text
        • custom_label (StyledText) – a frontend can supply a custom
        label to use instead of an automatically determined section
        number
    style_class alias of rinoh.structure.HeadingStyle
    prepare ( flowable_target )
        Determine number labels and register references with the
        document
    flow ( container, last_descender, state=None, **kwargs )
        Flow this flowable into container and return the vertical
        space consumed.
        The flowable's contents are preceded by a vertical space
        with a height as specified in its style's space_above
        attribute. Similarly, the flowed content is followed by a
        vertical space with a height given by the space_below style
        attribute.
class rinoh.structure.SectionTitles ( **strings )
    Collection of localized titles for common sections
    contents Title for the table of contents section
        Type String
    list_of_figures Title for the list of figures section
        Type String
    list_of_tables Title for the list of tables section
        Type String
    chapter Label for top-level sections
```

Type [String](#)
index Title for the index section
Type [String](#)

8.15.2 Lists

```
class rinoh.structure.List ( list_items, start_index=1, id=None, style=None, parent=None )
    style_class alias of rinoh.structure.ListStyle
class rinoh.structure.DefinitionList ( flowables, align=None, width=None, id=None, style=None,
parent=None, source=None )
```

8.15.3 Table of Contents

```
class rinoh.structure.TableOfContentsSection
class rinoh.structure.TableOfContents ( local=False, id=None, style=None, parent=None )
    style_class alias of rinoh.structure.TableOfContentsStyle
    flowables ( container )
        Generator yielding the Flowables to group
class rinoh.structure.TableOfContentsEntry ( flowable, id=None, style=None, parent=None )
    style_class alias of rinoh.structure.TableOfContentsEntryStyle
```

8.15.4 Admonitions

```
class rinoh.structure.Admonition ( flowables, title=None, type=None, id=None, style=None,
parent=None )
    style_class alias of rinoh.structure.AdmonitionStyle
    flowables ( container )
        Generator yielding the Flowables to group
class rinoh.structure.AdmonitionTitles ( **strings )
    Collection of localized titles for common admonitions
    attention Title for attention admonitions
        Type String
    caution Title for caution admonitions
        Type String
    danger Title for danger admonitions
        Type String
    error Title for error admonitions
        Type String
    hint Title for hint admonitions
        Type String
    important Title for important admonitions
        Type String
    note Title for note admonitions
```

Type [String](#)
tip Title for tip admonitions
Type [String](#)
warning Title for warning admonitions
Type [String](#)
seealso Title for see-also admonitions
Type [String](#)

8.15.5 Horizontal Rule

```
class rinoh.structure.HorizontalRule ( align=None, width=None, id=None, style=None,
parent=None, source=None )
```

style_class alias of [rinoh.structure.HorizontalRuleStyle](#)

```
render ( container, descender, state, **kwargs )
```

Renders the flowable's content to container, with the flowable's top edge lining up with the container's cursor. descender is the descender height of the preceding line or None.

8.16 Strings ([rinoh.strings](#))

```
class rinoh.strings.String ( description )
```

Descriptor used to describe a configurable string

Parameters description ([str](#)) – a short description for this string

```
class rinoh.strings.StringCollection ( **strings )
```

A collection of related configurable strings

Subclasses

- [AdmonitionTitles](#)
- [SectionTitles](#)
- [UserStrings](#)

```
class rinoh.strings.UserStrings ( **strings )
```

Collection of user-specified strings

Unlike other string collections, these are not limited to a predefined set.

Attributes:

```
class rinoh.strings.Strings ( *string_collections )
```

Stores several [StringCollections](#)

```
class rinoh.strings.StringField ( strings_class, key, style=None, parent=None )
```

Styled text that will be substituted with a configured string

The displayed string is either the localized string as determined by the language set for the document or the user-supplied string passed to the [TemplateConfiguration](#).

8.17 Style (rinoh.style)

class rinoh.style.Styled (id=None, style=None, parent=None, source=None)

A document element who's style can be configured.

Parameters style ([str](#), [Style](#)) – the style to associate with this element. If style is a string, the corresponding style is lookup up in the document's style sheet by means of selectors.

style_class The [Style](#) subclass that corresponds to this [Styled](#) subclass.

property has_class

Filter selection on a class of this [Styled](#)

property has_classes

Filter selection on a set of classes of this [Styled](#)

class rinoh.style.Style (base=None, **attributes)

Dictionary storing style attributes.

The style attributes associated with this [Style](#) are specified as class attributes of type [Attribute](#).

Style attributes can also be accessed as object attributes.

hide Suppress rendering this element

Accepts [Bool](#): true or false

Default: false

8.17.1 Style Sheet

class rinoh.style.StyleSheet (name, matcher=None, base=None, source=None, description=None, pygments_style=None, **user_options)

Dictionary storing a collection of related styles by name.

[Styles](#) stored in a [StyleSheet](#) can refer to their base style by name.

Parameters

- name ([str](#)) – a label for this style sheet
- matcher ([StyledMatcher](#)) – the matcher providing the selectors the styles contained in this style sheet map to. If no matcher is given and base is specified, the base's matcher is used. If base is not set, the default matcher is used.
- base ([StyleSheet](#) or [str](#)) – the style sheet to extend
- description ([str](#)) – a short string describing this style sheet
- pygments_style ([str](#)) – the Pygments style to use for styling code blocks

get_selector (name)

Find a selector mapped to a style in this or a base style sheet.

Parameters name ([str](#)) – a style name

Returns Selector – the selector mapped to the style name

Raises [KeyError](#) – if the style name was not found in this or a base style sheet

`class rinoh.style.StyleSheetFile (filename, base=None, source=None, **kwargs)`

Loads styles defined in a .rts file (INI format).

Parameters filename ([str](#)) – the path to the style sheet file

[StyleSheetFile](#) takes the same optional arguments as [StyleSheet](#). These can also be specified in the [STYLESHEET] section of the style sheet file. If an argument is specified in both places, the one passed as an argument overrides the one specified in the style sheet file.

`class rinoh.style.StyledMatcher (mapping_or_iterable=None, **kwargs)`

Dictionary mapping labels to selectors.

This matcher can be initialized in the same way as a [dict](#) by passing a mapping, an iterable and/or keyword arguments.

`update (**F [, E]) → None`. Update D from dict/iterable E and F.

If E is present and has a .keys() method, then does: for k in E: D[k] = E[k] If E is present and lacks a .keys() method, then does: for k, v in E: D[k] = v In either case, this is followed by: for k in F: D[k] = F[k]

8.18 Tables ([rinoh.table](#))

`class rinoh.table.Table (body, head=None, align=None, width=None, column_widths=None, id=None, style=None, parent=None)`

style_class alias of [rinoh.table.TableStyle](#)

`prepare (flowable_target)`

Determine number labels and register references with the document

`render (container, last_descender, state, space_below=0, **kwargs)`

Renders the flowable's content to container, with the flowable's top edge lining up with the container's cursor. descender is the descender height of the preceding line or None.

`class rinoh.table.TableWithCaption (flowables, align=None, width=None, id=None, style=None, parent=None, source=None)`

style_class alias of [rinoh.table.TableWithCaptionStyle](#)

`class rinoh.table.TableSection (rows, style=None, parent=None)`

`prepare (flowable_target)`

Determine number labels and register references with the document

`class rinoh.table.TableHead (rows, style=None, parent=None)`

`class rinoh.table.TableBody (rows, style=None, parent=None)`

`class rinoh.table.TableRow (cells, style=None, parent=None)`

`prepare (flowable_target)`

Determine number labels and register references with the document

```

get_rowspanned_columns ( )
    Return a dictionary mapping column indices to the
    number of columns spanned.

class rinoh.table.TableCell ( flowables, rowspan=1, colspan=1, id=None, style=None,
parent=None )
    style_class alias of rinoh.table.TableCellStyle

class rinoh.table.TableCellBorder ( rendered_cell, cell_height, position, style=None )
    style_class alias of rinoh.table.TableCellBorderStyle

class rinoh.table.TableCellBackground ( bottom_left, width, height, style=None, parent=None )
    style_class alias of rinoh.table.TableCellBackgroundStyle

class rinoh.table.VerticalAlign
    Accepts: top, middle, bottom

class rinoh.table.ListOfTables ( local=False, id=None, style=None, parent=None )

class rinoh.table.ListOfTablesSection
    list_class alias of rinoh.table.ListOfTables

```

8.19 Templates ([rinoh.template](#))

Document templates are created by subclassing [DocumentTemplate](#), just like the [standard templates](#) shipped with rinohtype.

```

class rinoh.template.DocumentTemplate ( document_tree, configuration=None, backend=None
)

```

Template for documents

Parameters

- `document_tree` ([DocumentTree](#)) – a tree of the document’s contents
- `configuration` ([TemplateConfiguration](#)) – configuration for this template
- `backend` – the backend used for rendering the document

`language` The main language of the document

Accepts [Language](#): the code of one of the [supported languages](#)

Default: [EN](#) (English)

`strings` Strings to override standard element names

Accepts [Strings](#): strings need to be entered in INI sections named after the [StringCollection](#) subclasses

Default: none

`stylesheet` The stylesheet to use for styling document elements

Accepts [StyleSheet](#): the name of an [installed style sheet](#) or the file-name of a stylesheet file (with the `.rts` extension)

Default: sphinx (= [rinoh.stylesheets.sphinx](#))

`parts` The parts making up this document

Accepts [PartsList](#): a space-separated list of document part template names

Default: (empty list)

Configuration alias of `rinoh.template.DocumentTemplateConfiguration`

ConfigurationFile alias of `rinoh.template.DocumentTemplateConfigurationFile`

Document templates can be customized by setting values for the configuration attributes defined in a `DocumentTemplate` subclass in a `TemplateConfiguration`. An template configuration can be passed as configuration on template instantiation. However, it is better to make use of the `document` method, however.

```
class rinoh.template.TemplateConfiguration ( name, base=None, source=None, template=None,
description=None, **options )
```

Stores a configuration for a `DocumentTemplate`

Parameters

- name (`str`) – a label for this template configuration
- base (`TemplateConfiguration`) – the template configuration to extend
- template (`DocumentTemplateMeta` or `str`) – the document template to configure
- description (`str`) – a short string describing this style sheet
- **options – configuration values for the configuration attributes defined by the document `template`

template = None The `DocumentTemplate` subclass to configure

document (document_tree, backend=None)

Create a `DocumentTemplate` object based on the given document tree and this template configuration

Parameters

- document_tree (`DocumentTree`) – tree of the document's contents
- backend – the backend to use when rendering the document

```
class rinoh.template.PartsList ( *parts )
```

Stores the names of the document part templates making up a document

Parameters *parts (`list[str]`) – the names of the document parts

8.19.1 Document Parts

```
class rinoh.template.DocumentPart ( template, document, flowables )
```

Part of a document.

Parameters

- template (`DocumentPartTemplate`) – the template that determines the contents and style of this document part
- document (`Document`) – the document this part belongs to
- flowables (`list[Flowable]`) – the flowables to render in this document part

configuration_class

alias of [rinoh.template.DocumentPartTemplate](#)

add_page (page)

Append page (Page) to this [DocumentPart](#).

new_page (page_number, new_chapter, **kwargs)

Called by render() with the Chain's that need more :class:`Container`s. This method should create a new :class:`Page` which contains a container associated with chain.

The document part templates which are listed by name in [DocumentTemplate.parts](#) are looked up as attributes of the [DocumentTemplate](#) subclass. They are instances of [DocumentPartTemplate](#) subclasses:

class rinoh.template.DocumentPartTemplate (base=None, **attributes)

A template that produces a document part

The document part is created given a set of flowables, and page templates. The latter are looked up in the [TemplateConfiguration](#) where this part template was.

page_number_format

The format for page numbers in this document part. If it is different from the preceding part's number format, numbering restarts at 1

Accepts [NumberFormat](#): none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: number

end_at_page The type of page to end this document part on

Accepts [PageType](#): left, right, any

Default: any

drop_if_empty Exclude this part from the document if it is empty (no flowables)

Accepts [Bool](#): true or false

Default: true

The following document part templates are used in the standard document templates:

class rinoh.template.TitlePartTemplate (base=None, **attributes)

The title page of a document.

drop_if_empty Overrides the default set in [DocumentPartTemplate](#)

Accepts [Bool](#): true or false

Default: false

page_number_format

The format for page numbers in this document part. If it is different from the preceding part's number format, numbering restarts at 1 (inherited from [DocumentPartTemplate](#))

Accepts [NumberFormat](#): none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: number

end_at_page The type of page to end this document part on (inherited from [DocumentPartTemplate](#))

Accepts [PageType](#): left, right, any

Default: any

class rinoh.template.ContentsPartTemplate (base=None, **attributes)

The body of a document.

Renders all of the content present in the [DocumentTree](#) passed to the [DocumentTemplate](#).

page_number_format

The format for page numbers in this document part. If it is different from the preceding part's number format, numbering restarts at 1 (inherited from [DocumentPartTemplate](#))

Accepts [NumberFormat](#): none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: number

end_at_page The type of page to end this document part on (inherited from [DocumentPartTemplate](#))

Accepts [PageType](#): left, right, any

Default: any

drop_if_empty Exclude this part from the document if it is empty (no flowables) (inherited from [DocumentPartTemplate](#))

Accepts [Bool](#): true or false

Default: true

class rinoh.template.FixedDocumentPartTemplate (base=None, **attributes)

A document part template that renders a fixed list of flowables

flowables The list of flowables to include in this document part

Accepts FlowablesList: Python source code that represents a list of [Flowables](#)

Default: []

page_number_format

The format for page numbers in this document part. If it is different from the preceding part's number format, numbering restarts at 1 (inherited from [DocumentPartTemplate](#))

Accepts [NumberFormat](#): none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: number

end_at_page The type of page to end this document part on (inherited from [DocumentPartTemplate](#))

Accepts [PageType](#): left, right, any

Default: any

`drop_if_empty` Exclude this part from the document if it is empty (no flowables) (inherited from [DocumentPartTemplate](#))
Accepts [Bool](#): true or false
Default: true

8.19.2 Page Templates

The document templates make use of page templates:

```
class rinoh.template.PageTemplate ( base=None, **attributes )
```

`header_footer_distance`

Distance of the header and footer to the content area

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 14pt

`columns` The number of columns for the body text

Accepts [Integer](#): a natural number (positive integer)

Default: 1

`column_spacing` The spacing between columns

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 1cm

`header_text` The text to place in the page header

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: '{SECTION_NUMBER}' ' '{SECTION_TITLE}'

`footer_text` The text to place in the page footer

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: '\t' '{PAGE_NUMBER}' '/' '{NUMBER_OF_PAGES}'

`chapter_header_text`

The text to place in the header on a page that starts a new chapter

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

`chapter_footer_text`

The text to place in the footer on a page that starts a new chapter

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "),

optionally followed by a style name enclosed in braces:
 'text string' (style name)
 Default: (no value)

chapter_title_flowables
 Generator that yields the flowables to represent the chapter title
 Accepts **FlowablesList**: Python source code that represents a list of **Flowables**
 Default: none

chapter_title_height
 The height of the container holding the chapter title
 Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 150pt

page_size The format of the pages in the document (inherited from **PageTemplateBase**)
 Accepts **Paper**: the name of a **predefined paper format** or <width> * <height> where width and height are **Dimensions**
 Default: A4

page_orientation The orientation of pages in the document (inherited from **PageTemplateBase**)
 Accepts **PageOrientation**: portrait, landscape
 Default: portrait

left_margin The margin size on the left of the page (inherited from **PageTemplateBase**)
 Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 3cm

right_margin The margin size on the right of the page (inherited from **PageTemplateBase**)
 Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 3cm

top_margin The margin size at the top of the page (inherited from **PageTemplateBase**)
 Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 3cm

bottom_margin The margin size at the bottom of the page (inherited from **PageTemplateBase**)
 Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 3cm

background An image to place in the background of the page (inherited from **PageTemplateBase**)
 Accepts **BackgroundImage**: filename of an image file enclosed in

quotes, optionally followed by space-delimited keyword arguments (<keyword>=<value>) that determine how the image is displayed

Default: none

after_break_background

An image to place in the background after a page break (inherited from [PageTemplateBase](#))

Accepts [BackgroundImage](#): filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (<keyword>=<value>) that determine how the image is displayed

Default: none

class rinoh.template.TitlePageTemplate (base=None, **attributes)

show_date Show or hide the document's date

Accepts [Bool](#): true or false

Default: true

show_author Show or hide the document's author

Accepts [Bool](#): true or false

Default: true

extra Extra text to include on the title page below the title

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

page_size The format of the pages in the document (inherited from [PageTemplateBase](#))

Accepts [Paper](#): the name of a [predefined paper format](#) or <width> * <height> where width and height are [Dimensions](#)

Default: A4

page_orientation The orientation of pages in the document (inherited from [PageTemplateBase](#))

Accepts [PageOrientation](#): portrait, landscape

Default: portrait

left_margin The margin size on the left of the page (inherited from [PageTemplateBase](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 3cm

right_margin The margin size on the right of the page (inherited from [PageTemplateBase](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 3cm

top_margin The margin size at the top of the page (inherited from [PageTemplateBase](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in,

pc, mm, cm, %, /4)

Default: 3cm

bottom_margin The margin size at the bottom of the page (inherited from [PageTemplateBase](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 3cm

background An image to place in the background of the page (inherited from [PageTemplateBase](#))

Accepts [BackgroundImage](#): filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (<keyword>=<value>) that determine how the image is displayed

Default: none

after_break_background

An image to place in the background after a page break (inherited from [PageTemplateBase](#))

Accepts [BackgroundImage](#): filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (<keyword>=<value>) that determine how the image is displayed

Default: none

The base class for these collects the common options:

`class rinoh.template.PageTemplateBase (base=None, **attributes)`

page_size The format of the pages in the document

Accepts [Paper](#): the name of a [predefined paper format](#) or <width> * <height> where width and height are [Dimensions](#)

Default: A4

page_orientation The orientation of pages in the document

Accepts [PageOrientation](#): portrait, landscape

Default: portrait

left_margin The margin size on the left of the page

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 3cm

right_margin The margin size on the right of the page

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 3cm

top_margin The margin size at the top of the page

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 3cm

bottom_margin The margin size at the bottom of the page

Accepts [Dimension](#): a numeric value followed by a unit (pt,

in, pc, mm, cm, %, /4)

Default: 3cm

background An image to place in the background of the page

Accepts [BackgroundImage](#): filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (<keyword>=<value>) that determine how the image is displayed

Default: none

after_break_background

An image to place in the background after a page break

Accepts [BackgroundImage](#): filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (<keyword>=<value>) that determine how the image is displayed

Default: none

Frequently Asked Questions

9

This is a list of commonly encountered problems and solutions to them.

PDFs produced by rinohtype contain mostly empty pages. What's up? Old versions of some PDF viewers do not support the way rinohtype embeds fonts in a PDF (see [issue 2](#)). PDF viewers that are known to be affected are:

- pre-37.0 Firefox's built-in PDF viewer (pdf.js)
- pre-0.41 [poppler](#)-based applications such as Evince

Installing rinohtype using pip fails with rinohtype requires Python 3.5 or higher rinohtype only works on Python 3.5 or higher. Make sure the pip you are using is one from a Python 3.5+ installation using `pip --version`. On some operating systems, you may need to use `pip3`.

10.1 Release 0.5.0-dev

New Features:

- Google Fonts: if a specified typeface is not installed, rinohtype attempts to download the corresponding fonts from Google Fonts. Simply supply the font name as listed on <https://fonts.google.com> as a value for the typeface style property.
- Table: in addition to fixed and relative-width columns, you can indicate columns to be automatically sized by specifying a value of 'auto' in the 'column_widths' style parameter in your style sheet.
- docutils frontend: support the :align: option to table directives, which will override the alignment set for the table in the style sheet.
- The starting number of enumerated lists in reStructuredText is respected.
- Sphinx frontend: the rinohtype_metadata configuration variable allows overriding the document's subtitle (and other strings) that are used on the title page and elsewhere in the document template (PR #182 by Alex Fergus).
- Table column widths can be specified in the style sheet, which take effect when these haven't been specified in the source document.
- Document elements now store where they have been defined (document tree, style sheet file or template configuration file); when you specify relative paths (e.g. for images), they are interpreted relative to the location of their source. This should make things more intuitive.
- The page_break style attribute is no longer reserved for sections; a page break can be forced before any flowable.
- Enumerated list items with a hidden label ('hide' style attribute) are no longer counted in the numbering.
- Templates and typefaces can be registered by name at runtime. This makes them referencable from template configuration and style sheet files. For example, custom templates/-typefaces can be imported in a Sphinx project's conf.py (to be documented).
- It's now possible to add arbitrary reStructuredText content to the front/back matter or elsewhere by adding a .. container:: with the 'out-of-line' class and a :name: to reference it by in the document template configuration, e.g. in the list of front matter flowables (to be documented).

- Selectors in style sheet files (.rts) now support boolean and 'None' values. For example, you can select StaticGroupedFlowables based on whether they have any children or not: e.g TableCell(empty=true) selects empty table cells.
- The document's title and author are now stored in the PDF metadata.
- "0" is now accepted as a valid value for Dimension-type attributes in style sheets and template configurations.

Changed:

- Rendering speed was more than doubled (caching)! (PR #197 by Alex Fargus)
- Sphinx frontend: rinoh_documents now takes a list of dictionaries, one for each PDF document to be built. This allows selecting e.g. the template and logo on a per-document level. Support for rinoh_template, rinoh_stylesheet, rinoh_paper_size, rinoh_domain_indices and rinoh_logo was removed. Also, only fallback to `latex_documents` is retained. (PR #192, #195, #208 and #216 by Alex Fargus)
- The default stylesheet ('Sphinx') now prevents captions from being separated from their image/table/code block (across pages).
- Font weights and widths are now internally represented by integer classes. In addition to integer values, string values are still accepted (mapped to classes).
- OpenTypeFont now determines the font weight, slant and width from the file. For backward compatibility, it still accepts these as arguments on instantiation but warns when they don't match the values stored in the font.

Fixed:

- Table column width determination was overhauled. Now fixed-width tables are supported and automatic-width columns should be handled better.
- The 'nested bulleted/enumerated list' selectors were broken; their corresponding styles were never applied
- Items inside a table cannot be referenced (issue #174)
- Sphinx frontend: fix handling of relative image paths in .rst files inside a directory in the Sphinx project root
- rinoh: fix --install-resources (broken since PyPI disabled XMLRPC searches)
- GroupedLabeledFlowables: respect label_min_width and fix a crash with respect to space_below handling
- Duplicate rendering of content in columns; if content was too small to fill the first column, it was rendered again in subsequent columns.
- Crash on encountering a style for which no selector is defined.

10.2 Release 0.4.2 (2020-07-28)

New Features:

- before/after style attributes for StyledText (issue #158)

- docutils/Sphinx frontend: don't abort on encountering `math/math_block`, output the (LaTeX) math markup instead, along with printing a warning.
- docutils frontend: raw inline text (with `:format: 'rinoh'`) is parsed as styled text

Fixed:

- crash when the 'contents' topic has multiple IDs (issue #173)
- loading of the references cache (issue #170)
- some issues with `space_below` handling

10.3 Release 0.4.1 (2020-07-01)

New Features:

- UserStrings: arbitrary user-defined strings that can be defined in the template configuration or as a substitution definition in `reStructuredText`
- strings in a `StringCollection` can now be styled text
- Sphinx frontend: use the `today` and `today_fmt` configuration variables for the date on the title page
- Sphinx frontend: allow extensions access to the builder object (issue #155)
- rinoh: `--output` writes the output PDF to a specified location

Fixed:

- Regression in handling images that don't fit on the current page (issue #153)
- Fix crash when rendering local table of contents (issue #160)
- Sphinx frontend: support `code-block/literalinclude` with caption (issue #128)
- rinoh: variables set in a template configuration file are sometimes ignored (issue #164)
- Crash when using a font that contains unsupported lookups (issue #141)

10.4 Release 0.4.0 (2020-03-05)

New Features:

- automatically generated lists of figures and tables
- paragraphs now provide default tab stops (proportional to font size) for indentation
- stylesheet (.rts) and template configuration (.rtt) files now support specifying inline and background images (#107 and #108); to be documented
- it is now possible to specify selector priority (+-) in style sheets
- Sphinx frontend: the rinoh builder can be discovered by entry point (no more need to add 'rinoh.frontend.sphinx' to the list of extensions)

- rinoh: set a return code of 1 when one or more referenced images could not be found (issue #104)
- rinoh: introduce the `--install-resources` option to control the automatic installation of resources from PyPI
- German locale (contributed by Michael Kaiser)
- Polish locale (contributed by Mariusz Jamro)

Changed:

- Python 3.3 & 3.4 are no longer supported since they have reached end-of-life
- remove the dependency on purepng by embedding its png.py
- limit the width of images to the available width by default
- XML frontend: special case mixed content nodes
- fixes in the design of stylesheet/template code

Fixed:

- various regressions (PR #142 by Norman Lorrain)
- fix issues with variables defined in a base style sheet/template config
- various footnote rendering issues
- border width is also taken into account for flowables that are continued on a new page (#127)
- Sphinx: handle case when `source_suffix` is a list (PR #110 by Nick Barrett)
- incompatibility with Sphinx 1.6.1+ (`latex_paper_size`)
- docutils: crash when a footnote is defined in an admonition (issue #95)
- docutils: crash on encountering a raw text role (issue #99)
- docutils: ‘decoration’ node (header/footer) is not yet supported (issue #112)
- crash when a table cell contains (only) an image
- colours of PNG images with gamma (gAMA chunk) set are incorrect (#102)
- Sphinx: image paths with wildcard extension are not supported (#119)
- GroupedFlowables: `space_below` should only be considered at the end
- adapt to PEP 479 (Change StopIteration handling inside generators), the default in Python 3.7 (issue #133)
- fix compatibility with Python 3.6.7 and 3.7.1 (tokenizer changes)
- fix crash caused by Python 3.8’s changes to `int.__str__`

10.5 Release 0.3.1 (2016-12-19)

New Features:

- rinoh is now also available as a stand-alone application for both Windows (installer) and macOS (app); they include an embedded CPython installation
- index terms can be StyledText now (in addition to str)
- the 'document author' metadata entry can now be displayed using a Field
- Sphinx frontend: support the 'desc_signature_line' node (new in Sphinx 1.5)
- rinoh -docs: open the online documentation in the default browser

Changed:

- more closely mimic the Sphinx LaTeX builder's title page (issue #60)
- there is no default for PageTemplate.chapter_title_flowables anymore since they are specific to the document template

Fixed:

- handle StyledText metadata (such as document title)
- Sphinx frontend: support the 'autosummary_toc' node
- DummyFlowable now sticks to the flowable following it (keep_with_next), so that (1) it does not break this behavior of Heading preceding it, and (2) IndexTargets do not get separated from the following flowable
- bug in LabeledFlowable that broke keep_with_next behavior
- the descender size of the last flowable in a GroupedFlowables with keep_with_next=True was getting lost
- GroupedFlowables should not mark the page non-empty; this caused empty pages before the first chapter if it is preceded by grouped DummyFlowables

10.6 Release 0.3.0 (2016-11-23)

New Features:

- support localization of standard document strings (en, fr, it, nl) (#53)
- localized strings can be overridden in the document template configuration
- make use of a fallback typeface when a glyph is not available (#55) (the 'fallback' style in the Sphinx stylesheet sets the fallback typeface)
- template configuration (INI) files: specify which document parts to include, configure document part and page templates, customize localized strings, ...
- support specifying more complex selectors directly in a style sheet file

- (figure and table) captions support hierarchical numbering (see `CaptionStyle`)
- make the frontends independent of the current working directory
- `reStructuredText`: support the `table :widths:` option (upcoming `docutils` 0.13)
- Sphinx frontend: provide styles for Sphinx’s inline markup roles
- `rinoh` (command line renderer):
 - support template configuration files
 - support file formats for which a frontend is installed (see `-list-formats`)
 - accept options to configure the frontend (see `-list-options`)
 - option to list the installed fonts (on the command line or in a PDF file)
- show the current page number as part of the rendering progress indicator
- Book template: support for setting a cover page
- frontends: raise a more descriptive exception when a document tree node is not mapped
- validate the default value passed to an `Attribute`
- preliminary support for writing a style sheet to an INI file, listing default values for non-specified attributes (#23)

Changed:

- `rinoh`: the output PDF is now placed in the current directory, not in the same directory as the input file
- Sphinx builder configuration: replace the `rinoh_document_template` and `rinoh_template_`-configuration options with `rinoh_template`
- if no base is given for a style, style attribute lookup proceeds to look in the style of the same name in the base style sheet (#66)
- `DEFAULT_STYLE` can be used as a base style to prevent style attribute lookup in the style of the same name in the base style sheet
- rename `FieldList` to `DefinitionList` and use it to replace uses (`docutils` and Sphinx frontends) of the old `DefinitionList` (#54)
- the new `DefinitionList` (`FieldList`) can be styled like the old `DefinitionList` by setting `max_label_width` to `None`, 0 or a 0-valued `Dimension`
- figures are now non-floating by default (float placement needs more work)
- hide the index chapter when there are no index entries (#51)
- style sheets: use the default matcher if none is specified
- Sphinx style sheet: copy the admonition style from the Sphinx LaTeX builder
- Sphinx style sheet: keep the admonition title together with the body
- Sphinx style sheet: color linked references as in the LaTeX output (#62)

- Sphinx style sheet: disable hyphenation/ligatures for literal strong text
- no more DocumentSection; a document now consists of parts (containing pages)
- template configuration:
 - refer to document part templates by name so that they can be replaced
 - the list of document parts can be changed in the template configuration
 - document parts take the 'end_at_page' option (left, right, or any)
 - find (left/right) page templates via the document part name they belong to
 - fall back to <doc_part>_page when the right or left template is not found
 - each template configuration requires a name
- DocumentTree: make the source_file argument optional
- don't abort when the document section hierarchy is missing levels (#67)
- use the PDF backend by default (no need to specify it)
- store the unit with Dimension instances (better printing)
- rename the float module to image

Fixed:

- improve compatibility with Windows: Windows path names and file encoding
- crash if a StyledText is passed to HeadingStyle.number_separator
- GroupedLabeledFlowables label width could be unnecessarily wide
- fix and improve automatic table column sizing
- Figures can now be referenced using the 'reference' format ("Figure 1.2")
- HorizontallyAlignedFlowable: make more robust
- make document elements referenceable by secondary IDs
- reStructuredText: only the first classifier for a definition term was shown
- Sphinx frontend: support the 'centered' directive
- Sphinx frontend: basic support for the 'hlist' directive
- Sphinx frontend: handle :abbr: without explanation
- Sphinx frontend: support nested inline nodes (guilabel & samp roles)
- PDF backend: fix writing of Type 1 fonts from a parsed PDF file
- PDF reader: handle multi-page PDFs (#71)
- PDF reader: fix parsing of XRef streams
- PDF reader: fix writing of parsed files

10.7 Release 0.2.1 (2016-08-18)

New Features:

- optionally limit the width of large images and make use of this to simulate the Sphinx LaTeX builder behavior (#46)
- reStructuredText/Sphinx: support for images with hyperlinks (#49)
- record the styled page numbers in the PDF as page labels (#41)
- unsupported Python versions: prevent installation where possible (sdist) or exit on import (wheel)
- support Python 3.6

Bugfixes:

- make StyleSheet objects picklable so the Sphinx builder's `rinoh_stylesheet` option can actually be used
- Fix #47: `ClassNotFound` exception in `Literal_Block.lexer_getter()`
- Fix #45: Images that don't fit are still placed on the page
- don't warn about duplicate style matches that resolve to the same style

10.8 Release 0.2.0 (2016-08-10)

Styling:

- generate a style log (show matching styles) to help style sheet development
- `keep_with_next` style attribute: prevent splitting two flowables across pages
- stylesheets can be loaded from files in INI format
- check the type of attributes passed to styles
- source code highlighting using Pygments
- table of contents entries can be styled more freely
- allow hiding the section numbers of table of contents entries
- allow for custom chapter titles
- selectors can now also select based on document part/section
- various small tweaks to selectors and matchers
- various fixes relating to style sheets

Templates:

- configurable standard document templates: article and book

- a proper infrastructure for creating custom document templates
- support for left/right page templates
- make the Article template more configurable
- pages now have background, content and header/footer layers
- support for generating an index
- make certain strings configurable (for localization, for example)

Frontends:

- Sphinx: interpret the LaTeX configuration variables if the corresponding rinohtype variable is not set
- Sphinx: roughly match the LaTeX output (document template and style sheet)
- added a CommonMark frontend based on recommonmark
- added basic ePUB and DocBook frontends
- XML frontends: fix whitespace handling
- frontends now return generators yielding flowables (more flexible)

Command-line Renderer (rinoh):

- allow specifying a template and style sheet
- automatically install typefaces used in the style sheet from PyPI

Fonts:

- typefaces are discovered/loaded by entry point
- more complete support for OpenType fonts
- fix support for the 14 base Type 1 fonts

Images:

- more versatile image sizing: absolute width/height & scaling
- allow specifying the baseline for inline images
- several fixes in the JPEG reader

Miscellaneous:

- reorganize the Container class hierarchy
- fixes in footnote handling
- drop Python 3.2 support (3.3, 3.4 and 3.5 are supported)

10.9 Release 0.1.3 (2015-08-04)

- recover from the slow rendering speed caused by a bugfix in 0.1.2 (thanks to optimized element matching in the style sheets)
- other improvements and bugfixes related to style sheets

10.10 Release 0.1.2 (2015-07-31)

- much improved Sphinx support (we can now render the Sphinx documentation)
- more complete support for reStructuredText (docutils) elements
- various fixes related to footnote placement
- page break option when starting a new section
- fixes in handling of document sections and parts
- improvements to section/figure/table references
- native support for PNG and JPEG images (drops PIL/Pillow requirement, but adds PurePNG 0.1.1 requirement)
- new ‘sphinx’ stylesheet used by the Sphinx builder (~ Sphinx LaTeX style)
- restores Python 3.2 compatibility

10.11 Release 0.1.1 (2015-04-12)

First preview release

Python Module Index

r

rhino

- rhino.attribute, 111
- rhino.color, 111
- rhino.dimension, 112
- rhino.document, 113
- rhino.draw, 114
- rhino.flowable, 115
- rhino.font, 117
- rhino.font.style, 119
- rhino.image, 119
- rhino.index, 121
- rhino.inline, 127
- rhino.language, 121
- rhino.number, 124
- rhino.paper, 125
- rhino.paragraph, 125
- rhino.reference, 129
- rhino.strings, 132
- rhino.structure, 130
- rhino.style, 133
- rhino.stylesheets, 33
- rhino.table, 134
- rhino.template, 135
- rhino.templates.article, 105
- rhino.templates.book, 107
- rhino.text, 126

Index

Symbols

- docs
 - rinoh command line option, 32
- format <format>
 - rinoh command line option, 31
- help
 - rinoh command line option, 31
- install-resources
 - rinoh command line option, 31
- list-fonts <filename>
 - rinoh command line option, 32
- list-formats
 - rinoh command line option, 32
- list-options <frontend>
 - rinoh command line option, 32
- list-stylesheets
 - rinoh command line option, 31
- list-templates
 - rinoh command line option, 31
- option <option=value>
 - rinoh command line option, 31
- output <filename or directory>
 - rinoh command line option, 31
- paper <paper>
 - rinoh command line option, 31
- stylesheet <name or filename>
 - rinoh command line option, 31
- template <name or filename>
 - rinoh command line option, 31
- version
 - rinoh command line option, 32
- f <format>
 - rinoh command line option, 31
- h
 - rinoh command line option, 31
- i
 - rinoh command line option, 31
- O <filename or directory>
 - rinoh command line option, 31
- o <option=value>
 - rinoh command line option, 31
- p <paper>

rinoh command line option, 31
-s <name or filename>
rinoh command line option, 31
-t <name or filename>
rinoh command line option, 31

A

A0 (in module rinoh.paper), 125
A1 (in module rinoh.paper), 125
A10 (in module rinoh.paper), 125
A2 (in module rinoh.paper), 125
A3 (in module rinoh.paper), 125
A4 (in module rinoh.paper), 125
A5 (in module rinoh.paper), 125
A6 (in module rinoh.paper), 125
A7 (in module rinoh.paper), 125
A8 (in module rinoh.paper), 125
A9 (in module rinoh.paper), 125
abstract_location (rinoh.templates.article.Article attribute), 106
AbstractLocation (class in rinoh.templates.article), 106
AcceptNoneAttributeType (class in rinoh.attribute), 111
add_page() (rinoh.template.DocumentPart method), 137
Admonition (class in rinoh.structure), 131
AdmonitionStyle (class in rinoh.structure), 96
AdmonitionTitles (class in rinoh.structure), 131
advance() (rinoh.paragraph.DefaultSpacing method), 127
advance() (rinoh.paragraph.FixedSpacing method), 128
advance() (rinoh.paragraph.Leading method), 128
advance() (rinoh.paragraph.LineSpacing method), 127
advance() (rinoh.paragraph.ProportionalSpacing method), 128
after (rinoh.image.CaptionStyle attribute), 55
after (rinoh.inline.InlineFlowableStyle attribute), 68
after (rinoh.paragraph.ParagraphStyle attribute), 64
after (rinoh.reference.NoteMarkerStyle attribute), 73
after (rinoh.reference.ReferencingParagraphStyle attribute), 72
after (rinoh.structure.HeadingStyle attribute), 80
after (rinoh.structure.ListItemLabelStyle attribute), 87
after (rinoh.structure.TableOfContentsEntryStyle attribute), 95
after (rinoh.structure.TableOfContentsStyle attribute), 92
after (rinoh.text.TextStyle attribute), 66
after_break_background (rinoh.template.PageTemplate attribute), 141
after_break_background (rinoh.template.PageTemplateBase attribute), 143
after_break_background (rinoh.template.TitlePageTemplate attribute), 142
align (rinoh.image.ImageArgs attribute), 120
align_baselines (rinoh.flowable.LabeledFlowableStyle attribute), 45
AnchorFlowable (class in rinoh.flowable), 115
append() (rinoh.text.MixedStyledText method), 127
arguments (rinoh.image.BackgroundImage attribute), 119
arguments (rinoh.image.InlineImage attribute), 119
Article (class in rinoh.templates.article), 105
attention (rinoh.structure.AdmonitionTitles attribute), 131
Attribute (class in rinoh.attribute), 111
AttributesDictionary (class in rinoh.attribute), 111

B

back_matter (rinoh.templates.book.Book attribute), 108
back_matter_left_page (rinoh.templates.book.Book attribute), 110

back_matter_page (rinoh.templates.book.Book attribute), 110
 back_matter_right_page (rinoh.templates.book.Book attribute), 110
 background (rinoh.template.PageTemplate attribute), 140
 background (rinoh.template.PageTemplateBase attribute), 143
 background (rinoh.template.TitlePageTemplate attribute), 142
 background_color (rinoh.flowable.FloatStyle attribute), 51
 background_color (rinoh.flowable.FlowableStyle attribute), 45
 background_color (rinoh.flowable.GroupedFlowablesStyle attribute), 49
 background_color (rinoh.flowable.LabeledFlowableStyle attribute), 47
 background_color (rinoh.image.CaptionStyle attribute), 54
 background_color (rinoh.image.FigureStyle attribute), 58
 background_color (rinoh.index.IndexStyle attribute), 60
 background_color (rinoh.inline.InlineFlowableStyle attribute), 68
 background_color (rinoh.paragraph.ParagraphStyle attribute), 63
 background_color (rinoh.reference.ReferencingParagraphStyle attribute), 70
 background_color (rinoh.structure.AdmonitionStyle attribute), 98
 background_color (rinoh.structure.HeadingStyle attribute), 79
 background_color (rinoh.structure.HorizontalRuleStyle attribute), 100
 background_color (rinoh.structure.ListItemLabelStyle attribute), 86
 background_color (rinoh.structure.ListStyle attribute), 83
 background_color (rinoh.structure.SectionStyle attribute), 76
 background_color (rinoh.structure.TableOfContentsEntryStyle attribute), 94
 background_color (rinoh.structure.TableOfContentsStyle attribute), 90
 background_color (rinoh.table.TableCellStyle attribute), 104
 background_color (rinoh.table.TableStyle attribute), 102
 BackgroundImage (class in rinoh.image), 119
 baseline (rinoh.inline.InlineFlowableStyle attribute), 66
 before (rinoh.image.CaptionStyle attribute), 55
 before (rinoh.inline.InlineFlowableStyle attribute), 68
 before (rinoh.paragraph.ParagraphStyle attribute), 64
 before (rinoh.reference.NoteMarkerStyle attribute), 73
 before (rinoh.reference.ReferencingParagraphStyle attribute), 72
 before (rinoh.structure.HeadingStyle attribute), 80
 before (rinoh.structure.ListItemLabelStyle attribute), 87
 before (rinoh.structure.TableOfContentsEntryStyle attribute), 95
 before (rinoh.structure.TableOfContentsStyle attribute), 91
 before (rinoh.text.TextStyle attribute), 66
 Book (class in rinoh.templates.book), 107
 Bool (class in rinoh.attribute), 111
 border (rinoh.flowable.FloatStyle attribute), 51
 border (rinoh.flowable.FlowableStyle attribute), 44
 border (rinoh.flowable.GroupedFlowablesStyle attribute), 49
 border (rinoh.flowable.LabeledFlowableStyle attribute), 47
 border (rinoh.image.CaptionStyle attribute), 53
 border (rinoh.image.FigureStyle attribute), 57
 border (rinoh.index.IndexStyle attribute), 60
 border (rinoh.inline.InlineFlowableStyle attribute), 67
 border (rinoh.paragraph.ParagraphStyle attribute), 62
 border (rinoh.reference.ReferencingParagraphStyle attribute), 70
 border (rinoh.structure.AdmonitionStyle attribute), 97
 border (rinoh.structure.HeadingStyle attribute), 78
 border (rinoh.structure.HorizontalRuleStyle attribute), 99
 border (rinoh.structure.ListItemLabelStyle attribute), 85
 border (rinoh.structure.ListStyle attribute), 82
 border (rinoh.structure.SectionStyle attribute), 76
 border (rinoh.structure.TableOfContentsEntryStyle attribute), 93
 border (rinoh.structure.TableOfContentsStyle attribute), 89
 border (rinoh.table.TableCellStyle attribute), 104

border (rinoh.table.TableStyle attribute), 101
border_bottom (rinoh.flowable.FloatStyle attribute), 51
border_bottom (rinoh.flowable.FlowableStyle attribute), 45
border_bottom (rinoh.flowable.GroupedFlowablesStyle attribute), 49
border_bottom (rinoh.flowable.LabeledFlowableStyle attribute), 47
border_bottom (rinoh.image.CaptionStyle attribute), 54
border_bottom (rinoh.image.FigureStyle attribute), 58
border_bottom (rinoh.index.IndexStyle attribute), 60
border_bottom (rinoh.inline.InlineFlowableStyle attribute), 68
border_bottom (rinoh.paragraph.ParagraphStyle attribute), 63
border_bottom (rinoh.reference.ReferencingParagraphStyle attribute), 70
border_bottom (rinoh.structure.AdmonitionStyle attribute), 97
border_bottom (rinoh.structure.HeadingStyle attribute), 78
border_bottom (rinoh.structure.HorizontalRuleStyle attribute), 99
border_bottom (rinoh.structure.ListItemLabelStyle attribute), 86
border_bottom (rinoh.structure.ListStyle attribute), 83
border_bottom (rinoh.structure.SectionStyle attribute), 76
border_bottom (rinoh.structure.TableOfContentsEntryStyle attribute), 94
border_bottom (rinoh.structure.TableOfContentsStyle attribute), 89
border_bottom (rinoh.table.TableCellStyle attribute), 104
border_bottom (rinoh.table.TableStyle attribute), 102
border_left (rinoh.flowable.FloatStyle attribute), 51
border_left (rinoh.flowable.FlowableStyle attribute), 44
border_left (rinoh.flowable.GroupedFlowablesStyle attribute), 49
border_left (rinoh.flowable.LabeledFlowableStyle attribute), 47
border_left (rinoh.image.CaptionStyle attribute), 54
border_left (rinoh.image.FigureStyle attribute), 57
border_left (rinoh.index.IndexStyle attribute), 60
border_left (rinoh.inline.InlineFlowableStyle attribute), 67
border_left (rinoh.paragraph.ParagraphStyle attribute), 62
border_left (rinoh.reference.ReferencingParagraphStyle attribute), 70
border_left (rinoh.structure.AdmonitionStyle attribute), 97
border_left (rinoh.structure.HeadingStyle attribute), 78
border_left (rinoh.structure.HorizontalRuleStyle attribute), 99
border_left (rinoh.structure.ListItemLabelStyle attribute), 85
border_left (rinoh.structure.ListStyle attribute), 82
border_left (rinoh.structure.SectionStyle attribute), 76
border_left (rinoh.structure.TableOfContentsEntryStyle attribute), 94
border_left (rinoh.structure.TableOfContentsStyle attribute), 89
border_left (rinoh.table.TableCellStyle attribute), 104
border_left (rinoh.table.TableStyle attribute), 102
border_right (rinoh.flowable.FloatStyle attribute), 51
border_right (rinoh.flowable.FlowableStyle attribute), 44
border_right (rinoh.flowable.GroupedFlowablesStyle attribute), 49
border_right (rinoh.flowable.LabeledFlowableStyle attribute), 47
border_right (rinoh.image.CaptionStyle attribute), 54
border_right (rinoh.image.FigureStyle attribute), 58
border_right (rinoh.index.IndexStyle attribute), 60
border_right (rinoh.inline.InlineFlowableStyle attribute), 67
border_right (rinoh.paragraph.ParagraphStyle attribute), 62
border_right (rinoh.reference.ReferencingParagraphStyle attribute), 70
border_right (rinoh.structure.AdmonitionStyle attribute), 97
border_right (rinoh.structure.HeadingStyle attribute), 78
border_right (rinoh.structure.HorizontalRuleStyle attribute), 99
border_right (rinoh.structure.ListItemLabelStyle attribute), 85
border_right (rinoh.structure.ListStyle attribute), 82
border_right (rinoh.structure.SectionStyle attribute), 76
border_right (rinoh.structure.TableOfContentsEntryStyle attribute), 94

- border_right (rinoh.structure.TableOfContentsStyle attribute), 89
- border_right (rinoh.table.TableCellStyle attribute), 104
- border_right (rinoh.table.TableStyle attribute), 102
- border_top (rinoh.flowable.FloatStyle attribute), 51
- border_top (rinoh.flowable.FlowableStyle attribute), 45
- border_top (rinoh.flowable.GroupedFlowablesStyle attribute), 49
- border_top (rinoh.flowable.LabeledFlowableStyle attribute), 47
- border_top (rinoh.image.CaptionStyle attribute), 54
- border_top (rinoh.image.FigureStyle attribute), 58
- border_top (rinoh.index.IndexStyle attribute), 60
- border_top (rinoh.inline.InlineFlowableStyle attribute), 67
- border_top (rinoh.paragraph.ParagraphStyle attribute), 62
- border_top (rinoh.reference.ReferencingParagraphStyle attribute), 70
- border_top (rinoh.structure.AdmonitionStyle attribute), 97
- border_top (rinoh.structure.HeadingStyle attribute), 78
- border_top (rinoh.structure.HorizontalRuleStyle attribute), 99
- border_top (rinoh.structure.ListItemLabelStyle attribute), 85
- border_top (rinoh.structure.ListStyle attribute), 83
- border_top (rinoh.structure.SectionStyle attribute), 76
- border_top (rinoh.structure.TableOfContentsEntryStyle attribute), 94
- border_top (rinoh.structure.TableOfContentsStyle attribute), 89
- border_top (rinoh.table.TableCellStyle attribute), 104
- border_top (rinoh.table.TableStyle attribute), 102
- bottom_margin (rinoh.template.PageTemplate attribute), 140
- bottom_margin (rinoh.template.PageTemplateBase attribute), 142
- bottom_margin (rinoh.template.TitlePageTemplate attribute), 142
- build_document() (rinoh.flowable.StaticGroupedFlowables method), 116
- bullet (rinoh.structure.ListStyle attribute), 81

C

- Caption (class in rinoh.image), 120
- CaptionStyle (class in rinoh.image), 52
- caution (rinoh.structure.AdmonitionTitles attribute), 131
- chapter (rinoh.structure.SectionTitles attribute), 130
- chapter_footer_text (rinoh.template.PageTemplate attribute), 139
- chapter_header_text (rinoh.template.PageTemplate attribute), 139
- chapter_title_flowables (rinoh.template.PageTemplate attribute), 140
- chapter_title_height (rinoh.template.PageTemplate attribute), 140
- CM (in module rinoh.dimension), 113
- Color (class in rinoh.color), 111
- column_spacing (rinoh.template.PageTemplate attribute), 139
- column_widths (rinoh.table.TableStyle attribute), 100
- columns (rinoh.template.PageTemplate attribute), 139
- Configuration (rinoh.template.DocumentTemplate attribute), 136
- Configuration (rinoh.templates.article.Article attribute), 106
- Configuration (rinoh.templates.book.Book attribute), 110
- configuration_class (rinoh.template.DocumentPart attribute), 137
- ConfigurationFile (rinoh.template.DocumentTemplate attribute), 136
- ConfigurationFile (rinoh.templates.article.Article attribute), 106
- ConfigurationFile (rinoh.templates.book.Book attribute), 110
- contents (rinoh.structure.SectionTitles attribute), 130
- contents (rinoh.templates.article.Article attribute), 106
- contents (rinoh.templates.book.Book attribute), 108
- contents_left_page (rinoh.templates.book.Book attribute), 109
- contents_page (rinoh.templates.article.Article attribute), 106
- contents_page (rinoh.templates.book.Book attribute), 109
- contents_right_page (rinoh.templates.book.Book attribute), 109

- ContentsPartTemplate (class in rinoh.template), 138
- copy() (rinoh.text.MixedStyledText method), 127
- cover (rinoh.templates.book.Book attribute), 107
- cover_page (rinoh.templates.book.Book attribute), 108
- custom_label (rinoh.image.CaptionStyle attribute), 56
- custom_label (rinoh.number.NumberStyle attribute), 124
- custom_label (rinoh.reference.NoteMarkerStyle attribute), 74
- custom_label (rinoh.structure.HeadingStyle attribute), 81
- custom_label (rinoh.structure.ListItemLabelStyle attribute), 88
- custom_label (rinoh.structure.ListStyle attribute), 83

D

- danger (rinoh.structure.AdmonitionTitles attribute), 131
- DEFAULT (in module rinoh.paragraph), 128
- DefaultSpacing (class in rinoh.paragraph), 127
- DefinitionList (class in rinoh.structure), 131
- depth (rinoh.structure.TableOfContentsStyle attribute), 88
- Dimension (class in rinoh.dimension), 112
- doc_format() (rinoh.color.Color class method), 112
- Document (class in rinoh.document), 113
- document() (rinoh.template.TemplateConfiguration method), 136
- DocumentPart (class in rinoh.template), 136
- DocumentPartTemplate (class in rinoh.template), 137
- DocumentTemplate (class in rinoh.template), 135
- DocumentTree (class in rinoh.document), 113
- DOUBLE (in module rinoh.paragraph), 128
- dpi (rinoh.image.ImageArgs attribute), 120
- drop_if_empty (rinoh.template.ContentsPartTemplate attribute), 138
- drop_if_empty (rinoh.template.DocumentPartTemplate attribute), 137
- drop_if_empty (rinoh.template.FixedDocumentPartTemplate attribute), 139
- drop_if_empty (rinoh.template.TitlePartTemplate attribute), 137
- DummyFlowable (class in rinoh.flowable), 115

E

- EN (in module rinoh.language), 121
- encoding (rinoh.font.Font attribute), 118
- end_at_page (rinoh.template.ContentsPartTemplate attribute), 138
- end_at_page (rinoh.template.DocumentPartTemplate attribute), 137
- end_at_page (rinoh.template.FixedDocumentPartTemplate attribute), 138
- end_at_page (rinoh.template.TitlePartTemplate attribute), 138
- environment variable
 - PATH, 11
- error (rinoh.structure.AdmonitionTitles attribute), 131
- extra (rinoh.template.TitlePageTemplate attribute), 141

F

- Field (class in rinoh.reference), 130
- Figure (class in rinoh.image), 120
- FigureStyle (class in rinoh.image), 56
- file_or_filename (rinoh.image.ImageArgs attribute), 120
- fill_color (rinoh.draw.ShapeStyle attribute), 43
- fill_color (rinoh.table.TableCellBackgroundStyle attribute), 105
- FixedDocumentPartTemplate (class in rinoh.template), 138
- FixedSpacing (class in rinoh.paragraph), 128
- Float (class in rinoh.flowable), 117
- float (rinoh.flowable.FloatStyle attribute), 50
- float (rinoh.image.FigureStyle attribute), 56

FloatStyle (class in rinoh.flowable), 50
 flow() (rinoh.flowable.Float method), 117
 flow() (rinoh.index.IndexTarget method), 121
 flow() (rinoh.structure.Heading method), 130
 Flowable (class in rinoh.flowable), 115
 flowable_spacing (rinoh.flowable.GroupedFlowablesStyle attribute), 48
 flowable_spacing (rinoh.image.FigureStyle attribute), 58
 flowable_spacing (rinoh.index.IndexStyle attribute), 59
 flowable_spacing (rinoh.structure.AdmonitionStyle attribute), 96
 flowable_spacing (rinoh.structure.ListStyle attribute), 81
 flowable_spacing (rinoh.structure.SectionStyle attribute), 74
 flowable_spacing (rinoh.structure.TableOfContentsStyle attribute), 88
 flowable_spacing (rinoh.table.TableCellStyle attribute), 103
 flowables (rinoh.template.FixedDocumentPartTemplate attribute), 138
 flowables() (rinoh.flowable.GroupedFlowables method), 116
 flowables() (rinoh.flowable.StaticGroupedFlowables method), 116
 flowables() (rinoh.index.Index method), 121
 flowables() (rinoh.structure.Admonition method), 131
 flowables() (rinoh.structure.TableOfContents method), 131
 FlowableState (class in rinoh.flowable), 115
 FlowableStyle (class in rinoh.flowable), 43
 FlowableWidth (class in rinoh.flowable), 117
 Font (class in rinoh.font), 117
 font_color (rinoh.image.CaptionStyle attribute), 55
 font_color (rinoh.paragraph.ParagraphStyle attribute), 63
 font_color (rinoh.reference.NoteMarkerStyle attribute), 73
 font_color (rinoh.reference.ReferencingParagraphStyle attribute), 71
 font_color (rinoh.structure.HeadingStyle attribute), 79
 font_color (rinoh.structure.ListItemLabelStyle attribute), 86
 font_color (rinoh.structure.TableOfContentsEntryStyle attribute), 95
 font_color (rinoh.structure.TableOfContentsStyle attribute), 91
 font_color (rinoh.text.TextStyle attribute), 65
 font_size (rinoh.image.CaptionStyle attribute), 55
 font_size (rinoh.paragraph.ParagraphStyle attribute), 63
 font_size (rinoh.reference.NoteMarkerStyle attribute), 73
 font_size (rinoh.reference.ReferencingParagraphStyle attribute), 71
 font_size (rinoh.structure.HeadingStyle attribute), 79
 font_size (rinoh.structure.ListItemLabelStyle attribute), 86
 font_size (rinoh.structure.TableOfContentsEntryStyle attribute), 95
 font_size (rinoh.structure.TableOfContentsStyle attribute), 91
 font_size (rinoh.text.TextStyle attribute), 65
 font_slant (rinoh.image.CaptionStyle attribute), 54
 font_slant (rinoh.paragraph.ParagraphStyle attribute), 63
 font_slant (rinoh.reference.NoteMarkerStyle attribute), 72
 font_slant (rinoh.reference.ReferencingParagraphStyle attribute), 71
 font_slant (rinoh.structure.HeadingStyle attribute), 79
 font_slant (rinoh.structure.ListItemLabelStyle attribute), 86
 font_slant (rinoh.structure.TableOfContentsEntryStyle attribute), 94
 font_slant (rinoh.structure.TableOfContentsStyle attribute), 91
 font_slant (rinoh.text.TextStyle attribute), 65
 font_variant (rinoh.image.CaptionStyle attribute), 55
 font_variant (rinoh.paragraph.ParagraphStyle attribute), 64
 font_variant (rinoh.reference.NoteMarkerStyle attribute), 73
 font_variant (rinoh.reference.ReferencingParagraphStyle attribute), 71
 font_variant (rinoh.structure.HeadingStyle attribute), 79
 font_variant (rinoh.structure.ListItemLabelStyle attribute), 86
 font_variant (rinoh.structure.TableOfContentsEntryStyle attribute), 95
 font_variant (rinoh.structure.TableOfContentsStyle attribute), 91

- font_variant (rinoh.text.TextStyle attribute), 65
- font_weight (rinoh.image.CaptionStyle attribute), 54
- font_weight (rinoh.paragraph.ParagraphStyle attribute), 63
- font_weight (rinoh.reference.NoteMarkerStyle attribute), 72
- font_weight (rinoh.reference.ReferencingParagraphStyle attribute), 71
- font_weight (rinoh.structure.HeadingStyle attribute), 79
- font_weight (rinoh.structure.ListItemLabelStyle attribute), 86
- font_weight (rinoh.structure.TableOfContentsEntryStyle attribute), 94
- font_weight (rinoh.structure.TableOfContentsStyle attribute), 90
- font_weight (rinoh.text.TextStyle attribute), 65
- font_width (rinoh.image.CaptionStyle attribute), 54
- font_width (rinoh.paragraph.ParagraphStyle attribute), 63
- font_width (rinoh.reference.NoteMarkerStyle attribute), 72
- font_width (rinoh.reference.ReferencingParagraphStyle attribute), 71
- font_width (rinoh.structure.HeadingStyle attribute), 79
- font_width (rinoh.structure.ListItemLabelStyle attribute), 86
- font_width (rinoh.structure.TableOfContentsEntryStyle attribute), 94
- font_width (rinoh.structure.TableOfContentsStyle attribute), 91
- font_width (rinoh.text.TextStyle attribute), 65
- fonts() (rinoh.font.Typeface method), 118
- FontSlant (class in rinoh.font.style), 119
- FontVariant (class in rinoh.font.style), 119
- FontWeight (class in rinoh.font.style), 119
- FontWidth (class in rinoh.font.style), 119
- footer_text (rinoh.template.PageTemplate attribute), 139
- format_number() (in module rinoh.number), 124
- FR (in module rinoh.language), 122
- front_matter (rinoh.templates.article.Article attribute), 106
- front_matter (rinoh.templates.book.Book attribute), 107
- front_matter_left_page (rinoh.templates.book.Book attribute), 109
- front_matter_page (rinoh.templates.article.Article attribute), 106
- front_matter_page (rinoh.templates.book.Book attribute), 108
- front_matter_right_page (rinoh.templates.book.Book attribute), 108

G

- get_font() (rinoh.font.Typeface method), 119
- get_glyph() (rinoh.font.Font method), 118
- get_kerning() (rinoh.font.Font method), 118
- get_ligature() (rinoh.font.Font method), 118
- get_position() (rinoh.paragraph.TabStop method), 129
- get_rowspanned_columns() (rinoh.table.TableRow method), 135
- get_selector() (rinoh.style.StyleSheet method), 133
- Glyph (class in rinoh.paragraph), 129
- GlyphsSpan (class in rinoh.paragraph), 129
- Gray (class in rinoh.color), 112
- GroupedFlowables (class in rinoh.flowable), 116
- GroupedFlowablesState (class in rinoh.flowable), 116
- GroupedFlowablesStyle (class in rinoh.flowable), 47
- GroupedLabeledFlowables (class in rinoh.flowable), 117
- grow() (rinoh.dimension.Dimension method), 112

H

- has_class() (rinoh.style.Styled property), 133
- has_classes() (rinoh.style.Styled property), 133
- header_footer_distance (rinoh.template.PageTemplate attribute), 139
- header_text (rinoh.template.PageTemplate attribute), 139
- Heading (class in rinoh.structure), 130

HeadingStyle (class in rinoh.structure), 76
 height (rinoh.image.ImageArgs attribute), 120
 height() (rinoh.text.StyledText method), 126
 HexColor (class in rinoh.color), 112
 hide (rinoh.draw.LineStyle attribute), 43
 hide (rinoh.draw.ShapeStyle attribute), 43
 hide (rinoh.flowable.FloatStyle attribute), 52
 hide (rinoh.flowable.FlowableStyle attribute), 45
 hide (rinoh.flowable.GroupedFlowablesStyle attribute), 49
 hide (rinoh.flowable.LabeledFlowableStyle attribute), 47
 hide (rinoh.image.CaptionStyle attribute), 56
 hide (rinoh.image.FigureStyle attribute), 58
 hide (rinoh.index.IndexStyle attribute), 61
 hide (rinoh.inline.InlineFlowableStyle attribute), 68
 hide (rinoh.number.NumberStyle attribute), 124
 hide (rinoh.paragraph.ParagraphStyle attribute), 63
 hide (rinoh.reference.NoteMarkerStyle attribute), 73
 hide (rinoh.reference.ReferencingParagraphStyle attribute), 72
 hide (rinoh.structure.AdmonitionStyle attribute), 98
 hide (rinoh.structure.HeadingStyle attribute), 81
 hide (rinoh.structure.HorizontalRuleStyle attribute), 100
 hide (rinoh.structure.ListItemLabelStyle attribute), 87
 hide (rinoh.structure.ListStyle attribute), 83
 hide (rinoh.structure.SectionStyle attribute), 76
 hide (rinoh.structure.TableOfContentsEntryStyle attribute), 96
 hide (rinoh.structure.TableOfContentsStyle attribute), 90
 hide (rinoh.style.Style attribute), 133
 hide (rinoh.table.TableCellBackgroundStyle attribute), 105
 hide (rinoh.table.TableCellBorderStyle attribute), 105
 hide (rinoh.table.TableCellStyle attribute), 104
 hide (rinoh.table.TableStyle attribute), 102
 hide (rinoh.text.TextStyle attribute), 66
 hint (rinoh.structure.AdmonitionTitles attribute), 131
 horizontal_align (rinoh.flowable.FloatStyle attribute), 50
 horizontal_align (rinoh.flowable.FlowableStyle attribute), 43
 horizontal_align (rinoh.flowable.GroupedFlowablesStyle attribute), 48
 horizontal_align (rinoh.flowable.LabeledFlowableStyle attribute), 46
 horizontal_align (rinoh.image.CaptionStyle attribute), 52
 horizontal_align (rinoh.image.FigureStyle attribute), 56
 horizontal_align (rinoh.index.IndexStyle attribute), 59
 horizontal_align (rinoh.inline.InlineFlowableStyle attribute), 66
 horizontal_align (rinoh.paragraph.ParagraphStyle attribute), 61
 horizontal_align (rinoh.reference.ReferencingParagraphStyle attribute), 69
 horizontal_align (rinoh.structure.AdmonitionStyle attribute), 96
 horizontal_align (rinoh.structure.HeadingStyle attribute), 77
 horizontal_align (rinoh.structure.HorizontalRuleStyle attribute), 98
 horizontal_align (rinoh.structure.ListItemLabelStyle attribute), 84
 horizontal_align (rinoh.structure.ListStyle attribute), 81
 horizontal_align (rinoh.structure.SectionStyle attribute), 74
 horizontal_align (rinoh.structure.TableOfContentsEntryStyle attribute), 92
 horizontal_align (rinoh.structure.TableOfContentsStyle attribute), 88
 horizontal_align (rinoh.table.TableCellStyle attribute), 103
 horizontal_align (rinoh.table.TableStyle attribute), 100
 HorizontalAlignment (class in rinoh.flowable), 117
 HorizontalRule (class in rinoh.structure), 132
 HorizontalRuleStyle (class in rinoh.structure), 98
 hyphen_chars (rinoh.image.CaptionStyle attribute), 55
 hyphen_chars (rinoh.paragraph.ParagraphStyle attribute), 64

- hyphen_chars (rinoh.reference.NoteMarkerStyle attribute), 73
- hyphen_chars (rinoh.reference.ReferencingParagraphStyle attribute), 72
- hyphen_chars (rinoh.structure.HeadingStyle attribute), 80
- hyphen_chars (rinoh.structure.ListItemLabelStyle attribute), 87
- hyphen_chars (rinoh.structure.TableOfContentsEntryStyle attribute), 95
- hyphen_chars (rinoh.structure.TableOfContentsStyle attribute), 91
- hyphen_chars (rinoh.text.TextStyle attribute), 65
- hyphen_lang (rinoh.image.CaptionStyle attribute), 55
- hyphen_lang (rinoh.paragraph.ParagraphStyle attribute), 64
- hyphen_lang (rinoh.reference.NoteMarkerStyle attribute), 73
- hyphen_lang (rinoh.reference.ReferencingParagraphStyle attribute), 72
- hyphen_lang (rinoh.structure.HeadingStyle attribute), 80
- hyphen_lang (rinoh.structure.ListItemLabelStyle attribute), 87
- hyphen_lang (rinoh.structure.TableOfContentsEntryStyle attribute), 95
- hyphen_lang (rinoh.structure.TableOfContentsStyle attribute), 91
- hyphen_lang (rinoh.text.TextStyle attribute), 65
- hyphenate (rinoh.image.CaptionStyle attribute), 55
- hyphenate (rinoh.paragraph.ParagraphStyle attribute), 64
- hyphenate (rinoh.reference.NoteMarkerStyle attribute), 73
- hyphenate (rinoh.reference.ReferencingParagraphStyle attribute), 71
- hyphenate (rinoh.structure.HeadingStyle attribute), 80
- hyphenate (rinoh.structure.ListItemLabelStyle attribute), 87
- hyphenate (rinoh.structure.TableOfContentsEntryStyle attribute), 95
- hyphenate (rinoh.structure.TableOfContentsStyle attribute), 91
- hyphenate (rinoh.text.TextStyle attribute), 65
- HyphenatorStore (class in rinoh.paragraph), 129

I

- Image (class in rinoh.image), 119
- ImageArgs (class in rinoh.image), 119
- important (rinoh.structure.AdmonitionTitles attribute), 131
- INCH (in module rinoh.dimension), 113
- indent_first (rinoh.image.CaptionStyle attribute), 52
- indent_first (rinoh.paragraph.ParagraphStyle attribute), 61
- indent_first (rinoh.reference.ReferencingParagraphStyle attribute), 68
- indent_first (rinoh.structure.HeadingStyle attribute), 77
- indent_first (rinoh.structure.ListItemLabelStyle attribute), 84
- indent_first (rinoh.structure.TableOfContentsEntryStyle attribute), 92
- indent_first (rinoh.structure.TableOfContentsStyle attribute), 90
- Index (class in rinoh.index), 121
- index (rinoh.structure.SectionTitles attribute), 131
- IndexLabel (class in rinoh.index), 121
- IndexSection (class in rinoh.index), 121
- IndexStyle (class in rinoh.index), 58
- IndexTarget (class in rinoh.index), 121
- IndexTerm (class in rinoh.index), 121
- initials (rinoh.index.IndexStyle attribute), 58
- inline_title (rinoh.structure.AdmonitionStyle attribute), 96
- InlineFlowable (class in rinoh.inline), 127
- InlineFlowableStyle (class in rinoh.inline), 66
- InlineImage (class in rinoh.image), 119
- InlineIndexTarget (class in rinoh.index), 121
- input
 - rinoh command line option, 31
- Integer (class in rinoh.attribute), 111
- is_script() (rinoh.text.StyledText method), 126
- IT (in module rinoh.language), 122

items() (rinoh.text.MixedStyledText property), 127
items() (rinoh.text.StyledText property), 126

J

JUNIOR_LEGAL (in module rinoh.paper), 125

K

keep_with_next (rinoh.flowable.FloatStyle attribute), 51
keep_with_next (rinoh.flowable.FlowableStyle attribute), 44
keep_with_next (rinoh.flowable.GroupedFlowablesStyle attribute), 49
keep_with_next (rinoh.flowable.LabeledFlowableStyle attribute), 47
keep_with_next (rinoh.image.CaptionStyle attribute), 53
keep_with_next (rinoh.image.FigureStyle attribute), 57
keep_with_next (rinoh.index.IndexStyle attribute), 60
keep_with_next (rinoh.inline.InlineFlowableStyle attribute), 67
keep_with_next (rinoh.paragraph.ParagraphStyle attribute), 62
keep_with_next (rinoh.reference.ReferencingParagraphStyle attribute), 70
keep_with_next (rinoh.structure.AdmonitionStyle attribute), 97
keep_with_next (rinoh.structure.HeadingStyle attribute), 77
keep_with_next (rinoh.structure.HorizontalRuleStyle attribute), 99
keep_with_next (rinoh.structure.ListItemLabelStyle attribute), 85
keep_with_next (rinoh.structure.ListStyle attribute), 82
keep_with_next (rinoh.structure.SectionStyle attribute), 75
keep_with_next (rinoh.structure.TableOfContentsEntryStyle attribute), 93
keep_with_next (rinoh.structure.TableOfContentsStyle attribute), 89
keep_with_next (rinoh.table.TableCellStyle attribute), 104
keep_with_next (rinoh.table.TableStyle attribute), 101
kerning (rinoh.image.CaptionStyle attribute), 55
kerning (rinoh.paragraph.ParagraphStyle attribute), 64
kerning (rinoh.reference.NoteMarkerStyle attribute), 73
kerning (rinoh.reference.ReferencingParagraphStyle attribute), 71
kerning (rinoh.structure.HeadingStyle attribute), 79
kerning (rinoh.structure.ListItemLabelStyle attribute), 87
kerning (rinoh.structure.TableOfContentsEntryStyle attribute), 95
kerning (rinoh.structure.TableOfContentsStyle attribute), 91
kerning (rinoh.text.TextStyle attribute), 65

L

label_max_width (rinoh.flowable.LabeledFlowableStyle attribute), 45
label_min_width (rinoh.flowable.LabeledFlowableStyle attribute), 45
label_prefix (rinoh.image.CaptionStyle attribute), 56
label_prefix (rinoh.number.NumberStyle attribute), 124
label_prefix (rinoh.reference.NoteMarkerStyle attribute), 74
label_prefix (rinoh.structure.HeadingStyle attribute), 80
label_prefix (rinoh.structure.ListItemLabelStyle attribute), 87
label_prefix (rinoh.structure.ListStyle attribute), 83
label_spacing (rinoh.flowable.LabeledFlowableStyle attribute), 45
label_suffix (rinoh.image.CaptionStyle attribute), 56
label_suffix (rinoh.number.NumberStyle attribute), 124
label_suffix (rinoh.reference.NoteMarkerStyle attribute), 74
label_suffix (rinoh.structure.HeadingStyle attribute), 80
label_suffix (rinoh.structure.ListItemLabelStyle attribute), 87
label_suffix (rinoh.structure.ListStyle attribute), 83
LabeledFlowable (class in rinoh.flowable), 115
LabeledFlowableState (class in rinoh.flowable), 116
LabeledFlowableStyle (class in rinoh.flowable), 45
Language (class in rinoh.language), 121

language (rinoh.template.DocumentTemplate attribute), 135
 language (rinoh.templates.article.Article attribute), 106
 language (rinoh.templates.book.Book attribute), 107
 languages (rinoh.language.Language attribute), 121
 Leading (class in rinoh.paragraph), 128
 LEDGER (in module rinoh.paper), 125
 left_margin (rinoh.template.PageTemplate attribute), 140
 left_margin (rinoh.template.PageTemplateBase attribute), 142
 left_margin (rinoh.template.TitlePageTemplate attribute), 141
 LEGAL (in module rinoh.paper), 125
 LETTER (in module rinoh.paper), 125
 ligatures (rinoh.image.CaptionStyle attribute), 55
 ligatures (rinoh.paragraph.ParagraphStyle attribute), 64
 ligatures (rinoh.reference.NoteMarkerStyle attribute), 73
 ligatures (rinoh.reference.ReferencingParagraphStyle attribute), 71
 ligatures (rinoh.structure.HeadingStyle attribute), 80
 ligatures (rinoh.structure.ListItemLabelStyle attribute), 87
 ligatures (rinoh.structure.TableOfContentsEntryStyle attribute), 95
 ligatures (rinoh.structure.TableOfContentsStyle attribute), 91
 ligatures (rinoh.text.TextStyle attribute), 65
 limit_width (rinoh.image.ImageArgs attribute), 119
 Line (class in rinoh.draw), 114
 line_spacing (rinoh.image.CaptionStyle attribute), 52
 line_spacing (rinoh.paragraph.ParagraphStyle attribute), 61
 line_spacing (rinoh.reference.ReferencingParagraphStyle attribute), 69
 line_spacing (rinoh.structure.HeadingStyle attribute), 77
 line_spacing (rinoh.structure.ListItemLabelStyle attribute), 84
 line_spacing (rinoh.structure.TableOfContentsEntryStyle attribute), 92
 line_spacing (rinoh.structure.TableOfContentsStyle attribute), 90
 LineSpacing (class in rinoh.paragraph), 127
 LineStyle (class in rinoh.draw), 43
 List (class in rinoh.structure), 131
 list_class (rinoh.image.ListOfFiguresSection attribute), 120
 list_class (rinoh.table.ListOfTablesSection attribute), 135
 list_of_figures (rinoh.structure.SectionTitles attribute), 130
 list_of_tables (rinoh.structure.SectionTitles attribute), 130
 ListItemLabelStyle (class in rinoh.structure), 84
 ListOfFigures (class in rinoh.image), 120
 ListOfFiguresSection (class in rinoh.image), 120
 ListOfTables (class in rinoh.table), 135
 ListOfTablesSection (class in rinoh.table), 135
 ListStyle (class in rinoh.structure), 81
 Locale (class in rinoh.text), 127
 location() (rinoh.attribute.RuleSetFile property), 111

M

margin_left (rinoh.flowable.FloatStyle attribute), 50
 margin_left (rinoh.flowable.FlowableStyle attribute), 44
 margin_left (rinoh.flowable.GroupedFlowablesStyle attribute), 48
 margin_left (rinoh.flowable.LabeledFlowableStyle attribute), 46
 margin_left (rinoh.image.CaptionStyle attribute), 53
 margin_left (rinoh.image.FigureStyle attribute), 57
 margin_left (rinoh.index.IndexStyle attribute), 59
 margin_left (rinoh.inline.InlineFlowableStyle attribute), 66
 margin_left (rinoh.paragraph.ParagraphStyle attribute), 61
 margin_left (rinoh.reference.ReferencingParagraphStyle attribute), 69
 margin_left (rinoh.structure.AdmonitionStyle attribute), 96

- margin_left (rinoh.structure.HeadingStyle attribute), 77
- margin_left (rinoh.structure.HorizontalRuleStyle attribute), 98
- margin_left (rinoh.structure.ListItemLabelStyle attribute), 84
- margin_left (rinoh.structure.ListStyle attribute), 82
- margin_left (rinoh.structure.SectionStyle attribute), 75
- margin_left (rinoh.structure.TableOfContentsEntryStyle attribute), 93
- margin_left (rinoh.structure.TableOfContentsStyle attribute), 88
- margin_left (rinoh.table.TableCellStyle attribute), 103
- margin_left (rinoh.table.TableStyle attribute), 101
- margin_right (rinoh.flowable.FloatStyle attribute), 50
- margin_right (rinoh.flowable.FlowableStyle attribute), 44
- margin_right (rinoh.flowable.GroupedFlowablesStyle attribute), 48
- margin_right (rinoh.flowable.LabeledFlowableStyle attribute), 46
- margin_right (rinoh.image.CaptionStyle attribute), 53
- margin_right (rinoh.image.FigureStyle attribute), 57
- margin_right (rinoh.index.IndexStyle attribute), 59
- margin_right (rinoh.inline.InlineFlowableStyle attribute), 67
- margin_right (rinoh.paragraph.ParagraphStyle attribute), 62
- margin_right (rinoh.reference.ReferenceParagraphStyle attribute), 69
- margin_right (rinoh.structure.AdmonitionStyle attribute), 96
- margin_right (rinoh.structure.HeadingStyle attribute), 78
- margin_right (rinoh.structure.HorizontalRuleStyle attribute), 98
- margin_right (rinoh.structure.ListItemLabelStyle attribute), 85
- margin_right (rinoh.structure.ListStyle attribute), 82
- margin_right (rinoh.structure.SectionStyle attribute), 75
- margin_right (rinoh.structure.TableOfContentsEntryStyle attribute), 93
- margin_right (rinoh.structure.TableOfContentsStyle attribute), 88
- margin_right (rinoh.table.TableCellStyle attribute), 103
- margin_right (rinoh.table.TableStyle attribute), 101
- matcher (in module rinoh.stylesheets), 34
- MixedStyledText (class in rinoh.text), 126
- MM (in module rinoh.dimension), 113
- module
 - rinoh.attribute, 111
 - rinoh.color, 111
 - rinoh.dimension, 112
 - rinoh.document, 113
 - rinoh.draw, 114
 - rinoh.flowable, 115
 - rinoh.font, 117
 - rinoh.font.style, 119
 - rinoh.image, 119
 - rinoh.index, 121
 - rinoh.inline, 127
 - rinoh.language, 121
 - rinoh.number, 124
 - rinoh.paper, 125
 - rinoh.paragraph, 125
 - rinoh.reference, 129
 - rinoh.strings, 132
 - rinoh.structure, 130
 - rinoh.style, 133
 - rinoh.stylesheets, 33
 - rinoh.table, 134
 - rinoh.template, 135
 - rinoh.templates.article, 105
 - rinoh.templates.book, 107
 - rinoh.text, 126

N

`new_page()` (rinoh.template.DocumentPart method), 137
`NL` (in module rinoh.language), 123
`Note` (class in rinoh.reference), 129
`note` (rinoh.structure.AdmonitionTitles attribute), 131
`NoteMarkerBase` (class in rinoh.reference), 129
`NoteMarkerByID` (class in rinoh.reference), 129
`NoteMarkerStyle` (class in rinoh.reference), 72
`NoteMarkerWithNote` (class in rinoh.reference), 130
`number_format` (rinoh.image.CaptionStyle attribute), 56
`number_format` (rinoh.number.NumberStyle attribute), 124
`number_format` (rinoh.reference.NoteMarkerStyle attribute), 74
`number_format` (rinoh.structure.HeadingStyle attribute), 80
`number_format` (rinoh.structure.ListStyle attribute), 83
`number_separator` (rinoh.image.CaptionStyle attribute), 52
`number_separator` (rinoh.structure.HeadingStyle attribute), 76
`NumberedParagraph` (class in rinoh.number), 124
`NumberFormat` (class in rinoh.number), 124
`numbering_level` (rinoh.image.CaptionStyle attribute), 52
`NumberStyle` (class in rinoh.number), 124

O

`OptionSet` (class in rinoh.attribute), 111
`ordered` (rinoh.structure.ListStyle attribute), 81
`OverrideDefault` (class in rinoh.attribute), 111

P

`padding` (rinoh.flowable.FloatStyle attribute), 50
`padding` (rinoh.flowable.FlowableStyle attribute), 44
`padding` (rinoh.flowable.GroupedFlowablesStyle attribute), 48
`padding` (rinoh.flowable.LabeledFlowableStyle attribute), 46
`padding` (rinoh.image.CaptionStyle attribute), 53
`padding` (rinoh.image.FigureStyle attribute), 57
`padding` (rinoh.index.IndexStyle attribute), 59
`padding` (rinoh.inline.InlineFlowableStyle attribute), 67
`padding` (rinoh.paragraph.ParagraphStyle attribute), 62
`padding` (rinoh.reference.ReferencingParagraphStyle attribute), 69
`padding` (rinoh.structure.AdmonitionStyle attribute), 97
`padding` (rinoh.structure.HeadingStyle attribute), 78
`padding` (rinoh.structure.HorizontalRuleStyle attribute), 99
`padding` (rinoh.structure.ListItemLabelStyle attribute), 85
`padding` (rinoh.structure.ListStyle attribute), 82
`padding` (rinoh.structure.SectionStyle attribute), 75
`padding` (rinoh.structure.TableOfContentsEntryStyle attribute), 93
`padding` (rinoh.structure.TableOfContentsStyle attribute), 89
`padding` (rinoh.table.TableCellStyle attribute), 103
`padding` (rinoh.table.TableStyle attribute), 101
`padding_bottom` (rinoh.flowable.FloatStyle attribute), 51
`padding_bottom` (rinoh.flowable.FlowableStyle attribute), 44
`padding_bottom` (rinoh.flowable.GroupedFlowablesStyle attribute), 49
`padding_bottom` (rinoh.flowable.LabeledFlowableStyle attribute), 46
`padding_bottom` (rinoh.image.CaptionStyle attribute), 53
`padding_bottom` (rinoh.image.FigureStyle attribute), 57
`padding_bottom` (rinoh.index.IndexStyle attribute), 60
`padding_bottom` (rinoh.inline.InlineFlowableStyle attribute), 67
`padding_bottom` (rinoh.paragraph.ParagraphStyle attribute), 62

padding_bottom (rinoh.reference.ReferencingParagraphStyle attribute), 70

padding_bottom (rinoh.structure.AdmonitionStyle attribute), 97

padding_bottom (rinoh.structure.HeadingStyle attribute), 78

padding_bottom (rinoh.structure.HorizontalRuleStyle attribute), 99

padding_bottom (rinoh.structure.ListItemLabelStyle attribute), 85

padding_bottom (rinoh.structure.ListStyle attribute), 82

padding_bottom (rinoh.structure.SectionStyle attribute), 75

padding_bottom (rinoh.structure.TableOfContentsEntryStyle attribute), 93

padding_bottom (rinoh.structure.TableOfContentsStyle attribute), 89

padding_bottom (rinoh.table.TableCellStyle attribute), 104

padding_bottom (rinoh.table.TableStyle attribute), 101

padding_left (rinoh.flowable.FloatStyle attribute), 50

padding_left (rinoh.flowable.FlowableStyle attribute), 44

padding_left (rinoh.flowable.GroupedFlowablesStyle attribute), 48

padding_left (rinoh.flowable.LabeledFlowableStyle attribute), 46

padding_left (rinoh.image.CaptionStyle attribute), 53

padding_left (rinoh.image.FigureStyle attribute), 57

padding_left (rinoh.index.IndexStyle attribute), 59

padding_left (rinoh.inline.InlineFlowableStyle attribute), 67

padding_left (rinoh.paragraph.ParagraphStyle attribute), 62

padding_left (rinoh.reference.ReferencingParagraphStyle attribute), 69

padding_left (rinoh.structure.AdmonitionStyle attribute), 97

padding_left (rinoh.structure.HeadingStyle attribute), 78

padding_left (rinoh.structure.HorizontalRuleStyle attribute), 99

padding_left (rinoh.structure.ListItemLabelStyle attribute), 85

padding_left (rinoh.structure.ListStyle attribute), 82

padding_left (rinoh.structure.SectionStyle attribute), 75

padding_left (rinoh.structure.TableOfContentsEntryStyle attribute), 93

padding_left (rinoh.structure.TableOfContentsStyle attribute), 89

padding_left (rinoh.table.TableCellStyle attribute), 103

padding_left (rinoh.table.TableStyle attribute), 101

padding_right (rinoh.flowable.FloatStyle attribute), 50

padding_right (rinoh.flowable.FlowableStyle attribute), 44

padding_right (rinoh.flowable.GroupedFlowablesStyle attribute), 48

padding_right (rinoh.flowable.LabeledFlowableStyle attribute), 46

padding_right (rinoh.image.CaptionStyle attribute), 53

padding_right (rinoh.image.FigureStyle attribute), 57

padding_right (rinoh.index.IndexStyle attribute), 59

padding_right (rinoh.inline.InlineFlowableStyle attribute), 67

padding_right (rinoh.paragraph.ParagraphStyle attribute), 62

padding_right (rinoh.reference.ReferencingParagraphStyle attribute), 70

padding_right (rinoh.structure.AdmonitionStyle attribute), 97

padding_right (rinoh.structure.HeadingStyle attribute), 78

padding_right (rinoh.structure.HorizontalRuleStyle attribute), 99

padding_right (rinoh.structure.ListItemLabelStyle attribute), 85

padding_right (rinoh.structure.ListStyle attribute), 82

padding_right (rinoh.structure.SectionStyle attribute), 75

padding_right (rinoh.structure.TableOfContentsEntryStyle attribute), 93

padding_right (rinoh.structure.TableOfContentsStyle attribute), 89

padding_right (rinoh.table.TableCellStyle attribute), 103

padding_right (rinoh.table.TableStyle attribute), 101

padding_top (rinoh.flowable.FloatStyle attribute), 51

padding_top (rinoh.flowable.FlowableStyle attribute), 44

padding_top (rinoh.flowable.GroupedFlowablesStyle attribute), 49

padding_top (rinoh.flowable.LabeledFlowableStyle attribute), 46

padding_top (rinoh.image.CaptionStyle attribute), 53

padding_top (rinoh.image.FigureStyle attribute), 57

padding_top (rinoh.index.IndexStyle attribute), 60

padding_top (rinoh.inline.InlineFlowableStyle attribute), 67

padding_top (rinoh.paragraph.ParagraphStyle attribute), 62

padding_top (rinoh.reference.ReferencingParagraphStyle attribute), 70

padding_top (rinoh.structure.AdmonitionStyle attribute), 97

padding_top (rinoh.structure.HeadingStyle attribute), 78

padding_top (rinoh.structure.HorizontalRuleStyle attribute), 99

padding_top (rinoh.structure.ListItemLabelStyle attribute), 85

padding_top (rinoh.structure.ListStyle attribute), 82

padding_top (rinoh.structure.SectionStyle attribute), 75

padding_top (rinoh.structure.TableOfContentsEntryStyle attribute), 93

padding_top (rinoh.structure.TableOfContentsStyle attribute), 89

padding_top (rinoh.table.TableCellStyle attribute), 103

padding_top (rinoh.table.TableStyle attribute), 101

Page (class in rinoh.document), 114

page (rinoh.templates.article.Article attribute), 106

page (rinoh.templates.book.Book attribute), 108

page() (rinoh.document.Page property), 114

page_break (rinoh.flowable.FloatStyle attribute), 51

page_break (rinoh.flowable.FlowableStyle attribute), 45

page_break (rinoh.flowable.GroupedFlowablesStyle attribute), 49

page_break (rinoh.flowable.LabeledFlowableStyle attribute), 47

page_break (rinoh.image.CaptionStyle attribute), 54

page_break (rinoh.image.FigureStyle attribute), 58

page_break (rinoh.index.IndexStyle attribute), 60

page_break (rinoh.inline.InlineFlowableStyle attribute), 68

page_break (rinoh.paragraph.ParagraphStyle attribute), 63

page_break (rinoh.reference.ReferencingParagraphStyle attribute), 70

page_break (rinoh.structure.AdmonitionStyle attribute), 98

page_break (rinoh.structure.HeadingStyle attribute), 79

page_break (rinoh.structure.HorizontalRuleStyle attribute), 100

page_break (rinoh.structure.ListItemLabelStyle attribute), 86

page_break (rinoh.structure.ListStyle attribute), 83

page_break (rinoh.structure.SectionStyle attribute), 76

page_break (rinoh.structure.TableOfContentsEntryStyle attribute), 94

page_break (rinoh.structure.TableOfContentsStyle attribute), 90

page_break (rinoh.table.TableCellStyle attribute), 104

page_break (rinoh.table.TableStyle attribute), 102

page_number_format (rinoh.template.ContentsPartTemplate attribute), 138

page_number_format (rinoh.template.DocumentPartTemplate attribute), 137

page_number_format (rinoh.template.FixedDocumentPartTemplate attribute), 138

page_number_format (rinoh.template.TitlePartTemplate attribute), 137

page_orientation (rinoh.template.PageTemplate attribute), 140

page_orientation (rinoh.template.PageTemplateBase attribute), 142

page_orientation (rinoh.template.TitlePageTemplate attribute), 141

page_size (rinoh.template.PageTemplate attribute), 140

page_size (rinoh.template.PageTemplateBase attribute), 142

page_size (rinoh.template.TitlePageTemplate attribute), 141

PageBreak (class in rinoh.flowable), 115

PageOrientation (class in rinoh.document), 114

PageTemplate (class in rinoh.template), 139

PageTemplateBase (class in rinoh.template), 142

PageType (class in rinoh.document), 114

Paper (class in rinoh.paper), 125

Paragraph (class in rinoh.paragraph), 126

ParagraphBase (class in rinoh.paragraph), 125

ParagraphState (class in rinoh.paragraph), 126

ParagraphStyle (class in rinoh.paragraph), 61

parse_string() (rinoh.color.Color class method), 112

- ParseError, 111
- parts (rinoh.template.DocumentTemplate attribute), 135
- parts (rinoh.templates.article.Article attribute), 106
- parts (rinoh.templates.book.Book attribute), 107
- PartsList (class in rinoh.template), 136
- PATH, 11
- PERCENT (in module rinoh.dimension), 113
- PICA (in module rinoh.dimension), 113
- PL (in module rinoh.language), 123
- place() (rinoh.document.Page method), 114
- Polygon (class in rinoh.draw), 114
- position (rinoh.image.CaptionStyle attribute), 55
- position (rinoh.paragraph.ParagraphStyle attribute), 64
- position (rinoh.reference.NoteMarkerStyle attribute), 73
- position (rinoh.reference.ReferencingParagraphStyle attribute), 71
- position (rinoh.structure.HeadingStyle attribute), 79
- position (rinoh.structure.ListItemLabelStyle attribute), 86
- position (rinoh.structure.TableOfContentsEntryStyle attribute), 95
- position (rinoh.structure.TableOfContentsStyle attribute), 91
- position (rinoh.text.TextStyle attribute), 65
- prepare() (rinoh.flowable.LabeledFlowable method), 116
- prepare() (rinoh.flowable.StaticGroupedFlowables method), 116
- prepare() (rinoh.image.Caption method), 120
- prepare() (rinoh.reference.NoteMarkerBase method), 129
- prepare() (rinoh.reference.NoteMarkerWithNote method), 130
- prepare() (rinoh.reference.RegisterNote method), 129
- prepare() (rinoh.structure.Heading method), 130
- prepare() (rinoh.table.Table method), 134
- prepare() (rinoh.table.TableRow method), 134
- prepare() (rinoh.table.TableSection method), 134
- prepare() (rinoh.text.MixedStyledText method), 127
- ProportionalSpacing (class in rinoh.paragraph), 127
- PT (in module rinoh.dimension), 112

Q

- QUARTERS (in module rinoh.dimension), 113

R

- Rectangle (class in rinoh.draw), 114
- Reference (class in rinoh.reference), 129
- ReferenceField (class in rinoh.reference), 129
- ReferenceText (class in rinoh.reference), 129
- ReferenceType (class in rinoh.reference), 129
- ReferencingParagraph (class in rinoh.reference), 129
- ReferencingParagraphStyle (class in rinoh.reference), 68
- RegisterNote (class in rinoh.reference), 129
- render() (rinoh.document.Document method), 113
- render() (rinoh.document.Page method), 114
- render() (rinoh.flowable.GroupedFlowables method), 116
- render() (rinoh.flowable.GroupedLabeledFlowables method), 117
- render() (rinoh.flowable.LabeledFlowable method), 116
- render() (rinoh.paragraph.ParagraphBase method), 125
- render() (rinoh.structure.HorizontalRule method), 132
- render() (rinoh.table.Table method), 134
- repeat_head (rinoh.table.TableStyle attribute), 100
- rgba() (rinoh.color.Color property), 112
- right_margin (rinoh.template.PageTemplate attribute), 140

- right_margin (rinoh.template.PageTemplateBase attribute), 142
- right_margin (rinoh.template.TitlePageTemplate attribute), 141
- rinoh command line option
 - docs, 32
 - format <format>, 31
 - help, 31
 - install-resources, 31
 - list-fonts <filename>, 32
 - list-formats, 32
 - list-options <frontend>, 32
 - list-stylesheets, 31
 - list-templates, 31
 - option <option=value>, 31
 - output <filename or directory>, 31
 - paper <paper>, 31
 - stylesheet <name or filename>, 31
 - template <name or filename>, 31
 - version, 32
 - f <format>, 31
 - h, 31
 - i, 31
 - O <filename or directory>, 31
 - o <option=value>, 31
 - p <paper>, 31
 - s <name or filename>, 31
 - t <name or filename>, 31
- input, 31
- rinoh.attribute
 - module, 111
- rinoh.color
 - module, 111
- rinoh.dimension
 - module, 112
- rinoh.document
 - module, 113
- rinoh.draw
 - module, 114
- rinoh.flowable
 - module, 115
- rinoh.font
 - module, 117
- rinoh.font.style
 - module, 119
- rinoh.image
 - module, 119
- rinoh.index
 - module, 121
- rinoh.inline
 - module, 127
- rinoh.language
 - module, 121
- rinoh.number
 - module, 124
- rinoh.paper
 - module, 125
- rinoh.paragraph
 - module, 125
- rinoh.reference

- module, 129
- rinoh.strings
 - module, 132
- rinoh.structure
 - module, 130
- rinoh.style
 - module, 133
- rinoh.stylesheets
 - module, 33
- rinoh.table
 - module, 134
- rinoh.template
 - module, 135
- rinoh.templates.article
 - module, 105
- rinoh.templates.book
 - module, 107
- rinoh.text
 - module, 126
- rinoh_documents
 - Sphinx builder configuration value, 32
- rinoh_domain_indices
 - Sphinx builder configuration value, 33
- rinoh_logo
 - Sphinx builder configuration value, 33
- rinoh_metadata
 - Sphinx builder configuration value, 33
- rinoh_paper_size
 - Sphinx builder configuration value, 33
- rinoh_stylesheet
 - Sphinx builder configuration value, 32
- rinoh_template
 - Sphinx builder configuration value, 32
- root() (rinoh.attribute.RuleSetFile property), 111
- rotate (rinoh.image.ImageArgs attribute), 120
- RuleSet (class in rinoh.attribute), 111
- RuleSetFile (class in rinoh.attribute), 111

S

- Scale (class in rinoh.image), 120
- scale (rinoh.image.ImageArgs attribute), 120
- script_level() (rinoh.text.StyledText method), 126
- Section (class in rinoh.structure), 130
- SectionStyle (class in rinoh.structure), 74
- SectionTitles (class in rinoh.structure), 130
- seealso (rinoh.structure.AdmonitionTitles attribute), 132
- SetMetadataFlowable (class in rinoh.flowable), 115
- Shape (class in rinoh.draw), 114
- ShapeStyle (class in rinoh.draw), 43
- show_author (rinoh.template.TitlePageTemplate attribute), 141
- show_date (rinoh.template.TitlePageTemplate attribute), 141
- show_in_toc (rinoh.structure.SectionStyle attribute), 74
- SINGLE (in module rinoh.paragraph), 128
- SingleStyledText (class in rinoh.text), 126
- space_above (rinoh.flowable.FloatStyle attribute), 50
- space_above (rinoh.flowable.FlowableStyle attribute), 43
- space_above (rinoh.flowable.GroupedFlowablesStyle attribute), 48

- space_above (rinoh.flowable.LabeledFlowableStyle attribute), 46
- space_above (rinoh.image.CaptionStyle attribute), 53
- space_above (rinoh.image.FigureStyle attribute), 56
- space_above (rinoh.index.IndexStyle attribute), 59
- space_above (rinoh.inline.InlineFlowableStyle attribute), 66
- space_above (rinoh.paragraph.ParagraphStyle attribute), 61
- space_above (rinoh.reference.ReferencingParagraphStyle attribute), 69
- space_above (rinoh.structure.AdmonitionStyle attribute), 96
- space_above (rinoh.structure.HeadingStyle attribute), 77
- space_above (rinoh.structure.HorizontalRuleStyle attribute), 98
- space_above (rinoh.structure.ListItemLabelStyle attribute), 84
- space_above (rinoh.structure.ListStyle attribute), 81
- space_above (rinoh.structure.SectionStyle attribute), 75
- space_above (rinoh.structure.TableOfContentsEntryStyle attribute), 93
- space_above (rinoh.structure.TableOfContentsStyle attribute), 88
- space_above (rinoh.table.TableCellStyle attribute), 103
- space_above (rinoh.table.TableStyle attribute), 100
- space_below (rinoh.flowable.FloatStyle attribute), 50
- space_below (rinoh.flowable.FlowableStyle attribute), 43
- space_below (rinoh.flowable.GroupedFlowablesStyle attribute), 48
- space_below (rinoh.flowable.LabeledFlowableStyle attribute), 46
- space_below (rinoh.image.CaptionStyle attribute), 53
- space_below (rinoh.image.FigureStyle attribute), 57
- space_below (rinoh.index.IndexStyle attribute), 59
- space_below (rinoh.inline.InlineFlowableStyle attribute), 66
- space_below (rinoh.paragraph.ParagraphStyle attribute), 61
- space_below (rinoh.reference.ReferencingParagraphStyle attribute), 69
- space_below (rinoh.structure.AdmonitionStyle attribute), 96
- space_below (rinoh.structure.HeadingStyle attribute), 77
- space_below (rinoh.structure.HorizontalRuleStyle attribute), 98
- space_below (rinoh.structure.ListItemLabelStyle attribute), 84
- space_below (rinoh.structure.ListStyle attribute), 81
- space_below (rinoh.structure.SectionStyle attribute), 75
- space_below (rinoh.structure.TableOfContentsEntryStyle attribute), 93
- space_below (rinoh.structure.TableOfContentsStyle attribute), 88
- space_below (rinoh.table.TableCellStyle attribute), 103
- space_below (rinoh.table.TableStyle attribute), 101
- sphinx (in module rinoh.stylesheets), 33
- Sphinx builder configuration value
 - rinoh_documents, 32
 - rinoh_domain_indices, 33
 - rinoh_logo, 33
 - rinoh_metadata, 33
 - rinoh_paper_size, 33
 - rinoh_stylesheet, 32
 - rinoh_template, 32
- sphinx_article (in module rinoh.stylesheets), 34
- sphinx_base14 (in module rinoh.stylesheets), 34
- split_minimum_rows (rinoh.table.TableStyle attribute), 100
- STANDARD (in module rinoh.paragraph), 128
- StaticGroupedFlowables (class in rinoh.flowable), 116
- String (class in rinoh.strings), 132
- StringCollection (class in rinoh.strings), 132
- StringField (class in rinoh.strings), 132
- Strings (class in rinoh.strings), 132
- strings (rinoh.template.DocumentTemplate attribute), 135
- strings (rinoh.templates.article.Article attribute), 106
- strings (rinoh.templates.book.Book attribute), 107

- Stroke (class in `rinoh.draw`), 114
- stroke (`rinoh.draw.LineStyle` attribute), 43
- stroke (`rinoh.draw.ShapeStyle` attribute), 43
- stroke (`rinoh.structure.HorizontalRuleStyle` attribute), 100
- stroke (`rinoh.table.TableCellBackgroundStyle` attribute), 105
- stroke (`rinoh.table.TableCellBorderStyle` attribute), 105
- Style (class in `rinoh.style`), 133
- style log, 27
- style_class (`rinoh.draw.Line` attribute), 114
- style_class (`rinoh.draw.Shape` attribute), 114
- style_class (`rinoh.flowable.GroupedFlowables` attribute), 116
- style_class (`rinoh.flowable.LabeledFlowable` attribute), 116
- style_class (`rinoh.image.Caption` attribute), 120
- style_class (`rinoh.image.Figure` attribute), 120
- style_class (`rinoh.index.Index` attribute), 121
- style_class (`rinoh.inline.InlineFlowable` attribute), 127
- style_class (`rinoh.number.NumberedParagraph` attribute), 124
- style_class (`rinoh.paragraph.Paragraph` attribute), 126
- style_class (`rinoh.paragraph.ParagraphBase` attribute), 125
- style_class (`rinoh.reference.NoteMarkerBase` attribute), 129
- style_class (`rinoh.reference.ReferencingParagraph` attribute), 129
- style_class (`rinoh.structure.Admonition` attribute), 131
- style_class (`rinoh.structure.Heading` attribute), 130
- style_class (`rinoh.structure.HorizontalRule` attribute), 132
- style_class (`rinoh.structure.List` attribute), 131
- style_class (`rinoh.structure.TableOfContents` attribute), 131
- style_class (`rinoh.structure.TableOfContentsEntry` attribute), 131
- style_class (`rinoh.style.Styled` attribute), 133
- style_class (`rinoh.table.Table` attribute), 134
- style_class (`rinoh.table.TableCell` attribute), 135
- style_class (`rinoh.table.TableCellBackground` attribute), 135
- style_class (`rinoh.table.TableCellBorder` attribute), 135
- style_class (`rinoh.table.TableWithCaption` attribute), 134
- style_class (`rinoh.text.StyledText` attribute), 126
- Styled (class in `rinoh.style`), 133
- StyledMatcher (class in `rinoh.style`), 134
- StyledText (class in `rinoh.text`), 126
- StyleSheet (class in `rinoh.style`), 133
- stylesheet (`rinoh.template.DocumentTemplate` attribute), 135
- stylesheet (`rinoh.templates.article.Article` attribute), 105
- stylesheet (`rinoh.templates.book.Book` attribute), 107
- StyleSheetFile (class in `rinoh.style`), 134

T

- tab_stops (`rinoh.image.CaptionStyle` attribute), 52
- tab_stops (`rinoh.paragraph.ParagraphStyle` attribute), 61
- tab_stops (`rinoh.reference.ReferencingParagraphStyle` attribute), 69
- tab_stops (`rinoh.structure.HeadingStyle` attribute), 77
- tab_stops (`rinoh.structure.ListItemLabelStyle` attribute), 84
- tab_stops (`rinoh.structure.TableOfContentsEntryStyle` attribute), 92
- tab_stops (`rinoh.structure.TableOfContentsStyle` attribute), 90
- TabAlign (class in `rinoh.paragraph`), 128
- Table (class in `rinoh.table`), 134
- table_of_contents (`rinoh.templates.article.Article` attribute), 105
- TableBody (class in `rinoh.table`), 134
- TableCell (class in `rinoh.table`), 135
- TableCellBackground (class in `rinoh.table`), 135

TableCellBackgroundStyle (class in rinoh.table), 105
 TableCellBorder (class in rinoh.table), 135
 TableCellBorderStyle (class in rinoh.table), 105
 TableCellStyle (class in rinoh.table), 102
 TableHead (class in rinoh.table), 134
 TableOfContents (class in rinoh.structure), 131
 TableOfContentsEntry (class in rinoh.structure), 131
 TableOfContentsEntryStyle (class in rinoh.structure), 92
 TableOfContentsSection (class in rinoh.structure), 131
 TableOfContentsStyle (class in rinoh.structure), 88
 TableRow (class in rinoh.table), 134
 TableSection (class in rinoh.table), 134
 TableStyle (class in rinoh.table), 100
 TableWithCaption (class in rinoh.table), 134
 TABLOID (in module rinoh.paper), 125
 TabStop (class in rinoh.paragraph), 128
 TabStopList (class in rinoh.paragraph), 129
 target_has_class() (rinoh.reference.ReferencingParagraph method), 129
 target_has_classes() (rinoh.reference.ReferencingParagraph method), 129
 target_style() (rinoh.reference.ReferencingParagraph method), 129
 template (rinoh.template.TemplateConfiguration attribute), 136
 TemplateConfiguration (class in rinoh.template), 136
 text (rinoh.reference.ReferencingParagraphStyle attribute), 68
 text (rinoh.structure.TableOfContentsEntryStyle attribute), 92
 text_align (rinoh.image.CaptionStyle attribute), 52
 text_align (rinoh.paragraph.ParagraphStyle attribute), 61
 text_align (rinoh.reference.ReferencingParagraphStyle attribute), 69
 text_align (rinoh.structure.HeadingStyle attribute), 77
 text_align (rinoh.structure.ListItemLabelStyle attribute), 84
 text_align (rinoh.structure.TableOfContentsEntryStyle attribute), 92
 text_align (rinoh.structure.TableOfContentsStyle attribute), 90
 TextAlign (class in rinoh.paragraph), 127
 TextPosition (class in rinoh.font.style), 119
 TextStyle (class in rinoh.text), 64
 tip (rinoh.structure.AdmonitionTitles attribute), 132
 title (rinoh.flowable.GroupedFlowablesStyle attribute), 48
 title (rinoh.image.FigureStyle attribute), 58
 title (rinoh.index.IndexStyle attribute), 59
 title (rinoh.structure.AdmonitionStyle attribute), 96
 title (rinoh.structure.ListStyle attribute), 81
 title (rinoh.structure.SectionStyle attribute), 74
 title (rinoh.structure.TableOfContentsStyle attribute), 88
 title (rinoh.table.TableCellStyle attribute), 102
 title (rinoh.templates.article.Article attribute), 106
 title (rinoh.templates.book.Book attribute), 107
 title_page (rinoh.templates.article.Article attribute), 106
 title_page (rinoh.templates.book.Book attribute), 108
 TitlePageTemplate (class in rinoh.template), 141
 TitlePartTemplate (class in rinoh.template), 137
 to_string() (rinoh.index.InlineIndexTarget method), 121
 to_string() (rinoh.text.StyledText method), 126
 top_margin (rinoh.template.PageTemplate attribute), 140
 top_margin (rinoh.template.PageTemplateBase attribute), 142
 top_margin (rinoh.template.TitlePageTemplate attribute), 141
 Typeface (class in rinoh.font), 118
 typeface (rinoh.image.CaptionStyle attribute), 54
 typeface (rinoh.paragraph.ParagraphStyle attribute), 63
 typeface (rinoh.reference.NoteMarkerStyle attribute), 72

typeface (rinoh.reference.ReferencingParagraphStyle attribute), 71
typeface (rinoh.structure.HeadingStyle attribute), 79
typeface (rinoh.structure.ListItemLabelStyle attribute), 86
typeface (rinoh.structure.TableOfContentsEntryStyle attribute), 94
typeface (rinoh.structure.TableOfContentsStyle attribute), 90
typeface (rinoh.text.TextStyle attribute), 64

U

update() (rinoh.style.StyledMatcher method), 134
UserStrings (class in rinoh.strings), 132

V

vertical_align (rinoh.table.TableCellStyle attribute), 102
VerticalAlign (class in rinoh.table), 135

W

WarnFlowable (class in rinoh.flowable), 115
warning (rinoh.structure.AdmonitionTitles attribute), 132
width (rinoh.flowable.FloatStyle attribute), 50
width (rinoh.flowable.FlowableStyle attribute), 43
width (rinoh.flowable.GroupedFlowablesStyle attribute), 47
width (rinoh.flowable.LabeledFlowableStyle attribute), 46
width (rinoh.image.CaptionStyle attribute), 52
width (rinoh.image.FigureStyle attribute), 56
width (rinoh.image.ImageArgs attribute), 120
width (rinoh.index.IndexStyle attribute), 58
width (rinoh.inline.InlineFlowableStyle attribute), 66
width (rinoh.paragraph.ParagraphStyle attribute), 61
width (rinoh.reference.ReferencingParagraphStyle attribute), 68
width (rinoh.structure.AdmonitionStyle attribute), 96
width (rinoh.structure.HeadingStyle attribute), 77
width (rinoh.structure.HorizontalRuleStyle attribute), 98
width (rinoh.structure.ListItemLabelStyle attribute), 84
width (rinoh.structure.ListStyle attribute), 81
width (rinoh.structure.SectionStyle attribute), 74
width (rinoh.structure.TableOfContentsEntryStyle attribute), 92
width (rinoh.structure.TableOfContentsStyle attribute), 88
width (rinoh.table.TableCellStyle attribute), 102
width (rinoh.table.TableStyle attribute), 100
wrap_label (rinoh.flowable.LabeledFlowableStyle attribute), 45

Y

y_offset() (rinoh.text.StyledText method), 126