



# Introduction to Computer Graphics with WebGL

Ed Angel

## Square Program Part 2

---

---

---

---

---

---

---



## WebGL and GLSL

- WebGL requires shaders and is based less on a state machine model than a data flow model
- Most state variables, attributes and related pre 3.1 OpenGL functions have been deprecated
- Action happens in shaders
- Job of application is to get data to GPU

---

---

---

---


---

---

---



## Execution Model



---

---


---

---

---

---

---



# Simple Vertex Shader

input from application

```

attribute vec4 vPosition;
void main(void)
{
    gl_Position = vPosition;
}

```

must link to variable in application

built in variable

Angel and Shreiner: Interactive Computer Graphics 7E © Addison-Wesley 2015

4

---

---

---


---

---

---

---

---




---

---

---


---

---

---

---

---



# Simple Fragment Program

```

precision mediump float;
void main(void)
{
    gl_FragColor = vec4(1.0, 0.0, 0.0, 1.0);
}

```

required by WebGL

GLSL type

built in variable

Angel and Shreiner: Interactive Computer Graphics 7E © Addison-Wesley 2015

6

---

---

---

---

---

---

---

---

## GLSL

- OpenGL Shading Language
- C-like with
  - Matrix and vector types (2, 3, 4 dimensional)
  - Overloaded operators
  - C++ like constructors
- Similar to Nvidia's Cg and Microsoft HLSL
- Code sent to shaders as source code
- WebGL functions compile, link and get information to shaders

---

---

---

---

---

---

---

## Program Organization

- HTML file
  - describe page
  - contains shaders
  - gather resources
  - open a canvas for drawing
- JS file
  - initial variables
  - establish a WebGL context
  - read, compile and link shaders into a program object
  - define listeners
  - compute and send data to GPU
  - render

---

---

---

---

---

---

---