

Citrix Virtual Apps and Desktops V4 Documentation Script ReadMe

NOTE: This script requires PowerShell V5 or later.

Support for non-English Versions of Microsoft Word

The script supports the following languages:

- Catalan
- Chinese
- Danish
- Dutch
- English
- Finnish
- French
- German
- Norwegian
- Portuguese
- Spanish
- Swedish

Prerequisites

Let us ensure we have the requirements before using PowerShell to document anything in a Citrix Virtual Apps and Desktops (CVAD) 2511 or later Site.

1. As of CVAD 2511, all the required PowerShell snap-ins are installed as a prerequisite on a Delivery Controller.
2. If the script runs remotely, you must manually install the PowerShell snap-ins.
 - a. Install the PowerShell snap-ins individually. Depending on the bitness of the computer, from the full CVAD 2511 or later installation media, install the following files from either x64 or x86 (?? is either 86 or 64):
 - i. Citrix Desktop Delivery Controller\ADIdentity_PowerShellSnapIn_x??
 - ii. Citrix Desktop Delivery Controller\Analytics_PowerShell_SnapIn_x??
 - iii. Citrix Desktop Delivery Controller\AppLibrary_PowerShell_SnapIn_x??
 - iv. Citrix Desktop Delivery Controller\Broker_PowerShell_SnapIn_x??
 - v. Citrix Desktop Delivery Controller\Configuration_PowerShell_SnapIn_x??
 - vi. Citrix Desktop Delivery Controller\ConfigurationLogging_PowerShell_SnapIn_x??
 - vii. Citrix Desktop Delivery Controller\DelegatedAdmin_PowerShellSnapIn_x??
 - viii. Citrix Desktop Delivery Controller\EnvTest_PowerShell_SnapIn_x??
 - ix. Citrix Desktop Delivery Controller\Host_PowerShell_SnapIn_x??
 - x. Citrix Desktop Delivery Controller\MachineCreation_PowerShellSnapIn_x??
 - xi. Citrix Desktop Delivery Controller\Monitor_PowerShellSnapIn_x??
 - xii. Citrix Desktop Delivery Controller\Orchestration_PowerShellSnapIn_x??
 - xiii. Citrix Desktop Delivery Controller\Storefront_PowerShellSnapIn_x??
 - xiv. Citrix Desktop Delivery Controller\Trust_PowerShellSnapIn_x??
 - xv. Citrix Desktop Delivery Controller\UserProfileManager_PowerShellSnapIn_x??
 - xvi. Citrix Desktop Delivery Controller\VdaUpdateService_PowerShellSnapIn_x??
 - xvii. Citrix Desktop Delivery Controller\XDPoshSnapin_x??
 - xviii. Citrix Policy\CitrixGroupPolicyManagement_x??
 - xix. DesktopStudio\PVS PowerShell SDK x??
 - xx. DesktopStudio\PzAppV_Studio_PowershellSnapin_x??
 - xxi. Licensing\LicensingAdmin_PowerShellSnapIn_x??

Script Usage

How to use this script?

1. Save the script as *CVAD_Inventory_V4.ps1* in your PowerShell scripts folder.
2. From the PowerShell prompt, change to your PowerShell scripts folder.
3. From the PowerShell prompt, type in:
 - a. *.\CVAD_Inventory_V4.ps1* and press *Enter*.
4. By default, an HTML document is created named after the CVAD 2511 or later Site.
5. If you use the *-MSWord* option, a Microsoft Word file is created named after the CVAD 2511 or later Site.
6. If you use the *-PDF* option, a PDF file is created named after the CVAD 2511 or later Site.
7. If you use the *-Text* option, a Text file is created named after the CVAD 2511 or later Site.

To run the script on a remote Controller:

.\CVAD_Inventory_V4.ps1 -AdminAddress DDCName and press *Enter*.

Full help text is available.

Get-Help *.\CVAD_Inventory_V4.ps1 -full*

The help text explains all the parameters the script accepts.

Help text

```
PS C:\CVADScript> get-help .\CVAD_Inventory_V4.ps1 -full
```

NAME

C:\CVADScript\CVAD_Inventory_V4.ps1

SYNOPSIS

Creates an inventory of a Citrix Virtual Apps and Desktops 2511 or later Site.

SYNTAX

```
C:\CVADScript\CVAD_Inventory_V4.ps1 [-AdminAddress <String>] [-HTML] [-Text]
[-MaxDetails] [-Administrators] [-Applications] [-BrokerRegistryKeys] [-Controllers]
[-Hardware] [-DeliveryGroups] [-DeliveryGroupsUtilization] [-Hosting] [-Logging]
[-StartDate <DateTime>] [-EndDate <DateTime>] [-MachineCatalogs] [-NoADPolicies]
[-NoPolicies] [-NoSessions] [-Policies] [-StoreFront] [-VDARegistryKeys] [-Section
<String[]>] [-AddDateTime] [-CSV] [-Dev] [-Folder <String>] [-Log] [-ScriptInfo]
[-ReportFooter] [-MSWord] [-PDF] [-CompanyAddress <String>] [-CompanyEmail <String>]
[-CompanyFax <String>] [-CompanyName <String>] [-CompanyPhone <String>] [-CoverPage
<String>] [-UserName <String>] [-SmtpServer <String>] [-SmtpPort <Int32>] [-UseSSL]
[-From <String>] [-To <String>] [<CommonParameters>]
```

DESCRIPTION

Creates an inventory of a Citrix Virtual Apps and Desktops (CVAD) 2511 or later Site using Microsoft PowerShell, Word, plain text, or HTML.

This script requires at least PowerShell version 5.

The default output is now HTML.

You do NOT have to run this script on a Controller. This script was developed and run from a Windows 10 VM.

You can run this script remotely using the -AdminAddress (AA) parameter.

This script supports CVAD versions starting with 2511.

If you are running XA/XD 7.0 through 7.7, please use:
<https://github.com/CarlWebster/Citrix-XenApp-XenDesktop-7-V1>

If you are running XA/XD 7.8 through CVAD 2006, please use:
<https://github.com/CarlWebster/Citrix-XenApp-XenDesktop-7-V2>

If you are running CVAD 2006 through 2511, please use:
<https://github.com/CarlWebster/Citrix-Virtual-Apps-and-Desktops-V3>

If you are running Citrix Cloud, please use:
<https://github.com/CarlWebster/Citrix-Cloud-Daas->

NOTE: The account used to run this script must have at least Read access to the SQL Server(s) that hold(s) the Citrix Site, Monitoring, and Logging databases.

By default, the script only gives summary information for:

- Administrators
- App-V Publishing
- Application Groups
- Applications
- Controllers
- Delivery Groups
- Hosting
- Logging

Machine Catalogs
Policies
StoreFront
Zones

The Summary information is what is shown in the top half of Citrix Studio for:

Machine Catalogs
Delivery Groups
Applications
Policies
Logging
Controllers
Administrators
Hosting
StoreFront

Using the MachineCatalogs parameter can cause the report to take a very long time to complete and can generate an extremely long report.

Using the DeliveryGroups parameter can cause the report to take a very long time to complete and can generate an extremely long report.

Using both the MachineCatalogs and DeliveryGroups parameters can cause the report to take an extremely long time to complete and generate an exceptionally long report.

Using BrokerRegistryKeys requires the script runs elevated.

Creates an output file named after the CVAD Site.

Word and PDF documents include a Cover Page, Table of Contents, and Footer.

Includes support for the following language versions of Microsoft Word:

Catalan
Chinese
Danish
Dutch
English
Finnish
French
German
Norwegian
Portuguese
Spanish
Swedish

PARAMETERS

-AdminAddress <String>

Specifies the address of a CVAD controller that the PowerShell snap-ins will connect to.

This can be provided as a hostname or an IP address.

This parameter defaults to Localhost.

This parameter has an alias of AA.

Required?	false
Position?	named
Default value	Localhost
Accept pipeline input?	false
Accept wildcard characters?	false

-HTML [<SwitchParameter>]

Creates an HTML file with an .html extension.

This parameter is set to True if no other output format is selected.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-Text [<SwitchParameter>]
Creates a formatted text file with a.txt extension.
This parameter is disabled by default.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-MaxDetails [<SwitchParameter>]
Adds maximum detail to the report.

This is the same as using the following parameters:

- Administrators
- Applications
- BrokerRegistryKeys
- Controllers
- DeliveryGroups
- HardWare
- Hosting
- Logging
- MachineCatalogs
- Policies
- StoreFront
- VDARegistryKeys

*****Requires the script runs elevated*****

Does not change the value of NoADPolicies.
Does not change the value of NoSessions.

WARNING: Using this parameter can create an extremely large report and
it can take a very long time to run.

This parameter has an alias of MAX.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-Administrators [<SwitchParameter>]
Give detailed information for Administrator Scopes and Roles.
This parameter is disabled by default.
This parameter has an alias of Admins.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-Applications [<SwitchParameter>]
Gives detailed information for all applications.
This parameter is disabled by default.

This parameter has an alias of Apps.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-BrokerRegistryKeys [<SwitchParameter>]

Adds information on 360 registry keys to the Controller section.

*****Requires the script runs elevated*****

For Word and PDF output, this adds 8 pages to the report per Controller.
For Text and HTML, this adds 315 lines to the report per Controller.

This parameter is disabled by default.
This parameter has an alias of BRK.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-Controllers [<SwitchParameter>]

Lists the following information to the Controllers section:

- List of installed Microsoft Hotfixes and Updates
- List of Citrix installed components
- List of Windows installed Roles and Features
- Appendix C: List of installed Microsoft Hotfixes and Updates for all Controllers
- Appendix D: List of Citrix installed components for all Controllers
- Appendix E: List of Windows installed Roles and Features for all Controllers

This parameter is disabled by default.
This parameter has an alias of DDC.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-Hardware [<SwitchParameter>]

Use WMI to gather hardware information on the Computer System, Disks, Processor, And Network Interface Cards

This parameter may require the script be run from an elevated PowerShell session using an account with permission to retrieve hardware information (i.e., Domain Admin or Local Administrator).

Selecting this parameter will add to both the time it takes to run the script and size of the report.

This parameter is disabled by default.
This parameter has an alias of HW.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-DeliveryGroups [<SwitchParameter>]

Gives detailed information on all desktops in all Desktop (Delivery) Groups.

Using the DeliveryGroups parameter can cause the report to take a very long time to complete, and can generate an extremely long report.

Using both the MachineCatalogs and DeliveryGroups parameters can cause the report to take an extremely long time to complete and generate an exceptionally long report.

This parameter is disabled by default.
This parameter has an alias of DG.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-DeliveryGroupsUtilization [<SwitchParameter>]

Gives a chart with the delivery group utilization for the last 7 days depending on the information in the database.

This option is only available when the report is generated in Word and requires Microsoft Excel to be locally installed.

Using the DeliveryGroupsUtilization parameter causes the report to take a longer time to complete and generates a longer report.

This parameter is disabled by default.
This parameter has an alias of DGU.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-Hosting [<SwitchParameter>]

Give detailed information for Hosts, Host Connections, and Resources.

This parameter is disabled by default.
This parameter has an alias of Host.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-Logging [<SwitchParameter>]

Give the Configuration Logging report with, by default, details for the previous seven days.

This parameter is disabled by default.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-StartDate <DateTime>
The start date for the Configuration Logging report.

The format for date only is MM/DD/YYYY.

Format to include a specific time range is "MM/DD/YYYY HH:MM:SS" in 24-hour format.
The double quotes are needed.

The default is today's date minus seven days.
This parameter has an alias of SD.

Required?	false
Position?	named
Default value	((Get-Date -displayhint date).AddDays(-7))
Accept pipeline input?	false
Accept wildcard characters?	false

-EndDate <DateTime>
The end date for the Configuration Logging report.

The format for date only is MM/DD/YYYY.

Format to include a specific time range is "MM/DD/YYYY HH:MM:SS" in 24-hour format.
The double quotes are needed.

The default is today's date.
This parameter has an alias of ED.

Required?	false
Position?	named
Default value	(Get-Date -displayhint date)
Accept pipeline input?	false
Accept wildcard characters?	false

-MachineCatalogs [<SwitchParameter>]
Gives detailed information for all machines in all Machine Catalogs.

Using the MachineCatalogs parameter can cause the report to take a very long time to complete, and can generate an extremely long report.

Using both the MachineCatalogs and DeliveryGroups parameters can cause the report to take an extremely long time to complete and generate an exceptionally long report.

This parameter is disabled by default.
This parameter has an alias of MC.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-NoADPolicies [<SwitchParameter>]
Excludes all Citrix AD-based policy information from the output document.
Includes only Site policies created in Studio.

This Switch is useful in large AD environments, where there may be thousands of policies, to keep SYSVOL from being searched.

This parameter is disabled by default.
This parameter has an alias of NoAD.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-NoPolicies [<SwitchParameter>]

Excludes all Site and Citrix AD-based policy information from the output document.

Using the NoPolicies parameter sets the Policies parameter to False.

This parameter is disabled by default.

This parameter has an alias of NP.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-NoSessions [<SwitchParameter>]

Excludes Machine Catalog, Application, and Hosting session data from the report.

Using the MaxDetails parameter does not change this setting.

This parameter is disabled by default.

This parameter has an alias of NS.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-Policies [<SwitchParameter>]

Give detailed information for both Site and Citrix AD-based Policies.

Using the Policies parameter can cause the report to take a very long time to complete and can generate an extremely long report.

There are three related parameters: Policies, NoPolicies, and NoADPolicies.

Policies and NoPolicies are mutually exclusive, and priority is given to NoPolicies.

This parameter is disabled by default.

This parameter has an alias of Pol.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-StoreFront [<SwitchParameter>]

Give detailed information for StoreFront.

This parameter is disabled by default.

This parameter has an alias of SF.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-VDARegistryKeys [<SwitchParameter>]

Adds registry key information to the Machine Details section.

If this parameter is used, MachineCatalogs is set to True.

This parameter is disabled by default.

This parameter has an alias of VRK.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-Section <String[]>

Processes one or more sections of the report.

Valid options are:

- Admins (Administrators)
- Apps (Applications and Application Group Details)
- AppV
- Catalogs (Machine Catalogs)
- Config (Configuration)
- Controllers
- Groups (Delivery Groups)
- Hosting
- Licensing
- Logging
- Policies
- StoreFront
- Zones
- All

This parameter defaults to All sections.

Multiple sections are separated by a comma. -Section catalogs, groups

Notes:

Using Logging will force the Logging Switch to True.

Using Policies will force the Policies Switch to True.

If Policies is selected and the NoPolicies Switch is used, the script will terminate.

Required?	false
Position?	named
Default value	All
Accept pipeline input?	false
Accept wildcard characters?	false

-AddDateTime [<SwitchParameter>]

Adds a date timestamp to the end of the file name.

The timestamp is in the format of yyyy-MM-dd_HH:mm.

June 1, 2027, at 6 PM is 2027-06-01_1800.

The output filename will be ReportName_2027-06-01_1800.docx (or.pdf).

This parameter is disabled by default.

This parameter has an alias of ADT.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-CSV [<SwitchParameter>]

Will create a CSV file for each Appendix.
The default value is False.

Output CSV filename is in the format:

CVADSiteName_Documentation_Appendix#_NameOfAppendix.csv

For example:

CVADSiteName_Documentation_AppendixA_VDARegistryItems.csv
CVADSiteName_Documentation_AppendixB_ControllerRegistryItems.csv
CVADSiteName_Documentation_AppendixC_MicrosoftHotfixesandUpdates.csv
CVADSiteName_Documentation_AppendixD_CitrixInstalledComponents.csv
CVADSiteName_Documentation_AppendixE_WindowsInstalledComponents.csv

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-Dev [<SwitchParameter>]

Clears errors at the beginning of the script.
Outputs all errors to a text file at the end of the script.

This is used when the script developer requests more troubleshooting data.
The text file is placed in the same folder as the script.

This parameter is disabled by default.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-Folder <String>

Specifies the optional output folder for the report.

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-Log [<SwitchParameter>]

Generates a log file for troubleshooting.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-ScriptInfo [<SwitchParameter>]

Outputs information about the script to a text file.
The text file is placed in the same folder as the script.

This parameter is disabled by default.
This parameter has an alias of SI.

Required?	false
Position?	named
Default value	False

Accept pipeline input? false
Accept wildcard characters? false

-ReportFooter [<SwitchParameter>]
Outputs a footer section at the end of the report.

This parameter has an alias of RF.

Report Footer
Report information:
Created with: <Script Name> - Release Date: <Script Release Date>
Script version: <Script Version>
Started on <Date Time in Local Format>
Elapsed time: nn days, nn hours, nn minutes, nn.nn seconds
Ran from domain <Domain Name> by user <Username>
Ran from the folder <Folder Name>

Script Name and Script Release date are script-specific variables.
Start Date Time in Local Format is a script variable.
Elapsed time is a calculated value.
Domain Name is \$env:USERDNSDOMAIN.
Username is \$env:USERNAME.
Folder Name is a script variable.

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-MSWord [<SwitchParameter>]
SaveAs DOCX file
This parameter is disabled by default.

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-PDF [<SwitchParameter>]
SaveAs PDF file instead of DOCX file.
This parameter is disabled by default.
The PDF file is roughly 5X to 10X larger than the DOCX file.
This parameter requires Microsoft Word to be installed.
This parameter uses the Word SaveAs PDF capability.

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-CompanyAddress <String>
Company Address to use for the Cover Page, if the Cover Page has the Address field.

The following Cover Pages have an Address field:
Banded (Word 2013/2016)
Contrast (Word 2010)
Exposure (Word 2010)
Filigree (Word 2013/2016)
Ion (Dark) (Word 2013/2016)
Retrospect (Word 2013/2016)

Semaphore (Word 2013/2016)
Tiles (Word 2010)
ViewMaster (Word 2013/2016)

This parameter is only valid with the MSWORD and PDF output parameters.
This parameter has an alias of CA.

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-CompanyEmail <String>

Company Email to use for the Cover Page, if the Cover Page has the Email field.

The following Cover Pages have an Email field:
Facet (Word 2013/2016)

This parameter is only valid with the MSWORD and PDF output parameters.
This parameter has an alias of CE.

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-CompanyFax <String>

Company Fax to use for the Cover Page, if the Cover Page has the Fax field.

The following Cover Pages have a Fax field:
Contrast (Word 2010)
Exposure (Word 2010)

This parameter is only valid with the MSWORD and PDF output parameters.
This parameter has an alias of CF.

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-CompanyName <String>

Company Name to use for the Cover Page.

The default value is contained in
HKCU:\Software\Microsoft\Office\Common\UserInfo\CompanyName or
HKCU:\Software\Microsoft\Office\Common\UserInfo\Company, whichever is populated
on the computer running the script.

This parameter is only valid with the MSWORD and PDF output parameters.
This parameter has an alias of CN.

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-CompanyPhone <String>

Company Phone to use for the Cover Page if the Cover Page has the Phone field.

The following Cover Pages have a Phone field:

Contrast (Word 2010)
Exposure (Word 2010)

This parameter is only valid with the MSWORD and PDF output parameters.
This parameter has an alias of CPh.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-CoverPage <String>

What Microsoft Word Cover Page to use.
Only Word 2010, 2013, and 2016 are supported.
(default cover pages in Word en-US)

Valid input is:

Alphabet (Word 2010. Works)
Annual (Word 2010. Doesn't work well for this report)
Austere (Word 2010. Works)
Austin (Word 2010/2013/2016. Doesn't work in 2013 or 2016, mostly works in 2010, but Subtitle/Subject & Author fields need moving after the title box is moved up)
Banded (Word 2013/2016. Works)
Conservative (Word 2010. Works)
Contrast (Word 2010. Works)
Cubicles (Word 2010. Works)
Exposure (Word 2010. Works if you like looking sideways)
Facet (Word 2013/2016. Works)
Filigree (Word 2013/2016. Works)
Grid (Word 2010/2013/2016. Works in 2010)
Integral (Word 2013/2016. Works)
Ion (Dark) (Word 2013/2016. Top date doesn't fit; box needs to be manually resized or font changed to 8 point)
Ion (Light) (Word 2013/2016. Top date doesn't fit; box needs to be manually resized or font changed to 8 point)
Mod (Word 2010. Works)
Motion (Word 2010/2013/2016. Works if the top date is manually changed to 36 point)
Newsprint (Word 2010. Works, but the date is not populated)
Perspective (Word 2010. Works)
Pinstripes (Word 2010. Works)
Puzzle (Word 2010. Top date doesn't fit; box needs to be manually resized or font changed to 14 point)
Retrospect (Word 2013/2016. Works)
Semaphore (Word 2013/2016. Works)
Sideline (Word 2010/2013/2016. Doesn't work in 2013 or 2016, works in 2010)
Slice (Dark) (Word 2013/2016. Doesn't work)
Slice (Light) (Word 2013/2016. Doesn't work)
Stacks (Word 2010. Works)
Tiles (Word 2010. Date doesn't fit unless changed to 26 point)
Transcend (Word 2010. Works)
ViewMaster (Word 2013/2016. Works)
Whisp (Word 2013/2016. Works)

The default value is Sideline.
This parameter has an alias of CP.
This parameter is only valid with the MSWORD and PDF output parameters.

Required? false

Position?	named
Default value	Sideline
Accept pipeline input?	false
Accept wildcard characters?	false

-UserName <String>
 Username to use for the Cover Page and Footer.
 The default value is contained in \$env:username
 This parameter has an alias of UN.
 This parameter is only valid with the MSWORD and PDF output parameters.

Required?	false
Position?	named
Default value	\$env:username
Accept pipeline input?	false
Accept wildcard characters?	false

-SmtpServer <String>
 Specifies the optional email server to send the output report.

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-SmtpPort <Int32>
 Specifies the SMTP port.
 The default is 25.

Required?	false
Position?	named
Default value	25
Accept pipeline input?	false
Accept wildcard characters?	false

-UseSSL [<SwitchParameter>]
 Specifies whether to use SSL for the SmtpServer.
 The default is False.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-From <String>
 Specifies the username for the From email address.
 If SmtpServer is used, this parameter is required.

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-To <String>
 Specifies the username for the To email address.
 If SmtpServer is used, this parameter is required.

Required?	false
Position?	named
Default value	


```
Accept pipeline input?      false
Accept wildcard characters?  false
```

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

None. You cannot pipe objects to this script.

OUTPUTS

No objects are output from this script.

This script creates a Word, PDF, plain text, or HTML document.

NOTES

```
NAME: CVAD_Inventory_V4.ps1
VERSION: 4.00
AUTHOR: Carl Webster
LASTEDIT: July 23, 2026
```

----- EXAMPLE 1 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1
```

Creates an HTML report by default.

The computer running the script for the AdminAddress.

----- EXAMPLE 2 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -MSWord
```

Uses all default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"

\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

Creates a Microsoft Word report.

The computer running the script for the AdminAddress.

----- EXAMPLE 3 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -AdminAddress DDC01
```

Creates an HTML report by default.

DDC01 for the AdminAddress.

----- EXAMPLE 4 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -PDF
```

Uses all default values and saves the document as a PDF file.

```
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or  
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"  
$env:username = Administrator
```

Carl Webster for the Company Name.
Sideline for the Cover Page format.
Administrator for the Username.
The computer running the script for the AdminAddress.

----- EXAMPLE 5 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -Text
```

Saves the document as a formatted text file.
The computer running the script for the AdminAddress.

----- EXAMPLE 6 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -HTML
```

Saves the document as an HTML file.
The computer running the script for the AdminAddress.

----- EXAMPLE 7 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -MachineCatalogs
```

Creates an HTML report with full details for all machines in all Machine Catalogs.
The computer running the script for the AdminAddress.

----- EXAMPLE 8 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -DeliveryGroups
```

Creates an HTML report with full details for all desktops in all Desktop (Delivery) Groups.
The computer running the script for the AdminAddress.

----- EXAMPLE 9 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -DeliveryGroupsUtilization -MSWord
```

Note: Using DeliveryGroupsUtilization requires the use of MSWord or PDF.

Creates a Microsoft Word report with utilization details for all Desktop (Delivery) Groups.

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

The computer running the script for the AdminAddress.

----- EXAMPLE 10 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -DeliveryGroupsUtilization -PDF
```

Note: Using DeliveryGroupsUtilization requires the use of MSWord or PDF.

Creates a PDF report with utilization details for all Desktop (Delivery) Groups.

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

The computer running the script for the AdminAddress.

----- EXAMPLE 11 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -DeliveryGroups -MachineCatalogs
```

Creates an HTML report with full details for all machines in all Machine Catalogs and all desktops in all Delivery Groups.

The computer running the script for the AdminAddress.

----- EXAMPLE 12 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -Applications
```

Creates an HTML report with full details for all applications.

The computer running the script for the AdminAddress.

----- EXAMPLE 13 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -Policies
```

Creates an HTML report with full details for Policies.
The computer running the script for the AdminAddress.

----- EXAMPLE 14 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -NoPolicies
```

Creates an HTML report with no Policy information.
The computer running the script for the AdminAddress.

----- EXAMPLE 15 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -NoADPolicies
```

Creates an HTML report with no Citrix AD-based Policy information.
The computer running the script for the AdminAddress.

----- EXAMPLE 16 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -Policies -NoADPolicies
```

Creates an HTML report with full details on the Site policies created in Web Studio
but no Citrix AD-based Policy information.

The computer running the script for the AdminAddress.

----- EXAMPLE 17 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -Administrators
```

Creates an HTML report with full details on Administrator Scopes and Roles.
The computer running the script for the AdminAddress.

----- EXAMPLE 18 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -Logging -StartDate 09/01/2027 -EndDate  
09/30/2027
```

Creates an HTML report with Configuration Logging details for the dates 09/01/2027
through 09/30/2027.

The computer running the script for the AdminAddress.

----- EXAMPLE 19 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -Logging -StartDate "09/01/2027 10:00:00"
-EndDate "09/01/2027 14:00:00" -MSWord
```

Creates a Microsoft Word report with Configuration Logging details for the time range 09/01/2027 10:00:00AM through 09/01/2027 02:00:00PM.

Narrowing the report down to seconds does not work. Seconds must be either 00 or 59.

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"

\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

The computer running the script for the AdminAddress.

----- EXAMPLE 20 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -Hosting
```

Creates an HTML report with full details for Hosts, Host Connections, and Resources. The computer running the script for the AdminAddress.

----- EXAMPLE 21 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -StoreFront
```

Creates an HTML report with full details for StoreFront.

The computer running the script for the AdminAddress.

----- EXAMPLE 22 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -MachineCatalogs -DeliveryGroups
-Applications -Policies -Hosting -StoreFront
```

Creates an HTML report with full details for all:

- Machines in all Machine Catalogs

- Desktops in all Delivery Groups

- Applications

- Policies

- Hosts, Host Connections, and Resources

- StoreFront

The computer running the script for the AdminAddress.

----- EXAMPLE 23 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -MC -DG -Apps -Policies -Hosting -PDF
```

Creates a PDF report with full details for all:

- Machines in all Machine Catalogs
- Desktops in all Delivery Groups
- Applications
- Policies
- Hosts, Host Connections, and Resources

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"

\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

The computer running the script for the AdminAddress.

----- EXAMPLE 24 -----

```
PS C:\>PS C:\PSScript.\CVAD_Inventory_V4.ps1 -MSWord -CompanyName "Carl Webster Consulting" -CoverPage "Mod" -UserName "Carl Webster" -AdminAddress DDC01
```

Creates a Microsoft Word report.

Uses:

Carl Webster Consulting for the Company Name.

Mod for the Cover Page format.

Carl Webster for the Username.

Controller named DDC01 for the AdminAddress.

----- EXAMPLE 25 -----

```
PS C:\>PS C:\PSScript.\CVAD_Inventory_V4.ps1 -CN "Carl Webster Consulting" -CP "Mod" -UN "Carl Webster" -MSWord
```

Creates a Microsoft Word report.

Uses:

Carl Webster Consulting for the Company Name (alias CN).

Mod for the Cover Page format (alias CP).

Carl Webster for the Username (alias UN).

The computer running the script for the AdminAddress.

----- EXAMPLE 26 -----

```
PS C:\>PS C:\PSScript.\CVAD_Inventory_V4.ps1 -MSWord -CompanyName "Sherlock Holmes Consulting" -CoverPage Exposure -UserName "Dr. Watson" -CompanyAddress "221B Baker Street, London, England" -CompanyFax "+44 1753 276600" -CompanyPhone "+44 1753 276200"
```

Creates a Microsoft Word report.

Uses:

Sherlock Holmes Consulting for the Company Name.
Exposure for the Cover Page format.
Dr. Watson for the Username.
221B Baker Street, London, England, for the Company Address.
+44 1753 276600 for the Company Fax.
+44 1753 276200 for the Company Phone.
The computer running the script for the AdminAddress.

----- EXAMPLE 27 -----

```
PS C:\>PS C:\PSScript.\CVAD_Inventory_V4.ps1 -MSWord -CompanyName "Sherlock Holmes Consulting" -CoverPage Facet -UserName "Dr. Watson" -CompanyEmail SuperSleuth@SherlockHolmes.com
```

Creates a Microsoft Word report.

Uses:

Sherlock Holmes Consulting for the Company Name.
Facet for the Cover Page format.
Dr. Watson for the Username.
SuperSleuth@SherlockHolmes.com for the Company Email.
The computer running the script for the AdminAddress.

----- EXAMPLE 28 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -AddDateTime
```

Creates an HTML report.

Adds a date and time stamp to the end of the file name.
The timestamp is in the format of yyyy-MM-dd_HH:mm.
June 1, 2027, at 6 PM is 2027-06-01_1800.
The output filename will be CVADSiteName_2027-06-01_1800.docx
The computer running the script for the AdminAddress.

----- EXAMPLE 29 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -PDF -AddDateTime
```

Creates a PDF report.

Uses all Default values and saves the document as a PDF file.
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.
Sideline for the Cover Page format.
Administrator for the Username.

Adds a date and time stamp to the end of the file name.
The timestamp is in the format of yyyy-MM-dd_HH:mm.
June 1, 2027, at 6PM is 2027-06-01_1800.
The output filename will be CVADSiteName_2027-06-01_1800.pdf

The computer running the script for the AdminAddress.

----- EXAMPLE 30 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -Hardware
```

Creates an HTML report with hardware information for the Controllers.
The computer running the script for the AdminAddress.

----- EXAMPLE 31 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -Folder \\FileServer\ShareName
```

Creates an HTML report.
Output file is saved in the path \\FileServer\ShareName
The computer running the script for the AdminAddress.

----- EXAMPLE 32 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -Section Policies
```

Creates an HTML report that contains only policy information.
Processes only the Policies section of the report.
The computer running the script for the AdminAddress.

----- EXAMPLE 33 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -Section Groups -DG
```

Creates an HTML report.
Processes only the Delivery Groups section of the report with Delivery Group details.
The computer running the script for the AdminAddress.

----- EXAMPLE 34 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -Section Groups
```

Creates an HTML report.
Processes only the Delivery Groups section of the report, excluding the Delivery Group details.
The computer running the script for the AdminAddress.

----- EXAMPLE 35 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -Section Config, Licensing -HTML
```


Creates an HTML report.

The report includes only the Configuration and Licensing sections.

----- EXAMPLE 36 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -BrokerRegistryKeys
```

Creates an HTML report.

*****Requires the script runs elevated*****

Adds the information on over 300 Broker registry keys to the Controllers section.
The computer running the script for the AdminAddress.

----- EXAMPLE 37 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -VDARegistryKeys
```

Creates an HTML report.

Adds the information on VDA registry keys to Appendix A.
Forces the MachineCatalogs parameter to \$True
The computer running the script for the AdminAddress.

----- EXAMPLE 38 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -MaxDetails
```

Set the following parameter values:

Administrators	= True
Applications	= True
BrokerRegistryKeys	= True
Controllers	= True
DeliveryGroups	= True
HardWare	= True
Hosting	= True
Logging	= True
MachineCatalogs	= True
Policies	= True
StoreFront	= True
VDARegistryKeys	= True
NoPolicies	= False
Section	= "All"

*****Requires the script runs elevated*****

Creates an HTML report.

The computer running the script for the AdminAddress.

----- EXAMPLE 39 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -MaxDetails -HTML -MSWord -PDF -Text
```

Creates four reports: HTML, Microsoft Word, PDF, and plain text.

For Microsoft Word and PDF, use all Default values.

```
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or
```

```
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
$env:username = Administrator
```

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

Set the following parameter values:

```
Administrators      = True
Applications        = True
BrokerRegistryKeys = True
Controllers         = True
DeliveryGroups      = True
HardWare            = True
Hosting             = True
Logging             = True
MachineCatalogs    = True
Policies            = True
StoreFront          = True
VDARegistryKeys     = True

NoPolicies          = False
Section             = "All"
```

*****Requires the script runs elevated*****

The computer running the script for the AdminAddress.

----- EXAMPLE 40 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -Dev -ScriptInfo -Log
```

Creates an HTML report.

Creates a text file named CVADInventoryScriptErrors_yyyyMMddTHHmssffff.txt that contains up to the last 250 errors reported by the script.

Creates a text file named CVADInventoryScriptInfo_yyyy-MM-dd_HHmm.txt that contains all the script parameters and other basic information.

Creates a text file for transcript logging named CVADDocScriptTranscript_yyyyMMddTHHmssffff.txt.

----- EXAMPLE 41 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -CSV
```

Uses all Default values.

LocalHost for AdminAddress.

Creates a CSV file for each Appendix.

For example:

```
CVADSiteName_Documentation_AppendixA_VDARegistryItems.csv
CVADSiteName_Documentation_AppendixB_ControllerRegistryItems.csv
CVADSiteName_Documentation_AppendixC_MicrosoftHotfixesandUpdates.csv
CVADSiteName_Documentation_AppendixD_CitrixInstalledComponents.csv
CVADSiteName_Documentation_AppendixE_WindowsInstalledComponents.csv
```

----- EXAMPLE 42 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -MaxDetails -HTML -MSWord -PDF -Text -Dev
-ScriptInfo -Log -CSV
```

Creates four reports: HTML, Microsoft Word, PDF, and plain text.

Creates a text file named CVADInventoryScriptErrors_yyyy-MM-dd_HHmm.txt that contains up to the last 250 errors reported by the script.

Creates a text file named CVADInventoryScriptInfo_yyyy-MM-dd_HHmm.txt that contains all the script parameters and other basic information.

Creates a text file for transcript logging named
CVADDocScriptTranscript_yyyy-MM-dd_HHmm.txt.

Creates a CSV file for each Appendix.

For example:

```
CVADSiteName_Documentation_AppendixA_VDARegistryItems.csv
CVADSiteName_Documentation_AppendixB_ControllerRegistryItems.csv
CVADSiteName_Documentation_AppendixC_MicrosoftHotfixesandUpdates.csv
CVADSiteName_Documentation_AppendixD_CitrixInstalledComponents.csv
CVADSiteName_Documentation_AppendixE_WindowsInstalledComponents.csv
```

For Microsoft Word and PDF, uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"

\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

Set the following parameter values:

```
Administrators      = True
Applications        = True
BrokerRegistryKeys = True
Controllers         = True
DeliveryGroups      = True
HardWare            = True
Hosting             = True
Logging             = True
MachineCatalogs    = True
Policies            = True
StoreFront          = True
VDARegistryKeys     = True

NoPolicies          = False
Section             = "All"
```

*****Requires the script runs elevated*****

The computer running the script for the AdminAddress.

----- EXAMPLE 43 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -SmtpServer mail.domain.tld -From  
CVADAdmin@domain.tld -To ITGroup@domain.tld
```

The script uses the email server mail.domain.tld, sending from CVADAdmin@domain.tld and sending to ITGroup@domain.tld.

The script uses the default SMTP port 25 and does not use SSL.

If the current user's credentials are not valid to send email, the script prompts the user to enter valid credentials.

Creates an HTML report.

The computer running the script for the AdminAddress.

----- EXAMPLE 44 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -SmtpServer mailrelay.domain.tld -From  
Anonymous@domain.tld -To ITGroup@domain.tld
```

SENDING UNAUTHENTICATED EMAIL

The script uses the email server mailrelay.domain.tld, sending from anonymous@domain.tld and sending to ITGroup@domain.tld.

To send an unauthenticated email using an email relay server requires the From email account to use the name Anonymous.

The script uses the default SMTP port 25 and does not use SSL.

GMAIL/G SUITE SMTP RELAY

<https://support.google.com/a/answer/2956491?hl=en>
<https://support.google.com/a/answer/176600?hl=en>

To send an email using a Gmail or Google Workspace account, you may have to turn ON the "Less secure app access" option on your account.

GMAIL/G SUITE SMTP RELAY

The script generates an anonymous, secure password for the anonymous@domain.tld account.

Creates an HTML report.

The computer running the script for the AdminAddress.

----- EXAMPLE 45 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -SmtpServer
labaddomain-com.mail.protection.outlook.com -UseSSL -From
SomeEmailAddress@labaddomain.com -To ITGroupDL@labaddomain.com
```

OFFICE 365 Example

<https://docs.microsoft.com/en-us/exchange/mail-flow-best-practices/how-to-set-up-a-multifunction-device-or-application-to-send-email-using-office-3>

This uses Option 2 from the above link.

OFFICE 365 Example

The script uses the email server labaddomain-com.mail.protection.outlook.com, sending from SomeEmailAddress@labaddomain.com and sending to ITGroupDL@labaddomain.com.

The script uses the default SMTP port 25 and SSL.

Creates an HTML report.

The computer running the script for the AdminAddress.

----- EXAMPLE 46 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -SmtpServer smtp.office365.com -SmtpPort 587
-UseSSL -From Webster@CarlWebster.com -To ITGroup@CarlWebster.com
```

The script uses the email server smtp.office365.com on port 587 using SSL, sending from webster@carlwebster.com and sending to ITGroup@carlwebster.com.

If the current user's credentials are not valid to send an email, the script prompts the user to enter valid credentials.

Creates an HTML report.

The computer running the script for the AdminAddress.

----- EXAMPLE 47 -----

```
PS C:\PSScript >.\CVAD_Inventory_V4.ps1 -SmtpServer smtp.gmail.com -SmtpPort 587
-UseSSL -From Webster@CarlWebster.com -To ITGroup@CarlWebster.com
```

*** NOTE ***

To send an email using a Gmail or Google Workspace account, you may have to turn ON the "Less secure app access" option on your account.

*** NOTE ***

The script uses the email server smtp.gmail.com on port 587 using SSL, sending from webster@gmail.com and sending to ITGroup@carlwebster.com.

If the current user's credentials are not valid to send an email, the script prompts the user to enter valid credentials.

Creates an HTML report.

The computer running the script for the AdminAddress.

RELATED LINKS