

XenDesktop 7.x Version 1 Documentation Script ReadMe

NOTE: This script requires PowerShell V3 or later.

NOTE: Best performance is obtained by using PowerShell V5.

NOTE: Word 2007 is not supported.

Support for non-English Versions of Microsoft Word

The script supports the following languages:

- Catalan
- Chinese
- Danish
- Dutch
- English
- Finnish
- French
- German
- Norwegian
- Portuguese
- Spanish
- Swedish

Prerequisites

Let us ensure we have the requirements before using PowerShell to document anything in a XenDesktop 7.x Site.

1. If the script runs remotely, there are two choices: install Citrix Studio or manually install the PowerShell snapins.
 - a. Install Studio from the full XenDesktop 7.x installation media. Installing Citrix Studio installs all the necessary PowerShell snapins.
 - b. Install the PowerShell snapins individually. Depending on the bitness of the computer, from the full XenDesktop 7.x installation media, install the following files from either x64 or x86 (?? is either 86 or 64):
 - i. Citrix Desktop Delivery Controller\ADIdentity_PowerShellSnapIn_x??
 - ii. (Only for XenDesktop 7.6 and later) Citrix Desktop Delivery Controller\Analytics_PowerShell_SnapIn_x??
 - iii. Citrix Desktop Delivery Controller\Broker_PowerShell_SnapIn_x??
 - iv. Citrix Desktop Delivery Controller\Configuration_PowerShell_SnapIn_x??
 - v. Citrix Desktop Delivery Controller\ConfigurationLogging_PowerShell_SnapIn_x??
 - vi. Citrix Desktop Delivery Controller\DelegatedAdmin_PowerShellSnapIn_x??
 - vii. Citrix Desktop Delivery Controller\EnvTest_PowerShell_SnapIn_x??
 - viii. Citrix Desktop Delivery Controller\Host_PowerShell_SnapIn_x??
 - ix. Citrix Desktop Delivery Controller\MachineCreation_PowerShellSnapIn_x??
 - x. Citrix Desktop Delivery Controller\Monitor_PowerShellSnapIn_x??
 - xi. Citrix Desktop Delivery Controller\Storefront_PowerShellSnapIn_x??
 - xii. Citrix Policy\CitrixGroupPolicyManagement_x??
 - xiii. DesktopStudio\PxAppV_Studio_PowershellSnapin_x??
 - xiv. Licensing\LicensingAdmin_PowerShellSnapIn_x??

Script Usage

How to use this script?

1. Save the script as *XD7_Inventory.ps1* in your PowerShell scripts folder.
2. From the PowerShell prompt, change to your PowerShell scripts folder.
3. From the PowerShell prompt, type in:
 - a. *.\XD7_Inventory.ps1* and press *Enter*.
4. By default, a Microsoft Word document is created named after the XenDesktop 7.x Site.
5. If you use the *–PDF* option, a PDF file is created named after the XenDesktop 7.x Site.
6. If you use the *–HTML* option, an HTML file is created named after the XenDesktop 7.x Site.
7. If you use the *–Text* option, a Text file is created named after the XenDesktop 7.x Site.

To run the script against a remote Controller:

.\XD7_Inventory.ps1-AdminAddress DDCName and press *Enter*.

Full help text is available.

Get-Help *.\XD7_Inventory.ps1 –full*

The help text explains all the parameters the script accepts.

Help text

NAME

C:\Scripts\XD7_Inventory.ps1

SYNOPSIS

Creates an inventory of a Citrix XenDesktop 7.0 through 7.7 Site.

SYNTAX

```
C:\Scripts\XD7_Inventory.ps1 [-AdminAddress <String>] [-Administrators]
[-Applications] [-DeliveryGroups] [-DeliveryGroupsUtilization] [-Hardware]
[-Hosting] [-Logging] [-StartDate <DateTime>] [-EndDate <DateTime>]
[-MachineCatalogs] [-NoADPolicies] [-NoPolicies] [-NoSessions] [-Policies]
[-StoreFront] [-MaxDetails] [-Section <String[]>] [-AddDateTime]
[-Dev] [-Folder <String>] [-Log] [-ScriptInfo] [-ReportFooter] [-MSWord]
[-CompanyAddress <String>] [-CompanyEmail <String>] [-CompanyFax <String>]
[-CompanyName <String>] [-CompanyPhone <String>] [-CoverPage <String>] [-UserName
<String>] [-SmtpServer <String>] [-SmtpPort <Int32>] [-From <String>] [-To <String>]
[-UseSSL] [<CommonParameters>]
```

```
C:\Scripts\XD7_Inventory.ps1 [-AdminAddress <String>] [-HTML] [-Administrators]
[-Applications] [-DeliveryGroups] [-DeliveryGroupsUtilization] [-Hardware]
[-Hosting] [-Logging] [-StartDate <DateTime>] [-EndDate <DateTime>]
[-MachineCatalogs] [-NoADPolicies] [-NoPolicies] [-NoSessions] [-Policies]
[-StoreFront] [-MaxDetails] [-Section <String[]>] [-AddDateTime] [-Dev] [-Folder
<String>] [-Log] [-ScriptInfo] [-ReportFooter] [-SmtpServer <String>] [-SmtpPort
<Int32>] [-From <String>] [-To <String>] [-UseSSL] [<CommonParameters>]
```

```
C:\Scripts\XD7_Inventory.ps1 [-AdminAddress <String>] [-Text] [-Administrators]
[-Applications] [-DeliveryGroups] [-DeliveryGroupsUtilization] [-Hardware]
[-Hosting] [-Logging] [-StartDate <DateTime>] [-EndDate <DateTime>]
[-MachineCatalogs] [-NoADPolicies] [-NoPolicies] [-NoSessions] [-Policies]
[-StoreFront] [-MaxDetails] [-Section <String[]>] [-AddDateTime] [-Dev] [-Folder
<String>] [-Log] [-ScriptInfo] [-ReportFooter] [-SmtpServer <String>] [-SmtpPort
<Int32>] [-From <String>] [-To <String>] [-UseSSL] [<CommonParameters>]
```

```
C:\Scripts\XD7_Inventory.ps1 [-AdminAddress <String>] [-Administrators]
[-Applications] [-DeliveryGroups] [-DeliveryGroupsUtilization] [-Hardware]
[-Hosting] [-Logging] [-StartDate <DateTime>] [-EndDate <DateTime>]
[-MachineCatalogs] [-NoADPolicies] [-NoPolicies] [-NoSessions] [-Policies]
[-StoreFront] [-MaxDetails] [-Section <String[]>] [-AddDateTime] [-Dev] [-Folder
<String>] [-Log] [-ScriptInfo] [-ReportFooter] [-PDF] [-CompanyAddress <String>]
[-CompanyEmail <String>] [-CompanyFax <String>] [-CompanyName <String>]
[-CompanyPhone <String>] [-CoverPage <String>] [-UserName <String>] [-SmtpServer
<String>] [-SmtpPort <Int32>] [-From <String>] [-To <String>] [-UseSSL]
[<CommonParameters>]
```

DESCRIPTION

Creates an inventory of a Citrix XenDesktop 7.0 through 7.7 Site using Microsoft PowerShell, Word, plain text, or HTML.

This script requires at least PowerShell version 3 but runs best in version 5.

Word is NOT needed to run the script. This script outputs in Text and HTML.

You do NOT have to run this script on a Controller. This script was developed and run from a Windows 8.1 VM.

You can run this script remotely using the -AdminAddress (AA) parameter.

This script supports versions of XenApp/XenDesktop from 7.0 to 7.7.

If you are running XA/XD 7.8 through CVAD 2006, please use:
<https://github.com/CarlWebster/Citrix-XenApp-XenDesktop-7-V2>

If you are running CVAD 2006 through 2511, please use:
<https://github.com/CarlWebster/Citrix-Virtual-Apps-and-Desktops-V3>

If you are running Citrix Cloud, please use:
<https://github.com/CarlWebster/Citrix-Cloud-Daas->

By default, only gives summary information for:

- Administrators
- Applications
- Delivery Groups
- Hosting
- Logging
- Machine Catalogs
- Policies
- StoreFront

The Summary information is what is shown in the top half of Citrix Studio for:

- Machine Catalogs
- Delivery Groups
- Applications
- Policies
- Logging
- Administrators
- Hosting
- StoreFront

Using the MachineCatalogs parameter can cause the report to take a very long time to complete and can generate an extremely long report.

Using the DeliveryGroups parameter can cause the report to take a very long time to complete and can generate an extremely long report.

Using both the MachineCatalogs and DeliveryGroups parameters can cause the report to take an extremely long time to complete and generate an exceptionally long report.

Creates an output file named after the XenDesktop 7.x Site.

Word and PDF Document includes a Cover Page, Table of Contents, and Footer.
Includes support for the following language versions of Microsoft Word:

- Catalan
- Chinese
- Danish
- Dutch
- English
- Finnish
- French
- German
- Norwegian
- Portuguese
- Spanish
- Swedish

PARAMETERS

-AdminAddress <String>

Specifies the address of a XenDesktop controller the PowerShell snapins connects.
This can be provided as a host name or an IP address.
This parameter defaults to LocalHost.
This parameter has an alias of AA.

Required?	false
Position?	named
Default value	localhost
Accept pipeline input?	false
Accept wildcard characters?	false

-HTML [<SwitchParameter>]
Creates an HTML file with an .html extension.
This parameter is disabled by default.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-Text [<SwitchParameter>]
Creates a formatted text file with a .txt extension.
This parameter is disabled by default.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-Administrators [<SwitchParameter>]
Give detailed information for Administrator Scopes and Roles.
This parameter is disabled by default.
This parameter has an alias of Admins.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-Applications [<SwitchParameter>]
Gives detailed information for all applications.
This parameter is disabled by default.
This parameter has an alias of Apps.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-DeliveryGroups [<SwitchParameter>]
Gives detailed information for all desktops in all Desktop (Delivery) Groups.

Using the DeliveryGroups parameter can cause the report to take a very long time to complete and can generate an extremely long report.

Using both the MachineCatalogs and DeliveryGroups parameters can cause the report to take an extremely long time to complete and generate an exceptionally long report.

This parameter is disabled by default.
This parameter has an alias of DG.

Required?	false
-----------	-------

Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-DeliveryGroupsUtilization [<SwitchParameter>]

Gives a chart with the delivery group utilization for the last 7 days depending on the information in the database.

This option is only available when the report is generated in Word and requires Microsoft Excel to be locally installed.

Using the DeliveryGroupsUtilization parameter causes the report to take a longer time to complete and generates a longer report.

This parameter is disabled by default.
This parameter has an alias of DGU.

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-Hardware [<SwitchParameter>]

Use WMI to gather hardware information on: Computer System, Disks, Processor and Network Interface Cards

This parameter may require the script be run from an elevated PowerShell session using an account with permission to retrieve hardware information (i.e. Domain Admin or Local Administrator).

Selecting this parameter will add to both the time it takes to run the script and size of the report.

This parameter is disabled by default.
This parameter has an alias of HW.

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-Hosting [<SwitchParameter>]

Give detailed information for Hosts, Host Connections and Resources.

This parameter is disabled by default.
This parameter has an alias of Host.

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-Logging [<SwitchParameter>]

Give the Configuration Logging report with, by default, details for the previous seven days.

This parameter is disabled by default.

Required? false
Position? named
Default value False

Accept pipeline input? false
Accept wildcard characters? false

-StartDate <DateTime>
Start date for the Configuration Logging report.

Format for date only is MM/DD/YYYY.

Format to include a specific time range is "MM/DD/YYYY HH:MM:SS" in 24 hour format.
The double quotes are needed.

The default is today's date minus seven days.
This parameter has an alias of SD.

Required? false
Position? named
Default value ((Get-Date -displayhint date).AddDays(-7))
Accept pipeline input? false
Accept wildcard characters? false

-EndDate <DateTime>
End date for the Configuration Logging report.

Format for date only is MM/DD/YYYY.

Format to include a specific time range is "MM/DD/YYYY HH:MM:SS" in 24 hour format.
The double quotes are needed.

The default is today's date.
This parameter has an alias of ED.

Required? false
Position? named
Default value (Get-Date -displayhint date)
Accept pipeline input? false
Accept wildcard characters? false

-MachineCatalogs [<SwitchParameter>]
Gives detailed information for all machines in all Machine Catalogs.

Using the MachineCatalogs parameter can cause the report to take a very long time to complete and can generate an extremely long report.

Using both the MachineCatalogs and DeliveryGroups parameters can cause the report to take an extremely long time to complete and generate an exceptionally long report.

This parameter is disabled by default.
This parameter has an alias of MC.

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-NoADPolicies [<SwitchParameter>]
Excludes all Citrix AD-based policy information from the output document.
Includes only Site policies created in Studio.

This switch is useful in large AD environments, where there may be thousands of policies, to keep SYSVOL from being searched.

This parameter is disabled by default.
This parameter has an alias of NoAD.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-NoPolicies [<SwitchParameter>]

Excludes all Site and Citrix AD-based policy information from the output document.

Using the NoPolicies parameter will cause the Policies parameter to be set to False.

This parameter is disabled by default.
This parameter has an alias of NP.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-NoSessions [<SwitchParameter>]

Excludes Machine Catalog, Application, and Hosting session data from the report.

Using the MaxDetails parameter does not change this setting.

This parameter is disabled by default.
This parameter has an alias of NS.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-Policies [<SwitchParameter>]

Give detailed information for both Site and Citrix AD-based Policies.

Note: The Citrix Group Policy PowerShell module will not load from an elevated PowerShell session.
If the module is manually imported, the module is not detected from an elevated PowerShell session.

Using the Policies parameter can cause the report to take a very long time to complete and can generate an extremely long report.

There are three related parameters: Policies, NoPolicies and NoADPolicies.

Policies and NoPolicies are mutually exclusive, and priority is given to NoPolicies.

Using both Policies and NoADPolicies results in only policies created in Studio being in the output document.

This parameter is disabled by default.
This parameter has an alias of Pol.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-StoreFront [<SwitchParameter>]
 Give detailed information for StoreFront.
 This parameter is disabled by default.
 This parameter has an alias of SF.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-MaxDetails [<SwitchParameter>]
 Adds maximum detail to the report.

This is the same as using the following parameters:

- Administrators
- Applications
- DeliveryGroups
- HardWare
- Hosting
- Logging
- MachineCatalogs
- Policies
- StoreFront

Does not change the value of NoADPolicies.
 Does not change the value of NoSessions.

WARNING: Using this parameter can create an extremely large report and can take a very long time to run.

This parameter has an alias of MAX.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-Section <String[]>
 Processes one or more sections of the report.
 Valid options are:

- Admins (Administrators)
- Apps (Applications)
- AppV
- Catalogs (Machine Catalogs)
- Config (Configuration)
- Controllers
- Groups (Delivery Groups)
- Hosting
- Licensing
- Logging
- Policies
- StoreFront
- Zones
- All

This parameter defaults to All sections.

Multiple sections are separated by a comma. -Section catalogs, groups

Notes:

Using Logging will force the Logging switch to True.
Using Policies will force the Policies switch to True.
If Policies is selected and the NoPolicies switch is used, the script will terminate.

Required?	false
Position?	named
Default value	All
Accept pipeline input?	false
Accept wildcard characters?	false

-AddDateTime [<SwitchParameter>]

Adds a date time stamp to the end of the file name.
Time stamp is in the format of yyyy-MM-dd_HHmm.
June 1, 2027 at 6PM is 2027-06-01_1800.
Output filename will be ReportName_2027-06-01_1800.docx (or .pdf).
This parameter is disabled by default.
This parameter has an alias of ADT.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-Dev [<SwitchParameter>]

Clears errors at the beginning of the script.
Outputs all errors to a text file at the end of the script.

This is used when the script developer requests more troubleshooting data.
Text file is placed in the same folder from where the script is run.

This parameter is disabled by default.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-Folder <String>

Specifies the optional output folder to save the output report.

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-Log [<SwitchParameter>]

Generates a log file for troubleshooting.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-ScriptInfo [<SwitchParameter>]

Outputs information about the script to a text file.
Text file is placed in the same folder from where the script is run.

This parameter is disabled by default.
This parameter has an alias of SI.

```

Required?                false
Position?                named
Default value            False
Accept pipeline input?    false
Accept wildcard characters? false

-ReportFooter [<SwitchParameter>]
  Outputs a footer section at the end of the report.

  This parameter has an alias of RF.

  Report Footer
    Report information:
      Created with: <Script Name> - Release Date: <Script Release Date>
      Script version: <Script Version>
      Started on <Date Time in Local Format>
      Elapsed time: nn days, nn hours, nn minutes, nn.nn seconds
      Ran from domain <Domain Name> by user <Username>
      Ran from the folder <Folder Name>

  Script Name and Script Release date are script-specific variables.
  Start Date Time in Local Format is a script variable.
  Elapsed time is a calculated value.
  Domain Name is $env:USERDNSDOMAIN.
  Username is $env:USERNAME.
  Folder Name is a script variable.

Required?                false
Position?                named
Default value            False
Accept pipeline input?    false
Accept wildcard characters? false

-MSWord [<SwitchParameter>]
  SaveAs DOCX file
  This parameter is set True if no other output format is selected.

Required?                false
Position?                named
Default value            False
Accept pipeline input?    false
Accept wildcard characters? false

-PDF [<SwitchParameter>]
  SaveAs PDF file instead of DOCX file.
  This parameter is disabled by default.
  The PDF file is roughly 5X to 10X larger than the DOCX file.
  This parameter requires Microsoft Word to be installed.
  This parameter uses the Word SaveAs PDF capability.

Required?                false
Position?                named
Default value            False
Accept pipeline input?    false
Accept wildcard characters? false

-CompanyAddress <String>
  Company Address to use for the Cover Page, if the Cover Page has the Address field.

  The following Cover Pages have an Address field:
    Banded (Word 2013/2016)
    Contrast (Word 2010)

```

Exposure (Word 2010)
Filigree (Word 2013/2016)
Ion (Dark) (Word 2013/2016)
Retrospect (Word 2013/2016)
Semaphore (Word 2013/2016)
Tiles (Word 2010)
ViewMaster (Word 2013/2016)

This parameter is only valid with the MSWORD and PDF output parameters.
This parameter has an alias of CA.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-CompanyEmail <String>

Company Email to use for the Cover Page, if the Cover Page has the Email field.

The following Cover Pages have an Email field:
Facet (Word 2013/2016)

This parameter is only valid with the MSWORD and PDF output parameters.
This parameter has an alias of CE.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-CompanyFax <String>

Company Fax to use for the Cover Page, if the Cover Page has the Fax field.

The following Cover Pages have a Fax field:
Contrast (Word 2010)
Exposure (Word 2010)

This parameter is only valid with the MSWORD and PDF output parameters.
This parameter has an alias of CF.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-CompanyName <String>

Company Name to use for the Cover Page.

The default value is contained in
HKCU:\Software\Microsoft\Office\Common\UserInfo\CompanyName or
HKCU:\Software\Microsoft\Office\Common\UserInfo\Company, whichever is populated
on the computer running the script.
This parameter has an alias of CN.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-CompanyPhone <String>

Company Phone to use for the Cover Page, if the Cover Page has the Phone field.

The following Cover Pages have a Phone field:

Contrast (Word 2010)
Exposure (Word 2010)

This parameter is only valid with the MSWORD and PDF output parameters.
This parameter has an alias of CPh.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-CoverPage <String>

What Microsoft Word Cover Page to use.
Only Word 2010, 2013 and 2016 are supported.
(default cover pages in Word en-US)

Valid input is:

Alphabet (Word 2010. Works)
Annual (Word 2010. Doesn't work well for this report)
Austere (Word 2010. Works)
Austin (Word 2010/2013/2016. Doesn't work in 2013 or 2016, mostly works in 2010 but Subtitle/Subject & Author fields need to be moved after title box is moved up)
Banded (Word 2013/2016. Works)
Conservative (Word 2010. Works)
Contrast (Word 2010. Works)
Cubicles (Word 2010. Works)
Exposure (Word 2010. Works if you like looking sideways)
Facet (Word 2013/2016. Works)
Filigree (Word 2013/2016. Works)
Grid (Word 2010/2013/2016. Works in 2010)
Integral (Word 2013/2016. Works)
Ion (Dark) (Word 2013/2016. Top date doesn't fit; box needs to be manually resized or font changed to 8 point)
Ion (Light) (Word 2013/2016. Top date doesn't fit; box needs to be manually resized or font changed to 8 point)
Mod (Word 2010. Works)
Motion (Word 2010/2013/2016. Works if top date is manually changed to 36 point)
Newsprint (Word 2010. Works but date is not populated)
Perspective (Word 2010. Works)
Pinstripes (Word 2010. Works)
Puzzle (Word 2010. Top date doesn't fit; box needs to be manually resized or font changed to 14 point)
Retrospect (Word 2013/2016. Works)
Semaphore (Word 2013/2016. Works)
Sideline (Word 2010/2013/2016. Doesn't work in 2013 or 2016, works in 2010)
Slice (Dark) (Word 2013/2016. Doesn't work)
Slice (Light) (Word 2013/2016. Doesn't work)
Stacks (Word 2010. Works)
Tiles (Word 2010. Date doesn't fit unless changed to 26 point)
Transcend (Word 2010. Works)
ViewMaster (Word 2013/2016. Works)
Whisp (Word 2013/2016. Works)

The default value is Sideline.

This parameter has an alias of CP.

This parameter is only valid with the MSWORD and PDF output parameters.

Required?	false
Position?	named
Default value	Sideline
Accept pipeline input?	false
Accept wildcard characters?	false

-UserName <String>
 Username to use for the Cover Page and Footer.
 The default value is contained in \$env:username
 This parameter has an alias of UN.
 This parameter is only valid with the MSWORD and PDF output parameters.

Required?	false
Position?	named
Default value	\$env:username
Accept pipeline input?	false
Accept wildcard characters?	false

-SmtpServer <String>
 Specifies the optional email server to send the output report.

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-SmtpPort <Int32>
 Specifies the SMTP port.
 The default is 25.

Required?	false
Position?	named
Default value	25
Accept pipeline input?	false
Accept wildcard characters?	false

-From <String>
 Specifies the username for the From email address.
 If SmtpServer is used, this is a required parameter.

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-To <String>
 Specifies the username for the To email address.
 If SmtpServer is used, this is a required parameter.

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-UseSSL [<SwitchParameter>]
 Specifies whether to use SSL for the SmtpServer.
 The default is False.

Required?	false
-----------	-------

Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

None. You cannot pipe objects to this script.

OUTPUTS

No objects are output from this script. This script creates a Word, PDF, plain text, or HTML document.

NOTES

NAME: XD7_Inventory.ps1
VERSION: 1.58
AUTHOR: Carl Webster
LASTEDIT: October 7, 2026

----- EXAMPLE 1 -----

PS C:\PSScript >.\XD7_Inventory.ps1

Uses all default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

The computer running the script for the AdminAddress.

----- EXAMPLE 2 -----

PS C:\PSScript >.\XD7_Inventory.ps1 -AdminAddress DDC01

Uses all default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

DDC01 for the AdminAddress.

----- EXAMPLE 3 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -PDF
```

Uses all default values and saves the document as a PDF file.
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.
Sideline for the Cover Page format.
Administrator for the Username.
The computer running the script for the AdminAddress.

----- EXAMPLE 4 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -TEXT
```

Uses all default values and saves the document as a formatted text file.
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.
Sideline for the Cover Page format.
Administrator for the Username.

----- EXAMPLE 5 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -HTML
```

Uses all default values and saves the document as an HTML file.
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.
Sideline for the Cover Page format.
Administrator for the Username.

----- EXAMPLE 6 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -MachineCatalogs
```

Creates a report with full details for all machines in all Machine Catalogs.
Uses all Default values.
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.
Sideline for the Cover Page format.
Administrator for the Username.

----- EXAMPLE 7 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -DeliveryGroups
```

Creates a report with full details for all desktops in all Desktop (Delivery) Groups.
Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl
Webster" or
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.
Sideline for the Cover Page format.
Administrator for the Username.

----- EXAMPLE 8 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -DeliveryGroupsUtilization
```

Creates a report with utilization details for all Desktop (Delivery) Groups.
Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl
Webster" or
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.
Sideline for the Cover Page format.
Administrator for the Username.

----- EXAMPLE 9 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -DeliveryGroups -MachineCatalogs
```

Creates a report with full details for all machines in all Machine Catalogs and
all desktops in all Delivery Groups.
Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl
Webster" or
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.
Sideline for the Cover Page format.
Administrator for the Username.

----- EXAMPLE 10 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -Applications
```

Creates a report with full details for all applications.

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"

\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

----- EXAMPLE 11 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -Policies
```

Creates a report with full details for Policies.

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"

\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

----- EXAMPLE 12 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -NoPolicies
```

Creates a report with no Policy information.

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"

\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

----- EXAMPLE 13 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -NoADPolicies
```

Creates a report with no Citrix AD-based Policy information.

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"

```
$env:username = Administrator
```

Carl Webster for the Company Name.
Sideline for the Cover Page format.
Administrator for the Username.

----- EXAMPLE 14 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -Policies -NoADPolicies
```

Creates a report with full details on Site policies created in Studio but no Citrix AD-based Policy information.

Uses all Default values.

```
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or
```

```
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
```

```
$env:username = Administrator
```

Carl Webster for the Company Name.
Sideline for the Cover Page format.
Administrator for the Username.

----- EXAMPLE 15 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -Administrators
```

Creates a report with full details on Administrator Scopes and Roles.

Uses all Default values.

```
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or
```

```
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
```

```
$env:username = Administrator
```

Carl Webster for the Company Name.
Sideline for the Cover Page format.
Administrator for the Username.

----- EXAMPLE 16 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -Logging -StartDate 01/01/2027 -EndDate 01/31/2027
```

Creates a report with Configuration Logging details for the dates 01/01/2027 through 01/31/2027.

Uses all Default values.

```
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or
```

```
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
```

```
$env:username = Administrator
```

Carl Webster for the Company Name.
Sideline for the Cover Page format.

Administrator for the Username.

----- EXAMPLE 17 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -Logging -StartDate "06/01/2027 10:00:00" -EndDate "06/01/2027 14:00:00"
```

Creates a report with Configuration Logging details for the time range 06/01/2027 10:00:00AM through 06/01/2027 02:00:00PM.

Narrowing the report down to seconds does not work. Seconds must be either 00 or 59.

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

----- EXAMPLE 18 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -Hosting
```

Creates a report with full details for Hosts, Host Connections, and Resources.

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

----- EXAMPLE 19 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -StoreFront
```

Creates a report with full details for StoreFront.

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

----- EXAMPLE 20 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -MachineCatalogs -DeliveryGroups -Applications  
-Policies -Hosting -StoreFront
```

Creates a report with full details for all:

- Machines in all Machine Catalogs
- Desktops in all Delivery Groups
- Applications
- Policies
- Hosts, Host Connections, and Resources
- StoreFront

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"

\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

----- EXAMPLE 21 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -MC -DG -Apps -Policies -Hosting
```

Creates a report with full details for all:

- Machines in all Machine Catalogs
- Desktops in all Delivery Groups
- Applications
- Policies
- Hosts, Host Connections, and Resources

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"

\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

----- EXAMPLE 22 -----

```
PS C:\>PS C:\PSScript .\XD7_Inventory.ps1 -CompanyName "Carl Webster Consulting"  
-CoverPage "Mod" -UserName "Carl Webster" -AdminAddress DDC01
```

Uses:

Carl Webster Consulting for the Company Name.

Mod for the Cover Page format.

Carl Webster for the Username.

Controller named DDC01 for the AdminAddress.

----- EXAMPLE 23 -----

```
PS C:\>PS C:\PSScript .\XD7_Inventory.ps1 -CN "Carl Webster Consulting" -CP "Mod" -UN
"Carl Webster"
```

Uses:

Carl Webster Consulting for the Company Name (alias CN).
Mod for the Cover Page format (alias CP).
Carl Webster for the Username (alias UN).
The computer running the script for the AdminAddress.

----- EXAMPLE 24 -----

```
PS C:\>PS C:\PSScript .\XD7_Inventory.ps1 -CompanyName "Sherlock Holmes Consulting"
-CoverPage Exposure -UserName "Dr. Watson" -CompanyAddress "221B Baker Street, London,
England" -CompanyFax "+44 1753 276600" -CompanyPhone "+44 1753 276200"
```

Uses:

Sherlock Holmes Consulting for the Company Name.
Exposure for the Cover Page format.
Dr. Watson for the Username.
221B Baker Street, London, England for the Company Address.
+44 1753 276600 for the Company Fax.
+44 1753 276200 for the Company Phone.

----- EXAMPLE 25 -----

```
PS C:\>PS C:\PSScript .\XD7_Inventory.ps1 -CompanyName "Sherlock Holmes Consulting"
-CoverPage Facet -UserName "Dr. Watson" -CompanyEmail SuperSleuth@SherlockHolmes.com
```

Uses:

Sherlock Holmes Consulting for the Company Name.
Facet for the Cover Page format.
Dr. Watson for the Username.
SuperSleuth@SherlockHolmes.com for the Company Email.

----- EXAMPLE 26 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -AddDateTime
```

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl
Webster" or
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.
Sideline for the Cover Page format.
Administrator for the Username.

Adds a date time stamp to the end of the file name.
The timestamp is in the format of yyyy-MM-dd_HH:mm.
June 1, 2027, at 6PM is 2027-06-01_1800.
The output filename will be XD7SiteName_2027-06-01_1800.docx

----- EXAMPLE 27 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -PDF -AddDateTime
```

Uses all Default values and save the document as a PDF file.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

Adds a date time stamp to the end of the file name.

The timestamp is in the format of yyyy-MM-dd_HH:mm.

June 1, 2027, at 6PM is 2027-06-01_1800.

The output filename will be XD7SiteName_2027-06-01_1800.pdf

----- EXAMPLE 28 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -Hardware
```

Uses all default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

----- EXAMPLE 29 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -Folder \\FileServer\ShareName
```

Uses all default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

Output file will be saved in the path \\FileServer\ShareName

----- EXAMPLE 30 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -Section Policies
```

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

Processes only the Policies section of the report.

----- EXAMPLE 31 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -Section Config, Licensing -HTML
```

Creates an HTML report.

The report includes only the Configuration and Licensing sections.

----- EXAMPLE 32 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -MaxDetails
```

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

Set the following parameter values:

Administrators	= True
Applications	= True
DeliveryGroups	= True
HardWare	= True
Hosting	= True
Logging	= True
MachineCatalogs	= True
Policies	= True
StoreFront	= True

NoPolicies	= False
Section	= "All"

----- EXAMPLE 33 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -Dev -ScriptInfo -Log
```

Uses all Default values.
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.
Sideline for the Cover Page format.
Administrator for the Username.

Creates a text file named XAXDVIInventoryScriptErrors_YYYY-MM-dd_HHMM.txt that contains up to the last 250 errors reported by the script.

Creates a text file named XAXDVIInventoryScriptInfo_YYYY-MM-dd_HHMM.txt that contains all the script parameters and other basic information.

Creates a text file for transcript logging named
XDVI DocScriptTranscript_YYYY-MM-dd_HHMM.txt.

----- EXAMPLE 34 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -SmtpServer mail.domain.tld -From  
XDAdmin@domain.tld -To ITGroup@domain.tld
```

The script uses the email server mail.domain.tld, sending from XDAdmin@domain.tld and sending to ITGroup@domain.tld.

The script uses the default SMTP port 25 and does not use SSL.

If the current user's credentials are not valid to send an email, the script prompts the user to enter valid credentials.

----- EXAMPLE 35 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -SmtpServer mailrelay.domain.tld -From  
Anonymous@domain.tld -To ITGroup@domain.tld
```

SENDING UNAUTHENTICATED EMAIL

The script uses the email server mailrelay.domain.tld, sending from anonymous@domain.tld and sending to ITGroup@domain.tld.

To send an unauthenticated email using an email relay server requires the From email account to use the name Anonymous.

The script uses the default SMTP port 25 and does not use SSL.

GMAIL/G SUITE SMTP RELAY
<https://support.google.com/a/answer/2956491?hl=en>
<https://support.google.com/a/answer/176600?hl=en>

To send an email using a Gmail or g-suite account, you may have to turn ON the "Less secure app access" option on your account.

GMAIL/G SUITE SMTP RELAY

The script generates an anonymous, secure password for the anonymous@domain.tld account.

----- EXAMPLE 36 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -SmtpServer
labaddomain-com.mail.protection.outlook.com -UseSSL -From
SomeEmailAddress@labaddomain.com -To ITGroupDL@labaddomain.com
```

OFFICE 365 Example

<https://docs.microsoft.com/en-us/exchange/mail-flow-best-practices/how-to-set-up-a-multifunction-device-or-application-to-send-email-using-office-3>

This uses Option 2 from the above link.

OFFICE 365 Example

The script uses the email server labaddomain-com.mail.protection.outlook.com, sending from SomeEmailAddress@labaddomain.com and sending to ITGroupDL@labaddomain.com.

The script uses the default SMTP port 25 and SSL.

----- EXAMPLE 37 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -SmtpServer smtp.office365.com -SmtpPort 587
-UseSSL -From Webster@CarlWebster.com -To ITGroup@CarlWebster.com
```

The script uses the email server smtp.office365.com on port 587 using SSL, sending from webster@carlwebster.com and sending to ITGroup@carlwebster.com.

If the current user's credentials are not valid to send an email, the script prompts the user to enter valid credentials.

----- EXAMPLE 38 -----

```
PS C:\PSScript >.\XD7_Inventory.ps1 -SmtpServer smtp.gmail.com -SmtpPort 587 -UseSSL
-From Webster@CarlWebster.com -To ITGroup@CarlWebster.com
```

*** NOTE ***

To send an email using a Gmail or g-suite account, you may have to turn ON the "Less secure app access" option on your account.

*** NOTE ***

The script uses the email server smtp.gmail.com on port 587 using SSL, sending from webster@gmail.com and sending to ITGroup@carlwebster.com.

If the current user's credentials are not valid to send an email, the script prompts the user to enter valid credentials.

RELATED LINKS