

XenDesktop 7.x Version 2 Documentation Script ReadMe

NOTE: This script requires PowerShell V3 or later.

NOTE: Best performance is obtained by using PowerShell V5.

NOTE: Word 2007 is not supported.

Support for non-English Versions of Microsoft Word

The script supports the following languages:

- Catalan
- Chinese
- Danish
- Dutch
- English
- Finnish
- French
- German
- Norwegian
- Portuguese
- Spanish
- Swedish

Prerequisites

Let us ensure we have the requirements before using PowerShell to document anything in a XenDesktop 7.x Site.

1. If the script runs remotely, there are two choices: install Citrix Studio or manually install the PowerShell snapins.
 - a. Install Studio from the full XenDesktop 7.x installation media. Installing Citrix Studio installs all the necessary PowerShell snapins.
 - b. Install the PowerShell snapins individually. Depending on the bitness of the computer, from the full XenDesktop 7.x installation media, install the following files from either x64 or x86 (?? is either 86 or 64):
 - i. Citrix Desktop Delivery Controller\ADIdentity_PowerShellSnapIn_x??
 - ii. Citrix Desktop Delivery Controller\Analytics_PowerShell_SnapIn_x??
 - iii. Citrix Desktop Delivery Controller\AppLibrary_PowerShell_SnapIn_x??
 - iv. Citrix Desktop Delivery Controller\Broker_PowerShell_SnapIn_x??
 - v. Citrix Desktop Delivery Controller\Configuration_PowerShell_SnapIn_x??
 - vi. Citrix Desktop Delivery Controller\ConfigurationLogging_PowerShell_SnapIn_x??
 - vii. Citrix Desktop Delivery Controller\DelegatedAdmin_PowerShellSnapIn_x??
 - viii. Citrix Desktop Delivery Controller\EnvTest_PowerShell_SnapIn_x??
 - ix. Citrix Desktop Delivery Controller\Host_PowerShell_SnapIn_x??
 - x. Citrix Desktop Delivery Controller\MachineCreation_PowerShellSnapIn_x??
 - xi. Citrix Desktop Delivery Controller\Monitor_PowerShellSnapIn_x??
 - xii. Citrix Desktop Delivery Controller\Orchestration_PowerShellSnapIn_x??
 - xiii. Citrix Desktop Delivery Controller\Storefront_PowerShellSnapIn_x??
 - xiv. Citrix Desktop Delivery Controller\Trust_PowerShellSnapIn_x??
 - xv. Citrix Desktop Delivery Controller\UserProfileManager_PowerShellSnapIn_x??
 - xvi. 7.13 and later: Citrix Desktop Delivery Controller\XDPoshSnapin_x??
 - xvii. Citrix Policy\CitrixGroupPolicyManagement_x??
 - xviii. DesktopStudio\PVS PowerShell SDK x??
 - xix. DesktopStudio\PzAppV_Studio_PowershellSnapin_x??
 - xx. Licensing\LicensingAdmin_PowerShellSnapIn_x??
 - c. Install these two files to get information on the SQL Server(s) and database(s). (?? is either 86 or 64)
 - i. Support\SharedManagementObjects\x??\SQLSysClrTypes.msi [must install first]
 - ii. Support\SharedManagementObjects\x??\SharedManagementObjects.msi

Script Usage

How to use this script?

1. Save the script as *XD7_Inventory_V2.ps1* in your PowerShell scripts folder.
2. From the PowerShell prompt, change to your PowerShell scripts folder.
3. From the PowerShell prompt, type in:
 - a. *.\XD7_Inventory_V2.ps1* and press *Enter*.
4. By default, a Microsoft Word document is created named after the XenDesktop 7.x Site.
5. If you use the *–PDF* option, a PDF file is created named after the XenDesktop 7.x Site.
6. If you use the *–HTML* option, an HTML file is created named after the XenDesktop 7.x Site.
7. If you use the *–Text* option, a Text file is created named after the XenDesktop 7.x Site.

To run the script on a remote Controller:

.\XD7_Inventory_V2.ps1-AdminAddress DDCName and press *Enter*.

Full help text is available.

Get-Help *.\XD7_Inventory_V2.ps1 –full*

The help text explains all the parameters the script accepts.

Help text

NAME

C:\Scripts\XD7_Inventory_V2.ps1

SYNOPSIS

Creates an inventory of a Citrix XenDesktop 7.8 through CVAD 2006 Site.

SYNTAX

```
C:\Scripts\XD7_Inventory_V2.ps1 [-AdminAddress <String>] [-Administrators]
[-AppDisks] [-Applications] [-BrokerRegistryKeys] [-Controllers] [-Hardware]
[-DeliveryGroups] [-DeliveryGroupsUtilization] [-Hosting] [-Logging] [-StartDate
<DateTime>] [-EndDate <DateTime>] [-MachineCatalogs] [-NoADPolicies] [-NoPolicies]
[-NoSessions] [-Policies] [-StoreFront] [-VDARegistryKeys] [-MaxDetails] [-Section
<String[]>] [-AddDateTime] [-CSV] [-Dev] [-Folder <String>] [-Log] [-ScriptInfo]
[-ReportFooter] [-MSWord] [-CompanyAddress <String>] [-CompanyEmail <String>]
[-CompanyFax <String>] [-CompanyName <String>] [-CompanyPhone <String>] [-CoverPage
<String>] [-UserName <String>] [-SmtpServer <String>] [-SmtpPort <Int32>] [-UseSSL]
[-From <String>] [-To <String>] [<CommonParameters>]
```

```
C:\Scripts\XD7_Inventory_V2.ps1 [-HTML] [-AdminAddress <String>] [-Administrators]
[-AppDisks] [-Applications] [-BrokerRegistryKeys] [-Controllers] [-Hardware]
[-DeliveryGroups] [-DeliveryGroupsUtilization] [-Hosting] [-Logging] [-StartDate
<DateTime>] [-EndDate <DateTime>] [-MachineCatalogs] [-NoADPolicies] [-NoPolicies]
[-NoSessions] [-Policies] [-StoreFront] [-VDARegistryKeys] [-MaxDetails] [-Section
<String[]>] [-AddDateTime] [-CSV] [-Dev] [-Folder <String>] [-Log] [-ScriptInfo]
[-ReportFooter] [-SmtpServer <String>] [-SmtpPort <Int32>] [-UseSSL] [-From <String>]
[-To <String>] [<CommonParameters>]
```

```
C:\Scripts\XD7_Inventory_V2.ps1 [-Text] [-AdminAddress <String>] [-Administrators]
[-AppDisks] [-Applications] [-BrokerRegistryKeys] [-Controllers] [-Hardware]
[-DeliveryGroups] [-DeliveryGroupsUtilization] [-Hosting] [-Logging] [-StartDate
<DateTime>] [-EndDate <DateTime>] [-MachineCatalogs] [-NoADPolicies] [-NoPolicies]
[-NoSessions] [-Policies] [-StoreFront] [-VDARegistryKeys] [-MaxDetails] [-Section
<String[]>] [-AddDateTime] [-CSV] [-Dev] [-Folder <String>] [-Log] [-ScriptInfo]
[-ReportFooter] [-SmtpServer <String>] [-SmtpPort <Int32>] [-UseSSL] [-From <String>]
[-To <String>] [<CommonParameters>]
```

```
C:\Scripts\XD7_Inventory_V2.ps1 [-AdminAddress <String>] [-Administrators]
[-AppDisks] [-Applications] [-BrokerRegistryKeys] [-Controllers] [-Hardware]
[-DeliveryGroups] [-DeliveryGroupsUtilization] [-Hosting] [-Logging] [-StartDate
<DateTime>] [-EndDate <DateTime>] [-MachineCatalogs] [-NoADPolicies] [-NoPolicies]
[-NoSessions] [-Policies] [-StoreFront] [-VDARegistryKeys] [-MaxDetails] [-Section
<String[]>] [-AddDateTime] [-CSV] [-Dev] [-Folder <String>] [-Log] [-ScriptInfo]
[-ReportFooter] [-PDF] [-CompanyAddress <String>] [-CompanyEmail <String>]
[-CompanyFax <String>] [-CompanyName <String>] [-CompanyPhone <String>] [-CoverPage
<String>] [-UserName <String>] [-SmtpServer <String>] [-SmtpPort <Int32>] [-UseSSL]
[-From <String>] [-To <String>] [<CommonParameters>]
```

DESCRIPTION

Creates an inventory of a Citrix XenDesktop 7.8 through CVAD 2006 Site using Microsoft PowerShell, Word, plain text, or HTML.

This script requires at least PowerShell version 3 but runs best in version 5.

Word is NOT needed to run the script. This script outputs in Text and HTML.

You do NOT have to run this script on a Controller. This script was developed and run from a Windows 10 VM.

You can run this script remotely using the -AdminAddress (AA) parameter.

This script supports versions of XenApp/XenDesktop starting with 7.8 through CVAD 2006.

If you are running XA/XD 7.0 through 7.7, please use:

<https://github.com/CarlWebster/Citrix-XenApp-XenDesktop-7-V1>

If you are running CVAD 2006 through 2511, please use:

<https://github.com/CarlWebster/Citrix-Virtual-Apps-and-Desktops-V3>

If you are running Citrix Cloud, please use:

<https://github.com/CarlWebster/Citrix-Cloud-Daas->

NOTE: The account used to run this script must have at least Read access to the SQL Server(s) that hold(s) the Citrix Site, Monitoring, and Logging databases.

By default, only gives summary information for:

- Administrators
- App-V Publishing
- AppDisks
- AppDNA
- Application Groups
- Applications
- Controllers
- Delivery Groups
- Hosting
- Logging
- Machine Catalogs
- Policies
- StoreFront
- Zones

The Summary information is what is shown in the top half of Citrix Studio for:

- Machine Catalogs
- AppDisks
- Delivery Groups
- Applications
- Policies
- Logging
- Controllers
- Administrators
- Hosting
- StoreFront

Using the MachineCatalogs parameter can cause the report to take a very long time to complete and can generate an extremely long report.

Using the DeliveryGroups parameter can cause the report to take a very long time to complete and can generate an extremely long report.

Using both the MachineCatalogs and DeliveryGroups parameters can cause the report to take an extremely long time to complete and generate an exceptionally long report.

Using BrokerRegistryKeys requires the script to run elevated.

Creates an output file named after the XenDesktop 7.8 through CVAD 2006 Site.

Word and PDF documents include a Cover Page, Table of Contents, and Footer.

Includes support for the following language versions of Microsoft Word:

- Catalan
- Chinese
- Danish
- Dutch
- English

Finnish
French
German
Norwegian
Portuguese
Spanish
Swedish

PARAMETERS

-HTML [<SwitchParameter>]

Creates an HTML file with an .html extension.
This parameter is disabled by default.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-Text [<SwitchParameter>]

Creates a formatted text file with a .txt extension.
This parameter is disabled by default.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-AdminAddress <String>

Specifies the address of a XenDesktop controller the PowerShell snapins will connect to.
This can be provided as a hostname or an IP address.
This parameter defaults to Localhost.
This parameter has an alias of AA.

Required?	false
Position?	named
Default value	Localhost
Accept pipeline input?	false
Accept wildcard characters?	false

-Administrators [<SwitchParameter>]

Give detailed information for Administrator Scopes and Roles.
This parameter is disabled by default.
This parameter has an alias of Admins.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-AppDisks [<SwitchParameter>]

Gives detailed information for all AppDisks.

This parameter is disabled by default.
This parameter has an alias of AD.

Required?	false
Position?	named
Default value	False

```

Accept pipeline input?      false
Accept wildcard characters? false

-Applications [<SwitchParameter>]
  Gives detailed information for all applications.
  This parameter is disabled by default.
  This parameter has an alias of Apps.

  Required?                  false
  Position?                  named
  Default value               False
  Accept pipeline input?     false
  Accept wildcard characters? false

-BrokerRegistryKeys [<SwitchParameter>]
  Adds information on 417 registry keys to the Controller section.

  *****Requires the script to run elevated*****

  For Word and PDF output, this adds eight pages, per Controller, to the report.
  For Text and HTML, this adds 315 lines, per Controller, to the report.

  This parameter is disabled by default.
  This parameter has an alias of BRK.

  Required?                  false
  Position?                  named
  Default value               False
  Accept pipeline input?     false
  Accept wildcard characters? false

-Controllers [<SwitchParameter>]
  As of version 2.22, adds the following information to the Controllers section:
    List of installed Microsoft Hotfixes and Updates
    List of Citrix installed components
    List of Windows installed Roles and Features
    Appendix C List of installed Microsoft Hotfixes and Updates for all
    Controllers
    Appendix D List of Citrix installed components for all Controllers
    Appendix E List of Windows installed Roles and Features for all Controllers

  This parameter is disabled by default.
  This parameter has an alias of DDC.

  Required?                  false
  Position?                  named
  Default value               False
  Accept pipeline input?     false
  Accept wildcard characters? false

-Hardware [<SwitchParameter>]
  Use WMI to gather hardware information on Computer System, Disks, Processor, and
  Network Interface Cards

  This parameter may require the script be run from an elevated PowerShell session
  using an account with permission to retrieve hardware information (i.e., Domain
  Admin or Local Administrator).

  Selecting this parameter will add to both the time it takes to run the script and
  size of the report.

  This parameter is disabled by default.
  This parameter has an alias of HW.

```

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-DeliveryGroups [<SwitchParameter>]

Gives detailed information on all desktops in all Desktop (Delivery) Groups.

Using the DeliveryGroups parameter can cause the report to take a very long time to complete and can generate an extremely long report.

Using both the MachineCatalogs and DeliveryGroups parameters can cause the report to take an extremely long time to complete and generate an exceptionally long report.

This parameter is disabled by default.
This parameter has an alias of DG.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-DeliveryGroupsUtilization [<SwitchParameter>]

Gives a chart with the delivery group utilization for the last 7 days depending on the information in the database.

This option is only available when the report is generated in Word and requires Microsoft Excel to be locally installed.

Using the DeliveryGroupsUtilization parameter causes the report to take a longer time to complete and generates a longer report.

This parameter is disabled by default.
This parameter has an alias of DGU.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-Hosting [<SwitchParameter>]

Give detailed information for Hosts, Host Connections, and Resources.

This parameter is disabled by default.

This parameter has an alias of Host.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-Logging [<SwitchParameter>]

Give the Configuration Logging report with, by default, details for the previous seven days.

This parameter is disabled by default.

Required?	false
Position?	named

Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-StartDate <DateTime>

The start date for the Configuration Logging report.

The format for date only is MM/DD/YYYY.

Format to include a specific time range is "MM/DD/YYYY HH:MM:SS" in 24-hour format. The double quotes are needed.

The default is today's date minus seven days.
This parameter has an alias of SD.

Required?	false
Position?	named
Default value	((Get-Date -displayhint date).AddDays(-7))
Accept pipeline input?	false
Accept wildcard characters?	false

-EndDate <DateTime>

The end date for the Configuration Logging report.

The format for date only is MM/DD/YYYY.

Format to include a specific time range is "MM/DD/YYYY HH:MM:SS" in 24-hour format. The double quotes are needed.

The default is today's date.
This parameter has an alias of ED.

Required?	false
Position?	named
Default value	(Get-Date -displayhint date)
Accept pipeline input?	false
Accept wildcard characters?	false

-MachineCatalogs [<SwitchParameter>]

Gives detailed information for all machines in all Machine Catalogs.

Using the MachineCatalogs parameter can cause the report to take a very long time to complete and can generate an extremely long report.

Using both the MachineCatalogs and DeliveryGroups parameters can cause the report to take an extremely long time to complete and generate an exceptionally long report.

This parameter is disabled by default.
This parameter has an alias of MC.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-NoADPolicies [<SwitchParameter>]

Excludes all Citrix AD-based policy information from the output document.
Includes only Site policies created in Studio.

This switch is useful in large AD environments, where there may be thousands of policies, to keep SYSVOL from being searched.

This parameter is disabled by default.
This parameter has an alias of NoAD.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-NoPolicies [<SwitchParameter>]

Excludes all Site and Citrix AD-based policy information from the output document.

Using the NoPolicies parameter will cause the Policies parameter to be set to False.

This parameter is disabled by default.
This parameter has an alias of NP.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-NoSessions [<SwitchParameter>]

Excludes Machine Catalog, Application, and Hosting session data from the report.

Using the MaxDetails parameter does not change this setting.

This parameter is disabled by default.
This parameter has an alias of NS.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-Policies [<SwitchParameter>]

Give detailed information for both Site and Citrix AD-based Policies.

Using the Policies parameter can cause the report to take a very long time to complete and can generate an extremely long report.

There are three related parameters: Policies, NoPolicies, and NoADPolicies.

Policies and NoPolicies are mutually exclusive, and priority is given to NoPolicies.

This parameter is disabled by default.
This parameter has an alias of Pol.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-StoreFront [<SwitchParameter>]

Give detailed information for StoreFront.

This parameter is disabled by default.
This parameter has an alias of SF.

Required?	false
-----------	-------

Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-VDARegistryKeys [<SwitchParameter>]
 Adds information on registry keys to the Machine Details section.

If this parameter is used, MachineCatalogs is set to True.

This parameter is disabled by default.
 This parameter has an alias of VRK.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-MaxDetails [<SwitchParameter>]
 Adds maximum detail to the report.

This is the same as using the following parameters:

- Administrators
- AppDisks
- Applications
- BrokerRegistryKeys
- Controllers
- DeliveryGroups
- HardWare
- Hosting
- Logging
- MachineCatalogs
- Policies
- StoreFront
- VDARegistryKeys

*****Requires the script to run elevated*****

Does not change the value of NoADPolicies.
 Does not change the value of NoSessions.

WARNING: Using this parameter can create an extremely large report and
 can take a very long time to run.

This parameter has an alias of MAX.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-Section <String[]>
 Processes one or more sections of the report.
 Valid options are:

- Admins (Administrators)
- AppDisks
- AppDNA
- Apps (Applications and Application Group Details)
- AppV
- Catalogs (Machine Catalogs)
- Config (Configuration)

- Controllers
- Groups (Delivery Groups)
- Hosting
- Licensing
- Logging
- Policies
- StoreFront
- Zones
- All

This parameter defaults to All sections.

Multiple sections are separated by a comma. -Section catalogs, groups

Notes:

Using Logging will force the Logging switch to True.

Using Policies will force the Policies switch to True.

If Policies is selected and the NoPolicies switch is used, the script will terminate.

Required?	false
Position?	named
Default value	All
Accept pipeline input?	false
Accept wildcard characters?	false

-AddDateTime [<SwitchParameter>]

Adds a date timestamp to the end of the file name.

The timestamp is in the format of yyyy-MM-dd_HH:mm.

June 1, 2027, at 6 PM is 2027-06-01_1800.

The output filename will be ReportName_2027-06-01_1800.docx (or .pdf).

This parameter is disabled by default.

This parameter has an alias of ADT.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-CSV [<SwitchParameter>]

Will create a CSV file for each Appendix.

The default value is False.

Output CSV filename is in the format:

CVADSiteName_Documentation_Appendix#_NameOfAppendix.csv

For example:

- CVADSiteName_Documentation_AppendixA_VDARegistryItems.csv
- CVADSiteName_Documentation_AppendixB_ControllerRegistryItems.csv
- CVADSiteName_Documentation_AppendixC_MicrosoftHotfixesandUpdates.csv
- CVADSiteName_Documentation_AppendixD_CitrixInstalledComponents.csv
- CVADSiteName_Documentation_AppendixE_WindowsInstalledComponents.csv

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-Dev [<SwitchParameter>]

Clears errors at the beginning of the script.

Outputs all errors to a text file at the end of the script.

This is used when the script developer requests more troubleshooting data.
The text file is placed in the same folder from where the script runs.

This parameter is disabled by default.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-Folder <String>

Specifies the optional output folder to save the output report.

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-Log [<SwitchParameter>]

Generates a log file for troubleshooting.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-ScriptInfo [<SwitchParameter>]

Outputs information about the script to a text file.

The text file is placed in the same folder from where the script runs.

This parameter is disabled by default.

This parameter has an alias of SI.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-ReportFooter [<SwitchParameter>]

Outputs a footer section at the end of the report.

This parameter has an alias of RF.

Report Footer

Report information:

Created with: <Script Name> - Release Date: <Script Release Date>
Script version: <Script Version>
Started on <Date Time in Local Format>
Elapsed time: nn days, nn hours, nn minutes, nn.nn seconds
Ran from domain <Domain Name> by user <Username>
Ran from the folder <Folder Name>

Script Name and Script Release date are script-specific variables.

Start Date Time in Local Format is a script variable.

Elapsed time is a calculated value.

Domain Name is \$env:USERDNSDOMAIN.

Username is \$env:USERNAME.

Folder Name is a script variable.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-MSWord [<SwitchParameter>]
 SaveAs DOCX file
 This parameter is set True if no other output format is selected.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-PDF [<SwitchParameter>]
 SaveAs PDF file instead of DOCX file.
 This parameter is disabled by default.
 The PDF file is roughly 5X to 10X larger than the DOCX file.
 This parameter requires Microsoft Word to be installed.
 This parameter uses the Word SaveAs PDF capability.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-CompanyAddress <String>
 Company Address to use for the Cover Page, if the Cover Page has the Address field.

The following Cover Pages have an Address field:

- Banded (Word 2013/2016)
- Contrast (Word 2010)
- Exposure (Word 2010)
- Filigree (Word 2013/2016)
- Ion (Dark) (Word 2013/2016)
- Retrospect (Word 2013/2016)
- Semaphore (Word 2013/2016)
- Tiles (Word 2010)
- ViewMaster (Word 2013/2016)

This parameter is only valid with the MSWORD and PDF output parameters.
 This parameter has an alias of CA.

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-CompanyEmail <String>
 Company Email to use for the Cover Page, if the Cover Page has the Email field.

The following Cover Pages have an Email field:

- Facet (Word 2013/2016)

This parameter is only valid with the MSWORD and PDF output parameters.
 This parameter has an alias of CE.

Required?	false
-----------	-------

-CompanyFax <String>
Company Fax to use for the Cover Page, if the Cover Page has the Fax field.

Contrast (Word 2010)
Exposure (Word 2010)

-CompanyName <String>
Company Name to use for the Cover Page.
The default value is contained in
HKCU:\Software\Microsoft\Office\Common\UserInfo\CompanyName or
HKCU:\Software\Microsoft\Office\Common\UserInfo\Company, whichever is populated
on the computer running the script.

-CompanyPhone <String>
Company Phone to use for the Cover Page if the Cover Page has the Phone field.

Contrast	(Word 2010)
Exposure	(Word 2010)

```
-CoverPage <String>
    What Microsoft Word Cover Page to use.
    Only Word 2010, 2013 and 2016 are supported.
    (default cover pages in Word en-US)
```

works in 2010, but Subtitle/Subject & Author fields need moving after the title box is moved up)

Banded (Word 2013/2016. Works)

Conservative (Word 2010. Works)

Contrast (Word 2010. Works)

Cubicles (Word 2010. Works)

Exposure (Word 2010. Works if you like looking sideways)

Facet (Word 2013/2016. Works)

Filigree (Word 2013/2016. Works)

Grid (Word 2010/2013/2016. Works in 2010)

Integral (Word 2013/2016. Works)

Ion (Dark) (Word 2013/2016. Top date doesn't fit; box needs to be manually resized or font changed to 8 point)

Ion (Light) (Word 2013/2016. Top date doesn't fit; box needs to be manually resized or font changed to 8 point)

Mod (Word 2010. Works)

Motion (Word 2010/2013/2016. Works if top date is manually changed to 36 point)

Newsprint (Word 2010. Works but date is not populated)

Perspective (Word 2010. Works)

Pinstripes (Word 2010. Works)

Puzzle (Word 2010. Top date doesn't fit; box needs to be manually resized or font changed to 14 point)

Retrospect (Word 2013/2016. Works)

Semaphore (Word 2013/2016. Works)

Sideline (Word 2010/2013/2016. Doesn't work in 2013 or 2016, works in 2010)

Slice (Dark) (Word 2013/2016. Doesn't work)

Slice (Light) (Word 2013/2016. Doesn't work)

Stacks (Word 2010. Works)

Tiles (Word 2010. Date doesn't fit unless changed to 26 point)

Transcend (Word 2010. Works)

ViewMaster (Word 2013/2016. Works)

Whisp (Word 2013/2016. Works)

The default value is Sideline.
 This parameter has an alias of CP.
 This parameter is only valid with the MSWORD and PDF output parameters.

Required?	false
Position?	named
Default value	Sideline
Accept pipeline input?	false
Accept wildcard characters?	false

-UserName <String>
 Username to use for the Cover Page and Footer.
 The default value is contained in \$env:username
 This parameter has an alias of UN.
 This parameter is only valid with the MSWORD and PDF output parameters.

Required?	false
Position?	named
Default value	\$env:username
Accept pipeline input?	false
Accept wildcard characters?	false

-SmtpServer <String>
 Specifies the optional email server to send the output report.

Required?	false
Position?	named
Default value	

Accept pipeline input?	false
Accept wildcard characters?	false

-SmtpPort <Int32>
 Specifies the SMTP port.
 The default is 25.

Required?	false
Position?	named
Default value	25
Accept pipeline input?	false
Accept wildcard characters?	false

-UseSSL [<SwitchParameter>]
 Specifies whether to use SSL for the SmtpServer.
 The default is False.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-From <String>
 Specifies the username for the From email address.
 If SmtpServer is used, this is a required parameter.

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-To <String>
 Specifies the username for the To email address.
 If SmtpServer is used, this is a required parameter.

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

<CommonParameters>
 This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

None. You cannot pipe objects to this script.

OUTPUTS

No objects are output from this script.
 This script creates a Word, PDF, plain text, or HTML document.

NOTES

NAME: XD7_Inventory_V2.ps1
 VERSION: 2.53

AUTHOR: Carl Webster
LASTEDIT: October 7, 2026

----- EXAMPLE 1 -----

PS C:\PSScript >.\XD7_Inventory_V2.ps1

Uses all default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

The computer running the script for the AdminAddress.

----- EXAMPLE 2 -----

PS C:\PSScript >.\XD7_Inventory_V2.ps1 -AdminAddress DDC01

Uses all default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

DDC01 for the AdminAddress.

----- EXAMPLE 3 -----

PS C:\PSScript >.\XD7_Inventory_V2.ps1 -PDF

Uses all default values and saves the document as a PDF file.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

The computer running the script for the AdminAddress.

----- EXAMPLE 4 -----

PS C:\PSScript >.\XD7_Inventory_V2.ps1 -TEXT

Uses all default values and saves the document as a formatted text file.

----- EXAMPLE 5 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -HTML
```

Uses all default values and saves the document as an HTML file.

----- EXAMPLE 6 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -MachineCatalogs
```

Creates a report with full details for all machines in all Machine Catalogs.

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"

\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

----- EXAMPLE 7 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -DeliveryGroups
```

Creates a report with full details for all desktops in all Desktop (Delivery) Groups.

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"

\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

----- EXAMPLE 8 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -DeliveryGroupsUtilization
```

Creates a report with utilization details for all Desktop (Delivery) Groups.

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"

\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

----- EXAMPLE 9 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -DeliveryGroups -MachineCatalogs
```

Creates a report with full details for all machines in all Machine Catalogs and all desktops in all Delivery Groups.

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"

\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

----- EXAMPLE 10 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -Applications
```

Creates a report with full details for all applications.

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"

\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

----- EXAMPLE 11 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -Policies
```

Creates a report with full details for Policies.

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"

\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

----- EXAMPLE 12 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -NoPolicies
```

Creates a report with no Policy information.

Uses all Default values.
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.
Sideline for the Cover Page format.
Administrator for the Username.

----- EXAMPLE 13 -----

PS C:\PSScript >.\XD7_Inventory_V2.ps1 -NoADPolicies

Creates a report with no Citrix AD-based Policy information.
Uses all Default values.
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.
Sideline for the Cover Page format.
Administrator for the Username.

----- EXAMPLE 14 -----

PS C:\PSScript >.\XD7_Inventory_V2.ps1 -Policies -NoADPolicies

Creates a report with full details on Site policies created in Studio but no Citrix AD-based Policy information.

Uses all Default values.
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.
Sideline for the Cover Page format.
Administrator for the Username.

----- EXAMPLE 15 -----

PS C:\PSScript >.\XD7_Inventory_V2.ps1 -Administrators

Creates a report with full details on Administrator Scopes and Roles.

Uses all Default values.
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.
Sideline for the Cover Page format.
Administrator for the Username.

----- EXAMPLE 16 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -Logging -StartDate 06/01/2027 -EndDate 06/31/2027
```

Creates a report with Configuration Logging details for the dates 06/01/2027 through 06/31/2027.

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.
Sideline for the Cover Page format.
Administrator for the Username.

----- EXAMPLE 17 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -Logging -StartDate "06/01/2027 10:00:00" -EndDate "06/01/2027 14:00:00"
```

Creates a report with Configuration Logging details for the time range 06/01/2027 10:00:00AM through 06/01/2027 02:00:00PM.

Narrowing the report down to seconds does not work. Seconds must be either 00 or 59.

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.
Sideline for the Cover Page format.
Administrator for the Username.

----- EXAMPLE 18 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -Hosting
```

Creates a report with full details for Hosts, Host Connections, and Resources.

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.
Administrator for the Username.

----- EXAMPLE 19 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -StoreFront
```

Creates a report with full details for StoreFront.
Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.
Sideline for the Cover Page format.
Administrator for the Username.

----- EXAMPLE 20 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -MachineCatalogs -DeliveryGroups -Applications  
-Policies -Hosting -StoreFront
```

Creates a report with full details for all:

- Machines in all Machine Catalogs
- Desktops in all Delivery Groups
- Applications
- Policies
- Hosts, Host Connections, and Resources
- StoreFront

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.
Sideline for the Cover Page format.
Administrator for the Username.

----- EXAMPLE 21 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -MC -DG -Apps -Policies -Hosting
```

Creates a report with full details for all:

- Machines in all Machine Catalogs
- Desktops in all Delivery Groups
- Applications
- Policies
- Hosts, Host Connections, and Resources

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl

Webster" or
HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.
Sideline for the Cover Page format.
Administrator for the Username.

----- EXAMPLE 22 -----

```
PS C:\>PS C:\PSScript .\XD7_Inventory_V2.ps1 -CompanyName "Carl Webster Consulting"  
-CoverPage "Mod" -UserName "Carl Webster" -AdminAddress DDC01
```

Uses:

Carl Webster Consulting for the Company Name.
Mod for the Cover Page format.
Carl Webster for the Username.
Controller named DDC01 for the AdminAddress.

----- EXAMPLE 23 -----

```
PS C:\>PS C:\PSScript .\XD7_Inventory_V2.ps1 -CN "Carl Webster Consulting" -CP "Mod"  
-UN "Carl Webster"
```

Uses:

Carl Webster Consulting for the Company Name (alias CN).
Mod for the Cover Page format (alias CP).
Carl Webster for the Username (alias UN).
The computer running the script for the AdminAddress.

----- EXAMPLE 24 -----

```
PS C:\>PS C:\PSScript .\XD7_Inventory_V2.ps1 -CompanyName "Sherlock Holmes Consulting"  
-CoverPage Exposure -UserName "Dr. Watson" -CompanyAddress "221B Baker Street, London,  
England" -CompanyFax "+44 1753 276600" -CompanyPhone "+44 1753 276200"
```

Uses:

Sherlock Holmes Consulting for the Company Name.
Exposure for the Cover Page format.
Dr. Watson for the Username.
221B Baker Street, London, England for the Company Address.
+44 1753 276600 for the Company Fax.
+44 1753 276200 for the Company Phone.

----- EXAMPLE 25 -----

```
PS C:\>PS C:\PSScript .\XD7_Inventory_V2.ps1 -CompanyName "Sherlock Holmes Consulting"  
-CoverPage Facet -UserName "Dr. Watson" -CompanyEmail SuperSleuth@SherlockHolmes.com
```

Uses:

Sherlock Holmes Consulting for the Company Name.

Facet for the Cover Page format.
Dr. Watson for the Username.
SuperSleuth@SherlockHolmes.com for the Company Email.

----- EXAMPLE 26 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -AddDateTime
```

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"

\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

Adds a date time stamp to the end of the file name.

The timestamp is in the format of yyyy-MM-dd_HH:mm.

June 1, 2027, at 6PM is 2027-06-01_1800.

The output filename will be XD7SiteName_2027-06-01_1800.docx

----- EXAMPLE 27 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -PDF -AddDateTime
```

Uses all Default values and saves the document as a PDF file.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"

\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

Adds a date time stamp to the end of the file name.

The timestamp is in the format of yyyy-MM-dd_HH:mm.

June 1, 2027, at 6PM is 2027-06-01_1800.

The output filename will be XD7SiteName_2027-06-01_1800.pdf

----- EXAMPLE 28 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -Hardware
```

Uses all default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"

\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

----- EXAMPLE 29 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -Folder \\FileServer\ShareName
```

Uses all default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

The output file is saved in the path \\FileServer\ShareName

----- EXAMPLE 30 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -Section Policies
```

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

Processes only the Policies section of the report.

----- EXAMPLE 31 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -Section Groups -DG
```

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

Processes only the Delivery Groups section of the report with Delivery Group details.

----- EXAMPLE 32 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -Section Config, Licensing -HTML
```

Creates an HTML report.

The report includes only the Configuration and Licensing sections.

----- EXAMPLE 33 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -Section Groups
```

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

Processes only the Delivery Groups section of the report with no Delivery Group details.

----- EXAMPLE 34 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -BrokerRegistryKeys
```

*****Requires the script runs elevated*****

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

Adds the information on over 300 Broker registry keys to the Controllers section.

----- EXAMPLE 35 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -VDARegistryKeys
```

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"
\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

Adds the information on VDA registry keys to Appendix A.

Forces the MachineCatalogs parameter to \$True

----- EXAMPLE 36 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -MaxDetails
```

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"

\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

Set the following parameter values:

Administrators = True

AppDisks = True

Applications = True

BrokerRegistryKeys = True

Controllers = True

DeliveryGroups = True

HardWare = True

Hosting = True

Logging = True

MachineCatalogs = True

Policies = True

StoreFront = True

VDARegistryKeys = True

NoPolicies = False

Section = "All"

*****Requires the script runs elevated*****

----- EXAMPLE 37 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -Dev -ScriptInfo -Log
```

Uses all Default values.

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\CompanyName="Carl Webster" or

HKEY_CURRENT_USER\Software\Microsoft\Office\Common\UserInfo\Company="Carl Webster"

\$env:username = Administrator

Carl Webster for the Company Name.

Sideline for the Cover Page format.

Administrator for the Username.

Creates a text file named XAXDV2InventoryScriptErrors_yyyyMMddTHHmssffff.txt that contains up to the last 250 errors reported by the script.

Creates a text file named XAXDV2InventoryScriptInfo_yyyy-MM-dd_HHm.txt that contains all the script parameters and other basic information.

Creates a text file for transcript logging named XDV2DocScriptTranscript_yyyyMMddTHHmssffff.txt.

----- EXAMPLE 38 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -CSV
```

Uses all Default values.
LocalHost for AdminAddress.
Creates a CSV file for each Appendix.

----- EXAMPLE 39 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -SmtpServer mail.domain.tld -From  
XDAdmin@domain.tld -To ITGroup@domain.tld
```

The script uses the email server mail.domain.tld, sending from XDAdmin@domain.tld and sending to ITGroup@domain.tld.

The script Uses the default SMTP port 25 and does not use SSL.

If the current user's credentials are not valid to send an email, the script prompts the user to enter valid credentials.

----- EXAMPLE 40 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -SmtpServer mailrelay.domain.tld -From  
Anonymous@domain.tld -To ITGroup@domain.tld
```

SENDING UNAUTHENTICATED EMAIL

The script uses the email server mailrelay.domain.tld, sending from anonymous@domain.tld and sending to ITGroup@domain.tld.

To send an unauthenticated email using an email relay server requires the From email account to use the name Anonymous.

The script uses the default SMTP port 25 and does not use SSL.

GMAIL/G SUITE SMTP RELAY

<https://support.google.com/a/answer/2956491?hl=en>
<https://support.google.com/a/answer/176600?hl=en>

To send an email using a Gmail or g-suite account, you may have to turn ON the "Less secure app access" option on your account.

GMAIL/G SUITE SMTP RELAY

The script generates an anonymous, secure password for anonymous@domain.tld account.

----- EXAMPLE 41 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -SmtpServer  
labaddomain-com.mail.protection.outlook.com -UseSSL -From  
SomeEmailAddress@labaddomain.com -To ITGroupDL@labaddomain.com
```

OFFICE 365 Example

<https://docs.microsoft.com/en-us/exchange/mail-flow-best-practices/how-to-set-up-a-multifunction-device-or-application-to-send-email-using-office-3>

This uses Option 2 from the above link.

OFFICE 365 Example

The script uses the email server labaddomain-com.mail.protection.outlook.com, sending from SomeEmailAddress@labaddomain.com and sending to ITGroupDL@labaddomain.com.

The script uses the default SMTP port 25 and SSL.

----- EXAMPLE 42 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -SmtpServer smtp.office365.com -SmtpPort 587
-UseSSL -From Webster@CarlWebster.com -To ITGroup@CarlWebster.com
```

The script uses the email server smtp.office365.com on port 587 using SSL, sending from webster@carlwebster.com and sending to ITGroup@carlwebster.com.

If the current user's credentials are not valid to send an email, the script prompts the user to enter valid credentials.

----- EXAMPLE 43 -----

```
PS C:\PSScript >.\XD7_Inventory_V2.ps1 -SmtpServer smtp.gmail.com -SmtpPort 587
-UseSSL -From Webster@CarlWebster.com -To ITGroup@CarlWebster.com
```

*** NOTE ***

To send an email using a Gmail or g-suite account, you may have to turn ON the "Less secure app access" option on your account.

*** NOTE ***

The script uses the email server smtp.gmail.com on port 587 using SSL, sending from webster@gmail.com and sending to ITGroup@carlwebster.com.

If the current user's credentials are not valid to send an email, the script prompts the user to enter valid credentials.

RELATED LINKS