



Doc. No.: TD-LO18-SP-2003	Doc. Title: 0.18um Logic Low Leakage 1P6M (1P5M, 1P4M) Salicide 1.8V/5.0V SPICE Model (Version 1.3)	Doc. Rev: 4R	Tech Dev Rev.: 1.3	Page No.: 1/11
------------------------------	--	-----------------	-----------------------	-------------------




Fig.C1 Fitting results of 1.8V N+/Pwell diode CV model at temp=25C




Fig.C2 Fitting results of 1.8V N+/Pwell diode CV model at temp=125C




Fig.C3 Fitting results of 1.8V N+/Pwell diode CV model at temp=-40C

The information contained herein is the exclusive property of SMIC, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SMIC.



Doc. No.: TD-LO18-SP-2003	Doc. Title: 0.18um Logic Low Leakage 1P6M (1P5M, 1P4M) Salicide 1.8V/5.0V SPICE Model (Version 1.3)	Doc. Rev: 4R	Tech Dev Rev.: 1.3	Page No.: 2/11
------------------------------	--	-----------------	-----------------------	-------------------




Fig.C4 Fitting results of 1.8V NMOS Cjgate at temp=25C




Fig.C5 Fitting results of 1.8V P+/Nwell diode CV model at temp=25C




Fig.C6 Fitting results of 1.8V P+/Nwell diode CV model at temp=125C

The information contained herein is the exclusive property of SMIC, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SMIC.



Doc. No.: TD-LO18-SP-2003	Doc. Title: 0.18um Logic Low Leakage 1P6M (1P5M, 1P4M) Salicide 1.8V/5.0V SPICE Model (Version 1.3)	Doc. Rev: 4R	Tech Dev Rev.: 1.3	Page No.: 3/11
------------------------------	--	-----------------	-----------------------	-------------------




Fig.C7 Fitting results of 1.8V P+/Nwell diode CV model at temp=-40C




Fig.C8 Fitting results of 1.8V PMOS Cjgate at temp=25C




Fig.C9 Fitting results of 5V N+/Pwell diode CV model at temp=25C

The information contained herein is the exclusive property of SMIC, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SMIC.



Doc. No.: TD-LO18-SP-2003	Doc. Title: 0.18um Logic Low Leakage 1P6M (1P5M, 1P4M) Salicide 1.8V/5.0V SPICE Model (Version 1.3)	Doc. Rev: 4R	Tech Dev Rev.: 1.3	Page No.: 4/11
------------------------------	--	-----------------	-----------------------	-------------------




Fig.C10 Fitting results of 5V N+/Pwell diode CV model at temp=125C




Fig.C11 Fitting results of 5V N+/Pwell diode CV model at temp= -40C




Fig.C12 Fitting results of 5V NMOS Cjgate at temp=25C

The information contained herein is the exclusive property of SMIC, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SMIC.



Doc. No.: TD-LO18-SP-2003	Doc. Title: 0.18um Logic Low Leakage 1P6M (1P5M, 1P4M) Salicide 1.8V/5.0V SPICE Model (Version 1.3)	Doc. Rev: 4R	Tech Dev Rev.: 1.3	Page No.: 5/11
------------------------------	--	-----------------	-----------------------	-------------------




Fig.C13 Fitting results of 5V P+/Nwell diode CV model at temp=25C




Fig.C14 Fitting results of 5V P+/Nwell diode CV model at temp=125C




Fig.C15 Fitting results of 5V P+/Nwell diode CV model at temp= -40C

The information contained herein is the exclusive property of SMIC, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SMIC.



Doc. No.: TD-LO18-SP-2003	Doc. Title: 0.18um Logic Low Leakage 1P6M (1P5M, 1P4M) Salicide 1.8V/5.0V SPICE Model (Version 1.3)	Doc. Rev: 4R	Tech Dev Rev.: 1.3	Page No.: 6/11
------------------------------	---	--------------	--------------------	----------------




Fig.C16 Fitting results of 5V PMOS Cjgate at temp=25C




Fig.C17 Fitting results of Nwell/PSUB diode CV model at temp=25C




Fig.C18 Fitting results of Nwell/PSUB diode CV model at temp=125C

The information contained herein is the exclusive property of SMIC, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SMIC.



Doc. No.: TD-LO18-SP-2003	Doc. Title: 0.18um Logic Low Leakage 1P6M (1P5M, 1P4M) Salicide 1.8V/5.0V SPICE Model (Version 1.3)	Doc. Rev: 4R	Tech Dev Rev.: 1.3	Page No.: 7/11
------------------------------	--	-----------------	-----------------------	-------------------




Fig.C19 Fitting results of 1.8V N+/Pwell diode IV model at temp=25C




Fig.C20 Fitting results of 1.8V N+/Pwell diode IV model at temp=125C




Fig.C21 Fitting results of 1.8V N+/Pwell diode IV model at temp=-40C

The information contained herein is the exclusive property of SMIC, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SMIC.



Doc. No.: TD-LO18-SP-2003	Doc. Title: 0.18um Logic Low Leakage 1P6M (1P5M, 1P4M) Salicide 1.8V/5.0V SPICE Model (Version 1.3)	Doc. Rev: 4R	Tech Dev Rev.: 1.3	Page No.: 8/11
------------------------------	--	-----------------	-----------------------	-------------------




Fig.C22 Fitting results of 1.8V P+/Nwell diode IV model at temp=25C




Fig.C23 Fitting results of 1.8V P+/Nwell diode IV model at temp=125C




Fig.C24 Fitting results of 1.8V P+/Nwell diode IV model at temp= -40C

The information contained herein is the exclusive property of SMIC, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SMIC.



Doc. No.: TD-LO18-SP-2003	Doc. Title: 0.18um Logic Low Leakage 1P6M (1P5M, 1P4M) Salicide 1.8V/5.0V SPICE Model (Version 1.3)	Doc. Rev: 4R	Tech Dev Rev.: 1.3	Page No.: 9/11
------------------------------	--	-----------------	-----------------------	-------------------




Fig.C25 Fitting results of 5V N+/Pwell diode IV model at temp=25C




Fig.C26 Fitting results of 5V N+/Pwell diode IV model at temp=125C




Fig.C27 Fitting results of 5V N+/Pwell diode IV model at temp= -40C

The information contained herein is the exclusive property of SMIC, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SMIC.



Doc. No.: TD-LO18-SP-2003	Doc. Title: 0.18um Logic Low Leakage 1P6M (1P5M, 1P4M) Salicide 1.8V/5.0V SPICE Model (Version 1.3)	Doc. Rev: 4R	Tech Dev Rev.: 1.3	Page No.: 10/11
------------------------------	--	-----------------	-----------------------	--------------------




Fig.C28 Fitting results of 5V P+/Nwell diode IV model at temp=25C




Fig.C29 Fitting results of 5V P+/Nwell diode IV model at temp=125C




Fig.C30 Fitting results of 5V P+/Nwell diode IV model at temp= -40C

The information contained herein is the exclusive property of SMIC, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SMIC.



Doc. No.: TD-LO18-SP-2003	Doc. Title: 0.18um Logic Low Leakage 1P6M (1P5M, 1P4M) Salicide 1.8V/5.0V SPICE Model (Version 1.3)	Doc. Rev: 4R	Tech Dev Rev.: 1.3	Page No.: 11/11
------------------------------	--	-----------------	-----------------------	--------------------




Fig.C31 Fitting results of Nwell/Psub diode IV model at temp=25C




Fig.C32 Fitting results of Nwell/Psub diode IV model at temp=125C




Fig.C33 Fitting results of Nwell/Psub diode IV model at temp= -40C

The information contained herein is the exclusive property of SMIC, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SMIC.