

## MESSAGE TYPE 12

### Inter-Signal Bias Message

Content	Field Number	No. Bits	16-bit Word	Bits															
				(MSB)								(LSB)							
$t_{OC}$	1	11	1	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
$WN_{OC}$	2	13	2	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	
ISC-L1 $M_E$	3	13	3	3	4	5	6	7	8	9	10	11	12	13	14	15	16		
ISC-L2 $M_E$	4	13	4	4	5	6	7	8	9	10	11	12	13	14	15	16			
ISC-L1 $M_S$	5	13	5	5	6	7	8	9	10	11	12	13	14	15	16				
ISC-L2 $M_S$	6	13	6	6	7	8	9	10	11	12	13	14	15	16					
ISA-L2 P(Y)	7	4	7	7	8	9	10	11	12	13	14	15	16	17	18	19	20		
ISA-L1 $M_E$	8	4	8	8	9	10	11	12	13	14	15	16	17	18	19	20			
ISA-L2 $M_E$	9	4	9	9	10	11	12	13	14	15	16	17	18	19	20				
ISA-L1 $M_S$	10	4	10	10	11	12	13	14	15	16	17	18	19	20					
ISA-L2 $M_S$	11	4	11	11	12	13	14	15	16	17	18	19	20						
Reserved	12	96	12	12	13	14	15	16	17	18	19	20							
Spare	18	128	18	18	19	20													
TOTAL:		320																	

Figure 20-20. Format of Message Type 12