

CSci 243 Homework 9

Due: Wednesday, November 16, end of day

Carlo Mehegan

1. (6 points) Give a recursive definition for each of the following sequences $\{a_n\}$ for $n = 1, 2, 3, \dots$

(a) $a_n = 4n - 2$

Basis step: $F(1) = 4 - 2 = 2$

Recursive step: $F(n) = F(n-1) + 4$

(b) $a_n = 1 + (-1)^n$

Basis step: $F(1) = 1 + (-1)^1 = 0, F(2) = 1 + (-1)^2 = 2$

Recursive step: $F(n) = F(n-2)$

(c) $a_n = (\frac{1}{2})^n$

Basis step: $F(1) = \frac{1}{2}$

Recursive step: $F(n) = F(n-1) * \frac{1}{2}$

2. For string $w = a_1a_2 \dots a_n$, the reversal of the string is defined as $w^R = a_n \dots a_2a_1$.

- (a) (4 points) What is ϵ^R ? What is $(10110)^R$?

$\epsilon^R = \epsilon, (10110)^R = 01110$

- (b) (4 points) Give a recursive definition of the reversal of a string.

Basis step: $F(a_1a_2) = (a_1a_2)^R = a_2a_1$

Recursive step: $F(a_1 \dots a_n) = a_n F(a_1 \dots a_{n-1})$

- (c) (6 points) Use structural induction to prove that $(w_1w_2)^R = w_2^Rw_1^R$.

Basis step: $w_1 = \emptyset, w_2 = \emptyset$. The equality holds because $\emptyset^R = \emptyset$.

I.H.: Assume for two strings w_1 and w_2 the equality holds.

I.S.: Create two new strings $v_1 = w_1w_2, v_2 = w_2w_1$, and show $(v_1v_2)^R = v_2^Rv_1^R$.

$(v_1v_2)^R = (w_1w_2w_2w_1)^R$

The pattern $w_1w_2w_2w_1$ is symmetrical, and is the same after being reversed. The contents of the w_1 and w_2 strings also must be reversed, leaving $(w_1^Rw_2^Rw_2^Rw_1^R)$

Going to the other side of the equality:

$v_2^Rv_1^R = (w_2w_1)^R(w_1w_2)^R$

The contents of the w_1 and w_2 strings also must be reversed, leaving $(w_1^Rw_2^R)(w_2^Rw_1^R)$. Remove parentheses and now both sides are equal.

$(v_1v_2)^R = v_2^Rv_1^R \Rightarrow w_1^Rw_2^Rw_2^Rw_1^R = w_1^Rw_2^Rw_2^Rw_1^R$

3. (10 points) A palindrome is a string that reads the same forward and backward, i.e., $w = w^R$. Give a recursive algorithm in pseudocode that checks whether a given string w is a palindrome. What is the time complexity of your algorithm?

```
method isPalindrome (w)
    if w.length == 1 or w.length == 0
        return true
    else if w.length == 2
        return w[0] == w[1]
```

```

else if w.length > 2
    outer_matching = w[0] == w[w.length-1]
    sub_string = w with the first and last characters removed
    return outer_matching and isPalindrome(sub_string)

```

Time complexity: linear time; each recursive step covers 2 values; $\frac{n}{2} + 1$ steps.

4. (10 points) Give a recursive algorithm in pseudocode that finds the maximum number among n integers. What is the time complexity of your algorithm?

```

method findMax ([a_1, ..., a_n])
    if n == 2
        return max(a_1, a_2)
    else if n > 2
        return max(a_n, findMax([a_1, ..., a_{n-1}]))

```

Time complexity: linear time; there are n steps, one for each value in the list.

5. An employee joined a company in 2015 with a starting salary of \$50,000. Every year this employee receives a raise of \$1000 plus 4% of the salary of the previous year.

- (3 points) Set up a recurrence relation for the salary of this employee n years after 2015.

$$a_0 = 50,000$$

$$a_n = a_{n-1} * 1.04 + 1000$$

- (4 points) Find an explicit formula for the salary of this employee n years after 2015.

$$\begin{aligned}
 a_n &= 50,000 * 1.04^n + 1000 * 1.04^{n-1} + 1000 * 1.04^{n-2} + \dots + 1000 * 1.04^2 + 1000 * 1.04^1 + 1000 \\
 &= 50,000 * 1.04^n + \frac{1000 * 1.04(1 - 1.04^{n-1})}{1 - 1.04} + 1000
 \end{aligned}$$

$$= 50,000 * 1.04^n + \frac{1040(1 - 1.04^{n-1})}{-0.04} + 1000$$

- (3 points) What will the salary of this employee be in 2030?

$$a_{15} = 50,000 * 1.04^{15} + \frac{1040(1 - 1.04^{14})}{-0.04} + 1000$$

$$= 110,071.375$$