


SCORECARD VARIABLE GROUPING AND SELECTION

Dr. Aric LaBarr

Institute for Advanced Analytics

Process Flow



VARIABLE GROUPING

Variable Grouping and Selection

- Scorecards end up with only just groups within a variable.
- Objectives:
 1. Eliminate weak characteristics (variables) or those that do not conform to good business logic.
 2. Group the strongest characteristics' attribute levels in order to produce a model in scorecard format.
- Function/package “smbinning” in R.
- Package “scorecard” or “OptBinning” in Python.
- PROC BINNING in SAS VIYA.

Variable	Level
MISS	$x < 24$
MISS	$24 \leq x < 36$
MISS	$36 \leq x < 48$
MISS	$x \geq 48$
HOME	OWN
HOME	RENT

Why Grouping (Binning)?

- Goal is to help simplify analysis through grouping:
 - Useful for understanding relationships – no worries about explaining coefficients.
 - Modeling nonlinearities – similar to decision trees.
(NO MORE LOGISTIC REGRESSION LINEARITY ASSUMPTION!)
 - Dealing with outliers – contained in the smallest / largest group.
 - Missing values typically in own group.


Initial Characteristic Analysis – SAS

- Need a starting point for the grouping / binning.
 - Quantiles are most popular technique.
- Pre-bin the interval variables into a number of user-specified quantiles / buckets for fine detailed groupings.
- Aggregate the fine detailed groupings into a smaller number to produce coarse groupings.
 - Chi-squared tests to combine groups.


Initial Characteristic Analysis – SAS

3 ←————→ 63


Initial Characteristic Analysis – SAS




Initial Characteristic Analysis – SAS



Initial Characteristic Analysis – SAS



Initial Characteristic Analysis – SAS




Initial Characteristic Analysis – R

- The package (and function) “smbinning” uses a different approach than SAS.
- Conditional Inference Trees:
 - CART methods have inherent bias – variables with more levels → more likely to be split on if split on Gini and Entropy.
 - CIT method adds extra statistical step before splits occur – statistical tests of significance.
 - What is **MOST** significant variable? → What is the best split (Chi-square) on **THIS** variable? → **REPEAT**.


Initial Characteristic Analysis – R




Initial Characteristic Analysis – R




Initial Characteristic Analysis – R




Initial Characteristic Analysis – R



Initial Characteristic Analysis – R



Initial Characteristic Analysis – R



Initial Characteristic Analysis

- Cut-offs may be rough from decision tree combining.
- **Optional to override** automatically generated groups to conform to business rules.
- Overrides may make groups suboptimal.

Group Definition
Missing
< \$35,200
\$35,200 - \$60,000
\$60,000 - \$85,000
\$85,000 - \$110,000
\$110,000 - \$142,530
> \$142,530

Initial Characteristic Analysis

- Cut-offs may be rough from decision tree combining.
- **Optional to override** automatically generated groups to conform to business rules.
- Overrides may make groups suboptimal.

Group Definition	Override
Missing	Missing
< \$35,200	< \$35,000
\$35,200 - \$60,000	\$35,000 - \$60,000
\$60,000 - \$85,000	\$60,000 - \$85,000
\$85,000 - \$110,000	\$85,000 - \$110,000
\$110,000 - \$142,530	\$110,000 - \$140,000
> \$142,530	> \$140,000

Initial Characteristic Analysis

- Cut-offs may be rough from decision tree combining.
- **Optional to override** automatically generated groups to conform to business rules.
- Overrides may make groups suboptimal.

Group Definition	Override
Missing	Missing
< \$35,200	< \$35,000
\$35,200 - \$60,000	\$35,000 - \$60,000
\$60,000 - \$85,000	\$60,000 - \$85,000
\$85,000 - \$110,000	\$85,000 - \$110,000
\$110,000 - \$142,530	\$110,000 - \$140,000
> \$142,530	> \$140,000

Initial Characteristic Analysis

- Calculate and examine the key assessment metrics:
 - **Weight of Evidence** (WOE) – how well attributes discriminate for each given characteristic
 - **Information Value** (IV) – evaluate a characteristic's overall predictive power
 - **Gini Statistic** – alternate to IV for selecting characteristics for final model.



WEIGHT OF EVIDENCE

Weight of Evidence (WOE)

- WOE measures the strength of the attributes of a characteristic in **separating good and bad accounts**.
- WOE is based on comparing the proportion of goods to bads at each attribute level (levels of the predictor variable).

$$WOE_i = \log \left(\frac{Dist. Good_i}{Dist. Bad_i} \right)$$

Weight of Evidence (WOE)

- WOE measures the strength of the attributes of a characteristic in **separating good and bad accounts**.
- WOE is based on comparing the proportion of goods to bads at each attribute level (levels of the predictor variable).

$$WOE_i = \log \left(\frac{Dist. Good_i}{Dist. Bad_i} \right)$$

$$Dist. Good_i = \frac{Number\ Good\ in\ group\ i}{Total\ Number\ Good}$$

Weight of Evidence (WOE)

- WOE measures the strength of the attributes of a characteristic in **separating good and bad accounts**.
- WOE is based on comparing the proportion of goods to bads at each attribute level (levels of the predictor variable).

$$WOE_i = \log \left(\frac{Dist. Good_i}{Dist. Bad_i} \right)$$

$$Dist. Bad_i = \frac{Number\ Bad\ in\ group\ i}{Total\ Number\ Bad}$$


Weight of Evidence (WOE)

- What are we looking for?
 - Looking for “big” differences in WOE between groups.
 - Monotonic changes within an attribute for **interval variables** (not always required).
- Why monotonic increases?
 - Oscillation back and forth of positive to negative values of WOE typically sign of variable that has trouble separating good vs. bad.
 - Not always required **if makes business sense** – credit card utilization for example.

WOE – Example

WOE for Bureau Score				
Group	Values	Event Count	Non-event Count	WOE
1	< 603	111	112	
2	604 – 662	378	678	
3	663 – 699	185	754	
4	700 – 717	74	440	
5	718 – 765	75	824	
6	> 765	15	498	
7	MISSING	80	153	
Total		918	3,459	

WOE – Example

WOE for Bureau Score				
Group	Values	Event Count	Non-event Count	WOE
1	< 603	111	112	
2	604 – 662	378	678	
3	663 – 699	185	754	
4	700 – 717	74	440	
5	718 – 765	75	824	
6	> 765	15	498	
7	MISSING	80	153	
Total		918	3,459	

$$Dist. Good_1 = \frac{112}{3459}$$

$$= 0.032$$

WOE – Example

WOE for Bureau Score				
Group	Values	Event Count	Non-event Count	WOE
1	< 603	111	112	
2	604 – 662	378	678	
3	663 – 699	185	754	
4	700 – 717	74	440	
5	718 – 765	75	824	
6	> 765	15	498	
7	MISSING	80	153	
Total		918	3,459	


$$Dist. Good_1 = \frac{112}{3459}$$

$$= 0.032$$


$$Dist. Bad_1 = \frac{111}{918}$$

$$= 0.121$$


WOE – Example



WOE – Example



WOE – Example



WOE – Example

WOE for Bureau Score				
Group	Values	Event Count	Non-event Count	WOE
1	< 603	111	112	-1.32
2	604 – 662	378	678	
3	663 – 699	185	754	
4	700 – 717	74	440	
5	718 – 765	75	824	
6	> 765	15	498	
7	MISSING	80	153	
Total		918	3,459	

$$Dist. Good_1 = \frac{112}{3459}$$

$$= 0.032$$

$$Dist. Bad_1 = \frac{111}{918}$$

$$= 0.121$$

$$WOE_1 = \log\left(\frac{0.032}{0.121}\right)$$

$$= -1.32$$

WOE – Example

WOE for Bureau Score				
Group	Values	Event Count	Non-event Count	WOE
1	< 603	111	112	-1.32
2	604 – 662	378	678	-0.74
3	663 – 699	185	754	0.08
4	700 – 717	74	440	0.46
5	718 – 765	75	824	1.07
6	> 765	15	498	2.18
7	MISSING	80	153	-0.68
Total		918	3,459	

Weight of Evidence (WOE)

- WOE measures the strength of the attributes of a characteristic in **separating good and bad accounts**.

$$WOE_i = \log \left(\frac{Dist. Good_i}{Dist. Bad_i} \right)$$

- WOE approximately zero implies what?

Weight of Evidence (WOE)

- WOE measures the strength of the attributes of a characteristic in **separating good and bad accounts**.

$$WOE_i = \log \left(\frac{Dist. Good_i}{Dist. Bad_i} \right)$$

- WOE approximately zero implies % good approximately equal to % bad so group doesn't separate good vs. bad well.


Weight of Evidence (WOE)

- WOE measures the strength of the attributes of a characteristic in **separating good and bad accounts**.


$$WOE_i = \log \left(\frac{Dist. Good_i}{Dist. Bad_i} \right)$$

- WOE approximately zero implies % good approximately equal to % bad so group doesn't separate good vs. bad well.
- WOE positive implies group identifies people who are good.
- WOE negative implies group identifies people who are bad.

WOE – Example



WOE – Example



WOE – R

```
result <- smbinning(df = train, y = "good", x = "bureau_score")
result$ivtable
```

##	Cutpoint	CntRec	CntGood	CntBad	CntCumRec	CntCumGood	CntCumBad	PctRec
## 1	<= 603	223	112	111	223	112	111	0.0509
## 2	<= 662	1056	678	378	1279	790	489	0.2413
## 3	<= 699	939	754	185	2218	1544	674	0.2145
## 4	<= 717	514	440	74	2732	1984	748	0.1174
## 5	<= 765	899	824	75	3631	2808	823	0.2054
## 6	> 765	513	498	15	4144	3306	838	0.1172
## 7	Missing	233	153	80	4377	3459	918	0.0532
## 8	Total	4377	3459	918	NA	NA	NA	1.0000

##	GoodRate	BadRate	Odds	LnOdds	WoE	IV
## 1	0.5022	0.4978	1.0090	0.0090	-1.3176	0.1167
## 2	0.6420	0.3580	1.7937	0.5843	-0.7423	0.1602
## 3	0.8030	0.1970	4.0757	1.4050	0.0785	0.0013
## 4	0.8560	0.1440	5.9459	1.7827	0.4562	0.0213
## 5	0.9166	0.0834	10.9867	2.3967	1.0701	0.1675
## 6	0.9708	0.0292	33.2000	3.5025	2.1760	0.2777
## 7	0.6567	0.3433	1.9125	0.6484	-0.6781	0.0291
## 8	0.7903	0.2097	3.7680	1.3265	0.0000	0.7738

WOE – R

```
result$cut
```


```
## [1] 603 662 699 717 765
```

```
result$iv
```

```
## [1] 0.7738
```


WOE – R

```
smbinning.plot(result, option = "dist", sub = "Bureau Score")
```




WOE – R

```
smbinning.plot(result, option = "goodrate", sub = "Bureau Score")
```




WOE – R

```
smbinning.plot(result, option = "badrate", sub = "Bureau Score")
```



WOE – R

```
smbinning.plot(result, option = "WoE", sub = "Bureau Score")
```



WOE – R

```
result <- smbinning.factor(df = train, y = "good", x = "purpose")
result$ivtable
```

##	Cutpoint	CntRec	CntGood	CntBad	CntCumRec	CntCumGood	CntCumBad	PctRec
## 1	= 'LEASE'	1466	1149	317	1466	1149	317	0.3349
## 2	= 'LOAN'	2911	2310	601	4377	3459	918	0.6651
## 3	Missing	0	0	0	4377	3459	918	0.0000
## 4	Total	4377	3459	918	NA	NA	NA	1.0000

##	GoodRate	BadRate	Odds	LnOdds	WoE	IV
## 1	0.7838	0.2162	3.6246	1.2877	-0.0388	0.0005
## 2	0.7935	0.2065	3.8436	1.3464	0.0199	0.0003
## 3	NaN	NaN	NaN	NaN	NaN	NaN
## 4	0.7903	0.2097	3.7680	1.3265	0.0000	0.0008

Separation Issues Remain

- Quasi-complete separation still a problem:

	Non-Event	Event	WOE
A	28	7	-0.032
B	16	0	∞
C	94	11	0.728
D	23	21	-1.327
Total	161	39	

Adjusted WOE

- Adjust the WOE calculation to account for possible quasi-complete separation:

$$\text{Adjusted } WOE_i = \log \left(\frac{\text{Dist. Good}_i + \eta_1}{\text{Dist. Bad}_i + \eta_2} \right)$$

- The η_1 and η_2 parameters are smoothing parameters that correct for potential overfitting and also protect against quasi-complete separation.
- Most software just sets $\eta_1 = \eta_2$ and has one parameter.

Adjusted WOE ($\eta_1 = \eta_2 = 0.005$)

- Quasi-complete separation no longer a problem:

	Non-Event	Event	WOE
A	28	7	-0.031
B	16	0	3.039
C	94	11	0.719
D	23	21	-1.302
Total	161	39	

Smoothed WOE (SWOE)

- SAS has recently proposed a slightly different smoothed version of the WOE calculation to account for possible quasi-complete separation:

$$SWOE_i = \log \left(\frac{\#Bad_i + (Overall\ Prop.\ Bad) \times c}{\#Good_i + (Overall\ Prop.\ Good) \times c} \right)$$

- This is just a smoothing parameter put in a slightly different place in the WOE calculation based on more Bayesian inference techniques.
- Haven't seen it really used elsewhere.



INFORMATION VALUE

Information Value (IV)

- How big is a “big” difference when looking across groups for WOE?
- IV measures the ability of the characteristic to separate goods vs. bads.

$$IV = \sum_{i=1}^L (Dist. Good_i - Dist. Bad_i) \times \log \left(\frac{Dist. Good_i}{Dist. Bad_i} \right)$$

Information Value (IV)

- How big is a “big” difference when looking across groups for WOE?
- IV measures the ability of the characteristic to separate goods vs. bads.

$$IV = \sum_{i=1}^L (Dist.Good_i - Dist.Bad_i) \times \log \left(\frac{Dist.Good_i}{Dist.Bad_i} \right)$$

Weight of Evidence!

Information Value (IV)

- How big is a “big” difference when looking across groups for WOE?
- IV measures the ability of the characteristic to separate goods vs. bads.

$$IV = \sum_{i=1}^L (Dist.Good_i - Dist.Bad_i) \times \log \left(\frac{Dist.Good_i}{Dist.Bad_i} \right)$$


- Used to select characteristics with strong predictive value.

Information Value (IV)

- Characteristics of IV:
 - $IV \geq 0$
 - Bigger is Better!
- Rules of Thumb:
 - $IV < 0.02$ – Not predictive
 - $0.02 < IV < 0.1$ – Weak predictor
 - $0.1 < IV < 0.25$ – Medium predictor
 - $0.25 < IV$ – Strong predictor

Information Value (IV) – R

```
iv_summary <- smbinning.sumiv(df = train, y = "good")  
  
smbinning.sumiv.plot(iv_summary)
```



Information Value (IV) – R

iv_summary

##	Char	IV	Process
## 12	bureau_score	0.7738	Numeric binning OK
## 10	tot_rev_line	0.3987	Numeric binning OK
## 11	rev_util	0.3007	Numeric binning OK
## 6	age_oldest_tr	0.2512	Numeric binning OK
## 4	tot_derog	0.2443	Numeric binning OK
## 19	ltv	0.1454	Numeric binning OK
## 5	tot_tr	0.1304	Numeric binning OK
## 15	down_pyt	0.0848	Numeric binning OK
## 9	tot_rev_debt	0.0782	Numeric binning OK
## 20	tot_income	0.0512	Numeric binning OK
## 17	loan_term	0.0496	Numeric binning OK
## 14	msrp	0.0353	Numeric binning OK
## 13	purch_price	0.0204	Numeric binning OK
## 16	purpose	0.0008	Factor binning OK
## 1	bankruptcy	NA	Uniques values < 5
## 2	bad	NA	Uniques values < 5
## 3	app_id	NA	No significant splits
## 7	tot_open_tr	NA	No significant splits
## 8	tot_rev_tr	NA	No significant splits
## 18	loan_amt	NA	No significant splits
## 21	used_ind	NA	Uniques values < 5
## 22	weight	NA	Uniques values < 5

Information Value (IV) – R

iv_summary

##	Char	IV	Process
## 12	bureau_score	0.7738	Numeric binning OK
## 10	tot_rev_line	0.3987	Numeric binning OK
## 11	rev_util	0.3007	Numeric binning OK
## 6	age_oldest_tr	0.2512	Numeric binning OK
## 4	tot_derog	0.2443	Numeric binning OK
## 19	ltv	0.1454	Numeric binning OK
## 5	tot_tr	0.1304	Numeric binning OK
## 15	down_pyt	0.0848	Numeric binning OK
## 9	tot_rev_debt	0.0782	Numeric binning OK
## 20	tot_income	0.0512	Numeric binning OK
## 17	loan_term	0.0496	Numeric binning OK
## 14	msrp	0.0353	Numeric binning OK
## 13	purch_price	0.0204	Numeric binning OK
## 16	purpose	0.0008	Factor binning OK
## 1	bankruptcy	NA	Uniques values < 5
## 2	bad	NA	Uniques values < 5
## 3	app_id	NA	No significant splits
## 7	tot_open_tr	NA	No significant splits
## 8	tot_rev_tr	NA	No significant splits
## 18	loan_amt	NA	No significant splits
## 21	used_ind	NA	Uniques values < 5
## 22	weight	NA	Uniques values < 5

Information Value (IV) – R

iv_summary

##	Char	IV	Process
## 12	bureau_score	0.7738	Numeric binning OK
## 10	tot_rev_line	0.3987	Numeric binning OK
## 11	rev_util	0.3007	Numeric binning OK
## 6	age_oldest_tr	0.2512	Numeric binning OK
## 4	tot_derog	0.2443	Numeric binning OK
## 19	ltv	0.1454	Numeric binning OK
## 5	tot_tr	0.1304	Numeric binning OK
## 15	down_pyt	0.0848	Numeric binning OK
## 9	tot_rev_debt	0.0782	Numeric binning OK
## 20	tot_income	0.0512	Numeric binning OK
## 17	loan_term	0.0496	Numeric binning OK
## 14	msrp	0.0353	Numeric binning OK
## 13	purch_price	0.0204	Numeric binning OK
## 16	purpose	0.0008	Factor binning OK
## 1	bankruptcy	NA	Uniques values < 5
## 2	bad	NA	Uniques values < 5
## 3	app_id	NA	No significant splits
## 7	tot_open_tr	NA	No significant splits
## 8	tot_rev_tr	NA	No significant splits
## 18	loan_amt	NA	No significant splits
## 21	used_ind	NA	Uniques values < 5
## 22	weight	NA	Uniques values < 5

Information Value (IV) – R

iv_summary

##	Char	IV	Process
## 12	bureau_score	0.7738	Numeric binning OK
## 10	tot_rev_line	0.3987	Numeric binning OK
## 11	rev_util	0.3007	Numeric binning OK
## 6	age_oldest_tr	0.2512	Numeric binning OK
## 4	tot_derog	0.2443	Numeric binning OK
## 19	ltv	0.1454	Numeric binning OK
## 5	tot_tr	0.1304	Numeric binning OK
## 15	down_pyt	0.0848	Numeric binning OK
## 9	tot_rev_debt	0.0782	Numeric binning OK
## 20	tot_income	0.0512	Numeric binning OK
## 17	loan_term	0.0496	Numeric binning OK
## 14	msrp	0.0353	Numeric binning OK
## 13	purch_price	0.0204	Numeric binning OK
## 16	purpose	0.0008	Factor binning OK
## 1	bankruptcy	NA	Uniques values < 5
## 2	bad	NA	Uniques values < 5
## 3	app_id	NA	No significant splits
## 7	tot_open_tr	NA	No significant splits
## 8	tot_rev_tr	NA	No significant splits
## 18	loan_amt	NA	No significant splits
## 21	used_ind	NA	Uniques values < 5
## 22	weight	NA	Uniques values < 5

Information Value (IV)

- Characteristics of IV:
 - $IV \geq 0$
 - Bigger is Better!
- Rules of Thumb:
 - $IV < 0.02$ – Not predictive
 - $0.02 < IV < 0.1$ – Weak predictor
 - $0.1 < IV < 0.25$ – Medium predictor
 - $0.25 < IV < 0.5$ – Strong predictor
 - $IV > 0.5$ – Over-predicting?

Information Value (IV)

- Rules of Thumb:
 - $IV < 0.02$ – Not predictive
 - $0.02 < IV < 0.1$ – Weak predictor
 - $0.1 < IV < 0.25$ – Medium predictor
 - $0.25 < IV < 0.5$ – Strong predictor
 - $IV > 0.5$ – Over-predicting?
- Over-predicting Example:
 - All previous mortgage decisions have been made only on bureau score so of course bureau score is highly predictive – becomes only significant variable!
 - Create two models – one with bureau score, one without bureau score and **ensemble**.



GINI STATISTIC

Gini Statistic

- **Gini statistic** is optional technique that tries to answer the same question as Information Value – which variables are strong enough to enter the scorecard model?
- IV is more in line with WOE calculation and used more often.
- Characteristics:
 - Range is 0 to 100.
 - Bigger is Better.


Gini Statistic Calculation

- More complicated technique for trying to evaluate how characteristics separate good from bad.
- Majority of the time Gini and IV agree, but could be different on the borderline cases.
- Calculation:
 - Sort L groups of variable by descending order of the proportion of all events.

$$Gini = \left(1 - \frac{(2 \sum_{i=2}^L (n_{i,E} \times \sum_{j=1}^{i-1} n_{j,NE}) + \sum_{i=1}^L (n_{i,E} \times n_{i,NE}))}{N_E \times N_{NE}} \right) \times 100$$

Gini Statistic Calculation


- More complicated technique for trying to evaluate how characteristics separate good from bad.
- Majority of the time Gini and IV agree, but could be different on the borderline cases.
- Calculation:
 - Sort L groups of variable by descending order of the proportion of all events.

$$Gini = \left(1 - \frac{(2 \sum_{i=2}^L (n_{i,E} \times \sum_{i=1}^{i-1} n_{i,NE}) + \sum_{i=1}^L (n_{i,E} \times n_{i,NE}))}{N_E \times N_{NE}} \right) \times 100$$


Number of events in group i

Gini Statistic Calculation

- More complicated technique for trying to evaluate how characteristics separate good from bad.
- Majority of the time Gini and IV agree, but could be different on the borderline cases.
- Calculation:
 - Sort L groups of variable by descending order of the proportion of all events.

$$Gini = \left(1 - \frac{(2 \sum_{i=2}^L (n_{i,E} \times \sum_{j=1}^{i-1} n_{j,NE}) + \sum_{i=1}^L (n_{i,E} \times n_{i,NE}))}{N_E \times N_{NE}} \right) \times 100$$


Number of non-events in group i

Gini Statistic Calculation

- More complicated technique for trying to evaluate how characteristics separate good from bad.
- Majority of the time Gini and IV agree, but could be different on the borderline cases.
- Calculation:
 - Sort L groups of variable by descending order of the proportion of all events.

$$Gini = \left(1 - \frac{(2 \sum_{i=2}^L (n_{i,E} \times \sum_{i=1}^{i-1} n_{i,NE}) + \sum_{i=1}^L (n_{i,E} \times n_{i,NE}))}{N_E \times N_{NE}} \right) \times 100$$

Total number of events and non-events



PROC BINNING IN SAS VIYA

WOE – SAS Viya

```
proc binning data = public.train method = tree(initbin = 100  
            maxnbins = 10);  
    target bad / level = int;  
    input bureau_score / level = int;  
    ods output BinDetails = bincuts VarTransInfo = bincount;  
run;
```

WOE – SAS Viya

[illegible]

WOE – SAS Viya

Transformation Information					
Variable	N	N Miss	N Bins	Importance	Relative Importance
bureau_score					

WOE – SAS Viya

```
data _null_;  
    set bincount;  
    call symput('numbin', Nbins - 1);  
run;  
  
proc sql;  
    select Max  
        into :cuts separated by ' '  
        from bincuts(firstobs = 2 obs = &numbin);  
quit;  
  
proc binning data = public.train numbin = &numbin  
                method=cutpts(&cuts) woe;  
    target bad / event = '1';  
    input bureau_score / level = int;  
run;
```

WOE – SAS Viya

[illegible]

WOE – SAS Viya

[illegible]

WOE – SAS Viya

Variable Information Value	
Variable	Information Value
bureau_score	

WOE – SAS Viya

```
proc tabulate data=public.train out=facwoe;  
  class bad purpose;  
  table purpose, bad*colpctn / rts=10;  
run;  
  
proc transpose data = facwoe out = facwoe2(rename=  
                                             (col1 = bad0 col2 = bad1));  
  
  var PctN_10;  
  by purpose;  
run;  
  
data facwoe2;  
  set facwoe2;  
  WOE = log(bad1/bad0);  
run;
```

WOE – SAS Viya

	bad	
	0	1
	ColPctN	ColPctN
purpose		
LEASE		
LOAN		

Obs	purpose	_NAME_	bad0	bad1	WOE
1					
2					

INTERACTIVE GROUPING NODE IN SAS EM

Pre-Binning of the Interval Variables

The screenshot shows the 'Train' dialog box in SAS EM. The 'Interval Variable Binning Options' section is expanded, and the 'Binning Method' is set to 'Quantile' and the 'Number of Bins' is set to '20'. A red box highlights these two settings, and a yellow callout box with an arrow points to them with the text 'Binning Method Number of Bins'.

Train	
Variables	
Interactive Grouping	
<input checked="" type="checkbox"/> Pre-Defined Groupings	
Use Frozen Groupings	No
Import Grouping Data	No
Import Dataset	...
Use Pre-Defined WOE values	None
<input checked="" type="checkbox"/> Interval Variable Binning Options	
Apply Level Rule	No
Binning Method	Quantile
Number of Bins	20
<input checked="" type="checkbox"/> Special Code Options	
Use Special Codes	No
Special Codes Data Set	...
<input checked="" type="checkbox"/> Grouping Options	
Interval Grouping Method	Optimal Criterion
Ordinal Grouping Method	Optimal Criterion
Tree Based Grouping Options	...
Constrained Optimal Options	...
Advanced Constrained Optimal	...

Grouping Options

The screenshot shows the 'Grouping Options' dialog box in SAS EM. Two red rounded rectangles highlight specific sections: the top section for 'Pre-Defined Groupings' and the bottom section for 'Grouping Options'. Arrows from yellow callout boxes point to these sections.

<input checked="" type="checkbox"/> Pre-Defined Groupings	
Use Frozen Groupings	No
Import Grouping Data	No
Import Dataset	...
Use Pre-Defined WOE values	None
<input checked="" type="checkbox"/> Interval Variable Binning Option	
Apply Level Rule	No
Binning Method	Quantile
Number of Bins	20
<input checked="" type="checkbox"/> Special Code Options	
Use Special Codes	No
Special Codes Data Set	...
<input checked="" type="checkbox"/> Grouping Options	
Interval Grouping Method	Optimal Criterion
Ordinal Grouping Method	Optimal Criterion
Tree Based Grouping Options	...
Constrained Optimal Options	...
Advanced Constrained Optimal	...
Maximum Number of Groups	5
Significant Digits	2
Apply Restrictions	Yes
Type	Percent
Percent	5.0
Count	.
Adjust WOE	Yes
Adjustment Factor	0.5

Pre-Defined Groupings

Grouping Options

Grouping Options: Tree Criteria

<input type="checkbox"/>	Pre-Defined Groupings	
<input type="checkbox"/>	Use Frozen Groupings	No
<input type="checkbox"/>	Import Grouping Data	No
<input type="checkbox"/>	Import Dataset	...
<input type="checkbox"/>	Use Pre-Defined WOE values	None
<input checked="" type="checkbox"/>	Interval Variable Binning Option	
<input type="checkbox"/>	Apply Level Rule	No
<input type="checkbox"/>	Binning Method	Quantile
<input type="checkbox"/>	Number of Bins	20
<input checked="" type="checkbox"/>	Special Code Options	
<input type="checkbox"/>	Use Special Codes	No
<input type="checkbox"/>	Special Codes Data Set	...
<input checked="" type="checkbox"/>	Grouping Options	
<input type="checkbox"/>	Interval Grouping Method	Optimal Criterion
<input type="checkbox"/>	Ordinal Grouping Method	Optimal Criterion
<input checked="" type="checkbox"/>	Tree Based Grouping Options	...
<input type="checkbox"/>	Constrained Optimal Options	...
<input type="checkbox"/>	Advanced Constrained Optimal	...
<input type="checkbox"/>	Maximum Number of Groups	5

**Control tree
criteria
for grouping:
Split Criterion
Missing Values
Minimum Group
Size**

Grouping Options: Interval vs. Ordinal

The screenshot shows the 'Grouping Options' section of a SAS EM dialog box. A red rectangle highlights the 'Interval Grouping Method' and 'Ordinal Grouping Method' rows, both set to 'Optimal Criterion'. A yellow callout box with a black border contains the text 'Interval Grouping Method' and 'Ordinal Grouping Method'. An arrow points from this box to the 'Interval Grouping Method' row.

<input checked="" type="checkbox"/> Pre-Defined Groupings	
<input type="checkbox"/> Use Frozen Groupings	No
<input type="checkbox"/> Import Grouping Data	No
<input type="checkbox"/> Import Dataset	
<input type="checkbox"/> Use Pre-Defined WOE values	None
<input checked="" type="checkbox"/> Interval Variable Binning Option	
<input type="checkbox"/> Apply Level Rule	No
<input type="checkbox"/> Binning Method	Quantile
<input type="checkbox"/> Number of Bins	20
<input checked="" type="checkbox"/> Special Code Options	
<input type="checkbox"/> Use Special Codes	No
<input type="checkbox"/> Special Codes Data Set	...
<input checked="" type="checkbox"/> Grouping Options	
<input type="checkbox"/> Interval Grouping Method	Optimal Criterion
<input type="checkbox"/> Ordinal Grouping Method	Optimal Criterion
<input type="checkbox"/> Tree Based Grouping Options	...
<input type="checkbox"/> Constrained Optimal Options	...
<input type="checkbox"/> Advanced Constrained Optimal	

Interval Grouping Method
Ordinal Grouping Method

Grouping Options: Number of Groups

Special Code Options	
Use Special Codes	No
Special Codes Data Set	...
Grouping Options	
Interval Grouping Method	Optimal Criterion
Ordinal Grouping Method	Optimal Criterion
Tree Based Grouping Options	...
Constrained Optimal Options	...
Advanced Constrained Optimal	...
Maximum Number of Groups	5
Significant Digits	2
Apply Restrictions	Yes
Type	Percent
Percent	5.0
Count	.
Adjust WOE	Yes
Adjustment Factor	0.5

Maximum Number of Groups

Grouping Options: Stopping Rules

The image shows a screenshot of the 'Grouping Options' dialog box in SAS EM. A yellow callout box with a black border points to the 'Apply Restrictions' option. The callout box contains the text: 'Apply Restrictions', 'Type', 'Percent', and 'Count'. The dialog box itself has a list of options on the left and their corresponding values on the right. A red rectangle highlights the 'Apply Restrictions' section, which includes 'Type' (Percent), 'Percent' (5.0), and 'Count' (1).

Option	Value
Interval Grouping Method	Optimal Criterion
Ordinal Grouping Method	Optimal Criterion
Tree Based Grouping Options	...
Constrained Optimal Options	...
Advanced Constrained Optimal	...
Maximum Number of Groups	5
Significant Digits	2
Apply Restrictions	Yes
Type	Percent
Percent	5.0
Count	1
Adjust WOE	Yes
Adjustment Factor	0.5

Grouping Options: WOE Adjustments

[-] Grouping Options	
Interval Grouping Method	Optimal Criterion
Ordinal Grouping Method	Optimal Criterion
Tree Based Grouping Options	...
Constrained Optimal Options	
Advanced Constrained Optimal	
Maximum Number of Groups	5
Significant Digits	2
Apply Restrictions	Yes
Type	Percent
Percent	5.0
Count	.
Adjust WOE	Yes
Adjustment Factor	0.5

**Adjust WOE
Adjustment Factor**

