Databases (Key: 1644)
Relational Algebra Class Example

---------   Arellanes Conde Esteban   ----------

Contents

1 Homework: Relational Algebra

Figure 1: Tarea7.1.

1.1 $R1 \times R2$

A	X	B	Y	B_2	W	D	Y_2	A_2	Z
7	2	6	11	2	5	6	11	1	30
7	2	6	11	2	5	6	11	1	30
3	4	9	15	4	7	8	4	7	8

Table 1: $R1 \times R2$

1.2 $R1 \bowtie R2$ (Join Natural)

A	B	Y
$\varnothing$	$\varnothing$	$\varnothing$

1.3 $R1 \bowtie ((R1.A > R2.Z$ or $R1.A \geq R2.W)$ and $R1.Y = R2.Y)R2$

A	X	B	Y	B_2	W	D	Y_2	A_2	Z
10	7	2	4	4	7	8	4	7	8

2 References

[1] Ramez Elmasri, Shamkant B. Navathe. Fundamentals of Database Systems (Global Edition). Pearson 2017

[2] De Miguel Martínez, Adoración, Piattini, Mario, Esperanza, Marcos Diseño de bases de datos relacionales. México, Alfaomega, 2000.

[3] Kriegel, Alex; Trukhnov. SQL Bible, second edition, Willey 2008.

[4] Alan Beaulieu, Learning SQL: Generate, Manipulate, and Retrieve Data, O'Reilly, 3rd. Edition - 2020.

[5] Joan Casteel, Oracle 12c: SQL. Cengage Learning, Sep 11, 2015.

[6] PostgreSQL Global Development Group, "PostgreSQL Documentation," `https://www.postgresql.org/docs/`.

[7] IEEE, "Guide to Software Requirements Specifications," IEEE Std 830-1984. `https://chumpolm.files.wordpress.com/2018/09/ieee-std-830-1984.pdf`