

2) Escriba unha función chamada `trienios_teuuser` que reciba un número de anos completos (int) e devolva o nº de trienios (int).

The screenshot shows the MySQL Workbench interface. The 'Schemas' pane on the left lists various databases, with 'trienios_CARLOSFL' selected. The main editor displays the SQL code for creating the function:

```
1 DELIMITER //
2 CREATE FUNCTION trienios_CARLOSFL(años INT) RETURNS INT DETERMINISTIC
3 BEGIN
4     DECLARE trienios INT;
5
6     SET trienios = años DIV 3; -- DIV realiza la división entera
7
8     RETURN trienios;
9 END //
10 DELIMITER ;
11
12 -- CARLOSFL
```

The 'Action Output' pane at the bottom shows the execution results:

#	Time	Action	Message	Duration / Fetch
1	20:41:31	CREATE FUNCTION trienios_CARLOSFL(años INT) RETURN...	0 row(s) affected	0.0050 sec
2	20:41:46	select trabajadores.trienios_CARLOSFL(3) LIMIT 0, 1000	1 row(s) returned	0.00042 sec / 0.000...

The screenshot shows the MySQL Workbench interface. The main editor displays the SQL code for calling the function:

```
1 select trabajadores.trienios_CARLOSFL(3);
2
```

The 'Result Grid' pane shows the output of the query:

#	trabajadores.trienios_CARLOSFL
1	1

The 'Action Output' pane at the bottom shows the execution results:

#	Time	Action	Message	Duration / Fetch
1	20:41:31	CREATE FUNCTION trienios_CARLOSFL(años INT) RETURN...	0 row(s) affected	0.0050 sec
2	20:41:46	select trabajadores.trienios_CARLOSFL(3) LIMIT 0, 1000	1 row(s) returned	0.00042 sec / 0.000...