
# Impinj Monza® R6 Steel Wire Seal RFID Tag









# **Key Features**

Frequency Band UHF 860-960 MHz

Chip

**IMPINJ MONZA®R6** 

**International Standard** 

ISO/IEC 18000-6C and EPC Global Gen2v2

**EPC Memory** 

96 bits

Read Range

Up to 6 m

### 1. Product Overview

IMPINJ MONZA®R6 RFID steel wire seal tags are widely used in the logistics industry, such as truck compartment door maintenance, well-head valve maintenance, etc. These tags are made of high-quality zinc alloy and steel wire rope to ensure that the data is not subject to electromagnetic interference, with excellent information storage capacity and excellent anti-pollution ability. Its advantage is its very fast reading speed.

### 2. Product Parameters

## 2.1 Physical Characteristics

| SKU                | AZCT-R6-AW                    |                                     |  |
|--------------------|-------------------------------|-------------------------------------|--|
| Material           | ABS and Steel wire            | ABS and Steel wire                  |  |
| Model No.          | AW-7828                       | AW-5053                             |  |
| Tag Size(L*W,mm)   | 78x28                         | 50x53                               |  |
| Cable Tie Size(mm) | 280x1                         | 280x1                               |  |
| Tag Type           | Disposable                    | Disposable                          |  |
| Weight             | 11 g                          | 8.5 g                               |  |
| Color              | Red / Yellow / Blue / Black / | Red / Yellow / Blue / Black / White |  |

### 2.2 Technical Parameters

| Communication Protocol | ISO/IEC 18000-6C, EPC Global Gen2v2 |
|------------------------|-------------------------------------|
| Operating Frequency    | UHF 860-960 MHz                     |
| Read Range             | Up to 6 m                           |



# 2.3 Chip Characteristics


| Chip Manufacturer | IMPINJ®         |
|-------------------|-----------------|
| Chip Type         | IMPINJ MONZA®R6 |
| Write Endurance   | 100 000 times   |
| Data Retention    | 10 years        |
| EPC Memory        | 96 Bits         |
| User Memory       | 0 Bits          |
| Read Sensitivity  | -22 dBm         |
| Write Sensitivity | -17 dBm         |
|                   |                 |

### 2.4 Additional Information


| Operating Environment | -30℃~+85℃   |
|-----------------------|---|
| Application           | Logistics industry, truck compartment doors upkeep, wellhead valves maintenance, etc. |

### Size and Specification Drawing: 3.

# (1) Model No. AW-7828 (Disposable)



# (2) Model No. AW-5053 (Disposable)





# https://www.rfidtag.com

Phone Number: +86-131-3958-0585 E-mail: sales@rfidtag.com Singapore Office: 10 Science Park Road #03-17A, The Alpha, Singapore Science Park, Singapore 117684 Shenzhen Office : 33-408, Qianhai SZ-HK Fund Town, Nanshan, Shenzhen, China 518052

Shenzhen Factory : Q5, XingDao Industrial Park, LongGang, Bantian, Shenzhen China 518129