










CARMINE-EMANUELE CELLA

PLAYING THE WORLD

AN INTRODUCTION TO PHYSICAL MODELLING FOR AUGMENTED REALITY

KATHARSIS AND MIMESIS



FROM PHYSICAL MODELLING TO PHYSICALLY-INSPIRED



Accurate

Expressive

Real sounds (almost)

Plausible sounds







 Physical modelling synthesis generates sounds by copying the mechanical system under vibration and not by copying the sound itself

- Physical modelling synthesis generates sounds by copying the mechanical system under vibration and not by copying the sound itself
- It is based on the solutions of wave equation: $\frac{\partial^2 u}{\partial t^2} = c^2 \frac{\partial^2 u}{\partial x^2}$.

- Physical modelling synthesis generates sounds by copying the mechanical system under vibration and not by copying the sound itself
- It is based on the solutions of wave equation: $rac{\partial^2 u}{\partial t^2}=c^2rac{\partial^2 u}{\partial x^2}$
- A simplification is represented by the system exciter-resonators



- Physical modelling synthesis generates sounds by copying the mechanical system under vibration and not by copying the sound itself
- ullet It is based on the solutions of wave equation: $\dfrac{\partial^2 u}{\partial t^2}=c^2\dfrac{\partial^2 u}{\partial x^2}$
- A simplification is represented by the system exciter-resonators



HISTORICAL PERSPECTIVE

- Karplus-Strong (1983): delay-line + lowpass filter
- Smith-Karplus-Strong (1983): delay-line + lowpass filter + allpass filter
- Waveguides (1990/2000, Smith): two delay lines with taps and various filters
- Modal synthesis (1990/2010, Adrien): resonant filters and modal weights

 A vibrating object can be described by the harmonic oscillator, that can be represented by the spring-mass system:

$$x = e^{-\alpha t} A \cos(\omega_d t + \phi) \tag{1}$$

 A vibrating object can be described by the harmonic oscillator, that can be represented by the spring-mass system:

$$x = e^{-\alpha t} A \cos(\omega_d t + \phi) \tag{1}$$

 A vibrating object can be described by the harmonic oscillator, that can be represented by the spring-mass system:

$$x = e^{-\alpha t} A \cos(\omega_d t + \phi) \tag{1}$$

ullet α is the decay constant of the system and depends on the mass and on the stiffness of the spring (dissipation)

 A vibrating object can be described by the harmonic oscillator, that can be represented by the spring-mass system:

$$x = e^{-\alpha t} A \cos(\omega_d t + \phi) \tag{1}$$


- ullet lpha is the decay constant of the system and depends on the mass and on the stiffness of the spring (dissipation)
- \bullet ω_d is the natural angular frequency

 A vibrating object can be described by the harmonic oscillator, that can be represented by the spring-mass system:

$$x = e^{-\alpha t} A \cos(\omega_d t + \phi) \tag{1}$$

- ullet α is the decay constant of the system and depends on the mass and on the stiffness of the spring (dissipation)
- \bullet ω_d is the natural angular frequency
- A and Φ are, respectively, the amplitude and the phase of the vibration and are determined by initial displacement and velocity

A natural mode of vibration, as described by equation 1




MODES AND FILTERS

In digital domain, equation 1 can be reproduced by the following second-order differential equation (two-poles):

$$y = x \cdot b_0 - y \cdot z^{-1} \cdot a_1 - y \cdot z^{-2} \cdot a_2$$
 (2)

where z^{-n} is the delay of n digital samples, b_0 , a_1 and a_2 are coefficients and x is the input signal




MODES AND FILTERS

In digital domain, equation 1 can be reproduced by the following second-order differential equation (two-poles):

$$y = x \cdot b_0 - y \cdot z^{-1} \cdot a_1 - y \cdot z^{-2} \cdot a_2$$
 (2)

where z^{-n} is the delay of n digital samples, b_0 , a_1 and a_2 are coefficients and x is the input signal



 The estimation of the parameters for resonators is based of experimental measurements

- The estimation of the parameters for resonators is based of experimental measurements
- Frequencies and the decays are based on physical properties (such as inharmonicity), amplitudes are usually determined by the feedback interaction between the resonators and the exciter

- The estimation of the parameters for resonators is based of experimental measurements
- Frequencies and the decays are based on physical properties (such as inharmonicity), amplitudes are usually determined by the feedback interaction between the resonators and the exciter
- Injecting a digital impulse into the resonators, will equally excite all resonators; with a feedback, the excitation signal will exhibits a temporal smearing and a frequency equalisation

- The estimation of the parameters for resonators is based of experimental measurements
- Frequencies and the decays are based on physical properties (such as inharmonicity), amplitudes are usually determined by the feedback interaction between the resonators and the exciter
- Injecting a digital impulse into the resonators, will equally excite all resonators; with a feedback, the excitation signal will exhibits a temporal smearing and a frequency equalisation



A CREATIVE APPROACH

 The simulation of a real vibrating object by means of modal synthesis (for example a musical instrument) can be a difficult task

A CREATIVE APPROACH


- The simulation of a real vibrating object by means of modal synthesis (for example a musical instrument) can be a difficult task
- The simulation of quasi-physical instruments can be an interesting creative activity

A CREATIVE APPROACH

- The simulation of a real vibrating object by means of modal synthesis (for example a musical instrument) can be a difficult task
- The simulation of quasi-physical instruments can be an interesting creative activity
- Physically-inspired synthesis is variant of modal synthesis that generates sounds with special physical characteristics without modelling real vibrating objects


PARAMETER MODELS

In physically-inspired synthesis, the feedback between the exciter and the resonators is replaced by a **parameter model** and the excitation is provided by a **sensor**



PARAMETER MODELS

In physically-inspired synthesis, the feedback between the exciter and the resonators is replaced by a **parameter model** and the excitation is provided by a **sensor**





$$\sum_{n=1}^{\infty} \frac{1}{n^{\alpha} \cdot \beta^n + \gamma}$$


Our model will use a generalised series (harmonic + geometric) for the parameters of each mode, where each variable is connected to a physical property:

$$\sum_{n=1}^{\infty} \frac{1}{n^{\alpha} \cdot \beta^n + \gamma}$$

mode number







CALCULATION OF PARAMETERS


We will split previous series in two parts; one will be used for frequencies and the other for decays:

$$\sum_{n=1}^{\infty} \frac{1}{n^{\alpha}}$$

$$\sum_{n=1}^{\infty} \frac{1}{\beta^n}$$

CALCULATION OF PARAMETERS


We will split previous series in two parts; one will be used for frequencies and the other for decays:




$$\sum_{n=1}^{\infty} \frac{1}{\beta^n}$$

CALCULATION OF PARAMETERS


We will split previous series in two parts; one will be used for frequencies and the other for decays:




LET'S GO LIVE!



CAN WE SONIFY THE WORLD?




GESTURE MAPPING



LOW-LEVEL FEATURES FOR GESTURES

Numerical values describing the contents of a signal according to different kinds of inspection: temporal, spectral, perceptual, etc.



SPECTRAL FEATURES


Spectral centroid (brightness) and spectral spread (bandwidth) are important features:

$$\mu = \int x \cdot p(x) dx.$$

$$\sigma^2 = \int (x - \mu)^2 \cdot p(x) dx.$$

Where x are the frequencies of the spectrum and p(x) are the respective amplitudes; the spectral centroid is the weighted average

LET'S GO LIVE AGAIN!



MOGEES



MOGEES



INSIDE-OUT

for smart percussions (2017) commissioned by Ircam and Percussions de Strasbourg first performance: june 2017, Paris







INSIDE-OUT



• Modelling reality means choosing an abstraction level (mimesis and katharsis)

Modelling reality means choosing an abstraction level (mimesis and katharsis)

 Physical modelling synthesis is a flexible framework to model the acoustic behaviours of physical objects

- Modelling reality means choosing an abstraction level (mimesis and katharsis)
- Physical modelling synthesis is a flexible framework to model the acoustic behaviours of physical objects
- Physically-inspired synthesis expands this possibility by creating plausible sounds by means of sensors and parameter models

- Modelling reality means choosing an abstraction level (mimesis and katharsis)
- Physical modelling synthesis is a flexible framework to model the acoustic behaviours of physical objects
- Physically-inspired synthesis expands this possibility by creating plausible sounds by means of sensors and parameter models
- Gesture recognition, by means of low-level features, is the key step to create a system for augmented reality

GITHUB REPOSITORY OF THIS LECTURE

https://github.com/CarmineCella/Berkeley2018

SELECTED REFERENCES

- C. E. Cella, Generalized series for spectral design, 2013
- C. E. Cella, On physically-inspired synthesis of sound, 2012
- Rossing Fletcher, The physics of musical instruments, 2002
- J. Smith, Physical audio signal processing, 2006
- M. Puckette, The theory and techniques of electronic music, 2006

ANY QUESTIONS?



carmine.emanuele.cella@gmail.com