Moon

A Scripting Language for Sound And Music Computing

User Manual v0.5

Moon is a small, expressive scripting language designed as a control and computation layer for algorithmic composition, signal processing, and music technology research. It provides first-class numeric vectors, heterogeneous arrays, first-class procedures, file I/O, and a clean extension API for connecting to C++ libraries.

(c) 2026 by Carmine-Emanuele Cella

Contents

1 Overview **3**

2 Types and Values **3**
2.1 Numbers (scalars) . . . 4
2.2 Numeric vectors . . . 4
2.3 Arrays . . . 4
2.4 Strings . . . 5
2.5 Procs . . . 5

3 Variables and Expressions **5**
3.1 Variable declaration and assignment . . . 5
3.2 Operator precedence . . . 5
3.3 Arithmetic on vectors and scalars . . . 6
3.4 Comparison operators . . . 6
3.5 Logical operators . . . 6

4 Control Flow **6**
4.1 If / else if / else . . . 6
4.2 While . . . 6
4.3 For / in . . . 7
4.4 Return . . . 7

5 Procedures **7**
5.1 Named procedures . . . 7
5.2 Anonymous proc literals . . . 7
5.3 Calling procs by value . . . 7
5.4 Higher-order patterns . . . 8
5.5 Recursion . . . 8

6 Vectors — Numeric Arrays **8**
6.1 Creation . . . 8
6.2 Element-wise arithmetic . . . 8
6.3 Math functions (all element-wise) . . . 8
6.4 Reductions . . . 9
6.5 Indexing . . . 9
6.6 Iteration . . . 9
6.7 Conversion . . . 9

7 Arrays — Heterogeneous Lists **9**
7.1 Creation . . . 9
7.2 Indexing and assignment . . . 9
7.3 Mutation . . . 10
7.4 Non-mutating operations . . . 10
7.5 Reference semantics and copy . . . 10

8 Strings **10**

9 File I/O and Modules **11**
9.1 File I/O . . . 11
9.2 Loading modules . . . 11

9.3 Eval and exec 11

10 Built-in Functions Reference **11**
10.1 Math 11
10.2 Vector constructors and reductions 12
10.3 String builtins 12
10.4 Array builtins 12
10.5 Type and conversion 13
10.6 File I/O and modules 13
10.7 Higher-order and control 13

11 Standard Library Reference **14**
11.1 Constants 14
11.2 Core math 14
11.3 Number formatting 14
11.4 String utilities 15
11.5 Vector statistics 15
11.6 Array algorithms 15
11.7 Higher-order functions 16
11.8 Testing framework 16

12 Extending Moon from C++ **16**
12.1 Including Moon 16
12.2 Registering a builtin 17
12.3 Injecting global variables 17
12.4 Value types in C++ 17

13 Quick Reference **17**

1 Overview

Moon is a dynamically-typed, interpreted scripting language implemented as a single C++ header (`moon.h`). It is designed for use as a frontend for C++ tools in music technology, orchestration, and signal processing.

Key characteristics

- **Four value types:** number (scalar), vector (numeric array), string, array (heterogeneous), and proc (first-class function).
- **Numeric vectors** are `std::valarray<double>` under the hood; all arithmetic and math functions apply element-wise with scalar broadcasting.
- **Heterogeneous arrays** hold any mix of values; they have reference semantics (assignment shares the data).
- **First-class procedures** can be stored in variables, passed as arguments, and stored in arrays.
- **Modular:** `load("file.moon")` executes another file in the current environment; the `~/.moon/` directory is on the search path.
- **Extensible:** register C++ functions as Moon builtins with one line.

Building and running

To compile using CMake, from the *root* folder type:

```
mkdir build
cd build
cmake ..
make
```

You can also compile the code manually, from the src folder, with:

```
g++ -std=c++17 -O2 -o moon moon.cpp    # compile the interpreter
```

To run the interpreter, call:

```
./moon script.moon                          # run a file
./moon lib.moon script.moon                 # run multiple files,
   shared state
./moon                                      # start interactive REPL
```

Files loaded with `load()` search first in the current directory, then in `~/.moon/`.

2 Types and Values

Moon has five types. Use `type(x)` to inspect any value at runtime.

Type	`type()` result	**C++ representation**	**Semantics**
Scalar number	`"number"`	`valarray<double>` size 1	value (copies on assign)
Numeric vector	`"vector"`	`valarray<double>` size >1	value (copies on assign)
String	`"string"`	`std::string`	value (copies on assign)
Array	`"array"`	`shared_ptr<MoonArray>`	reference (shares on assign)
Proc	`"proc"`	`shared_ptr<Proc>`	reference (shares on assign)

2.1 Numbers (scalars)

Every numeric literal creates a 1-element vector, which behaves as an ordinary number in all arithmetic and comparisons. The internal representation is `std::valarray<double>`; scalar operations compile to single-element valarray arithmetic and are as fast as raw `double`.

```
var x = 42
var y = 3.14
var z = .5          # leading dot supported
var tiny = 1e-10    # scientific notation supported
var big  = 6.674e-11
```

Moon has no integer type. All numbers are IEEE 754 doubles. Use `floor`, `ceil`, and `mod` when integer arithmetic is needed.

2.2 Numeric vectors

A vector is a `std::valarray<double>` with more than one element. It is created with the `vec`, `linspace`, `zeros`, `ones`, or `range-to-to_vec` functions. All arithmetic operators and all math builtins (`sin`, `cos`, `sqrt`, etc.) apply element-wise.

```
var v = vec(1, 2, 3, 4, 5)      # from individual scalars
var w = linspace(0, 1, 5)       # 5 points evenly spaced in [0, 1]
var z = zeros(4)                # <0 0 0 0>
var o = ones(3)                 # <1 1 1>

print v + 10         # <11 12 13 14 15>   scalar broadcast
print v * v          # <1 4 9 16 25>      element-wise
print sin(w * PI)    # element-wise sin
```

Vectors print as `<1 2 3>` with angle brackets, distinguishing them from arrays which print as `[1, 2, 3]`.

Value semantics: assigning a vector copies all its data. Mutating the copy does not affect the original.

```
var a = vec(1, 2, 3)
var b = a            # b is an independent copy
b[0] = 99
print a[0]           # a is unchanged
```

2.3 Arrays

An array is a heterogeneous, mutable, ordered list of values. Elements may be numbers, strings, other arrays, or procs. The backing store is a `shared_ptr<vector<Value>>`.

```
var a = [1, "two", [3, 4], proc(x){ return x*2 }]
print a[0]           # 1
print a[1]           # two
print a[2][1]        # 4      -- nested indexing
print a[3](5)        # 10     -- calling a stored proc
```

Reference semantics: assigning an array copies the *pointer*, not the data. Both variables refer to the same underlying list. Use `copy(a)` to obtain an independent shallow copy.

```
var x = [1, 2, 3]
var y = x            # y and x share the same list
y[0] = 99
```

```
print x[0]            # x sees the change

var z = copy(x)       # z is a new, independent copy
z[0] = 0
print x[0]            # x is unaffected
```

`copy()` is a *shallow* copy: inner arrays are still shared. `range(lo, hi)` also produces an array (suitable for `for`/`in` loops). For numeric computation, prefer `linspace` which produces a vector.

2.4 Strings

Strings are immutable. The `+` operator concatenates and coerces numbers:

```
var s = "score: " + 99        # "score: 99"
var t = "ha" + "ha"           # "haha"
```

Escape sequences: `\n` (newline), `\t` (tab), `\\` (backslash), `\"` (double quote).

2.5 Procs

Procs are first-class values. A named `proc` declaration stores the proc in the global proc table; an anonymous `proc` literal creates a `shared_ptr<Proc>` value.

```
proc square (n) { return n * n }      # named proc

var double = proc (x) { return x * 2 }    # anonymous, stored in variable
print double(7)     # 14
```

Note: Procs are *not* closures. They see the global environment at call time, not the local variables of the scope in which they were defined.

3 Variables and Expressions

3.1 Variable declaration and assignment

```
var name = expression       # declare and initialise
name = expression           # assign to existing variable
```

`var` inside a proc creates a local variable. `var` at the top level creates a global. Plain assignment (`=` without `var`) searches locals first, then globals; creates a new binding if not found.

3.2 Operator precedence

Precedence	Operators	Associativity
1 (lowest)	`or`	left
2	`and`	left
3	`not`	right (unary)
4	`< > <= >= == !=`	non-associative
5	`+ -`	left
6	`* /`	left
7	`-` (unary)	right
8 (highest)	`[i]` subscript, `()` call	left

3.3 Arithmetic on vectors and scalars

All arithmetic operators are element-wise on vectors. When one operand is a scalar (1-element vector) and the other is a multi-element vector, the scalar is *broadcast* to match the vector size:

```
var v = vec(1, 2, 3)
print v + 10              # <11 12 13>     scalar broadcast
print v * v               # <1 4 9>        element-wise
print v + vec(10,20,30)   # <11 22 33>     vector + vector
```

Mismatched sizes (neither is 1) produce a runtime error.

3.4 Comparison operators

On scalars, comparisons return `1` (true) or `0` (false). On vectors, comparisons are element-wise and return a *mask vector* of 0s and 1s:

```
print 5 > 3               # 1
print vec(1,5,3) > 2      # <0 1 1>    mask
print all(vec(1,5,3) > 0)   # all elements > 0
print any(vec(1,5,3) > 4)   # some elements > 4
```

Use `all()` and `any()` to reduce a vector mask to a scalar for use in `if` and `while` conditions.

String equality uses `==` and `!=` only; ordering operators on strings produce a runtime error.

3.5 Logical operators

`and`, `or`, `not` always return a scalar `1` or `0`. Truthiness: any non-zero number, any non-empty string, any non-empty array, any proc is truthy; zero, empty string, and empty array are falsy.

4 Control Flow

4.1 If / else if / else

```
if (condition) {
    ...
} else if (other_condition) {
    ...
} else {
    ...
}
```

Parentheses around the condition are required. Any number of `else if` branches may appear; the final `else` is optional.

4.2 While

```
while (condition) {
    ...
    break        # exit the loop immediately
}
```

`break` exits the innermost `while` or `for` loop. There is no `continue`.

4.3 For / in

Iterates over arrays, numeric vectors, or strings:

```
# Over an array (range returns an array)
for (var i in range(0, 5)) {
    print i
}

# Over a numeric vector
for (var x in linspace(0, 1, 5)) {
    print x
}

# Over a string (yields one character per iteration)
for (var ch in "hello") {
    print ch
}
```

The loop variable is declared with `var`; it is visible within the loop body. `break` works inside `for`/`in`.

> **Note:** `range(lo, hi)` produces an *array*, while `linspace(lo, hi, n)` produces a *vector*. Use `range` for integer loops, `linspace` for mathematical sequences.

4.4 Return

`return expression` exits the current proc and passes the value to the caller. A proc that falls off the end without `return` returns `0`.

5 Procedures

5.1 Named procedures

```
proc name (param1, param2, ...) {
    var local = ...
    return value
}
```

Named procs are stored in a global proc table and are available everywhere after their declaration. Parameters are local variables; modifications to parameter *vectors* do not affect the caller (value semantics). Modifications to parameter *arrays do* affect the caller (reference semantics).

5.2 Anonymous proc literals

```
var f = proc (x) { return x * x }
print f(5)          # 25
print type(f)       # proc
```

Anonymous procs can be stored in variables, passed to other procs, and stored in arrays. They are first-class values.

5.3 Calling procs by value

When a variable holds a proc, calling it uses the same `name(args)` syntax:

```
var transforms = [
    proc (x) { return x + 1 },
    proc (x) { return x * 2 }
]
print transforms[0](5)    # 6
print transforms[1](5)    # 10
```

5.4 Higher-order patterns

```
proc map (a, f) {
    var out = []
    for (var x in a) { push(out, f(x)) }
    return out
}
var doubled = map([1,2,3,4], proc(x){ return x*2 })
```

The stdlib provides `map`, `filter`, and `reduce`. The `apply(f, args)` builtin calls a proc value or a named proc with an array of arguments.

5.5 Recursion

Recursive calls work normally; there is no tail-call optimisation, so very deep recursion will exhaust the C++ call stack.

```
proc fib (n) {
    if (n <= 1) { return n }
    return fib(n-1) + fib(n-2)
}
```

6 Vectors — Numeric Arrays

6.1 Creation

```
var v = vec(1, 2, 3, 4, 5)          # from scalar arguments
var w = linspace(0, PI, 512)        # 512 points, 0 to PI inclusive
var z = zeros(1024)                  # 1024 zeros
var o = ones(256)                    # 256 ones
```

6.2 Element-wise arithmetic

```
var v = vec(1, 2, 3)
print v + 10            # <11 12 13>
print v * v             # <1 4 9>
print -v                # <-1 -2 -3>
print pow(v, 2)         # <1 4 9>  (element-wise power)
```

6.3 Math functions (all element-wise)

`floor`, `ceil`, `abs`, `sqrt`, `sin`, `cos`, `tan`, `exp`, `log`, `log2` accept a single vector argument. `pow(v, e)` and `atan2(y, x)` accept two vector arguments (with broadcast).

```
var phase = linspace(0, TAU, 512)
var wave  = sin(phase)              # one call, 512 sine values
var env   = linspace(1, 0, 512)     # linear fade
var faded = wave * env              # element-wise product
```

6.4 Reductions

```
var v = vec(1, 2, 3, 4, 5)
print sum(v)          # 15
print all(v > 0)      # 1
print any(v > 4)      # 1
print len(v)          # 5
```

6.5 Indexing

Negative indices count from the end (`-1` is the last element).

```
var v = vec(10, 20, 30)
print v[0]      # 10
print v[-1]     # 30
v[1] = 99
print v         # <10 99 30>
```

6.6 Iteration

```
var total = 0
for (var x in vec(1, 2, 3, 4, 5)) {
    total = total + x
}
```

6.7 Conversion

`to_arr(v)` converts a vector to an array of numbers. `to_vec(a)` converts an array of numbers to a vector (fails if any element is non-numeric).

7 Arrays — Heterogeneous Lists

7.1 Creation

```
var a = [1, "two", [3, 4]]       # literal
var b = arr(5)                    # [0, 0, 0, 0, 0]
var c = arr(3, "x")               # ["x", "x", "x"]
var d = range(0, 5)               # [0, 1, 2, 3, 4]
var e = split("a,b,c", ",")       # ["a", "b", "c"]
```

7.2 Indexing and assignment

```
print a[0]           # first element
print a[-1]          # last element
a[1] = "TWO"         # mutates in place (visible through all aliases)

var matrix = [[1,2,3],[4,5,6]]
```

```
print matrix[1][2]   # 6
matrix[1][2] = 99    # nested assignment
```

7.3 Mutation

All mutation functions modify the array in place. Because arrays have reference semantics, mutations are visible through all aliases.

```
var a = [1, 2, 3]
push(a, 4)            # [1, 2, 3, 4]
push(a, 5, 6)         # variadic: [1, 2, 3, 4, 5, 6]
var x = pop(a)        # removes and returns 6
insert(a, 2, 99)      # insert before index 2: [1, 2, 99, 3, 4, 5]
var r = remove(a, 0)  # removes index 0, returns 1
```

7.4 Non-mutating operations

These return new arrays; the original is unchanged.

```
var s = slice(a, 1, 4)        # elements [1, 4)
var c = concat(a, b)          # all elements of a then b
var cp = copy(a)              # shallow copy
var sh = shuffle(a)           # randomly shuffled copy
```

7.5 Reference semantics and copy

```
var x = [1, 2, 3]
var y = x                # y aliases x
y[0] = 99
print x[0]               # shared mutation

var z = copy(x)          # break sharing
z[0] = 0
print x[0]               # x unaffected
```

Warning: Arrays passed to procs are passed by reference. A proc that calls `push`, `pop`, `insert`, or `remove` on a parameter will modify the caller's array. Call `copy(a)` inside the proc if you need a local version.

8 Strings

Strings are immutable value types. The `+` operator concatenates; if either operand is a number it is converted to string first.

```
var s = "Hello, " + "Moon!"
var t = "score: " + 99         # "score: 99"
print len(s)                   # 12
print upper(s)                 # "HELLO, MOON!"
print sub(s, 0, 5)             # "Hello"
print find(s, ",")             # 5
```

Strings can be iterated character by character with `for/in`.

9 File I/O and Modules

9.1 File I/O

```
write("/tmp/out.txt", "line one\nline two\n")     # create or overwrite
append("/tmp/out.txt", "line three\n")            # add to end
var content = read("/tmp/out.txt")                # whole file as string
```

9.2 Loading modules

```
load("stdlib.moon")           # search current dir, then ~/.moon/
load("/abs/path/lib.moon")    # absolute path
```

All procs and variables defined in the loaded file become globally available in the calling environment. Files are executed sequentially; circular loads will loop indefinitely.

9.3 Eval and exec

```
eval("var x = " + str(42))    # parse and execute a string as Moon code
eval("proc cube(n){ return n*n*n }")

var rc = exec("ls -l /tmp")   # run a shell command; returns exit code
```

10 Built-in Functions Reference

All built-in functions are always available without loading any library. Functions marked **[vec]** operate element-wise on vectors. Functions marked **[arr]** require an array argument.

10.1 Math

Function	Signature	Description
`floor` [vec]	`floor(x)`	Largest integer $\leq x$.
`ceil` [vec]	`ceil(x)`	Smallest integer $\geq x$.
`abs` [vec]	`abs(x)`	Absolute value.
`sqrt` [vec]	`sqrt(x)`	Square root.
`sin` [vec]	`sin(x)`	Sine (radians).
`cos` [vec]	`cos(x)`	Cosine (radians).
`tan` [vec]	`tan(x)`	Tangent (radians).
`exp` [vec]	`exp(x)`	e^x.
`log` [vec]	`log(x)`	Natural logarithm.
`log2` [vec]	`log2(x)`	Base-2 logarithm.
`pow` [vec]	`pow(base, exp)`	$\texttt{base}^{\texttt{exp}}$, element-wise with broadcast.
`atan2` [vec]	`atan2(y, x)`	Four-quadrant arctangent, element-wise.
`rand`	`rand()`	Pseudo-random number in $[0, 1)$.

10.2 Vector constructors and reductions

Function	Signature	Description
`vec`	`vec(a, b, ...)`	Create a vector from scalar arguments.
`linspace`	`linspace(lo, hi, n)`	n evenly-spaced values in [`lo`, `hi`] inclusive.
`zeros`	`zeros(n)`	Vector of n zeros.
`ones`	`ones(n)`	Vector of n ones.
`sum`	`sum(v)`	Sum of all elements (vectors only; use `total` for arrays).
`all`	`all(v)`	Returns 1 if every element is non-zero.
`any`	`any(v)`	Returns 1 if any element is non-zero.
`to_arr`	`to_arr(v)`	Convert vector to array of numbers.
`to_vec`	`to_vec(a)`	Convert array of numbers to vector.

10.3 String builtins

Function	Signature	Description
`len`	`len(x)`	Length of string, array, or vector.
`sub`	`sub(s, lo, hi)`	Substring `s[lo..hi)`.
`find`	`find(s, pattern)`	First occurrence of `pattern` in `s`, or -1.
`upper`	`upper(s)`	Uppercase copy.
`lower`	`lower(s)`	Lowercase copy.
`str`	`str(x)`	Convert any value to its string representation.
`num`	`num(s)`	Parse string to number.
`char`	`char(n)`	Character with ASCII code n.
`asc`	`asc(s)`	ASCII code of first character of `s`.
`split`	`split(s, delim)`	Split string on delimiter; returns array of strings.

10.4 Array builtins

Function	Signature	Description
`arr`	`arr()`	Empty array.
	`arr(n)`	Array of n zeros.
	`arr(n, val)`	Array of n copies of `val`.
`len`	`len(a)`	Number of elements.
`push`	`push(a, v1, v2, ...)`	Append one or more values; mutates in place. Returns `a`.
`pop`	`pop(a)`	Remove and return last element; mutates.
`insert`	`insert(a, i, val)`	Insert `val` before index `i`; mutates. Returns `a`.
`remove`	`remove(a, i)`	Remove element at index `i`; mutates. Returns removed element.
`slice`	`slice(a, lo, hi)`	New array with elements `[lo, hi)`.
`concat`	`concat(a, b)`	New array with all elements of `a` then `b`.
`copy`	`copy(a)`	Shallow copy; breaks reference sharing.
`range`	`range(lo, hi)`	Array of integers [`lo`, `hi`).

Function	Signature	Description
	`range(lo, hi, step)`	With custom step; negative step goes downward.
`shuffle`	`shuffle(a)`	New randomly shuffled copy. Original unchanged.
`join`	`join(a, sep)`	Concatenate elements as strings with separator. Returns string.
`keys`	`keys()`	Array of all current global variable names (debugging).

10.5 Type and conversion

Function	Signature	Description
`type`	`type(x)`	Returns `"number"`, `"vector"`, `"string"`, `"array"`, or `"proc"`.
`str`	`str(x)`	Any value to string. Vectors print as `<1 2 3>`.
`num`	`num(s)`	String to number.
`char`	`char(n)`	ASCII code to single-character string.
`asc`	`asc(s)`	First character to ASCII code.

10.6 File I/O and modules

Function	Signature	Description
`read`	`read(path)`	Read entire file; returns string.
`write`	`write(path, text)`	Write string to file (create or overwrite).
`append`	`append(path, text)`	Append string to file.
`load`	`load(path)`	Execute `.moon` file in current environment.
`eval`	`eval(code)`	Execute string as Moon source code.
`exec`	`exec(cmd)`	Run shell command. Returns exit code.

10.7 Higher-order and control

Function	Signature	Description
`apply`	`apply(f, args)`	Call proc value `f` or proc named `f` (string) with array `args`.
`input`	`input()`	Read one line from stdin.
	`input(prompt)`	Print prompt, then read one line.
`clock`	`clock()`	CPU time in seconds (useful for benchmarking).
`exit`	`exit(code)`	Terminate interpreter with exit code.
`assert`	`assert(cond)`	Throw error if `cond` is falsy.
	`assert(cond, msg)`	Throw error with message.

11 Standard Library Reference

Load with `load("stdlib.moon")` (the file must be present in the local folder, or installed in `~/.moon/`).

11.1 Constants

Name	Value	Description
`PI`	3.14159265358979	π
`TAU`	6.28318530717959	2π
`E`	2.71828182845905	Euler's number e
`PHI`	1.61803398874989	Golden ratio φ
`LN2`	0.693147180559945	$\ln 2$
`SQRT2`	1.41421356237310	$\sqrt{2}$

11.2 Core math

Function	Signature	Description
`min`	`min(a, b)`	Smaller of two scalars.
`max`	`max(a, b)`	Larger of two scalars.
`clamp`	`clamp(x, lo, hi)`	Clamp x to [`lo`, `hi`]. Works on scalars and vectors (via broadcast).
`sign`	`sign(x)`	-1, 0, or 1.
`round`	`round(x)`	Round to nearest integer (half up).
`round_to`	`round_to(x, decimals)`	Round to d decimal places.
`mod`	`mod(a, b)`	Modulo, always non-negative: `mod(-1, 5) = 4`.
`even`	`even(n)`	1 if n is even.
`odd`	`odd(n)`	1 if n is odd.
`between`	`between(x, lo, hi)`	1 if `lo` $\leq x \leq$ `hi`.
`hypot`	`hypot(a, b)`	$\sqrt{a^2 + b^2}$.
`gcd`	`gcd(a, b)`	Greatest common divisor (integers).
`lcm`	`lcm(a, b)`	Least common multiple.
`ipow`	`ipow(base, exp)`	Integer power (`exp` ≥ 0).
`lerp`	`lerp(a, b, t)`	Linear interpolation. Works on scalars and vectors.
`map_range`	`map_range(x,il,ih,ol,oh)`	Re-map from one range to another.
`deg2rad`	`deg2rad(d)`	Degrees to radians.
`rad2deg`	`rad2deg(r)`	Radians to degrees.

11.3 Number formatting

Function	Signature	Description
`pad_left`	`pad_left(s, w, ch)`	Pad string on left to width w with character `ch`.
`pad_right`	`pad_right(s, w, ch)`	Pad string on right to width w.

Function	Signature	Description
`fmt_fixed`	`fmt_fixed(x, d)`	Format number with exactly d decimal places.
`fmt_pct`	`fmt_pct(x, d)`	Format as percentage: `fmt_pct(0.752, 1)` → `"75.2%"`.

11.4 String utilities

Function	Signature	Description
`starts_with`	`starts_with(s, prefix)`	1 if `s` starts with `prefix`.
`ends_with`	`ends_with(s, suffix)`	1 if `s` ends with `suffix`.
`ltrim`	`ltrim(s)`	Remove leading spaces.
`rtrim`	`rtrim(s)`	Remove trailing spaces.
`trim`	`trim(s)`	Remove leading and trailing spaces.
`repeat_str`	`repeat_str(s, n)`	Repeat string n times.
`count_str`	`count_str(s, pattern)`	Count non-overlapping occurrences of `pattern`.
`replace`	`replace(s, old, new)`	Replace all occurrences of `old` with `new`.

11.5 Vector statistics

These functions apply to *vectors*. `mean` and `stdev` also accept arrays (via internal dispatch on `type`).

Function	Signature	Description
`mean`	`mean(x)`	Arithmetic mean. Accepts vector or numeric array.
`stdev`	`stdev(x)`	Population standard deviation. Accepts vector or numeric array.
`normalize`	`normalize(v)`	Scale vector to $[0, 1]$ (min becomes 0, max becomes 1).
`dot`	`dot(a, b)`	Dot product of two vectors: $\sum a_i b_i$.

11.6 Array algorithms

Function	Signature	Description
`total`	`total(a)`	Sum of all numeric elements in array. (Note: use `sum` for vectors.)
`minimum`	`minimum(a)`	Smallest element. (Note: `min(a,b)` compares two scalars.)
`maximum`	`maximum(a)`	Largest element.
`contains`	`contains(a, val)`	1 if `val` is in array.
`index_of`	`index_of(a, val)`	First index of `val`, or -1.
`reversed`	`reversed(a)`	New array in reversed order. Original unchanged.

Function	Signature	Description
`sorted`	`sorted(a)`	New array sorted ascending (numeric). Original unchanged.
`zip`	`zip(a, b)`	Pair elements: `zip([1,2],["a","b"])` → `[[1,"a"],[2,"b"]]`. Stops at shorter.
`flatten`	`flatten(a)`	Collapse one level of nesting.

11.7 Higher-order functions

Function	Signature	Description
`map`	`map(a, f)`	Apply proc `f` to each element; return new array.
`filter`	`filter(a, pred)`	Keep elements for which `pred(x)` is truthy.
`reduce`	`reduce(a, f, init)`	Fold: `acc = f(acc, x)` for each element, starting from `init`.

```
var doubled = map([1,2,3,4], proc(x){ return x * 2 })    # [2,4,6,8]
var evens   = filter([1..8], proc(x){ return mod(x,2)==0 })
var total3  = reduce([1,2,3,4,5], proc(a,x){ return a+x }, 0)    # 15
```

11.8 Testing framework

Function	Signature	Description
`assert`	`assert(cond, msg)`	Fail with message if `cond` is falsy.
`assert_eq`	`assert_eq(a, b, msg)`	Fail if `a != b`, showing both values.
`assert_near`	`assert_near(a,b,eps,msg)`	Fail if $\lvert a - b\rvert > \varepsilon$. Use for floating-point tests.
`test_summary`	`test_summary()`	Print pass/fail counts.

Global counters `_tests_run`, `_tests_passed`, and `_tests_failed` are maintained automatically.

12 Extending Moon from C++

Moon is designed to be embedded. Any C++ application can register custom builtins that become callable from Moon scripts.

12.1 Including Moon

```
#include "moon.h"

int main() {
    Environment env;
    env.exec("print \"hello\"", "script.moon");
}
```

12.2 Registering a builtin

A builtin has the signature: `Value(std::vector<Value>&, Interpreter&)`.

```
env.register_builtin("midi_to_hz", [](std::vector<Value>& args,
    Interpreter& I) -> Value {
     double midi = std::get<NumVal>(args[0])[0];
     return NumVal{440.0 * std::pow(2.0, (midi - 69.0) / 12.0)};
});
```

After this call, `midi_to_hz(69)` is available in all Moon scripts run through `env`.

12.3 Injecting global variables

```
env.globals["SAMPLE_RATE"] = NumVal{48000.0};
env.globals["SOL_PATH"]    = std::string{"/opt/sol/samples"};
```

12.4 Value types in C++

Moon type	C++ type	Access
number / vector	`NumVal` = `std::valarray<double>`	`std::get<NumVal>(v)`
string	`std::string`	`std::get<std::string>(v)`
array	`ArrayPtr` = `shared_ptr<MoonArray>`	`std::get<ArrayPtr>(v)`
proc	`ProcVal` = `shared_ptr<Proc>`	`std::get<ProcVal>(v)`

Use `std::holds_alternative<T>(v)` to test the type before accessing. Throw `Error{filename, line, message, {}}` for runtime errors from builtins.

13 Quick Reference

Language grammar summary

```
statement  ::= var name = expr
             | name = expr
             | name[expr] = expr
             | proc name (params) { stmts }
             | if (expr) { stmts } (else if (expr) { stmts })* (else
               { stmts })?
             | while (expr) { stmts }
             | for (var name in expr) { stmts }
             | return expr
             | break
             | print expr*
             | call

expr       ::= or_expr (< > <= >= == != or_expr)*
or_expr    ::= and_expr (or and_expr)*
and_expr   ::= not_expr (and not_expr)*
not_expr   ::= not not_expr | comparison
comparison ::= add ((< > <= >= == !=) add)*
add        ::= mul ((+ -) mul)*
mul        ::= unary ((* /) unary)*
unary      ::= - unary | atom ([expr])* ((args))?
atom       ::= number | string | [exprs] | (expr) | name | proc(
    params){stmts}
```

Common patterns

```
# Integer loop
for (var i in range(0, 10)) { print i }

# Numeric vector operation
var wave = sin(linspace(0, TAU, 512))

# Map over array
var doubled = map(data, proc(x){ return x * 2 })

# Sort and get min/max
var s = sorted(data)
print s[0]       # minimum
print s[-1]      # maximum

# Convert array to vector for math
var v = to_vec(numeric_array)
print mean(v) "  std=" stdev(v)

# Filter and reduce
var positives = filter(data, proc(x){ return x > 0 })
var total4    = reduce(positives, proc(a,x){ return a+x }, 0)
```

Licensing

The Moon language is released under the BSD 2-Clause license.