



Musil

Scripting Language for Sound And Music Computing

User Manual version 0.9.0

Musil is a small scripting language for sound and music computing: Scheme underneath, Tcl on the surface. Numbers are vectors, functions are values, code is data. The language is one C++ header with no dependencies; the libraries add the operating system, linear algebra and machine learning, signal processing, real-time sound and plotting, and the IDE puts all of it in a window.

Contents

1	Overview	2
1.1	Two ways to run Musil	2
1.2	Building and installing	2
1.3	Getting help	2
2	The language	3
2.1	Reading a program	3
2.2	Values	3
2.3	Variables: <code>var</code> and <code>set</code>	4
2.4	Control flow	4
2.5	Functions	4
2.6	Infix arithmetic: <code>expr</code>	5
2.7	Errors	5
2.8	Code as data	6
2.9	Loading files	6
2.10	Sharing and copying	6
3	The IDE	6
4	Tutorial	7
4.1	The language	7
4.2	Files and input	9
4.3	The standard library	9
4.4	Signals	10
4.5	Scientific	11
4.6	Live	11
4.7	Music	12
5	Programming practices	13
5.1	The shape of a program	13
5.2	Vectors first	14
5.3	Rules of thumb	14
5.4	Adding a library	15
5.5	Style at a glance	16
6	Libraries	16
6.1	core	16
6.2	std	20
6.3	system	26
6.4	scientific	29
6.5	signals	34
6.6	live	46
6.7	music	56
6.8	plot	81
7	Extending Musil from C++	84
8	Examples	84

1 Overview

Musil is a programming language for people who make music with computation: composers, researchers and students. It is deliberately small. The core language fits in one C++ file of under a thousand lines, and every feature described in this manual, from convolution to live coding to orchestral scores, is reached from that core by loading a library written partly in C++ and partly in Musil itself. Three commitments shape the design:

- **Numbers are vectors.** A scalar is a vector of size one; `(+ v 10)` adds ten to every element; `(sin v)` is elementwise. Signal processing and numerical work are written as arithmetic, and run at C++ speed.
- **Functions are values.** They are created anywhere, stored in lists, passed to `map`, applied to too few arguments to make partial applications, and called in tail position without growing the stack.
- **Code is data.** A program is a list; `'(+ 1 2)` is a list you can build, inspect and `eval`.

What makes it comfortable to use is the surface: each line is a command, so `print "x ="x` needs no parentheses around it; `( )` encloses a list or a nested call; `{ }` encloses a block of lines; and `(expr (a + b * 2))` gives you infix arithmetic when a formula reads better that way. If you know a Lisp you will find the evaluation rule familiar; if you know a shell, the command lines.

1.1 Two ways to run Musil

The command line. `musil file.mu` runs a file; `musil` alone is a REPL; `musil a.mu b.mu - x y` runs several files in one interpreter with `args` bound to `(x y)`; `musil -e "print 42"` evaluates a string.

The IDE. *Musil* the application is an editor with syntax colouring where Cmd-Enter runs the block under the cursor, a console with an input line, the list of your variables, a documentation search, and plots and controls in windows of their own. It runs the same interpreter. See section 3.

1.2 Building and installing

```
cmake -B build -DCMAKE_BUILD_TYPE=Release
cmake --build build
ctest --test-dir build           # every library has a test and a
                                # reference
cmake --install build           # musil -> /usr/local/bin, *.mu and
                                # help.txt -> ~/.musil
./deploy_macos.sh               # macOS: dist/Musil.app
```

The build fetches FLTK 1.4, the one external dependency, used by the plot library, the controls window and the IDE; `-DMUSIL_FLTK=OFF` builds everything else with no dependency at all. Libraries are found by `load` in `~/.musil` after installing, in any directory listed in the `MUSIL_PATH` environment variable, or next to the file that loads them; during development `MUSIL_PATH=src` points at the source tree.

1.3 Getting help

`(help name)` prints the signature and description of any builtin or library function, taken from the same comments this manual is generated from:

```
> help range
```

```
(range n) (range a b) (range a b step)
a vector of evenly spaced numbers, end excluded
```

The files `examples/reference_*.mu` are runnable tours of the core and of each library; `examples/reference.mu` is the best place to start.

2 The language

2.1 Reading a program

A program is a sequence of lines. Each line is a command: its first word is a function and the rest are its arguments.

```
print "hello"           # (print "hello")
var x 10                # (var x 10)
print "x + 1 =" (+ x 1) # a parenthesised form is a
    sub-expression
```

Inside parentheses, newlines are ordinary whitespace, so a long call can span lines. Braces group lines into a block, which is what `if`, `while` and function bodies take:

```
if (> x 5) {
    print "big"
    var y (* x 2)
}
```

A line holding a single parenthesised form is that form; a line holding a single literal is that value; a line holding a single *symbol* calls it (`ctr` calls the function `ctr`, as in Tcl). A comment runs from `#` to the end of the line; a backslash at the end of a line continues it, and so does **indentation**: at the top level, a line that starts with spaces continues the command above it, which is how a function's body goes on the next line:

```
function lead (gate freq cutoff)
    (pan (* (adsr sr gate 0.01 0.2 0.5 0.4) (lowpass (osc sr freq
        saw-table) sr cutoff 2)) 0)
```

Inside `{ }` lines are separate commands whatever their indentation. `'x` is short for `(quote x)`.

2.2 Values

Type	Literal or constructor	(type x)
number, vector	42, 3.14, (vec 1 2 3), (range 8)	scalar, vec
string	"text\n"	string
symbol	'name, (sym "name")	symbol
list	(list 1 "two" (vec 3 4))	list
function	(function (x) (* x x))	function
nil	nil	nil

All numbers are IEEE double vectors; there is no integer type, and `floor`, `round` and `mod` do integer work. A scalar is a vector of size one, so every arithmetic and math builtin is elementwise, with size-one broadcasting:

```
var v (vec 1 2 3)
(+ v 10)           # (11 12 13)
(* v v)            # (1 4 9)
(sin (/ (range 8) 8)) # elementwise
(+ (vec 1 2) (vec 1 2 3)) # error: +: size mismatch (2 vs 3)
```

Lists hold anything, including other lists and vectors; that is also how matrices (a list of row vectors) and spectra ((`list re im`)) are represented. Strings are immutable; `getidx` on a string gives a one-character string.

Truth: everything is true except 0, `nil`, an empty string, an empty list, and a vector with a zero in it. Comparisons return 1 or 0, elementwise on vectors; `==` and `equal?` compare structure on non-numbers, and `<` orders two strings lexicographically. Constants: `nil`, `true`, `false`, `pi`, `inf`, `version`.

2.3 Variables: `var` and `set`

`var` defines a variable in the *current* environment: at top level a global, inside a function a local of that call. It never touches a variable of the same name further out, so a library's locals cannot clobber yours. `set` assigns to the nearest existing variable, however far out, and is an error if there is none.

```
var counter 0
function bump () (set counter (+ counter 1))
function shadow () {
  var counter 99          # a different, local counter
  return counter
}
bump
print counter (shadow) counter    # 1 99 1
```

Blocks (`{ }`, loop bodies, `if` branches) do not open a scope: a `var` in a `while` body inside a function is the function's local.

2.4 Control flow

```
if (< x 0) { print "negative" } { print "not negative" } #
  then-block, optional else-block
while (< i 10) { var i (+ i 1) }
for (var k 0) (< k 10) (var k (+ k 1)) { print k }      # init,
  condition, step, body
if (== k 7) { break }                                # break and continue are calls, so inside
  a block or in parens
```

There is no `else if`; a chain of `ifs` with early `returns` reads the same way inside a function. `do` evaluates forms in order and returns the last; it is what a block is.

2.5 Functions

```
function square (n) (* n n)          # named, one-expression body
function fact (n) {                  # block body; return leaves early
  if (< n 2) { return 1 }
  return (* n (fact (- n 1)))
}
var inc (function (n) (+ n 1))      # anonymous function in a
  variable
```

```
(map (vec 1 2 3) square)           # functions are values
```

Closures capture the environment they were created in; a stateful closure updates a captured variable with `set`:

```
function make-counter () {
  var c 0
  return (function () { set c (+ c 1) })
}
var ctr (make-counter)
ctr           # 1
print (ctr)   # 2
```

Currying. A function called with fewer arguments than it takes returns a partial application; with more, the result is applied to the rest:

```
function add3 (a b c) (+ a b c)
var add1 (add3 1)
(add1 2 3)           # 6
(map (vec 1 2 3) (add3 10 100))   # (111 112 113)
function twice (f) (function (x) (f (f x)))
(twice inc 5)        # 7: (twice inc) applied to 5
```

Warning: Because of currying, calling a library function with one argument too few returns a function instead of failing: `(mat-str M)` is a partial application, not a string. Functions have no optional arguments for this reason; where a default makes sense there are two functions (`dist` and `dist-p`, `mat-print` and `mat-print-with`). Builtins do check their arity.

Tail calls run in constant space: a recursive function whose recursive call is the last thing it does can loop a million times. An early `return` inside a block is rewritten to a tail call at definition time, so the natural style costs nothing; only a `return` from inside a loop unwinds.

2.6 Infix arithmetic: `expr`

```
(expr (x + y * 2))           # precedence as usual: 16 for x
  =10, y=3
(expr ((x + y) * 2))         # parentheses group
(expr ((sqrt x) + 1))       # a form without an operator in
  second position is a call
(expr (a > 1 && b < 2))      # comparisons and logic: < > <= >
  = == != && ||
```

2.7 Errors

```
var r (try (num "abc") catch e (concat "caught: " e))
error "negative not allowed: " n      # raise; the arguments become the
  message
assert (== (+ 2 2) 4) "arithmetic"   # std: stop unless true
```

Every error carries the file, the line and the call stack, innermost first:

```
reference.mu:426: from inner
1> inner() at reference.mu:428
2> outer() at reference.mu:431
```

Builtins check the number and types of their arguments (`sqrt:` expected 1 argument, got 0; `+`: expected number, got string). Deep recursion stops with `stack overflow` rather than crashing.

2.8 Code as data

```
var code '(+ 1 2)           # a list, not a call
(eval code)                 # 3
(eval (list '* 2 (+ 1 2)))  # code built at run time: 6
(apply add3 (list 1 2 3))   # a list spread as arguments
(eval (parse "var z (* 6 7)")) # text read into a form, then
    evaluated: a REPL in two calls
```

`examples/bootstrap.mu` takes this to its end: an evaluator for the language, written in the language in eighty lines (`environments`, `closures`, `if`, `var`, `set`, `return`, `while`), with a prompt at which every line is read by the host and evaluated by it.

2.9 Loading files

`(load "file.mu")` runs a file once in the global environment. A relative name is searched next to the loading file, in the current directory, in each entry of `MUSIL_PATH`, then in `~/musil`. Reading functions (`read`, `read-wav`, `read-csv`, `exists?`, `stat`) apply a similar rule to their data: a relative path that does not exist in the current directory is looked for next to the file being run, so a script finds its data from wherever it was started, on the command line or from the IDE. A file that ran is not run again (so mutual loads are safe); a file that failed is not cached. Nothing is loaded automatically: a program that wants the standard library says `load "std.mu"`; each library loads what it needs (`signals.mu` loads `scientific.mu`, which loads `std.mu`).

2.10 Sharing and copying

Lists and vectors are shared by reference: `(var alias orig)` makes two names for one object, and `push` or `setidx` through either is visible through both. `(copy x)` makes a new list or vector with the same elements (a shallow copy). Strings and numbers behave as values.

3 The IDE

Musil the application is the interpreter with an editor around it.

- **Editor** (top left): `.mu` files with syntax colouring (keywords, the documented builtins, strings, numbers, comments). **Cmd-Enter** runs the block around the cursor (the lines between blank lines) or the selection; **Cmd-Shift-Enter** the whole file; **Cmd-Alt-Enter** the current line. The lines sent flash. A toolbar has Run file, Run block, Run line, Stop, Clear, Controls and Settings. Undo, find (`Cmd-F`, `Cmd-G`), comment/uncomment (`Cmd-/`), text size (`Cmd+`, `Cmd-`, for every panel), go to line (`Cmd-L`), clear the console (`Cmd-K`), files by drag and drop; Settings (`Cmd-,`) chooses the font (one fixed-width font for everything, colours only mark syntax), the size, line numbers, the current-line highlight, the margin guide and the evaluation port (0 turns it off), and remembers them.
- **Console** (bottom left): everything printed, and a line to type Musil into: Enter runs it, Up/Down recall history, Tab completes a name. Esc or `Cmd-.` stops a running program (the interpreter checks at safe points, so the session survives).
- **Variables** (top right): the globals with a preview of their values, coloured by kind (numbers, strings, lists, functions); double-click prints one.

- **Help** (bottom right): type a name or a word to search the documentation of every function. (manual) or the Help menu opens this PDF; Help → Examples copies any bundled example into an untitled buffer (the original stays untouched; its data is still found), to run and edit.
- **Plots and controls** open in windows of their own, from the IDE exactly as from the command line; several plots can be open at once.
- **From another editor**: the IDE listens on port 7770; code sent from VS Code (the extension in `editors/vscode/musil`) or from `nc` is evaluated in the same session.

The interpreter runs on its own thread; the window stays responsive while a program runs. Libraries are found inside the app bundle, so nothing needs to be installed. On macOS, `./deploy_macos.sh` builds `dist/Musil.app`.

4 Tutorial

This chapter teaches Musil from nothing, by doing. Every fragment in it can be typed into the IDE's console, sent from the editor with `Cmd-Enter`, or saved and run with `musil file.mu`; all of them were run as written. Chapter 2 is the precise account of the syntax and the evaluation rule, chapter 5 the style that experience has shown to work, and chapter 6 the reference of every function; at the console, `(help name)` prints a function's entry.

4.1 The language

Commands and expressions. A program is a list of commands, one per line. A command is a name followed by its arguments; parentheses are only needed to nest a call inside another.

```
print "hello"           # a command: the function print with one
                        argument
print (+ 1 2) (* 3 4)    # two nested calls: prints 3 12
var x 10                 # a variable
print (* x 2)
```

Inside parentheses the operator comes first, Lisp-style: `(+ 1 2)`, `(< x 5)`, `(max 3 7)`. Comments start with `#`.

Values. Numbers are vectors: a scalar is a vector of length one, and arithmetic works on whole vectors at once, element by element, a scalar spreading over a vector.

```
var v (vec 1 2 3)        # a vector
print (* v 2)            # (2 4 6)
print (+ v (vec 10 20 30)) # (11 22 33)
print (sum v) (mean v) (max v) (length v)
print (range 5)          # (0 1 2 3 4)
print (getidx v 1)       # 2: indices start at 0
print (take v 2) (drop v 1) # (1 2) (2 3)
```

Strings are in double quotes; `concat` joins, `str` converts to text, `num` back to a number. Symbols are names used as values, written with a quote: `'mf`, `'freq`; they name keys, kinds and parameters. Lists hold anything, in order: `(list 1 "two" 'three (vec 4 5))`; `head`, `last`, `getidx`, `length`, `push` work on them. `nil` is the absence of a value; the truth values are 1 and 0, and `type` tells what something is.

Functions. `function` name (parameters)body, the body one expression, or several in braces with `return`.

```
function square (x) (* x x)
function rms-db (x) (amp->db (rms x))

function clamp (x lo hi) {
  if (< x lo) { return lo }
  if (> x hi) { return hi }
  return x
}
print (square 4) (clamp 12 0 10)
```

A function's body may also start on the next line, indented. Functions are values: you can pass them, return them, keep them in lists. `(function (x)(* x x))` is one without a name. Giving fewer arguments than parameters gives back a function waiting for the rest (currying), so a function has one arity: there are no optional arguments.

Flow. `if` takes a condition, a then-branch and an optional else-branch; `and/or` short-circuit; `while` and `for` loop, with `break` and `continue`.

```
if (> x 5) { print "big" } { print "small" }
for (var k 0) (< k 3) (var k (+ k 1)) { print k }
var n 0
while (< n 100) { set n (* 2 (+ n 1)) }
```

`var` declares, `set` changes an existing variable (also one of an enclosing scope, from inside a function). The everyday loop, though, is not `for` but `each`, and most of what looks like a loop is a whole-vector operation:

```
each (list "a" "b" "c") (function (s) (print s))
each (range 3) (function (k) (print k (square k)))
var t (/ (range 44100) 44100) # a second of time, no
    loop
var y (* (exp (* -3 t)) (sin (* tau 440 t))) # a decaying sine, no
    loop
```

map, filter, reduce. They build new collections from old ones and are the functional heart of the language; use them when the function fits on the line.

```
print (map (list 1 2 3) square) # (1 4 9)
print (filter (range 10) odd?) # (1 3 5 7 9)
print (reduce (list 1 2 3 4) + 0) # 10
print (map (list "a" "bb") length) # (1 2)
print (sort-by (list "pear" "fig" "apple") length) # (fig pear
apple)
```

Records. Structured data is a list of (list key value) pairs, made with `record`, read with `get` (an error when absent) or `opt` (a default), changed with `put!`. Keys are symbols. Events, options and database entries are all records.

```
var e (record (list 'pitch 60 'dur 0.5 'amp 0.8))
print (get e 'pitch) (opt e 'pan 0)
put! e 'amp 0.6
print (keys e) (values e)
```

Errors. `error` raises with a message; `try ... catch` handles it.

```
function safe-div (a b) { if (== b 0) { error "safe-div: division by
    zero" }
                          return (/ a b) }
var r (try (safe-div 1 0) catch err (concat "caught: " err))
print r
```

Code as data. `'(+ 1 2)` is a list of three elements, `eval` runs a form, `parse` turns text into forms, `apply` calls a function on a list of arguments. Patterns, scores and instruments are data because of this; in ordinary programs you will rarely need it.

4.2 Files and input

```
load "system.mu"
write "/tmp/notes.txt" "a line of text"           # a string, or anything
    printed
var text (read "/tmp/notes.txt")
var rows (read-csv "data/iris.csv")                # a list of rows (
    vectors of numbers)
write-csv "/tmp/out.csv" (list (vec 1 2) (vec 3 4))
var w (read-wav "data/drums.wav")                  # (list sample-rate
    channels)
var sr (head w)
var x (head (getidx w 1))                           # the first channel
write-wav "/tmp/out.wav" sr x                       # 16-bit; 24, 32, "float
    " as a fourth argument
write-wav "/tmp/stereo.wav" sr (list x x)           # a list of channels
print (ls ".") (exists? "/tmp/out.wav")
var answer (input "your name? ")                    # a line from the
    console
```

A relative path is looked for in the current directory, then next to the file being run, then next to the program that was started, so an example in `examples/` reads `data/drums.wav` from anywhere. `load` runs a file once (the libraries, or your own), searching the load path too (`MUSIL_PATH`, `~/musil`, the installed libraries). Nothing is loaded by itself: a program that uses `signals` starts with `load "signals.mu"`, which loads `std` as well.

4.3 The standard library

`std` is loaded by every other library. What you will use daily:

```
load "std.mu"
print (zip (list 1 2) (list "a" "b"))           # ((1 a) (2 b))
print (concat-list (list 1) (list 2 3))         # (1 2 3)
print (unique (list 1 1 2)) (reverse (list 1 2 3)) (sort-list (list 3
1 2))
print (split "a,b,c" ",") (join (list "a" "b") "-") (replace "hello" "
1" "L")
print (starts-with? "musil" "mu") (contains? "musil" "si") (trim " x
")
print (find-first (list 1 4 9) (function (x) (> x 3))) # 4
print (group-by (list 1 2 3 4) odd?)             # ((1 (1 3)) (0 (2 4))
)
print (fixed 3.14159 2) (round 2.5) (floor 2.7) (mod 7 3)
print (rand) (seed 3)                            # random numbers, and
a seed for repeatable ones
```

```
print (clock) (now)                                # seconds since the
    start, and the date
```

Vectors have their own family: `zeros`, `ones`, `vec` (concatenation), `slice`, `argmax`, `cumsum`, `dot`, `norm`, `clip`, `abs`, `sqrt`, `exp`, `log`, `sin` ... all element-wise.

4.4 Signals

Load a sound, look at it, filter it, convolve it, write it.

```
load "signals.mu"
load "plot.mu"
var w (read-wav "data/drums.wav")
var sr (head w)
var x (head (getidx w 1))
print (length x) "samples," (fixed (/ (length x) sr) 2) "s, rms" (
    fixed (rms x) 3)
show (waveform x sr)
var dull (lowpass x sr 800 0.7)                                # a biquad:
    cutoff, Q
var bright (highpass x sr 2000 0.7)
var hall (concerthall x sr 0.7 0.3)                            # the shipped
    concert hall (stereo)
write-wav "/tmp/drums_hall.wav" sr hall
var ir (head (getidx (read-wav "data/Concertgebouw-s.wav") 1))
var wet (conv x (resample-to ir 44100 sr))                    # any
    impulse response, by FFT
```

Synthesis as functions. A sound is a function of time; write it as vector algebra.

```
function tone (sr freq dur)
    (* (sine sr freq dur) (exp (* -4 (/ (range (* sr dur)) sr))))
function fm (sr carrier ratio index dur) {
    var t (/ (range (* sr dur)) sr)
    return (sin (+ (* tau carrier t) (* index (sin (* tau carrier
        ratio t)))))
}
write-wav "/tmp/fm.wav" 44100 (* 0.5 (fm 44100 220 1.5 3 2))
```

The same function can be an instrument for the live engine when it is written with a gate: (`function` (gate freq)(* (adsr sr gate 0.01 0.1 0.5 0.3)(osc sr (sig gate freq)saw-table))) renders offline with `synth-render` and streams with `synth` (section 4.6).

Spectra. `fft` gives real and imaginary parts, `magnitude-spectrum` the magnitudes of the positive frequencies, `stft` the frames of a short-time transform; the descriptors summarise them.

```
var mags (magnitude-spectrum (take x 4096))
var freqs (spectrum-freqs 4096 sr)
print "centroid" (fixed (spectral-centroid mags freqs) 0) "Hz"
show (spectrogram x sr 1024 256)
var frames (stft x 1024 256)                                # complex
    frames, for your own analysis
```

Further. Time stretching keeps the pitch (`pvoc-stretch x 2`), onsets find the attacks (`onsets x sr 1024 256 0.25`), and harmonic/percussive separation splits a recording into its sustained and its struck parts:

```
var parts (hpss x 2048 512 31)
write-wav "/tmp/harmonic.wav" sr (head parts)
write-wav "/tmp/percussive.wav" sr (last parts)
```

`nmf-separate` goes further, into any number of sources; `binaural` and `ambi-encode` place a sound in space. Chapter 6 lists them all.

4.5 Scientific

A matrix is a list of row vectors; the C++ half does the products and decompositions, the Musil half the construction and the statistics.

```
load "scientific.mu"
var A (list->mat (list (list 2 1) (list 1 3)))
var b (vec 3 5)
print (mat-mul A A) (transpose A) (det A) (inv A)
print (solve A b) # A x = b
print (eig-sym A) # eigenvalues
    and vectors of a symmetric matrix
var X (list->mat (list (list 1 2) (list 2 4.1) (list 3 6.2)))
var P (pca X)
print (pca-explained P) # how much
    variance each direction carries
var groups (kmeans X 2)
print (kmeans-labels groups)
var W-H (nmf (mat-map X abs) 1 50) # non-negative
    factorisation
```

In music these are the tools behind feature spaces (a database's spectra as rows: PCA maps them, k-means groups them, `knn` classifies a new sound), behind NMF separation, and behind the regressions of `examples/regression.mu`. `mat-map`, `mat-add`, `hadamard`, `mat-sum` and friends are the element-wise algebra; `cov`, `mat-mean`, `mat-std` the statistics.

4.6 Live

A live session is: open the device, define an instrument, play it, then keep redefining things while the clock runs.

```
load "live.mu"
audio-init # 44100 Hz,
    stereo
var sr (audio-sr)
function pluck (gate freq cutoff)
    (* (adsr sr gate 0.005 0.2 0.3 0.2) (lowpass (osc sr (sig gate
        freq) saw-table) sr cutoff 2))
var p (synth pluck) # compiled
    into the engine
set-param p 'freq 220
set-param p 'cutoff 1500
note p 0.5 # gate on for
    half a second
```


Pitches, rhythms, lines. Pitches are strings ("F#4") or MIDI numbers, nil a rest; a rhythm is a list of durations, negative for a pause. Elements make fragments, lists of (at dur payload), that add! places.

```
var line (list "C4" "F#4" "D4" "G#4" "E4")
var r (rhythm (list 0.5 0.25 0.25 1 -0.5))
add! s 4 (notes db 'Ob 'mf 'ord line r)
add! s 8 (notes db 'Ob 'mf 'ord (invert line "C4") (retrograde r))
add! s 12 (chords db 'Vn 'p 'ord (list (list "C4" "F#4") (list "D4" "G#4")) (rhythm (list 1 1)))
add! s 14 (texture db (list 'Vn 'Vc) 'pp 'ord line (rhythm (list 0.25 0.25 0.5)) (list 1 1.2 1.5))
add! s 18 (pivots db (list 'Ob 'Hn) 'mf 'ord (list "D5" "A3") 3 (rhythm (list 0.5 0.5 1)))
add! s 22 (chordinterp db 'Vn 'p 'ord (list "C4" "E4" "G4") (list "C#4" "F#4" "A#4") (tuplet 6 6))
```

Because fragments and pitches are lists, the language composes them: map a fragment to transpose it (fragment-map), reverse a rhythm, fragment-scale for an augmentation, each to place an ostinato three times, fragment->score to make a section that another score holds as one event. algorithmic_comp.mu and score_in_score.mu go through all of it.

A convention. Pitches are always strings ("A3", "D#5"): a sharp needs one, since # starts a comment in a symbol, and one spelling is better than two. Symbols name things: instruments, dynamics, techniques, keys and parameters ('Vn, 'mf, 'ord, 'freq). Numbers are for computed pitches ((+ 7 60)), and every element accepts them.

5 Programming practices

This chapter is about writing Musil that reads well and runs fast, and about extending the language with a library of your own. The language is a Scheme in its bones (everything is an expression, functions are values, code is data) with a Tcl surface (one command per line, no parentheses around a top-level call). The style that fits it best is *imperative at the top, functional in the small*: a program is a sequence of steps that build and transform vectors and lists, and the functional tools (map, filter, reduce) are used inside those steps where they are shorter than a loop, never as an end in themselves.

5.1 The shape of a program

A program is a list of steps. Name the intermediate results; do not nest what can be sequenced.

```
load "signals.mu"
var w (read-wav "data/drums.wav")
var sr (head w)
var x (head (getidx w 1))
var flux (onset-strength x 1024 256)
var t-on (onsets x sr 1024 256 0.25)
print (length t-on) "onsets:" (fixed t-on 3)
write-wav "/tmp/out.wav" sr (normalize-peak x)
```

- One idea per line. A nesting deeper than three parentheses is asking to be split with a var.
- Top-level calls need no parentheses: print x, write-wav path sr x, audio-init. Parentheses are for calls that are arguments: var y (fixed x 2).

- A function's body goes on the next line, indented: indentation continues a top-level command. Braces for several statements. No backslashes are needed.
- `return` ends a function early; the last expression is the value otherwise. Inside `{ }`, use `return` when the body has steps, so the reader sees where the value comes from.
- `and` and `or` short-circuit, left to right, and return the deciding value, so `(and (> k 0) (getidx v k))` is safe and `(or x default)` reads as it should.

```
function rms-db (x)
  (amp->db (rms x))

function normalise-to (x target) {
  var g (/ target (rms x))
  return (* x g)
}
```

5.2 Vectors first

Numbers are vectors. Anything that can be written as an operation on whole vectors is faster (the loop runs in C++) and shorter than a loop in Musil.

```
var t (/ (range n) sr)                # a time axis
var y (* (exp (* -3 t)) (sin (* tau 440 t))) # a decaying sine,
      no loop
var peak (max (abs y))
var clipped (clip y -0.5 0.5)
```

Broadcasting: a scalar with a vector applies to every element; two vectors must have the same length (a mismatch is an error, on purpose). `vec` concatenates; `slice`, `take`, `drop` cut; `add-at!` adds into a buffer in place; `mix` builds a buffer from placed pieces. Reach for a loop over samples only when each sample depends on the previous one and no builtin does it (`osc`, `lag`, `iir`, `delay`, `comb`, `adsr` are there); such a loop usually belongs in C++ (section 5.4).

5.3 Rules of thumb

The tutorial (chapter 4) shows how loops, records, files and errors work; this is how to choose between them when writing something that will last.

- **Loops.** each for doing something with every element (printing, pushing, writing files); `for` when an index and a step are the point or the loop must stop early; `while` for a condition that is not a count. Prefer `map`, `filter` and `reduce` when the result is a new collection and the function fits on the line; name the function first otherwise.
- **Recursion** is for trees and for algorithms that are recursive by nature (a nested pattern, an evaluator). A tail call costs nothing, but a loop written as a recursive function reads worse than `for` to most people, and a non-tail recursion over a long list will overflow the evaluation depth: use a loop or `reduce`.
- **Building.** Lists grow with `push` or come out of `map`; do not `concat-list` inside a loop over long lists, every call copies. Vectors are preallocated with `zeros` and filled with `add-at!` or `setidx`.
- **Records** are the shape of every option list, event and database entry; keys are symbols, and a string key is a different key, so pick one and keep it. `get` when the key must be there, `opt` when it may not.
- **Symbols and quoting.** `'x` names a thing (a parameter, a kind, a key); quoting a whole form `('(+ 1 2))` and `eval` are for programs that build programs, patterns and instruments, and rarely for anything else.

- **Files.** Relative paths are looked for in the current directory, next to the file being run, then next to the program that was started; examples write into `/tmp/` with a `musil_` prefix so that running them never litters the tree; sample rates travel in a variable and are never hard-coded. Data an example shares lives in `examples/data/`; data a library needs (the HRTFs, the hall) in `src/` next to the `.mu` files.
- **Errors.** Check arguments at the top of a function and fail early with a message that names it: `if (<= n 0){ error "hann: n must be > 0"}`. `error-of` gives a failing thunk's message, which is how tests check errors. A program should be silent when it succeeds and precise when it fails.

5.4 Adding a library

A library is four files plus registration; `signals` is the model.

1. `src/name.h`: the C++ half, for anything needing an element loop, per-sample state, the OS, or a callback. One `inline vptr sig_thing(vlist& a, Interp& i)` per builtin, arguments checked with `i.num`, `i.scalar`, `i.str`, `i.list`, `i.index`, errors with `i.bad("thing: what was wrong")`; then `inline void add_name(Interp& i)` registering them with `i.def("thing", sig_thing, min, max)`. Everything is inline in namespace `musil` (header-only).
2. `src/name.mu`: the Musil half, for anything expressible as vector operations. It starts with `load "std.mu"` (and whatever it builds on). Loading is explicit: a program does `load "name.mu"`.
3. `tests/test_name.mu`: self-checking. `load "test.mu"`, then `check` lines with a message each, then `report "test_name"`. Cover the normal case, an edge (empty, one element), and the errors. Register it in `CMakeLists.txt`.
4. `examples/reference_name.mu`: a tour that prints every function once, in the order a reader would want to meet them; its output is a golden file in `tests/golden/`, refreshed with `tests/golden.cmake -DUPDATE=1` whenever the printed text changes on purpose.

Then `#include "name.h"` and `add_name(i)` in `src/musil.h`; the library in LIBS of `tools/gendoc.py`; `\input{generated/name.tex}` and a paragraph in this manual.

Rules that keep the libraries coherent:

- **Doc comments are the documentation.** `// (thing args)` what it does above a builtin in the `.h`, `# (thing args)` what it does above a function in the `.mu`; several forms on one line share the text; indented continuation lines extend it. `help`, this manual and the VS Code grammar are generated from these; a function without one is a bug.
- **No optional arguments.** Currying makes a missing argument a partial application, so a function has one arity; variants get names (`onsets` / `onsets-adaptive`).
- **Names** are lowercase with hyphens; predicates end in `?`; in-place mutation ends in `!` (`add-at!`, `put!`); a function returning a new value has no mark.
- **Element loops in C++, vector algebra in Musil.** A Musil function that loops over samples is a sign the loop belongs in the `.h`.
- **Offline and streaming are one definition.** A signal function that should also run in a synth takes a state struct in C++ (`osc_run`, `iir_run` ...), is listed in the ugen table in `live.h`, and must satisfy `synth-render` equals the direct call (a test in `test_live.mu`). Constants inside instruments are signals (`(sig gate 190)`), so they work in both executions.
- **Environment variables the tests rely on:** `MUSIL_NOSHOW` (no windows), `MUSIL_NULL_AUDIO` (the silent device). A library that opens windows or devices honours them.
- **The version** is set once, in `src/core.h`; CMake, the deploy scripts, the VS Code extension and this manual read it from there.

Adding a builtin to an existing library is the same, smaller: the function and its doc comment, a `check` in the test, a line in the reference, a regenerated golden; `./build.sh -test` before sending.

5.5 Style at a glance

```
# a comment says why, the code says what
load "live.mu"
audio-init
var sr (audio-sr)

function pluck-note (gate freq)                                # instrument: a
  function of its parameters
  (* (adsr sr gate 0.005 0.1 0.3 0.2) (osc sr (sig gate freq)
    saw-table))

var p (synth pluck-note)                                       # streamed
var buffer (pluck-note (vec (ones 400) (zeros 8000)) 220)     # or
  rendered: the same function

function bassline (cycle)                                     # a pattern: events
  from data
  (melody p "a1 ~ a1 c2" 4 (list))
live-loop 'bassline 4
```

Prefer this to cleverness: named steps, vectors over loops, `each` over recursion, records for structured data, one arity per function, a doc line on every definition.

6 Libraries

A library is a pair of files: `name.h` holds the functions that need C++, an element-by-element loop or the operating system; `name.mu` holds everything that is a composition of vector operations, which runs at the same speed in Musil. The C++ halves are registered when the interpreter starts; the Musil half is loaded with `load "name.mu"`. Each library has a test (`tests/test_name.mu`) and a runnable reference (`examples/reference_name.mu`).

Library	Load	Contents
core	built in	the language, arithmetic, lists, vectors, strings, errors, load
std	<code>load "std.mu"</code>	vector constructors and statistics, sequences, strings, files, map/filter/reduce
system	<code>load "system.mu"</code>	processes, directories, CSV, WAV, UDP/OSC
scientific	<code>load "scientific.mu"</code>	matrices, decompositions, regression, PCA, k-means, KNN
signals	<code>load "signals.mu"</code>	generators, FFT, STFT, phase vocoder, features, filters, reverb
live	<code>load "live.mu"</code>	the audio device, a sample-accurate clock, voices playing buffers and files
plot	<code>load "plot.mu"</code>	figures of lines, points, bars, images and surfaces; windows and PNGs

The function references that follow are generated from the doc comment above each function in the source, the same text that `help` prints.

6.1 core

Always available, no `load` needed. Special forms are listed first.

(quote x)

'x: x itself, unevaluated: code as data

(do forms...)

evaluate in order, return the last; what { } builds

(if cond then [else])

cond is true unless it is 0, nil, empty, or a vector with a zero

(while cond body)

loop; (break) and (continue) inside it

(for init cond step body)

C-style loop: (for (var i 0) (< i 10) (var i (+ i 1)) { ... })

(var name value)

define name in the current environment; a function's var is always local

(set name value)

assign to the nearest existing name, however far out; error if none

(function name (params)

body) define a function; (function (params) body) an anonymous one

(return [value])

leave the function; free in tail position

(break) (continue)

leave or restart the innermost loop

(try body catch e handler)

run body; on an error bind its message to e and run handler

(expr (a op b ...))

) infix arithmetic: + - * / % < > <= >= == != && ||; () groups, (f x) calls

(parse "text")

read Musil source into a form: (do line ...), the same reading a file gets; (eval (parse s)) runs it

(eval form)

evaluate a form (code built as data) in the global environment

(apply f list)

call f with the elements of list as arguments

(+ a b ...) (- a [b ...]) (* a b ...) (/ a [b ...])

arithmetic, elementwise with size-1 broadcasting; $(- x)$ negates, $(/ x)$ is the reciprocal, $(+)$ is 0 and $(*)$ is 1

`(< a b)` `(> a b)` `(<= a b)` `(>= a b)`

comparisons: elementwise 1/0 on numbers, lexicographic on two strings

`(== a b)` `(!= a b)`

equality: elementwise on numbers, structural on anything else

`(equal? a b)`

structural equality as a single 1/0, also for vectors and nested lists

`(same? a b)`

are a and b the same object (not merely equal in value)? For records and lists: the very one, however large; a number or a string is never the same object as another copy of it

`(sin x)` `(cos x)` `(tan x)` `(asin x)` `(acos x)` `(atan x)` `(sqrt x)` `(exp x)` `(log x)`
`(log2 x)` `(log10 x)`

trigonometry and logs, elementwise

`(abs x)` `(floor x)` `(ceil x)` `(round x)`

rounding and magnitude, elementwise

`(tanh x)`

hyperbolic tangent, elementwise (a soft clip for signals)

`(mod a b)` `(pow a b)` `(atan2 y x)`

remainder (sign follows fmod), power, two-argument arctangent; elementwise

`(not x)`

the negation of a truth value

`(and a b ...)` `(or a b ...)`

short-circuit, left to right: `(and)` stops at the first false value, `(or)` at the first true one; the last argument is returned as it is, so `(or x default)` is x when x is true. Special forms: later arguments are not evaluated when the answer is known, so `(and (> k 0) (getidx v k))` is safe.

`(min v)` `(max v)`

smallest or largest element of one vector; with several arguments, elementwise over them

`(list x ...)`

a list of anything

`(append L x ...)`

a new list with $x \dots$ at the end

`(push L x)`

append in place, returning the list; (pop L) remove and return the last element

(append L x ...)

a new list with x ... added at the end

(pop L)

remove and return the last element of a list, in place

(length x) (head x) (tail x) (empty? x)

on a list, a vector or a string

(getidx x k)

element k of a list, vector or string; negative k counts from the end

(setidx x k v)

set element k of a list or vector in place

(vec x ...)

a vector from numbers, vectors and lists of numbers, concatenated; a scalar is a vector of size 1

(sum v)

sum of the elements (0 for an empty vector)

(print x ...)

print the arguments separated by spaces, then a newline

(exit [code])

end the program

(type x)

"scalar" "vec" "string" "symbol" "list" "function" "nil" or "opaque:tag"

(str x)

x printed as a string

(sym s)

a symbol from a string; (num s) a number from a string

(copy x)

a shallow copy: a new list or vector with the same elements

(error x ...)

raise an error with the arguments as message

(clock)

seconds from a monotonic clock, for timing

`(load "file.mu")`

run a file once, searched next to the loading file, in the current directory, in `MUSIL_PATH` and in `~/.musil`

`(defined? 'name)`

is name bound?

`(vars)`

the global names, sorted

`(help name)`

print the documentation of a builtin or library function (from `help.txt`)

`(num s)`

the number written in a string (or a number unchanged)

6.2 std

The general-purpose standard library. Vectors: `range` is the constructor everything else is built on (`zeros`, `ones`, `linspace`), then statistics (`mean`, `stdev`, `median`, `quantile`, `histogram`), and `interp1` for table lookup. Sequences: `slice`, `take`, `drop`, `find`, `zip`, `unique`. Strings: `split`, `join`, `format`, `fmt-fixed`. Files: `read`, `write`. Higher-order: `map`, `filter`, `reduce`, `each`, all of them on lists and vectors alike.

```
load "std.mu"
var v (range 0 10 0.5)
print (mean v) (stdev v) (quantile v 0.9)
print (map (list "a" "b") upper) (filter v (function (x) (> x 7)))
print (format "{} of {}".format (count v even?) (length v)))
```

`(range n)` `(range a b)` `(range a b step)`

a vector of evenly spaced numbers, end excluded

`(seed n)`

seed the random generator so that `rand` repeats

`(rand)`

a number in `[0, 1)`; `(rand n)` a vector of `n` of them

`(sort v)`

the elements of a vector in ascending order

`(argsort v)`

the indices that would sort a vector ascending (stable: equal values keep their order)

`(reverse x)`

a list, vector or string reversed

`(slice x start [count])`

part of a list, vector or string; negative start counts from the end

`(find x v)`

index of the first element equal to `v`, or of the substring `v` in a string; -1 if absent

`(concat x ...)`

the arguments printed and joined into one string

`(get rec key)`

the value of `key`; an error when absent

`(opt rec key default)`

the value of `key` in a record, or `default`

`(has? rec key)`

is the `key` present?

`(put! rec key value)`

set a `key` in place (replacing an existing pair, or adding one); returns the record

`(split s sep)`

the pieces of `s` between occurrences of `sep`; `(split s "")` the characters

`(join L sep)`

the elements of `L` printed and joined with `sep`

`(format "text {} more {}" x y)`

each `{}` replaced by the next argument

`(upper s)` `(lower s)` `(trim s)`

case changes and whitespace trimming

`(chr n)`

the character with code `n`

`(ord s)`

the code of the first character of `s`

`(read path)`

the whole file as a string; a relative path that does not exist in the current directory is looked for next to the file being run (so a script finds its data from anywhere)

`(write path x)`

write `x` (printed) to a file, replacing it

`(append-file path x)`

write `x` (printed) at the end of a file

`(directory? path)`

is the path an existing directory?

`(exists? path)`

does the file or directory exist?

`(input [prompt])`

a line read from the console, or nil at end of input

`(map x f)`

`f` applied to every element: a list for a list; for a vector, a vector when every result is a number, a list otherwise

`(filter x f)`

the elements for which `f` is true, as a list or vector like `x`

`(reduce x f init)`

fold: `(f (f (f init x0) x1) x2) ...`

`(assert cond [message ...])`

stop with an error unless `cond` is true

`(regex-match? pattern s)`

does the regular expression (ECMAScript syntax) match anywhere in `s`?

`(sign x)`

-1, 0 or 1

`(even? n) (odd? n)`

`(between? x lo hi)`

`lo <= x <= hi`

`(hypot a b)`

`sqrt(a^2 + b^2)`

`(gcd a b) (lcm a b)`

on non-negative integers

`(lerp a b t)`

linear interpolation, `t` in `[0, 1]`

`(map-range x in-lo in-hi out-lo out-hi)`

re-map x from one range into another

(deg->rad d) (rad->deg r)

(zeros n)

vector of n zeros

(ones n)

vector of n ones

(linspace a b n)

n points from a to b inclusive

(mean v)

arithmetic mean

(prod v)

product of the elements

(dot a b)

inner product (sizes must match)

(norm v)

euclidean norm

(cumsum v)

running sum

(stdev v)

population standard deviation

(normalize v)

scale to [0, 1]; a constant vector becomes zeros

(diff v)

first differences, one element shorter

(argmin v) (argmax v)

index of the smallest / largest element

(median v)

the middle value (mean of the two middle values for even length)

(quantile v q)

value below which a fraction q of the data lies (linear interpolation)

(histogram v bins)

counts per bin over [min v, max v]; returns (list counts edges)

(interp1 xs ys xq)

linear interpolation of the table (xs, ys) at the points xq; xs must be increasing; xq outside the table is clamped to the ends

(clip v lo hi)

clamp every element to [lo, hi]

(fixed x d)

round x to d decimal places

(last x)

last element

(take x n)

first n elements

(drop x n)

all but the first n elements

(vec->list v)

the elements of a vector as a list

(contains? x v)

is v an element of x (or a substring, for strings)?

(each x f)

call f on every element, for side effects; returns nil

(any? x f)

does f hold for some element?

(all? x f)

does f hold for every element?

(count x f)

number of elements for which f holds

(concat-list a b)

a new list with the elements of a then those of b

(flatten L)

one level of nested lists removed

(zip a b)

list of two-element lists

(unique L)

elements in first-seen order, duplicates removed

(sort-list L)

sort a list of numbers or strings (insertion sort; fine for short lists)

(min-of L) (max-of L)

smallest / largest element of a list of numbers

(repeat s n)

string s repeated n times

(starts-with? s prefix) (ends-with? s suffix)

(replace s old new)

every occurrence of old replaced by new

(count-substr s pat)

number of non-overlapping occurrences of pat

(pad-left s w ch) (pad-right s w ch)

pad to width w with character ch

(fmt-fixed x d)

x as a string with exactly d decimals: (fmt-fixed pi 4) => "3.1416"

(fmt-pct x d)

x as a percentage string: (fmt-pct 0.752 1) => "75.2%"

(put rec key value)

a new record with the key set, the original untouched

(keys rec) (values rec)

the keys, the values, in order

(record key value ...)

a record from alternating keys and values: (record 'freq 440 'dur 0.5)

(sort-by L f)

the elements ordered by f (a number or string per element), stable

(group-by L f)

a record from key to the list of elements with that key, in first-seen order

`(find-first L f)`

the first element for which `f` holds, or `nil`

`(reject L f)`

the elements for which `f` does not hold

`(min-by L f)` `(max-by L f)`

the element with the smallest / largest `f`

`(sum-by L f)`

the sum of `f` over the elements

`(partition L f)`

(list those-for-which-f-holds the-others)

`(remove-at L k)` `(insert-at L k x)`

a new list without / with an element at `k`

`(shuffle L)`

the elements in a random order (a new list)

`(identity x)`

`(compose f g)`

the function `x -> (f (g x))`

`(times n f)`

call `f` `n` times with `0 .. n-1`

`(assert-near a b eps msg)`

numeric comparison within `eps`

`(assert-equal actual expected msg)`

structural comparison with a helpful message

6.3 system

Access to the operating system. `read-wav` returns `(list sample-rate (list channel ...))`, each channel a vector, which is the representation every signal function uses; `write-wav` takes a vector (mono) or a list of vectors. CSV tables are lists of rows, numeric cells become numbers.

```
load "system.mu"
var w (read-wav "sound.wav")
var sr (head w)
var left (head (getidx w 1))
```

```
write-wav "/tmp/out.wav" sr (* 0.5 left)
print (file-lines "notes.txt") (ls ".") (getenv "HOME")
```

(exec "command")

=> the command's standard output as a string

(getenv "NAME")

=> value or nil

(sleep seconds)

(find-file "name")

=> the path of a file as load resolves it (the current directory, the file being run, the load path: MUSIL_PATH, ~/.musil, the libraries), or "" when not found

(resolve-path "name")

=> the path a reading function would open for a relative name: as given if it exists from the current directory, else next to the file being run, else next to the program that was started

(interactive?)

=> is the standard input a terminal? (a script asks before prompting for input)

(breathe)

let the background work run once (windows, schedulers, the score player): for a long computation done from a window's button, once per step

(now)

=> seconds since the Unix epoch (wall clock; clock is the monotonic one)

(cwd)

=> current directory

(ls [dir])

=> list of entry names, sorted

(mkdir path)

=> creates the directory and its parents; nil

(remove path)

=> deletes a file or an empty directory; 1 if something was removed

(stat path)

=> (list size is-dir modified-seconds) or nil if it does not exist

(read-csv path)

=> table. write-csv is in system.mu.

(read-wav path)

=> (list sample-rate (list channel-vector ...)): 8, 16, 24 and 32-bit PCM or 32/64-bit float, any channels and rate

(write-wav path sample-rate channels [bits])

=> nil. channels: a vector (mono) or a list of vectors (any number); bits 8, 16 (default), 24 or 32 for integer PCM, "float" (or 32.0 with a decimal point: use "float") for 32-bit IEEE float, "double" for 64-bit; any sample rate. Integer files clip at +-1.

(udp-send host port payload [osc?])

=> 1 on success, 0 on failure. With osc?=1 the payload is

(udp-receive host port [timeout-seconds])

=> the next datagram as a string, or nil on timeout/failure

(serve port)

start the evaluation port; (serve-stop); (serving) => the port or 0

(file-lines path)

list of lines, without the trailing newline

(write-lines path lines)

write a list of lines, one per line

(file? path) (dir? path)

existence tests by kind

(file-size path)

size in bytes, or nil

(basename path) (dirname path) (extension path)

string surgery on paths

(csv-escape s)

quote a field if it holds a comma, a quote or a newline

(write-csv path table)

table is a list of rows, a row a list of cells

(elapsed thunk)

seconds taken by calling thunk

(wav-duration w)

seconds of a value returned by read-wav

6.4 scientific

Linear algebra, statistics and machine learning. A matrix is a list of row vectors: `(list (vec 1 2) (vec 3 4))` is 2×2 ; `(getidx M i)` is a row. Products, transposition, elimination (`det`, `inv`, `solve`), the symmetric eigensolver, k-means and KNN are C++; construction, elementwise arithmetic, statistics along an axis, covariance, PCA, regression, NMF and the model helpers are Musil; `mp`, matching pursuit over a dictionary (greedy, optionally non-negative or orthogonal), is C++ and serves the orchestrators.

```
load "scientific.mu"
var A (list (vec 2 1) (vec 1 3))
print (mat-mul A (inv A)) (solve A (vec 3 5)) (eig-sym A)
var P (pca X)                                # rows: direction then
      eigenvalue, largest first
var km (kmeans X 3)                          # (list labels centroids)
var model (knn-model training 3)
print (accuracy (knn-test model test) test)
```

`(mat-mul A B ...)`

matrix product, left to right

`(transpose M)`

`(det M)`

`(rank M)`

`(inv M)`

by Gauss-Jordan on $[M \mid I]$

`(solve A b)`

$\Rightarrow x$ with $A x = b$

`(mp x D iterations threshold options)`

$\Rightarrow$ a record: atoms (the indices of the chosen rows of D , in the order chosen), weights, residual, error (the residual's norm over x 's), and approx (the reconstruction). x a vector, D a dictionary (a matrix: one atom per row, the same length as x). Greedy: the atom most correlated with the residual is taken with its projection weight and subtracted, until iterations are done, the error is below threshold, or no atom helps. options: a record with 'nonneg (1: only atoms with a positive projection, weights kept positive; the choice for magnitude spectra) and 'orthogonal (1: orthogonal matching pursuit, every weight refitted by least squares after each pick)

`(median-filter v order)`

the running median of width order

`(eig-sym M)`

$\Rightarrow$ (list eigenvalues eigenvectors) of a symmetric matrix by Jacobi rotations;

(kmeans M k)

=> (list labels centroids): labels is a vector of cluster indices, centroids a k x d matrix

(knn training k queries)

=> list of predicted labels.

(list->mat L)

a matrix from a list of lists of numbers

(mat-fill r c v)

r x c matrix filled with v

(mat-zeros r c) (mat-ones r c)

matrices of zeros or ones

(mat-ones r c)

a matrix of ones

(mat-rand r c)

r x c matrix of values in [-1, 1]

(eye n)

identity; (diag v) diagonal matrix from a vector

(diag v)

a square matrix with v on the diagonal

(mat-diag M)

the diagonal of a matrix as a vector

(nrows M) (ncols M)

the number of rows or columns

(ncols M)

the number of columns

(mat-shape M)

(list rows cols)

(mat-get M i j)

element; (mat-set M i j v) in place

(mat-set M i j v)

set an element in place

(mat-row M i)

row i as a vector; (mat-col M j) column j as a vector

(mat-col M j)
column j as a vector

(get-rows M from n)
 n rows starting at from, as a matrix

(get-cols M from n)
 n columns starting at from, as a matrix

(mat-vec A x)
 A x as a vector; (vec-mat x A) x A as a vector

(vec-mat x A)
 x A as a vector

(outer u v)
the matrix u v' , rows $u[i]$ * v

(trace M)
sum of the diagonal

(mat-add A B) (mat-sub A B) (hadamard A B)
elementwise sum, difference and product of two matrices

(mat-sub A B)
elementwise difference

(hadamard A B)
elementwise product

(mat-scale M s) (mat-shift M s)
every element times s , or plus s

(mat-shift M s)
every element plus s

(mat-map M f)
 f applied to every element

(mat-round M d)
every element rounded to d decimals (for printing)

(vstack A B)
rows of A then rows of B

(hstack A B)

each row of A followed by the row of B

(col-stack vectors)

a matrix whose columns are the given vectors: (col-stack (list x y))

(lp-norm v p)

$(\sum |v|^p)^{1/p}$; $p = 2$ is the euclidean norm

(dist x y)

euclidean distance; (dist-p x y p) with another p

(dist-p x y p)

distance with another p: 1 for the city-block distance

(dist-matrix M)

pairwise euclidean distances between the rows of M

(nearest M x)

index of the row of M closest to x

(mat-sum M axis)

(mat-mean M axis)

(mat-std M axis)

population standard deviation

(zscore M)

columns standardised to mean 0, std 1 (constant columns become 0)

(standardize M)

the same as zscore

(center M)

each column minus its mean

(cov M)

sample covariance of the columns (rows are observations)

(corr M)

correlation of the columns; constant columns give 0

(linefit x y)

(slope intercept) of the least-squares line through the points

`(mat-str M d)`

one line per row, d decimals, columns aligned

`(mat-print M)`

print with 3 decimals; `(mat-print-with M d)` chooses the decimals

`(mat-print-with M d)`

print with d decimals

`(linreg-fit X y)`

coefficients b with $y \sim X b$, by the normal equations; y is a vector

`(linreg-predict X b)`

X b as a vector

`(linreg-residuals X y b)`

`(add-intercept X)`

a column of ones in front of X, for a model with a constant term

`(pca X)`

=> d x (d+1) matrix: row k is the k-th principal direction followed by its eigenvalue, largest first

`(pca-directions P)`

the directions of a pca result as a d x d matrix

`(pca-eigenvalues P)`

its eigenvalues as a vector

`(pca-scores X k)`

X projected on the first k principal directions, n x k

`(pca-explained P)`

fraction of variance per component

`(kmeans-labels result) (kmeans-centroids result)`

the two parts of a kmeans result

`(kmeans-centroids result)`

the centroids of a kmeans result, k x d

`(cluster-sizes labels k)`

how many points fell in each of the k clusters

`(knn-model training k)`

a model: (list training k); training is a list of (list features label)

`(knn-predict model queries)`

labels for a list of feature vectors

`(knn-predict-one model q)`

`(knn-test model samples)`

predictions for samples given as (list features label)

`(accuracy predictions samples)`

fraction of predictions equal to the samples' labels

`(train-test-split samples fraction)`

(list training test), first part of the list

`(shuffle L)`

a new list in random order (Fisher-Yates)

`(nmf V k iterations)`

V ($r \times c$, non-negative) $\sim W H$ with W $r \times k$ and H $k \times c$, both non-negative: Lee & Seung's multiplicative updates for the KL divergence (the usual choice for magnitude spectrograms); $\Rightarrow$ (list $W H$). Columns of W are the parts (spectral shapes), rows of H their activations over time.

`(nmf-with-parts V W iterations)`

the activations H of known parts W (their columns), $V \sim W H$ with W fixed: supervised NMF, when the parts were learnt from examples of each source

`(mat-min M) (mat-max M)`

the smallest and the largest element

`(mat-div A B)`

elementwise quotient

`(nmf-error V W H)`

the KL divergence between V and $W H$ (what the updates decrease)

6.5 signals

Offline signal processing on vectors. A signal is a vector of samples; a complex spectrum is `(list re im)`; a polar spectrum is `(list mag phase)`. The FFT, the table oscillator, the IIR filter, delay, resampling, autocorrelation, peak picking and gather are C++; generators, windows, convolution, the STFT and its inverse, cepstral envelopes, the phase vocoder, the spectral

and temporal descriptors, the RBJ biquads, comb and allpass sections and the Schroeder reverb are Musil, as compositions of vector operations; so are `convverb` (a convolution reverb through any response, dry and wet, per channel) and `concerthall` (the Concertgebouw's response, `hall_concertgebouw.wav`, shipped with the libraries; every `play-score` goes through it), both on `conv-fast`, a C++ overlap-add over blocks that gives `conv`'s result and lets the interpreter breathe between blocks. `hpss` (harmonic/percussive separation by median filters over the spectrogram) is C++; `onset-strength`, `onsets` (a global threshold), `onsets-adaptive` (a threshold on the flux's moving median, for material whose loudness drifts) and `segments` build onset detection from the spectral flux in Musil; onsets always start with 0 and are placed at the sample where the energy rises.

Separation by NMF. `nmf V k iterations` (in `scientific`, fifteen lines of Musil on the C++ matrix product: Lee and Seung's multiplicative updates for the KL divergence) factors a non-negative matrix into `k` parts; `nmf-separate x n hop k iterations` applies it to the magnitude spectrogram and splits the sound into `k` sources by Wiener masks that add up to the input. Supervised separation, when examples of each source exist: `nmf-learn-parts` learns a few parts from each example alone, `nmf-separate-with` learns only the activations on the mix (`nmf-with-parts`) and returns one source per instrument; `examples/nmf.mu` does both on a four-stem mix (drums, bass, chords, melody, with each stem alone to score against; made, like every synthetic demo sound, by `make_audio_demos.mu`).

Spatial. Conventions as in AmbiX: azimuth in degrees, 0 in front, positive to the left; elevation up; a multichannel signal is a list of channel vectors, which `write-wav` and `play` take. `pan-azimuth` is stereo from a direction; `pan-n` feeds a ring of speakers (amplitude panning between the two nearest); `ambi-encode` places a mono signal as B-format ($(\text{order}+1)^2$ channels, ACN/SN3D, orders 0–7) with `ambi-gains` the spherical harmonics behind it; `ambi-rotate` turns a whole field exactly; `ambi-decode` samples the field at a speaker layout (max-rE weighted); `ambi-render` places several sources, `moving-source` one that moves. For headphones, `hrir` gives the two ears' impulse responses of a direction from the measured MIT KEMAR set (710 directions, full sphere, 128 taps; shipped as `hrtf_kemar.csv` with the libraries, loaded on first use, resampled to the session's rate) or, with `hrtf-unload` or when the file is absent, from a spherical-head model (`hrir-model`: interaural delay and head shadow only, so left and right but no front/back or height, which are cues of the pinna that only measured responses carry); `hrtf-load` takes another set in the same CSV layout. `binaural` renders a source through it, `binaural-decode` renders B-format through ten virtual speakers. Every one of these streams in a synth as well (`live`); `binaural` as a node crossfades its responses when the direction moves, so a sound can be flown around the listener from two sliders. `examples/spatial.mu`, `flyby.mu` (a helicopter in front, overhead, behind and around, also as third-order B-format for an external decoder such as the IEM BinauralDecoder in a DAW), `flyby_controls.mu` and `live_spatial.mu` do all of it.

```
load "signals.mu"
var x (sine 44100 440 1)
var frames (stft x 2048 512)
var y (istft frames 2048 512)                                # exact reconstruction
var slow (pvoc-stretch x 2)                                  # twice as long, same
    pitch
var up (pvoc-pitch-formant x 1.5 400)                        # a fifth up, formants
    kept
var any (pvoc x (list (list "stretch" (list 1 3)) (list "pitch" 0.75)
    (list "envelope" 400)))
var lp (lowpass x 44100 500 0.707)
print (spectral-centroid (magnitude-spectrum x) (spectrum-freqs 65536
    44100))
```

The phase vocoder is one engine, `pvoc`, in C++ (a frame is sixty vector operations on 4096 bins, ten thousand times a minute): a fixed synthesis hop with the analysis hop derived from the stretch, zero-phase windowing, phases locked to the nearest spectral peak, pitch shift and formant move in the spectrum, envelope preservation through the cepstral envelope, denoising, three cross-synthesis modes and two phase effects, every parameter able to ramp over the file. `pvoc-stretch`, `pvoc-pitch`, `pvoc-pitch-formant`, `pvoc-formants`, `pvoc-cross`, `denoise`, `robotize` and `whisperize` are one-line wrappers around it.

`(fft signal)`

=> (list re im), each of length `next-pow2(length)`; the signal is zero-padded

`(ifft (list re im)`

) => real signal of the same length (a power of two)

`(osc sr freqs table)`

=> one sample per element of `freqs`, reading the wavetable with linear

`(iir x b a)`

=> y with $a_0 y[n] = \sum b[k] x[n-k] - \sum a[k>0] y[n-k]$; $a[0]$ need not be 1

`(delay x d)`

=> x delayed by d samples (fractional, linear interpolation), same length

`(resample x factor)`

=> x with its length multiplied by factor, by windowed-sinc interpolation

`(autocorr x)`

=> biased autocorrelation (sum / n) for lags 0 .. $n/2 - 1$; it decays with lag, which

`(interleave (list a b ...))`

) => one vector $a_0 b_0 a_1 b_1 \dots$

`(deinterleave v channels)`

=> (list a b ...): the channels of an interleaved vector

`(local-maxima v)`

=> indices k with $v[k] > v[k-1]$ and $v[k] > v[k+1]$ (interior points only)

`(gather v indices)`

=> the elements of v at the given (integer) indices, as a vector

`(add-at! dst pos src)`

=> dst, with src added in place starting at pos; dst must be long enough.

`(comb x d g)`

=> feedback comb $y[n] = x[n] + g y[n-d]$; (allpass x d g) => Schroeder allpass

`(pvoc x opts)`

after sparkle: fixed synthesis hop $I = \text{window}/\text{overlap}$, analysis hop $D = I/\text{stretch}$

`(adsr sr gate a d s r)`

=> an envelope following a gate signal (1 = on, 0 = off): attack a and

`(lag x sr seconds)`

=> x smoothed by a one-pole lowpass with the given time constant (parameter

`(hpss x n hop kernel)`

=> (list harmonic percussive): STFT with a periodic Hann window of n and

`(ambi-gains order az el)`

=> the $(\text{order}+1)^2$ encoding gains (SN3D, ACN) of a direction

`(ambi-rotate B yaw)`

=> B turned by yaw degrees about the vertical axis (positive to the left): within each order, the pair (m, -m) rotates by m yaw, exactly; B is a list of $(\text{order}+1)^2$ channel vectors

`(conv-fast x h)`

=> the linear convolution of x and h (length $n + m - 1$), by overlap-add over blocks the size of h: the same result as conv, faster on long inputs, and the interpreter breathes between blocks (the windows stay responsive while a long score goes through the hall)

`(hrtf-load path)`

load a set from a CSV: each row azimuth, elevation, then the left ear's samples and the right's (as src/hrtf_kemar.csv, the MIT KEMAR compact set at 44100 Hz, found on the load path); => the number of directions. Once a set is loaded, hrir takes the nearest measured direction (resampled to the requested rate); (hrtf-unload) goes back to the spherical-head model; (hrtf-loaded) => directions loaded, 0 for the model.

`(hrir-model az el sr)`

=> the spherical-head model, whatever is loaded (below)

`(hrir az el sr)`

=> (list left right): the nearest measured direction of the loaded set (the MIT KEMAR set is loaded from the load path on first use), resampled to sr; the spherical-head model when no set is available for each ear a head-shadow filter, whose high-frequency roll-off grows with the angle from that ear, and the interaural delay (Woodworth). No measured data: the model externalises and lateralises well enough to work with; real HRTFs can replace it (a WAV pair per direction convolved the same way).

`(sine sr freq dur)`

a sine of freq Hz lasting dur seconds

`(noise n)`

white noise in [-1, 1]; n may also be a signal, giving noise of its length (so an instrument can write (noise gate): offline as long as the gate, streamed forever)

`(impulse n)`

a 1 followed by n-1 zeros

(gen n amps)

one period of a wavetable with the given harmonic amplitudes, plus a guard point (n+1 samples, last = first), normalised to a peak of 1; for osc

(oscbank sr amps freqs table)

sum of oscillators; amps and freqs are lists of per-sample envelopes

(mix layers)

overlay (list (list position signal) ...) into one signal

(add-at dst pos src)

dst with src added starting at pos; dst grows if needed

(pan x pos)

a mono signal to (list left right), equal power; pos from -1 (left) to 1 (right)

(fade-in x n) (fade-out x n)

linear fades over n samples

(rms x)

root mean square

(normalize-peak x)

scale so the peak is 1; (normalize-rms x target) so the rms is target

(normalize-rms x target)

scale so the rms is target

(amp->db x) (db->amp d)

amplitude to decibels and back

(next-pow2 n)

the smallest power of two $\geq n$ (fft sizes)

(window n a0 a1 a2)

generalised cosine window, periodic (so hann overlap-adds exactly at hop n/4); (hann n) (hamming n) (blackman n) are the usual ones

(hann n) (hamming n) (blackman n)

the usual windows, periodic

(hamming n)

the Hamming window

(blackman n)

the Blackman window

`(car->pol spec)`

(list re im) -> (list mag phase); (pol->car) the other way

`(pol->car spec)`

(list mag phase) -> (list re im)

`(magnitudes spec) (phases spec)`

from a complex spectrum

`(spectrum-freqs n sr)`

the frequency of each of the first $n/2$ bins

`(magnitude-spectrum x)`

the positive-frequency magnitudes of x, normalised so a full-scale sine reads 1

`(complex-mul a b)`

product of two (list re im) spectra

`(conv x h)`

linear convolution through the FFT, length $(+ (\text{length } x) (\text{length } h) - 1)$

`(cepstrum mags)`

real cepstrum of a full (symmetric) magnitude spectrum

`(spectral-envelope mags order)`

smooth envelope of a full magnitude spectrum: the "true envelope", a cepstral smoothing (first 'order' coefficients) iterated so that it rides on the harmonic peaks instead of averaging peaks and valleys. The order sets the resolution: about $sr / (2 f_0)$ of the sound (e.g. 150 for a voice at 44.1 kHz) follows the formants without rippling at the harmonics

`(flatten-spectrum mags order)`

the magnitudes divided by their envelope: the fine structure alone

`(impose-envelope mags source order)`

mags reshaped to carry the spectral envelope of source

`(stft x n hop)`

=> list of (list re im); (istft frames n hop) => signal by overlap-add

`(istft frames n hop)`

the signal back from stft frames by windowed overlap-add

`(stft-magnitudes frames)`

list of positive-frequency magnitude vectors, one per frame

(princarg x)

wrap a phase to $(-\pi, \pi]$

(ramp v)

a parameter given as a number or as (list start end) -> (list start end)

(fftshift v)

rotate a vector by half its length (zero-phase windowing)

(pvoc-stretch x factor)

time-stretch by factor with the pitch kept

(pvoc-pitch x ratio)

pitch-shift by ratio at the same length (formants move too)

(pvoc-pitch-formant x ratio order)

pitch-shift keeping the formants (order about sr/100: 400 at 44.1 kHz)

(pvoc-formants x ratio order)

move the formants by ratio, the pitch kept

(pvoc-cross x y mode amount order)

cross synthesis of x by y: mode 1 multiplicative, 2 spectral flattener (y's envelope on x), 3 morphing

(robotize x)

zero phases: a buzz at the frame rate

(whisperize x)

random phases: the spectral envelope on noise

(denoise x threshold)

magnitudes below threshold x the peak are zeroed (0.01 - 0.1)

(gate-spectrum mags threshold)

magnitudes below threshold times the frame's peak set to zero

(spectral-morph a b t n hop)

between two sounds of the same length: magnitudes interpolated linearly, phases taken from a below $t = 0.5$ and from b above

(onset-strength x n hop)

the spectral flux of every frame, as a vector (one value per hop)

(onsets x sr n hop threshold)

onset times in seconds, always starting with 0 (so the segments cover the sound from its beginning): then the peaks of the spectral flux (local maxima) above threshold $\times$ the flux's maximum, at least n samples apart from the previous onset, each placed at the sample where the energy jumps inside its frame (64-sample blocks: the block with the largest rise), so a hit is found where it starts, not a window early

(onsets-adaptive $\times$ sr n hop threshold width)

the same with a threshold that follows the material: a peak counts when it exceeds threshold $\times$ the moving median of the flux over width frames (odd, e.g. 9); for sounds whose loudness drifts, where a global level misses the quiet hits or admits the loud sustain

(onsets-of-flux $\times$ sr n hop flux level)

the shared picker: peaks of flux above level (a vector), spaced and refined

(onset-refine $\times$ start n)

the sample within [start, start + n) where the energy rises most (64-sample blocks)

(segments $\times$ sr times)

the pieces of x between consecutive onset times (and the end), as a list

(spectral-moment amps freqs order centroid)

weighted moment of the frequencies about a centroid

(spectral-centroid amps freqs)

amplitude-weighted mean frequency

(spectral-spread amps freqs)

standard deviation around the centroid

(spectral-skewness amps freqs)

asymmetry of the spectrum about its centroid

(spectral-kurtosis amps freqs)

peakedness of the spectrum about its centroid

(spectral-flux amps previous)

rectified increase from the previous frame

(spectral-irregularity amps)

sum of absolute differences between neighbouring bins

(spectral-decrease amps)

weighted decrease relative to the first bin

(spectral-flatness amps)

geometric over arithmetic mean: 1 for noise, 0 for a pure tone

(spectral-rolloff amps freqs fraction)

frequency below which the fraction of the energy lies

(hfc amps)

high-frequency content

(zcr x)

zero-crossing rate per sample

(acf-f0 x sr)

fundamental by autocorrelation; 0 when no clear peak

(biquad type sr f0 q gain-db)

=> (list b a) of an RBJ biquad; type is one of "lowpass" "highpass" "bandpass" "notch" "peak" "lowshelf" "highshelf"

(apply-filter x coeffs)

run x through (list b a) as returned by biquad

(lowpass x sr f0 q) (highpass x sr f0 q) (bandpass x sr f0 q) (notch x sr f0 q)

one biquad, applied

(highpass x sr f0 q)

a highpass biquad, applied

(bandpass x sr f0 q)

a bandpass biquad, applied

(notch x sr f0 q)

a notch biquad, applied

(peak-eq x sr f0 q gain-db) (lowshelf x sr f0 q gain-db) (highshelf x sr f0 q gain-db)

the equaliser biquads, applied

(lowshelf x sr f0 q gain-db)

a low shelf, applied

(highshelf x sr f0 q gain-db)

a high shelf, applied

(dc-block x)

remove the DC offset; (dc-block-r x r) with pole radius r (default 0.995)

(dc-block-r x r)

a DC blocker with pole radius r

(reson x sr freq tau)

two-pole resonator at freq Hz with decay time tau seconds; the output lasts tau seconds, so a short excitation rings out

`(schroeder-reverb x sr rt60)`

four parallel combs into two allpasses; rt60 is the decay time in seconds (how long the tail takes to fall by 60 dB). The output is the input plus rt60 seconds, so the tail is not cut off.

`(resample-to x sr-in sr-out)`

`(bpf start segments)`

break-point function: piecewise linear segments as one vector; segments is a list of (list length end): (bpf 0 (list (list 4 1) (list 4 0))) rises then falls. Each segment's end value is excluded (it starts the next one).

`(envelope-follow x n)`

rms over hops of n samples, one value per hop

`(envelope-from-values v hop)`

piecewise-linear signal through successive values, hop samples apart

`(frame-spectra x block hop ncoeff)`

the magnitude spectrum of every frame (a Hann window of block samples every hop), the first ncoeff bins: the same space as a database's spectrum features, one spectrum per frame instead of the average

`(spectral-similarity a b)`

the cosine similarity of two magnitude spectra on a log scale (1: alike; 0: unrelated)

`(event-rate x sr window hop)`

how many attacks a second around every instant: the peaks of the spectral flux that stand above its moving median (twice it, at least 60 ms apart: a held sound's tremolo or vibrato ripples at the floor and does not count), counted in a window of window seconds, one value every hop samples; => (list times rates peaks)

`(flux-peaks x sr n hop threshold width)`

the times (seconds) of the peaks of the spectral flux (the rectified change of the magnitude spectrum, n and hop as onset-strength) that stand above threshold times the flux's moving median over width frames (odd): every noticeable spectral change, an attack or not, counted as the target's activity; threshold 2 keeps the attacks, 1.5 admits the ripples of a held sound too; peaks within 50 ms of the previous one count as one; => a vector

`(peak-density times secs window hop)`

how many of some times (a vector, seconds) fall a second around every instant: the count within window seconds centred on each hop-second step over secs seconds, divided by the window; => a vector, one value per step (a density in events a second)

`(polyphony-estimate spectra)`

how many voices seem to sound in each frame: the spectral peaks standing above twice the frame's mean (a lower bound, capped at 16); => a vector, one per frame

(register-curve spectra sr block)

where the sound sits: for each frame the centroid in MIDI pitch (the powers weighting the pitch of every bin above 30 Hz, so an octave is an octave), the spread around it in octaves, and the lowest strong partial in MIDI pitch (a tone's fundamental, more or less: where the register begins); => (list centroids spreads lows)

(loudness-curve x sr hop)

the level of every hop in dB, roughly as the ear weighs it (the extreme bass and treble taken out); => a vector, one value per hop, -100 for silence

(coherence-time spectra hop sr threshold)

how long the sound keeps its spectrum from each frame on: the time until the spectral-similarity with the frame falls under threshold (0.75 is reasonable), at most 8 s; a sustained sound gives long times, a percussive one short; => a vector

(spectral-peaks m sr block n)

the n strongest peaks of a magnitude spectrum as (list freqs mags), each frequency refined by a parabola through the peak and its neighbours

(converb x ir dry wet)

x through an impulse response: x a vector or a list of channels, ir a vector (applied to every channel) or a list of channels (one per output channel; a mono x is spread over them); => a list of channels, dry x plus wet x convolved, as long as x plus the response's tail

(hall-ir sr)

the impulse response of the Concertgebouw (Amsterdam), shipped with the libraries, at a rate

(concerthall x sr dry wet)

x (a vector or channels, at sr) in the Concertgebouw: converb with the shipped response; => stereo (a mono x is placed in the middle), as long as x plus the hall's tail (~3 s)

(pan-azimuth x az)

a mono signal to (list left right), equal power from its azimuth (-90 right .. 90 left; behind is folded onto the front)

(speaker-ring n)

n speakers evenly around, as azimuths starting in front and going left

(pan-n x speakers az)

a mono signal onto a horizontal ring of speakers (a list of azimuths) by amplitude panning between the two nearest speakers (VBAP in 2D); => a list of n channels

(princarg-deg a)

an angle wrapped to -180..180

(ambi-encode x order az el)

a mono signal at a direction as B-format: (order+1)^2 channels (ACN, SN3D)

(ambi-add a b)

two B-format signals of the same order summed

(ambi-decode B speakers)

B-format to a list of speakers, each (list az el) or a bare azimuth, by sampling the sound field at every speaker direction (the basic decoder), with max-rE weights per order for a smoother field off-centre

(max-re-weights order)

the per-channel max-rE weights of an order (Zotter & Frank): concentrates the energy vector

(binaural x az el sr)

a mono signal at a direction for headphones: convolved with the two ears' impulse responses of a spherical head (hrir); => (list left right)

(channel sig k)

one channel of a multichannel signal (a list of vectors); a vector is its own channel

(stereo-add a b) (stereo-scale a g)

stereo signals summed, scaled (written with channel, so they stream)

(binaural-decode B sr)

B-format for headphones: decoded to eight virtual speakers around the listener and two above, each rendered binaurally with the spherical head, summed; => (list left right). One expression, so it streams in a synth too.

(normalize-peak-stereo s)

a stereo (or any multichannel) signal scaled so its loudest sample is 1

(ambi-render sources order)

several (list x az el) placed and summed as one B-format signal

(moving-source x order az-curve el-curve blocks)

a signal whose direction changes: encoded block by block (blocks samples each) at the azimuth and elevation curves (vectors, one value per block)

(nmf-separate x n hop k iterations)

x split into k sources: NMF of its magnitude spectrogram (V = magnitudes, bins x frames) into k parts, then a Wiener mask per part (its share of $W H$ at every bin and frame) applied to the complex spectra and inverted; => (list (list source-1 ... source-k) $W H$). The sources add up to the input. Which part is which sound is for the caller to decide (their spectral shapes W and activations H say).

(nmf-spectrogram frames n)

the magnitude spectrogram of stft frames as a bins x frames matrix

(nmf-sources x frames n hop $W H$ groups)

the sources of a factorization: groups is a list of lists of part indices, one source per group (a source may be several parts); Wiener masks, ISTFT

(nmf-learn-parts examples n hop k iterations)

supervised separation, step one: for each example sound (a list of vectors, one per source) learn k spectral parts by NMF; $\Rightarrow$ W with k columns per source, and the groups (which columns belong to which source)

(nmf-separate-with x n hop W groups iterations)

supervised separation, step two: the mix x against known parts W (nmf-with-parts learns only the activations), one source per group

6.6 live

Real-time sound. The interpreter never runs on the audio thread: it posts commands (play this buffer at this time, stop that voice, set the gain) into a lock-free queue, and the audio callback drains the queue, advances a sample clock and mixes the voices into an N -channel bus. A voice plays a buffer (mono, or a list of channels) at its own sample rate, with amplitude, pan, rate and loop, from a start time on the clock, so sounds asked for slightly ahead land exactly where asked however late the program is. The device is miniaudio, with no window needed; a silent “null” device (the option (list (list "device" "null")), or the environment variable MUSIL_NULL_AUDIO) runs the same callback from a timer, which is how the test suite exercises everything but the ears.

```
load "live.mu"
audio-init                                # 44100 Hz, 256 samples,
    stereo, started
var v (play-file "data/drums.wav")        # a voice
wait-for v
var lp (loop-buffer x sr)
set-rate lp 0.5
stop lp
var t (audio-time)
each (range 8) (function (k) (play-at (+ t (* k 0.25)) hit sr)) #
    sample-accurate, ahead of time
audio-quit
```

Synths. An instrument is an ordinary Musil function of its parameters whose body combines the *streamable* builtins: *osc*, *noise*, *adsr*, *lag*, the biquads (*lowpass* ... *highshelf*), *iir*, *dc-block*, *delay*, *comb*, *allpass*, *conv* (partitioned when streaming), *pan*, *list*, arithmetic and elementwise math (the list is (*streamable*)). Called normally it returns a buffer, because every one of those is a vector function in *signals*. Handed to (*synth f*) its body is compiled into a graph of nodes that run *the same loops* from *signals.h* one block at a time, and its parameters become hot: (*set-param id 'cutoff 200 0.5*) ramps the running sound; a parameter named *gate* is what *note-on*/*note-off* set. *synth-render* runs the graph offline with parameter curves, and the test suite checks it equals the direct call to float precision. Anything not streamable (*pvoc*, *resample*, ...) is refused by name; it is still a fine offline instrument.

```
function lead (gate freq cutoff) \
    (pan (* (adsr sr gate 0.01 0.2 0.5 0.4) (lowpass (osc sr freq
        saw-table) sr cutoff 2)) 0)
var a (synth lead)                        # compiled, silent
set-params a (list (list 'freq 110) (list 'cutoff 1200))
note a 0.5                                # gate on, off after
    half a second (scheduled)
set-param a 'cutoff 300 1.5                # ramp while it plays
var y (lead gate-vector freq-vector 1200) # the same function,
    offline: a buffer
```

Loops. A loop is a function of the cycle number returning events, each (`list beat dur thunk`); (`live-loop 'bass 4`) calls the function *named* `bass` every four beats, slightly ahead of the clock (`lookahead`), and the thunks schedule sounds sample-accurately (`synth-ev`, `play-ev`, or your own `note-at`/`play-at`). Because the function is looked up by name at each cycle, redefining it while the loop runs is the live coding: the next cycle plays the new definition. `tempo`, `beat`, `stop-loop`; and the transformations of event lists, `fast`, `slow`, `shift`, `rev`, `every`, `degrade`, `cat`, `stack`, `steps`, are plain list functions. The scheduler runs in the interpreter's idle time (while the REPL or the IDE waits, and inside `sleep`), on one thread with everything else.

```
tempo 110
function drums (cycle) (stack (list
  (steps 1 (list 1 nil 1 nil) (function (x) (function (t d) (note-at
    t k 0.1))))
  (every 4 cycle (function (e) (fast e 2)) (steps 0.5 (list nil 1) (
    function (x) (function (t d) (note-at t h 0.05)))))))
live-loop 'drums 4
function drums (cycle) ...           # redefine: next cycle it changes
```

Notes, patterns, a kit. `hz`, `note->midi`, `midi->hz`, `chord-midi` for pitch names and chords; `pat` is a compact notation for steps, one string per cycle ("`bd ~ sn ~`": spaces are steps, `~` a rest, `[a b]` a subdivision, `a*n` a repeat), turned into events by `pat-events`, `drums` (a kit) and `melody` (a synth); `euclid`, `swing`, `humanize`, `sometimes`, `chance` shape rhythms; `poly` and `chord-ev` play chords on several instances. `kick`, `snare`, `clap`, `hat`, `ohat`, `acid`, `stab`, `pad` are ordinary instrument functions (`house-kit` makes the drums), so they render offline too; `tkick`, `rumble`, `that`, `tohat`, `tclap`, `perc`, `sub`, `hoover` (portamento through lag), `tstab`, `tpad`, `zap` and `techno-kit` are the harder set, with `duck` (a pad pumping under the kick), `sweep` and `accents`. A synth function may call your own helper functions (`sig` makes a constant as long as a signal, so (`osc sr (sig gate 190)table`) is a fixed pitch offline and streamed): the compiler inlines them. `examples/live_house.mu`, `live_techno.mu` and `live_trance.mu` are tracks meant to be edited while they play.

Controls and OSC. (`control 'cutoff 100 5000 800`) declares a named value with a range, (`toggle 'on 1`) an on/off one; `bind-control` makes synth parameters follow it, `set-control` and `control-value` read and write it from code, (`controls`) opens the window of sliders and check boxes and returns. `osc-listen` and `osc-map` let an incoming OSC message move a control; `osc-send` sends one; `osc-encode` and `osc-decode` are OSC in the language, over `udp-send` and `udp-receive`, for anything the conveniences do not cover. None of this is the evaluation port below: OSC carries numbers to controls over UDP, the port carries code over TCP.

Editors. (`serve 7770`) (in `system`; the IDE does it at start-up; the command line with `-serve 7770 -i`) opens a local port that evaluates the text it receives, in the session, as if typed. The VS Code extension in `editors/vscode/musil` sends the block around the cursor with `Cmd-Enter` (the file with `Cmd-Shift-Enter`) and gives `.mu` files syntax colouring, from a grammar generated with `help`. From a shell, `musil -send 7770 block.mu` (or with the code on `stdin`) sends and prints the reply, and any editor that can run a command can do the same; the two Musil processes stay separate sessions, the port only lets one hand code to the other.

(`audio-open sr block channels [opts]`)

open the audio device; if one is already open with the same sample rate and channels it is reused (voices cleared), otherwise it is closed and reopened. `opts`: (`list "device" "null"`) for the silent backend (tests, headless machines). Fails if a device is already open.

(`audio-close`)

stop and close the device

(play-cues cues)

hand a list of cues to the engine: each (list when path skip dur rate amp pan) for a file (when in seconds on the clock; skip: seconds of the sound left out at its start; dur: seconds to play) or (list when buffer sr 0 dur rate amp pan) for a buffer (a vector or a list of channels) already in memory. The loader thread reads and queues them ahead of the clock; the interpreter is free.
=> the number of cues

(stop-cues)

drop the cues not yet played (the voices playing are stopped by stop-all)

(cues-status)

=> (list active next total loaded failed cache-mb last-error)

(cue-cache-limit bytes)

how much decoded sound the loader keeps (2 GB by default); (cue-lookahead seconds) how far ahead of the clock it reads (3 s)

(bus-reverb ir dry wet)

the whole output through an impulse response (a vector, or a list of one response per channel, at the device's rate), mixed dry and wet; a delay of (bus-reverb-latency) seconds applies to everything while it is on. (bus-reverb-off) takes it off; (bus-reverb-latency) => seconds (0 when off)

(bus-limiter on)

the peak limiter on the output (on by default): the bus is held under 0.95 with a fast duck and a slow recovery instead of clipping; (bus-limiter 0) takes it off

(audio-start) (audio-stop)

run or pause the callback; the clock advances only while running

(audio-status)

=> (list (list "open" 0/1) (list "running" 0/1) (list "sr" sr) (list "block" n) (list "channels" n) (list "device" name) (list "time" seconds) (list "voices" n) (list "load" fraction) (list "peak" x))

(audio-devices)

=> list of the playback device names

(audio-time)

=> seconds on the engine's clock (sample-accurate, advances while running)

(play-buffer buffer sr amp pan rate loop at)

=> voice id. buffer is a vector (mono) or a list of channel vectors, at its own sample rate; at is the start time in seconds on the clock (0 = now)

(stop voice)

stop one voice; (stop-all) every voice

(master-gain g)

the output gain, applied to the whole bus

(voice-set voice "amp"|"pan"|"rate" value)

change a playing voice, ramped over a few blocks

(voices)

=> the ids of the voices playing or scheduled

(synth f)

=> id: compile the function f into a running instrument (silent until its parameters say otherwise). f's parameters become hot parameters; its body may use only the streamable builtins (see (streamable))

(set-param id name value [ramp-seconds])

change a synth's parameter, immediately or ramped

(synth-render f params seconds [sr])

=> the sound of f as the engine would stream it, computed offline block by block with its parameters set to params (a list of (list name value) or (list name buffer) for a value per sample); the same graph as (synth f), so the result equals f called on the same signals. No device needed.

(free id)

remove a synth from the graph

(synth-params id)

=> the parameter names of a synth, in the order of its function

(synths)

=> the ids of the running synths

(streamable)

=> the names of the builtins a synth function may use

(idle-hook! name)

call the global function of that name from the idle work, until (idle-hook-off! name); an error in it is printed and takes it off

(idle-hooks)

=> the names hooked

(tempo bpm)

set the tempo; beats are counted from now

(beat)

=> the current beat (a number, fractional); (beat-time b) => the clock time of beat b; (bpm) => the tempo

(live-loop name beats)

start (or restart) the loop named name: the function of that name is called every cycle of 'beats' beats; (stop-loop name) (stop-loops) (loops) => the names

(lookahead seconds)

how far ahead of the clock loops are scheduled (default 0.25)

(control name lo hi value)

declare a control (a range and a value); (toggle name value) an on/off one

(set-control name value) (control-value name) (controls-list)

=> (list (list name lo hi value toggle?) ...)

(bind-control name synth-id param)

a synth parameter follows the control (several bindings allowed); (unbind-control name)

(clear-controls)

forget every control

(osc-encode address args...)

=> the bytes of an OSC message as a string, for udp-send; (osc-decode bytes) => (list address args...) or nil: OSC in the language, on top of udp-send and udp-receive; osc-send, osc-listen and osc-map are conveniences over them

(osc-send host port address args...)

send an OSC message (numbers as floats, anything else as strings)

(osc-listen port)

receive OSC on a port (polled in the background); (osc-map "/address" control-name) the first number of a message at that address sets the control; (osc-stop)

(playhead! t0 from end [owner])

tell the roll that a score plays from 'from' seconds, started at clock time t0, until end; owner the score's number (register-score), so only that score's roll follows; (playhead-off!) it stopped; (playhead) => (list on time owner) the cursor's position now

(audio-init)

open the default device at 44100 Hz, 256 samples, stereo, and start it

(audio-init-with sr block channels)

the same with your numbers. With the environment variable MUSIL_NULL_AUDIO set (the test suite does), the silent null device is used. A device left open by a stopped program is reused (or reopened if the numbers differ), so running one live example after another just works.

(audio-quit)

stop everything and close the device

(audio-sr) (audio-channels) (audio-running?)

from audio-status

(audio-report)

print the status, one line per field

(play buffer sr)

play a buffer (a vector, or (list left right ...)) recorded at sr; => voice id

(play-with buffer sr opts)

the same with options: (list (list "amp" 0.5) (list "pan" -1) (list "rate" 2) (list "loop" 1) (list "at" 0.5)); at is a time in seconds on the audio clock

(play-file path)

play a WAV file (any channels) at its own sample rate; => voice id

(play-file-with path opts)

(play-at t buffer sr)

play at time t (seconds on the audio clock): sample-accurate however late the program is, as long as t is still ahead

(loop-buffer buffer sr)

play looping; stop it with (stop voice)

(set-amp voice a) (set-pan voice p) (set-rate voice r)

change a playing voice, ramped

(wait-for voice)

return when the voice has finished (polls the engine)

(wait-until t)

return when the audio clock has passed t seconds

(sequence steps)

play (list (list time buffer sr) ...) at their times, all scheduled at once

(note-on id) (note-off id)

set the synth's gate parameter to 1 or 0

(note id dur)

gate on now, off after dur seconds (sample-accurate, scheduled)

(note-at t id dur)

the same at time t on the clock

(set-params id pairs)

several parameters at once: (list (list 'freq 440) (list 'cutoff 800))

(play-synth f pairs)

compile f, set its parameters, gate it on; => id

(free-all)

free every synth

(synth-render-file f pairs seconds path)

render a synth offline through its graph and write a WAV

(ev beat dur thunk)

an event

(synth-ev beat dur id pairs)

a note on a synth: sets the parameters and gates it for dur

(play-ev beat buffer sr)

a buffer at a beat; (play-ev-with beat buffer sr opts) with play-with's options

(ev-beat e) (ev-dur e) (ev-thunk e)

(shift events beats)

move every event later by beats

(fast events factor)

squeeze the events in time by factor (2 = twice as fast); (slow events factor)

(rev events length)

play the cycle backwards (length = the loop's beats)

(every n cycle f events)

apply f to the events on every n-th cycle (cycle is the loop's cycle number)

(degrade events p)

keep each event with probability p

(cat lists length)

several cycles' worth of events one after another, each of length beats

(stack lists)

several event lists at once

(steps beats-per-step items thunk-of-item)

one event per item, evenly spaced; nil items are rests

(midi->hz n) (hz->midi f)

MIDI note numbers and Hz (69 = A4 = 440)

(note->midi "C#4")

a note name with octave (# or b) to a MIDI number; (hz "A4") straight to Hz

(chord-midi root kind)

the MIDI numbers of a chord: kind is 'maj 'min 'dom7 'min7 'maj7 'sus4 'dim 'min9; root a note name

(pat "bd ~ sn ~" beats)

one string per cycle: tokens separated by spaces are steps of equal length, ~ is a rest, [a b] subdivides a step, a*n repeats a token n times; => (list (list beat dur token) ...) spread over 'beats'. It is a notation for steps, nothing more: (pat "x ~ x ~" 4) equals (steps 1 (list "x" nil "x" nil) ...)

(pat-events pattern maker)

events from a pattern: maker gets the token and returns a thunk (t d)

(euclid hits steps)

the Euclidean rhythm as a list of 1 / nil, for steps: (euclid 3 8) = x ~ ~ x ~ ~ x ~

(swing events amount)

push the off-beat eighths later by amount (0 none, 0.33 heavy), in beats

(humanize events beats)

move every event by a random amount up to +/- beats

(sometimes p f events)

apply f to the events with probability p, per cycle

(chance p events)

keep each event with probability p (an alias of degrade with the argument order of sometimes)

(poly f n)

n instances of the synth function f; => (list id ...)

(chord-ev beat dur ids midis pairs)

a chord: each instance gets a pitch (as freq) and the pairs, and is gated for dur

(sig gate v)

the constant v as a signal as long as gate: (osc sr (sig gate 190) table) is a fixed 190 Hz both offline (a vector) and streamed (a node); plain 190 would be one sample offline

(kick gate)

a sine with a pitch drop and a click, saturated

(snare gate)

bright noise and a short 190 Hz tone

(clap gate)

band-limited noise with a spread attack

`(hat gate) (ohat gate)`

closed and open hi-hats: highpassed noise, short and long

`(acid gate freq cutoff res)`

a sawtooth into a resonant lowpass whose cutoff follows an envelope, then drive (a moving cutoff is a streaming feature: use synth-render for a buffer of it)

`(stab gate freq cutoff)`

the chord voice: two detuned saws and a sub octave, lowpassed

`(pad gate freq cutoff)`

slow detuned saws for the breakdown

`(house-kit)`

synths for kick snare clap hat ohat as (list (list 'kick id) ...); (kit-get kit 'name)

`(drums kit pattern-string beats)`

events for a kit from a pattern whose tokens are bd sn cp hh oh

`(melody id pattern-string beats pairs)`

notes for a synth from a pattern of note names (a2 c3 ...) and rests

`(tkick gate)`

a hard kick: deep pitch drop, click transient, saturated

`(rumble gate)`

the kick's tail: a low sine with a long decay through a comb, lowpassed

`(that gate) (tohat gate)`

metallic hats: ring-modulated squares through a highpass

`(tclap gate)`

a wide clap: noise through a resonant bandpass with two attacks

`(perc gate freq)`

a tuned percussion: noise burst plus a pitch-dropping tone

`(sub gate freq)`

a sub bass: a sine an octave under freq, with a hint of the fundamental

`(hoover gate freq cutoff glide)`

detuned saws with portamento (the frequency is lagged by glide seconds), a dark lowpass

`(tstab gate freq cutoff)`

a dark stab: squares through a lowpass with a fast decay

(tpad gate freq cutoff amp)

a pad with an amp parameter, for ducking (duck)

(zap gate freq)

a fast downward sweep: saw with a pitch envelope, for accents

(techno-kit)

synths for kick rumble hat ohat clap perc, as (list (list 'kick id) ...); tokens for drums: bd rm hh oh cp pc

(drums kit s beats)

also understands rm (rumble) and pc (perc) tokens

(duck ids beats depth)

ducking events on the beats: every beat the amp parameter of each id drops to depth and comes back in a quarter beat (the pad's "pumping" under the kick)

(sweep id name from to beats)

ramp a parameter from one value to another over beats (returns at once)

(accents events amount)

push every event a little later except the ones on the beat (a lazy feel)

(supersaw gate freq cutoff spread)

seven detuned saws (spread in cents, ~12) through a lowpass: the lead and pad of trance

(pluck gate freq cutoff)

a short bright saw pluck: the arpeggio voice (its cutoff falls with the note)

(offbass gate freq)

the off-beat bass: a saw and a sub, tight envelope, lowpassed

(riser gate rate)

a build: noise whose highpass opens with an envelope, over rate seconds (streaming: a moving cutoff)

(trance-kit)

the drums as synths: kick clap hat ohat (house sounds, a harder kick), tokens bd cp hh oh

(arp midis mode steps beats)

an arpeggio as a list of MIDI notes over steps: mode 'up 'down 'updown 'random

(arp-events id midis mode n beats pairs)

the arpeggio of n steps over beats, played on a synth

(gater ids pattern-string beats depth)

the trance gate: the amp parameter of the ids follows a pattern of x and ~ (x = open, ~ = closed to depth), for pads with an amp parameter (tpad)

(roll id beats n)

a snare or clap roll accelerating over beats: n hits spaced tighter and tighter

6.7 music

The score: things placed in time. A score is a record (name, sample rate, events, layout); an event has an onset, a duration, a kind, a source, a gain and a position (azimuth and elevation, for the spatial layouts). What an event holds is decided by what is placed:

```
var s (score "study" 44100)
event s 0 3.5 "bells.wav" # a sound
    file, read when rendered, cached
event s 2 3.6 buffer # a vector,
    or a list of channel vectors
event s 4 1 (note db 'Vn 'C5 'mf 'ord) # a sound
    from a database (nearest pitch, shifted)
event s 5 2 (instrument pluck (list (list 'freq 440))) # a synth:
    an instrument function and its parameters
event s 6 1 (call my-function (list 1 2 'dur)) # any
    function, called when rendered ('dur = the duration)
event-at s 7 1 my-function 90 0 # a bare
    function is called with the duration; placed at the left
event s 8 0 other-score # a score
    inside a score (0: its whole length); any depth
render s "study.wav" "stereo" # layouts:
    "mono" "stereo" "binaural" "ambi N", a ring, or N channels
play-score s 0.8 # through
    live, ahead of the clock, scaled
display s # the roll,
    drawn like music
```

A sound longer than its event is faded out at the end; a shorter one is left as it is; a synth's gate is the duration and its release plays on. A mono sound is spatialised at its position; a sound with as many channels as the layout goes in as it is. **play-score** (with a gain for the whole; **play-score-from** from a time) hands the score to the engine and returns: nothing is rendered in advance and the interpreter is not involved while it plays. Every event becomes a *cue* at a clock time (a file to read, or a buffer already made; a synth is compiled and gated), the list goes to the engine's cue player (**play-cues** of **live**), and a loader thread reads each sound a few seconds before it is due (**cue-lookahead**; a cache of decoded files, 2 GB by default, **cue-cache-limit**), cuts it to its duration at its own rate and queues it as a voice that the audio thread plays at the note's pitch shift (a linear interpolation; the offline render keeps the windowed sinc). The concert hall sits on the output bus as a convolution on a thread of its own (**bus-reverb**: partitioned, a latency of 93 ms that the playhead allows for; **score-reverb!** sets the dry and wet amounts, (**score-reverb! s 1 0**) plays dry), and a peak limiter (**bus-limiter**) ducks a tutti at *fff* rather than clipping it; a score's **'level** (0.5 by default) scales it before that. So Play starts within a second whatever the score's length, Stop stops at once, and neither the windows nor the interpreter can stall the music, nor the music them; **cues-status** says how the loader is doing. **render-buffer s layout** is the offline way: the whole score as channels, in the hall exactly as the roll plays it (the score's dry and wet amounts; dry when the wet is 0), scaled down when it would clip, a buffer to keep working on; **render s path layout** writes it as a WAV and **render-hall** is the same in stereo (the roll's **Render...**); **score-render** is the dry mix itself.

score-schedule is the older live way, every event on the clock at once; **play** and **play-file** of **live** still play a buffer or a file.

The roll (display) draws the score like music: one staff per instrument for the notes, in orchestral order, with a drawn treble or bass clef chosen by the instrument's range, ledger lines, sharps, and the dynamics under the staff where they change and there is room for them; then a line per kind (files, buffers, synths, calls); every event is a head at its onset and a thin line of the same colour for its duration (a line stops short of a following note's sharp); above a note, in a small script, its playing technique where it changes and its tuning in cents when it is not zero (**note-cents!** sets it; the orchestrators that know a target's exact frequencies will), written where there is room. A D pan and + - zoom in time, W S scroll and Z X zoom the rows, R resets; the wheel scrolls rows (sideways, or with Shift, time; with Ctrl it zooms), and scrollbars show the visible part once zoomed; hovering shows an event's data and the time; a double-click plays that event alone; a click in the background places the cursor, **Play** (or Space) plays the score from it, in the hall, **Stop** stops, and the red playhead follows (any **play-score** too, through **playhead**); the roll's picture is drawn once and kept, only the playhead and the hovered event are drawn at each frame, so a score of thousands of notes plays without the drawing taking the machine; **Render...** asks for a file name and writes the score in the hall (**render-hall**), scaled so that it never clips (the window is slow to answer meanwhile: a render is the whole score at once); **Save...** writes the score's notes as an Orchidea connection (below). It is a player of the code's score, not an editor: the score lives in the code, and a change is a line of Musil. **score-shift!**, **score-scale!**, **score-select**, **score-sort!**, **score-remove!**, **score-merge** are the transformations; **event-move!**, **event-length!**, **event-gain!**, **event-place!** edit one event. A score placed as an event renders into the parent's layout with its own positions kept, cut to the event's duration with a fade (0 means its whole length), at any depth; a score cannot contain itself, and the roll opens a score inside on a double-click.

Saving and loading. **score-save** writes a score's notes as an Orchidea *connection*, the text Orchidea exports and its Max patches read: an orchestra line, then one segment per onset (in ms) holding one solution whose lines are [**note duration instrument style pitch dynamics other file cents**]. Only notes travel: a file, a buffer, a synth, a call or a score inside has no place in the format and is left out (the count is printed), and a note's gain is not kept (the sample's dynamics are). **score-load db path name** reads one back into a score, each note's sound found in the database by its file name under any of the database's folders, or by instrument, pitch, dynamics and style when that file is not there; an unpitched sound becomes a file event. So an orchestration made by a script can be kept, reloaded, displayed and played later, and a connection exported by Orchidea can be played and shown here.

Elements. Pitches are names ("**C4**", "**F#3**") or MIDI numbers, nil a rest; a **rhythm** is a list of durations in seconds, negative for a pause (**beats** converts from beats at a tempo). **chord** is a payload: several pitches sounding together on one instrument, one event. The other elements make a *fragment*, a list of (**at dur payload**) from time 0: **notes** (a line on a rhythm, the shorter of the two repeating), **chords** (chords on a rhythm), **texture** (one line at several speeds on cycled instruments, the faster voices repeating until the slowest has played once: micropolyphony), **pivots** (one line per pitch of a chord, wandering at random within an interval of it), **chordinterp** (from one chord to another in as many steps as the rhythm has). **add!** and **add-placed!** put a fragment into a score, **fragment->score** makes it a score, **fragment-shift**, **fragment-scale**, **fragment-repeat**, **fragment-until**, **fragment-map** transform it, and **transpose-pitches**, **invert**, **scale-pitches** work on the pitches, so the list functions (**map**, **each**, **reverse** ...) compose everything. Around them: a tempo on the score (**score-tempo!**, **add-beats!**); gains and dynamics along a fragment (**fragment-gain**, **fragment-dynamics**), articulation, thinning by a probability or a density curve, placing, snapping to a pitch field; voicings (**chord-voicing**), series (**rotate**, **retrograde**, **cycle**, **interleave**), the harmonic series and the partials of a

sound as pitches (**harmonic-series**, **pitches-from-spectrum**); rhythms from patterns, augmented, triplets, polyrhythms; random walks, staggered textures, arpeggios, eased and set-wise chord interpolation, textures running through chords or around them (**texture-on-chords**, **texture-on-pivots**), a line orchestrated by register, **score-map!**. **algorithmic_comp.mu** (a row and its forms, Ligeti-like micropolyphony, spectral pivots after Grisey, moving textures) and **score_in_score.mu** show it.

MIDI files. **midi-read** parses a standard MIDI file (formats 0 and 1, the tempo map applied) into notes with times in seconds; **midi->fragment** puts them on an instrument, velocities becoming dynamics, **midi->fragment-by-channel** an instrument per channel, **midi->score** a score. Material from a sequencer, or a target for an orchestration.

Orchestrations. Every orchestrator returns a *result*: a record with its method and parameters and a list of segments, each covering a span of the target and holding solutions, every solution a fragment (at the segment's time) with a cost. **solutions** and **solution** read them; **connection** joins one chosen solution per segment into a fragment (a note continued across a boundary on the same instrument and pitch becomes one longer note), **best-connection** takes the first of each, **connect!** places a connection in a score. Three orchestrators share this: **orchestrate-granular** (below), **orchestrate-morphological** (the granulator driven by a target's analysis, below) and **orchestrate-mimetic** (Orchidea, below).

The orchestral granulator. Orchestration as granular synthesis: a stochastic process, described by envelopes over time, realised by the players of an orchestra with never more sounding at once than there are players: (**orchestra** (**list** 'Vn 'Vn 'Fl 'Fl)) is two violins and two flutes, each holding one note at a time, and a player busy with a note is not given another until it ends. **orchestra** takes a list where a symbol is a player, a string "**Fl|Picc**" a player with an ossia (one instrument or the other, by the pitch), and a list a paired group scheduled together. Playability is a property of the samples: an event's constraints (the register, the set of styles of the moment) select the samples of the database, and the event goes to a free player whose instrument has samples in that set (**player-styles**, **player-pitches**, **db-pitches-of**); the player takes a style of the set it has samples of there (a **trem** never goes to a flute; the flute takes the set's **ord** or **flatt**) and one of those samples at its own pitch, at the dynamics asked for or the nearest recorded. Nothing is relaxed and nothing transposed: a player without samples for the event is not given it; when no free player has any, the event is a rest; when no player of the orchestra could ever have any (a register, or a whole style set, none of its instruments was recorded with), the granulator prints that the request is unplayable and writes nothing for it. An ossia player takes the instrument that has the pitch with the technique. **orchestra-octaves** (and **orchestra-range**, in MIDI) is what an orchestra can play at all, to clip a band taken from a recording or a diagram to it, as the *Atmosphères* examples do. **env** is a value changing with time: at each breakpoint a number, a range (**list** lo hi) or a set (techniques, dynamics, chords); between breakpoints numbers and ranges are interpolated and sets crossfaded by chance, so a process moves from one state to another rather than switching. **orchestrate-granular db orch secs params** takes a record of parameters, each an envelope or a fixed value: **'density** (events per second), **'register** (octaves), **'duration**, **'styles**, **'dynamics**, **'chords**, and **'method**: **'random** among the player's pitches in the register (or those of the chord's pitch classes), **'pivots** (each player around a pitch of the chord within **'interval**), **'chordinterp** (the chord itself moving between two chords over time, **chordinterp-env**), **'markov** (transitions learnt from a score, **'markov-score**), **'harmonic** (partials of a **'fundamental** with probability **'harmonicity**); **'dynamics** may also be a level from 0 (ppp) to 1 (fff), interpolated, which picks the nearest recorded dynamics and sets a gain between them for a truly continuous crescendo; **'chord-weight** says how often a pitch comes from the chord rather than the register, so a chord dissolves into a cloud gradually; **'coupling** says how often a paired group actually sounds together (an envelope from 1 to 0 makes an orchestra synchronised at first and free later); **'solutions** asks for several

realisations.

The players as people. The rest of the parameters make the output a part a real player can sit down and play, and check it. A player has a memory: with `'seat` (seconds) an ossia player keeps the instrument it took for at least that long, and meanwhile is only eligible for what that instrument can play (a person plays one instrument, not one per note; a large value is a fixed seating); `'inertia` (0..1) is how often it keeps the technique of its last note when the set still holds it; `'leap` (semitones) keeps its next pitch within that interval of its last one when it has samples there (2: chromatic lines, a micropolyphony). The dynamics can be a constraint like the technique: with `'dynamics-strict` a player must have a sample at the dynamics asked for (`player-styles`, `player-pitches` and `db-pitches-at` take the dynamics too); without it the nearest recorded dynamics is taken and the substitution counted. `'balance` is a record from instrument codes or families (`'strings`, `'winds`, `'brass`, `'percussion`, `'keyboard`, `'plucked`; `instrument-family`) to decibels added to their notes, to keep the brass under the strings at the same marking (`balance-gain`). Where the pitches fall in the band: `'method` `'cluster` gives every pitch of the band once before any is repeated, the counts shared by the players (a chromatic saturation, a Ligeti cluster, where random draws repeat and leave holes); `'weight` (-1..1) draws the middle of the band more often (towards 1) or its edges (towards -1) and `'tilt` its bottom or its top. A signed `'leap`, (`list -2 -1`), is a direction: each next pitch one or two semitones below the last, a descending line that starts again (at the top, with `'tilt`) when it runs out of band; and `'just 1` tunes the `'harmonic` method's partials in just intonation, each note carrying its cents (`just-cents`: the 7th partial 31 low, the 11th 49 low, the 13th 41 high), an overtone chord. Every note the granulator writes says which player played it (`'player`), and a connection merges continuations only within a player. Time: `'spread` (seconds) scatters the players of a group struck together within that time (an orchestra's attack rather than a sampler's); `'duration-law` draws the duration in its range uniformly, log-uniformly (`'log`: as many short as long by ratio, a granular texture) or by an exponent (2: mostly short); `'group-density` gives each paired group its own rate (the event's rate is their sum, the event goes to a group with a probability proportional to its rate). One orchestra for a whole piece: with `'continue` the orchestra's own player records carry the state (every note booked so far, last pitches, seats) into the call and out of it, `'start` being the time in the piece the call begins at, so a run of granulators placed one after another, or overlapping, in any order, share the same people and never book one twice (a note is cut where the player's next booking begins; `orchestra-rest!` clears the state). Every run returns a report (`(get result 'report)`), printed by `granulation-report`): the events due, played and skipped because every able player was busy (the saturation: the number to tune the density against the orchestra's size), the unplayable ones, the dynamics substituted, and each player's notes and busy fraction. And `score-validate s orch` checks any score against an orchestra as a copyist would: at every moment each sounding note must have a player of its own able to play its instrument (an ossia player counts for either, so it is a matching, not a count), and every note must be at a pitch the instrument was recorded at; the record it returns (`'ok`, `'overbooked`, `'transposed`, the `'peak` per instrument) is printed by `validation-print`. `gran_orchestration3.mu` teaches these one section at a time. The database is indexed once (`db-index!`: the available pitched sounds of every instrument by dynamics and technique), so a note costs nothing on a large set; `db-techniques-of` and `db-dynamics-of` say what an instrument was recorded with, which is how an example builds its orchestra and its palette from whatever database is loaded. **Morphological orchestration.** `target-analyse` turns a sound into curves over time, computed once (the descriptors of `signals`): the frame spectra in the database's feature space, and a second set with a long window (5 Hz bins) that the peaks are read from; the attacks as the peaks of the spectral flux (`flux-peaks`: those standing above the local median, 50 ms apart at least) and their density in events a second (`peak-density`); the register (`register-curve`: the centroid in pitch, the spread around it in octaves, the lowest strong partial); and the loudness (`loudness-curve`); the estimates smoothed

by a moving median. `orchestrate-morphological db orch target params` is the granulator driven by those curves (`target-envelopes`: the density from the flux peaks a second, times `'density-scale`, at least `'min-density`; the register as the centroid $\pm$ `'width` spreads, extended down to the lowest partial, since a bass note lies under the centroid of its own spectrum; the dynamics as a level from the loudness, from *fff* at the target's loudest point to *ppp* `'range` dB under it; any parameter of your own overrides, `'styles` restricts the techniques). At every event the note is chosen by a matching pursuit (mp of `scientific`, non-negative, on the square roots of the magnitudes: between the linear, where one strong partial decides everything, and the log, where the noise between partials does): the dictionary is the free players' sounds whose pitch is one of the target's spectral peaks at that instant (`target-peaks`, `target-dictionary`: the partials of a sound are the pitches an orchestra can double it with, and the register and the dynamics of the moment narrow the choice), the signal is the target's spectrum over the next 100ms less what already sounds (`target-residual`: the sounding notes refitted to the frame together), and each atom is a note with its instrument, pitch and technique (`target-notes`: the best atom always, more up to `'voices` when each accounts for `'min-gain` of the residual; when the sounding notes explain the frame the pursuit doubles it instead). A note lasts as long as the target keeps its sound (`atom-persistence`: the projection of the frames ahead on the sound's spectrum stays above `'persist` of its peak, 6dB by default, up to `'max-length`); a life shorter than `'short` takes a short technique of the same sound when the database has one (`technique-short?`, a table of names); the tuning in cents is the target's nearest peak against the sound's own frequency (`entry-f0`). When every player is busy and an event is due the oldest note gives way (`'steal`). Nothing is segmented: a long sound under short ones comes out as a long note under short ones, which is what granulating rather than cutting is for. `morph_orchestration.mu` orchestrates a recording this way and places the target after it to compare.

Mimetic orchestration (Orchidea). `orchestrate-mimetic db orch x sr params` is assisted orchestration: the target is imitated as a whole. Its search core is Orchidea's (`src/music/orchidea.h`: the genetic search, the additive forecast, the asymmetric fitness, the connection between segments and the continuity model, ported as they are); what Orchidea did with files, Musil's database, score and roll do. The target, a vector at a rate (or a target already analysed), is cut at its onsets: the peaks of the spectral flux above `'threshold` (2 by default: above 1 nothing passes and the target is one segment, static; 0.1 cuts a piano phrase at every chord) and at least `'timegate` seconds apart, or `'segmentation` `'frames`, `'none`, or a list of onsets. Each segment is analysed into the database's features, standardised, and into the pitches of its partials with their cents (`'partials`, the threshold on the partials, 0.1; 0 turns the pitch filter off, for noisy targets where timbre matters more than pitch; `'partials-window` the window they are read with, 32768, large for a low target; `'extra-pitches` adds some). `mimetic-target` does this alone and `mimetic-print` shows it, to tune the segmentation before a long search. The search space of a segment is the sounds of the orchestra at the segment's pitches (and with the `'styles`, `'dynamics`, `'others` asked for, when given); a genetic search of `'population` individuals (300) over `'epochs` (300), each individual one sound per player or a rest (a player is dropped with probability `'sparsity` at every generation: 0.001 for symphonic targets, 0.1 for a single instrument as target), with `'crossover` (0.8), `'mutation` (0.01) and `'pursuit` (0: a random first population; k : from the k sounds nearest the target per player), looks for the combination whose summed features are nearest the target's by an asymmetric distance: a partial the solution has and the target lacks costs `'positive` (0.5), the reverse `'negative` (10); `'regularization` (> 0) sponsors sparse solutions. The memory between segments goes further than Orchidea's: the segments are searched and connected one after the other, so that each search knows the solution chosen for the segment before; `'hysteresis` (> 0) makes it lean, in timbre, towards the previous choices (the standardised forecasts, fading by that factor a segment back: the original compared a standardised candidate with unstandardised forecasts, which no weight could make meaning-

ful); `'dovetail` (> 0) raises a candidate's cost by that fraction of the previous choice's pitches it drops, on any player, which is what dovetailing is: pivot notes passed from one instrument to another; `'octaves` widens the pitch filter by octaves (`(list 0 -1)`: the partials' pitches and the octave below); `'hold` caps a note continued across segments at that many seconds (the player starts it again). The `'solutions` best unique individuals (10) are kept per segment, ranked by cost, and a `'connection` chooses one per segment: `'closest` (Orchidea's), each segment's solution nearest in timbre to the one chosen before; `'best`; or `'path`, the shortest path through the solutions, each costing its distance from its segment's best in percent plus `'movement` (1) per semitone a player moves or per player that starts or stops: the least melodic movement, the continuity of lines. The segmentation can also be `'adaptive`: the flux peaks against their local median (`'ratio`, 2), so the sensitivity follows the sound rather than its loudest attack. The players are the same people from one segment to the next: with `'sustain` (1) a player whose pitch the target still has holds its very sound on into the next segment, fixed in every chromosome, so the search fills only what changed and a held chord comes out as long notes, for at most `'hold` seconds; the result carries a report (`mimetic-report`: per segment the cost, the players sounding and holding on, the sounds in the search space and the target's pitches no instrument of the orchestra covers, which says why a segment sounds thin). A fitness cache spares the chromosomes seen before (most of a population, after the first epochs) and `'patience` (150) stops a search that stalls. The same search can also make the decisions of the morphological orchestrator: `'decision` `'genetic` replaces its greedy pursuit at each event by a genetic search over the free players' sounds at the target's peaks for the combination nearest what still lacks, in the morphological clock, with the durations from persistence: the copy of the mimetic without the segmentation. The result is an orchestration like the others: its segments hold the ranked solutions as fragments, each note the very sound chosen, at the target's cents, with its `'player` and, with `'seating` (1), the azimuth of Orchidea's seating (violins left, cellos right); `'choices` is the connection, `mimetic-connection` that connection as a fragment, `best-connection` the best of each segment, `solution-print` the solutions of a segment with their costs. `connect!` places a connection in a score, a note continued across a boundary on the same player and pitch becoming one longer note (Orchidea's continuity model), and the score remembers the orchestration: in the roll a dashed line marks every segment, and clicking in one fills the *solution* menu with its solutions by cost; choosing one replaces the segment's notes (`score-choose!`, `score-solutions`) and the playback follows. The search prints its progress (`'quiet` 1 silences it), Esc interrupts it in the IDE, `'seed` fixes its draws. `static_orchidea.mu` orchestrates a bell, `dynamic_orchidea.mu` a piano phrase cut at its chords, `orchfest.mu` puts the three orchestrators one after the other on the same sound. The names are Musil's; Orchidea's (`pop_size`, `max_epochs`, `xover_rate`, `onsets_threshold`, `partials_filtering...`) are in the function's documentation. One difference from Orchidea's own analysis: the target's pitches are named as the database's files name theirs, $C4 = 261.6$ Hz, so the pitch filter keeps the sounds at the target's pitch.

`gran_orchestration.mu` realises a unison that accelerates into a storm of every style over five octaves and then slows down towards the harmonic series of E2; `modulations.mu` follows the analysis of Grisey's *Modulations*, section by section, with the harmonicity, density, duration, dynamics, register and coupling envelopes of each process on the spectrum of E.

Databases. A database in the *SQL layout (TinySQL, OrchideaSQL, FullSQL) is a feature file next to a folder of the same name holding the sounds by family and instrument (TinySQL.spectrum.db and TinySQL/); the file's first line gives the type, block, hop and number of coefficients, then one line per sound: its path relative to the sounds' folder and its features. The sounds' folder is found by content, whatever its name (TinySQL/, tinysql/, a copy called otherwise): the folder next to the feature file that holds its sounds; and each sound is found by its file name anywhere under that folder, so a copy whose folders are named otherwise than the feature file says (Strings/Vn/ for Strings/Violin/) or spells sharps as _ loads

too. **db-load** reads the metadata (the file names carry instrument, technique, pitch, dynamics; a technique may be several tokens, **pizz-lv**, so the pitch is the first token that reads as one, and an unpitched sound has none) and the features, in C++, and never the sounds: those are opened when a note is rendered or played, and cached. **db-query** (nil matches anything, a list matches any of its members), **db-grep** (a regular expression on the file name), **db-find** (a substring), **db-between** (a pitch range), **db-nearest** (the closest features), **db-instruments** (in orchestral order), **db-techniques**, **db-dynamics**, **db-pitches**, **db-range**, **db-features**, **db-path**, **db-available?**, **db-available**, **db-instruments-available**. **db-gen** makes a feature file from a folder of sounds (Orchidea's **dbgen**, in C++: the energy-weighted average spectrum at 44100 Hz, as **spectrum**, **logspec**, **specpeaks**, **specenv**, **mfcc** or **moments**; the bundled TinySOL features are reproduced exactly); **db-make** generates and loads. Several databases whose features agree load as one: (**db-load** (list "a.db" "b.db")) or **db-merge**; every entry keeps its own sounds' folder, and **note** draws on all of them. **note** finds the entry for an instrument, pitch, dynamics and technique, or the nearest available pitch of that instrument, and shifts it by resampling; only sounds present on disk are candidates, so a feature file describing more than is present still works. A sharp in a pitch is written as a string ("D#5"): a # in a symbol would start a comment. The bundled **examples/data/microsol** (MicroSOL: oboe, horn, violin, cello, C4–G4, 32 sounds) makes every example run from a fresh clone; the full TinySOL is fetched into **datasets/** (ignored by git) with **./fetch_tinysol.sh**, and each example has a commented line to switch to it.

```
(pitch->midi "D#5")
```

```
=> 75: a note name with sharps (#, _) or flats (b) and an octave (C4 = 60); -1 if not a pitch
```

```
(midi->pitch 75)
```

```
=> "D#5"
```

```
(db-read path)
```

```
=> (list type block hop ncoeff entries): the feature file parsed; each entry a record (file instr tech
pitch dyn other midi features), the file relative to the database's root
```

```
(db-gen folder path type block hop ncoeff)
```

```
=> the number of sounds analysed: every WAV under folder (recursively), its features written
to path in the database format (first line: type block hop ncoeff; then the file's path relative to
folder and the features); the file names carry the metadata (instr-tech-pitch-dyn-other). Sounds
that cannot be read are skipped with a message.
```

```
(db-locate root file)
```

```
=> the path on disk of a sound named file (a path from a feature file) under root, found by its
file name whatever the folders are called; "" when it is not there. (db-index-size root) => how
many sounds root holds
```

```
(orchidea-analyse x sr type block hop ncoeff opts)
```

```
the target's segments for a mimetic orchestration: x a vector at sr (resampled to 44100 Hz, the
databases' rate), cut at its onsets, each segment analysed into the features of the database's type
(block, hop, ncoeff, as db-gen makes them) and standardised, and into the pitches of its partials
with their cents. opts a record: 'segmentation ("flux": the onsets of the spectral flux above
'threshold, a 'timegate apart; "frames": every block; "none": one segment; or a list of onset
times in seconds), 'threshold (2: above 1 there is one segment, a static target), 'timegate (0.1 s),
'partials-window (32768), 'partials (0.2: the threshold on the partials, 0..1, 0 for no pitch filter),
'extra-pitches (names added to every segment) => a list of records (at dur features notes), notes
a record from pitch name to cents
```

(orchidea-search entries orchestra segments opts)

Orchidea's genetic search: entries a database's entries (records with instr tech pitch dyn other features), orchestra a list of players as strings ("Fl", "Fl|Picc"), segments as orchidea-analyse gives them, opts a record: 'population 'epochs 'pursuit 'crossover 'mutation 'sparsity 'positive 'negative 'hysteresis 'regularization 'dovetail 'movement 'solutions (the best kept per segment) 'connection ("closest", "best" or "path") 'octaves (the pitch filter widened by octaves) 'styles 'dynamics 'others (lists of names that filter the search space) 'seed 'quiet => a record: 'segments a list, one per segment, each a record ('solutions (list (list cost (list index...)) ...), the best first, an index -1 for a silent player; 'curve the fitness per epoch; 'players the index in the orchestra of each of the solution's slots: the players that had sounds in the search space; 'missing the target's pitches no sound of the orchestra covers; 'used how many players the chosen solution sounds; 'held how many hold their sound on from the segment before ('sustain 1: a player whose pitch the target keeps is not searched again, for at most 'hold seconds); 'space the sounds in the search space), 'choices the connection's solution per segment, 'cache the fitness cache's hits and misses; 'patience (150) stops a search that stalls

(midi-read path)

=> a record: ppq, seconds, tracks (names), and notes (records: track channel pitch velocity at dur), times in seconds after the file's tempo map

(render s "out.wav" "stereo")

writes the mix; layouts: "mono" "stereo" "binaural" "ambi N", a list of speaker azimuths (a ring), or a number of channels (multichannel events as they are)

(play-score s gain)

plays it through live, ahead of the clock (synths compiled, the rest rendered), everything scaled by gain

(display s)

the roll: rows by kind (notes in orchestral order, then files, buffers, synths, calls); WASD and + - 0 navigate in time, hovering shows an event and the time

(score name sr)

a new, empty score at a sample rate

(score-tempo! s bpm) (score-bpm s)

the score's tempo, for times written in beats (60 by default: a beat is a second)

(beat->sec s b)

a time in beats of the score as seconds

(score-reverb! s dry wet)

how much of the score is heard dry and through the hall when it is played (0.7 and 0.3 by default; (score-reverb! s 1 0) plays it dry)

(score-events s) (score-sr s) (score-duration s)

its events (in the order they were added), rate, end time

(event-end e)

when the event ends

(event s at dur what)

add an event; what is a path, a buffer, a note, an instrument, a call, or a function; => the event record (its at and dur can be changed later with put!)

(event-at s at dur what az el)

the same, placed at an azimuth and an elevation (degrees, 0 in front, left positive)

(score-next-id! s)

a fresh event number: ids are never reused, even after events are removed (the roll and score-choose! find events by their id)

(payload->event what)

the event record of a payload (kind and source), without its time

(filename path)

the last part of a path, for labels

(event-gain! e g)

the gain of an event (1 by default); (event-move! e at) (event-length! e dur) (event-place! e az el)

(instrument f params)

a synth event: f a streamable instrument function (gate first), params its parameters as (list (list 'freq 440) ...); the gate is the event's duration

(call f args)

a call event: f applied to args when the score is rendered; its result (a vector or a list of channels) is the sound. A function taking the duration can ask for it: pass 'dur among the args, it is replaced by the event's duration in seconds

(fn-name f)

the name a function prints as, for labels

(load-sound path)

a WAV as (list sr channels), from the cache

(note-sound e sr)

a note's channels at a rate: the file's, shifted by resampling when the pitch was not the recording's; only what the event's duration needs is resampled (a little more for the fade), and the result is kept in the cache under file, shift, rate and length

(clear-sound-cache)

forget the loaded files and the notes made from them

(to-rate channels from to)

channels resampled from one rate to another (nothing to do when equal)

(render-event e sr)

the sound of an event at the score's rate: a list of channels, cut to its duration with a fade at the end when the sound is longer, gain applied

`(fit-duration x dur sr)`

`x` cut to `dur` seconds with a fade-out over the last 20 ms (or a quarter of `dur`), if longer

`(layout-channels layout)`

how many channels a layout has

`(place chans layout az el sr)`

an event's channels into the layout's channels: a mono sound is spatialised at its direction; a sound with as many channels as the layout goes in as it is; anything else is summed to mono first

`(score-render s layout)`

the whole score as channels at its rate; a score placed as an event is rendered into the same layout (its own positions kept), cut to the event's duration with a fade

`(render-buffer s layout)`

the score as channels, in the concert hall as the roll plays it (`score-reverb!`: the dry and wet amounts; (`score-reverb! s 1 0`) renders dry), scaled down when it would clip; the buffer to keep working on; (`score-render s layout`) is the dry mix itself

`(render s path layout)`

`render-buffer` written as a WAV at the score's rate; $\Rightarrow$ the channels

`(render-hall s path)`

the score in the hall, in stereo, as a WAV (the roll's `Render...` button): (`render s path "stereo"`)

`(play-score s gain)`

play the score now (the device is opened if needed) and wait until it ends or is stopped (`stop-score`); gain scales it, with the score's `'level` (0.5 by default: many players at fff add up; the bus limiter catches the rest); the roll's cursor follows

`(play-score-from s gain from)`

the same from a time in seconds

`(bus-hall! sr dry wet)`

the concert hall on the output bus at a rate and mix, set only when it changes (setting it again would cut the tail)

`(score-play-now s gain from)`

start playing and return at once (what the roll's `Play` button does); $\Rightarrow$ the end time on the clock. `stop-score` stops it.

`(azimuth->pan az)`

an azimuth in degrees (0 in front, left positive) as the engine's pan, -1 (left) to 1 (right)

`(score-flatten s depth)`

the score's events with those of the scores inside brought to the top: copies at absolute times, the gains multiplied, cut to their score's event; $\Rightarrow$ a list

(score-hall-mix s sr)

the score rendered in stereo and put in the hall, at a rate; kept in the score (its 'cache) with a signature of the events, so playing again without a change is instant

(score-clear-cache! s)

forget the rendered mix (an event's sound changed in a way the signature cannot see)

(stop-score)

stop whatever score is playing, at once

(score-render-at s layout sr)

the score rendered at a rate other than its own (the device's, when playing)

(score-schedule s gain from)

the live way: every event scheduled on the clock (synths compiled and gated, the rest rendered), no hall; returns at once => (list synth-ids end-clock-time start-clock-time); free the synths when it is over

(instrument-rank instr)

where an instrument code sits in the orchestral order (unknown ones after)

(score-rows s)

the rows of the roll: one per instrument (orchestral order) for the notes, then one per kind: files, buffers, synths, calls; => (list (list label events) ...)

(roll-events s)

the events as the roll shows them: a chord becomes one note per pitch (same id and time)

(score-roll s)

the roll as a figure: rows (name and clef) and bars (row start dur label tip group lane lanes midi dyn id tech cents); pitched events sit on their row's staff, the others on a line; the technique is written above a note where it changes, the tuning in cents when not zero

(register-score s)

remember a score under a number (the roll carries it); => the number

(displayed-score id)

the score registered under a number

(roll-play score-id from)

start a displayed score from a time (the roll's Play button); (roll-stop) stops it; (roll-render score-id path) the score in the hall as a WAV (the roll's Render button)

(roll-save score-id path)

the score's notes as a connection file (the roll's Save button; score-save)

(roll-choose score-id orch seg n)

solution n of segment seg of the orch-th orchestration in a displayed score (the roll's solution menu): the score's notes replaced (score-choose!) and the roll redrawn

`(play-event score-id event-id)`

play one event of a displayed score, alone (a double-click in the roll does this)

`(event-lanes events)`

a lane number per event such that events sharing a lane do not overlap in time

`(display s)`

show the score as a roll: a staff per instrument with note heads and duration lines, a line per other kind; A D pan and + - zoom in time, W S scroll and Z X zoom the rows, R resets; hovering shows an event; a double-click plays it; Play (or Space) plays the score from the cursor (a click in the background places it), Stop stops; the cursor follows any play-score

`(db-load path)`

load a database from its feature file: TinySOL.spectrum.db with the sounds in TinySOL/ next to it (the paths in the file are relative to that folder); when no such folder exists the sounds are looked for next to the file itself. => a record with 'path, 'root (the sounds' folder), 'type, 'block, 'hop, 'ncoeff and 'entries (records: file instr tech pitch dyn other midi features). The sounds are not read: notes open them when rendered or played.

`(db-sounds-folder dir entries)`

where the sounds of a feature file in dir are: the folder next to it (or dir itself) under which the first entry's file exists, whatever the folder is called (TinySOL/, tinysol/, a copy named otherwise); dir when nothing is found (a note then says the sound is missing)

`(db-merge dbs)`

one database out of a list of several, when their features agree (same type and number of coefficients): the entries of all, each remembering its own sounds' folder; a note then draws on every set at once. (db-load (list "a.db" "b.db")) is the same.

`(db-size db) (db-instruments db) (db-techniques db) (db-dynamics db) (db-pitches db)`

what the database holds

`(db-query db instr pitch dyn tech)`

the entries matching the given values; nil matches anything, a list matches any of its members: (db-query db 'Vn nil 'mf nil) every mf violin sound, (db-query db (list 'Vn 'Va) nil (list 'pp 'p) 'ord) quiet upper strings

`(db-grep db pattern)`

the entries whose file name matches a regular expression: (db-grep db "Fl-ord-C.-pp")

`(db-find db text)`

the entries whose file name contains the text: (db-find db "Vn-ord-C5")

`(db-between db instr lo hi)`

the entries of an instrument between two pitches (names or MIDI numbers), inclusive

`(db-nearest db entry n)`

the n entries whose features are closest (euclidean) to an entry's: sounds alike

`(db-available db)`

the entries whose sounds are on disk; `(db-instruments-available db)` their instruments

`(db-techniques-of db instr)`

the techniques an instrument was recorded with (on disk); `(db-dynamics-of db instr)` its dynamics

`(db-range db instr)`

the lowest and highest MIDI note of an instrument, as `(list lo hi)`

`(db-range-available db instr)`

the range of the sounds actually on disk, from the index (fast; what the orchestrators use)

`(db-path db entry)`

the sound file of an entry, on disk: under the sounds' folder at the path the feature file gives when it exists, else found by its file name anywhere under that folder (the folders of a copy may be named otherwise, and a sharp written `#` in the file may be `_` on disk); the path as the file gives it when the sound is not there at all

`(db-available? db entry)`

is the sound file of an entry on disk? (a feature file may describe more sounds than are present)

`(db-features entry)`

the feature vector of an entry

`(db-make folder path type block hop ncoeff)`

analyse every WAV under a folder into a feature file (`db-gen`) and load it

`(db-index! db)`

builds (if not yet) the index: for every instrument, its available pitched entries, grouped by dynamics and technique; note and `db-range` read it, so a large database (FullSOL has tens of thousands of entries) costs a scan once, not per note

`(db-candidates db instr dyn tech)`

the available pitched entries of an instrument with these dynamics and technique; failing that, with the technique; failing that, any of the instrument

`(note db instr pitch dyn tech)`

a note event (pitch a name, "D#5", or a MIDI number): the entry matching instrument, pitch, dynamics and technique, or the nearest available pitch of that instrument (same dynamics and technique when they exist), shifted by resampling to the pitch asked for. Only entries whose sound is on disk are candidates.

`(note-cents! n cents)`

a note's tuning away from its pitch, in cents (shown in the roll; used by the orchestrators that know the target's exact frequencies); the shift by resampling follows it

`(note-path e)`

the sound file of a note event, on disk

(note-duration e)

how long the note's sound is, in seconds (after the shift)

(pitch->name p)

a pitch as a name, whatever was given

(pitch->number p)

a pitch as a MIDI number

(rhythm d ...)

durations in seconds; negative ones are pauses: (rhythm 0.5 0.5 -0.25 1)

(beats bpm r)

a rhythm given in beats, at a tempo

(rhythm-duration r)

how long a rhythm lasts (pauses count)

(chord db instr dyn tech pitches)

a chord payload: the pitches sounding together on one instrument (as many notes, each resolved by note); place it with event, or in a fragment

(notes db instr dyn tech pitches rhythm)

a line: the pitches one after another with the rhythm's durations; the shorter of the two repeats until the longer ends; => a fragment

(chords db instr dyn tech chord-list rhythm)

chords (lists of pitches) one after another, with the rhythm

(line-of items rhythm maker)

the shared engine of notes and chords: items and durations cycled to the longer, maker turns an item into a payload (nil items and negative durations are rests)

(fragment-duration f) (fragment-shift f dt) (fragment-scale f k) (fragment-map f g)

fragments as data: their length, moved in time, stretched (times and durations by k), or every (at dur payload) triple through g

(fragment-repeat f times)

the fragment played times in a row

(fragment-until f secs)

the fragment repeated until secs (the last events cut off), for textures

(add! s at fragment)

place a fragment's events into a score at a time; => the events

(fragment->score name sr fragment)

a score of its own, to place inside another with event

`(texture db instrs dyn tech pitches rhythm scales)`

micropolyphony: one voice per scale factor, each the same line with the rhythm multiplied by its factor, every voice repeating its line until the slowest has played it once; instruments cycled over the voices; => a fragment

`(pivots db instrs dyn tech chord interval rhythm)`

as many lines as the chord has pitches, each wandering at random within +- interval semitones of its pitch, one note per duration of the rhythm; => a fragment

`(chordinterp db instr dyn tech chord1 chord2 rhythm)`

from one chord to another in as many steps as the rhythm has durations, each voice moving by rounded semitone steps (the shorter chord's voices held); => a fragment

`(transpose-pitches pitches n)`

pitches n semitones higher (rests kept); (invert pitches axis) mirrored around a pitch

`(scale-pitches root mode degrees)`

pitches of a scale: root a pitch, mode 'major' 'minor' 'dorian' 'phrygian' 'lydian' 'mixolydian' 'aeolian' 'locrian' 'chromatic' 'whole' 'pentatonic', degrees a list of scale steps (0 = root)

`(add-beats! s beat fragment)`

a fragment whose times are in beats, placed at a beat of the score (its tempo)

`(fragment-gain f from to)`

the events' gains ramped from one value to another along the fragment (a crescendo)

`(fragment-dynamics db f dyns)`

the notes of a fragment re-resolved with dynamics stepping through a list along it

`(fragment-articulate f fraction)`

every event sounding for a fraction of its duration (staccato at 0.3)

`(fragment-thin f p)`

each event kept with probability p

`(fragment-density f curve)`

events kept with a probability read along the fragment from a curve (a list, 0..1)

`(fragment-place f az el)`

the events placed at a direction (kept when added with add!)

`(fragment-snap f field)`

the notes snapped to the nearest pitch of a field (a list of pitches), re-resolved

`(snap-to-field p field)`

the pitch of the field nearest to p

(pitch-field root mode octaves)

every pitch of a scale over some octaves from the root, as a field to snap to

(chord-voicing pitches mode)

a chord revoiced: 'close (as given, sorted), 'open (every other voice up an octave), 'drop2 (the second from the top down an octave), 'spread (each voice an octave above the previous), (list 'invert n) (n inversions: the lowest voices up an octave)

(rotate L n) (retrograde L) (cycle L n) (interleave a b)

series as lists: turned by n, backwards, n elements round and round, alternated

(pitches-from-spectrum x sr n)

the n strongest partials of a sound as MIDI pitches, low to high: a chord from a spectrum, the way spectral music builds one (a harmonic sound gives its harmonic series)

(harmonic-series fundamental n)

the first n partials of a fundamental (a pitch) as MIDI pitches, rounded

(just-cents fundamental pitch n)

the cents a tempered pitch is away from the nearest of the first n partials of a fundamental (a just overtone chord: the 7th partial -31, the 11th -49, the 13th +41, the 14th -31 cents); nil when the pitch is not one of them (within a quarter tone)

(rhythm-from-pattern "x..x.x" step)

a rhythm from a string: x an attack, . a continuation of the step, each step lasting step seconds

(rhythm-augment r k) (rhythm-diminish r k)

every duration multiplied, divided by k

(tuplet n total)

n equal durations filling total seconds (a triplet: (tuplet 3 1))

(polyrhythm ra rb)

the two rhythms extended to a common length (each repeated), => (list ra' rb')

(walk db instrs dyn tech starts step-max rhythm)

random walks: one line per start pitch, each note within step-max semitones of the previous one (pivots stay near a centre; a walk drifts)

(texture-staggered db instrs dyn tech pitches rhythm scales entries)

a texture whose voices enter one after another (entries: a delay in seconds per voice), each repeating until the last has played once

(arpeggio db instr dyn tech pitches spread mode dur)

the chord's notes one after another spread seconds apart, 'up 'down 'updown or 'random, each held for dur; => a fragment

(chordinterp-ease db instr dyn tech c1 c2 rhythm exponent)

chord interpolation with a curve: exponent 1 linear, > 1 slow then fast, < 1 fast then slow

`(chordinterp-sets db instr dyn tech c1 c2 rhythm)`

interpolation between pitch sets: every voice of the first chord goes to the nearest free pitch of the second (no crossing by index), then as `chordinterp`

`(texture-on-chords db instrs dyn tech chord-list rhythm scales)`

a texture whose line runs through the chords in turn (each chord's pitches, then the next), so the micropolyphony moves from one harmony to another: the chord list can come from `chordinterp`'s chords

`(texture-on-pivots db instrs dyn tech chord interval rhythm scales)`

the pivots' lines taken as a texture: every voice wanders around its chord pitch at its own speed

`(orchestrate-line db line rhythm registers dyn tech)`

a line distributed over instruments by register: registers a list of (list instr lo hi); each pitch goes to the first instrument whose range holds it

`(score-map! s f)`

every event through `f` (a function of the event record, returning a record), in place

`(score-instrument s instr)`

the events of an instrument

`(midi->fragment path db instr tech)`

the notes of a MIDI file as a fragment on one instrument, velocities becoming dynamics (pp p mp mf f ff over 0..127); times as the file's tempo map says

`(midi->fragment-by-channel path db instrs tech)`

the same with an instrument per MIDI channel (instrs a list; a channel beyond the list takes the last one), => one fragment

`(velocity->dynamics v)`

a MIDI velocity as one of pp p mp mf f ff

`(midi->score path db instrs tech name)`

a score from a MIDI file, an instrument per channel

`(orchestration method params segments)`

a result record

`(segment at dur solutions)`

a segment: solutions a list of (list cost fragment), best first

`(solutions result k)`

the solutions of segment `k`, best first, as (list cost fragment) pairs

`(solution result k n)`

the fragment of the n-th solution of segment k

(connection result choices)

one solution per segment (choices: an index per segment) joined into a fragment; a note that continues across a boundary on the same instrument at the same pitch is merged

(best-connection result)

the first solution of every segment

(connect! s at result choices)

a connection placed in a score; the score remembers the orchestration, so that the roll (or score-choose!) can put another solution of a segment in its place

(score-choose! s k seg n)

in the k-th orchestration connected into the score (connect!, in order), solution n of segment seg in place of the one chosen: its notes replaced; => the new events

(score-solutions s)

the orchestrations connected into a score, with their segments and the solution chosen in each: a list of (list at (list (list seg-at seg-dur chosen costs) ...)); what the roll shows

(merge-continuations f)

in a fragment, a note starting where a note of the same instrument and pitch ends becomes the continuation of that note (one longer event), as an orchestration's connection does; notes that carry their 'player (the granulator's do) merge only with the same player's

(merge-continuations-within f hold)

the same, a continued note never longer than hold seconds: a player who cannot hold a note that long (an oboe without a breath) starts it again instead

(env t0 v0 t1 v1 ...)

a value changing with time: at each breakpoint a value; between breakpoints a number or a range (list lo hi) is interpolated, and a set (a list of symbols, pitches or chords) is crossfaded: nearer the earlier breakpoint the earlier set is drawn more often. Given as a flat list: (env (list 0 (list 1 2) 10 (list 0.1 0.2)))

(env-at e t)

the value at time t: an interpolated number or range, or a set chosen by the crossfade

(draw-in range)

a random number in a range (or the number itself)

(pick-from set)

a random element of a set (or the value itself when it is not a list of alternatives)

(dynamics-level? v)

is a dynamics parameter a level (a number or a range) rather than a set of labels?

(level->dynamics x)

a level 0..1 as the nearest label of ppp pp p mp mf f ff fff; (dynamics->level d) the reverse

(level->gain x)

a level as a gain, 0.25 at ppp to 1 at fff (the sample carries the timbre of its dynamics, the gain the finer steps between the recorded ones)

(orchestra spec)

the players: spec a list where a symbol is one player of that instrument, a string with | is one player alternating between instruments (an ossia: "Fl|Picc"), and a list is a group of players scheduled together (paired): (orchestra (list 'Fl 'Fl "Ob|EH" (list 'Vn 'Vc))) => a list of player records: instrs, group, and the state the granulator keeps for each (busy-until, last-pitch, last-tech, seat)

(orchestra-rest! orch)

every player free again and its memory cleared (the last pitch, the technique, the seat): for a run of granulators that share one orchestra ('continue) when a new piece begins

(orchestra-size orch)

how many players; (orchestra-instruments orch) every instrument they can play

(orchestra-range db orch)

the lowest and highest MIDI pitch any instrument of the orchestra was recorded at (on disk); (orchestra-octaves db orch) the same as octaves, the granulator's register unit: what to clip a band taken from a recording to, so that it asks nothing the orchestra cannot play

(instrument-family instr)

'winds 'brass 'percussion 'keyboard 'plucked or 'strings by the instrument code (the orchestral order); 'other for a code it does not know. What a 'balance may be given by

(balance-gain balance instr)

the gain of an instrument under a 'balance: a record from instrument codes or families to decibels, (record (list 'brass -6 'Hn -3)): the instrument's own entry, else its family's, else 0 dB; => a linear gain

(orchestrate-granular db orch secs params)

orchestration as granular synthesis: a stochastic process realised by the players of an orchestra, never more at once than there are players, each event a note that a player of the orchestra can play as recorded (the pitch, the technique, and with 'dynamics-strict the dynamics, are those of a sample of the instrument: the constraints select and are never relaxed; what no player can play is reported and left out). params is a record; every parameter may be an env (see env) or a fixed value: 'density events per second, a range: (env (list 0 (list 4 6) 10 (list 0.5 1))) 'group-density one density per paired group of the orchestra (a list, in the order of the groups): the event's rate is their sum and the event goes to a group with a probability proportional to its rate; players outside any group keep 'density 'register octaves, a range: (env (list 0 (list 3 3) 10 (list 3 6))) (octave 4 holds middle C) 'duration seconds, a range (default (list 0.2 1)); 'duration-law how it is drawn in the range: 'uniform (default), 'log (log-uniform: as many short as long by ratio, a granular texture), or a number, the exponent of the draw (2: mostly short, near the minimum; 0.5: mostly long) 'styles a set of techniques: (env (list 0 (list 'ord) 10 (list 'pizz 'flatt))); each player takes one of the set it has samples of in the register 'dynamics a set of labels, (env (list 0 (list 'pp) 10 (list 'ff))), crossfaded by chance; or a level from 0 (ppp) to 1 (fff), a number or a range, interpolated: (env (list 0 0 40 1)) is a continuous crescendo, mapped to the scale ppp pp p mp mf f ff fff for the sample and to a gain for the rest 'dynamics-strict 1: the dynamics is a constraint like the technique: a player must have a sample at the dynamics asked for (0 by default: the nearest recorded dynamics is taken and the substitution counted in the report) 'balance a record from instrument codes or families ('strings 'winds 'brass 'percussion 'keyboard 'plucked) to decibels, added to every note of them: (record (list 'brass -6 'Hn -3)) keeps the brass under the strings at the same marking 'chords a set of chords (lists of pitches), or nil: any pitch of the register 'chord-weight 0..1: how often a pitch comes from the chord rather than from the whole register (1 by default); an envelope from 1 to 0 dissolves a chord into a cloud gradually 'method how a pitch is chosen: 'random (in the register, or of the chord), 'cluster (every pitch of the band once before any is repeated: the players between them saturate the band chromatically, as in a Ligeti cluster), 'pivots (each player around its chord pitch, within 'interval semitones), 'chordinterp (between the chords of the envelope, voice by voice, as time passes), 'markov (from 'markov-score: a score whose lines train a transition table per instrument), 'harmonic (a partial of 'fundamental with probability 'harmonicity, else random; with 'just 1 the partials are tuned in just intonation, the note carrying its cents (just-cents): an overtone chord) 'weight -1..1: where in the band the pitches fall: 0 evenly (default), towards 1 the middle of the band more often, towards -1 its edges; 'tilt -1..1 the same between the bottom (-1) and the top (1) 'leap semitones: a player's next pitch is within this interval of its last one when it has samples there (2: chromatic lines, a micropolyphony; nil, the default: anywhere in the band); a signed range (list -3 -1) is a direction: each next pitch one to three semitones below the last, a descending line that starts again anywhere (at the top, with 'tilt) when it runs out of band 'inertia 0..1: how often a player keeps the technique of its last note when the set still holds it (0 by default: drawn anew at every note; 0.9: a player changes bowing rarely) 'seat seconds: an ossia player that has taken an instrument keeps it at least this long (a person playing one instrument), and is only eligible for what that instrument can play meanwhile; 0 (default): the band decides the instrument at every note; a large value: a fixed seating for the whole process 'spread seconds: the players of a paired group struck together are scattered within this time (0.03: an orchestra's attack rather than a sampler's); 0 by default 'polyphony how many players may sound at once at most (an envelope; the orchestra's size by default) 'steal in the 'target method (1 by default): when an event is due and no player is free, the oldest note ends and gives up its player, so the target's density is honoured 'coupling 0..1: how often a paired group actually sounds together (1: always; 0: its players independent), an envelope makes an orchestra synchronised at first and free later, or the reverse 'continue 1: the orchestra's own player records carry the state (every note booked so far, last pitches, seats) into this call and out of it, so a run of granulators placed one after another, or overlapping, in any order, share one orchestra and never book a player twice (a note is cut where the player's next booking begins); give 'start, the time in the piece this call begins at, so the bookings compare (orchestra-rest! clears the state) 'solutions how many realisations to make (default 1), each with its own random draws => an orchestration result with one segment; (best-connection result) is its fragment; (get result 'report) the run's report (granulation-report prints it): events due, events that wrote notes and the notes written (a paired group writes several a event), events skipped because every able player was busy (the saturation), events unplayable by the orchestra, dynamics substituted, and each player's notes and busy fraction; 'reports one per solution

`(value-at v t)`

an env at a time, or the value itself; (param-at params key t default) the same for a parameter

`(draw-duration range law)`

a duration drawn in a range by a law: 'uniform, 'log (log-uniform), or an exponent

`(pick-weighted items f)`

a random element, each weighed by f (a non-negative number per element)

`(band-weigher lo hi weight tilt)`

the weight of a pitch in the band lo..hi (MIDI) under 'weight (middle vs edges) and 'tilt (bottom vs top); => a function of the pitch

`(granulation-report result)`

a granular orchestration's report printed: the events due and written, the saturation (events skipped with every able player busy), the unplayable ones, the dynamics substituted, and every player's notes and busy fraction; => the report record

`(db-pitches-of db instr tech)`

the MIDI pitches an instrument was recorded at with a technique (any dynamics), sorted; tech nil: with any technique. From the index, kept once computed. What a granulated player may be asked to play: a real player's pitch is one the database proves.

`(db-pitches-at db instr tech dyn)`

the MIDI pitches an instrument was recorded at with a technique at one dynamics (nil: any dynamics; tech nil: any technique), sorted; what a strict granulator draws from

`(instrument-has? db instr tech dyn lo hi)`

has an instrument samples with a technique (and, dyn given, at that dynamics) inside lo..hi (MIDI)? (a vector test: what the granulator asks hundreds of times an event)

`(player-styles db player styles dyn lo hi)`

the styles of a set a player has samples of inside lo..hi (MIDI), at a dynamics when one is given (nil: any): what the event's style set leaves this player; empty when it can play none of them there

`(player-pitches db player tech dyn lo hi)`

the pitches a player may be given for an event: the samples of its instruments with the technique asked for (and the dynamics, when one is given), inside the register lo..hi (MIDI); the constraints select, they are never relaxed: an empty list means this player cannot play what the event asks for (no instrument of it was recorded so in that range) and the event goes to another player; => a sorted list

`(markov-table s)`

transitions learnt from a score's notes: a record from a pitch to the list of pitches that followed it (per instrument, in time order); repeated followers weigh more

`(target-analyse x sr block hop)`

what a morphological orchestration reads off a sound, computed once: the frame spectra (block as the database's features, so a frame and a sound's spectrum compare), the attacks (the peaks of the spectral flux) and their density in events a second, the register (the centroid in MIDI pitch, the spread around it in octaves, the lowest strong partial) and the loudness in dB, each a curve sampled every hop; => a record ('sr 'block 'hop 'seconds 'times 'spectra 'fine 'attacks 'density 'centroid 'spread 'low 'loudness); 'fine holds a second set of frame spectra with a long window ('fine-block, 8192: 5 Hz bins at 44.1 kHz) from which the peaks are read, since the database's block tells a low note's pitch too coarsely. (target-analyse-with x sr block hop opts) the same with options: 'threshold (2: a flux peak counts above this times the local median; 1.5 counts the ripples of a held sound too), 'window (1 s: the span the density is counted over), 'fine

(moving-median v n)

each value replaced by the median of the n around it

(target-frame target t)

the index of the frame at a time; (target-at target key t) a curve's value at a time

(target-spectrum target k n)

the spectrum of frame k, its first n bins (a database may keep fewer coefficients than the block gives)

(target-now target t n look)

the target's spectrum at t as the pursuit sees it: the frames from t over the next look seconds averaged (0.1 s: the attack's smear evened out, the frequencies of what starts read from the sound settled), the first n bins

(target-level target t range)

the loudness at t as a dynamics level 0..1: 1 at the target's loudest point, 0 at range dB under it (40 by default)

(curve->env times values step maker)

an env from a curve: one breakpoint every step seconds (the values averaged over the step), each passed through maker (a number or a range out)

(target-envelopes target opts)

the granulator's envelopes from a target's curves: 'density from the flux peaks a second times 'density-scale (1: as the target; 2 twice as busy), at least 'min-density (0.5: a held sound is re-attacked now and then), 'register from the centroid and the spread (centroid $\pm$ 'width times the spread, in octaves, extended down to the lowest strong partial: a bass note lies under the centroid of its own spectrum), 'dynamics as a level from the loudness (target-level, 'range dB); opts also 'step (seconds per breakpoint, 0.25)

(target-peaks target t n)

the frequencies (Hz) of the n strongest spectral peaks of the target at t (the fine frames over the next 0.1 s averaged), above 30 Hz and a twentieth of the strongest, each refined by a parabola: the pitches the notes may take, as the partials of a sound are the pitches an orchestra can double it with; => a vector

(entry-atom e)

a database entry's spectrum in the pursuit's space, kept on the entry once computed

(entry-f0 e sr block)

the frequency a database entry actually sounds at: the peak of its average spectrum nearest its nominal pitch (within a semitone, refined by a parabola), kept on the entry; the nominal frequency when the spectrum has no peak there. sr and block as the features were computed

(target-dictionary db peaks players lo hi dyn styles)

the sounds a pursuit may draw on: for every player the available sounds of its instruments whose pitch is one of the target's peaks (frequencies; within 60 cents) and within lo..hi (MIDI), with the dynamics dyn (any when the instrument has not got it) and one of the styles (all when nil); => a list of (list player entry)

(db-by-midi! slot)

an instrument's index slot grouped by MIDI pitch (built once): a record from the pitch (as a string) to its entries

(pursuit-space m)

a magnitude spectrum as the pursuit compares it: its square root, so that the quieter notes of a chord weigh against the loudest one (in the linear magnitudes one strong partial decides everything; in the log the noise between the partials does)

(target-residual target t sounding n)

the target's spectrum at t (its first n bins, in the pursuit's space) less what the sounding notes account for (their spectra refitted to the frame together, weights non-negative); => (list residual frame)

(atom-persistence target features t persist max-length)

how long a sound goes on being part of the target from t: the frames ahead in which the target still holds it (the projection of the frame on the sound's spectrum, in the linear magnitudes, stays at least persist of its peak within the first 0.1 s: 0.5 is 6 dB down), in seconds up to max-length; the length of a note whose sound the target keeps, short for one it drops

(technique-short? t)

does a technique name belong to the short ones?

(target-notes db target t free sounding params)

the notes to start at time t on the free players: the target's spectrum now less what still sounds (target-residual), pursued (mp, non-negative) over the players' sounds at the target's peaks (target-dictionary: the register and the dynamics of the moment narrow it); the best atom always makes a note, further ones ('voices at most) when each accounts for 'min-gain of the residual; when the sounding notes leave less than 'floor of the spectrum the pursuit is over the whole spectrum instead (a doubling). Each note lasts as long as the target holds its sound (atom-persistence, 'persist, 'max-length), at least 'min-length, and a short life takes a short technique of the same sound when there is one ('short); its tuning is the nearest peak's, in cents; => a list of (list player note dur)

(target-note-of db target t e residual peaks level dyn params)

the note a morphological orchestration makes of a database entry chosen at time t: as long as the target holds the sound (atom-persistence), a short technique of the same sound when its life is short, at the target's level, tuned to the nearest peak; => (list note life)

(target-notes-genetic db target t free sounding params)

the same decision as target-notes, but made by Orchidea's search instead of a greedy pursuit: at each event a genetic search over the free players' sounds at the target's peaks (the dictionary of the moment) looks for the combination, one sound per free player or a rest, whose summed spectrum is nearest the target's now, less what still sounds (the residual): the mimetic decision inside the morphological clock, no segmentation, the durations from persistence. 'genetic is a record of the search's parameters (population 60, epochs 40, sparsity 0.1, and the others of orchestrate-mimetic); => a list of (list player note dur)

(orchestrate-morphological db orch target params)

orchestration as granular synthesis whose process is read off a target sound (target-analyse), no segmentation: the density of the flux peaks gives the events a second, the centroid and the spread the register, the loudness the dynamics (target-envelopes); at every event a matching pursuit over the free players' sounds at the target's spectral peaks picks instrument, pitch and technique for the target's spectrum at that instant, less what already sounds (target-notes), and each note lasts as long as the target keeps its sound (atom-persistence). When every player is busy and an event is due, the oldest note gives way ('steal, 1 by default). params: 'voices (2: notes an event may start), 'min-gain (0.2), 'floor (0.2), 'persist (0.5), 'min-length (0.1), 'max-length (8), 'short (0.4), 'width (1: the register's width in spreads), 'range (40 dB: the dynamics' span), 'density-scale (1), 'min-density (0.5), 'step, 'styles (the techniques allowed; all by default), 'solutions, 'trace (1: every atom considered is printed), and 'density, 'register, 'dynamics or 'duration of your own in place of the target's; 'decision ('pursuit, the greedy matching pursuit, or 'genetic: at each event Orchidea's search over the free players' sounds for the combination nearest the residual, one sound per player or a rest, the mimetic decision inside the morphological clock; its parameters in 'genetic, a record: population 60, epochs 40, sparsity 0.1, patience 20, and the others of orchestrate-mimetic)

(chordinterp-env chords rhythm)

an env for 'chords that steps through chordinterp's chords over time: chords a list of two chords, rhythm the times; use with 'method 'chordinterp (or 'random)

(score-validate s orch)

checks a score against an orchestra, as a copyist would: at every moment each sounding note must have a player of its own able to play its instrument (an ossia player "Vn|Va" counts for either, a paired group is just players), and every note must be at a pitch the instrument was recorded at (a shifted note is one the database does not prove). Notes of scores inside the score count too. => a record: 'ok; 'overbooked the moments where the players ran out, each (list at instr sounding), one per note that had no player; 'transposed the notes with a shift, (list at instr pitch shift); 'peak how many notes of each instrument sounded at once at most, a record; 'players the orchestra's size. (validation-print r) prints it

(validation-print r)

a validation printed: playable or not, and why not

(mimetic-target db x sr params)

the target analysed: x a vector (a sound read with read-wav, a rendered score, a synthesis) at sr; params a record: 'segmentation ('flux: at the peaks of the spectral flux above 'threshold (2; above 1 no peak passes: one segment, a static target) and at least a 'timegate apart (0.1 s); 'adaptive: the peaks of the flux against their local median (flux-peaks, 'ratio 2: twice the median), so the sensitivity follows the sound rather than its loudest attack; 'frames: every block; 'none: one segment; or a list of onsets in seconds), 'partials-window (32768: the window the pitches are read with; large for a low target), 'partials (0.2: the threshold on the partials, 0.1; 0: no pitch filter, every sound of the database may serve: for noisy targets), 'extra-pitches (names added to every segment's pitches). => a record ('sr 'seconds 'segments (records: at dur features notes) 'params); (mimetic-print target) prints the segments and their pitches

(note-of-entry db e)

a note event from a database entry itself (the very sound the search chose, not the nearest by pitch and dynamics as note picks)

(mimetic-seating instr)

where an instrument sits, as an azimuth in degrees (left positive): the seating Orchidea's mixes use (violins left, cellos right, the winds in the middle); 0 for one it does not know

(orchestrate-mimetic db orch x sr params)

Orchidea: the target *x* (a vector at *sr*, or a target from *mimetic-target*) orchestrated by the players of *orch* (an orchestra: a symbol is one player, "Fl|Picc" a doubling), one sound per player per segment (or a rest), chosen by the genetic search. *params* is a record (Orchidea's names in brackets): the target 'segmentation' 'threshold' 'timegate' 'partials-window' 'partials' 'extra-pitches' (*mimetic-target*) the search 'population' (*pop_size*, 300), 'epochs' (*max_epochs*, 300), 'pursuit' (0: a random first population; *k*: from the *k* sounds nearest the target per player), 'crossover' (*xover_rate*, 0.8), 'mutation' (*mutation_rate*, 0.01), 'sparsity' (0.001: how often a player is dropped; 0.1 for a single instrument as target), 'positive' and 'negative' (0.5 and 10: the penalizations of a partial the solution has and the target lacks, and the reverse), 'regularization' (0: > 0 sponsors sparse solutions) the space 'styles' 'dynamics' 'others': lists of names; only sounds with one of them enter the search the memory 'hysteresis' (0: > 0 makes each segment's search lean, in timbre, towards the solutions chosen for the segments before, fading by that factor a segment back), 'dovetail' (0: > 0 raises the cost of a candidate by that fraction of the pitches of the previous chosen solution it drops, on any player: pivot notes passed between instruments), 'octaves' (the pitch filter widened: (list 0 -1) admits the partials' pitches and the octave below), 'hold' (seconds: a note continued across segments on the same player and pitch is never longer; the player starts it again) the result 'solutions' (10: the best kept per segment), 'connection' ('closest: each segment's solution nearest, in timbre, to the one chosen for the segment before, Orchidea's; 'best: the best of each; 'path: the shortest path through the solutions, each costing its distance from its segment's best in percent plus 'movement' (1) per semitone a player moves, or per player that starts or stops: the least melodic movement, the continuity of lines; chosen at the end, so 'sustain is off with it), 'sustain' (1: a player whose pitch the target keeps holds its very sound on into the next segment, fixed in every chromosome, so the search fills only what changed and a held chord comes out as long notes; 0: every segment searched afresh), 'patience' (150: epochs without a better population before a search stops), 'seating' (1: the notes placed as Orchidea's mixes seat the orchestra; 0: centred), 'seed', 'quiet' (1: no progress) => an orchestration result ('mimetic) whose segments hold the ranked solutions as (list cost fragment), each fragment the notes at their time in the target (the very sounds chosen, at the target's cents, with 'player the player's index); 'choices the connection's solution per segment, (*mimetic-connection* result) that connection as a fragment, (*best-connection* result) the best of each; 'target the analysed target; 'curves the fitness per epoch of each segment. *connect!* places a connection in a score (a note continued across a boundary on the same player and pitch becomes one longer note)

(mimetic-report result)

a mimetic orchestration's report printed, a line per segment: its time, the cost of its best solution, the players the chosen solution sounds and those holding their sound on from the segment before, the sounds in its search space, and the target's pitches no instrument of the orchestra covers (where a segment sounds thin, this says why); => the report (*result* 'report)

(mimetic-connection result)

the connection Orchidea chose (*result* 'choices) as a fragment; (*connect!* s at *result* (*get result* 'choices)) places it

(solution-print result k)

the solutions of segment *k* printed, with their costs and sounds

`(score-save s path)`

write the score's notes as a connection; => the number of notes written

`(score-load db path name)`

a score from a connection file, its notes' sounds from db; => the score

`(note-from-file db file instr pitch dyn tech)`

a note whose sound is the database entry with that file name (the folder may differ); when the file is not there, the note by its fields; an unpitched sound (pitch N) as a file event

`(score-shift! s dt) (score-scale! s f)`

every event moved by dt seconds; every onset and duration multiplied by f

`(score-select s f)`

the events for which f holds

`(score-sort! s)`

the events ordered by onset

`(score-remove! s e)`

an event taken out

`(score-merge s1 s2)`

a new score with the events of both (s2's after s1's end when shifted with score-shift!)

`(score-print s)`

the events, one line each

6.8 plot

A figure is `(list title layers options)`; `plot.mu` builds it and `show` opens it in a window of its own and returns, from the command line and from the IDE alike; the interpreter keeps the windows alive while it waits or sleeps, so several plots can be open while a program goes on, and a script that ends with windows open stays until they are closed. `save-png` writes a file. `subplots` puts several figures in one grid. Keys in a window: +/- zoom, W A S D pan, arrows orbit a surface, 0 or r reset, e exports a PNG under an automatic name, Esc or q closes; the mouse drags to pan or orbit, the wheel zooms; the **Export...** button asks for a file name and writes the figure as shown. Layers are lines, points, bars, an image (a matrix as a heat map) or a surface (a matrix in 3D). The one-call helpers build and show in one go; the ready-made figures know about signals and data.

```
load "plot.mu"
var fig (figure "two sines")
add-line fig nil (sin (/ (range 100) 8)) "sin"
add-line fig nil (cos (/ (range 100) 8)) "cos"
set-labels fig "sample" "value"
show fig
save-png (spectrogram x sr 1024 256) "/tmp/spec.png"
show (scatter-clusters petals (kmeans-labels km) 3)
```

`(save-png fig path [w h])`

render a figure to a PNG file (900 x 560 by default)

`(show fig [w h])`

open the figure in a window of its own and return; the program goes on and the window stays (the idle hook keeps it alive); several can be open. Skipped when `MUSIL_NOSHOW` is set.

`(plot-windows)`

=> how many plot windows are open; `(close-plots)` closes them

`(roll-refresh fig)`

the roll windows showing a score take a new figure of it (`score-roll`), keeping their view: what `roll-choose` calls after replacing a segment's notes

`(figure title)`

an empty figure

`(fig-title fig) (fig-layers fig) (fig-options fig)`

the three parts of a figure

`(fig-layers fig)`

the layers

`(fig-options fig)`

the options

`(add-line fig x y label)`

x may be nil to use 0, 1, 2, ...

`(add-scatter fig x y label)`

points; `(add-bars fig x y label) bars`

`(add-bars fig x y label)`

bars

`(add-image fig M)`

a matrix as a heat map, row 0 at the bottom

`(add-surface fig M)`

a matrix as a 3D surface (a figure with a surface shows only that)

`(add-layer fig layer)`

add a raw layer (list kind data ...)

`(x-or-index x y)`

x, or 0 1 2 ... when x is nil

(set-option fig key value)

keys: "xlabel" "ylabel" "xmin" "xmax" "ymin" "ymax"

(set-labels fig xlabel ylabel)

axis labels; (set-xrange fig lo hi) (set-yrange fig lo hi) axis limits

(set-xrange fig lo hi)

x-axis limits

(set-yrange fig lo hi)

y-axis limits

(subplots title figs rows cols)

a grid of figures, drawn together; rows or cols may be 0 (auto)

(add-subplot fig sub)

add one more figure to a grid

(plot y)

or (plot-xy x y) a line

(plot-xy x y)

a line of y against x

(plot-lines ys labels)

several lines sharing the index axis

(scatter x y) (bars y) (image M) (surface M)

build and show a one-layer figure

(bars y)

build and show a bar chart

(image M)

build and show a heat map

(surface M)

build and show a 3D surface

(waveform x sr)

a signal against time in seconds

(spectrum x sr)

magnitude spectrum in dB against frequency

(spectrogram x sr n hop)

STFT magnitudes in dB as an image: time along x, frequency along y

(scatter-clusters X labels k)

the rows of an n x 2 matrix coloured by cluster

(histogram-figure v bins)

a bar chart of (histogram v bins)

7 Extending Musil from C++

The interpreter is one header. A host includes it, registers functions, and runs code:

```
#include "musil.h"
musil::Interp I;
musil::make_env(I);                                // the C++ halves of the
                                                    libraries
I.def("hello", [](musil::vlist& a, musil::Interp& i) -> musil::vpstr {
    return musil::v_str("hello, " + i.str(a[0]));
}, 1, 1);                                           // name, function, min and
                                                    max arguments
I.run("print (hello \"world\")");
```

A builtin receives its evaluated arguments as a `vlist` and the interpreter. `eval` has already checked the argument count. Inside, `i.num(v)`, `i.scalar(v)`, `i.index(v)`, `i.str(v)`, `i.list(v)` and `i.fn(v)` return the payload or raise a Musil error naming the builtin; `i.bad("message")` raises one with your text. Values are made with `v_num`, `v_arr`, `v_str`, `v_list`; `i.call_fn(f, args)` calls a Musil function; `i.yield_fn` is called every 1024 evaluations for hosts that service an event loop.

Document a builtin with a comment above it in the form `// (name args) description`; `tools/gendoc.py` turns those comments into `help.txt` and into this manual. A library is complete when it has `name.h`, `name.mu`, `tests/test_name.mu` and `examples/reference_name.mu`.

8 Examples

All in `examples/`, all run by `ctest`. Run them from that directory.

```
reference*.mu
hello, if, while, procs, math, strings, arrays, files
music_demo.mu
chords.mu
matrices.mu, iris.mu
stft, filters, reverb, cross_synth, additive, features
phase_vocoder.mu
plots.mu, iris_plot.mu
live_play.mu, live_chorale.mu, live_probe.mu
live_synth.mu, live_offline.mu
live_loops.mu, live_controls.mu, live_session.mu
live_house.mu, live_techno.mu, live_trance.mu
onsets.mu, transients.mu
spatial.mu, flyby.mu, flyby_controls.mu, live_spatial.mu
nmf.mu, make_audio_demos.mu
simple_score.mu, loaddb.mu, random_music.mu, random_collage.mu
score_in_score.mu, algorithmic_comp.mu
gran_orchestration.mu, gran_orchestration2.mu, gran_orchestration3.mu, haas.mu, static_orchidea.mu
bootstrap.mu
```
