

5 Unique HTML Tags



Abdul Rehman
@abdul-rehman2



<kbd>

The <kbd> tag is used to define keyboard input. The content inside is displayed in the browser's default monospace font.



```
<p>  
  Press <kbd>CMD</kbd> + <kbd>P</kbd> to print.  
</p>
```

Output

Press CMD + P to print.



Abdul Rehman
@abdul-rehman2



<address>

This tag defines the contact info for the author/owner of a document or an article.

```
<address>
  Glen Stansberry
  1234 Web Dev Lane
  Anywhere, USA
</address>
```

Output

Glen Stansberry 1234 Web Dev Lane Anywhere, USA



Abdul Rehman
@abdul-rehman2



<mark>

This tag is used to highlight a piece of info that is very important and needs attention.



Follow `<mark>@DevWithSaad</mark>` for more such content.

Output

Follow **@DevWithSaad** for more such content.



Abdul Rehman
@abdul-rehman2




<meter>

The <meter> tag is used to define a scale for measuring in a specific range and can also handle fractional values.



```
<p>  
  Low storage space  
  <meter optimum="40" high="80" max="100" value="20">  
    85%  
  </meter>  
</p>
```

Output

Low storage space 



Abdul Rehman
@abdul-rehman2



<progress>

The HTML < progress> tag is used to show how far work has progressed.



```
<div>  
  Progress: <progress value="750" max="1000"></progress>  
</div>
```

Output

Progress: 



Abdul Rehman
@abdul-rehman2



Did you Find it Useful?



Abdul Rehman
@abdul-rehman2

Follow For More !