



**VectorBlox**  
embedded supercomputing

# VectorBlox MXP Quickstart for MXP Simulator

# Contents

<b>1</b>	<b>Installation</b>	<b>3</b>
1.1	Prerequisites . . . . .	3
1.2	Installing . . . . .	3
<b>2</b>	<b>Software</b>	<b>4</b>
2.1	Running the software . . . . .	4

# 1 Installation

This guide describes installing VectorBlox MXP Simulation Library to run on an x86\_64 host compiling with GCC

## 1.1 Prerequisites

Before you begin, make sure you have:

- GCC installed. Your native compiler should work on any linux workstation. On Windows you want to install [mingw-w64](#) (Note that this is not to be confused with mingw from mingw.org, though you may want to download some utilities from that project such as GNU Make )
- (Windows Only) A unix-like environment we recommend msys from [mingw](#). But make sure that the gcc command still points to the compiler described in the point above.

## 1.2 Installing

- There is no need to install the simulator, just remember where it is when you link to the library. This is done automatically in the example makefiles.
- To use the License File set the environment variable `export VECTORBLOX_SIM_LICENSE=/path/to/license`

## 2 Software

This section describes how to compile and run software when linked to the simulator.

The string **EXAMPLES** refers to the `examples` subdirectory of the extracted release.

### 2.1 Running the software

#### 1. Make the executable

Navigate to a test application such as `vbw_vec_add_t`, located in `EXAMPLES/software/bmark/vbw_vec_add_t`.

```
make clean_all all SIMULATOR=true
```

This command builds the `vbxapi` and `vbxsim` libraries, the `test.c`, and then links them.

Note that we used the `clean_all` target first to ensure that any libraries that might have been compiled for a different target in the past were cleaned and re-compiled. If you know that the libraries were already compiled for the correct target, you can omit the `clean_all` target.

#### 2. Execute the generated program

In order to execute the program that you just created make sure the environment variable `VECTOR_BLOX_SIM_LICENSE` points to the correct path, and it is exported (child processes will inherit the value). Then run the program with the command `./test.elf`