

Peptide Self-Assembly Design Code User Manual

Running the code:

1. Prepare input structure

To run the Peptide Self Assembly (PepSAD) code the first step is to build the initial coordinate file (PDB format) of the desired structure. The structure can be constructed in a molecule design package like Discovery Studio 3.5. Once the desired structure is built, it should be relaxed by running a short molecular dynamics simulation using a molecular dynamics package to eliminate unfavourable atomic overlaps.

Save the PDB file as comp.pdb. Add N and C to the terminal amino acids of each peptide (for example, NHIE). Delete TER lines.

2. Edit the input file

The input file looks like the following. The input file can be edited as per the requirements of the project

filename Name of the initial input structure file, (e.g. : comp.pdb)	recalcu_switch Equal to zero if starting from the original pdb file (eg: comp.pdb); equal to 1 if restarting from another file		
nstep_start The starting step number	nstep_terminal The final step number (typically 10000)		
idum The seed for the random number	ekt A value determined empirically determined (typically ≤ 1) for each project. It is referred to as $kT_{sequence}$.		
fpho No. of hydrophobic residues	fpol No. of hydrophilic residues	fchg No. of charged residues	foth No. of charged residues
num4category(i) Sheet number for a β sheet type structure			
peptideID(i) Peptide number on the sheet (i)	peptideID(i+1) Peptide number on the sheet (i)	peptideID(i+2) Peptide number on the sheet (i)	peptideID(i+3) Peptide number on the sheet (i)

3. Submitting the job

To be able to submit a PepSAD join the following files should be present in the directory:

- main.f90 (Main code file)
- comp.pdb (starting input structure file)

- c. lib folder (directory containing the amber forcefield data)
- d. pdbfiles (an empty directory where the PDB files from the design will be stored)

Once all the above files are present in the directory the main.f90 code can be compiled using a fortran compiler and the job can be submitted. An example of a command that can be used to compile the code using the ifort compiler:

```
ifort -O3 -r8 -o main main.f90
```

Details of PepSAD output files

energydetails.txt

step	attempt	score	binding energy	entropy	score4hydration	$P_{aggregation}$	Type of move:
							Not SCMF: Residue mutation
							Intra SCMF: Intra chain residue exchange

energyprofile.txt

step	score	binding energy	entropy	score4hydration	$P_{aggregation}$
------	-------	----------------	---------	-----------------	-------------------

minimumenergy.txt

step	attempt	score
------	---------	-------