

React

What's the big deal?

No seriously, what's the big deal

Quinn Stephens



<https://github.com/QuinnStephens/code-platoon-intro-to-react>

What is React?

- A Javascript library for creating views
- That's it

What makes React special*

- Components
- JSX
- The diffing algorithm
- The ecosystem

Components

Break up your UI into small pieces

Let them focus on one thing

JSX

A Frankenstein's monster of HTML and
JavaScript

(but a good monster)

JSX is optional

But it's much nicer than
the alternative

```
<div className="profile">
  <img src={ user.avatarUrl }/>
  <h1>{ user.name }</h1>
  <h2>{ user.city }</h2>
</div>
```

```
React.createElement(
  "div",
  { className: "profile" },
  React.createElement(
    "img",
    { src: user.avatarUrl }),
  React.createElement(
    "h1",
    null,
    user.name),
  React.createElement(
    "h2",
    null,
    user.city))
```

The diffing algorithm

Data changes. UI updates.

No thinking required

The rest is up to you

- React is not a framework but a set of tools
- React is just the view layer
- Structure for the app comes from other tools...
 - React frameworks (Redux)
 - Backend frameworks (Rails, Node, et al)
- ...but this is changing
 - Context
 - Hooks

Let's see an example!

- Open the source of project you created with `create-react-app`
- Run `npm start` in the terminal from your project's root
-- (You can also use `yarn start`)

Edit the text

Watch the diff engine at work.

Don't bother reloading

Edit the style

- Normal CSS, except...
- Use `className` instead of `class`

Replace text with a variable

Move the header into its own
component

Pass the variable into the
component as a prop

Props are **external** values that are passed into
the component

Pass in a callback function as a prop

- Add a button
- Add a prop to show a simple alert in the parent component

Move the `text` variable to state

State is a set of **internal** values managed
within the component

Update the state on button press

- Don't change the state directly!
- `setState` is async

Questions?

Your turn: Create a click counter

- Keep the counter value in the App state
- Update the counter value through a button press



My counter app

24

Add to count

Let's make a simple form

- Single text field
- Update state on change

Add a submit button

- Show an alert with the value

Conditionally show components

- Only show a component once the user has submitted

Your turn—do some more conditional logic

- Only show a component if the user has entered more than a certain number of characters

Component lifecycle methods

- `constructor`
- `componentWillMount` / `componentDidMount`
- `componentWillUnmount`
- `UNSAFE_componentWillReceiveProps`
- `componentDidUpdate`
- `shouldComponentUpdate`

Let's make an API call

- Fetch within `componentDidMount` and update state on response
- URL: <https://jsonplaceholder.typicode.com/photos/1>

Your turn: Show a loading state
before the call finishes

Thank you for coming!

Quinn Stephens



<https://github.com/QuinnStephens/code-platoon-intro-to-react>