Table 1: **Leave-one-video-out prediction with training-only outcome scaling.** Panels A and B show mean RMSE across 28 held-video folds in original outcome units and training-fold standard-deviation units, respectively. Panel C compares rating-only and combined models against the assigned-label model using original-unit fold errors. Tests are paired two-sided Wilcoxon comparisons across held videos, with BH correction across the 12 comparisons; negative differences favor the first model named.

Panel A. Mean held-video RMSE in original units

Metric	Participant only	Assigned label	Ratings	Combined
PLV	0.0569	0.0572	0.0572	0.0573
PLI	0.0383	0.0385	0.0383	0.0385
wPLI	0.0643	0.0646	0.0644	0.0647
AEC	0.0835	0.0837	0.0837	0.0838
MaxXC	0.0521	0.0523	0.0523	0.0525
Lag (ms)	24.151	24.252	24.142	24.254

Panel B. Mean held-video RMSE in training-SD units

Metric	Participant only	Assigned label	Ratings	Combined
PLV	1.124	1.132	1.123	1.132
PLI	1.128	1.133	1.128	1.133
wPLI	1.100	1.106	1.100	1.106
AEC	1.120	1.125	1.121	1.125
MaxXC	1.118	1.124	1.117	1.123
Lag	1.084	1.088	1.084	1.088

Panel C. Paired comparisons in original units

Metric	Comparison	Mean difference	Median difference	p	BH–FDR q
PLV	rating − label	0.000018	0.000139	0.695	0.884
PLV	combined − label	0.000148	0.000129	0.070	0.611
PLI	rating − label	-0.000179	-0.000116	0.245	0.611
PLI	combined − label	0.000015	0.000008	0.451	0.761
wPLI	rating − label	-0.000270	-0.000136	0.316	0.632
wPLI	combined − label	0.000019	0.000033	0.508	0.761
AEC	rating − label	0.000013	-0.000280	0.884	0.884
AEC	combined − label	0.000135	0.000180	0.255	0.611
MaxXC	rating − label	0.000017	0.000080	0.867	0.884
MaxXC	combined − label	0.000144	0.000093	0.186	0.611
Lag	rating − label	-0.1101	-0.0565	0.218	0.611
Lag	combined − label	0.0019	-0.0032	0.779	0.884

Predictions were transformed back to original units for Panels A and C; Lag is in milliseconds and the other outcomes are dimensionless. Outcome means and population SDs were fitted separately for each participant using 27 training videos. One participant had constant Lag; a scale of one original unit was used in its 28 folds, without dropping observations. No comparison survived BH correction using training-SD errors either (all $q \geq 0.179$). Correcting jointly across both scales (24 tests) also yielded no significant comparison. These exploratory fold comparisons use overlapping training sets.