

PHY321: Review of Vectors, Math and first Numerical Examples for simple Motion Problems

Morten Hjorth-Jensen^{1,2}

Scott Pratt¹

Carl Schmidt³

¹Department of Physics and Astronomy and National Superconducting Cyclotron Laboratory, Michigan State University, USA

²Department of Physics, University of Oslo, Norway

³Department of Physics and Astronomy, Michigan State University, USA

Jan 10, 2020

Space, Time, Motion, Reference Frames and Reminder on vectors and other mathematical quantities

Our studies will start with the motion of different types of objects such as a falling ball, a runner, a bicycle etc etc. It means that an object's position in space varies with time. In order to study such systems we need to define

- choice of origin
- choice of the direction of the axes
- choice of positive direction (left-handed or right-handed system of reference)
- choice of units and dimensions

These choices lead to some important questions such as

- is the physics of a system independent of the origin of the axes?
- is the physics independent of the directions of the axes, that is are there privileged axes?
- is the physics independent of the orientation of system?
- is the physics independent of the scale of the length?

Dimension, units and labels. Throughout this course we will use the standardized SI units. The standard unit for length is thus one meter 1m, for mass one kilogram 1kg, for time one second 1s, for force one Newton 1kgm/s^2 and for energy 1 Joule $1\text{kgm}^2\text{s}^{-2}$.

We will use the following notations for various variables (vectors are always boldfaced in these lecture notes):

- position \mathbf{r} , in one dimension we will normally just use x ,
- mass m ,
- time t ,
- velocity \mathbf{v} or just v in one dimension,
- acceleration \mathbf{a} or just a in one dimension,
- momentum \mathbf{p} or just p in one dimension,
- kinetic energy K ,
- potential energy V and
- frequency ω .

More variables will be defined as we need them.

It is also important to keep track of dimensionalities. Don't mix this up with a chosen unit for a given variable. We mark the dimensionality in these lectures as $[a]$, where a is the quantity we are interested in. Thus

- $[\mathbf{r}] = \text{length}$
- $[m] = \text{mass}$
- $[K] = \text{energy}$
- $[t] = \text{time}$
- $[\mathbf{v}] = \text{length over time}$
- $[\mathbf{a}] = \text{length over time squared}$
- $[\mathbf{p}] = \text{mass times length over time}$
- $[\omega] = 1/\text{time}$

Elements of Vector Algebra

Using the fact that multiplication of reals is distributive we can show that

$$\mathbf{a}(\mathbf{b} + \mathbf{c}) = \mathbf{a}\mathbf{b} + \mathbf{a}\mathbf{c},$$

Similarly we can also show that (using product rule for differentiating reals)

$$\frac{d}{dt}(\mathbf{a}\mathbf{b}) = \mathbf{a} \frac{d\mathbf{b}}{dt} + \mathbf{b} \frac{d\mathbf{a}}{dt}.$$

We can repeat these operations for the cross products and show that they are distributive

$$\mathbf{a} \times (\mathbf{b} + \mathbf{c}) = \mathbf{a} \times \mathbf{b} + \mathbf{a} \times \mathbf{c}.$$

We have also that

$$\frac{d}{dt}(\mathbf{a} \times \mathbf{b}) = \mathbf{a} \times \frac{d\mathbf{b}}{dt} + \mathbf{b} \times \frac{d\mathbf{a}}{dt}.$$

The rotation of a three-dimensional vector $\mathbf{a} = (a_x, a_y, a_z)$ in the xy plane around an angle ϕ results in a new vector $\mathbf{b} = (b_x, b_y, b_z)$. This operation can be expressed in terms of linear algebra as a matrix (the rotation matrix) multiplied with a vector. We can write this as

$$\begin{bmatrix} b_x \\ b_y \\ b_z \end{bmatrix} = \begin{bmatrix} \cos \phi & \sin \phi & 0 \\ -\sin \phi & \cos \phi & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} a_x \\ a_y \\ a_z \end{bmatrix}.$$

We can write this in a more compact form as $\mathbf{b} = \mathbf{R}\mathbf{a}$, where the rotation matrix is defined as

$$\mathbf{R} = \begin{bmatrix} \cos \phi & \sin \phi & 0 \\ -\sin \phi & \cos \phi & 0 \\ 0 & 0 & 1 \end{bmatrix}.$$

Falling baseball in one dimension

We anticipate the mathematical model to come and assume that we have a model for the motion of a falling baseball without air resistance. Our system (the baseball) is at an initial height y_0 (which we will specify in the program below) at the initial time $t_0 = 0$. In our program example here we will plot the position every five seconds. The mathematical formula for the position $y(t)$ as function of time t is

$$y(t) = y_0 - \frac{1}{2}gt^2,$$

where $g = 9.80665 = 0.980655 \times 10^1 \text{m/s}^2$ is a constant representing the standard acceleration due to gravity. We have here adopted the conventional standard value. This does not take into account other effects, such as buoyancy or drag.

As of now we simply assume that we know the formula. Below we will derive it.

Our Python Encounter

We start with preparing folders for storing our calculations, figures and if needed, specific data files we use as input files.

You could also define a function for making our plots. You can obviously avoid this and simply set up various **matplotlib** commands every time you need them. You may however find it convenient to collect all such commands in one function and simply call this function.

Python practicalities, Software and needed installations

We will make extensive use of Python as programming language and its myriad of available libraries. You will find Jupyter notebooks invaluable in your work.

If you have Python installed (we strongly recommend Python3) and you feel pretty familiar with installing different packages, we recommend that you install the following Python packages via **pip** as

1. `pip install numpy scipy matplotlib ipython scikit-learn mglearn sympy pandas pillow`

For Python3, replace **pip** with **pip3**.

For OSX users we recommend, after having installed Xcode, to install **brew**. Brew allows for a seamless installation of additional software via for example

1. `brew install python3`

For Linux users, with its variety of distributions like for example the widely popular Ubuntu distribution, you can use **pip** as well and simply install Python as

1. `sudo apt-get install python3 (or python for python2.7)`

etc etc.

Python installers

If you don't want to perform these operations separately and venture into the hassle of exploring how to set up dependencies and paths, we recommend two widely used distributions which set up all relevant dependencies for Python, namely

- [Anaconda](#),

which is an open source distribution of the Python and R programming languages for large-scale data processing, predictive analytics, and scientific computing, that aims to simplify package management and deployment. Package versions are managed by the package management system **conda**.

- [Enthought canopy](#)

is a Python distribution for scientific and analytic computing distribution and analysis environment, available for free and under a commercial license.

Furthermore, [Google's Colab](#) is a free Jupyter notebook environment that requires no setup and runs entirely in the cloud. Try it out!

Useful Python libraries

Here we list several useful Python libraries we strongly recommend (if you use anaconda many of these are already there)

- [NumPy](#) is a highly popular library for large, multi-dimensional arrays and matrices, along with a large collection of high-level mathematical functions to operate on these arrays
- [The pandas](#) library provides high-performance, easy-to-use data structures and data analysis tools
- [Xarray](#) is a Python package that makes working with labelled multi-dimensional arrays simple, efficient, and fun!
- [Scipy](#) (pronounced “Sigh Pie”) is a Python-based ecosystem of open-source software for mathematics, science, and engineering.
- [Matplotlib](#) is a Python 2D plotting library which produces publication quality figures in a variety of hardcopy formats and interactive environments across platforms.
- [Autograd](#) can automatically differentiate native Python and Numpy code. It can handle a large subset of Python's features, including loops, ifs, recursion and closures, and it can even take derivatives of derivatives of derivatives
- [SymPy](#) is a Python library for symbolic mathematics.
- [scikit-learn](#) has simple and efficient tools for machine learning, data mining and data analysis
- [TensorFlow](#) is a Python library for fast numerical computing created and released by Google
- [Keras](#) is a high-level neural networks API, written in Python and capable of running on top of TensorFlow, CNTK, or Theano
- And many more such as [pytorch](#), [Theano](#) etc

Your jupyter notebook can easily be converted into a nicely rendered **PDF** file or a Latex file for further processing. For example, convert to latex as

```
pycod jupyter nbconvert filename.ipynb --to latex
```

And to add more versatility, the Python package [SymPy](#) is a Python library for symbolic mathematics. It aims to become a full-featured computer algebra system (CAS) and is entirely written in Python.

Numpy examples and Important Matrix and vector handling packages

There are several central software libraries for linear algebra and eigenvalue problems. Several of the more popular ones have been wrapped into other software packages like those from the widely used text **Numerical Recipes**. The original source codes in many of the available packages are often taken from the widely used software package LAPACK, which follows two other popular packages developed in the 1970s, namely EISPACK and LINPACK. We describe them shortly here.

- LINPACK: package for linear equations and least square problems.
- LAPACK: package for solving symmetric, unsymmetric and generalized eigenvalue problems. From LAPACK's website <http://www.netlib.org> it is possible to download for free all source codes from this library. Both C/C++ and Fortran versions are available.
- BLAS (I, II and III): (Basic Linear Algebra Subprograms) are routines that provide standard building blocks for performing basic vector and matrix operations. Blas I is vector operations, II vector-matrix operations and III matrix-matrix operations. Highly parallelized and efficient codes, all available for download from <http://www.netlib.org>.

Basic Matrix Features

Matrix properties reminder.

$$\mathbf{A} = \begin{bmatrix} a_{11} & a_{12} & a_{13} & a_{14} \\ a_{21} & a_{22} & a_{23} & a_{24} \\ a_{31} & a_{32} & a_{33} & a_{34} \\ a_{41} & a_{42} & a_{43} & a_{44} \end{bmatrix} \quad \mathbf{I} = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

The inverse of a matrix is defined by

$$\mathbf{A}^{-1} \cdot \mathbf{A} = \mathbf{I}$$

Relations	Name	matrix elements
$A = A^T$	symmetric	$a_{ij} = a_{ji}$
$A = (A^T)^{-1}$	real orthogonal	$\sum_k a_{ik} a_{jk} = \sum_k a_{ki} a_{kj} = \delta_{ij}$
$A = A^*$	real matrix	$a_{ij} = a_{ij}^*$
$A = A^\dagger$	hermitian	$a_{ij} = a_{ji}^*$
$A = (A^\dagger)^{-1}$	unitary	$\sum_k a_{ik} a_{jk}^* = \sum_k a_{ki}^* a_{kj} = \delta_{ij}$

Some famous Matrices.

- Diagonal if $a_{ij} = 0$ for $i \neq j$
- Upper triangular if $a_{ij} = 0$ for $i > j$
- Lower triangular if $a_{ij} = 0$ for $i < j$
- Upper Hessenberg if $a_{ij} = 0$ for $i > j + 1$
- Lower Hessenberg if $a_{ij} = 0$ for $i < j - 1$
- Tridiagonal if $a_{ij} = 0$ for $|i - j| > 1$
- Lower banded with bandwidth p : $a_{ij} = 0$ for $i > j + p$
- Upper banded with bandwidth p : $a_{ij} = 0$ for $i < j - p$
- Banded, block upper triangular, block lower triangular....

More Basic Matrix Features.

Some Equivalent Statements. For an $N \times N$ matrix \mathbf{A} the following properties are all equivalent

- If the inverse of \mathbf{A} exists, \mathbf{A} is nonsingular.
- The equation $\mathbf{Ax} = 0$ implies $\mathbf{x} = 0$.
- The rows of \mathbf{A} form a basis of R^N .
- The columns of \mathbf{A} form a basis of R^N .
- \mathbf{A} is a product of elementary matrices.
- 0 is not eigenvalue of \mathbf{A} .

Numpy and arrays

[Numpy](#) provides an easy way to handle arrays in Python. The standard way to import this library is as

Here follows a simple example where we set up an array of ten elements, all determined by random numbers drawn according to the normal distribution. We defined a vector x with $n = 10$ elements with its values given by the Normal distribution $N(0, 1)$. Another alternative is to declare a vector as follows Here we have defined a vector with three elements, with $x_0 = 1$, $x_1 = 2$ and $x_2 = 3$. Note that both Python and C++ start numbering array elements from 0 and on. This means that a vector with n elements has a sequence of entities $x_0, x_1, x_2, \dots, x_{n-1}$.

We could also let (recommended) Numpy to compute the logarithms of a specific array as

In the last example we used Numpy's unary function *np.log*. This function is highly tuned to compute array elements since the code is vectorized and does not require looping. We normally recommend that you use the Numpy intrinsic functions instead of the corresponding **log** function from Python's **math** module. The looping is done explicitly by the **np.log** function. The alternative, and slower way to compute the logarithms of a vector would be to write

We note that our code is much longer already and we need to import the **log** function from the **math** module. The attentive reader will also notice that the output is `[1, 1, 2]`. Python interprets automagically our numbers as integers (like the **automatic** keyword in C++). To change this we could define our array elements to be double precision numbers as or simply write them as double precision numbers (Python uses 64 bits as default for floating point type variables), that is To check the number of bytes (remember that one byte contains eight bits for double precision variables), you can use simple use the **itemsize** functionality (the array *x* is actually an object which inherits the functionalities defined in Numpy) as

Matrices in Python

Having defined vectors, we are now ready to try out matrices. We can define a 3×3 real matrix \hat{A} as (recall that we use lowercase letters for vectors and uppercase letters for matrices)

If we use the **shape** function we would get `(3, 3)` as output, that is verifying that our matrix is a 3×3 matrix. We can slice the matrix and print for example the first column (Python organized matrix elements in a row-major order, see below) as We can continue this was by printing out other columns or rows. The example here prints out the second column Numpy contains many other functionalities that allow us to slice, subdivide etc etc arrays. We strongly recommend that you look up the [Numpy website for more details](#). Useful functions when defining a matrix are the **np.zeros** function which declares a matrix of a given dimension and sets all elements to zero or initializing all elements to or as unitarily distributed random numbers (see the material on random number generators in the statistics part)

Meet the Pandas



Another useful Python package is [pandas](#), which is an open source library providing high-performance, easy-to-use data structures and data analysis tools for Python. **pandas** stands for panel data, a term borrowed from econometrics and is an efficient library for data analysis with an emphasis on tabular data. **pandas** has two major classes, the **DataFrame** class with two-dimensional data objects and tabular data organized in columns and the class **Series** with a focus on one-dimensional data objects. Both classes allow you to index data easily as we will see in the examples below. **pandas** allows you also to perform mathematical operations on the data, spanning from simple reshaping of vectors and matrices to statistical operations.

The following simple example shows how we can, in an easy way make tables of our data. Here we define a data set which includes names, place of birth and date of birth, and displays the data in an easy to read way. We will see repeated use of **pandas**, in particular in connection with classification of data.

In the above we have imported **pandas** with the shorthand **pd**, the latter has become the standard way we import **pandas**. We make then a list of various variables and reorganize the above lists into a **DataFrame** and then print out a neat table with specific column labels as *Name*, *place of birth* and *date of birth*. Displaying these results, we see that the indices are given by the default numbers from zero to three. **pandas** is extremely flexible and we can easily change the above indices by defining a new type of indexing as *Thereafter* we display the content of the row which begins with the index **Aragorn**

We can easily append data to this, for example

Here are other examples where we use the **DataFrame** functionality to handle arrays, now with more interesting features for us, namely numbers. We set up a matrix of dimensionality 10×5 and compute the mean value and standard deviation of each column. Similarly, we can perform mathematical operations like squaring the matrix elements and many other operations.

Thereafter we can select specific columns only and plot final results We can produce a 4×4 matrix and many other operations.

The **Series** class is another important class included in **pandas**. You can view it as a specialization of **DataFrame** but where we have just a single column of data. It shares many of the same features as *DataFrame*. *As with DataFrame, most operations are vectorized, ach*