

Predicting LIDAR Intensity from RGB and Depth Images

Project Report in computer science

vorgelegt von

Carsten Schmotz

geb. am 23.09.1996 in Dachau

angefertigt am

Department Informatik
Lehrstuhl Graphische Datenverarbeitung
Friedrich-Alexander-Universität Erlangen-Nürnberg

Betreuer: Richard Marcus

Betreuender Hochschullehrer: Prof. Dr. Marc Stamminger

Beginn der Arbeit: 22.07.2024

Abgabe der Arbeit: 29.07.2024

Contents

1	Introduction	3
1.1	Motivation	3
1.2	Contribution	3
1.3	Related Work	3
2	Preparations	5
3	Predicting LIDAR Intensity from RGB and Depth Images	7
3.1	Setup	7
3.2	Implementation	7
3.3	Results	7
4	Conclusion	9
4.1	Appendix	9
4.2	References	9

Abstract

This project will use rgb images and depth maps to predict lidar intensities. The neural network pix2pix will be used to train and evaluated on the kitti dataset.

Chapter 1

Introduction

1.1 Motivation

the sensor simulation project focuses on different approaches with the lidar images on the kitti dataset. In this work the

1.2 Contribution

The use of the depth as additional input is a new way of improvement for the lidar intensity prediction.

1.3 Related Work

bpnet depth anything v1 2 and metric change pix2pix to 4 dim input

Chapter 2

Preparations

used google colab, pix2pix network getting the right input, pix2pix problems




Figure 2.1: caption.

Chapter 3

Predicting LIDAR Intensity from RGB and Depth Images

3.1 Setup

used the bp net it is for depth completion and depth prediction

3.2 Implementation

3.3 Results

Chapter 4

Conclusion

4.1 Appendix

4.2 References

List of Figures

2.1 caption. 5