



# **Display information about FPolicy configurations**

**ONTAP 9**

NetApp  
June 09, 2022

# Table of Contents

- Display information about FPolicy configurations ..... 1
  - How the show commands work ..... 1
  - Commands for displaying information about FPolicy configurations ..... 1
- Display information about FPolicy policy status ..... 2
- Display information about enabled FPolicy policies ..... 3

# Display information about FPolicy configurations

## How the show commands work

It is helpful when displaying information about the FPolicy configuration to understand how the `show` commands work.

A `show` command without additional parameters displays information in a summary form. Additionally, every `show` command has the same two mutually exclusive optional parameters, `-instance` and `-fields`.

When you use the `-instance` parameter with a `show` command, the command output displays detailed information in a list format. In some cases, the detailed output can be lengthy and include more information than you need. You can use the `-fields fieldname[,fieldname...]` parameter to customize the output so that it displays information only for the fields you specify. You can identify which fields that you can specify by entering `?` after the `-fields` parameter.



The output of a `show` command with the `-fields` parameter might display other relevant and necessary fields related to the requested fields.

Every `show` command has one or more optional parameters that filter that output and enable you to narrow the scope of information displayed in command output. You can identify which optional parameters are available for a command by entering `?` after the `show` command.

The `show` command supports UNIX-style patterns and wildcards to enable you to match multiple values in command-parameters arguments. For example, you can use the wildcard operator (`*`), the NOT operator (`!`), the OR operator (`()`), the range operator (`integer...integer`), the less-than operator (`<`), the greater-than operator (`>`), the less-than or equal to operator (`<=`), and the greater-than or equal to operator (`>=`) when specifying values.

For more information about using UNIX-style patterns and wildcards, see the "Using the ONTAP command-line interface" section of the *System Administration Guide for SVM Administrators*.

## Commands for displaying information about FPolicy configurations

You use the `fpolicy show` commands to display information about the FPolicy configuration, including information about FPolicy external engines, events, scopes, and policies.

If you want to display information about FPolicy...	Use this command...
External engines	<code>vserver fpolicy policy external-engine show</code>
Events	<code>vserver fpolicy policy event show</code>
Scopes	<code>vserver fpolicy policy scope show</code>

Policies	<code>vserver fpolicy policy show</code>
----------	--

See the man pages for the commands for more information.

## Display information about FPolicy policy status

You can display information about the status for FPolicy policies to determine whether a policy is enabled, what external engine it is configured to use, what the sequence number is for the policy, and to which storage virtual machine (SVM) the FPolicy policy is associated.

### About this task

If you do not specify any parameters, the command displays the following information:

- SVM name
- Policy name
- Policy sequence number
- Policy status

In addition to displaying information about policy status for FPolicy policies configured on the cluster or a specific SVM, you can use command parameters to filter the command's output by other criteria.

You can specify the `-instance` parameter to display detailed information about listed policies. Alternatively, you can use the `-fields` parameter to display only the indicated fields in the command output, or `-fields ?` to determine what fields you can use.

### Step

1. Display filtered information about FPolicy policy status by using the appropriate command:

If you want to display status information about policies...	Enter the command...
On the cluster	<code>vserver fpolicy show</code>
That have the specified status	<code>vserver fpolicy show -status {on off}</code>
On a specified SVM	<code>vserver fpolicy show -vserver vserver_name</code>
With the specified policy name	<code>vserver fpolicy show -policy-name policy_name</code>
That use the specified external engine	<code>vserver fpolicy show -engine engine_name</code>

### Example

The following example displays the information about FPolicy policies on the cluster:

```
cluster1::> vserver fpolicy show
```

Vserver	Policy Name	Sequence	Status	Engine
		Number		
FPolicy	cserver_policy	-	off	eng1
vs1.example.com	v1p1	-	off	eng2
vs1.example.com	v1p2	-	off	native
vs1.example.com	v1p3	-	off	native
vs1.example.com	cserver_policy	-	off	eng1
vs2.example.com	v1p1	3	on	native
vs2.example.com	v1p2	1	on	eng3
vs2.example.com	cserver_policy	2	on	eng1

## Display information about enabled FPolicy policies

You can display information about enabled FPolicy policies to determine what FPolicy external engine it is configured to use, what the priority is for the policy, and to which storage virtual machine (SVM) the FPolicy policy is associated.

### About this task

If you do not specify any parameters, the command displays the following information:

- SVM name
- Policy name
- Policy priority

You can use command parameters to filter the command's output by specified criteria.

### Step

1. Display information about enabled FPolicy policies by using the appropriate command:

If you want to display information about enabled policies...	Enter the command...
On the cluster	<code>vserver fpolicy show-enabled</code>
On a specified SVM	<code>vserver fpolicy show-enabled -vserver vs1.example.com</code>
With the specified policy name	<code>vserver fpolicy show-enabled -policy-name policy_name</code>
With the specified sequence number	<code>vserver fpolicy show-enabled -priority integer</code>

### Example

The following example displays the information about enabled FPolicy policies on the cluster:

```
cluster1::> vserver fpolicy show-enabled
```

Vserver	Policy Name	Priority
vs1.example.com	pol_native	native
vs1.example.com	pol_native2	native
vs1.example.com	pol1	2
vs1.example.com	pol2	4

## Copyright Information

Copyright © 2022 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

## Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.