

The Cartographer Framework

CONFIGURATION

Application Configuration Guide

Step-By-Step Guide for Application Configuration

TABLE OF CONTENTS


1.	GROUP SYNC CONFIGURATION	
	Configure Group Members	03-09
2.	APPLICATION CONFIGURATION	
	How to Configure Testing Coverage	10-11
	Configure Flagship Model	12-13
	Configure Custom Model	14-16
	Configure Prompt Choice for Testing	17-18
	Configure Red Team Techniques for Testing	19-20
	How to Configure Schedule Frequency	21-22
	How to Configure Recurring Schedule	22-23
	How to Configure Target Allow/Disallow List	23-25
	How to Configure a Test	26-30

Group Configuration Steps

Configure Group Member Setup


Step 1

Find Installer.exe, double click




Step 2

Click “Start Cartographer” to Provision your Group



Step 3

The installer will prompt a panel with a URL, copy this and send it to your team members



The screenshot shows a web application window titled "Cartographer — POC Install Tool". The interface has a header with the title "THE CARTOGRAPHER" and a progress bar with five steps: "Credentials", "Group Setup", "Provisioning", "Enrollment" (which is active and highlighted in orange), and "Complete". Below the header, the main content area is titled "Device Enrollment". It contains a text input field with the URL "http://107.20.205.178:8080/enroll/WHXDLIViOgKxVH". Below the input field is a "Copy URL" button. Underneath, it says "Enrolled devices: 0" and "Waiting for devices to enroll...". There is a large empty rectangular box below this. At the bottom, there is a "Device count override (optional):" label next to a text input field containing the number "0". Finally, there is a large orange button labeled "Confirm Group & Provision Core Infrastructure →".

Cartographer — POC Install Tool

THE CARTOGRAPHER

POC Install Tool

✓ Credentials ✓ Group Setup ✓ Provisioning ● Enrollment ○ Complete

Device Enrollment

Enrollment URL — distribute this to all operators:

Copy URL

Enrolled devices: 0


Waiting for devices to enroll...

Device count override (optional):

Confirm Group & Provision Core Infrastructure →


Step 4

Notify all team members to connect to the OVPN tunnel using the .ovpn file they received. Do not proceed until this step is communicated.



Step 5

Once members have connected to the OVPN environment, instruct each team member to run `setup.py` on their individual machine. This script synchronizes each machine to the shared group environment.



The screenshot shows a window titled "Cartographer — Device Setup". The main heading is "THE CARTOGRAPHER" with the subtitle "Device Setup".

VPN Auto-Enrollment

Connect to your VPN, then click Start Listening. The sync server will detect this device and push the enrollment URL automatically.

Start Listening (port 12415) Listening on 0.0.0.0:12415
rnc server pushes enrollment URL when it detects this device

or enter URL manually

Manual Enrollment

Enter the enrollment URL provided by your administrator:

`http://107.20.205.178:8080/enroll/WHXDLiViOgKxVH`

Device name (leave blank to use hostname):


Hardware ID: `a39bfbf82fb9b731...87042624`

Enroll This Device

Cancel

Step 6


From the client, monitor the user synchronization panel as team members connect. When the expected number of users are shown as synchronized, click Confirm to proceed.



The screenshot shows a web application window titled "Cartographer — POC Install Tool". The main header is "THE CARTOGRAPHER" with a subtitle "POC Install Tool". A progress bar at the top right indicates the current step: "Enrollment" (highlighted in orange) with other steps like "Credentials", "Group Setup", "Provisioning", and "Complete" marked as completed. The main content area is titled "Device Enrollment". It contains a section for "Enrollment URL — distribute this to all operators:" with a text input field containing the URL "http://107.20.205.178:8080/enroll/WHXDLIViOgKxVH" and a "Copy URL" button. Below this, it shows "Enrolled devices: 0" and the status "Waiting for devices to enroll...". At the bottom, there is a "Device count override (optional):" input field with the value "0" and a large orange button labeled "Confirm Group & Provision Core Infrastructure →".

Step 7

Wait for the environment generation process to complete fully. Do not interrupt the process. When complete, save the output file to a secure location on your computer — this file contains your environment credentials.




Application Configuration Steps

How to Configure Testing Coverage


Step 1

To configure testing coverage, browse through the Coverage Panel within the application. This panel provides a full view of all available test coverage options organized by AML technique ID.



Step 2


Select one or more AML.T00NN IDs you wish to test for. Locate the Coverage column on the right side of the panel to identify and confirm your selections.



Configure Flagship Model


Step 1

To configure a flagship model, navigate to the Models Window within the application. From the list of available providers, choose one of the main supported providers to use as your flagship model for testing.



Step 2

From the list of available providers, choose one of the main supported providers to use as your flagship model for testing.



Configure Custom Model

Step 1

To configure a new custom model, navigate to the Models Window and select the 'Create New Model' option to begin the configuration process.

The screenshot shows the 'Schedule Test' configuration window. On the left is a sidebar with categories like Reconnaissance, Source Development, Initial Access, Model Access, Execution, Persistence, Privilege Escalation, Defense Evasion, Credential Access, Recovery, Lateral Movement, Attack Staging, and Exfiltration. The main area is titled 'Schedule Test' and contains several sections: 'MODELS' with a dropdown menu showing 'CUSTOM' selected; 'PROMPT CHOICE' with two options 'A' and 'B'; 'TECHNIQUES' with checkboxes for Enumeration, LLM Interrogation, Prompt Engineering, Web Page Poison, and Data Poison; 'SCHEDULE' with buttons for 'QUARTERLY', 'MONTHLY', and 'WEEKLY'; and 'JOB OUTPUT' with a 'START TEST' button. The 'CUSTOM' model option is highlighted in the 'MODELS' dropdown.


Step 2

Scroll down within the new model form to locate the window titled New Custom Target. This section contains the fields required to define your custom model.

The screenshot shows the 'New Custom Target' configuration window. It features a 'TECHNIQUES' section with checkboxes for Enumeration, LLM Interrogation, Prompt Engineering, Web Page Poison, and Data Poison. A 'SCHEDULE' section has buttons for 'QUARTERLY', 'MONTHLY', and 'WEEKLY'. A 'RECURRING' section has a toggle switch for 'Off'. The 'NEW CUSTOM TARGET' section includes fields for 'TARGET NAME' (e.g., my_llm_api), 'ENDPOINT URL' (https://api.example.com/v1/chat), and 'REQUEST BODY TEMPLATE' (JSON format). A 'START TEST' button is located in the top right corner.

Step 3


Enter the name of the custom model in the provided name field. This label will be used to identify the model throughout the application.



The screenshot shows a web interface with a top navigation bar containing 'Data Poison', 'WEEKLY', a toggle switch set to 'Off', and 'MY SCHEDULE'. Below the navigation bar is a 'JOB OUTPUT' section. Within this section, there is a 'NEW CUSTOM TARGET' form. The form has four input fields: 'TARGET NAME' with the value 'my_custom_target', 'ENDPOINT URL' with the value 'https://api.example.com/v1/chat', 'REQUEST BODY TEMPLATE' with the value 'USE {{SYSTEM_PROMPT}} AND {{USER_PROMPT}}', and an empty 'REQUEST BODY' field.

Step 4

Enter the JSON Body representing the expected request structure for the model. Note: `{{USER_PROMPT}}` and `{{SYS_PROMPT}}` are reserved template variables replaced at runtime with the active test prompt and system prompt respectively. Place these placeholders correctly within the JSON body to match your model's expected input format.



The screenshot shows the 'JOB OUTPUT' section of the application. It contains a large text area with a JSON body:

```
{
  "model": "llama3.1:8b",
  "prompt": "{{user_prompt}}",
  "system": "{{system_prompt}}",
  "stream": false,
  "options": {
    "temperature": 0.7,
    "num_predict": 1000
  }
}
```

 Below the JSON body is a section for 'HEADERS (OPTIONAL) - KEY: VALUE, ONE PER LINE'. It contains two lines of text: 'Authorization: Bearer your-api-key' and 'Content-Type: application/json'.

Step 5

Enter the Authorization Keys required to authenticate requests to the custom model's API endpoint.

HEADERS (OPTIONAL) – KEY: VALUE, ONE PER LINE

Authorization: Bearer BEARER
X-API-KEY: FakeAPIKey

Step 6

Enter the API Endpoint URL where the custom model is hosted. This is the address the application will send test requests to during execution.

JOB OUTPUT

NEW CUSTOM TARGET

TARGET NAME

my_custom_target

ENDPOINT URL

https://localhost:11434/api/generate


REQUEST BODY TEMPLATE USE {{SYSTEM_PROMPT}} AND {{USER_PROMPT}}

```
{  
  "model": "llama3.1:8b",  
  "messages": [{"role": "system", "content": "You are a helpful assistant."},  
                {"role": "user", "content": "Hello!"}]
```


How to Configure Prompt Choice for Testing

Step 1

To configure testing prompts, locate the System Prompt Panel within the application.




Step 2

Choose either System Prompt A or System Prompt B as the active prompt for your test. Only one prompt may be active per test run.



Step 3

To modify the selected prompt, click the **Edit** button associated with the chosen prompt to open the prompt editor.



Configure Red Team Techniques for Testing


Step 1

To configure red team techniques, navigate to the Techniques Panel within the application. This panel lists all available red team techniques that can be designated for testing.



Step 2

Designate one or more techniques for your test run by selecting them from the available list. Multiple techniques may be selected to broaden the scope of a single test execution.



How to Configure Schedule Frequency for Testing

Step 1

To configure a test schedule, locate the Scheduling Panel within the application. This panel provides options for automating when test runs are executed.



Step 2


Choose one of the available frequencies from the scheduling options provided. The selected frequency will determine how often the test run is automatically triggered.



How to Set a Configured Schedule as Recurring

Step 1

To set a schedule as recurring, locate the Recurring option within the Scheduling Panel.



Step 2


Click the Recurring Schedule button to toggle the schedule into recurring mode. Once enabled, the test run will repeat indefinitely until disabled.



How to Configure Target Allow/Disallow List

Step 1

To add items to your model's Allow/Disallow List, Find the Profile Button in the Testing Dashboard



Step 2

See Guardrails, Capabilities, Tools

TARGET AI PROFILE – ALLOW / DISALLOW

Disallow items become test objectives. Allow items provide context.

GUARDRAILS

DISALLOW (TEST OBJECTIVES)

Refuses to provide specific exploit code

Will not help create malware

Blocks requests for personal information extrac

+ Add item

ALLOW (CONTEXT ONLY)

Discusses general safety topics factually

Provides educational content on cybersecurity ci

Explains vulnerability types in abstract terms

+ Add item

CAPABILITIES

DISALLOW (TEST OBJECTIVES)

Cannot execute code directly

No real-time internet access

Cannot access external APIs

+ Add item

ALLOW (CONTEXT ONLY)

Code generation in multiple languages

Document analysis and summarization

Multi-turn conversation with context retention

+ Add item

TOOLS

Tool: Code Interpreter

DISALLOW

No network access from sandbox

Cannot persist files between sessions

Limited to specific libraries

+ Add item

ALLOW

Execute Python code in sandbox


Generate visualizations

SAVE PROFILE

Cancel


Step 3

Add Items to respective categories to define work items and objectives



Step 4


Click Save Profile when finished



How to Configure a Test

Step 1

From the Main Dashboard, Create a Project by clicking the "New" button on the dashboard.




Step 2

Find the named project, click execute



Step 3

In the Testing Panel, select Threat ID Coverage in the Left Column



Step 4

Select a Model For testing




Step 5

Confirm your Prompt Choice



Step 6

Define Red Team Techniques



Step 7

Choose a Schedule

The screenshot shows a configuration interface with a sidebar on the left containing a list of items, one of which is highlighted in blue. The main area features a 'SCHEDULE' section with three buttons: 'QUARTERLY' (highlighted in red), 'MONTHLY', and 'WEEKLY'. To the right of the 'SCHEDULE' section is a 'RECURRING' section with a toggle switch labeled 'On'.

+ ADD ALL

SCHEDULE

QUARTERLY

MONTHLY

WEEKLY

RECURRING

On

Injection

or through crafted inputs

Step 8

Set test to Recurring if necessary

The screenshot shows a configuration interface with a sidebar on the left containing a list of items, one of which is highlighted in blue. The main area features a 'SCHEDULE' section with three buttons: 'QUARTERLY' (highlighted in red), 'MONTHLY', and 'WEEKLY'. To the right of the 'SCHEDULE' section is a 'RECURRING' section with a toggle switch labeled 'On'.

QUARTERLY

MONTHLY

WEEKLY

RECURRING

On

Step 9

Click "Start Test" Button to begin Test Process

