



# C Piscine

## Day 05

Staff 42 [pedago@42.fr](mailto:pedago@42.fr)

*Summary: This document is the subject for Day05 of the C Piscine @ 42.*

# Contents

I	Instructions	2
II	Foreword	4
III	Exercise 00 : ft_putstr	5
IV	Exercise 01 : ft_putnbr	6
V	Exercise 02 : ft_atoi	7
VI	Exercise 03 : ft_strcpy	8
VII	Exercise 04 : ft_strncpy	9
VIII	Exercise 05 : ft_strstr	10
IX	Exercise 06 : ft_strcmp	11
X	Exercise 07 : ft_strncmp	12
XI	Exercise 08 : ft_strupcase	13
XII	Exercise 09 : ft_strlowercase	14
XIII	Exercise 10 : ft_strcapitalize	15
XIV	Exercise 11 : ft_str_is_alpha	16
XV	Exercise 12 : ft_str_is_numeric	17
XVI	Exercise 13 : ft_str_is_lowercase	18
XVII	Exercise 14 : ft_str_is_uppercase	19
XVIII	Exercise 15 : ft_str_is_printable	20
XIX	Exercise 16 : ft_strcat	21
XX	Exercise 17 : ft_strncat	22
XXI	Exercise 18 : ft_strlcat	23
XXII	Exercise 19 : ft_strlcpy	24
XXIII	Exercise 20 : ft_putnbr_base	25

<b>XXIV</b>	<b>Exercise 21 : ft_atoi_base</b>	<b>27</b>
<b>XXV</b>	<b>Exercise 22 : ft_putstr_non_printable</b>	<b>28</b>
<b>XXVI</b>	<b>Exercise 23 : ft_print_memory</b>	<b>29</b>

# Chapter I

## Instructions

- Only this page will serve as reference: do not trust rumors.
- Watch out! This document could potentially change up to an hour before submission.
- Make sure you have the appropriate permissions on your files and directories.
- You have to follow the submission procedures for all your exercises.
- Your exercises will be checked and graded by your fellow classmates.
- On top of that, your exercises will be checked and graded by a program called Moulinette.
- Moulinette is very meticulous and strict in its evaluation of your work. It is entirely automated and there is no way to negotiate with it. So if you want to avoid bad surprises, be as thorough as possible.
- Moulinette is not very open-minded. It won't try and understand your code if it doesn't respect the Norm. Moulinette relies on a program called **Norminator** to check if your files respect the norm. TL;DR: it would be idiotic to submit a piece of work that doesn't pass **Norminator**'s check.
- These exercises are carefully laid out by order of difficulty - from easiest to hardest. We **will not** take into account a successfully completed harder exercise if an easier one is not perfectly functional.
- Using a forbidden function is considered cheating. Cheaters get **-42**, and this grade is non-negotiable.
- If `ft_putchar()` is an authorized function, we will compile your code with our `ft_putchar.c`.
- You'll only have to submit a `main()` function if we ask for a program.
- Moulinette compiles with these flags: `-Wall -Wextra -Werror`, and uses `gcc`.
- If your program doesn't compile, you'll get 0.

- You cannot leave any additional file in your directory than those specified in the subject.
- Got a question? Ask your peer on your right. Otherwise, try your peer on your left.
- Your reference guide is called `Google / man / the Internet / ....`
- Examine the examples thoroughly. They could very well call for details that are not explicitly mentioned in the subject...
- By Odin, by Thor ! Use your brain !!!



Norminator must be launched with the `-R CheckForbiddenSourceHeader` flag. Moulinette will use it too.

# Chapter II

## Foreword

Here is a discuss extract from the Silicon Valley serie:

- I mean, why not just use Vim over Emacs? (CHUCKLES)
- I do use Vim over Emacs.
- Oh, God, help us! Okay, uh you know what? I just don't think this is going to work. I'm so sorry. Uh, I mean like, what, we're going to bring kids into this world with that over their heads? That's not really fair to them, don't you think?
- Kids? We haven't even slept together.
- And guess what, it's never going to happen now, because there is no way I'm going to be with someone who uses spaces over tabs.
- Richard! (PRESS SPACE BAR MANY TIMES)
- Wow. Okay. Goodbye.
- One tab saves you eight spaces! - (DOOR SLAMS) - (BANGING)

. . .


(RICHARD MOANS)

- Oh, my God! Richard, what happened?
- I just tried to go down the stairs eight steps at a time. I'm okay, though.
- See you around, Richard.
- Just making a point.

Hopefully, you are not forced to use emacs and your space bar to complete the following exercises.

# Chapter III

## Exercise 00 : ft\_putstr

	Exercise 00
	ft_putstr
	Turn-in directory : <i>ex00/</i>
	Files to turn in : <b>ft_putstr.c</b>
	Allowed functions : <b>ft_putchar</b>


*42 - Classics* : Theses exercises are key assignments that do not earn points, but are mandatory to validate in order to access to the real assignments of the day.

- Create a function that displays a string of characters on the standard output.
- Here's how it should be prototyped :

```
void    ft_putstr(char *str);
```

# Chapter IV

## Exercise 01 : ft\_putnbr

	Exercise 01
	ft_putnbr
	Turn-in directory : <i>ex01/</i>
	Files to turn in : <b>ft_putnbr.c</b>
	Allowed functions : <b>ft_putchar</b>

*42 - Classics* : Theses exercises are key assignments that do not earn points, but are mandatory to validate in order to access to the real assignments of the day.

- Create a function that displays the number entered as a parameter. The function has to be able to display all possible values within an `int` type variable.
- Here's how it should be prototyped :


```
void ft_putnbr(int nb);
```

- For example:
  - `ft_putnbr(42)` displays "42".



# Chapter V

## Exercise 02 : ft\_atoi

	Exercise 02
ft_atoi	
Turn-in directory : <i>ex02/</i>	
Files to turn in : <b>ft_atoi.c</b>	
Allowed functions : <b>None</b>	


*42 - Classics* : Theses exercises are key assignments that do not earn points, but are mandatory to validate in order to access to the real assignments of the day.

- Reproduce the behavior of the function `atoi` (man `atoi`).
- Here's how it should be prototyped :

```
int    ft_atoi(char *str);
```

# Chapter VI

## Exercise 03 : ft\_strcpy


	Exercise 03
	ft_strcpy
	Turn-in directory : <i>ex03/</i>
	Files to turn in : <b>ft_strcpy.c</b>
	Allowed functions : None

- Reproduce the behavior of the function **strcpy** (man strcpy).
- Here's how it should be prototyped :

```
char *ft_strcpy(char *dest, char *src);
```

# Chapter VII

## Exercise 04 : ft\_strncpy


	Exercise 04
	ft_strncpy
	Turn-in directory : <i>ex04/</i>
	Files to turn in : <b>ft_strncpy.c</b>
	Allowed functions : None

- Reproduce the behavior of the function **strncpy** (man strncpy).
- Here's how it should be prototyped :

```
char      *ft_strncpy(char *dest, char *src, unsigned int n);
```

# Chapter VIII

## Exercise 05 : ft\_strstr


	Exercise 05
ft_strstr	
Turn-in directory : <i>ex05/</i>	
Files to turn in : <b>ft_strstr.c</b>	
Allowed functions : None	

- Reproduce the behavior of the function **strstr** (man strstr).
- Here's how it should be prototyped :

```
char *ft_strstr(char *str, char *to_find);
```

# Chapter IX

## Exercise 06 : ft\_strcmp


	Exercise 06
	ft_strcmp
	Turn-in directory : <i>ex06/</i>
	Files to turn in : <b>ft_strcmp.c</b>
	Allowed functions : None

- Reproduce the behavior of the function **strcmp** (man strcmp).
- Here's how it should be prototyped :

```
int      ft_strcmp(char *s1, char *s2);
```

# Chapter X

## Exercise 07 : ft\_strncmp


	Exercise 07
	ft_strncmp
	Turn-in directory : <i>ex07/</i>
	Files to turn in : <b>ft_strncmp.c</b>
	Allowed functions : None

- Reproduce the behavior of the function `strncmp` (man `strncmp`).
- Here's how it should be prototyped :

```
int      ft_strncmp(char *s1, char *s2, unsigned int n);
```

# Chapter XI

## Exercise 08 : ft\_strupcase

	Exercise 08
	ft_strupcase
	Turn-in directory : <i>ex08/</i>
	Files to turn in : <b>ft_strupcase.c</b>
	Allowed functions : None


- Create a function that transforms every letter of every word to uppercase.
- Here's how it should be prototyped :

```
char *ft_strupcase(char *str);
```

- It should return `str`.

# Chapter XII

## Exercise 09 : ft\_strlowercase

	Exercise 09
	ft_strlowercase
	Turn-in directory : <i>ex09/</i>
	Files to turn in : <b>ft_strlowercase.c</b>
	Allowed functions : None

- Create a function that transforms every letter of every word to lowercase.
- Here's how it should be prototyped :


```
char *ft_strlowercase(char *str);
```

- It should return **str**.



# Chapter XIII

## Exercise 10 : ft\_strcapitalize

	Exercise 10
	ft_strcapitalize
	Turn-in directory : <i>ex10/</i>
	Files to turn in : <b>ft_strcapitalize.c</b>
	Allowed functions : None

- Create a function that capitalizes the first letter of each word and transforms all other letters to lowercase.
- A word is a string of alphanumeric characters.
- Here's how it should be prototyped :

```
char *ft_strcapitalize(char *str);
```

- It should return `str`.
- For example:


```
salut, comment tu vas ? 42mots quarante-deux; cinquante+et+un
```

- Becomes:

```
Salut, Comment Tu Vas ? 42mots Quarante-Deux; Cinquante+Et+Un
```

# Chapter XIV

## Exercise 11 : ft\_str\_is\_alpha

	Exercise 11
	ft_str_is_alpha
	Turn-in directory : <i>ex11/</i>
	Files to turn in : <b>ft_str_is_alpha.c</b>
	Allowed functions : None


- Create a function that returns 1 if the string given as a parameter contains only alphabetical characters, and 0 if it contains any other character.
- Here's how it should be prototyped :

```
int ft_str_is_alpha(char *str);
```

- It should return 1 if **str** is empty.

# Chapter XV

## Exercise 12 : ft\_str\_is\_numeric

	Exercise 12
ft_str_is_numeric	
Turn-in directory : <i>ex12/</i>	
Files to turn in : <code>ft_str_is_numeric.c</code>	
Allowed functions : None	


- Create a function that returns 1 if the string given as a parameter contains only digits, and 0 if it contains any other character.
- Here's how it should be prototyped :

```
int ft_str_is_numeric(char *str);
```

- It should return 1 if `str` is empty.

# Chapter XVI

## Exercise 13 : ft\_str\_is\_lowercase

	Exercise 13
	ft_str_is_lowercase
	Turn-in directory : <i>ex13/</i>
	Files to turn in : <b>ft_str_is_lowercase.c</b>
	Allowed functions : None


- Create a function that returns 1 if the string given as a parameter contains only lowercase alphabetical characters, and 0 if it contains any other character.
- Here's how it should be prototyped :

```
int      ft_str_is_lowercase(char *str);
```

- It should return 1 if **str** is empty.

# Chapter XVII

## Exercise 14 : ft\_str\_is\_uppercase

	Exercise 14
	ft_str_is_uppercase
	Turn-in directory : <i>ex14/</i>
	Files to turn in : <b>ft_str_is_uppercase.c</b>
	Allowed functions : None


- Create a function that returns 1 if the string given as a parameter contains only uppercase alphabetical characters, and 0 if it contains any other character.
- Here's how it should be prototyped :

```
int ft_str_is_uppercase(char *str);
```

- It should return 1 if **str** is empty.

# Chapter XVIII

## Exercise 15 : ft\_str\_is\_printable

	Exercise 15
ft_str_is_printable	
Turn-in directory : <i>ex15/</i>	
Files to turn in : <b>ft_str_is_printable.c</b>	
Allowed functions : None	


- Create a function that returns 1 if the string given as a parameter contains only printable characters, and 0 if it contains any other character.
- Here's how it should be prototyped :

```
int ft_str_is_printable(char *str);
```

- It should return 1 if **str** is empty.

# Chapter XIX

## Exercise 16 : ft\_strcat


	Exercise 16
ft_strcat	
Turn-in directory : <i>ex16/</i>	
Files to turn in : <b>ft_strcat.c</b>	
Allowed functions : None	

- Reproduce the behavior of the function **strcat** (man strcat).
- Here's how it should be prototyped :

```
char *ft_strcat(char *dest, char *src);
```

# Chapter XX

## Exercise 17 : ft\_strncat

	Exercise 17
ft_strncat	
Turn-in directory : <i>ex17/</i>	
Files to turn in : <b>ft_strncat.c</b>	
Allowed functions : None	


- Reproduce the behavior of the function **strncat** (man strncat).
- Here's how it should be prototyped :

```
char *ft_strncat(char *dest, char *src, int nb);
```



# Chapter XXI

## Exercise 18 : ft\_strlcat


	Exercise 18
ft_strlcat	
Turn-in directory : <i>ex18/</i>	
Files to turn in : <b>ft_strlcat.c</b>	
Allowed functions : None	

- Reproduce the behavior of the function **strlcat** (man strlcat).
- Here's how it should be prototyped :

```
unsigned int ft_strlcat(char *dest, char *src, unsigned int size);
```

# Chapter XXII

## Exercise 19 : ft\_strlcpy


	Exercise 19
	ft_strlcpy
	Turn-in directory : <i>ex19/</i>
	Files to turn in : <b>ft_strlcpy.c</b>
	Allowed functions : None

- Reproduce the behavior of the function **strlcpy** (man strlcpy).
- Here's how it should be prototyped :

```
unsigned int ft_strlcpy(char *dest, char *src, unsigned int size);
```

# Chapter XXIII

## Exercise 20 : ft\_putnbr\_base


	Exercise 20
	ft_putnbr_base
	Turn-in directory : <i>ex20/</i>
	Files to turn in : <b>ft_putnbr_base.c</b>
	Allowed functions : <b>ft_putchar</b>

- Create a function that displays a number in a base system onscreen.
- This number is given in the shape of an **int**, and the radix in the shape of a **string of characters**.
- The base-system contains all useable symbols to display that number :
  - 0123456789 is the commonly used base system to represent decimal numbers ;
  - 01 is a binary base system ;
  - 0123456789ABCDEF an hexadecimal base system ;
  - poneyvif is an octal base system.
- The function must handle negative numbers.
- If there's an invalid argument, nothing should be displayed. Examples of invalid arguments :
  - base is empty or size of 1;
  - base contains the same character twice ;
  - base contains + or - ;
  - etc.
- Here's how it should be prototyped :

```
void      ft_putnbr_base(int nbr, char *base);
```

# Chapter XXIV

## Exercise 21 : ft\_atoi\_base


	Exercise 21
	ft_atoi_base
	Turn-in directory : <i>ex21/</i>
	Files to turn in : <code>ft_atoi_base.c</code>
	Allowed functions : None

- Create a function that returns a number. This number is shaped as a **string of characters**.
- The string of characters reveals the number in a specific base, given as a second parameter.
- The function must handle negative numbers.
- The function must handle signs like `man atoi`.
- If there's an invalid argument, the function should return 0. Examples of invalid arguments :
  - str is an empty string ;
  - the base is empty or size of 1;
  - str contains characters that aren't part of the base, or aren't + nor - ;
  - the base contains the same character twice ;
  - the base contains + or - ;
  - etc.
- Here's how it should be prototyped :

```
int ft_atoi_base(char *str, char *base);
```

# Chapter XXV

## Exercise 22 : ft\_putstr\_non\_printable

	Exercise 22
ft_putstr_with_non_printable	
Turn-in directory : <i>ex22/</i>	
Files to turn in : <b>ft_putstr_non_printable.c</b>	
Allowed functions : <b>ft_putchar</b>	

- Create a function that displays a string of characters onscreen. If this string contains characters that aren't printable, they'll have to be displayed in the shape of hexadecimals (lowercase), preceded by a "backslash".
- For example :

```
Coucou\ntu vas bien ?
```

- The function should display :


```
Coucou\0atu vas bien ?
```

- Here's how it should be prototyped :

```
void      ft_putstr_non_printable(char *str);
```

# Chapter XXVI

## Exercise 23 : ft\_print\_memory

	Exercise 23
	ft_print_memory
	Turn-in directory : <i>ex23/</i>
	Files to turn in : <b>ft_print_memory.c</b>
	Allowed functions : <b>ft_putchar</b>

- Create a function that displays the memory area onscreen.
- The display of this memory area should be split into three columns :
  - The hexadecimal address of the first line's first character ;
  - The content in hexadecimal ;
  - The content in printable characters.
- If a character is non-printable, it'll be replaced by a dot.
- Each line should handle sixteen characters.
- If **size** equals to 0, nothing should be displayed.

- Example:

```
guilla_i@seattle $> ./ft_print_memory
00000000: 5361 6c75 7420 6c65 7320 616d 696e 6368 Salut les aminch
00000010: 6573 2063 2765 7374 2063 6f6f 6c20 7368 es c'est cool sh
00000020: 6f77 206d 656d 206f 6e20 6661 6974 2064 ow mem on fait d
00000030: 6520 7472 7563 2074 6572 7269 626c 6500 e truc terrible.
00000040: 2e00 0102 0304 0506 0708 090e 0f1b 7f .....
guilla_i@seattle $> ./ft_print_memory | cat -te
00000000: 5361 6c75 7420 6c65 7320 616d 696e 6368 Salut les aminch$
00000010: 6573 2063 2765 7374 2063 6f6f 6c20 7368 es c'est cool sh$
00000020: 6f77 206d 656d 206f 6e20 6661 6974 2064 ow mem on fait d$
00000030: 6520 7472 7563 2074 6572 7269 626c 6500 e truc terrible.$
00000040: 2e00 0102 0304 0506 0708 090e 0f1b 7f .....$
guilla_i@seattle $>
```

- Here's how it should be prototyped :

```
void      *ft_print_memory(void *addr, unsigned int size);
```

- It should return addr.