

## A QUICK BATTERY HOLDER FOR ELECTRICAL EXPERIMENTS

by **Thinkenstein** on July 11, 2009

## Table of Contents



intro: A QUICK BATTERY HOLDER FOR ELECTRICAL EXPERIMENTS .....	2
step 1: MODIFY THE CLOTHESPINS .....	2
step 2: NAIL THE CLOTHESPINS TO THE SPACER WOOD .....	3
step 3: INSERT THE WIRES THROUGH THE HOLES .....	3
Related Instructables .....	4
Advertisements .....	5

## intro: A QUICK BATTERY HOLDER FOR ELECTRICAL EXPERIMENTS

This is a quick way to hold wires to the terminals of a AAA or a AA battery for electrical experiments. Two modified clothespins are mounted to a 3/4" thick wood spacer. The clothespin springs maintain pressure on the battery terminals.

Two holes in each of the clothespins allow for attachment of the wires.

I just nailed the clothespins to the wood with 3/4" finishing nails. You could also use a little glue if you wish.




## step 1: MODIFY THE CLOTHESPINS

Slide one half of the clothespin sideways out from under the spring that holds it. Cut the end off one of the halves. Make sure that when the battery is in place, the terminals of the battery will make contact with and be held by the contact points on either side of the holder.

If you don't have a tiny drill bit to make the holes with, you can just drive in and pull out a 3/4" finishing nail. If the wood splits, it may still work. If it splits badly, try another clothespin. Sometimes they don't split.









## step 2: NAIL THE CLOTHESPIN TO THE SPACER WOOD

Use a 3/4" finishing nail to nail the short half of the clothespins to the spacer wood. I nailed them with the springs in place. Just be careful not to hammer the springs, and finish driving the nail with a nail set.



### Image Notes

1. Nail here.


## step 3: INSERT THE WIRES THROUGH THE HOLES

Stick the wire through one hole and back through the other. Bend over the end of the wire to hold it in place.


The clothespins come apart easily sideways. Putting them back together is easier by sliding the tapered end in under the spring until everything snaps in place.




Hole for wire was made by driving in and removing a 3/4" finishing nail.




Bend wire back through second hole. Bend over wire end to keep in place.



Insert the long half under the spring starting at the tapered end.



The finished battery holder.



## Related Instructables



**Master the wonders of Samuel B.F. Morse! (My First Instructable)** by arpoky



**\$5 Dollar Burglar Alarm!** by johnnyrockstah



**Temporary / lab button cell battery holder** by matseng



**Jump start Halloween: Cyclops Visor** by Aftershock



**Balancing Robot** by vahid\_you2004



**How to make a simple electric motor for class demo** by dodo



**HOMEMADE AA BATTERY CONNECTOR! (video)** by johnnyrockstah



**Balance-BOT (slideshow)** by daniel2008

