

Package ‘casal2’

July 29, 2019

Title casal2 extract package

Version 1.0

Date 2017-03-20

Author D. Fu and C. Marsh

Description A set of R functions for extracting and plotting from casal2 output files.

Maintainer Casal2 development team <casal2@niwa.co.nz>

License CPL v1.0. See the CASAL2 User Manual for license details.

URL <http://www.niwa.co.nz>

Copyright National Institute of Water & Atmospheric Research (NIWA),
New Zealand Ministry for Primary Industries.

LazyData true

BugReports <https://github.com/NIWAFisheriesModelling/CASAL2/issues>

RoxygenNote 6.1.1

R topics documented:

apply.dataweighting.to.csl2	2
burn.in.tabular	3
check_mpd_identifiability	3
check_short_hand	4
CV.for.CPUE	4
extract.csl2.file	5
extract.mcmc	6
extract.mpd	6
extract.parameters	7
extract.tabular	8
generate.starting.pars	8
Method.TA1.8	9
mpd_derived_quantity	10
plot.derived_quantities	10
plot.fits	11
plot.pressure	12
plot.recruitment	13
plot.ycs	14
ReadSimulatedData	15

reformat.compositional.data	15
Rlnorm	16
summary.default	16
write.csl2.file	17

Index	18
--------------	-----------

apply.dataweighting.to.csl2

apply.dataweighting.to.csl2 reads in your observation.csl2 file and applies a reweighting factor and saves as a new .csl2 file.

Description

This function reads in your observation.csl2 file and applies a reweighting factor and saves as a new .csl2 file, pretty much just trying to automate the dataweighting process. The problem with this method, is that it strips out all the comments from the original observation.csl2 file.

Usage

```
apply.dataweighting.to.csl2(Path = "", weighting_factor,
  Observation_csl2_file = "Observations.csl2", Observation_label = "",
  Observation_out_filename = "Observation.csl2.0", fileEncoding = "")
```

Arguments

Path path to the directory containing the Observation.csl2 file.

weighting_factor - the multiplier for the effective sample sizes for the compositional data.

Observation_csl2_file the name of the configuration file containing the @observation blocks.

Observation_label the label of the observation you want to apply the weighting to.

Observation_out_filename the file name of the Observation.csl2 file to be saved after applying weighting.

fileEncoding Optional, allows the R-library to read in files that have been encoded in alternative UTF formats, see the manual for the error message that would indicate when to use this switch.

Value

a file named 'Observation_out_filename.out' in the path directory

Author(s)

Craig Marsh

burn.in.tabular	<i>burn.in.tabular used to return a list that has had the beginning cut off.</i>
-----------------	--

Description

returns a casal2TAB class that has been shortened to the ith iteration

Usage

```
burn.in.tabular(tab_object, Row)
```

Arguments

tab_object	casal2TAB object you want to burn-in
Row	number to burn in from, note this is not the iteration but the row that corresponds to your iteration that you want to burn-in from. if keep > 1 then the iteration and row will be different

Value

a 'casal2TAB' object which has been manipulated.

Author(s)

Craig Marsh

Examples

```
library(casal2)
# plotting Standard Output
tab <- extract.tabular(file = system.file("extdata", "tabular_report.out", package="casal2"),
burn_in_tab = burn.in.tabular(tab_object = tab, Row = 5);
```

check_mpd_identifiability	<i>check_mpd_identifiability</i>
---------------------------	----------------------------------

Description

Do an eigen decomposition of the hessian matrix to identify correlated estimated parameters and parameters with high uncertainty. Small or zero eigenvalues (high condition number) indicates ill-posedness, i.e. the parameter estimation problem does not have a unique solution. This eigenvalue decomposition has been widely used in the estimation literature

Usage

```
check_mpd_identifiability(cas2_mod, delta = .Machine$double.eps)
```

Arguments

`model` <casal2MPD> object that are generated from the `extract.mpd()` function. It expects the report of type `covariance_matrix` to be present.

Value

a data frame or message about the model

Author(s)

C.Marsh

<code>check_short_hand</code>	<i>Utility extract function</i>
-------------------------------	---------------------------------

Description

Utility extract function

Usage

```
check_short_hand(x)
```

Author(s)

Craig Marsh

<code>CV.for.CPUE</code>	<i>CV.for.CPUE</i>
--------------------------	--------------------

Description

This function is useful for deciding on a c.v. to be used with a CPUE series in a stock assessment model. Originally written in Chris Francis's DataWeighting Package, this has been copied over and modified so that users can use this functionality with Casal2 models/output.

Usage

```
CV.for.CPUE(year, cpue, f, plot.it = TRUE)
```

Arguments

<code>year</code>	vector of years with CPUE indices
<code>cpue</code>	CPUE indices
<code>f</code>	degree of lowess smoothing (0 = no smoothing, 1 = maximum smoothing)
<code>plot.it</code>	If TRUE, plot the index and the smoothed fit. Otherwise, return a dataframe of the year, index, smoothed fitted value, and cv)

Value

The function either plots the CPUE, together with a lowess line fitted to it, and returns the c.v. of the residuals to the fit. Or returns a dataframe of the lowess line fits and associated c.v.s for each point.

Note

The idea is to fit a lowess line of "appropriate" smoothness to the CPUE data, and use the c.v. of the residuals from that fit in the stock assessment model. This is equivalent to saying that we expect the stock assessment model to fit these data as well as the smoother. You judge what is "appropriate" by visual examination of lines with different degrees of smoothing. This approach is recommended on p. 1132 of the following paper: Francis, R.I.C.C. (2011). Data weighting in statistical fisheries stock assessment models. Canadian Journal of Fisheries and Aquatic Sciences 68: 1124-1138.

Author(s)

Chris Francis

`extract.csl2.file` *Model configuration write function*

Description

This function reads a Casal2 configuration file and returns a list object in R. Where each element is a command and subcommand from the configuration file

Usage

```
extract.csl2.file(file, path = "", fileEncoding = "")
```

Arguments

<code>file</code>	the name of the input file containing model configuration
<code>path</code>	Optionally, the path to the file
<code>fileEncoding</code>	Optional, allows the R-library to read in files that have been encoded in alternative UTF formats, see the manual for the error message that would indicate when to use this switch.

Author(s)

Craig Marsh

extract.mcmc	<i>extract.mcmc function for casal2 output</i>
--------------	--

Description

An extract function that reads objective and sample output that are produced from a 'casal2 -m' model run. This function also creates a 'casal2.mcmc' class which can be used in plotting and summary functions.

Usage

```
extract.mcmc(samples.file = "mcmc_samples.out.0",
             objectives.file = "mcmc_objectives.out.0", path = "",
             return_covariance = F, fileEncoding = "")
```

Arguments

samples.file	<string> the name of the input file containing the samples.file output by casal2
objectives.file	<string> the name of the input file containing the objectives.file output by casal2
path	Optional<string>, the path to the file
return_covariance	Optional<bool>, Whether you want to extract the covariance matrix with the mcmc object?
fileEncoding	Optional, allows the R-library to read in files that have been encoded in alternative UTF formats, see the manual for the error message that would indicate when to use this switch.

Value

a 'casal2MCMC' that can be integrated using the str() function.

Author(s)

C. Marsh

extract.mpd	<i>extract MPD function for readin in Casal2 output that has been generated from a -r, -e, -f, -p run mode.</i>
-------------	---

Description

An extract function that reads Casal2 output that are produced from a '-r' or '-e' or '-f' or '-p' model run. This function also creates a 'casal2.mpd' class which can be used in plotting and summary functions. See the casal2 manual for more information.

Usage

```
extract.mpd(file, path = "", fileEncoding = "")
```

Arguments

<code>file</code>	the name of the input file containing model output to extract
<code>path</code>	Optionally, the path to the file
<code>fileEncoding</code>	Optional, allows the R-library to read in files that have been encoded in alternative UTF formats, see the manual for the error message that would indicate when to use this switch.

Value

a 'casal2MPD' object which is essentially a list, that can be integrated using the `str()` function.

Author(s)

Dan Fu

Examples

```
library(casal2)
data <- extract.mpd(file = system.file("extdata", "MPD.log", package="casal2"))
class(data)
```

`extract.parameters` *Utility extract.parameters function*

Description

This function reads in a parameter file that would be generated using the `-o` syntax.

Usage

```
extract.parameters(file, path = "", fileEncoding = "")
```

Arguments

<code>file</code>	the name of the input file containing model output to extract
<code>path</code>	Optionally, the path to the file
<code>fileEncoding</code>	Optional, allows the R-library to read in files that have been encoded in alternative UTF formats, see the manual for the error message that would indicate when to use this switch.

Value

Data <"data.frame"> of parameters that are from a `-i` format.

Author(s)

Craig Marsh

<code>extract.tabular</code>	<i>extract Tabular function for readin in Casal2 output that has been generated from a -r, -e, -f, -p run mode with the -tabular.</i>
------------------------------	---

Description

An extract function that reads Casal2 output that are produced from a '-r' or '-e' or '-f' or '-p' model run. This function also create a 'casal2TAB' class which can be used in plotting and summary functions. See the casal2 manual for more information.

Usage

```
extract.tabular(file, path = "", fileEncoding = "")
```

Arguments

<code>file</code>	the name of the input file containing model output to extract
<code>path</code>	Optionally, the path to the file
<code>fileEncoding</code>	Optional, allows the R-library to read in files that have been encoded in alternative UTF formats, see the manual for the error message that would indicate when to use this switch.

Value

a 'casal2TAB' object which is essentially a list, that can be integrated using the str() function.

Author(s)

Craig Marsh

<code>generate.starting.pars</code>	<i>generate.starting.pars Generates a parameter file that is formatted for -i input into Casal2.</i>
-------------------------------------	--

Description

This function reads a Casal2 estimation configuration file and returns a par file. Where each parameter is drawn from the prior defined in an @estimate block.

Usage

```
generate.starting.pars(path = "",
  Estimation_csl2_file = "Estimation.csl2", N = 10,
  par_file_name = "starting_pars.out", all_uniform = FALSE,
  fileEncoding = "")
```


Arguments

<code>path</code>	Optionally, the path to the file
<code>Estimation_csl2_file</code>	the name of the configuration file containing the @estimate blocks.
<code>N</code>	the number of random samples you want.
<code>par_file_name</code>	= the filename of the file created
<code>all_uniform</code>	= logical if TRUE draw from a uniform between bounds regardless of prior distribution
<code>fileEncoding</code>	Optional, allows the R-library to read in files that have been encoded in alternative UTF formats, see the manual for the error message that would indicate when to use this switch.

Value

a file named 'parms.out' in the path directory

Author(s)

Craig Marsh

Method.TA1.8

Method.TA1.8

Description

This function is useful for deciding on the data weights of one or more at-age or at-length data sets with assumed multinomial error structure in a stock assessment. Can produce a diagnostic plot if the analysis is for a single data set

Usage

```
Method.TA1.8(model, observation_labels, plot.it = F, xlim = NULL,
             ylim = NULL)
```

Arguments

<code>model</code>	Casal2 output that is the result of a -r, -e run.
<code>observation_labels</code>	vector<string> Labels of the observations you want to apply the iterative weighting too, can be multiple datasets as in in Chris's original package <code>multiple = T</code> .
<code>plot.it</code>	If TRUE, plot the index and the smoothed fit. Otherwise, return a dataframe of the year, index, smoothed fitted value, and cv)
<code>xlim</code>	x-axis limits for the illustrative plot
<code>ylim</code>	y-axis limits for the illustrative plot

Value

Outputs a multiplier, w , so that $N2y = w \times N1y$, where $N1y$ and $N2y$ are the stage-1 and stage-2 multinomial sample sizes for the data set in year y .

Note

Method TA1.8 is described in Appendix A of the following paper Francis, R.I.C.C. (2011). Data weighting in statistical fisheries stock assessment models. Canadian Journal of Fisheries and Aquatic Sciences 68: 1124-1138. (With corrections to the equation in Francis R.I.C.C. (2011) Corrigendum: Data weighting in statistical fisheries stock assessment models.

Author(s)

Chris Francis

```
mpd_derived_quantity
```

Utility function for summary

Description

Utility function for summary

Usage

```
mpd_derived_quantity(report_list)
```

Author(s)

C Marsh This is a utility function that will summarise a derived quantity report for a Casal2MPD class

```
plot.derived_quantities
```

plot.derived_quantities default

Description

A plotting function to plot Derived Quantities for the 'casal2TAB' and 'casal2MPD' objects.

Usage

```
plot.derived_quantities(model, report_label = "", type = "number",
  xlim, ylim, xlab, ylab, main, col, plot.it = T, ...)

## S3 method for class 'casal2MPD'
plot.derived_quantities(model, report_label = "",
  type = "number", xlim, ylim, xlab, ylab, main, col, plot.it = T, ...)

## S3 method for class 'casal2TAB'
plot.derived_quantities(model, report_label = "",
  type = "number", xlim, ylim, xlab, ylab, main, col, plot.it = T, ...)
```

Arguments

model	<casal2MPD, casal2TAB> object that are generated from one of the extract() functions.
report_label	<string>
type	<string> whether numbers or scaled by B0.
plot.it	Whether to generate a default plot or return the values as a matrix.
...	remaining plotting options

Value

A plot of derived quantities over time if plot.it = T, if plot.it = F it will return a matrix of derived quantities.

NULL

NULL

Author(s)

Craig Marsh

plot.fits	<i>plot.fits default</i>
-----------	--------------------------

Description

A plotting function to fits to Casal2 observations from a model run.

Usage

```
plot.fits(model, report_label = "", plot.it = T, xlim, ylim, xlab,
  ylab, main, col, ...)

## S3 method for class 'casal2MPD'
plot.fits(model, report_label = "", type = "fit",
  plot.it = T, xlim, ylim, xlab, ylab, main, col, ...)

## S3 method for class 'casal2TAB'
plot.fits(model, report_label = "", type = "resid",
  plot.it = T, xlim, ylim, xlab, ylab, main, col, ...)
```

Arguments

model	<casal2MPD, casal2TAB> object that are generated from one of the extract() functions.
report_label	<string>
plot.it	Whether to generate a default plot or return the values as a matrix.
...	remaining plotting options
type	Whether to plot an observed vs expected (fit) or plot the residuals (resid)

Value

A plot of derived quantities over time if plot.it = T, if plot.it = F it will return a matrix of derived quantities.

NULL

NULL

Author(s)

Craig Marsh

Examples

```
library(casal2)
# plotting Standard Output
data <- extract.mpd(file = system.file("extdata", "estimate.log", package="casal2"))
names(data)
par(mfrow = c(1,2))
plot.fits(model = data, report_label = "Tangaroa_propn_at_age_Aug")
plot.fits(model = data, report_label = "wcsiTRLcpue")
# if you are unhappy with the default plotting you can use plot.it = FALSE and create a plot
Tangaroa_fits = plot.fits(model = data, report_label = "Tangaroa_propn_at_age_Aug", plot.it = FALSE)
# plotting Tabular Output
tab <- extract.tabular(file = system.file("extdata", "tabular_report.out", package="casal2"))
names(tab)
plot.fits(model = tab, report_label = "Tangaroa_propn_at_age_Aug")
par(mfrow = c(1,1))
plot.fits(model = tab, report_label = "wcsiTRLcpue")
```

plot.pressure

plot.pressure plot fishing pressure if there has been an exploitation process reported.

Description

A plotting function to plot fishing pressure (U's) for the 'casal2TAB' and 'casal2MPD' objects.

Usage

```
plot.pressure(model, report_label = "", xlim, ylim, xlab, ylab, main,
              col, plot.it = T, ...)

## S3 method for class 'casal2MPD'
plot.pressure(model, report_label = "",
              xlim = NULL, ylim = NULL, xlab = NULL, ylab = NULL,
              main = NULL, col = NULL, plot.it = T, ...)

## S3 method for class 'casal2TAB'
plot.pressure(model, report_label = "", xlim, ylim,
              xlab, ylab, main, col, plot.it = T, ...)
```

Arguments

model <casal2MPD, casal2TAB> object that are generated from one of the extract.mpd() and extract.tabular() functions.

report_label <string>

plot.it Whether to generate a default plot or return the values as a matrix.

... remaining plotting options

Value

generate a plot over time if plot.it = T, if plot.it = F it will return a matrix of values.

NULL

NULL

Author(s)

Craig Marsh

plot.recruitment	<i>plot.recruitment plot the stock recruitment relationship from a Casal2 model output.</i>
------------------	---

Description

A plotting function to plot the stock recruitment relationship for the 'casal2TAB' and 'casal2MPD' objects.

Usage

```
plot.recruitment(model, report_label = "", xlim, ylim, xlab, ylab, main,
  col, ...)

## S3 method for class 'casal2MPD'
plot.recruitment(model, report_label = "",
  xlim = NULL, ylim = NULL, xlab = NULL, ylab = NULL,
  main = NULL, col = NULL, ...)

## S3 method for class 'casal2TAB'
plot.recruitment(model, report_label = "", xlim,
  ylim, xlab, ylab, main, col, ...)
```

Arguments

model <casal2MPD, casal2TAB> object that are generated from one of the extract.mpd() and extract.tabular() functions.

report_label <string> the report label containing recruitment process

... remaining plotting options

Value

generate a plot of SSB_y vs R_y with the assumed Stock recruitment relationship through it.

NULL

NULL

Author(s)

Craig Marsh

plot.ycs

plot.ycs plot true Year Class Strengths from a Casal2 model.

Description

A plotting function to plot YCS for the 'casal2TAB' and 'casal2MPD' objects.

Usage

```
plot.ycs(model, report_label = "", xlim, ylim, xlab, ylab, main, col,
         plot.it = T, ...)
```

```
## S3 method for class 'casal2MPD'
plot.ycs(model, report_label = "", xlim = NULL,
         ylim = NULL, xlab = NULL, ylab = NULL, main = NULL, col = NULL,
         plot.it = T, ...)
```

```
## S3 method for class 'casal2TAB'
plot.ycs(model, report_label = "", xlim, ylim, xlab,
         ylab, main, col, plot.it = T, ...)
```

Arguments

model <casal2MPD, casal2TAB> object that are generated from one of the extract.mpd() and extract.tabular() functions.

report_label <string>

plot.it Whether to generate a default plot or return the values as a matrix.

... remaining plotting options

Value

generate a plot over time if plot.it = T, if plot.it = F it will return a matrix of values.

NULL

NULL

Author(s)

Craig Marsh

ReadSimulatedData *Read in multiple sets of Simualted data for a single observation*

Description

This function reads in a set of simulated observations generated from Casal2 in simulation mode. These functions read in all the simulated obs as a list, for visualising and summarising in R

Usage

```
ReadSimulatedData(filename, path = "")
```

Arguments

filename	the name of simulated obs for an observation. For example if you generated 100 sets of simulated observations named "SubAntarticObs". Casal2 will generate 100 of these with the following extensions SubAntarticObs.001, SubAntarticObs.002, SubAntarticObs.003,,, SubAntarticObs.100. filename = SubAntarticObs.
path	Optionally, the path to the file, default is current working directory.

Author(s)

Craig Marsh

```
reformat.compositional.data
```

Reformat Casal2 compositional observation so it is the same format as the legacy Casal observation.

Description

This function will take a compositional observation that has been generated by Casal2 and re-format it so that it has the same structure as a CASAL reported compositional observation. The purpose for this function is to reformat the Casal2 observations so we can then feed them into packages that have been tailored for Casal observations, such as Chris Francis's DataWeighting library. I found this useful when comparing with CASAL model runs.

Usage

```
reformat.compositional.data(model, report_label)
```

Arguments

model	the r object that has been extracted using the extract() function.
report_label	<string> the label of the report for the observation you want converted

Author(s)

Craig Marsh

Rlnorm

Utility extract function

Description

Utility extract function

Usage

```
Rlnorm(n, mu, cv)
```

Arguments

n	number of samples to draw
mu	mean in normal space
cv	cv in normal space

Value

n randomly generated values from a lognormal distribution

Author(s)

Craig marsh

summary.default

summary default

Description

A summary function for 'casal2MCMC' 'casal2TAB' and 'casal2MPD' objects.

Usage

```
summary.default(model)

## S3 method for class 'casal2MPD'
summary(model)

## S3 method for class 'casal2MCMC'
summary(model)
```

Arguments

model	<casal2MPD, casal2TAB, casal2MCMC> object that are generated from one of the extract() functions.
-------	---

Value

NULL

NULL

Author(s)

C. Marsh

write.csl2.file	<i>Model configuration write function</i>
-----------------	---

Description

This function will write a Casal2 configuration file based on a list object in R. Ususally this function will be used once a model has been read into R using `extract.csl2.file` and modified. This function will then print our the configuration to a new file where it can be re run into Casal2

Usage

```
write.csl2.file(object, file, path = "")
```

Arguments

<code>object</code>	An R list object that follows the same structure that <code>extract.csl2.file</code> would produce
<code>file</code>	Optionally, the file name
<code>path</code>	Optionally, the path to ouput the file

Author(s)

Craig Marsh

Index

`apply.dataweighting.to.csl2`, 2

`burn.in.tabular`, 3

`check_mpd_identifiability`, 3

`check_short_hand`, 4

`CV.for.CPUE`, 4

`extract.csl2.file`, 5

`extract.mcmc`, 6

`extract.mpd`, 6

`extract.parameters`, 7

`extract.tabular`, 8

`generate.starting.pars`, 8

`Method.TA1.8`, 9

`mpd_derived_quantity`, 10

`plot.derived_quantities`, 10

`plot.fits`, 11

`plot.pressure`, 12

`plot.recruitment`, 13

`plot.ycs`, 14

`ReadSimulatedData`, 15

`reformat.compositional.data`, 15

`Rlnorm`, 16

`summary.casal2MCMC`
 (*summary.default*), 16

`summary.casal2MPD`
 (*summary.default*), 16

`summary.default`, 16

`write.csl2.file`, 17